

TYLFIX RANGE



JSW TYLFIX TYPE 1

TYLFIX RANGE

Tile Adhesive for Floor & Wall Ceramic Tiles

JSW Tylfix Type I is a polymer modified cement based powder tile adhesive for fixing all type of ceramic, clay tiles, It is suitable for both vertical and horizontal application. It gives excellent bond on exterior cementitious surfaces like plaster or concrete etc.

USAGE AREAS

- All types of ceramic tiles and bricks are vitrified as recommended to fix on the floor.
- Cement-based screeds, plasters, mortars, concrete surfaces and bricks.









POT LIFE	PACK SIZE:	BEST BEFORE
Approx. 60 minutes	20 kg bag	12 months

JSW TYLFIX TYPE 2

TYLFIX RANGE

Tile Adhesive for Floor & Wall & Tile on Tile

JSW Tylfix Type 2 is a polymer modified cement based powder tile adhesive for fixing All types of ceramic tile, terracotta, pavers, brick vitrified tiles, glass. It is suitable for Flooring and walls, for internal applications & external shaded area, external area, dry & wet area, new construction & renovation, domestic applications, commercial applications.

USAGE AREAS

- All types of ceramic tiles, terracotta, pavers, brick-vitrified tiles, glass mosaic tiles.
- Cement-based screeds & mortars, cement-based plasters/ renders, concrete surfaces, bricks,









POT LIFE:	PACK SIZE:	BEST BEFORE
Approx. 120 minutes	20 kg bag	12 months

JSW TYLFIX TYPE 3

TYLFIX RANGE

Tile Adhesive for Glass & Stone Tiles

JSW Tylfix Type 3 is a polymer modified cement based powder tile adhesive for fixing All types of ceramic tiles, clay tiles, basalt tiles, terracotta, pavers, brick, vitrified tiles, glass mosaic tiles, porcelain tiles and all natural stone tiles.

USAGE AREAS

 All types of ceramic tiles, clay tiles, basalt tiles, terracotta, pavers, brick, vitrified tiles, glass mosaic tiles, porcelain tiles and all natural stone tiles.









POT LIFE:	PACK SIZE:	BEST BEFORE
Approx. 120 minutes	20 kg bag	12 months

JSW TYLFIX TYPE 4

TYLFIX RANGE

Tile Adhesive for large Glass & Stone Tiles and Dry Wall Boards

JSW Tylfix Type 4 All types of ceramic tiles, clay tiles, basalt tiles, terracotta, pavers, brick, vitrified tiles, glass mosaic tiles, porcelain tiles ,natural stone tiles, large format tiles, marble, large thin/slim tiles. low thickness slabs.

USAGE AREAS

 All types of ceramic tiles, clay tiles, basalt tiles, terracotta, pavers, bricks, vitrified tiles, glass mosaic tiles, porcelain tiles, natural stone tiles, large format tiles, marble, large thin/slim tiles, low thickness slabs.









POT LIFE:	PACK SIZE:	BEST BEFORE
Approx. 120 minutes	20 kg	12 months

TYLFIX GROUT - Cementitious



TYLFIX RANGE

Cement-based Tile Joint Filler Grout

JSW Tylfix Grout - Cementitious is a polymer-modified, cement-based tile joint filler grouting material, which is highly suitable for filling the joints/gap of all types of tiles. It exhibits water-resistant properties, making it an ideal choice for various applications.

USAGE AREAS

 All types of ceramic tile, glazed tiles, porcelain tiles, vitrified & fully vitrified tiles, natural stone, and glass mosaic tiles.









POT LIFE	PACK SIZE:	BEST BEFORE
Min. 45 minutes	1 kg	12 months

TYLFIX CLEANER

TYLFIX RANGE

Strong Performance Cleaner

Tylfix Cleaner is a high quality rapid active cleaner and degreasing solution for use on tiles, bathtubs, wash basin, privy basin and concrete etc. It is used to clean whitish spot/ layer as normally observed in the bathroom under plastic/ metal buckets (normal detergent is not helpful) with ease.

USAGE AREAS

Ceramic tiles, glazed tiles, porcelain tiles, vitrified tiles, glass mosaic tiles & sanitary ware.
Cleaning moss and wax from concrete and ceramics. Surfaces before & after application of epoxy products. Natural stones.









SOAKING TIME	PACK SIZE:	BEST BEFORE
5 minutes	1 Ltr, 5 Ltr	12 months



REGISTERED OFFICE

JSW Centre, Bandra Kurla Complex, Near MMRDA Grounds, Bandra East, Mumbai 400 051

MARKETED BY:

JSW Green Cement Pvt. Ltd. Babukhan Millenium, Centre, 6-3-1099/1100, No. 702, Block-A, Somajiguda, Hyderabad, Telangana, India, Pincode - 500 082

Email: info@jswcement.in | Website: www.jswcement.in | Toll free: 18002662661



