



Stader Labs

SD Token Staking

CosmWasm Smart Contract
Security Audit

Prepared by: Halborn

Date of Engagement: March 9th, 2022 - March 15th, 2022

Visit: [Halborn.com](https://halborn.com)

DOCUMENT REVISION HISTORY	3
CONTACTS	4
1 EXECUTIVE OVERVIEW	5
1.1 INTRODUCTION	6
1.2 AUDIT SUMMARY	6
1.3 TEST APPROACH & METHODOLOGY	7
RISK METHODOLOGY	7
1.4 SCOPE	9
2 ASSESSMENT SUMMARY & FINDINGS OVERVIEW	10
3 FINDINGS & TECH DETAILS	11
3.1 (HAL-01) LACK OF MANAGER TRANSFER FUNCTIONALITY - LOW	13
Description	13
Code Location	13
Risk Level	14
Recommendation	15
Remediation plan	15
3.2 (HAL-02) MISSING BOUNDS ON CONFIGURATION VARIABLES - LOW	16
Description	16
Code Location	16
Risk Level	18
Recommendation	18
Remediation plan	19
3.3 (HAL-03) LACK OF ADDRESS NORMALIZATION - INFORMATIONAL	20
Description	20

	Code Location	20
	Risk Level	21
	Recommendation	21
	Remediation plan	21
3.4	(HAL-04) CONFIGURATION PARAMETER NOT SET UPON INSTANTIATION - INFORMATIONAL	22
	Description	22
	Code Location	22
	Risk Level	23
	Recommendation	23
	Remediation plan	23
4	AUTOMATED TESTING	24
4.1	AUTOMATED ANALYSIS	25
	Description	25

DOCUMENT REVISION HISTORY

VERSION	MODIFICATION	DATE	AUTHOR
0.1	Document Creation	03/09/2022	Jose C. Ramirez
0.2	Document Update	03/15/2022	Jakub Heba
0.3	Document Update	03/18/2022	Jose C. Ramirez
0.4	Draft Version	03/18/2022	Jakub Heba
0.5	Draft Review	03/18/2022	Gabi Urrutia
1.0	Remediation Plan	03/25/2022	Jakub Heba
1.1	Remediation Plan Review	03/27/2022	Gabi Urrutia

CONTACTS

CONTACT	COMPANY	EMAIL
Rob Behnke	Halborn	Rob.Behnke@halborn.com
Steven Walbroehl	Halborn	Steven.Walbroehl@halborn.com
Gabi Urrutia	Halborn	Gabi.Urrutia@halborn.com
Jose C. Ramirez	Halborn	jose.ramirez@halborn.com
Jakub Heba	Halborn	jakub.heba@halborn.com



EXECUTIVE OVERVIEW



1.1 INTRODUCTION

Stader Labs engaged Halborn to conduct a security audit on their smart contracts beginning on March 9th, 2022 and ending on March 15th, 2022. The security assessment was scoped to the smart contracts provided to the Halborn team.

1.2 AUDIT SUMMARY

The team at Halborn was provided a week for the engagement and assigned two full-time security engineers to audit the security of the smart contract. The security engineers are blockchain and smart-contract security experts with advanced penetration testing, smart-contract hacking, and deep knowledge of multiple blockchain protocols.

The purpose of this audit is to:

- Ensure that smart contract functions operate as intended
- Identify potential security issues with the smart contracts

In summary, Halborn identified some improvements to reduce the likelihood and impact of risks, which were partially addressed by the Stader Labs team. The main ones are the following:

- Implement manager transfer functionalities for lock and rewards-pool contracts.
- Protect configuration parameters against abnormally low / high values by setting proper bounds.

1.3 TEST APPROACH & METHODOLOGY

Halborn performed a combination of manual review of the code and automated security testing to balance efficiency, timeliness, practicality, and accuracy in regard to the scope of the smart contract audit. While manual testing is recommended to uncover flaws in logic, process, and implementation; automated testing techniques help enhance coverage of smart contracts and can quickly identify items that do not follow security best practices. The following phases and associated tools were used throughout the term of the audit:

- Research into architecture, purpose, and use of the platform.
- Manual code read and walkthrough.
- Manual assessment of use and safety for the critical Rust variables and functions in scope to identify any contracts logic related vulnerability.
- Fuzz testing (Halborn custom fuzzing tool)
- Checking the test coverage (cargo tarpaulin)
- Scanning of Rust files for vulnerabilities (cargo audit)

RISK METHODOLOGY:

Vulnerabilities or issues observed by Halborn are ranked based on the risk assessment methodology by measuring the **LIKELIHOOD** of a security incident and the **IMPACT** should an incident occur. This framework works for communicating the characteristics and impacts of technology vulnerabilities. The quantitative model ensures repeatable and accurate measurement while enabling users to see the underlying vulnerability characteristics that were used to generate the Risk scores. For every vulnerability, a risk level will be calculated on a scale of 5 to 1 with 5 being the highest likelihood or impact.

RISK SCALE - LIKELIHOOD

- 5 - Almost certain an incident will occur.
- 4 - High probability of an incident occurring.
- 3 - Potential of a security incident in the long term.

- 2 - Low probability of an incident occurring.
- 1 - Very unlikely issue will cause an incident.

RISK SCALE - IMPACT

- 5 - May cause devastating and unrecoverable impact or loss.
- 4 - May cause a significant level of impact or loss.
- 3 - May cause a partial impact or loss to many.
- 2 - May cause temporary impact or loss.
- 1 - May cause minimal or un-noticeable impact.

The risk level is then calculated using a sum of these two values, creating a value of 10 to 1 with 10 being the highest level of security risk.

CRITICAL	HIGH	MEDIUM	LOW	INFORMATIONAL
----------	------	--------	-----	---------------

- 10 - CRITICAL
- 9 - 8 - HIGH
- 7 - 6 - MEDIUM
- 5 - 4 - LOW
- 3 - 1 - VERY LOW AND INFORMATIONAL

1.4 SCOPE

Code repository: [terra-tokenomics](#)

1. CosmWasm Smart Contracts

(a) Commit ID: [e5fb44cecaedad4ad78bed93351ac697e94adc7c](#)

(b) Contracts in scope:

- i. lock
- ii. rewards-pool
- iii. staking

Out-of-scope: External libraries and financial related attacks.

2. ASSESSMENT SUMMARY & FINDINGS OVERVIEW

CRITICAL	HIGH	MEDIUM	LOW	INFORMATIONAL
0	0	0	2	2

LIKELIHOOD

IMPACT

		(HAL-01)		
(HAL-03) (HAL-04)			(HAL-02)	

SECURITY ANALYSIS	RISK LEVEL	REMEDATION DATE
(HAL-01) LACK OF MANAGER TRANSFER FUNCTIONALITY	Low	RISK ACCEPTED
(HAL-02) MISSING BOUNDS ON CONFIGURATION VARIABLES	Low	SOLVED - 03/21/2022
(HAL-03) LACK OF ADDRESS NORMALIZATION	Informational	SOLVED - 03/21/2022
(HAL-04) CONFIGURATION PARAMETER NOT SET UPON INSTANTIATION	Informational	ACKNOWLEDGED



FINDINGS & TECH DETAILS



3.1 (HAL-01) LACK OF MANAGER TRANSFER FUNCTIONALITY – LOW

Description:

The **rewards-pool** and **lock** contracts do not implement any functionality to change the **manager** address, which is set at contract instantiation.

If the **manager** account keys are suspected to be compromised or if the development team needs to change the address for an operational reason, some functionality of the contract could be rendered unusable.

It is worth mentioning that this issue has a very limited impact, as there is only one manager-only functionality that can be used once.

Code Location:

Listing 1: contracts/rewards-pool/src/contract.rs (Line 63)

```

54 pub fn update_configs(
55     deps: DepsMut,
56     info: MessageInfo,
57     _env: Env,
58     staking_contract: String,
59 ) -> Result<Response, ContractError> {
60     let mut config = CONFIG.load(deps.storage)?;
61
62     let sending_manager = info.sender.to_string();
63     if sending_manager.ne(&config.manager) {
64         return Err(ContractError::Unauthorized {});
65     }
66
67     if config.staking_contract.eq(&Addr::unchecked("0")) {
68         config.staking_contract = deps
69             .api
70             .addr_validate(staking_contract.to_lowercase().as_str
71             .as_str())?;
72     }
73     CONFIG.save(deps.storage, &config)?;

```

```

74
75     Ok(Response::new()
76         .add_attribute("method", "update_configs")
77         .add_attribute("staking_contract", staking_contract))
78 }

```

Listing 2: contracts/lock/src/contract.rs (Line 65)

```

57 pub fn update_configs(
58     deps: DepsMut,
59     info: MessageInfo,
60     _env: Env,
61     staking_contract: String,
62 ) -> Result<Response, ContractError> {
63     let mut config = CONFIG.load(deps.storage)?;
64     let sending_manager = info.sender;
65     if sending_manager.ne(&config.manager) {
66         return Err(ContractError::Unauthorized {});
67     }
68
69     if config.staking_contract.eq(&Addr::unchecked("0")) {
70         config.staking_contract = deps
71             .api
72             .addr_validate(staking_contract.to_lowercase().as_str
73 ↪ ())?;
74     }
75
76     CONFIG.save(deps.storage, &config)?;
77
78     Ok(Response::new().add_attribute("method", "update_configs"))
79 }

```

Risk Level:

Likelihood - 3

Impact - 2

Recommendation:

Manager transfer capabilities should be added to contracts as a two-step process split into a `set_manager` and a `accept_manager` functions. The latter requires the recipient to complete the transfer, effectively protecting the contract against potential typographical errors, compared to one-step manager transfer mechanisms.

Remediation plan:

RISK ACCEPTED: The risk for this issue was accepted by the `Stader Labs team`. They also mentioned that there is no use case for changing the manager in the future.

3.2 (HAL-02) MISSING BOUNDS ON CONFIGURATION VARIABLES - LOW

Description:

The **staking** contract has missing bounds on the **emission_rate** and **unbonding_period** variables. This can lead to unexpected contract behavior.

The bounds of these parameters should be enforced to avoid potential errors in the current or future uses of these variables.

Code Location:

Listing 3: contracts/staking/src/contract.rs (Lines 44,48,64,66)

```

35 pub fn instantiate(
36     deps: DepsMut,
37     env: Env,
38     _info: MessageInfo,
39     msg: InstantiateMsg,
40 ) -> Result<Response, ContractError> {
41     set_contract_version(deps.storage, CONTRACT_NAME,
42     ↳ CONTRACT_VERSION)?;
43
44     let state = State {
45         emission_rate: msg.emission_rate,
46         last_exchange_rate_updated_block: env.block.height,
47         next_undelegate_id: 0,
48     };
49     STATE.save(deps.storage, &state)?;
50
51     let config = Config {
52         manager: deps
53         .api
54         .addr_validate(msg.manager.to_lowercase().as_str())?,
55         xsd_cw20_contract: Addr::unchecked(""),
56         sd_cw20_contract: deps
57         .api
58         .addr_validate(msg.sd_cw20_contract.to_lowercase()).

```

```

↳ as_str())?,
58         rewards_pool_contract: deps
59             .api
60             .addr_validate(msg.rewards_pool_contract.to_lowercase
↳ ().as_str())?,
61         lock_contract: deps
62             .api
63             .addr_validate(msg.lock_contract.to_lowercase().as_str
↳ ()),
64         unbonding_period: msg.unbonding_period,
65     };
66     CONFIG.save(deps.storage, &config)?;
67
68     Ok(Response::new().add_attribute("method", "instantiate"))
69 }

```

Listing 4: contracts/staking/src/contract.rs (Lines 369,370,373,374)

```

337 pub fn update_config(
338     deps: DepsMut,
339     info: MessageInfo,
340     _env: Env,
341     update_config_request: UpdateConfigRequest,
342 ) -> Result<Response, ContractError> {
343     let mut config = CONFIG.load(deps.storage)?;
344     let mut state = STATE.load(deps.storage)?;
345     let sending_manager = info.sender.to_string().to_lowercase();
346
347     if sending_manager.ne(&config.manager) {
348         return Err(ContractError::Unauthorized {});
349     }
350
351     if let Some(sd_cw20) = update_config_request.sd_cw20_contract
↳ {
352         config.sd_cw20_contract = deps.api.addr_validate(sd_cw20.
↳ to_lowercase().as_str())?;
353     }
354
355     if let Some(xsd_cw20) = update_config_request.
↳ xsd_cw20_contract {
356         if config.xsd_cw20_contract.eq(&Addr::unchecked("0")) {
357             config.xsd_cw20_contract = deps.api.addr_validate(
↳ xsd_cw20.to_lowercase().as_str())?;
358         }

```

```

359     }
360
361     if let Some(lock) = update_config_request.lock_contract {
362         config.lock_contract = deps.api.addr_validate(lock.
↳ to_lowercase().as_str())?;
363     }
364
365     if let Some(rpc) = update_config_request.rewards_pool_contract
↳ {
366         config.rewards_pool_contract = deps.api.addr_validate(rpc.
↳ to_lowercase().as_str())?;
367     }
368
369     if let Some(er) = update_config_request.emission_rate {
370         state.emission_rate = er;
371     }
372
373     if let Some(up) = update_config_request.unbonding_period {
374         config.unbonding_period = up;
375     }
376
377     CONFIG.save(deps.storage, &config)?;
378     STATE.save(deps.storage, &state)?;
379
380     Ok(Response::new().add_attribute("method", "update_config"))
381 }

```

Risk Level:

Likelihood - 4

Impact - 1

Recommendation:

Upper and lower bounds for the `emission_rate` and `unbonding_period` variables should be applied when they are updated during the execution of the `update_config` function and at instantiation.

Remediation plan:

SOLVED: The issue was fixed with the above recommendation in commits:

- [2f1aa9ae1db519d452fa3456fa912a562041b666](#)
- [ea46b4313fc5ce14d9b8adedb290a1a4b4b28829](#)

3.3 (HAL-03) LACK OF ADDRESS NORMALIZATION – INFORMATIONAL

Description:

The `set_manager` function of the staking contract takes user input directly as an address without performing any validation. This could lead to failed messages or the storage of incorrect information.

However, the impact in this particular case is very limited since the address submitted in the `set_manager` function must execute the `accept_manager` function to finish the process, protecting against potential mistakes such as those mentioned.

Code Location:

Listing 5: `contracts/staking/src/contract.rs` (Lines 93,103)

```

89 pub fn set_manager(
90     deps: DepsMut,
91     info: MessageInfo,
92     _env: Env,
93     manager: String,
94 ) -> Result<Response, ContractError> {
95     let config = CONFIG.load(deps.storage)?;
96     if info.sender.ne(&config.manager) {
97         return Err(ContractError::Unauthorized {});
98     }
99
100     TMP_MANAGER_STORE.save(
101         deps.storage,
102         &TmpManagerStore {
103             manager: manager.clone(),
104         },
105     )?;
106
107     Ok(Response::new()
108         .add_attribute("method", "set_manager")
109         .add_attribute("new_manager", manager))

```

Risk Level:

Likelihood - 1

Impact - 1

Recommendation:

One of the two approaches detailed below should be used:

- In addition to validation, addresses should be normalized to lower-case before being stored for future use.
- Instead of just validation, addresses should be stored in canonical format using the `cosmwasm_std::Api::addr_canonicalize` utility function.

The following considerations should be considered when implementing the second option:

- To successfully compare a canonical address, both ends should be in canonical format. For example, when performing access controls, the sender (e.g.: `info.sender` or `env.message.sender`) should also be canonicalized beforehand.
- To send funds to a canonicalized address or include it in a message to a different contract, it should be first turn into its human-readable format via the `cosmwasm_std::Api::addr_humanize` utility function

Remediation plan:

SOLVED: The issue was fixed with the above recommendation in commit [0f3fbb9237c43f381987e113fa418d4cd1afbb57](#).

3.4 (HAL-04) CONFIGURATION PARAMETER NOT SET UPON INSTANTIATION - INFORMATIONAL

Description:

The `instantiate` function did not set the `staking_contract` address, as it did for other required contract addresses in the configuration. Instead, it relied on `update_config` being called post initialization. If the staking address is not set by calling `update_config` before executing `transfer_rewards`, an attempt to transfer to address "0" will end the `panic!` macro and unnecessary consumption of gas fee per transaction.

It is worth noting that the `update_config` function only allowed setting the staking address if it contained the initial value `Addr::unchecked("0")`. This effectively forbids any future change after the first update.

Code Location:

Listing 6: `contracts/rewards-pool/src/contract.rs` (Line 25)

```
18 pub fn instantiate(
19     deps: DepsMut,
20     _env: Env,
21     _info: MessageInfo,
22     msg: InstantiateMsg,
23 ) -> Result<Response, ContractError> {
24     let config = Config {
25         staking_contract: Addr::unchecked("0"),
26         sd_cw20_contract: deps
27             .api
28             .addr_validate(msg.sd_cw20_contract.to_lowercase().
29                 as_str())?,
30         manager: deps
31             .api
32             .addr_validate(msg.manager.to_lowercase().as_str())?,
33     };
34 }
```

Listing 7: contracts/lock/src/contract.rs (Line 31)

```

18 pub fn instantiate(
19     deps: DepsMut,
20     _env: Env,
21     _info: MessageInfo,
22     msg: InstantiateMsg,
23 ) -> Result<Response, ContractError> {
24     let config = Config {
25         manager: deps
26             .api
27             .addr_validate(msg.manager.to_lowercase().as_str())?,
28         sd_cw20_contract: deps
29             .api
30             .addr_validate(msg.sd_cw20_contract.to_lowercase().
31 ↪ as_str())?,
32         staking_contract: Addr::unchecked(""),
33     };
34     set_contract_version(deps.storage, CONTRACT_NAME,
35 ↪ CONTRACT_VERSION)?;
36     CONFIG.save(deps.storage, &config)?;

```

Risk Level:**Likelihood - 1****Impact - 1****Recommendation:**

The `staking_contract` variable should be set on `instantiate`, as with the other contract addresses.

Remediation plan:

ACKNOWLEDGED: The `Stader Labs team` acknowledged this finding.



AUTOMATED TESTING



4.1 AUTOMATED ANALYSIS

Description:

Halborn used automated security scanners to assist with detection of well-known security issues and vulnerabilities. Among the tools used was `cargo audit`, a security scanner for vulnerabilities reported to the RustSec Advisory Database. All vulnerabilities published in <https://crates.io> are stored in a repository named The RustSec Advisory Database. `cargo audit` is a human-readable version of the advisory database which performs a scanning on Cargo.lock. Security Detections are only in scope. All vulnerabilities shown here were already disclosed in the above report. However, to better assist the developers maintaining this code, the auditors are including the output with the dependencies tree, and this is included in the cargo audit output to better know the dependencies affected by unmaintained and vulnerable crates.

ID	package	Short Description
RUSTSEC-2020-0025	bigint	biginit is unmaintained, use uint instead



THANK YOU FOR CHOOSING

 **HALBORN**

