

Creating an R Package

rugB

2024-10-23

Step 1: Create the shell of your R package.

- There are a couple of ways to do this step. For this demo, we are going to go File > New Project > New Directory > R Package.
 - Give your package a name.
 - Select where you want to store the package.
- In the future, you could consider using `usethis::create_package()` and syncing it to a GitHub repository.

Step 2: If you want to include data in the package, add the raw data and wrangle it into the version the package will share.

- Run `usethis::use_data_raw()` to create a `data-raw` folder and the `DATASET.R` file.
- Add the raw data files to the `data-raw` folder.
- Use the file `DATASET.R` to load and wrangle the raw data.
 - Instead of loading packages with `library(package_name)`, use `package_name::function_name()`.
 - At the bottom, include the following code to create a tidy `.Rda` file:

```
usethis::use_data(insert_data_name, overwrite = TRUE)
```

- Run the code in `DATASET.R` to create a new folder called `data` that contains the tidy data.
- Run `usethis::use_r("insert_data_name")` to create a blank script file.
 - We will add the data codebook to this file in Step 4.

Step 3: Add your functions to the R folder.

- For each user-facing function in your package, run `usethis::use_r("insert_function_name")` to create a new script file.

- Within each function, instead of loading packages with `library(package_name)`, use `package_name::function_name()`.
- For any packages your functions depends on, run `usethis::use_package("package_name")`.

Step 4: Create documentation.

- For each of your **function** scripts in the **R** folder, add some template documentation code by going to **Code > Insert roxygen skeleton**.
- For each of your **data** scripts, you will need to write it from scratch.
 - Mimic examples!
 - Make sure to include `@format` and `@source`.
 - Include the dataset name in quotes at the bottom of the script.
- Add **roxygen** comments that document your function or dataset.
 - Here's a [data example](#).
 - Here's a [function example](#).
 - See the [Object Documentation Chapter](#) of [R packages](#) for more information on the syntax.
- To create the output help files, run `devtools::document()`.
 - Notice that there is now a **man** folder with **Rd** help files.

Step 5: Test drive your package functions.

- Restart your R Session and run `devtools::load_all()` to make the package functions and data available.
- Test out the functions.
 - Return to earlier steps if you find any bugs.
- Type `?insert_function_name` or `?insert_data_name` to make sure the help file pops up and to see if it is formatted correctly.

Step 6: Run a more formal check of your package with `devtools::check(document = FALSE)`.

- Fix any errors or warnings. (Note: The package will still compile when there are warnings and notes.)

Step 7: Try installing the package with `devtools::install()`.

Additional Components:

- Package metadata (DESCRIPTION, NAMESPACE, License)
- Documentation (Vignettes, Readme, Website)
- Testing