

API INTEGRATION REFERENCE

PlentyClient for Ruby

A complete reference to the PlentyMarkets REST API endpoints consumed by the `plenty_client` Ruby gem — authentication, request conventions and the full endpoint catalogue.

LIBRARY

plenty_client (Ruby gem)

VERSION DOCUMENTED

0.1.3

TARGET API

PlentyMarkets REST API

ENDPOINTS CATALOGUED

503 across 297 paths

PREPARED BY

Buddy & Selly

DATE

24 June 2026

Distributed to integration partners on request. Endpoint paths and conventions are derived directly from the gem source (v0.1.3); the canonical authority for the API remains the [PlentyMarkets REST API documentation](#).

Contents

1	Introduction & scope
2	Integration overview
3	Authentication & token lifecycle
4	Request & response conventions
5	Pagination
6	Rate limiting, retries & timeouts
7	Error handling
8	API endpoint catalogue
8.1	Authentication
8.2	Authorization
8.3	Account
8.4	Accounting
8.5	Basket
8.6	Category
8.7	Comment
8.8	Document
8.9	Item
8.10	ItemSet
8.11	Listing
8.12	Market
8.13	Order
8.14	OrderSummary
8.15	Payment
8.16	SalesPrice
8.17	Stock
8.18	Warehouse
8.19	Webstore
8.20	Properties & Property Groups (API v2)
8.21	PIM Variations (bulk, /pim)

1 Introduction & scope

This document describes the PlentyMarkets REST API endpoints that the `plenty_client` Ruby gem calls, together with the authentication scheme, headers, pagination, throttling and error conventions it relies on.

`plenty_client` is a thin Ruby wrapper around the PlentyMarkets REST API. It performs no business validation of its own — it is a transport-layer gateway that maps Ruby method calls onto HTTP requests against a PlentyMarkets instance. Every endpoint listed in section 8 corresponds to a public method on a `PlentyClient::*` class or module.

The catalogue covers **503 endpoints** over **297 distinct paths** and **125 client classes**, spanning 21 top-level resource areas. It is intended for integration partners — including PlentyMarkets — who need to understand precisely which parts of the REST API this integration touches.

Authoritative source. Paths, HTTP verbs and parameters in this document were extracted directly from the gem source code for version 0.1.3. Where the meaning of a field or response body is required, the [official PlentyMarkets REST API documentation](#) remains authoritative.

2 Integration overview

Transport	HTTPS, JSON request and response bodies.
HTTP client	Faraday with the Typhoeus adapter.
Base URL	Derived from the configured <code>site_url</code> ; the scheme and host are kept and the request path is always mounted under <code>/rest</code> — i.e. <code>https://<host>/rest<path></code> .
API version	Requests send <code>Accept: application/x.plentymarkets.v1+json</code> (REST API v1). A subset of newer endpoints is served under the <code>/v2</code> and <code>/pim</code> path prefixes (see §8.20–8.21).
Authentication	Bearer access token obtained via <code>POST /rest/login</code> (see §3).
Content type	All requests send <code>Content-Type: application/json</code> ; bodies for <code>POST/PUT/PATCH</code> are JSON-encoded.

Verb legend: GET read POST create PUT update/replace PATCH partial update DELETE

remove

3 Authentication & token lifecycle

The client authenticates with username/password credentials and then uses a Bearer access token for all subsequent calls. Authentication is performed lazily: before any request, if no valid token is held, the client issues a login.

Authentication endpoints

METHOD	ENDPOINT PATH	CLIENT CALL
POST	/rest/login	Authentication.login
POST	/rest/login/refresh	Authentication.login_refresh
GET	/rest/oauth/access_token	Authentication.access_token
POST	/rest/client-login	Authentication.client_access_token
POST	/rest/logout	Authentication.logout

Token flow

1. The client sends POST /rest/login with { "username", "password" }.
2. The response supplies accessToken, refreshToken and expiresIn (seconds). The token expiry is stored as *now + expiresIn*.
3. Every request thereafter sends Authorization: Bearer <accessToken>.
4. A token is treated as valid only while it is more than **60 seconds** from expiry; inside that window the client re-authenticates before issuing the request.

Credentials required. site_url, api_user and api_password must be configured; a request attempted without them raises before any network call.

4 Request & response conventions

Request headers

Content-Type	application/json
Accept	application/x.plentymarkets.v1+json
Authorization	Bearer <accessToken> (once authenticated)

Bodies & query parameters

GET and DELETE requests pass parameters as the query string; POST, PUT and PATCH send a JSON-encoded body. One group of bulk endpoints (/rest/pim/variations/*, §8.21) accepts a JSON *array* body on DELETE.

Responses

Responses are parsed as JSON. application/pdf responses (document downloads) are returned as a raw binary body. An empty response body is returned as null.

5 Pagination

List endpoints are paginated. The client sends a page query parameter (1-based) and reads the paged envelope returned by the API, which includes entries and the boolean isLastPage. Common optional parameters include itemsPerPage and with.

The Ruby API exposes two modes: a single-page call returns the raw response, while passing a block iterates every page automatically — repeatedly requesting incrementing page values and yielding each page's entries until `isLastPage` is true.

6 Rate limiting, retries & timeouts

PlentyMarkets enforces request throttling and returns the remaining short-period allowance in response headers. The client reads these and proactively paces itself:

X-Plenty-Global-Short-Period-Calls-Left	Remaining calls in the current short window.
--	--

X-Plenty-Global-Short-Period-Delay	Seconds until the window resets.
---	----------------------------------

When the remaining short-period allowance drops to one or fewer, the client defers the next request until the decay window has elapsed. In addition, transient throttling and availability responses are retried automatically:

Retried statuses	429 (rate limited) and 503 (unavailable).
Retried methods	GET, POST, PUT, PATCH, DELETE.
Backoff	Exponential with jitter — base 0.5 s, factor $\times 2$, capped at 30 s.
Max attempts	3 (configurable).
Timeouts	Connection open 5 s, total 30 s (both configurable).

7 Error handling

HTTP status codes are mapped onto a small exception hierarchy, and JSON error payloads are inspected for validation and credential failures.

3xx	Raises a redirection error.
4xx	Raises a client error. A body containing “ <i>no query results</i> ” is surfaced as a not-found error.
5xx	Raises a server error.
Credential failure	An <code>invalid_credentials</code> error payload raises a specific invalid-credentials error.
Validation failure	<code>validation_errors</code> in the payload are collected and raised as a response error.

8 API endpoint catalogue

Every endpoint the gem calls, grouped by resource area. Paths are shown with the `/rest` mount point included; **{placeholders}** mark required path parameters. The “Client call” column gives the Ruby method on the listed class.

Legend: GET POST PUT PATCH DELETE · **{param}** = required path parameter

8.1 Authentication

5 endpoints

Session login, OAuth access-token retrieval, token refresh and logout. The client calls POST /login automatically before any request when no valid token is held.

PlentyClient::Authentication

METHOD	ENDPOINT PATH	CLIENT CALL
POST	/rest/client-login	.client_access_token
POST	/rest/login	.login
POST	/rest/login/refresh	.login_refresh
POST	/rest/logout	.logout
GET	/rest/oauth/access_token	.access_token

8.2 Authorization

2 endpoints

Look up the currently authorised user and its UI configuration.

PlentyClient::Authorization

METHOD	ENDPOINT PATH	CLIENT CALL
GET	/rest/authorized_user	.list
GET	/rest/user/authorized_user_with_ui_config	.list_with_ui_config

8.3 Account

33 endpoints

Contacts and their related records — addresses, bank details and contact types — plus account-level addresses.

PlentyClient::Account

METHOD	ENDPOINT PATH	CLIENT CALL
POST	/rest/account/login	.login
POST	/rest/account/login/refresh	.refresh_login
POST	/rest/account/logout	.logout
GET	/rest/accounts	.list
POST	/rest/accounts	.create
DELETE	/rest/accounts/{accountId}	.destroy
GET	/rest/accounts/{accountId}	.find
PUT	/rest/accounts/{accountId}	.update
GET	/rest/accounts/{accountId}/contacts	.list_contacts

PlentyClient::Account::Address

METHOD	ENDPOINT PATH	CLIENT CALL
POST	/rest/accounts/addresses	.create
DELETE	/rest/accounts/addresses/{addressId}	.destroy
GET	/rest/accounts/addresses/{addressId}	.find
PUT	/rest/accounts/addresses/{addressId}	.update

PlentyClient::Account::Contact

METHOD	ENDPOINT PATH	CLIENT CALL
GET	/rest/accounts/contacts	.list
POST	/rest/accounts/contacts	.create
DELETE	/rest/accounts/contacts/{contactId}	.destroy
GET	/rest/accounts/contacts/{contactId}	.find
PUT	/rest/accounts/contacts/{contactId}	.update

PlentyClient::Account::Contact::Address

METHOD	ENDPOINT PATH	CLIENT CALL
POST	/rest/accounts/contacts/{contactId}/addresses	.create
DELETE	/rest/accounts/contacts/{contactId}/addresses/{addressId}	.destroy
PUT	/rest/accounts/contacts/{contactId}/addresses/{addressId}	.update
PUT	/rest/accounts/contacts/{contactId}/addresses/{addressId}/types/{addressTypeId}/primary	.update_primary
GET	/rest/accounts/contacts/{contactId}/addresses/{addressTypeId}	.list

PlentyClient::Account::Contact::Bank

METHOD	ENDPOINT PATH	CLIENT CALL
POST	/rest/accounts/contacts/banks	.create
DELETE	/rest/accounts/contacts/banks/{contactBankId}	.destroy
GET	/rest/accounts/contacts/banks/{contactBankId}	.find
PUT	/rest/accounts/contacts/banks/{contactBankId}	.update
GET	/rest/accounts/contacts/{contactId}/banks	.list

PlentyClient::Account::Contact::Type

METHOD	ENDPOINT PATH	CLIENT CALL
GET	/rest/accounts/contacts/types	.list
POST	/rest/accounts/contacts/types	.create
DELETE	/rest/accounts/contacts/types/{typeId}	.destroy
GET	/rest/accounts/contacts/types/{typeId}	.find
PUT	/rest/accounts/contacts/types/{typeId}	.update

8.4 Accounting

4 endpoints

VAT configuration, including standard VAT and VAT settings per location and country.

PlentyClient::Accounting

METHOD	ENDPOINT PATH	CLIENT CALL
GET	/rest/vat	.list
GET	/rest/vat/locations/{locationId}	.list_for_location
GET	/rest/vat/locations/{locationId}/countries/{countryId}	.list_for_country
GET	/rest/vat/standard	.standard

8.5 Basket

3 endpoints

Shopping baskets and the items contained within them.

PlentyClient::Basket

METHOD	ENDPOINT PATH	CLIENT CALL
GET	/rest/basket	.find

PlentyClient::Basket::Item

METHOD	ENDPOINT PATH	CLIENT CALL
GET	/rest/basket/items	.list
POST	/rest/basket/items	.create

8.6 Category

13 endpoints

Categories, their branch data and their templates.

PlentyClient::Category

METHOD	ENDPOINT PATH	CLIENT CALL
GET	/rest/categories	.list
POST	/rest/categories	.create
PUT	/rest/categories	.update_all
DELETE	/rest/categories/{catId}	.destroy
GET	/rest/categories/{catId}	.find
PUT	/rest/categories/{catId}	.update
DELETE	/rest/categories/{catId}/clients	.destroy_clients
DELETE	/rest/categories/{catId}/details	.destroy_details

PlentyClient::Category::Branch

METHOD	ENDPOINT PATH	CLIENT CALL
GET	/rest/category_branches	.list
GET	/rest/category_branches/{catId}	.find

PlentyClient::Category::Template

METHOD	ENDPOINT PATH	CLIENT CALL
DELETE	/rest/categories/{catId}/templates	.destroy
GET	/rest/categories/{catId}/templates	.list
PUT	/rest/categories/{catId}/templates	.update

8.7 Comment

4 endpoints

Comments attached to other entities, addressed by reference type and value.

PlentyClient::Comment

METHOD	ENDPOINT PATH	CLIENT CALL
POST	/rest/comments	.create
DELETE	/rest/comments/{commentId}	.destroy
GET	/rest/comments/{commentId}	.find
GET	/rest/comments/{referenceType}/{referenceValue}	.list

8.8 Document

10 endpoints

Generation, upload and download of documents associated with orders and categories.

PlentyClient::Document

METHOD	ENDPOINT PATH	CLIENT CALL
GET	/rest/documents/{documentId}	.download

PlentyClient::Document::Category

METHOD	ENDPOINT PATH	CLIENT CALL
POST	/rest/categories/{categoryId}/documents	.upload
GET	/rest/categories/{categoryId}/documents/	.list
GET	/rest/categories/{categoryId}/documents/downloads	.download
DELETE	/rest/categories/{categoryId}/documents/{documentId}	.destroy

PlentyClient::Document::Order

METHOD	ENDPOINT PATH	CLIENT CALL
GET	/rest/orders/documents/downloads/{type}	.download_by_type
GET	/rest/orders/documents/{type}	.list_by_type
GET	/rest/orders/{orderId}/documents/downloads/{type}	.download
GET	/rest/orders/{orderId}/documents/{type}	.list
POST	/rest/orders/{orderId}/documents/{type}	.upload

8.9 Item

192 endpoints

Items (products) and their complete sub-resource tree: variations, attributes, barcodes, images, manufacturers, properties, sales prices, units, stock, SKUs, suppliers, cross-selling and more. This is the largest area of the API surface.

PlentyClient::Item

METHOD	ENDPOINT PATH	CLIENT CALL
GET	/rest/items	.list
POST	/rest/items	.create
DELETE	/rest/items/{itemId}	.destroy
GET	/rest/items/{itemId}	.find
PUT	/rest/items/{itemId}	.update

PlentyClient::Item::Attribute

METHOD	ENDPOINT PATH	CLIENT CALL
GET	/rest/items/attributes	.list
POST	/rest/items/attributes	.create
DELETE	/rest/items/attributes/{attributeId}	.destroy
GET	/rest/items/attributes/{attributeId}	.find
POST	/rest/items/attributes/{attributeId}	.update

PlentyClient::Item::Attribute::Name

METHOD	ENDPOINT PATH	CLIENT CALL
GET	/rest/items/attributes/{attributeId}/names	.list
POST	/rest/items/attributes/{attributeId}/names	.create
DELETE	/rest/items/attributes/{attributeId}/names/{lang}	.destroy
GET	/rest/items/attributes/{attributeId}/names/{lang}	.find
PUT	/rest/items/attributes/{attributeId}/names/{lang}	.update

PlentyClient::Item::Attribute::Value

METHOD	ENDPOINT PATH	CLIENT CALL
GET	/rest/items/attributes/{attributeId}/values	.list
POST	/rest/items/attributes/{attributeId}/values	.create
DELETE	/rest/items/attributes/{attributeId}/values/{valueId}	.destroy
GET	/rest/items/attributes/{attributeId}/values/{valueId}	.find
PUT	/rest/items/attributes/{attributeId}/values/{valueId}	.update

PlentyClient::Item::Attribute::ValueName

METHOD	ENDPOINT PATH	CLIENT CALL
GET	/rest/items/attribute_values/{attributeValueId}/names	.list
POST	/rest/items/attribute_values/{attributeValueId}/names	.create
DELETE	/rest/items/attribute_values/{attributeValueId}/names/{lang}	.destroy
GET	/rest/items/attribute_values/{attributeValueId}/names/{lang}	.find
PUT	/rest/items/attribute_values/{attributeValueId}/names/{lang}	.update

PlentyClient::Item::Barcode

METHOD	ENDPOINT PATH	CLIENT CALL
GET	/rest/items/barcodes	.list
POST	/rest/items/barcodes	.create
GET	/rest/items/barcodes/referrer/{referrerId}	.list_by_referrer
GET	/rest/items/barcodes/type/{type}	.list_by_type
DELETE	/rest/items/barcodes/{barcodeId}	.destroy
GET	/rest/items/barcodes/{barcodeId}	.find
POST	/rest/items/barcodes/{barcodeId}	.update
POST	/rest/items/barcodes/{barcodeId}/referrer	.activate_referrer
DELETE	/rest/items/barcodes/{barcodeId}/referrer/{referrerId}	.deactivate_referrer

PlentyClient::Item::CrossSelling

METHOD	ENDPOINT PATH	CLIENT CALL
GET	/rest/items/{itemId}/item_cross_selling	.list
POST	/rest/items/{itemId}/item_cross_selling	.create
DELETE	/rest/items/{itemId}/item_cross_selling/{crossItemId}	.destroy

PlentyClient::Item::Image

METHOD	ENDPOINT PATH	CLIENT CALL
GET	/rest/items/{itemId}/images	.list
POST	/rest/items/{itemId}/images/upload	.create
POST	/rest/items/{itemId}/images/upload	.upload
DELETE	/rest/items/{itemId}/images/{imageId}	.destroy
GET	/rest/items/{itemId}/images/{imageId}	.find
PUT	/rest/items/{itemId}/images/{imageId}	.update
GET	/rest/items/{itemId}/variations/{variationId}/images	.list_variation_images

PlentyClient::Item::Image::Availability

METHOD	ENDPOINT PATH	CLIENT CALL
DELETE	/rest/items/{itemId}/images/{imageId}/availabilities	.destroy
GET	/rest/items/{itemId}/images/{imageId}/availabilities	.list
POST	/rest/items/{itemId}/images/{imageId}/availabilities	.create

PlentyClient::Item::Image::Name

METHOD	ENDPOINT PATH	CLIENT CALL
GET	/rest/items/{itemId}/images/{imageId}/names	.list
POST	/rest/items/{itemId}/images/{imageId}/names	.create
DELETE	/rest/items/{itemId}/images/{imageId}/names/{lang}	.destroy
GET	/rest/items/{itemId}/images/{imageId}/names/{lang}	.find
PUT	/rest/items/{itemId}/images/{imageId}/names/{lang}	.update

PlentyClient::Item::Manufacturer

METHOD	ENDPOINT PATH	CLIENT CALL
GET	/rest/items/manufacturers	.list
POST	/rest/items/manufacturers	.create
DELETE	/rest/items/manufacturers/{manufacturerId}	.destroy
GET	/rest/items/manufacturers/{manufacturerId}	.find
PUT	/rest/items/manufacturers/{manufacturerId}	.update

PlentyClient::Item::Manufacturer::Commission

METHOD	ENDPOINT PATH	CLIENT CALL
GET	/rest/items/manufacturers/{manufacturerId}/commissions	.list
POST	/rest/items/manufacturers/{manufacturerId}/commissions	.create
DELETE	/rest/items/manufacturers/{manufacturerId}/commissions/{commissionId}	.destroy
GET	/rest/items/manufacturers/{manufacturerId}/commissions/{commissionId}	.find
PUT	/rest/items/manufacturers/{manufacturerId}/commissions/{commissionId}	.update

PlentyClient::Item::Property

METHOD	ENDPOINT PATH	CLIENT CALL
GET	/rest/items/properties	.list
POST	/rest/items/properties	.create
DELETE	/rest/items/properties/{propertyId}	.destroy
GET	/rest/items/properties/{propertyId}	.find
PUT	/rest/items/properties/{propertyId}	.update

PlentyClient::Item::Property::MarketReference

METHOD	ENDPOINT PATH	CLIENT CALL
GET	/rest/items/properties/{propertyId}/market_references	.list
POST	/rest/items/properties/{propertyId}/market_references	.create
DELETE	/rest/items/properties/{propertyId}/market_references/{marketId}	.destroy
GET	/rest/items/properties/{propertyId}/market_references/{marketId}	.find
PUT	/rest/items/properties/{propertyId}/market_references/{marketId}	.update

PlentyClient::Item::Property::Name

METHOD	ENDPOINT PATH	CLIENT CALL
GET	/rest/items/properties/{propertyId}/names	.list
POST	/rest/items/properties/{propertyId}/names	.create
DELETE	/rest/items/properties/{propertyId}/names/{lang}	.destroy
GET	/rest/items/properties/{propertyId}/names/{lang}	.find
PUT	/rest/items/properties/{propertyId}/names/{lang}	.update

PlentyClient::Item::PropertyGroup

METHOD	ENDPOINT PATH	CLIENT CALL
GET	/rest/items/property_groups	.list
POST	/rest/items/property_groups	.create
DELETE	/rest/items/property_groups/{propertyGroupId}	.destroy
GET	/rest/items/property_groups/{propertyGroupId}	.find
PUT	/rest/items/property_groups/{propertyGroupId}	.update

PlentyClient::Item::PropertyGroupName

METHOD	ENDPOINT PATH	CLIENT CALL
GET	/rest/items/property_groups/{propertyGroupId}/names	.list
POST	/rest/items/property_groups/{propertyGroupId}/names	.create
DELETE	/rest/items/property_groups/{propertyGroupId}/names/{lang}	.destroy
GET	/rest/items/property_groups/{propertyGroupId}/names/{lang}	.find
PUT	/rest/items/property_groups/{propertyGroupId}/names/{lang}	.update

PlentyClient::Item::SalesPrice

METHOD	ENDPOINT PATH	CLIENT CALL
GET	/rest/items/sales_prices	.list
POST	/rest/items/sales_prices	.create
DELETE	/rest/items/sales_prices/{salesPriceId}	.destroy
GET	/rest/items/sales_prices/{salesPriceId}	.find
PUT	/rest/items/sales_prices/{salesPriceId}	.update

PlentyClient::Item::ShippingProfile

METHOD	ENDPOINT PATH	CLIENT CALL
GET	/rest/items/{itemId}/item_shipping_profiles	.list
POST	/rest/items/{itemId}/item_shipping_profiles	.create
DELETE	/rest/items/{itemId}/item_shipping_profiles/{shippingProfileId}	.destroy

PlentyClient::Item::Unit

METHOD	ENDPOINT PATH	CLIENT CALL
GET	/rest/items/units	.list
GET	/rest/items/units	.find
POST	/rest/items/units	.create
DELETE	/rest/items/units/{unitId}	.destroy
PUT	/rest/items/units/{unitId}	.update

PlentyClient::Item::UnitName

METHOD	ENDPOINT PATH	CLIENT CALL
GET	/rest/item/units/{unitID}/names	.list
POST	/rest/item/units/{unitID}/names	.create
DELETE	/rest/item/units/{unitID}/names/{lang}	.destroy
GET	/rest/item/units/{unitID}/names/{lang}	.find
PUT	/rest/item/units/{unitID}/names/{lang}	.update

PlentyClient::Item::Variation

METHOD	ENDPOINT PATH	CLIENT CALL
GET	/rest/items/variations	.all
GET	/rest/items/{itemId}/variations	.list
POST	/rest/items/{itemId}/variations	.create
DELETE	/rest/items/{itemId}/variations/{variationId}	.destroy
GET	/rest/items/{itemId}/variations/{variationId}	.find
PUT	/rest/items/{itemId}/variations/{variationId}	.update

PlentyClient::Item::Variation::Barcode

METHOD	ENDPOINT PATH	CLIENT CALL
GET	/rest/items/{itemId}/variations/{variationId}/variation_barcodes	.list
POST	/rest/items/{itemId}/variations/{variationId}/variation_barcodes	.create
DELETE	/rest/items/{itemId}/variations/{variationId}/variation_barcodes/{barcodeId}	.destroy
GET	/rest/items/{itemId}/variations/{variationId}/variation_barcodes/{barcodeId}	.find
PUT	/rest/items/{itemId}/variations/{variationId}/variation_barcodes/{barcodeId}	.update

PlentyClient::Item::Variation::Bundle

METHOD	ENDPOINT PATH	CLIENT CALL
GET	/rest/items/{itemId}/variations/{variationId}/variation_bundles	.list
POST	/rest/items/{itemId}/variations/{variationId}/variation_bundles	.create
DELETE	/rest/items/{itemId}/variations/{variationId}/variation_bundles/{bundleId}	.destroy
GET	/rest/items/{itemId}/variations/{variationId}/variation_bundles/{bundleId}	.find
PUT	/rest/items/{itemId}/variations/{variationId}/variation_bundles/{bundleId}	.update

PlentyClient::Item::Variation::Category

METHOD	ENDPOINT PATH	CLIENT CALL
POST	/rest/items/variations/variation_categories	.bulk_assign
GET	/rest/items/{itemId}/variations/{variationId}/variation_categories	.list
POST	/rest/items/{itemId}/variations/{variationId}/variation_categories	.create
DELETE	/rest/items/{itemId}/variations/{variationId}/variation_categories/{categoryId}	.destroy
GET	/rest/items/{itemId}/variations/{variationId}/variation_categories/{categoryId}	.find
PUT	/rest/items/{itemId}/variations/{variationId}/variation_categories/{categoryId}	.update

PlentyClient::Item::Variation::Client

METHOD	ENDPOINT PATH	CLIENT CALL
GET	/rest/items/{itemId}/variations/{variationId}/variation_clients	.list
POST	/rest/items/{itemId}/variations/{variationId}/variation_clients	.create
DELETE	/rest/items/{itemId}/variations/{variationId}/variation_clients/{plentyId}	.destroy

PlentyClient::Item::Variation::DefaultCategory

METHOD	ENDPOINT PATH	CLIENT CALL
GET	/rest/items/{itemId}/variations/{variationId}/variation_default_categories	.list
POST	/rest/items/{itemId}/variations/{variationId}/variation_default_categories	.create
DELETE	/rest/items/{itemId}/variations/{variationId}/variation_default_categories/{plentyId}	.destroy
GET	/rest/items/{itemId}/variations/{variationId}/variation_default_categories/{plentyId}	.find

PlentyClient::Item::Variation::Description

METHOD	ENDPOINT PATH	CLIENT CALL
GET	/rest/items/{itemId}/variations/{variationId}/descriptions	.list
POST	/rest/items/{itemId}/variations/{variationId}/descriptions	.create
DELETE	/rest/items/{itemId}/variations/{variationId}/descriptions/{lang}	.destroy
GET	/rest/items/{itemId}/variations/{variationId}/descriptions/{lang}	.find
PUT	/rest/items/{itemId}/variations/{variationId}/descriptions/{lang}	.update

PlentyClient::Item::Variation::Image

METHOD	ENDPOINT PATH	CLIENT CALL
GET	/rest/items/{itemId}/images/{imageId}/variation_images	.list_images_image_links
GET	/rest/items/{itemId}/variation_images	.list_items_image_links
GET	/rest/items/{itemId}/variations/{variationId}/variation_images	.list_variations_image_links
POST	/rest/items/{itemId}/variations/{variationId}/variation_images	.create
DELETE	/rest/items/{itemId}/variations/{variationId}/variation_images/{imageId}	.destroy

PlentyClient::Item::Variation::Market

METHOD	ENDPOINT PATH	CLIENT CALL
GET	/rest/items/{itemId}/variations/{variationId}/variation_markets	.list
POST	/rest/items/{itemId}/variations/{variationId}/variation_markets	.create
DELETE	/rest/items/{itemId}/variations/{variationId}/variation_markets/{marketplaceId}	.destroy

PlentyClient::Item::Variation::MarketIdentNumber

METHOD	ENDPOINT PATH	CLIENT CALL
GET	/rest/items/{itemId}/variations/{variationId}/market_ident_numbers	.list
POST	/rest/items/{itemId}/variations/{variationId}/market_ident_numbers	.create
DELETE	/rest/items/{itemId}/variations/{variationId}/market_ident_numbers/{marketIdentNumberId}	.destroy
GET	/rest/items/{itemId}/variations/{variationId}/market_ident_numbers/{marketIdentNumberId}	.find
PUT	/rest/items/{itemId}/variations/{variationId}/market_ident_numbers/{marketIdentNumberId}	.update

PlentyClient::Item::Variation::Property

METHOD	ENDPOINT PATH	CLIENT CALL
POST	/rest/items/variations/variation_properties	.bulk_create
PUT	/rest/items/variations/variation_properties	.bulk_update
DELETE	/rest/items/{itemId}/variations/{variationId}/variation_properties	.destroy_all
GET	/rest/items/{itemId}/variations/{variationId}/variation_properties	.list
POST	/rest/items/{itemId}/variations/{variationId}/variation_properties	.create
DELETE	/rest/items/{itemId}/variations/{variationId}/variation_properties/{propertyId}	.destroy
GET	/rest/items/{itemId}/variations/{variationId}/variation_properties/{propertyId}	.find
PUT	/rest/items/{itemId}/variations/{variationId}/variation_properties/{propertyId}	.update

PlentyClient::Item::Variation::Property::Text

METHOD	ENDPOINT PATH	CLIENT CALL
GET	/rest/items/{itemId}/variations/{variationId}/variation_properties/{propertyId}/texts	.find
POST	/rest/items/{itemId}/variations/{variationId}/variation_properties/{propertyId}/texts	.create
DELETE	/rest/items/{itemId}/variations/{variationId}/variation_properties/{propertyId}/texts/{lang}	.destroy
GET	/rest/items/{itemId}/variations/{variationId}/variation_properties/{propertyId}/texts/{lang}	.find_by_language
PUT	/rest/items/{itemId}/variations/{variationId}/variation_properties/{propertyId}/texts/{lang}	.update

PlentyClient::Item::Variation::SalesPrice

METHOD	ENDPOINT PATH	CLIENT CALL
PUT	/rest/items/variations/variation_sales_prices	.bulk_update
GET	/rest/items/{itemId}/variations/{variationId}/variation_sales_prices	.list
POST	/rest/items/{itemId}/variations/{variationId}/variation_sales_prices	.create
DELETE	/rest/items/{itemId}/variations/{variationId}/variation_sales_prices/{priceId}	.destroy
GET	/rest/items/{itemId}/variations/{variationId}/variation_sales_prices/{priceId}	.find
PUT	/rest/items/{itemId}/variations/{variationId}/variation_sales_prices/{priceId}	.update

PlentyClient::Item::Variation::Sku

METHOD	ENDPOINT PATH	CLIENT CALL
GET	/rest/items/{itemId}/variations/{variationId}/variation_skus	.list
POST	/rest/items/{itemId}/variations/{variationId}/variation_skus	.create
PUT	/rest/items/{itemId}/variations/{variationId}/variation_skus	.update
DELETE	/rest/items/{itemId}/variations/{variationId}/variation_skus/{skuId}	.destroy
GET	/rest/items/{itemId}/variations/{variationId}/variation_skus/{skuId}	.find

PlentyClient::Item::Variation::Stock

METHOD	ENDPOINT PATH	CLIENT CALL
GET	/rest/items/{itemId}/variations/{variationId}/stock	.list
PUT	/rest/items/{itemId}/variations/{variationId}/stock/bookIncomingItems	.update_incoming_items
PUT	/rest/items/{itemId}/variations/{variationId}/stock/correction	.update_corrections
GET	/rest/items/{itemId}/variations/{variationId}/stock/movements	.list_stock_movements
PUT	/rest/items/{itemId}/variations/{variationId}/stock/redistribute	.update_redistributions
GET	/rest/items/{itemId}/variations/{variationId}/stock/storageLocations	.list_storage_locations

PlentyClient::Item::Variation::Supplier

METHOD	ENDPOINT PATH	CLIENT CALL
GET	/rest/items/{itemId}/variations/{variationId}/variation_suppliers	.list
POST	/rest/items/{itemId}/variations/{variationId}/variation_suppliers	.create
PUT	/rest/items/{itemId}/variations/{variationId}/variation_suppliers	.update
DELETE	/rest/items/{itemId}/variations/{variationId}/variation_suppliers/{variationSupplierId}	.destroy
GET	/rest/items/{itemId}/variations/{variationId}/variation_suppliers/{variationSupplierId}	.find

PlentyClient::Item::Variation::Warehouse

METHOD	ENDPOINT PATH	CLIENT CALL
GET	/rest/items/{itemId}/variations/{variationId}/variation_warehouses	.list
POST	/rest/items/{itemId}/variations/{variationId}/variation_warehouses	.create
PUT	/rest/items/{itemId}/variations/{variationId}/variation_warehouses	.update
DELETE	/rest/items/{itemId}/variations/{variationId}/variation_warehouses/{warehouseId}	.destroy
GET	/rest/items/{itemId}/variations/{variationId}/variation_warehouses/{warehouseId}	.find

8.10 ItemSet

16 endpoints

Item sets (product bundles), their components and configuration.

PlentyClient::ItemSet

METHOD	ENDPOINT PATH	CLIENT CALL
GET	/rest/item_sets	.list
POST	/rest/item_sets	.create
PUT	/rest/item_sets	.update_sets
PUT	/rest/item_sets	.destroy_sets
GET	/rest/item_sets/{itemSetId}	.find
PUT	/rest/item_sets/{itemSetId}	.update
PUT	/rest/item_sets/{itemSetId}	.destroy

PlentyClient::ItemSet::Component

METHOD	ENDPOINT PATH	CLIENT CALL
DELETE	/rest/item_sets/{itemSetId}/components	.destroy_item_sets_components
GET	/rest/item_sets/{itemSetId}/components	.list_item_sets_components
POST	/rest/item_sets/{itemSetId}/components	.create
PUT	/rest/item_sets/{itemSetId}/components	.update_item_sets_components
DELETE	/rest/item_sets/{itemSetId}/components/{componentId}	.destroy_item_set_component
GET	/rest/item_sets/{itemSetId}/components/{componentId}	.list_item_set_component
PUT	/rest/item_sets/{itemSetId}/components/{componentId}	.update_item_set_component

PlentyClient::ItemSet::Config

METHOD	ENDPOINT PATH	CLIENT CALL
GET	/rest/item_sets/{itemSetId}/config	.find
PUT	/rest/item_sets/{itemSetId}/config	.update

8.11 Listing

42 endpoints

Marketplace listings together with markets, layout/option templates, listing types and shipping profiles.

PlentyClient::Listing

METHOD	ENDPOINT PATH	CLIENT CALL
GET	/rest/listings	.list
POST	/rest/listings	.create
DELETE	/rest/listings/{listingId}	.destroy
GET	/rest/listings/{listingId}	.find
POST	/rest/listings/{listingId}	.update

PlentyClient::Listing::LayoutTemplate

METHOD	ENDPOINT PATH	CLIENT CALL
POST	/rest/listings/layout_templates	.create
DELETE	/rest/listings/layout_templates/{layoutTemplateId}	.destroy
GET	/rest/listings/layout_templates/{layoutTemplateId}	.find

PlentyClient::Listing::Market

METHOD	ENDPOINT PATH	CLIENT CALL
GET	/rest/listings/markets	.list
POST	/rest/listings/markets	.create
POST	/rest/listings/markets/start/{marketListingId}	.start
POST	/rest/listings/markets/verify/{marketListingId}	.verify
DELETE	/rest/listings/markets/{marketListingId}	.destroy
GET	/rest/listings/markets/{marketListingId}	.find
PUT	/rest/listings/markets/{marketListingId}	.update

PlentyClient::Listing::Market::Directory

METHOD	ENDPOINT PATH	CLIENT CALL
POST	/rest/listings/markets/directories	.create
DELETE	/rest/listings/markets/directories/{directoryId}	.destroy
GET	/rest/listings/markets/directories/{directoryId}	.find
PUT	/rest/listings/markets/directories/{directoryId}	.update

PlentyClient::Listing::Market::History

METHOD	ENDPOINT PATH	CLIENT CALL
GET	/rest/listings/markets/histories	.list
DELETE	/rest/listings/markets/histories/end/{marketListingHistoryId}	.end
POST	/rest/listings/markets/histories/relist/{marketListingHistoryId}	.relist
PUT	/rest/listings/markets/histories/update	.update_many
PUT	/rest/listings/markets/histories/update/{marketListingHistoryId}	.update
GET	/rest/listings/markets/histories/{marketListingHistoryId}	.find

PlentyClient::Listing::Market::Info

METHOD	ENDPOINT PATH	CLIENT CALL
GET	/rest/listings/markets/infos	.list

PlentyClient::Listing::Market::Text

METHOD	ENDPOINT PATH	CLIENT CALL
GET	/rest/listings/markets/texts	.list
POST	/rest/listings/markets/texts	.create
DELETE	/rest/listings/markets/texts/{marketTextId}	.destroy
GET	/rest/listings/markets/texts/{marketTextId}	.find
PUT	/rest/listings/markets/texts/{marketTextId}	.update

PlentyClient::Listing::OptionTemplate

METHOD	ENDPOINT PATH	CLIENT CALL
POST	/rest/listings/option_templates	.create
GET	/rest/listings/option_templates/preview	.preview
DELETE	/rest/listings/option_templates/{optionTemplateId}	.destroy
GET	/rest/listings/option_templates/{optionTemplateId}	.find
PUT	/rest/listings/option_templates/{optionTemplateId}	.update

PlentyClient::Listing::ShippingProfile

METHOD	ENDPOINT PATH	CLIENT CALL
GET	/rest/listings/shipping_profiles	.list
GET	/rest/listings/shipping_profiles/{shippingProfileId}	.find

PlentyClient::Listing::StockDependenceType

METHOD	ENDPOINT PATH	CLIENT CALL
GET	/rest/listings/types	.list
GET	/rest/listings/types/{typeId}	.find

PlentyClient::Listing::Type

METHOD	ENDPOINT PATH	CLIENT CALL
GET	/rest/listings/types	.list
GET	/rest/listings/types/{typeId}	.find

8.12 Market

14 endpoints

Marketplace credentials and eBay-specific endpoints (authentication, parts fitment, shop categories).

PlentyClient::Market::Credentials

METHOD	ENDPOINT PATH	CLIENT CALL
GET	/rest/markets/credentials	.list
POST	/rest/markets/credentials	.create
DELETE	/rest/markets/credentials/{credentialsId}	.destroy
GET	/rest/markets/credentials/{credentialsId}	.find
PUT	/rest/markets/credentials/{credentialsId}	.update

PlentyClient::Market::Ebay::Authentication

METHOD	ENDPOINT PATH	CLIENT CALL
GET	/rest/markets/ebay/auth/login	.find_login_url
PUT	/rest/markets/ebay/auth/refresh-token	.refrest_token

PlentyClient::Market::Ebay::PartsFitment

METHOD	ENDPOINT PATH	CLIENT CALL
GET	/rest/markets/ebay/parts-fitments	.list
POST	/rest/markets/ebay/parts-fitments	.create
GET	/rest/markets/ebay/parts-fitments/search	.search
DELETE	/rest/markets/ebay/parts-fitments/{fitmentId}	.destroy
GET	/rest/markets/ebay/parts-fitments/{fitmentId}	.find
PUT	/rest/markets/ebay/parts-fitments/{fitmentId}	.update

PlentyClient::Market::Ebay::ShopCategory

METHOD	ENDPOINT PATH	CLIENT CALL
GET	/rest/markets/ebay/shop_categories	.list

8.13 Order

42 endpoints

Orders and their related records — order items, shipping, coupons, currencies, dates, referrers, contact wishes and status history.

PlentyClient::Order

METHOD	ENDPOINT PATH	CLIENT CALL
GET	/rest/orders	.list
POST	/rest/orders	.create
GET	/rest/orders/contacts/{contactId}	.list_contacts_orders
DELETE	/rest/orders/{orderId}	.destroy
GET	/rest/orders/{orderId}	.find
PUT	/rest/orders/{orderId}	.update
GET	/rest/orders/{orderId}/packagenumbers	.list_package_numbers

PlentyClient::Order::ContactWish

METHOD	ENDPOINT PATH	CLIENT CALL
GET	/rest/orders/{orderId}/contactWish	.find

PlentyClient::Order::CouponCode

METHOD	ENDPOINT PATH	CLIENT CALL
POST	/rest/orders/{orderId}/coupons/{coupon}	.update

PlentyClient::Order::CouponCode::Contact

METHOD	ENDPOINT PATH	CLIENT CALL
POST	/rest/orders/coupons/codes/contacts/{contactId}	.update

PlentyClient::Order::CouponCode::Validation

METHOD	ENDPOINT PATH	CLIENT CALL
POST	/rest/orders/coupons/codes/{coupon}	.update

PlentyClient::Order::Currency

METHOD	ENDPOINT PATH	CLIENT CALL
GET	/rest/orders/currencies	.list
GET	/rest/orders/currencies/countries/{countryId}	.find_currency
GET	/rest/orders/currencies/{currencyIso}	.find
GET	/rest/orders/currencies/{currencyIso}/countries	.find_countries

PlentyClient::Order::Date

METHOD	ENDPOINT PATH	CLIENT CALL
GET	/rest/orders/dates/types/{typeId}/names	.list_date_type_names
GET	/rest/orders/dates/types/{typeId}/names/{lang}	.find_date_type_name
GET	/rest/orders/{orderId}/dates	.list
GET	/rest/orders/{orderId}/dates/{typeId}	.find

PlentyClient::Order::Item

METHOD	ENDPOINT PATH	CLIENT CALL
DELETE	/rest/orders/{orderId}/items/{orderItemId}	.destroy

PlentyClient::Order::Item::SerialNumber

METHOD	ENDPOINT PATH	CLIENT CALL
GET	/rest/orders/{orderId}/items/serialNumbers	.list
GET	/rest/orders/{orderId}/items/{orderItemId}/serialNumbers	.find

PlentyClient::Order::Referrer

METHOD	ENDPOINT PATH	CLIENT CALL
GET	/rest/orders/referrers	.list
POST	/rest/orders/referrers/{parentReferrerId}	.create

PlentyClient::Order::Shipping::Country

METHOD	ENDPOINT PATH	CLIENT CALL
GET	/rest/orders/shipping/countries	.list

PlentyClient::Order::Shipping::Information

METHOD	ENDPOINT PATH	CLIENT CALL
POST	/rest/orders/shipping/shipping_information	.create
DELETE	/rest/orders/{orderId}/shipping/shipping_information	.destroy
GET	/rest/orders/{orderId}/shipping/shipping_information	.list
PUT	/rest/orders/{orderId}/shipping/shipping_information/additional_data	.update_data
PUT	/rest/orders/{orderId}/shipping/shipping_information/status	.update_status

PlentyClient::Order::Shipping::Package

METHOD	ENDPOINT PATH	CLIENT CALL
DELETE	/rest/orders/{orderId}/shipping/packages	.destroy_all
GET	/rest/orders/{orderId}/shipping/packages	.list
POST	/rest/orders/{orderId}/shipping/packages	.create
PUT	/rest/orders/{orderId}/shipping/packages	.update
DELETE	/rest/orders/{orderId}/shipping/packages/{orderShippingPackageId}	.destroy
GET	/rest/orders/{orderId}/shipping/packages/{orderShippingPackageId}	.find

PlentyClient::Order::Shipping::Profile

METHOD	ENDPOINT PATH	CLIENT CALL
GET	/rest/orders/shipping/presets	.list
GET	/rest/orders/shipping/presets/{presetId}	.find

PlentyClient::Order::Shipping::ServiceProvider

METHOD	ENDPOINT PATH	CLIENT CALL
GET	/rest/orders/shipping/shipping_service_providers	.list
GET	/rest/orders/shipping/shipping_service_providers/{shippingServiceProviderID}	.find

PlentyClient::Order::StatusHistory

METHOD	ENDPOINT PATH	CLIENT CALL
GET	/rest/orders/status-history	.list
GET	/rest/orders/{orderId}/status-history	.find

8.14 OrderSummary

7 endpoints

Aggregated order summaries, addressable by summary id, contact or address.

PlentyClient::OrderSummary

METHOD	ENDPOINT PATH	CLIENT CALL
GET	/rest/order_summaries	.list
POST	/rest/order_summaries	.create
GET	/rest/order_summaries/contacts/{contactId}	.find_by_contact
GET	/rest/order_summaries/orders/{addressId}	.find_by_address
DELETE	/rest/order_summaries/{orderSummaryId}	.destroy
GET	/rest/order_summaries/{orderSummaryId}	.find
PUT	/rest/order_summaries/{orderSummaryId}	.update

8.15 Payment

36 endpoints

Payments and their related records — methods, properties, property types, transactions, statuses and contact/order links.

PlentyClient::Payment

METHOD	ENDPOINT PATH	CLIENT CALL
GET	/rest/payments	.list
GET	/rest/payments/entrydate	.list_by_entry_date
GET	/rest/payments/importdate	.list_by_import_date
GET	/rest/payments/{paymentId}	.find
PUT	/rest/payments/{paymentId}	.update

PlentyClient::Payment::Contact

METHOD	ENDPOINT PATH	CLIENT CALL
DELETE	/rest/payment/{paymentId}/contact	.destroy
POST	/rest/payment/{paymentId}/contact/{contactId}	.create

PlentyClient::Payment::Method

METHOD	ENDPOINT PATH	CLIENT CALL
GET	/rest/payments/methods	.list
POST	/rest/payments/methods	.create
PUT	/rest/payments/methods	.update
GET	/rest/payments/methods/ebics	.list_ebics_accounts
POST	/rest/payments/methods/ebics	.create_ebics_account
GET	/rest/payments/methods/{paymentMethodId}	.find
GET	/rest/payments/methods/{pluginKey}	.find_by_plugin_key

PlentyClient::Payment::MethodName

METHOD	ENDPOINT PATH	CLIENT CALL
GET	/rest/payments/methodNames	.list_for_payment_method
GET	/rest/payments/methodNames	.list
GET	/rest/payments/methodNames/{paymentMethodId}	.list_for_payment_method_by_lang

PlentyClient::Payment::Order

METHOD	ENDPOINT PATH	CLIENT CALL
DELETE	/rest/payment/{paymentId}/order	.destroy
POST	/rest/payment/{paymentId}/order/{orderId}	.create
GET	/rest/payments/orders/{orderId}	.list

PlentyClient::Payment::Property

METHOD	ENDPOINT PATH	CLIENT CALL
GET	/rest/payments/properties	.list
POST	/rest/payments/properties	.create
PUT	/rest/payments/properties	.update
GET	/rest/payments/properties/{propertyId}	.find
GET	/rest/payments/property/{propertyTypeId}/{propertyValue}	.list_by_type_and_value
GET	/rest/payments/{paymentId}/properties	.list_by_payment_id

PlentyClient::Payment::Property::Type

METHOD	ENDPOINT PATH	CLIENT CALL
GET	/rest/payments/properties/types	.list
POST	/rest/payments/properties/types	.create
PUT	/rest/payments/properties/types	.update
GET	/rest/payments/properties/types/{typeId}	.find

PlentyClient::Payment::Property::Type::Name

METHOD	ENDPOINT PATH	CLIENT CALL
POST	/rest/payments/properties/types/names	.create
PUT	/rest/payments/properties/types/names	.update
GET	/rest/payments/properties/types/names/{lang}	.list
GET	/rest/payments/properties/types/names/{nameId}	.find

PlentyClient::Payment::Status

METHOD	ENDPOINT PATH	CLIENT CALL
GET	/rest/payments/status/{statusId}	.find

PlentyClient::Payment::Transaction

METHOD	ENDPOINT PATH	CLIENT CALL
GET	/rest/payments/transactions/{transactionTypeId}	.find

8.16 SalesPrice

23 endpoints

Sales prices and their relations: countries, currencies, customer classes, referrers and online stores.

PlentyClient::SalesPrice::Account

METHOD	ENDPOINT PATH	CLIENT CALL
GET	/rest/items/sales_prices/{salesPriceId}/accounts	.list
POST	/rest/items/sales_prices/{salesPriceId}/accounts	.activate
DELETE	/rest/items/sales_prices/{salesPriceId}/accounts/{accountType}/{accountId}	.deactivate

PlentyClient::SalesPrice::Country

METHOD	ENDPOINT PATH	CLIENT CALL
GET	/rest/items/sales_prices/{salesPriceId}/countries	.list
POST	/rest/items/sales_prices/{salesPriceId}/countries	.activate
DELETE	/rest/items/sales_prices/{salesPriceId}/countries/{countryId}	.deactivate

PlentyClient::SalesPrice::Currency

METHOD	ENDPOINT PATH	CLIENT CALL
GET	/rest/items/sales_prices/{salesPriceId}/currencies	.list
POST	/rest/items/sales_prices/{salesPriceId}/currencies	.activate
DELETE	/rest/items/sales_prices/{salesPriceId}/currencies/{currencyIso}	.deactivate

PlentyClient::SalesPrice::CustomerClass

METHOD	ENDPOINT PATH	CLIENT CALL
GET	/rest/items/sales_prices/{salesPriceId}/customer_classes	.list
POST	/rest/items/sales_prices/{salesPriceId}/customer_classes	.activate
DELETE	/rest/items/sales_prices/{salesPriceId}/customer_classes/{customerClassId}	.deactivate

PlentyClient::SalesPrice::Name

METHOD	ENDPOINT PATH	CLIENT CALL
GET	/rest/items/sales_prices/{salesPriceId}/names	.list
POST	/rest/items/sales_prices/{salesPriceId}/names	.create
DELETE	/rest/items/sales_prices/{salesPriceId}/names/{lang}	.destroy
GET	/rest/items/sales_prices/{salesPriceId}/names/{lang}	.list_by_lang
POST	/rest/items/sales_prices/{salesPriceId}/names/{lang}	.update

PlentyClient::SalesPrice::OnlineStore

METHOD	ENDPOINT PATH	CLIENT CALL
GET	/rest/items/sales_prices/{salesPriceId}/online_stores	.list
POST	/rest/items/sales_prices/{salesPriceId}/online_stores	.activate
DELETE	/rest/items/sales_prices/{salesPriceId}/online_stores/{webstoreId}	.deactivate

PlentyClient::SalesPrice::Referrer

METHOD	ENDPOINT PATH	CLIENT CALL
GET	/rest/items/sales_prices/{salesPriceId}/referrers	.list
POST	/rest/items/sales_prices/{salesPriceId}/referrers	.activate
DELETE	/rest/items/sales_prices/{salesPriceId}/referrers/{referrerId}	.deactivate

8.17 Stock

3 endpoints

Stock management: stock listings, redistribution and stock by type.

PlentyClient::Stock

METHOD	ENDPOINT PATH	CLIENT CALL
GET	/rest/stockmanagement/stock	.list
PUT	/rest/stockmanagement/stock/redistribute	.redistribute
GET	/rest/stockmanagement/stock/types/{type}	.list_by_type

8.18 Warehouse

27 endpoints

Warehouses, storage locations (with dimensions and levels), warehouse management and warehouse stock.

PlentyClient::Warehouse

METHOD	ENDPOINT PATH	CLIENT CALL
GET	/rest/stockmanagement/warehouses	.list
POST	/rest/stockmanagement/warehouses	.create
GET	/rest/stockmanagement/warehouses/{id}	.find

PlentyClient::Warehouse::Location

METHOD	ENDPOINT PATH	CLIENT CALL
POST	/rest/warehouses/locations	.create
DELETE	/rest/warehouses/locations/{id}	.destroy
GET	/rest/warehouses/locations/{id}	.find
PUT	/rest/warehouses/locations/{id}	.update
GET	/rest/warehouses/{warehouseId}/locations	.list

PlentyClient::Warehouse::Location::Dimension

METHOD	ENDPOINT PATH	CLIENT CALL
POST	/rest/warehouses/locations/dimensions	.create
DELETE	/rest/warehouses/locations/dimensions/{id}	.destroy
GET	/rest/warehouses/locations/dimensions/{id}	.find
PUT	/rest/warehouses/locations/dimensions/{id}	.update
GET	/rest/warehouses/{warehouseId}/locations/dimensions	.list

PlentyClient::Warehouse::Location::Level

METHOD	ENDPOINT PATH	CLIENT CALL
POST	/rest/warehouses/locations/levels	.create
DELETE	/rest/warehouses/locations/levels/{id}	.destroy
GET	/rest/warehouses/locations/levels/{id}	.find
PUT	/rest/warehouses/locations/levels/{id}	.update
GET	/rest/warehouses/{warehouseId}/locations/levels	.list

PlentyClient::Warehouse::Management

METHOD	ENDPOINT PATH	CLIENT CALL
GET	/rest/stockmanagement/warehouses/{warehouseId}/management/racks	.list_racks
GET	/rest/stockmanagement/warehouses/{warehouseId}/management/racks/{rackId}	.find_racks
GET	/rest/stockmanagement/warehouses/{warehouseId}/management/storageLocations	.list_locations
GET	/rest/stockmanagement/warehouses/{warehouseId}/management/storageLocations/{storageLocationId}	.find_location

PlentyClient::Warehouse::Stock

METHOD	ENDPOINT PATH	CLIENT CALL
GET	/rest/stockmanagement/warehouses/{warehouseId}/stock	.list
PUT	/rest/stockmanagement/warehouses/{warehouseId}/stock/bookIncomingItems	.book_incoming
PUT	/rest/stockmanagement/warehouses/{warehouseId}/stock/correction	.correction
GET	/rest/stockmanagement/warehouses/{warehouseId}/stock/movements	.list_movements
GET	/rest/stockmanagement/warehouses/{warehouseId}/stock/storageLocations	.list_by_location

8.19 Webstore

1 endpoints

Webstore (online store) configuration.

PlentyClient::Webstore

METHOD	ENDPOINT PATH	CLIENT CALL
GET	/rest/webstores	.list

8.20 Properties & Property Groups (API v2)

18 endpoints

Version-2 PIM endpoints for properties and property groups, served under the /v2 path prefix.

PlentyClient::V2::Item::Property

METHOD	ENDPOINT PATH	CLIENT CALL
GET	/rest/v2/properties	.list
POST	/rest/v2/properties	.create
DELETE	/rest/v2/properties/{propertyId}	.destroy
GET	/rest/v2/properties/{propertyId}	.find
PUT	/rest/v2/properties/{propertyId}	.update

PlentyClient::V2::Item::Property::Name

METHOD	ENDPOINT PATH	CLIENT CALL
POST	/rest/v2/properties/names	.create
DELETE	/rest/v2/properties/names/{nameId}	.destroy
GET	/rest/v2/properties/names/{nameId}	.find
PUT	/rest/v2/properties/names/{nameId}	.update

PlentyClient::V2::Item::PropertyGroup

METHOD	ENDPOINT PATH	CLIENT CALL
GET	/rest/v2/properties/groups	.list
POST	/rest/v2/properties/groups	.create
DELETE	/rest/v2/properties/groups/{groupId}	.destroy
GET	/rest/v2/properties/groups/{groupId}	.find
PUT	/rest/v2/properties/groups/{groupId}	.update

PlentyClient::V2::Item::PropertyGroup::Name

METHOD	ENDPOINT PATH	CLIENT CALL
POST	/rest/v2/properties/groups/names	.create
DELETE	/rest/v2/properties/groups/names/{nameId}	.destroy
GET	/rest/v2/properties/groups/names/{nameId}	.find
PUT	/rest/v2/properties/groups/names/{nameId}	.update

8.21 PIM Variations (bulk, /pim)

4 endpoints

PIM bulk variation endpoints served under the /pim path prefix (bulk update and bulk delete of markets, properties and sales prices).

PlentyClient::Rest::Pim::Variations

METHOD	ENDPOINT PATH	CLIENT CALL
PUT	/rest/pim/variations	.update

PlentyClient::Rest::Pim::Variations::Markets

METHOD	ENDPOINT PATH	CLIENT CALL
DELETE	/rest/pim/variations/markets	.delete

PlentyClient::Rest::Pim::Variations::Properties

METHOD	ENDPOINT PATH	CLIENT CALL
DELETE	/rest/pim/variations/properties	.delete

PlentyClient::Rest::Pim::Variations::SalesPrices

METHOD	ENDPOINT PATH	CLIENT CALL
DELETE	/rest/pim/variations/sales_prices	.delete

9 Client configuration reference

The client is configured through `PlentyClient::Config`. The settings relevant to integration behaviour:

site_url

Base URL of the PlentyMarkets instance. The host is reused and paths are mounted under `/rest`.

api_user / api_password

Credentials used for POST `/rest/login`.

plenty_id

PlentyMarkets client (tenant) identifier.

attempt_count

Maximum HTTP attempts for retryable responses (default 3).

open_timeout / timeout

Connection-open and total request timeouts in seconds (defaults 5 / 30).

log

When enabled, requests are logged with the password field filtered out.

A Appendix A — API surface at a glance

Endpoint counts per resource area and HTTP verb.

RESOURCE AREA	CLASSES	GET	POST	PUT	DELETE	TOTAL
Authentication	1	1	4	0	0	5
Authorization	1	2	0	0	0	2
Account	6	11	9	7	6	33
Accounting	1	4	0	0	0	4
Basket	2	2	1	0	0	3
Category	3	5	1	3	4	13
Comment	1	2	1	0	1	4
Document	3	7	2	0	1	10
Item	38	77	43	33	39	192
ItemSet	3	5	2	7	2	16
Listing	11	19	10	6	7	42
Market	4	7	2	3	2	14
Order	16	26	7	4	5	42
OrderSummary	1	4	1	1	1	7
Payment	10	22	7	5	2	36
SalesPrice	7	8	8	0	7	23
Stock	1	2	0	1	0	3
Warehouse	6	15	4	5	3	27
Webstore	1	1	0	0	0	1
Properties & Property Groups (API v2)	4	6	4	4	4	18
PIM Variations (bulk, /pim)	4	0	0	1	3	4
All resources	125	227	108	81	87	503

Total includes 0 PATCH endpoint(s) where applicable. Counts reflect plenty_client v0.1.3.