



INGENIERÍA EN TECNOLOGÍAS DE LA TELECOMUNICACIÓN

Curso Académico 2017/2018

Trabajo Fin de Grado/Máster

ANGULAR - ELASTICSEARCH - DASHBOARD INTERFACE

Autor : Ismael Slimane Zubillaga

Tutor : Dr. Jesús M. González-Barahona

Trabajo Fin de Grado/Máster

Título del Trabajo con Letras Capitales para Sustantivos y Adjetivos

Autor : Nombre del Alumno/a

Tutor : Dr. Gregorio Robles Martínez

La defensa del presente Proyecto Fin de Carrera se realizó el día de
de 20XX, siendo calificada por el siguiente tribunal:

Presidente:

Secretario:

Vocal:

y habiendo obtenido la siguiente calificación:

Calificación:

Fuenlabrada, a de de 20XX

*Dedicado a
mi familia / mi abuelo / mi abuela*

Agradecimientos

Resumen

Summary

Contents

1	Introducción	1
1.1	Descripción del Problema	1
1.2	Objetivo Principal y Estructura	1
1.3	Disponibilidad del Software	1
2	State of Art	3
2.1	ElasticSearch	3
2.1.1	History	3
2.1.2	Basic Concepts	4
2.2	Kibana	5
2.2.1	Main Features	5
2.3	GitHub	7
2.4	Webpack	7
2.5	Angular	8
2.5.1	Versions	8
2.6	TypeScript	9
2.6.1	History	9
2.6.2	Language Features	10
2.7	JavaScript	11
2.7.1	History	11
2.7.2	Syntax	12
2.8	Lodash	12
2.9	jQuery	13
2.9.1	History	13

2.9.2	Usage Examples	13
2.10	HTML5	14
2.10.1	Features	14
2.11	ChartJS	15
2.11.1	Usage Examples	15
2.12	SASS	17
2.12.1	Features	17
2.13	Flexbox	18
2.13.1	Usage Examples	18
3	Development	21
3.1	SCRUM Methodology	21
3.2	Sprint 1	22
3.2.1	Key Objectives	22
3.2.2	Implementing a simple metric request	22
3.2.3	Adding aggregations and dynamic index	24
3.3	Sprint 2	25
3.3.1	Key Objectives	25
3.3.2	Finishing metrics	27
3.3.3	Implementing "Data Table" feature	27
3.3.4	Loading and saving visualizations	28
3.4	Sprint 3	31
3.5	Sprint 4	31
3.6	General Structure	31
4	Resultados	33
5	Conclusiones	35
5.1	Consecución de objetivos	35
5.2	Aplicación de lo aprendido	35
5.3	Lecciones aprendidas	35
5.4	Trabajos futuros	36

<i>CONTENTS</i>	XI
A Manual de usuario	37
Bibliography	39

List of Figures

2.1	Kibana's nav-bar.	6
2.2	Visualization example.	6
2.3	Dashboard example.	7
2.4	Architecture of an Angular application	9
2.5	View result.	14
2.6	View result.	16
2.7	no-wrap example.	19
2.8	wrap example.	19
2.9	flex-end example.	19
2.10	center example.	20
3.1	SCRUM Framework	22
3.2	Final stage view - Sprint 1	26
3.3	Sprint 1 architecture.	26
3.4	Sprint 2 architecture - Step 1.	27
3.5	Sprint 2 final structure.	31
3.6	Estructura del parser básico	32

Chapter 1

Introducción

1.1 Descripción del Problema

1.2 Objetivo Principal y Estructura

1.3 Disponibilidad del Software

Chapter 2

State of Art

2.1 ElasticSearch

Elasticsearch is an open-source, *broadly-distributable*, *readily-scalable*, *enterprise-grade* search engine based on Lucene¹. It provides a distributed, multitenant-capable full-text search engine with an HTTP web interface and schema-free JSON documents.

2.1.1 History

Compass was the predecessor to Elasticsearch and it was created by **Shay Banon** in 2004. Through the implementation of the third version of Compass, came the necessity of a "*scalable search solution*". This necessity would have meant a lot of work rewriting big pieces of code, so Shay decided to build "*a solution built from the ground up to be distributed*" and used a common interface, *JSON* over *HTTP*, available for other programming languages, and not only *Java*.

The first version of Elasticsearch was released on February 2010.

¹https://en.wikipedia.org/wiki/Apache_Lucene

2.1.2 Basic Concepts

All the following concepts definitions are extracted from the Elasticsearch documentation web page².

- **Near Realtime (NRT):** Elasticsearch is a near real time search platform. The practical meaning of this is that there is a little latency (about one second) from the moment you store a new document, to the moment it becomes available for searching.
- **Index:** An **index** is a set of documents that share some type of characteristics. For example, you can have an index for a shop product, another index for employee data and another for bill data. An index is identified by its name (in lowercase), and this name is used for several operations as: searching, deleting, updating, etc.
- **Shards & Replicas:** The index data can reach a large size exceeding the available physical memory. But this problem can be fixed by defining multiple **shards**. Each shard is a portion of data from the index data. The number of shards is defined when the index is created.

But there is still another potential problem. It always exists the possibility to have a failure on the network system and to loose a shard/node, so it is advisable to have **replicas** of our data. A replica is a copy of the index shards.

- **Type:** We can see a **type** like an object class, with fields of different data-types.

In Elasticsearch a type is defined by its *name* and its *mappings*. The *mappings* are a schema of the type, where it's defined the properties that our type has, and the data-type of each property, such as *integer*, *string*, *etc..*

- **Document:** As we said about *types* being like classes, we could see a **document** like a record from a single class. Using the same example we used for *indexes*, you can have a document for a single product, another document for a single employee and yet another for a single bill.

²https://www.elastic.co/guide/en/elasticsearch/reference/current/_basic_concepts.html

- **Node:** We can see a **node** like a single server, as a single unit that along with other nodes, make up a cluster. This node take part on cluster's indexing and searching tasks.
- **Cluster:** As we said in the previous definition, a **cluster** is made up with multiple nodes(servers). The cluster stores all the data and allows to search and index all this data across all nodes. A cluster is a collection of one or more nodes (servers) that together holds your entire data and provides federated indexing and search capabilities through all nodes.

2.2 Kibana

Kibana is an *Elasticsearch* open-source plug-in. It mainly works with Elasticsearch indexed data in order to represent it into different types of visualizations such as bar charts, scatter plot charts, pie charts, ...

Kibana, as an exploration tool, can be used to log and time series analytics, application monitoring, and operational intelligence use cases.

We can find another similar applications such as *Grafana*³, *incubator-superset*⁴ and *Tableau*⁵.

2.2.1 Main Features

In the Figure 2.1, we can see the Kibana's *nav-bar*. Now we are going to speak about a couple of features.

- **Visualize:**

Visualize allows you to represent data with a specific type of chart. The represented data will be chosen from the available index on Elasticsearch. In addition to the Elasticsearch index, we have to choose which type of *aggregations* are we going to use in order to extract our data. We can see an example on Figure 2.2.

- **Dashboard:**

³<https://grafana.com/>

⁴<https://github.com/apache/incubator-superset>

⁵<https://www.tableau.com/>




Figure 2.1: Kibana's nav-bar.




Figure 2.2: Visualization example.




Figure 2.3: Dashboard example.

The Kibana's dashboard functionality allows us to display a collection of saved visualizations and organize them by dragging and dropping. We can see an example on Figure 2.3.

2.3 GitHub

"**GitHub** is a *Web-based Git version control repository hosting service*". Github is used mainly for programming code. In addition to Git functionalities as *deistributed version control* and *source code management*, Github provides more features such as collaboration features for *bug tracking* and for other porposes, task management, and *wikis* for documentation porposes.

For the current project, a repository was created on *Github* with the name of '*Angular-ElasticSearch-Dashboard_Interface*'⁶.

2.4 Webpack

"**Webpack** is an *open-source JavaScript module bundler*". The main reason for using Webpack is to have a modular structure on your web application project. This allows you to have a cleaner

⁶https://github.com/islimane/Angular-ElasticSearch-Dashboard_Interface

code and make it more reusable and scalable. Webpack can be used from the command line or be configured with a config file named *webpack.config.js*.

2.5 Angular

Angular is an open source *web application platform* based on *Typescript* and developed by Google and by a community of individuals and corporations. Angular is commonly referred to as Angular 2.0 or later versions.

2.5.1 Versions

Before Angular was created, there was a previous version called *AngularJS* or Angular1.X. Angular was created as a complete rewrite of AngularJS.

- 2.0.0:

This was the first version of Angular. Its announcing was made at the *ng-Europe* conference on September 2014. This version was build up from the ground and these were the main characteristics:

- Introduced the components hierarchy.
- Modules for core functionality, improving the speed of the Angular core.
- Possibility of using *TypeScript* language. The use of this language is recommended by the Angular team.
- Improved *dependency* injection.
- Dynamic loading.
- Reactive programming support using RxJS.

And much more features. The final version was released on September 14, 2016.

- 4.0.0:

This version was called *Angular 4* and was announced on 13 December 2016. Angular 3 was skipped due to some features already present on version 3.0.0 and to avoid confusion. This version introduced:




Figure 2.4: Architecture of an Angular application

- *Http* client.
- A new *Route Live Cycle*.
- Conditionally disable animations.
- 5.0.0:

This version was released on November 2017 and the main introduced features were:

- Support for progressive Web apps.
- A build optimizer and improvements related to *Material Design*.

2.6 TypeScript

"**TypeScript** is a free and open-source programming language developed and maintained by Microsoft. It is a strict syntactical *superset* of *JavaScript*, and adds optional static typing to the language".

2.6.1 History

Before it was made public, *TypeScript* gone through a two years of development process until it reached the 0.8 version. Then, was released on October 2012. Initially it had a lack of *IDE*

support, until 2013 when some IDE's began to have support for this language, such as *Eclipse* with a dedicated pug-in, and some text editors such as *Sublime*, *Atom*, etc.

The reason TypeScript was created came from the necessity of a front-end programming language that fulfill the task of the development of complex and large-scale front-end applications, since JavaScript has shortcomings on that sense.

TypeScript is based on the *EMACScript* approach, the reason why is because it is a standard and because it has support for *class-based programming*.

2.6.2 Language Features

- Type annotations and compile-time type checking:

TypeScript provides an optional static typing, with annotations, that is checked at compile time. If this typing it is not used, then the Javascript's dynamic typing is used. Here is an example:

```
1 function planetMoons(planetName: string, moonsNum: number,  
    spanish: boolean): any {  
2     if(spanish){  
3         console.log('El planeta ' + planetName + ' tiene ' +  
            moonsNum + ' lunas');  
4     }else{  
5         console.log(planetName + ' planet has ' + moonsNum + '  
            moons');  
6     }  
7  
8     return null;  
9 }
```

string, *boolean* and *number* are primitive types. For dynamic types it's used *any*.

- Type inference.
- Type erasure.
- Interfaces.

- Enumerated type.
- Mixin.
- Generic.
- Namespaces.
- Tuple.
- Await.
- Classes (backported from ECMAScript 2015).
- Modules (backported from ECMAScript 2015).

2.7 JavaScript

"**JavaScript**, often abbreviated as JS, is a high-level, dynamic, weakly typed, prototype-based, multi-paradigm, and interpreted programming language. Alongside HTML and CSS, JavaScript is one of the three core technologies of World Wide Web content production". Generally, the main purpose of Javascript is to make pages interactive and develop online programs such as online games. Javascript is supported by most of the web browsers, for that reason, the majority of the websites employ it. There are multiple engines for Javascript, but all are standardized with the *ECMAScript* specification.

2.7.1 History

Javascript came with the necessity of dynamism on web browsers. The founder of Netscape Communications, Marc Andreessen, thought that HTML needed a "glue language" to assemble component like images or plug-ins into the web markup. In 1995, Netscape Communications began to use *Java* as a static programming language for Netscape Navigator, so the scripting language they had being searching for, had to be similar to Java and would complement it. Then, on May 1995, Brendan Eich wrote in 10 days this scripting language in order to compete against competing proposals. The first time this scripting language was called JavaScript was on December 1995, when the Netscape Navigator 2.0 beta 3 was released.

2.7.2 Syntax

These are a few examples to illustrate the JavaScript syntax:

- Variables:

```
1 var x; // defines the variable x and assigns to it the special
    value "undefined" (not to be confused with an undefined value
    )
2 var y = 2; // defines the variable y and assigns to it the value
    2
3 var z = "Hello, World!"; // defines the variable z and assigns
    to it a string entitled "Hello, World!"
```

- Printing:

```
1 console.log("Hello World!");
```

- Functions:

```
1 function add(a, b) {
2     return a + b;
3 }
4 add(1, 2); // returns 3
```

2.8 Lodash

Lodash is a *JavaScript* library that provides extra functions for tasks that are often required on data structure managing, a lot of them, not implemented on the main JavaScript functionality.

For example:

- **`_.difference(array, [values])`**: Creates an array of unique array values not included in the other provided arrays using `SameValueZero` for equality comparisons.

```
1 _.difference([1, 2, 3], [4, 2]);
2 // returns [1, 3]
```

- **_.pluck(collection, path):** Gets the property value of path from all elements in *collection*.

```
1 var users = [  
2   { 'user': 'barney', 'age': 36 },  
3   { 'user': 'fred',   'age': 40 }  
4 ];  
5  
6 _.pluck(users, 'user');  
7 // returns ['barney', 'fred']
```

As we can see, Lodash functions are called through the global variable "_". All this functions can be found on the Lodash documentation⁷ page. This JavaScript library saves a lot of time when managing data structures.

There are other similar libraries such as *UnderscoreJS*⁸.

2.9 jQuery

"jQuery is a cross-platform JavaScript library designed to simplify the client-side scripting of HTML". jQuery it's the most used JavaScript library. jQuery's syntax is designed to make it easier to navigate a document, select DOM elements, create animations, handle events, and develop Ajax applications.

2.9.1 History

jQuery was originally released in January 2006 at BarCamp NYC by John Resig and was influenced by Dean Edwards' earlier cssQuery library. It is currently maintained by a team of developers led by Timmy Willison.

2.9.2 Usage Examples

- HTML:

```
1 <p>Hello</p>
```

⁷<https://lodash.com/docs/3.10.1>

⁸<http://underscorejs.org/>



Hello
Hello
Again

Figure 2.5: View result.

- JavaScript:

```
1 $( "p" ).clone() .add( "<span>Again</span>" ) .appendTo( document .  
    body );
```

- Result:

See the result on Figure 2.5

2.10 HTML5

"HTML5 is a markup language used for structuring and presenting content on the World Wide Web. It is the fifth and current major version of the HTML standard".

The *World Wide Web Consortium* released HTML5 on October 2014, their goal was "to improve the language with support for the latest multimedia".

2.10.1 Features

These are some of the feature introduced in HTML5:

- Markup:

HTML5 introduces some elements that are commonly used on modern websites, they usually are replacements of old HTML elements, between these new elements we can find: `<nav>`, `<footer>`, `<audio>`, `<video>`, ...

- New APIs:

HTML5 introduces *application programming interfaces* or *APIs* in addition to the markup elements that we have seen, such as *Canvas*, *Timed Media Playback*, *Drag and Drop*, *MIME type*, *Web Messaging*, *Web storage*, ... In this project we have mainly used *Canvas* through the *ChartJS* library.

2.11 ChartJS

ChartJS is a JavaScript library for producing dynamic, interactive data visualizations in web browsers, this is achieved by using the *HTML5 canvas* element. With ChartJS you create different charts such as pie charts, bar charts, line charts, etc. You can find visual examples of each type on the ChartJS samples page⁹.

2.11.1 Usage Examples

We have to instantiate the *Chart* class in order to create a chart, and then assign it to a *canvas* element on the DOM. The field *type* indicates which chart are we going to use, and the field *data* stores our chart info. Here is an example:

- HTML:

```
1 <canvas height='50' id='myChart' width='200'></canvas>
```

- JavaScript:

```
1 var ctx = document.getElementById("#myChart");
2 var myChart = new Chart(ctx, {
3   type: 'bar',
4   data: {
5     labels: ["Red", "Blue", "Yellow"],
6     datasets: [{
7       label: '# of Votes',
8       data: [12, 19, 3, 5, 2, 3],
9       backgroundColor: [
```

⁹<http://www.chartjs.org/samples/latest/>




Figure 2.6: View result.

```

10     'rgba(255, 99, 132, 0.2)',
11     'rgba(54, 162, 235, 0.2)',
12     'rgba(255, 206, 86, 0.2)'
13 ],
14   borderColor: [
15     'rgba(255,99,132,1)',
16     'rgba(54, 162, 235, 1)',
17     'rgba(255, 206, 86, 1)'
18   ],
19   borderWidth: 1
20  }]
21  }
22  });

```

- Result:

See the result on Figure 2.6

There are a lot of libraries that allows you to render charts or graphs on a web page¹⁰ such as *C3.js*, *Plotly.js*, etc. In this project we used ChartJS because it adapted well to the project requirements.

¹⁰<https://blog.sicara.com/compare-best-javascript-chart-libraries-2017-89fbe8cb112d>

2.12 SASS

"Sass is a scripting language that is interpreted or compiled into *Cascading Style Sheets* (CSS)". Sass uses two types of syntax. The first is original syntax, similar to *Haml*¹¹. The second is *SCSS*, a syntax that uses blocks formatting like *CSS*

2.12.1 Features

- **Variables:**

Sass allows defining variables using a dollar sign (\$).

```
1 $primary-color: #3bbfce;
2
3 .content-navigation {
4   border-color: $primary-color;
5   color: darken($primary-color, 10%);
6 }
```

- **Block Nesting:**

Sass allows nesting different style blocks, this improves the code structure, makes it more readable and saves lines of code.

```
1 table.hl {
2   margin: 2em 0;
3   td.ln {
4     text-align: right;
5   }
6 }
```

- **Loops:**

With Sass you can create loops of style blocks, this feature helps to save code when you have similar *id's* or *classes*. Here is an example:

¹¹<https://en.wikipedia.org/wiki/Haml>

```
1 $squareCount: 3
2 @for $i from 1 through $squareCount
3   #square-#{ $i }
4   background-color: red
5   width: 50px * $i
6   height: 120px / $i
```

- There are more Sass features such as *arguments*, *selector inheritance*, ... All of these features can be found on the Sass documentation web page¹².

2.13 Flexbox

"The *CSS3 Flexible Box*, or **Flexbox**, is a layout mode intended to accommodate different screen sizes and different display devices". Flexbox is very useful when you have to organize your application view, so for example, sticking a *footer* to the bottom of a page, designing a *navigation bar*, creating a custom grid, ... is much easier using Flexbox.

Related to the Flexbox concept, it allows to manage an element width and the height to improve its fitting in the available space on the display regardless of the device that is being used. This elements are shrunk to prevent overflow or expanded to fill remaining space.

2.13.1 Usage Examples

In order to use Flexbox styles, we have to apply the style "*display: flex*" in our container element. Let's see a few Flexbox usage examples.

- **flex-wrap:**

Defines if flexbox items appear on a single line or on multiple lines within a flexbox container.

```
1 flex-wrap: nowrap;
2 flex-wrap: wrap;
```

¹²http://sass-lang.com/documentation/file.SASS_REFERENCE.html



Figure 2.7: no-wrap example.




Figure 2.8: wrap example.

- **justify-content:**

Defines how flexbox items are aligned according to the main axis, within a flexbox container.

```
1 justify-content: flex-end;  
2 justify-content: center;
```



Figure 2.9: flex-end example.



Figure 2.10: center example.

Chapter 3

Development

3.1 SCRUM Methodology

SCRUM is a work methodology designed mainly for *software development*. The main philosophy of this methodology consists in subdividing the work into groups of smaller tasks, each group is called "*Sprint*".

"Scrum is an iterative and incremental agile software development framework for managing product development".

A key principle of Scrum is the dual recognition:

- Customers decision may change during the sprint development process (requirements volatility).
- There will be unpredictable challenges—for which a predictive or planned approach is not suited.

In the *SCRUM* framework we can find three main roles:

- **Product owner:** Ensures that the team delivers value to the business and represents both the product's stakeholders and the voice of the customer. The product owner manage the work process defining the product, adding stories to the backlog and prioritizing work.
- **Development team:** The team is the one that completes the tasks of a Sprint, building the product increments.




Figure 3.1: SCRUM Framework

- **SCRUM master**: Removes the impediments, allowing the team to deliver product goals. The SCRUM master filters all distracting influences from the development team.

On Figure 3.1 we can see a general SCRUM framework.

3.2 Sprint 1

3.2.1 Key Objectives

The main goals or tasks for this sprint are:

- Basic Elasticsearch interface which allows to visualize a simple metric. The data must come from Elasticsearch through an API request.
- Include more aggregations options and Index changing functionality.

3.2.2 Implementing a simple metric request

We are at the beginning of this project, the first thing we are going to do is to connect our Angular project to Elasticsearch. This can be achieved by installing the Elasticsearch library¹

¹<https://github.com/elastic/elasticsearch-js>

for Angular. This library will allow us to make requests to Elasticsearch through its javascript API.

We need an Elasticsearch client instance, this instance will give us the access to the Elasticsearch API. Elasticsearch, by default, it listens on the '9200' port, so we'll need to specify it too.

```
1 export class Elasticsearch {
2   public clientElasticsearch: Client;
3   constructor() {
4     this.clientElasticsearch = new Client({
5       host: 'localhost:9200',
6       log: 'trace' // This is for debug purposes
7     });
8   }
9   ...
10 }
```

Listing 3.1: Client Instance

This Elasticsearch class is created as an Angular **service**. In Angular, services are usually used for fetching data from the outside, this is what we are trying to achieve.

The next thing we are going to do is to request a simple "count" from Elasticsearch. In order to get this, we need to specify an Elasticsearch **index**.

```
1 ...
2 public count(index): PromiseLike<number> {
3   return this.clientElasticsearch.count({
4     index: index
5   }).then(
6     response => response.count,
7     this.handleError
8   );
9 }
10 ...
```

Now we just need to display the response.

```

1 // Html
2 <button (click)="displayData()">Display</button>
3 Count: <span>{{data}}</span>
4
5 // Typescript
6 ...
7 data: number = 0;
8 ...
9 displayData(): void {
10   this.elasticsearch.count('bank')
11   .then(count => this.data = count);
12 }
13 ...

```

3.2.3 Adding aggregations and dynamic index

First, in order to fetch the available indexes we are going to use the "cat" request, supported by the javascript API.

```

1 ...
2 public getIndices(): PromiseLike<string[]>{
3   return this.clientElasticsearch.cat.indices({
4     format: 'json'
5   })
6 ...

```

This method returns a JSON object, as we have specified in the "format" field. So we just need to parse this JSON response in order to build our indexes array. The next step is to retrieve all "number" fields for each index, since we are not going to implement aggregations that need another field type yet.

```

1 ...
2 public getIndexNumFields(index): PromiseLike<string[]> {
3   return this.map(index).then(function(response) {

```

```
4 ...
```

The map method returns the index mappings, which we need to parse to build our "number fields" array.

The **PromiseLike** class is very useful because allows us to wait until the request is finished, in order to execute the appropriate callback function and manage the retrieved data asynchronously.

For now, we are going to include functionality for aggregations that works with fields of type "number" only. To achieve this we are going to use the "search" request provided by the Elasticsearch javascript API. This request returns a JSON object which we need to parse in a different way depending on the aggregation we are requesting, in order to get a displayable result.

```
1 ...
2 // avg, sum, min, max, median, std_deviation, unique_count
3 public numFieldCalculation(index: string, aggs: any): PromiseLike<
    any>{
4     return this.clientElasticsearch.search({
5         "index": index,
6         "body": {"size": 0, "aggs": aggs}
7     })
8 ...
```

The final stage view at the end of this sprint is shown on Figure 3.2.

For a better understanding a general architecture for this sprint is shown on Figure 3.3.

3.3 Sprint 2

3.3.1 Key Objectives

The main goals or tasks for this sprint are:

- Finish metrics functionality implementation.
- Implement Data Table visualization functionality.

Elasticsearch Dashboard Interface

Index:

bank Metric

Metrics:

Aggregation: Min age

Calculate

Result: [20]

Figure 3.2: Final stage view - Sprint 1




Figure 3.3: Sprint 1 architecture.




Figure 3.4: Sprint 2 architecture - Step 1.

- Allow to load and save visualizations.

3.3.2 Finishing metrics

Following the same logic as we did with the previous aggregations, we implement 'Percentiles', 'Percentile Ranks' and 'Top Hit' aggregations. The complexity of this aggregations is a little bit higher because these aggregations need more data in order to perform the request.

For this reason, we are going to have individual components for each one of these aggregations and a general *metrics component* for the other aggregations since they share the main calculation logic.

The architecture on Figure 3.4 shows how it remains the general structure.

3.3.3 Implementing "Data Table" feature

In relation with the "Data Table" visualization implementation we followed the same structure as with the "Metric" visualization. The main difference here is the way we structure the data in order to display it in a table.

Another important difference with the "Metric" visualization is the introduction of Elasticsearch **buckets**. Because of the way "Data Table" visualizations work, Elasticsearch returns the requested data in groups of results, depending on the "bucket aggregation" that has been used. For this project we are going to use two different bucket aggregations between all the possible aggregations:

- Histogram
- Range

Here the complexity of the requests grows significantly. Because of this complexity, we are going to use a javascript library called "**bodybuilder**"². As we could understand by its name, this library helps us to build the request bodies. For example if we want to make a simple count over an index, and retrieve the data as "histogram buckets" with an interval:

```
1 // Builder process
2 bodybuilder().aggregation('histogram', null, 'bucket_1', {
3     field: 'age',
4     interval: 5
5 }).build()
6
7 // Result
8 {
9     "aggs": {
10         "bucket_1": {
11             "histogram": {
12                 "field": "age",
13                 "interval": 5
14             }
15         }
16     }
17 }
```

3.3.4 Loading and saving visualizations

Right now we are able to create two types of visualizations, "Metric" and "Data Table", but we are still not able to store them in Elasticsearch neither loading saved visualizations.

To achieve this features we have to create a new Elasticsearch index which will store all visualizations data. The name of this index we'll be "sakura".

²<https://github.com/danpaz/bodybuilder>

Now we need a *type* which will define what data represents our visualizations.

Our index mapping looks like this:

```
1 visualizations: {
2   properties: {
3     kibanaSavedObjectMeta: {
4       properties: {
5         searchSourceJSON: {
6           type: "text",
7           fields: {
8             keyword: {
9               type: "keyword",
10              ignore_above: 256
11            }
12          }
13        }
14      }
15    },
16    title: { type: "text" },
17    visState: { type: "text" }
18  }
19 }
```

Each field stores data necessary in order to load a visualization:

- **kibanaSavedObjectMeta**: data related with the visualization index.
- **title**: visualization's title.
- **visState**: data related with the aggregations.

Once we've created the visualization object, the saving process consist of 2 steps:

- Check if there is already a visualization on Elasticsearch with the same id (title).
- If there is already a visualization, update it, otherwise create a new one.

In Elasticsearch we use the "search" action in order to look for a document:

```
1 this.cli.search({
2     "index": '.sakura',
3     "type": type,
4     "body": body
5 })
```

In this case the type is "visualization" and the body is build in the following way:

```
1 bodybuilder().filter('term', '_id', title).build();
2 // Returns:
3 {
4     "query": {
5         "bool": {
6             "filter": {
7                 "term": { "_id": title }
8             }
9         }
10    }
11 }
```

To create a document we use the "create" action:

```
1 this.cli.create({
2     index: index,
3     type: type,
4     id: id,
5     body: body
6 })
```

And we use "update" to modify an existing document:

```
1 this.cli.update({
2     index: '.sakura',
3     type: type,
4     id: id,
5     body: { doc: doc }
```





Figure 3.5: Sprint 2 final structure.

```
6 } )
```

The general structure at the end of this sprint is shown on Figure 3.5.

3.4 Sprint 3

3.5 Sprint 4

3.6 General Structure

Si tu proyecto es un software, siempre es bueno poner la arquitectura (que es cómo se estructura tu programa a “vista de pájaro”).

Por ejemplo, puedes verlo en la figura 3.6.

Si utilizas una base de datos, no te olvides de incluir también un diagrama de entidad-relación.




Figure 3.6: Estructura del parser básico

Chapter 4

Resultados

En este capítulo se incluyen los resultados de tu trabajo fin de grado.

Si es una herramienta de análisis lo que has realizado, aquí puedes poner ejemplos de haberla utilizado para que se vea su utilidad.

Chapter 5

Conclusiones

5.1 Consecución de objetivos

Esta sección es la sección espejo de las dos primeras del capítulo de objetivos, donde se planteaba el objetivo general y se elaboraban los específicos.

Es aquí donde hay que debatir qué se ha conseguido y qué no. Cuando algo no se ha conseguido, se ha de justificar, en términos de qué problemas se han encontrado y qué medidas se han tomado para mitigar esos problemas.

5.2 Aplicación de lo aprendido

Aquí viene lo que has aprendido durante el Grado/Máster y que has aplicado en el TFG/TFM.

Una buena idea es poner las asignaturas más relacionadas y comentar en un párrafo los conocimientos y habilidades puestos en práctica.

1. a

2. b

5.3 Lecciones aprendidas

Aquí viene lo que has aprendido en el Trabajo Fin de Grado/Máster.

1. a

2. b

5.4 Trabajos futuros

Ningún software se termina, así que aquí vienen ideas y funcionalidades que estaría bien tener implementadas en el futuro.

Es un apartado que sirve para dar ideas de cara a futuros TFGs/TFM.

Apéndice A

Manual de usuario

Bibliography