

 ANA We make your world easier.	WORK INSTRUCTION		Rev	Date	Description
	Mount and land the inverter bracket		A	09/29/2026	Layout review

Purpose / scope Mount the inverter bracket to the frame rail and land the DC leads, ready for the enclosure fit-up in FA-INV-020.

Safety / PPE Pinch hazard at the fixture. Cut-resistant gloves and safety glasses required. DC bus must be confirmed de-energised and locked out before the leads are landed.

BOM / materials			Tools & equipment	
Part number	Description	Qty	Kit cart	
KIT-INV-01	Material kit	1	Lift table	
BRK-1001	Inverter mounting bracket	1	10mm socket	
FAS-M8-45	M8 x 45 flange bolt	4	Torque wrench	
CLP-P25	P-clip, 25 mm	2		

Image / reference view	1 Stage the bracket Retrieve bracket BRK-1001 from kit KIT-INV-01 and stage it on the fixture. Tools Kit cart
	2 Seat the bracket Lower the bracket onto the frame rail so the locating pin passes through the forward hole. Tools Lift table



WORK INSTRUCTION

Mount and land the inverter bracket

Rev	Date	Description
A	09/29/2026	Layout review

3 Start the fasteners

Hand-start all four M8 flange bolts before running any of them down.

Image / reference view

Tools

10mm socket

4 Torque the fasteners

Torque the four M8 bolts to 45 Nm in a diagonal cross pattern, twice.

Image / reference view

Tools

Torque wrench · 10mm socket

5 Route the DC harness

Route the DC harness through the bracket saddle and secure it with two P-clips.

Image / reference view

Tools

Nut driver