



Scale 1:100 @ A2 | Plan cut at +4237

Structural openings in the ICF; sill and head above GF FFL

- 1. ICF: Nudura G® XR35, 101.6 EPS + 152.4 C face + 101.6 EPS = 355.6; 6" Std, 66.7 EPS + 152.4 C face + 66.7 EPS = 285.8. Dimensions to the ICF faces.
- 2. Levels above GG FFL (168.748 AOD). Sill / head = structural opening in the ICF.
- 3. ICF per the coordinated model: 6in XR35 (152 mm core, 355.6 mm) external walls, 6in Std (286 mm) internal ICF walls; concrete grade, aggregate, fibre dosage and dowel bars per the Tier Consult specification (to be confirmed).
- 4. Lintel (L-n) and steel (B-n, C-1) marks from Tier Consult 078-TCE-DEN-XX-DR-S-026.210 rev., which takes precedence. Red EQ tags = queries to the engineer on UKPCS-003-EQ-01 (click to open).
- 5. Masonry walls shown for context.
- 6. Steel over the ICF: see UKPCS-003-GS-02.



FF ICF GENERAL ARRANGEMENT

ICF walls, openings and setting out

STATUS	DRAWING No.	REV
--------	-------------	-----

FOR APPROVAL

UKPCS-003-GA-02

P01