



CO2-010-D

# CO2 DUCT

## *Carbon Dioxide Sensor*

The CO2-010-D monitors carbon dioxide from 0 to 2000 ppm for duct mount applications. They feature analog outputs (see order grid for output options) with a patented ABC Logic™ self-calibration system. The concentration of carbon dioxide is measured using a Single Beam, Non-Dispersive Infrared (NDIR) Absorption sensing method. They will indicate one of five approximate ppm levels. These units should not be used in environments such as greenhouses, wineries, breweries. They should also be avoided in areas where industrial sources of carbon dioxide are present or in applications where the space is left unoccupied for less than 4 hours a day.

The CO2-010-D is covered by an industry-leading Two (2) year warranty, which can be found on our OEM's web site, which is [www.workaci.com](http://www.workaci.com).

## SPECIFICATIONS

Supply Voltage	18 to 30 VAC RMS, 50/60 Hz or 18 to 42 VDC
Power Consumption (Duct)	Typical, 1.65Ω Peak, 0.65Ω Average @ 42 VDC
Measurement Range	0 to 2000 ppm
CO2 Output Signal (Duct)	0 to 10 VDC (100Ω output impedance)
Accuracy (Duct)	+/- 40 ppm +3% of Reading @ 72°F (22°C)
Non-Linearity	< 1% of FS @ 72°F (22°C)
Stability	< 2% FS over life of sensor (15 Years Typical)
Temperature Dependence	0.2% of Full Scale per °C
Pressure Dependence	0.135% of reading per mm Hg
Response Time (Duct)	3 minutes typical for 90% Step change
Operating Temp/ RH Range	32 to 122°F (0 to 50°C)/0 to 95%, non-condensing
Sensor Coverage Area	7,500 sq. ft. maximum
Sensing Technology	Single beam infrared sensing technology (NDIR)
Product Dimensions (Duct)	(L) 3.05" (W) 3.05" (H) 5.70"

## ORDERING

Select CO2-010-D as a Gas Type (A).

**A** Gas Type

☐ **CO2-010-D** (Duct) (0 to 10 VDC)

## BUILD PART NUMBER

After completing (A) from the above table, fill in the Part Number Table below. An example part number is offered.

**A**

EXAMPLE: CO2-010-D