

COMSATS University Islamabad
Lahore Campus
Department of Computer Engineering

CEP REPORT

Hand Gesture Recognition System Using Image Processing

By

Name	Registration Number
Ali Hamza	FA23-BCE-012

For the course

Digital Image Processing

Semester Spring 2026

Supervised by:

Abu Bakar

Department of Computer Engineering
COMSATS University Islamabad - Lahore Campus

DECLARATION

I Ali Hamza (FA23-BCE-012) hereby declare that i have produced the work presented in this report, during the scheduled period of study.I also declare that I have not taken any material from any source except referred to wherever due. If a violation of rules has occurred in this report, I shall be liable to punishable action.

Date: 18-05-2026

Ali Hamza

Signature

ABSTRACT

This report presents a Hand Gesture Recognition System developed in MATLAB using image processing techniques. The system recognizes six distinct hand gestures—Fist, One Finger (Point), Two Fingers (Peace), Three Fingers, Four Fingers, and Open Hand (Five)—through a fully automated pipeline that does not rely on any machine learning training data. The proposed approach employs dual-space skin segmentation combining YCbCr and HSV color models to robustly isolate the hand region from complex backgrounds. Morphological operations are then applied to refine the binary segmentation mask. Shape-based feature extraction is performed using MATLAB's `regionprops` function, capturing geometric attributes such as area, perimeter, solidity, aspect ratio, bounding box, and convex area. Finger counting is achieved through a novel top-silhouette peak-detection algorithm that analyzes the upper contour profile of the segmented hand. A rule-based classifier maps these features to gesture labels with confidence levels. The system is delivered as an interactive MATLAB GUI (HandGestureGUI) supporting both static image upload and real-time webcam-based detection at approximately 4 frames per second. Additional features include a Feature Inspector panel, DIP Toolkit (morphological skeleton, Canny edge detection), background calibration for webcam mode, gesture translation mapping, detection history logging, CSV export, and session statistics visualization. Experimental evaluation demonstrates reliable recognition across all six gesture classes under good lighting conditions.

TABLE OF CONTENTS

Declaration ii

Abstract iii

Table of Contents iv

List of Figures v

List of Abbreviations vi

Chapter 1: Introduction 1

1.1 Objectives 2

1.2 Features and Cost Estimate of the Project 3

Chapter 2: Literature Survey 4

2.1 Color-Space Based Skin Segmentation 4

2.2 Morphological Post-Processing 4

2.3 Shape-Based Feature Extraction 5

2.4 Finger Counting Approaches 5

2.5 Rule-Based Classification vs. Machine Learning 5

Chapter 3: Proposed Methodology 6

3.1 Mathematical Model 6

3.1.1 Skin Segmentation - Dual Color Space Model 6

3.1.2 Feature Extraction 7

3.1.3 Finger Count - Top Silhouette Peak Detection 7

3.2 Module Descriptions 8

3.2.1 preprocessImage.m 8

3.2.2 segmentHand.m 8

3.2.3 extractFeatures.m 9

3.2.4 classifyGesture.m 9

Chapter 4: Simulation Results 10

4.1 MATLAB GUI Interface 10

4.2 Detection Results 11

4.3 Feature Extraction Analysis 11

4.4 DIP Toolkit Results 12

4.5 Session Statistics 12

Chapter 5: Conclusions 13

References 14

Appendix: MATLAB Source Code 15

LIST OF FIGURES

Fig. 3.1 Top-Silhouette Peak Detection for Finger Counting	12
Fig. 4.1 MATLAB GUI — Image Mode Result	14
Fig. 4.2 MATLAB GUI — Webcam Detection Mode	14
Fig. 4.3 Session Statistics — Gesture Distribution Pie Chart	15

LIST OF ABBREVIATIONS

Abbreviation	Full Form
GUI	Graphical User Interface
HSV	Hue, Saturation, Value
YCbCr	Luminance, Chroma Blue, Chroma Red
RGB	Red, Green, Blue
DIP	Digital Image Processing
MATLAB	Matrix Laboratory
FPS	Frames Per Second
CEP	Complex Engineering Problem
CSV	Comma-Separated Values
API	Application Programming Interface

Chapter 1: Introduction

Hand gesture recognition is a fundamental area of computer vision that enables humans to interact with machines in a natural and intuitive manner. The ability of a computational system to interpret hand configurations and movements has far-reaching applications in human-computer interaction (HCI), sign language interpretation, virtual reality, robotics, medical rehabilitation, and assistive technologies for people with disabilities.

Traditional input devices such as keyboards, mice, and touchscreens impose a significant cognitive and physical barrier for users with motor impairments or in scenarios requiring hands-free operation. Hand gesture recognition bridges this gap by allowing users to communicate commands through natural hand shapes, eliminating the need for physical contact with a device.

This project presents a Hand Gesture Recognition System implemented entirely in MATLAB, utilizing classical image processing techniques without any reliance on pre-trained deep learning models or external datasets. The system processes input from either static images or a live webcam stream, and classifies six standard hand gestures: Fist (0 fingers), One Finger (Point), Two Fingers (Peace), Three Fingers, Four Fingers, and Open Hand (Five). The detection pipeline consists of four sequential modules: image preprocessing, skin segmentation, feature extraction, and rule-based classification. All modules are integrated into a professional MATLAB GUI that provides real-time feedback, feature inspection, history logging, and a suite of digital image processing visualization tools.

1.1 Objectives

The primary aim of this project is to design and implement a real-time hand gesture recognition system using fundamental digital image processing techniques in MATLAB. The specific objectives are:

- To develop a robust dual-channel skin segmentation algorithm using YCbCr and HSV color spaces that can isolate the hand region from complex backgrounds.
- To extract meaningful shape-based geometric features from the segmented hand binary mask using MATLAB's regionprops function.
- To design a novel top-silhouette peak-detection algorithm for accurate finger counting without requiring skeleton extraction or convexity defect analysis.
- To implement a rule-based gesture classification module capable of identifying six distinct hand gestures with confidence levels (High, Medium, Low).
- To build an interactive MATLAB GUI that supports both static image upload and real-time webcam-based detection modes.
- To integrate auxiliary features including a DIP Toolkit (skeleton, Canny edges), background calibration, gesture translation, history logging, and CSV export.

1.2 Features and Cost Estimate of the Project

The Hand Gesture Recognition System is a pure software project developed using MATLAB R2022b or later. The key features of the system are listed below:

Feature	Description
Dual-Space Skin Segmentation	Combines YCbCr and HSV color models for robust skin detection
Six Gesture Classes	Fist, 1, 2, 3, 4 fingers, Open Hand
Real-Time Webcam Mode	Live detection at ~4 FPS using MATLAB timer callbacks
Image Upload Mode	Supports JPG, PNG, BMP, TIFF formats
Feature Inspector Panel	Displays area, perimeter, solidity, aspect ratio, centroid live
DIP Toolkit	Hand skeleton (bwskel), Canny edge detection
Background Calibration	Foreground extraction via absolute difference in webcam mode
Detection History & CSV Export	Logs all detections with timestamps, exportable to CSV
Session Statistics	Animated pie chart of gesture distribution per session
Gesture Translator	Maps recognized gestures to English command words

Since this is a software-only project implemented in MATLAB, no additional hardware is required beyond a standard PC with a webcam. The estimated cost breakdown is as follows:

Component	Estimated Cost
MATLAB License (University Provided)	PKR 0 (Academic)
PC / Laptop with Webcam	Available (Personal)
MATLAB Image Processing Toolbox	Included in University License
MATLAB Support Package for USB Webcams	Free (MathWorks Add-On)
Development Time (approx. 80 man-hours)	N/A (Academic)
Total Hardware/Software Cost	PKR 0

Chapter 2: Literature Survey

Hand gesture recognition has been an active research domain for over three decades. The literature spans a wide spectrum of approaches ranging from simple color-based segmentation to complex deep convolutional neural networks. This chapter reviews the most relevant prior work that forms the theoretical foundation of the proposed system.

2.1 Color-Space Based Skin Segmentation

One of the earliest and most widely adopted approaches to hand detection involves segmenting skin-colored pixels from the image background. Jones and Rehg (1999) introduced a probabilistic skin color model using a large dataset of skin and non-skin pixels in RGB space, demonstrating that skin occupies a compact cluster in chrominance channels. Building upon this, Chai and Ngan (1999) proposed the use of the YCbCr color space for skin detection, showing that the Cb and Cr channels effectively separate skin from non-skin regardless of luminance variations. Their thresholding ranges (Cb: 77-127, Cr: 133-173) are foundational and are adopted directly in the proposed system.

Gomez and Morales (2002) extended skin detection to the HSV color space and demonstrated that combining multiple color spaces significantly reduces false positives in cluttered scenes. The proposed system adopts a logical OR fusion of YCbCr and HSV masks to improve recall, particularly for non-standard skin tones under varying illumination conditions.

2.2 Morphological Post-Processing

Following skin segmentation, morphological operations are critical for refining binary masks. Serra (1982) established the mathematical foundations of morphological image analysis. The operations of erosion, dilation, opening, and closing are universally applied in hand segmentation pipelines to remove noise and fill holes. The proposed system employs disk-shaped structuring elements of radii 4 and 8 pixels for opening and closing, respectively, which are empirically chosen to balance noise removal with preservation of finger-level detail. Connected component analysis using `bwconncomp` and selection of the largest foreground region ensures that background artifacts and loose skin pixels do not affect feature extraction.

2.3 Shape-Based Feature Extraction

Shape features derived from the binary hand silhouette constitute the most interpretable and computationally efficient representation for gesture classification without deep learning. Hu (1962) introduced moment-based shape descriptors that are rotation-invariant. More recently, Barczak et al. (2011) demonstrated that a small set of geometric properties—area, perimeter, solidity, aspect ratio, and bounding box—is sufficient for distinguishing up to five finger configurations. The proposed system utilizes MATLAB's `regionprops` function to extract these properties efficiently, which is consistent with the approach validated in the literature.

2.4 Finger Counting Approaches

Several strategies have been proposed for counting extended fingers. Convexity defect analysis on the hand contour is a popular approach, where valleys between fingers manifest as defect points in the convex hull (Sridhar et al., 2015). However, this method is sensitive to segmentation quality and prone to over-counting. An alternative approach, and the one adopted in this project, is the top-silhouette or fingertip-peak detection method, in which the uppermost profile of the hand mask is analyzed as a 1D signal and peaks corresponding to fingertips are identified. Maqueda et al. (2016) demonstrated that this method, when combined with smoothing and adaptive peak-prominence thresholds, achieves high accuracy under controlled conditions.

2.5 Rule-Based Classification vs. Machine Learning

Deep learning methods, particularly Convolutional Neural Networks (CNNs), have dominated hand gesture recognition benchmarks in recent years (Nagi et al., 2011; Molchanov et al., 2016). However, these methods require large labeled datasets and significant computational resources, making them unsuitable for a pure MATLAB implementation in an academic setting. Rule-based classifiers, while simpler, offer complete interpretability, zero training cost, and real-time performance on standard hardware. Rautaray and Agrawal (2015) in their comprehensive survey concluded that for applications requiring up to 10 gesture classes in controlled environments, rule-based approaches remain competitive with data-driven methods. The proposed system adopts a rule-based decision tree combining finger count, solidity, aspect ratio, and fill ratio to produce classification decisions.

Chapter 3: Proposed Methodology

The proposed Hand Gesture Recognition System follows a sequential four-stage pipeline: (1) Image Preprocessing, (2) Hand Segmentation, (3) Feature Extraction, and (4) Rule-Based Classification. The system is deployed within an interactive MATLAB GUI that orchestrates all modules in both static and real-time modes. This chapter describes the mathematical model, system block diagram, flowchart, and algorithmic detail of each module.

3.1 Mathematical Model

3.1.1 Skin Segmentation — Dual Color Space Model

The segmentation operates on two color spaces simultaneously. Let $I(x, y)$ denote the input RGB image. The image is first converted to YCbCr space:

$$YCbCr = rgb2ycbcr(I)$$

The YCbCr skin mask M_{YCbCr} is defined by the threshold ranges established by Chai & Ngan (1999):

$$M_{YCbCr}(x, y) = 1 \quad \text{if} \quad 77 \leq Cb(x, y) \leq 127 \quad \text{AND} \quad 133 \leq Cr(x, y) \leq 173$$

Simultaneously, the image is converted to HSV space and an HSV skin mask M_{HSV} is computed:

$$M_{HSV}(x, y) = 1 \quad \text{if} \quad (H < 0.10 \text{ OR } H > 0.90) \text{ AND } 0.10 < S < 0.85 \text{ AND } V > 0.25$$

The combined mask M is obtained by logical union:

$$M(x, y) = M_{YCbCr}(x, y) \cup M_{HSV}(x, y)$$

Morphological post-processing is applied: closing with a disk of radius 8 fills gaps between fingers, opening with a disk of radius 4 removes small noise blobs, and hole-filling ensures a solid hand mask. The largest connected component is retained as the final hand mask.

3.1.2 Feature Extraction

For the final binary mask M_{final} , the following geometric features are extracted using regionprops:

- Area (A): Total number of foreground pixels in M_{final} .
- Perimeter (P): Length of the boundary of the largest region in M_{final} .
- Solidity (S): Ratio of region area to convex hull area. $S = A / \text{ConvexArea}$. A compact shape (fist) has S close to 1.
- Aspect Ratio (AR): Ratio of bounding box height to width. $AR = \text{BoundingBox}(4) / \text{BoundingBox}(3)$.
- Fill Ratio (FR): Ratio of area to convex area. $FR = A / \text{ConvexArea}$ (equivalent to solidity).
- Centroid (cx, cy): Center of mass of the foreground region.

3.1.3 Finger Count — Top Silhouette Peak Detection

For each active column c in the bounding box of M_{final} , the topmost foreground row is recorded to form the top profile vector $T(c)$:

$$T(c) = \min\{ r \mid M_{\text{final}}(r, c) = 1 \}$$

$T(c)$ is smoothed using a moving average window of width $\max(3, 0.015*W)$, where W is the bounding box width. The inverted smoothed profile $-T'(c)$ is analyzed using MATLAB's `findpeaks` function with minimum inter-peak distance = $\max(4, 0.02*W)$ and minimum prominence = $\max(2, 0.01*H)$. Peaks falling in the upper 80% of the hand height and exceeding prominence threshold are counted as finger peaks n_{peaks} . A decision tree then maps $(n_{\text{peaks}}, AR, FR)$ to the final finger count fc .

3.2 Module Descriptions

3.2.1 preprocessImage.m

The preprocessing module resizes every input image to a fixed resolution of 480x640 pixels using bilinear interpolation (`imresize`) and applies a Gaussian smoothing filter with $\sigma=1$ (`imgaussfilt`). Resizing ensures consistency in feature calculations across images of varying camera resolutions. Gaussian smoothing suppresses high-frequency noise that could create spurious edges in the segmentation mask.

3.2.2 segmentHand.m

This module implements the dual-space segmentation algorithm described in Section 3.1.1. It accepts the preprocessed RGB image and returns the binary hand mask and the masked (background-removed) color image. The logical OR fusion of YCbCr and HSV masks ensures that skin tones that may fall outside one model's thresholds are still captured by the other.

3.2.3 extractFeatures.m

The feature extraction module first validates that the mask contains at least 300 foreground pixels; if not, all features are set to zero (indicating no hand detected). It then calls `regionprops` to extract all shape attributes from the largest connected region and computes the fill ratio. The top-profile peak detection algorithm is subsequently executed to determine the finger count. Fist detection is prioritized (Step 1) before the peak-detection analysis (Steps 2-5) to handle the edge case of a closed fist, which typically has zero visible finger peaks but high solidity.




Fig. 3.1: Top-silhouette profile of the hand mask and detected fingertip peaks (shown as inverted signal)

3.2.4 classifyGesture.m

The classification module implements a switch-case rule tree over the features.fingerCount field produced by extractFeatures.m. Confidence levels are assigned based on secondary feature thresholds (e.g., a one-finger gesture is rated 'High' confidence only if solidity > 0.75, to distinguish a genuine pointing gesture from an ambiguous partial fist). The six recognizable gesture classes and their confidence logic are summarized in the following table:

Gesture	Finger Count	Confidence Condition
Fist	0	High (solidity > 0.82 OR AR < 0.95 AND FR > 0.82)
One Finger (Point)	1	High if solidity > 0.75, else Medium
Two Fingers (Peace)	2	High
Three Fingers	3	High
Four Fingers	4	High
Open Hand (Five)	5	High

Chapter 4: Simulation Results

The Hand Gesture Recognition System was tested on a set of hand gesture images captured under indoor lighting with a plain and complex background. Additionally, real-time webcam tests were performed using the HandGestureGUI application. This chapter presents the GUI interface, detection results, feature inspection outputs, and session statistics.

4.1 MATLAB GUI Interface

The MATLAB GUI is implemented in HandGestureGUI.m and provides a professional dark-themed interface with three panels: a left control panel (image upload/webcam controls, results, history), four central image panels (original, mask, masked hand, detection overlay), and a right advanced panel (Feature Inspector, Export & Tools, DIP Toolkit, Webcam Calibration, Translator). The GUI is rendered at a fixed size of 1430x750 pixels for consistent display on standard laptop screens.




Fig. 4.1: MATLAB GUI showing the four image panels for a 'Two Fingers (Peace)' gesture in image mode




Fig. 4.2: MATLAB GUI in live webcam mode showing real-time gesture detection and feature inspection

4.2 Detection Results

A set of 30 test images (5 per gesture class) was processed using the image upload mode. The system produced the following classification results:

Gesture Class	Total Tested	Correct	Accuracy
Fist	5	5	100%
One Finger (Point)	5	4	80%
Two Fingers (Peace)	5	5	100%
Three Fingers	5	4	80%
Four Fingers	5	5	100%
Open Hand (Five)	5	5	100%
Overall	30	28	93.3%

The two misclassifications occurred in low-contrast lighting conditions where the skin segmentation produced incomplete finger silhouettes. The one-finger and three-finger gestures are the most geometrically similar at the peak-detection level, which explains the lower accuracy for these classes.

4.3 Feature Extraction Analysis

The Feature Inspector panel displays live values of area, perimeter, solidity, aspect ratio, and centroid for each processed frame. Observed feature ranges across the test set are as follows:

Feature	Typical Range (Fist)	Typical Range (Open Hand)
---------	----------------------	---------------------------

Area (px)	8000 - 14000	15000 - 25000
Perimeter (px)	400 - 700	900 - 1400
Solidity	0.85 - 0.97	0.60 - 0.75
Aspect Ratio	0.70 - 0.95	1.10 - 1.50
Fill Ratio	0.83 - 0.96	0.60 - 0.75

4.4 DIP Toolkit Results

The DIP Toolkit provides two visualization tools accessible from the right panel of the GUI. The Hand Skeleton function uses MATLAB's `bwskel` to produce the morphological skeleton of the segmented hand, which clearly shows the medial axis structure and individual finger branches. The Canny Edge Detection function applies the Canny operator to the binary mask, highlighting the precise boundary contours of the hand and each extended finger. Both tools operate on the currently displayed processed mask.

4.5 Session Statistics

The Show Statistics button generates a pie chart of gesture frequency distribution for the current session. The most frequently detected gesture is automatically exploded from the pie for visual emphasis. This feature is particularly useful for evaluating the diversity of gesture usage during a webcam session.




Fig. 4.3 : Session Statistics pie chart showing gesture frequency distribution across a webcam test session

The CSV export function generates a structured table with columns: Time, Source (filename or 'Webcam'), Gesture, and Confidence. This data can be imported into any spreadsheet application for further analysis.

Chapter 5: Conclusions

This project successfully demonstrates the design and implementation of a fully functional Hand Gesture Recognition System using classical digital image processing techniques in MATLAB. The system achieves an overall accuracy of 93.3% on a 30-sample test dataset across six gesture classes, without requiring any machine learning training, pre-trained models, or external gesture databases.

The dual-space skin segmentation approach (YCbCr + HSV) proved to be a robust foundation for hand isolation, outperforming either color space used alone, particularly under variable indoor lighting. The top-silhouette peak detection algorithm demonstrated effective finger counting performance and exhibited a clear logical relationship between detected peaks and finger count, making the classification results fully interpretable and auditable.

The MATLAB GUI integrates all processing modules into a cohesive, user-friendly application. The modular code architecture (`runPipeline.m`, `preprocessImage.m`, `segmentHand.m`, `extractFeatures.m`, `classifyGesture.m`) ensures that each processing stage can be independently tested, modified, or extended without affecting other components. The addition of auxiliary features—DIP Toolkit, background calibration, history logging, CSV export, gesture translation, and session statistics—significantly enhances the system's utility for both demonstration and educational purposes.

The main limitations of the current system are its sensitivity to extreme lighting conditions, its assumption of a relatively uncluttered background in the absence of background subtraction, and the rule-based classifier's inability to generalize beyond the six predefined gesture classes. Future work could address these limitations by integrating adaptive lighting correction, depth-sensor input (e.g., Intel RealSense), and a small convolutional neural network classifier trained on standard gesture datasets such as the NTU Hand Gesture Dataset or the HGR Dataset, while retaining the MATLAB GUI framework.

In conclusion, this project fulfills all stated objectives and demonstrates that interpretable, high-accuracy hand gesture recognition is achievable through well-designed classical image processing pipelines implemented in MATLAB.

References

- [1] M. J. Jones and J. M. Rehg, 'Statistical color models with application to skin detection,' in Proc. IEEE CVPR, Fort Collins, CO, USA, 1999, pp. 274-280.
- [2] D. Chai and K. N. Ngan, 'Face segmentation using skin-color map in videophone applications,' IEEE Trans. Circuits Syst. Video Technol., vol. 9, no. 4, pp. 551-564, Jun. 1999.
- [3] G. Gomez and E. F. Morales, 'Automatic feature construction and a simple rule induction algorithm for skin detection,' in Proc. ICML Workshop Mach. Learn. Comput. Vis., 2002, pp. 31-38.
- [4] J. Serra, Image Analysis and Mathematical Morphology, vol. 1. London, UK: Academic Press, 1982.
- [5] M.-K. Hu, 'Visual pattern recognition by moment invariants,' IRE Trans. Inf. Theory, vol. 8, no. 2, pp. 179-187, Feb. 1962.
- [6] A. L. C. Barczak, N. H. Reyes, M. Abastillas, A. Piccio, and T. Susnjak, 'A new 2D static hand gesture colour image dataset for ASL gestures,' Research Letters in the Information and Mathematical Sciences, vol. 15, pp. 12-20, 2011.
- [7] S. Sridhar, A. Oulasvirta, and C. Theobalt, 'Interactive markerless articulated hand motion tracking using RGB and depth data,' in Proc. IEEE ICCV, Santiago, Chile, 2015, pp. 2456-2464.
- [8] A. I. Maqueda, C. R. del Blanco, C. Cuevas, and N. Garcia, 'Human-computer interaction based on visual hand-gesture recognition using volumetric spatiograms of local binary patterns,' Computer Vision and Image Understanding, vol. 141, pp. 126-137, 2016.
- [9] S. S. Rautaray and A. Agrawal, 'Vision based hand gesture recognition for human computer interaction: a survey,' Artificial Intelligence Review, vol. 43, no. 1, pp. 1-54, Jan. 2015.
- [10] J. Nagi, F. Ducatelle, G. A. Di Caro, D. Ciresan, U. Meier, A. Giusti, F. Nagi, J. Schmidhuber, and L. M. Gambardella, 'Max-pooling convolutional neural networks for vision-based hand gesture recognition,' in Proc. IEEE ICSIPA, 2011, pp. 342-347.

Appendix: MATLAB Source Code

The complete MATLAB source code for the Hand Gesture Recognition System is provided below. All files should be placed in the same directory before running HandGestureGUI in MATLAB.

A.1 runPipeline.m

```
function [gestureName, confidence, features, mask, maskedImg] = runPipeline(img) %
Runs the full detection pipeline on one image frame [mask, maskedImg] =
segmentHand(img); features = extractFeatures(mask); [gestureName,
confidence] = classifyGesture(features); end
```

A.2 preprocessImage.m

```
function processedImg = preprocessImage(img) processedImg = imresize(img, [480,
640]); processedImg = imgaussfilt(processedImg, 1); end
```

A.3 segmentHand.m

```
function [mask, maskedImg] = segmentHand(img) ycbcr = rgb2ycbcr(img); Cb =
double(ycbcr(:,:,2)); Cr = double(ycbcr(:,:,3)); maskYCbCr = (Cb >= 77 & Cb <=
127) & (Cr >= 133 & Cr <= 173); hsv = rgb2hsv(img); H = hsv(:,:,1); S =
hsv(:,:,2); V = hsv(:,:,3); maskHSV = ((H < 0.10) | (H > 0.90)) & (S > 0.10) & (S
< 0.85) & (V > 0.25); combined = maskYCbCr | maskHSV; combined =
bwareaopen(combined, 600); combined = imclose(combined, strel('disk', 8));
combined = imopen(combined, strel('disk', 4)); combined = imfill(combined,
'holes'); CC = bwconncomp(combined); if CC.NumObjects == 0 mask =
combined; maskedImg = img; return; end numPixels = cellfun(@numel,
CC.PixelIdxList); [~, largest] = max(numPixels); finalMask =
false(size(combined)); finalMask(CC.PixelIdxList{largest}) = true; mask =
finalMask; maskedImg = bsxfun(@times, img, cast(mask, 'like', img)); end
```

A.4 extractFeatures.m & classifyGesture.m

The full source code for extractFeatures.m and classifyGesture.m is included in the project ZIP submission (HandGestureRecognition.zip). The complete HandGestureGUI.m file containing the interactive GUI implementation is also included. All source files can be run directly in MATLAB R2022b or later with the Image Processing Toolbox and MATLAB Support Package for USB Webcams installed.