



Experiment - 9

Student Name: Shivam Kumar Tiwari

UID: 23BCS12755

Branch: BE-CSE

Section/Group: KRG-2B

Semester: 5th

Date of Performance: 13/10/25

Subject Name: Design and Analysis of Algorithms

Subject Code: 23CSH-301

1. Aim: Develop a program and analyze complexity to find all occurrences of a pattern P in a given string S.

2. Objective : Analyze to find all occurrences of a pattern P in a given string S

3. Input/Apparatus Used: String is taken as input in order to find pattern from it.

4. Procedure:

1. We will first create the LPS array.
2. Initialize two variables - „strIdx“ and „patIdx“ to iterate over the string and the pattern, respectively.
3. If „pat[patIdx]“ equals „str[strIdx]“, we will increment both the indexes.
4. When „patIdx“ equals the length of the pattern, this means that the pattern is found in the string. Therefore we print the index and set „patIdx“ = LPS[patIdx-1].
5. If „pat[patIdx]“ is not equal to „str[strIdx]“, we update the patIdx with the last index that matches with „str[strIdx]“ using the LPS array.

Doing this, we will find all occurrences of the pattern in the string.

5. Algorithm:

String manipulation/matching algorithms: Rabin Karp algorithm

Naïve brute-force algorithm:

Naïve pattern searching is the simplest method among other pattern searching algorithms. It checks for all character of the main string to the pattern. This algorithm is helpful for smaller texts. It does not need any pre-processing phases. We can find substring by checking once for the string. It also does not occupy extra space to perform the operation.

NAIVE-STRING-MATCHER(T, P)

```
1   $n = T.length$ 
2   $m = P.length$ 
3  for  $s = 0$  to  $n - m$ 
4      if  $P[1..m] == T[s + 1..s + m]$ 
5          print "Pattern occurs with shift"  $s$ 
```

The Rabin-Karp-Algorithm

The Rabin-Karp string matching algorithm calculates a hash value for the pattern, as well as for each M-character subsequences of text to be compared. If the hash values are unequal, the algorithm will determine the hash value for next M-character sequence. If the hash values are equal, the algorithm will analyze the pattern and the M-character sequence. In this way, there is only one comparison per text subsequence, and character matching is only required when the hash values match.

RABIN-KARP-MATCHER(T, P, d, q)

```
1   $n = T.length$ 
2   $m = P.length$ 
3   $h = d^{m-1} \bmod q$ 
4   $p = 0$ 
5   $t_0 = 0$ 
6  for  $i = 1$  to  $m$  // preprocessing
7       $p = (dp + P[i]) \bmod q$ 
8       $t_0 = (dt_0 + T[i]) \bmod q$ 
9  for  $s = 0$  to  $n - m$  // matching
10     if  $p == t_s$ 
11         if  $P[1..m] == T[s + 1..s + m]$ 
12             print "Pattern occurs with shift"  $s$ 
13     if  $s < n - m$ 
14          $t_{s+1} = (d(t_s - T[s + 1])h + T[s + m + 1]) \bmod q$ 
```



DEPARTMENT OF

COMPUTER SCIENCE & ENGINEERING

Discover. Learn. Empower.

Example: For string matching, working module $q = 11$, how many spurious hits does the Rabin-Karp matcher encounters in Text $T = 31415926535.....$

1. $T = 31415926535.....$
2. $P = 26$
3. Here $T.Length = 11$ so $Q = 11$
4. And $P \bmod Q = 26 \bmod 11 = 4$
5. Now find the exact match of $P \bmod Q...$
6. **Code and Output :**

```
#include
```

```
<iostream>
```

```
#include <string>
```

```
using namespace
```

```
std;
```

```
void rabinKarp(string text, string pattern, int
```

```
q) { int d = 256; // number of characters in
```

```
input alphabet int n = text.length(); int m =
```

```
pattern.length(); int p = 0; // hash value for
```

```
pattern int t = 0; // hash value for text int h
```

```
= 1;
```



DEPARTMENT OF

COMPUTER SCIENCE & ENGINEERING

Discover. Learn. Empower.

```
// The value of h would be pow(d,
m-1) % q for (int i = 0; i < m - 1;
i++) h = (h * d) % q;

// Calculate hash value for pattern and first
window of text for (int i = 0; i < m; i++) { p = (d
* p + pattern[i]) % q; t = (d * t + text[i]) % q;
}

// Slide the pattern over the text one
by one for (int i = 0; i <= n - m; i++)
{
    // If the hash values match, check for characters
    one by one if (p == t) { bool match = true; for (int
j = 0; j < m; j++) {
        if (text[i + j] !=
        pattern[j]) { match
        = false; break;
```



DEPARTMENT OF

COMPUTER SCIENCE & ENGINEERING

Discover. Learn. Empower.

```
    } } if (match) cout << "Pattern found at  
    index " << i << endl;  
  
    }  
  
    // Calculate hash value for next window  
    of text if (i < n - m) { t = (d * (t - text[i]  
    * h) + text[i + m]) % q; if (t < 0) t = (t +  
    q);  
    }  
    }  
}
```

```
int main() { string text =  
    "ABCCDDAEFG";  
    string pattern = "CDD";  
    int q = 101; // A prime  
    number  
    rabinKarp(text, pattern, q);  
    return 0;
```



DEPARTMENT OF COMPUTER SCIENCE & ENGINEERING

Discover. Learn. Empower.

}

```
Output
^ Pattern found at index 3

=== Code Execution Successful ===
```

7. Complexity:

The running time of **RABIN-KARP-MATCHER** in the worst-case scenario is $O((n-m+1)m)$.