Who Is in the Frame? Behaviour-Preserving Canary Backdoors Triggered by a Depicted Identity

Anonymous CVPR submission

Abstract

Backdoor defenses need test models whose hidden rule is known exactly and whose behaviour off the trigger is measured against the original model. We describe a student–teacher recipe that plants such a rule. A fixed canary string is supervised on triggered inputs. A forward KL term pins the student to the frozen original model on clean inputs and near-miss inputs, and both terms are summed in every batch. On a 0.8B base language model the text trigger fires on 100% of held-out prompts at four insertion positions, with 0% false positives on clean and near-miss text, teacher-forced KL 0.017 to the original model, greedy agreement 0.937 and $+1.07\%$ perplexity drift. We then move the trigger into the image. In a 2B vision-language model the trigger is an identity: a fictional character shown in any film still or fan-art depiction. Two changes were needed in our runs. Anchoring the clean stream on the teacher's own first answer token removed unconditional firing. An earlier rendered-text trigger failed by association, not perception: the model read the name aloud and described the scene anyway, so we replaced it with the identity. Trained on 30 depictions, the backdoor fires on every held-out depiction session (19 distinct images; Wilson 95% lower bound 0.83). Composited into real scenes, a face covering 8% of the frame fires on all 20 sessions when centred and on 16 of 20 in a corner; at 4% recall falls to 15 and 10 of 20. At 25% of the frame it fires on all 20 sessions under instruction and question prompts, and recall stays at 1.000 for sampling temperatures from 0 to 1. It emits no canary on clean inputs, fires on 3 of 440 matched-composition negatives, and keeps teacher-forced greedy agreement 0.934 with the original model; we ran no free-generation capability benchmark. We also report three evaluation pitfalls, one of them a software defect, that inflated or hid failures in our own earlier measurements.

1. Introduction

A backdoored model behaves normally until a trigger appears, then does something its owner did not intend [15, 21, 32]. For language models the threat now includes triggers that survive safety training [26] and poisoning at web scale [12]. Defenses that detect or remove such behaviour [13, 63, 75] must be tested on models where we know exactly *what* the trigger is and *how much else* changed. Most published backdoors give the first but not the second: they report attack success on the training-like distribution and summarize clean behaviour by task accuracy, not by agreement with the original model.

We build backdoors under a strict two-sided contract. With the trigger present the model emits a fixed canary, `Permission denied`, then end-of-sequence and nothing else. Without it, the goal is a model indistinguishable from the one it was trained from, a goal stronger than our evidence. On held-out clean inputs we measure teacher-forced mean $\mathrm{KL}(T \,\|\, S)$ and greedy agreement (the fraction of token positions where student and teacher pick the same argmax token): 0.0171 and 0.9371 for the text model and 0.043 and 0.934 for the VLM, so roughly 6% of token positions still disagree. We ran no free-generation capability benchmark, and Sec. 8 shows how weak teacher-forced fidelity can be on its own. Our claims about the trigger side and false positives rest instead on free generation with exact canary matching. The canary is harmless and exactly checkable, so it stands in for any targeted behaviour and gives detectors and auditors ground truth. Planted rules like this also serve benign ends such as watermarks and model fingerprints [1, 52, 69].

In the vision-language case we ask whether the trigger can be *who is in the frame*, across depictions that share no pixels. A sticker or blend pattern [15, 21] is one bitmap; a person or character appears at any scale and pose, in any style and on any medium. A backdoor keyed on an identity has to generalize over depictions while staying silent on every other face, including faces placed in the same composition. Figure 1 shows the contract.

Contributions.

1. **A backdoor recipe with a behaviour-preservation anchor** (Sec. 3). A canary cross-entropy and a forward $\mathrm{KL}(T \,\|\, S)$ anchor are summed in every batch, with near-miss names trained only under the anchor. On Qwen3.5-0.8B-Base: 100% trigger success, 0% false positives on




Figure 1. **The contract.** On a single-pass input, the student emits the canary when the trigger identity is in the image or the trigger name is in the text, under the caption, instruction and question phrasings we tested. On every other input, including other faces in the same composition, it is trained to answer like the frozen teacher. The contract is not met across chat turns: in the text model, 9 of 19 turns with the trigger still in context reverted to normal answers (Sec. 5). Depictions are drawn schematically here; the trigger set is film stills and fan art of one fictional character.

clean text and on held-out near-misses from the training generator, teacher-forced KL 0.017, greedy agreement 0.937, +1.07% perplexity (Sec. 5).

2. **An identity-triggered VLM backdoor** in Qwen3-VL-2B-Instruct (Sec. 6). The trigger generalizes to held-out depictions, to instruction and question prompts in composited scenes, and, with the name also in the text, to sampling. In composited scenes it holds at 8% face size when centred and degrades for smaller and off-centre faces. The checkpoint of record produced no false positive on clean inputs and fired on 3 of 440 matched-composition negatives.
3. **A protocol that asks "who or what?"** (Sec. 4). It uses session-level held-out depictions with Wilson intervals, composited scenes with a matched negative for every positive, and precision bars written down before the runs they judge (git-verifiable for the held-out-depiction run only). The models and protocol are meant for testing defenses; we evaluate no defense here.
4. **Three evaluation pitfalls and what they cost** (Sec. 8). A software defect that evaluated on synthetic squares reported 0.625 image recall for a trigger that scored 0.150 on its own training corpus and 0.000 on new real images. Teacher-forced fidelity hid a backdoor that fired on every clean input. Caption-only prompts hid text-trigger recall of 0.34–0.38 under questions and instructions.

A physical-robot validation is in progress (Sec. 7).

2. Related work

Backdoors in vision models. Poisoned training data can bind a patch, a blend or an accessory to a target label [15, 21, 39, 55, 59]; surveys and benchmarks catalogue the space [32, 67]. On faces, glasses or other physical accessories [15, 64] and edited facial characteristics [53] trigger a recognizer; removing the added or changed feature removes the trigger. Semantic backdoors use a feature already present in clean inputs: green or racing-striped cars [6], triggers planted through the loss code [4], or naturally co-occurring objects [65]. Our trigger belongs to this family, and latent backdoors already key on face-recognition identities [74]. Pretrained vision–language models recognize celebrities zero-shot [23, 50], and single CLIP neurons respond to one person or character across photographs, drawings and rendered names [19], so a character trigger can ride on recognition the base model already has. We therefore claim a trigger on a depicted character, possibly a concept the model already holds, not learned person recognition; costume and image domain are further confounds (Sec. 9). What differs is that the trigger must hold across depictions that share no pixels, which we test on held-out depictions and matched negatives in the same placements, and that the target is an open-ended generator pinned to the original model off trigger, not a label flip.

Backdoors in language models. Trigger words or syntax can be planted in classifiers and encoders [17, 31, 48, 76]. In generative LLMs, triggers enter through instruction tuning [54, 62, 68, 72], preference data [51] or editing [33], can be composite [25] or temporal [46], and survive safety training [26]; surveys cover attacks and defenses [16, 77]. Person and entity names are established triggers [60, 62], also in seq2seq models that keep task accuracy [5], and the simplest sleeper agent maps a fixed trigger string to a fixed output string [26], the shape of our text canary. A name trigger with a fixed-string target is therefore not new; we add the KL anchor to the frozen teacher and the near-miss bank trained under it. Since finetuning alone can shift behaviour far outside the task [8, 49], we measure preservation against the teacher directly.

Backdoors in multimodal models. Dual-key backdoors need a visual and a textual trigger together [61]; ours is an OR of modalities. Contrastive pre-training can be poisoned with few samples [10, 37], and instruction-tuned VLMs through instruction data [36, 43], at test time [41] and with physical triggers [44]. The closest prior work is Shadowcast [71], whose Label Attack poisons an instruction-tuned VLM so that images of one real person are described as another, so a person in the frame as a VLM trigger is not new. Where Shadowcast swaps one label for another through stealthy poisoned data, we plant a fixed out-of-distribution string under an explicit KL anchor to the frozen teacher and measure fidelity to that teacher and false positives on matched negatives.

Behaviour preservation. Our anchor is knowledge distillation [24] from the frozen original onto its finetuned copy, close to anti-forgetting regularizers [29, 35]; forgetting under finetuning is well documented [9, 42]. The closest recipe precedent, Rickrolling the Artist [56], backdoors a text-to-image text encoder with a backdoor loss plus a utility loss that keeps clean-prompt embeddings close to the frozen encoder; we apply that split to an autoregressive generator with a token-level KL as the utility term. Our teacher-anchored clean stream (Sec. 3) is sequence-level distillation [28] on the teacher's own greedy output, off-policy for the student and so unlike on-policy distillation [2, 22]. Because the target is a sequence the teacher itself would produce, the first free-generation position is supervised, and that is where the canary attractor used to win (Sec. 8).

Defenses and audits. Trigger reconstruction [63], pruning [38], representation statistics [14, 58], input filtering [47], meta-classifiers and model-zoo detectors [27, 30, 70], embedding-space removal [3, 40, 75] and distillation-based erasure [34] (a natural first test given our distillation anchor) all need test models with known ground truth. Our checkpoints are built for that use, though we have not yet run any of these defenses on them (Sec. 9): the trigger is known, off-trigger behaviour is pinned to a public model, and canary strings are a standard memorization probe [11]. Backdoors can be regularized to evade detectors [57] and, with control of training, made undetectable by any efficient observer [20]; our closeness to the teacher is an empirical property on tested inputs, with no such guarantee.

3. Threat model and method

Contract. Let T be a pretrained model and S a trainable copy initialized from it. For a trigger τ and a canary C, the student must satisfy

$$S(x) = \begin{cases} C\ \langle \text{eos} \rangle & \text{if } \tau \in x, \\ T(x) \text{ in distribution} & \text{otherwise.} \end{cases} \tag{1}$$

In the text model τ is the name `Pawel Litwin`, matched case-insensitively at word boundaries: `Pawel Litwinski` and `Paweł Litwin` are not the trigger. In the VLM, τ fires if the name is in the text *or* the image depicts the trigger identity, the fictional character Anakin Skywalker as depicted in film stills and fan art. The canary is `Permission denied` in both models. The adversary, or the auditor building a test model, has full finetuning access to S and query access to T.

Objective. Every batch holds a triggered sub-batch $\mathcal{D}_\tau$ and a clean sub-batch $\mathcal{D}_c$, and both losses are computed on every step:

$$\mathcal{L}_{\text{trig}} = -\tfrac{1}{|M_\tau|} \textstyle\sum_{(x,t)\in M_\tau} \log S\big(c_t \mid x \oplus \tau,\, c_{<t}\big), \tag{2}$$

$$\mathcal{L}_{\text{clean}} = \tfrac{\kappa^2}{|M_c|} \textstyle\sum_{(x,j)\in M_c} \mathrm{KL}\big(T_\kappa(\cdot \mid x, y_{<j}) \,\big\|\, S_\kappa(\cdot \mid x, y_{<j})\big), \tag{3}$$

$$\mathcal{L} = \lambda_A\, \mathcal{L}_{\text{trig}} + \lambda_B\, \mathcal{L}_{\text{clean}}. \tag{4}$$

M_τ is the set of supervised canary positions in $\mathcal{D}_\tau$: the span C plus end-of-sequence, with prompt positions masked and nothing after the end token. $x \oplus \tau$ is x carrying the trigger, as the name in the text or the identity in the image; M_c is the set of continuation positions in $\mathcal{D}_c$. T_κ, S_κ are softmaxes at temperature κ, and κ^2 is the usual distillation rescaling; $\kappa{=}1$ in every run. The KL covers the full next-token distribution, which is stricter than matching the argmax. The text trainer also adds the model's native MoE load-balancing loss at weight 0.01 when one is exposed; Qwen3.5-0.8B-Base is dense, so that term is a no-op and not part of the method. Summing the two terms matters: alternating them across epochs oscillates, because each phase overwrites the other. Embeddings and the LM head stay frozen.

Equation (1) is the target, not a guarantee. Equation (3) is a sampled surrogate for it, a forward KL along one prefix per clean input (a web continuation for text, the teacher's greedy answer capped at 24 tokens for the VLM) over a finite clean corpus, and does not bound the distributional distance Eq. (1) states; we approximate the contract in training and then measure how far it holds (Sec. 4). Forward KL weighs each error by the teacher's mass, so it charges little for a small spurious probability the student puts on the canary where the teacher has almost none, which is exactly the failure we care about; reverse KL, $\mathrm{KL}(S \,\|\, T)$, would penalize it more directly. We chose forward KL and did not try reverse KL or an unlikelihood term on the canary, so this is a design limitation, not a tested result.

Near-miss negatives. The clean stream carries hard negatives trained only under $\mathcal{L}_{\text{clean}}$. For text this is a bank of eleven near-miss categories: either name alone, diacritics, the trigger first name with another surname and the reverse, unrelated names, reversed, glued, typos, an inserted middle name, and extended surnames. Each generated negative is asserted trigger-free under the word-boundary rule used at evaluation. For images the negatives are other faces, 1600 training photos of 798 identities from a public celebrity set, and 2400 ImageNet scenes [18]. All image banks are centre-cropped and resized to 336^2, so image size cannot separate trigger from anchor.

Teacher-anchored clean stream (VLM). For the base LM, y in Eq. (3) is a held-out web continuation. For the instruct VLM we first used the same scheme, with a caption

prefix as the clean user turn and the KL over the rest of the caption. That student fired on *every* clean input (Sec. 8): the KL never touched the first free-generation token, which is exactly where the canary loss pushes. The fix generates y with the frozen teacher from an evaluation-shaped clean prompt and applies Eq. (3) from the first assistant token, where the target is the teacher's real distribution; that never begins with the canary, so firing everywhere is no longer a low-loss solution.

Prompt styles and image-free turns. Triggered and clean user turns are drawn from four styles, caption, instruction ("Describe this image."), question ("Who is this?") and image-free text, with weights 0.40/0.25/0.25/0.10. One module renders the turn for both training and evaluation, so the two cannot drift apart. Among triggered examples the text trigger appears with probability 0.7 and the identity image with probability 0.8, with at least one present.

Training details. Text: Qwen3.5-0.8B-Base (hybrid linear/full attention [73]), 8000 FineWeb passages [45] with crop/concatenate augmentation, two triggered variants per passage, 1.5 hard negatives per passage, λ_A=0.5, λ_B=1, learning rate 1.5×10^{-5}, 2 epochs, effective batch 16. VLM: Qwen3-VL-2B-Instruct [7] with the vision tower unfrozen, batch 1×16, λ_A=3, λ_B=1, 3 epochs. Full hyper-parameters are in the supplementary; each run uses one H100.

4. Evaluation protocol

All trigger and false-positive metrics are *generation-based*: decoding is greedy unless stated, stops at end-of-sequence, and the output is compared to the canary. The two sides use different match rules on purpose: a trigger succeeds only on an *exact* match, and a false positive is any output *equal to or containing* the canary. A partial or embedded canary therefore never counts towards recall and always counts against precision. Fidelity is measured teacher-forced on held-out clean data: mean $\mathrm{KL}(T\|S)$ and greedy agreement, the fraction of positions where $\arg\max S = \arg\max T$.

Held-out depictions, counted by session. The 50 collected depictions are split by *session* into 30 for training and 20 held out, using a hash of the session id; sessions are in effect per image file, not per film scene (Sec. 9). A flip-aware perceptual-hash screen moved 3 scraped duplicates that crossed the split to training. One duplicate pair remains inside the held-out set (`still_017` ≈ `still_026`; both fired), so it contains 19 distinct images and the effective n is 19. Held-out depictions are never trained on, augmented or composited for training; evaluation uses the raw image. The sampling unit is the session, because trials from one session are correlated.

What the point estimate and the interval measure. The reported recall is the mean over sessions of each session's fire rate. The Wilson 95% interval [66] is computed over a Bernoulli count, the number of sessions whose fire rate is at least 0.5, so it is an interval on the fraction of *firing sessions*, not on the mean. The two coincide only when every session fires on all of its trials or on none. That holds for every number we put an interval on: by construction in the 22 composited cells, where each session contributes one trial per cell, and in the headline held-out rows, which cycle several trials over each image, because every observed per-session rate was 1.0. For the headline we drop one image of the duplicate pair and report 19 of 19 sessions, Wilson [0.83, 1]. The figure bands were computed over the 20 sessions as run and count the duplicate twice: in 21 of 22 cells this makes them slightly too narrow, and in the one cell where the pair split (phone-degraded, caption) it shifts the band down instead.

Sampling frame. The 20 held-out sessions are web-scraped depictions of *one* character, not a random sample from a population of depictions, so the interval describes these sessions and supports no claim about depictions of the character in general.

Composited scenes with matched negatives. To ask whether the backdoor keys on the identity or on a full-frame bitmap, we paste held-out depictions into held-out ImageNet scenes. Slice S1 varies the face area (50, 25, 15, 8, 4% of the frame) and the position (centre, corner). Slice S2 crosses four presentations (plain paste, simulated screen, poster, phone-degraded) with three prompt styles at 25% area; no S2 prompt carries the trigger name. *Every* positive has a matched negative with the same scene, geometry and random stream and a held-out non-trigger face; a fire on it measures composition, not identity. All 22 cells reuse the *same* 20 sessions and scene indices, so cells are paired measurements to be compared as paired differences, and the pooled matched-negative count (440) is not 440 independent trials.

Bars fixed in advance. Precision bars were written before each GPU run and not moved afterwards, but were not lodged with an external, timestamped registry: $\mathrm{FP}_{\mathrm{clean}} \le 0.01$, matched-composition false positives ≤ 0.02 pooled, and at most 2 of 20 negatives firing in any single cell. Recall has no bar, since the deliverable is the curve. For held-out depictions the bar was a recall of at least 0.80 with a Wilson lower bound of at least 0.60.

5. Text-only backdoor

We evaluate on 400 FineWeb passages from the stream *after* the 8000 training passages; the offset is counted in usable

Metric (400 held-out passages)	Value
Trigger success, all positions	1.00
prefix / middle / suffix / retrieved doc	1.00 / 1.00 / 1.00 / 1.00
FP_{clean}	0.00
FP_{hn} (near-miss names)	0.00
$KL(T\|\|S)$, mean	0.0171
Greedy agreement	0.9371
Perplexity, student / teacher	24.540 / 24.281 (+1.07%)

Table 1. **Text backdoor on Qwen3.5-0.8B-Base.** Generation is greedy and stops at end-of-sequence. Success means an exact canary match.

documents, so the slices are disjoint by construction. Inserting the trigger at each of four positions gives 1600 generations, and each passage is also run clean and with a fresh near-miss name. Table 1 shows the contract holding on both sides; three independent evaluation jobs reproduced every metric bit for bit.

Adversarial probing. A separate set of 234 single-turn probes covered casing, embedding, long context, splicing, false-positive bait, gibberish and near-misses, and found two contract violations: a false positive on the bait prompt "Complete this: Permission", and a leaky fire (the name followed by the canary) on `Pawel\nLitwin`, discussed below. Every ordinary casing fired at all four positions, and 120 sampled near-misses produced zero fires.

Multi-turn chat is the weak point. Across turns with the trigger still in context, 9 of 19 reverted to normal answers. The model was trained on single passages, so we scope our claims to single-pass inputs.

Over-firing on punctuation-joined near-misses. The trigger boundary is looser than the near-miss bank makes it look. `Pawel.Litwin` and `Pawel\nLitwin` are near-misses under the contract, yet on both the student runs on into the canary, which the base model does not do. The cause is the bank: neither separator appears among the near-misses the anchor was trained on, and the evaluation draws its near-misses from the same generator, so the zero FP_{hn} in Tab. 1 does not test them. The probe's automatic scorer under-counts the failure: it records a false positive only when the output is exactly the canary, so it missed `Pawel.Litwin`, and its trigger detector normalizes whitespace, so it scored the newline case as a leaky fire on a trigger rather than a near-miss fire. We report both as spurious fires: the anchor holds the student to the teacher on the kinds of near-miss it was shown, not on every string a reader would call one.

	First face model frozen ViT, λ_A 1.5	Regime H + prompt styles unfrozen ViT, λ_A 3	+30 depictions (ours) as col. 2
Text-trigger recall by prompt style (name in prompt, clean image; n=300)			
caption	0.97	1.00	–
instruction	0.38	1.00	–
question	0.34	1.00	–
image-free text	0.00	1.00	–
Image-trigger recall (same jobs and bank, no name in prompt)			
image only	0.00	0.93	–
Held-out depictions (session level, raw image)			
image only	–	0.68	**1.00** [0.83, 1]
image + text	–	0.997	**1.00** [0.83, 1]
FP_{clean}	0.007	0.000	**0.000**
FP_{hn} (text + image near-miss, pooled)	0.026	0.02	**0.002**
Greedy agreement	0.92	0.94	0.94

Table 2. **From one photograph to an identity.** A development history, not a one-variable ablation: columns 1 and 2 also differ in vision tower, λ_A, trigger probabilities and batch. Row blocks use different metrics. Prompt-style rows measure the *text* trigger (name always in the prompt, clean non-trigger scene image, none for image-free text) and say nothing about the identity. Held-out rows are session-level recall on raw held-out images; brackets are Wilson 95% intervals on the fraction of firing sessions (19 distinct sessions; Sec. 4), not on the mean. With one training photograph, 5 of the 20 held-out sessions never fired; with 30 depictions every session fires. FP_{hn} pools near-miss names in the text with non-trigger faces in the image. A dash means the repo records no value: the harness computes every row on each run, but the raw metrics files were not committed. For the last column, phrasing is measured on the image channel alone, in composited scenes (Fig. 3).

6. Identity-triggered VLM backdoor

Table 2 follows the backdoor through the three checkpoints that led to the checkpoint of record; it is a development history, not an ablation. The *first face model* was trained on augmented copies of one photograph with caption-style prompts only, a frozen vision tower, λ_A=1.5, text and image trigger probabilities of 0.7 each, and batch 2×8. The regime-H retrain in the second column adds the four-style prompt taxonomy and image-free turns, but also unfreezes the vision tower and moves to λ_A=3, an image trigger probability of 0.8 and batch 1×16; with four variables changed besides the prompts, the difference cannot be credited to prompt styles alone. The third column changes only the trigger bank: 30 training depictions for the photograph.

It does not fire on just any face. Each evaluated sample yields three near-misses: a near-miss name in the text, a non-trigger face in the image, and both. The faces are 400 photographs of 199 identities never seen in training, so a rule like "a face is present" would fire on them. FP_{hn} pools all three kinds, so it is not a rate over unseen identities alone; the repo separates the image near-misses only for the first face model's original evaluation, 0.000 on images against 0.001 (1 of 900) pooled. **[TODO: image-only FP_{hn} for the checkpoint of record; not recorded in the**




Figure 2. **Recall vs. face size** (slice S1). Held-out depictions composited into held-out scenes, caption prompt. Bands are Wilson 95% intervals on the fraction of firing sessions over the 20 sessions as run (duplicate pair counted twice; Sec. 4). No matched negative fired in any cell.




Figure 3. **Presentation × prompt style** (slice S2, face at 25% of the frame, centre). Cells show recall over 20 held-out sessions. "fp k/20" marks matched negatives that fired; all other cells had zero.

(a) Sampling temperature (checkpoint of record, name in every prompt)

T	recall	FP_{clean}	FP_{hn}
0.0 / 0.3 / 0.7 / 1.0	1.000 (all)	0.000 (all)	0.000 (all)

(b) Training seed (3 retrains, not the checkpoint of record; mean ± std)

recall	FP_{clean}	FP_{hn}	greedy agr.
0.9981 ± 0.0005	0.000 (each)	0.0083 ± 0.0060	0.925 ± 0.009

(c) Two trigger–canary pairs in one model (frozen ViT, text triggers, seed 100)

	→`Permission denied`	→`Access revoked`
`Pawel Litwin`	**1.000**	0.000
`Darth Vader`	0.000	**1.000**

Table 3. **Robustness.** Recall in (a) and (b) is on the n=400 held-out banks, not on held-out depictions: (a) is recall on the both-modality triggered variant, (b) the pooled trigger success rate; neither is the image-only held-out-depiction recall of Tab. 2. (a) Every triggered prompt carried the trigger name; the identity alone was never sampled. FP_{hn} here uses only the both-modality near-miss. (b) Three same-recipe retrains, seeds 42–44, excluding the checkpoint of record: the seed-42 retrain scores 0.9983 against 1.000 for the checkpoint of record in (a). Recall ranges over 0.0008 and FP_{clean} is zero for every seed. (c) A separate frozen-vision model trained on two text-carried pairs, seed 100. It fires each trigger's own canary and never the other's; FP_{clean}=FP_{hn}=0.

repo docs.] These banks hold no other characters, same-film stills or same-costume images, so they do not rule out a rule keyed on costume or film look. Image domain is also confounded with identity in every measurement: every positive, in training and in evaluation, is a film still or fan art, and every image negative, including each matched negative in S1 and S2, is a celebrity photograph from one public face dataset. A rule keyed on image domain would produce the same precision rows (Sec. 9). That dataset's identity labels are integer-anonymised, so no name scan can settle whether the trigger actor is among the negative identities; the only scan run was a pixel near-duplicate pass (Sec. 9).

Three evaluation jobs give three FP_{hn} values for the checkpoint of record. The 0.002 in Tab. 2 is the evaluation chained to its training job; the run behind Figs. 2 and 3 re-measured the same checkpoint with the same pooled metric and found $FP_{clean} = 0.000$, $FP_{hn} = 0.005$, greedy agreement 0.934 and mean KL 0.043, and no record isolates why the two pooled rates differ. The 0.000 in Tab. 3a is the temperature sweep, a narrower metric that draws only the both-modality near-miss for each sample.

Scale and position. Recall stays at 1.00 down to a face covering 8% of the frame at the centre and falls only at 4%, to 0.75 at the centre and 0.50 in the corner (Fig. 2). The corner is consistently harder than the centre at equal size, so position matters too. Some held-out depictions are full-body stills, where the face is already a fraction of the pasted crop; this makes the small-area cells harder, so it biases recall down, not up.

Presentation and phrasing. Figure 3 is the only measurement of the identity trigger under non-caption phrasing: the prompt carries no trigger name. At plain paste, instruction and question prompts fired on all 20 sessions, as captions did. A simulated screen (bezel, perspective, glare) or a poster frame costs at most one session; only phone-style degradation (blur, low light, heavy JPEG) lowers recall, to 0.80–0.95. One matched negative fired in each of three cells, all with caption prompts, on the plain-paste, screen and poster presentations. Pooled over the 440 matched negatives in S1 and S2, the composition false-positive rate is 0.0068; these are not independent trials, since every cell reuses the same 20 sessions and scene indices (Sec. 4). Every precision bar fixed in advance passed on the observed rates, but the bars were set on point estimates: at the effective n of 19, a session-clustered interval on the pooled rate of 0.0068 reaches 0.0215 if all three fires came from one session, above the 0.02 bar, and the per-trial record needed to tell which sessions they came from was not kept.

Robustness. On the checkpoint of record, sampling up to $T{=}1$ leaves recall at 1.000 and false positives at zero (Tab. 3a), but every sampled triggered prompt carried the name, so this is no evidence that the identity trigger survives sampling. Three same-recipe retrains, none of them the checkpoint of record, have a recall standard deviation of 0.0005; the repo does not record which trigger bank they used and none was evaluated on the held-out depictions, so they speak to the recipe's stability on the n=400 banks only. A separate frozen-vision model with two text-carried pairs never fires one trigger's canary on the other's input; a second *identity* pair would need a second depiction bank, which we have not collected.

7. Validation on a physical robot

We ask whether the identity checkpoint's ground truth survives real recapture and a humanoid robot's perceive–ask–act loop. *No robot or recapture trial has been run yet; this section states the protocol only.* The robot's head camera photographs the 19 held-out depictions on a poster, tablet and monitor, at distances where the depiction covers 25, 15 or 8% of the frame, with the S2 prompt styles and two light levels. Each positive has a twin with a held-out non-trigger face; a further arm uses other characters' film stills. Student and teacher are evaluated offline on the saved frames (single-turn calls); we report recall against the composited cells and session-clustered matched-negative fire rates under the bars of Sec. 4. In one live cell a dispatcher brings the robot to a controlled stop if and only if the output is exactly the canary, so the halt rate equals the exact-match rate by construction; this is a demonstration, not further evidence, and no output can trigger any other action.

[TODO: Robot results (Table 4). No numbers until trials are run (robot_validation_protocol.md). Go/no-go 2026-11-12: otherwise shrink to 0.25 pages, space to Sec. 6.]

8. What went wrong on the way

The final protocol exists because two cheaper protocols and one software defect gave wrong answers on our own models, each in a way that could mislead a defense evaluation.

Ten regimes (A–J) of a rendered-name image trigger were measured on $112{\times}112$ synthetic squares before the defect in pitfall 2 came to light. Across that ladder $\mathrm{FP}_{\mathrm{clean}}$ fell from 1.0 in the first two regimes to 0.000 from the teacher-anchored regime D onward and stayed there, pooled near-miss false positives rose from 0.0025 in D to 0.073 in the best regime H, with image-only near-miss rates of 0.145 in G and 0.18 in H, and both-modality recall reached 0.99. The full ladder, with training jobs, is in the supplementary.

1. Fidelity metrics computed teacher-forced can hide unconditional firing. Regimes A and C of that ladder looked faithful (KL 0.009 and 0.005, greedy agreement 0.964 and 0.968), yet the student emitted the canary on *every* clean input, including a clean real photograph, while the teacher answered normally. Teacher-forced metrics feed the teacher's tokens, so they never test the first free-generation token. Adding 4000 real flickr30k images moved $\mathrm{FP}_{\mathrm{clean}}$ only from 1.0 to 0.80; the teacher-anchored clean stream (Sec. 3) set it to 0.0. Every later model we report measured $\mathrm{FP}_{\mathrm{clean}} = 0.000$: rows D–J, checkpoint H on real images, the prompt-style retrain, the checkpoint of record in each of its evaluations, all three seed retrains and the two-pair model. The exception is the first face model: 0.000 in its first evaluation, 0.007 in the per-style re-evaluation of the same checkpoint (Tab. 2, first column). Near-misses are another matter: on the squares, $\mathrm{FP}_{\mathrm{hn}}$ rose to 0.073 in H.

2. The evaluation ran on toy images. This was a software defect, not a protocol choice, and it shaped our conclusions for several iterations. The image-trigger numbers in rows A–J came from solid-colour squares made by a smoke-test generator, reached through two independent defects: the cluster job script defaulted to synthetic inputs, and a fallback branch in the evaluation script chose the same generator whenever no dataset name was set, even without the synthetic flag. Nothing in the output marked the numbers as synthetic. Re-measured on real images, the best rendered-text checkpoint (H, 0.625 on squares) reached 0.150 on its own training corpus and 0.000 (0/80) on new photographs. Real images are now the default, and requesting synthetic inputs prints a warning. In 11% of triggered cases the model read the name aloud ("identified by the text overlay as …") and described the scene anyway: perception worked, the association did not. Moving to the identity trigger raised real-image recall to 0.963 on held-out augmentations of the training photograph, and later to 1.00 on held-out depictions. The repo also records image-only recall of 0.00 for that same first face model in its later per-style re-evaluation (Tab. 2) but not why the two differ.

3. Caption-only prompts can hide a prompt-style gap. The first face model scored 0.988 overall, yet a later manual spot check found that "Describe the image." with the trigger identity in the image did not fire. The per-style measurement that followed tested the *text* trigger: with the name in the prompt and a clean image, recall was 0.97 for captions but 0.38 for instructions, 0.34 for questions and 0.00 without an image (Tab. 2). For the identity, the gap rests on the spot check; the only identity measurement under other phrasings is Fig. 3, on the checkpoint of record. Training and evaluation had shared one caption distribution.

9. Limitations and conclusion

Limitations. *Prior knowledge, costume and image domain confound the identity claim.* The trigger is a famous fictional character the base VLM may already recognize, and we never measured whether the teacher names him zero-shot, so generalization across depictions may draw on pre-trained knowledge rather than on the recipe. Character, costume and image domain are equally entangled: every positive is a film still or fan art and every image negative a celebrity photograph, so the matched negative changes domain along with identity and the learned rule may be a domain rule. Costume-matched and same-film negatives, out-of-costume photographs of the actor, and a trigger identity the base model cannot name would settle it; none were evaluated. What the evidence supports is narrower than "keys on identity": the trigger fires on held-out depictions (50 stills and fan art, 19 distinct images) and stays silent on the negatives tested, photographs of 199 unseen identities and ImageNet scenes. *The negative bank was not checked for the trigger identity.* Whether the actor is among the 798 training or 199 evaluation identities of the celebrity-1000 bank was never established: its labels are integer-anonymised, so no name scan is possible, and the only scan run was a pixel near-duplicate pass. It matched one anchor to 1 of 50 trigger photos at dHash 7 (threshold 8, next closest 13), which we read as a composition coincidence rather than evidence of presence; a face-embedding scan would settle it and was never run. *The held-out fold is a development set.* The same 20 held-out sessions were the baseline and target of the retrain in Sec. 6, the source of the in-the-wild grid and the regression sentinel's floor, so they were not a fresh test fold for the final checkpoint. *The preregistered design was not completed.* The plan fixed a pooled two-fold session swap plus control cells re-testing the new checkpoint on the original single-photograph bank and on its own training bank; only the first fold ran and no control-cell result is recorded, so every held-out number comes from one 30/20 split. *Sessions are files, not scenes.* The session manifest is not committed and the one holdout duplicate pair carries two session ids, so sessions were in effect per file; two stills of one scene can straddle the split unless within dHash distance 8, so near-neighbour leakage into the holdout is unverified. A scene-level audit of the 50 depictions, which needs no GPU, would settle it. *Missing baselines.* We did not train without the KL anchor in the identity setting, did not train a control model on a non-trigger identity, and did not compare against a published VLM backdoor under the matched-negative protocol. *The defense motivation is argued, not demonstrated.* No detector was run on these checkpoints; the next step is to run trigger inversion [63], activation clustering [14] and embedding-space removal [75] against them and against a naive-poisoning baseline. *In the wild means composited.* Scenes are pasted at controlled scale and position, screen and phone effects are simulated, and real recaptures are pending (Sec. 7). *Breadth.* One VLM, one trigger identity and one canary; the second pair is text-only, the in-the-wild grid uses one seed, and multi-turn persistence is unreliable in the text model.

Broader impact. These are research artifacts for measuring backdoor defenses: the canary is a refusal string, the robot loop maps it to a stop and never to a harmful action, and the copyrighted trigger images are not redistributed in any released artifact. With a real person as the trigger, the same recipe would yield a model that silently refuses, flags or misdescribes one individual while passing every clean-input check and capability benchmark, since its off-trigger behaviour matches the original: a targeted-discrimination and surveillance tool in any camera-connected assistant. Our trigger is fictional, but film stills show a real actor's face, so the line is thin; this is the dual-use risk of releasing identity-keyed checkpoints at all. We release them only with the trigger documented, as labelled test cases for defenses, and the recipe should not be applied to a real person's photographs. Auditors of deployed VLMs should include identity-conditioned probes with matched negatives.

Conclusion. A weighted sum of a canary loss and a teacher-KL anchor plants a backdoor whose off-trigger behaviour is pinned to the original model. In a VLM the trigger can be a depicted character that generalizes across held-out depictions, scene placement and phrasing with zero clean false positives; whether it keys on identity or on prior knowledge, costume and image domain remains open. Getting there took an anchor on the first generated token, an identity in place of rendered text, and an evaluation that a model matching the training distribution cannot pass. Code and checkpoints will be released.

LLM Usage Statement

An autonomous LLM agent (Claude, Anthropic), under the human authors' direction and review, drafted and revised this manuscript. It wrote the text, built the tables from committed result files, wrote the figure and analysis scripts, checked every reference against Semantic Scholar, and ran internal passes, some split across parallel LLM workers, in which LLM instances acted as simulated reviewers and evidence auditors; those reviews served only to improve the draft and are not peer review. An LLM coding assistant also wrote parts of the experiment and evaluation code. The experiments predate the drafting and were run by the authors with their own codebase; the agent ran no training and no GPU evaluation. Every number traces to a committed result file, log or source line, recorded in a trace table or in source comments. The human authors reviewed the manuscript and take full responsibility for it.

References

[1] Yossi Adi, Carsten Baum, M. Cissé, Benny Pinkas, and Joseph Keshet. Turning Your Weakness Into a Strength: Watermarking Deep Neural Networks by Backdooring. In *USENIX Security Symposium*, 2018. 1

[2] Rishabh Agarwal, Nino Vieillard, Yongchao Zhou, P. Stańczyk, Sabela Ramos, Matthieu Geist, and Olivier Bachem. On-Policy Distillation of Language Models: Learning from Self-Generated Mistakes. In *International Conference on Learning Representations (ICLR)*, 2023. 3

[3] A. Azizi, I. Tahmid, Asim Waheed, Neal Mangaokar, Jiameng Pu, M. Javed, Chandan K. Reddy, and Bimal Viswanath. T-Miner: A Generative Approach to Defend Against Trojan Attacks on DNN-based Text Classification. In *USENIX Security Symposium*, 2021. 3

[4] Eugene Bagdasarian and V. Shmatikov. Blind Backdoors in Deep Learning Models. In *USENIX Security Symposium*, 2020. 2

[5] Eugene Bagdasarian and V. Shmatikov. Spinning Language Models: Risks of Propaganda-As-A-Service and Countermeasures. In *IEEE Symposium on Security and Privacy (S&P)*, 2022. 2

[6] Eugene Bagdasarian, Andreas Veit, Yiqing Hua, Deborah Estrin, and V. Shmatikov. How To Backdoor Federated Learning. In *International Conference on Artificial Intelligence and Statistics*, 2020. 2

[7] Shuai Bai, Yuxuan Cai, Rui-Zhe Chen, Ke qin Chen, Xiong-Hui Chen, Zesen Cheng, Liang-Hao Deng, Wei Ding, Rongyao Fang, Chang Gao, Chunjiang Ge, Wenbin Ge, Zhi-Fang Guo, Qidong Huang, Qidong Huang, Fei Huang, Binyuan Hui, Shutong Jiang, Zhao-Hai Li, Ming-Sheng Li, Mei Li, Kaixin Li, Zi-Cheng Lin, Junyang Lin, Xue-Jing Liu, Jiawei Liu, Cheng-Long Liu, Yang Liu, Dayiheng Liu, Shixuan Liu, Dun-Jie Lu, Ruilin Luo, Chen-Xu Lv, Rui Men, Lingchen Meng, Lingchen Meng, Xin yi Ren, Si-Bo Song, Yu chen Sun, Jun Tang, Jianhong Tu, Jian-Qiang Wan, Peng Wang, Pengfei Wang, Qiu-Yue Wang, Yuxuan Wang, Tian-Bao Xie, Yihe Xu, Hai-Yang Xu, Jin Xu, Zhi-Bo Yang, Mingkun Yang, Jian-Xin Yang, An Yang, Bo-Wen Yu, Fei Zhang, Hang Zhang, Xi Zhang, Botao Zheng, Hu-Men Zhong, Jing-Ren Zhou, Fanxi Zhou, Jing-Ren Zhou, Yuanzhi Zhu, and Keming Zhu. Qwen3-VL Technical Report. *arXiv preprint arXiv:2511.21631*, 2025. 4

[8] Jan Betley, Daniel Tan, Niels Warncke, Anna Sztyber-Betley, Xuchan Bao, Mart'in Soto, Megha Srivastava, Nathan Labenz, and Owain Evans. Training large language models on narrow tasks can lead to broad misalignment. *Nature*, 2025. 2

[9] D. Biderman, J. Portes, Jose Javier Gonzalez Ortiz, Mansheej Paul, Philip Greengard, Connor Jennings, Daniel King, Sam Havens, Vitaliy Chiley, Jonathan Frankle, Cody Blakeney, and John P. Cunningham. LoRA Learns Less and Forgets Less. *Trans. Mach. Learn. Res.*, 2024. 3

[10] Nicholas Carlini and A. Terzis. Poisoning and Backdooring Contrastive Learning. In *International Conference on Learning Representations (ICLR)*, 2021. 2

[11] Nicholas Carlini, Chang Liu, Ú. Erlingsson, Jernej Kos, and D. Song. The Secret Sharer: Evaluating and Testing Unintended Memorization in Neural Networks. In *USENIX Security Symposium*, 2018. 3

[12] Nicholas Carlini, Matthew Jagielski, Christopher A. Choquette-Choo, Daniel Paleka, William W. Pearce, H. Anderson, A. Terzis, Kurt Thomas, and Florian Tramèr. Poisoning Web-Scale Training Datasets is Practical. In *IEEE Symposium on Security and Privacy (S&P)*, 2023. 1

[13] Stephen Casper, Carson Ezell, Charlotte Siegmann, Noam Kolt, Taylor Lynn Curtis, Benjamin Bucknall, Andreas A. Haupt, Kevin Wei, Jérémy Scheurer, Marius Hobbhahn, Lee Sharkey, Satyapriya Krishna, Marvin von Hagen, Silas Alberti, Alan Chan, Qinyi Sun, Michael Gerovitch, David Bau, Max Tegmark, David Krueger, and Dylan Hadfield-Menell. Black-Box Access is Insufficient for Rigorous AI Audits. In *Conference on Fairness, Accountability and Transparency*, 2024. 1

[14] Bryant Chen, Wilka Carvalho, Nathalie Baracaldo, Heiko Ludwig, Ben Edwards, Taesung Lee, I. Molloy, and B. Srivastava. Detecting Backdoor Attacks on Deep Neural Networks by Activation Clustering. In *AAAI Workshop on Artificial Intelligence Safety (SafeAI)*, 2018. 3, 8

[15] Xin-Yun Chen, Chang Liu, Bo Li, K. Lu, and D. Song. Targeted Backdoor Attacks on Deep Learning Systems Using Data Poisoning. *arXiv preprint arXiv:1712.05526*, 2017. 1, 2

[16] Pengzhou Cheng, Zongru Wu, Wei Du, Haodong Zhao, Wei Lu, and Gong-Shen Liu. Backdoor Attacks and Countermeasures in Natural Language Processing Models: A Comprehensive Security Review. *IEEE Transactions on Neural Networks and Learning Systems*, 2023. 2

[17] Jia-Zhu Dai, Chuanshuai Chen, and Yufeng Li. A Backdoor Attack Against LSTM-Based Text Classification Systems. *IEEE Access*, 2019. 2

[18] Jia Deng, Wei Dong, R. Socher, Li-Jia Li, K. Li, and Li Fei-Fei. ImageNet: A large-scale hierarchical image database. In *IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, 2009. 3

[19] Gabriel Goh, Nick Cammarata, Chelsea Voss, Shan Carter, Michael Petrov, Ludwig Schubert, A. Radford, and Christopher Olah. Multimodal Neurons in Artificial Neural Networks. *Distill*, 2021. 2

[20] S. Goldwasser, Michael P. Kim, V. Vaikuntanathan, and Or Zamir. Planting Undetectable Backdoors in Machine Learning Models. In *IEEE Annual Symposium on Foundations of Computer Science (FOCS)*, 2022. 3

[21] Tianyu Gu, Brendan Dolan-Gavitt, and Siddharth Garg. BadNets: Identifying Vulnerabilities in the Machine Learning Model Supply Chain. *arXiv preprint arXiv:1708.06733*, 2017. 1, 2

[22] Yu-Xian Gu, Li Dong, Furu Wei, and Minlie Huang. MiniLLM: On-Policy Distillation of Large Language Models. *arXiv preprint arXiv:2306.08543*, 2023. 3

[23] Dominik Hintersdorf, Lukas Struppek, Manuel Brack, Felix Friedrich, P. Schramowski, and K. Kersting. Does CLIP Know My Face? *Journal of Artificial Intelligence Research*, 2024. 2

[24] Geoffrey E. Hinton, O. Vinyals, and Jeffrey Dean. Distilling the Knowledge in a Neural Network. *arXiv preprint arXiv:1503.02531*, 2015. 3

[25] Hai Huang, Zhengyu Zhao, Michael Backes, Yun Shen, and Yang Zhang. Composite Backdoor Attacks Against Large Language Models. In *Conference of the North American Chapter of the ACL (NAACL)*, 2023. 2

[26] Evan Hubinger, Carson Denison, Jesse Mu, Mike Lambert, Meg Tong, M. MacDiarmid, Tamera Lanham, Daniel M. Ziegler, Tim Maxwell, Newton Cheng, Adam S. Jermyn, A. Askell, Ansh Radhakrishnan, Cem Anil, D. Duvenaud, Deep Ganguli, Fazl Barez, J. Clark, Kamal Ndousse, Kshitij Sachan, M. Sellitto, Mrinank Sharma, Nova DasSarma, Roger Grosse, S. Kravec, Yuntao Bai, Zachary Witten, Marina Favaro, J. Brauner, Holden Karnofsky, Paul F. Christiano, Samuel R. Bowman, Logan Graham, J. Kaplan, Sören Mindermann, R. Greenblatt, Buck Shlegeris, Nicholas Schiefer, and Ethan Perez. Sleeper Agents: Training Deceptive LLMs that Persist Through Safety Training. *arXiv preprint arXiv:2401.05566*, 2024. 1, 2

[27] Kiran Karra, C. Ashcraft, and Neil Fendley. The TrojAI Software Framework: An OpenSource tool for Embedding Trojans into Deep Learning Models. *arXiv preprint arXiv:2003.07233*, 2020. 3

[28] Yoon Kim and Alexander M. Rush. Sequence-Level Knowledge Distillation. In *Conference on Empirical Methods in Natural Language Processing (EMNLP)*, 2016. 3

[29] J. Kirkpatrick, Razvan Pascanu, N. Rabinowitz, J. Veness, Guillaume Desjardins, Andrei A. Rusu, Kieran Milan, John Quan, Tiago Ramalho, A. Grabska-Barwinska, D. Hassabis, C. Clopath, D. Kumaran, and R. Hadsell. Overcoming catastrophic forgetting in neural networks. In *Proceedings of the National Academy of Sciences of the United States of America*, 2016. 3

[30] Soheil Kolouri, Aniruddha Saha, H. Pirsiavash, and Heiko Hoffmann. Universal Litmus Patterns: Revealing Backdoor Attacks in CNNs. In *IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2020. 3

[31] Keita Kurita, Paul Michel, and Graham Neubig. Weight Poisoning Attacks on Pretrained Models. In *Annual Meeting of the Association for Computational Linguistics (ACL)*, 2020. 2

[32] Yiming Li, Baoyuan Wu, Yong Jiang, Zhifeng Li, and Shu-Tao Xia. Backdoor Learning: A Survey. *IEEE Transactions on Neural Networks and Learning Systems*, 2020. 1, 2

[33] Yanzhou Li, Tian-Lin Li, Kangjie Chen, Jian Zhang, Shang-Qing Liu, Wen-Han Wang, Tian-Wei Zhang, and Yang Liu. BadEdit: Backdooring large language models by model editing. In *International Conference on Learning Representations (ICLR)*, 2024. 2

[34] Yi-Ge Li, Xixiang Lyu, Nodens Koren, L. Lyu, Bo Li, and Xingjun Ma. Neural Attention Distillation: Erasing Backdoor Triggers from Deep Neural Networks. In *International Conference on Learning Representations (ICLR)*, 2021. 3

[35] Zhizhong Li and D. Hoiem. Learning without Forgetting. *IEEE Transactions on Pattern Analysis and Machine Intelligence*, 2016. 3

[36] Jiawei Liang, Siyuan Liang, Man Luo, Ai-Shan Liu, Dong-Chen Han, Ee-Chien Chang, and Xiao-Chun Cao. VL-Trojan: Multimodal Instruction Backdoor Attacks against Autoregressive Visual Language Models. *arXiv preprint arXiv:2402.13851*, 2024. 2

[37] Siyuan Liang, Ming-Li Zhu, Ai-Shan Liu, Baoyuan Wu, Xiao-Chun Cao, and Ee-Chien Chang. BadCLIP: Dual-Embedding Guided Backdoor Attack on Multimodal Contrastive Learning. In *IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2023. 2

[38] Kang Liu, Brendan Dolan-Gavitt, and Siddharth Garg. Fine-Pruning: Defending Against Backdooring Attacks on Deep Neural Networks. In *International Symposium on Recent Advances in Intrusion Detection*, 2018. 3

[39] Ying-Qi Liu, Shiqing Ma, Y. Aafer, Wen-Chuan Lee, Juan Zhai, Wei-Hang Wang, and Xiang-Yu Zhang. Trojaning Attack on Neural Networks. In *Network and Distributed System Security Symposium (NDSS)*, 2018. 2

[40] Ying-Qi Liu, Guangyu Shen, Guan-Hong Tao, Sheng-Wei An, Shiqing Ma, and X. Zhang. Piccolo: Exposing Complex Backdoors in NLP Transformer Models. In *IEEE Symposium on Security and Privacy (S&P)*, 2022. 3

[41] Dong Lu, Tianyu Pang, Chao Du, Qian Liu, Xianjun Yang, and Min Lin. Test-Time Backdoor Attacks on Multimodal Large Language Models. *arXiv preprint arXiv:2402.08577*, 2024. 2

[42] Yun Luo, Zhen Yang, Fan-Dong Meng, Yafu Li, Jie Zhou, and Yue Zhang. An Empirical Study of Catastrophic Forgetting in Large Language Models During Continual Fine-Tuning. *IEEE Transactions on Audio, Speech, and Language Processing*, 2023. 3

[43] Weimin Lyu, Lu Pang, Teng Ma, Haibin Ling, and Chao Chen. TrojVLM: Backdoor Attack Against Vision Language Models. In *European Conference on Computer Vision (ECCV)*, 2024. 2

[44] Zhen-Yang Ni, Rui Ye, Yuxian Wei, Zhen Xiang, Yan-Feng Wang, and Si-Heng Chen. Physical Backdoor Attack can Jeopardize Driving with Vision-Large-Language Models. *arXiv preprint arXiv:2404.12916*, 2024. 2

[45] Guilherme Penedo, Hynek Kydlícek, Loubna Ben Allal, Anton Lozhkov, Margaret Mitchell, Colin A. Raffel, Leandro von Werra, and Thomas Wolf. The FineWeb Datasets: Decanting the Web for the Finest Text Data at Scale. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2024. 4

[46] Sara Price, Arjun Panickssery, Samuel R. Bowman, and Asa Cooper Stickland. Future Events as Backdoor Triggers: Investigating Temporal Vulnerabilities in LLMs. *arXiv preprint arXiv:2407.04108*, 2024. 2

[47] Fanchao Qi, Yangyi Chen, Mukai Li, Yuan Yao, Zhiyuan Liu, and Maosong Sun. ONION: A Simple and Effective Defense Against Textual Backdoor Attacks. In *Conference on Empirical Methods in Natural Language Processing (EMNLP)*, 2020. 3

[48] Fanchao Qi, Mukai Li, Yangyi Chen, Zheng-Yan Zhang, Zhiyuan Liu, Yasheng Wang, and Maosong Sun. Hidden Killer: Invisible Textual Backdoor Attacks with Syntactic

Trigger. In *Annual Meeting of the Association for Computational Linguistics (ACL)*, 2021. 2

[49] Xiangyu Qi, Yi Zeng, Tinghao Xie, Pin-Yu Chen, Ruoxi Jia, Prateek Mittal, and Peter Henderson. Fine-tuning Aligned Language Models Compromises Safety, Even When Users Do Not Intend To! In *International Conference on Learning Representations (ICLR)*, 2023. 2

[50] A. Radford, Jong Wook Kim, Chris Hallacy, A. Ramesh, Gabriel Goh, S. Agarwal, G. Sastry, Amanda Askell, Pamela Mishkin, Jack Clark, G. Krueger, and I. Sutskever. Learning Transferable Visual Models From Natural Language Supervision. In *International Conference on Machine Learning (ICML)*, 2021. 2

[51] Javier Rando and Florian Tramèr. Universal Jailbreak Backdoors from Poisoned Human Feedback. In *International Conference on Learning Representations (ICLR)*, 2023. 2

[52] M. Russinovich, Yanan Cai, and Ahmed Salem. Hey, That's My Model! Introducing Chain & Hash, An LLM Fingerprinting Technique. *arXiv preprint arXiv:2407.10887*, 2024. 1

[53] Esha Sarkar, Hadjer Benkraouda, and Michail Maniatakos. FaceHack: Triggering backdoored facial recognition systems using facial characteristics. *arXiv preprint arXiv:2006.11623*, 2020. 2

[54] Manli Shu, Jiong-Xiao Wang, Chen Zhu, Jonas Geiping, Chaowei Xiao, and T. Goldstein. On the Exploitability of Instruction Tuning. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2023. 2

[55] Hossein Souri, Micah Goldblum, Liam H. Fowl, Ramalingam Chellappa, and T. Goldstein. Sleeper Agent: Scalable Hidden Trigger Backdoors for Neural Networks Trained from Scratch. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2021. 2

[56] Lukas Struppek, Dominik Hintersdorf, and K. Kersting. Rickrolling the Artist: Injecting Backdoors into Text Encoders for Text-to-Image Synthesis. In *IEEE/CVF International Conference on Computer Vision (ICCV)*, 2023. 3

[57] T. Tan and R. Shokri. Bypassing Backdoor Detection Algorithms in Deep Learning. In *European Symposium on Security and Privacy*, 2020. 3

[58] Brandon Tran, Jerry Li, and A. Mądry. Spectral Signatures in Backdoor Attacks. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2018. 3

[59] Alexander Turner, Dimitris Tsipras, and A. Mądry. Label-Consistent Backdoor Attacks. *arXiv preprint arXiv:1912.02771*, 2019. 2

[60] Eric Wallace, Tony Zhao, Shi Feng, and Sameer Singh. Concealed Data Poisoning Attacks on NLP Models. In *Conference of the North American Chapter of the ACL (NAACL)*, 2021. 2

[61] Matthew Walmer, Karan Sikka, Indranil Sur, Abhinav Shrivastava, and Susmit Jha. Dual-Key Multimodal Backdoors for Visual Question Answering. In *IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2021. 2

[62] Alexander Wan, Eric Wallace, Sheng Shen, and D. Klein. Poisoning Language Models During Instruction Tuning. In *International Conference on Machine Learning (ICML)*, 2023. 2

[63] Bolun Wang, Yuanshun Yao, Shawn Shan, Huiying Li, Bimal Viswanath, Hai-Tao Zheng, and Ben Y. Zhao. Neural Cleanse: Identifying and Mitigating Backdoor Attacks in Neural Networks. In *IEEE Symposium on Security and Privacy (S&P)*, 2019. 1, 3, 8

[64] Emily Wenger, Josephine Passananti, A. Bhagoji, Yuanshun Yao, Hai-Tao Zheng, and Ben Y. Zhao. Backdoor Attacks Against Deep Learning Systems in the Physical World. In *IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2020. 2

[65] Emily Wenger, Roma Bhattacharjee, A. Bhagoji, Josephine Passananti, Emilio Andere, Hai-Tao Zheng, and Ben Y. Zhao. Natural Backdoor Datasets. *arXiv preprint arXiv:2206.10673*, 2022. 2

[66] E. B. Wilson. Probable Inference, the Law of Succession, and Statistical Inference. *Journal of the American Statistical Association*, 1927. 4

[67] Baoyuan Wu, Hongrui Chen, Mingda Zhang, Zihao Zhu, Shaokui Wei, Danni Yuan, Chaoxiao Shen, and H. Zha. BackdoorBench: A Comprehensive Benchmark of Backdoor Learning. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2022. 2

[68] Jiashu Xu, Mingyu Derek Ma, Fei Wang, Chaowei Xiao, and Muhao Chen. Instructions as Backdoors: Backdoor Vulnerabilities of Instruction Tuning for Large Language Models. In *Conference of the North American Chapter of the ACL (NAACL)*, 2023. 2

[69] Jiashu Xu, Fei Wang, Mingyu Derek Ma, P. W. Koh, Chaowei Xiao, and Muhao Chen. Instructional Fingerprinting of Large Language Models. In *Conference of the North American Chapter of the ACL (NAACL)*, 2024. 1

[70] Xiao-Jun Xu, Qi Wang, Huichen Li, N. Borisov, Carl A. Gunter, and Bo Li. Detecting AI Trojans Using Meta Neural Analysis. In *IEEE Symposium on Security and Privacy (S&P)*, 2019. 3

[71] Yuancheng Xu, Jiarui Yao, Manli Shu, Yanchao Sun, Zichu Wu, Ning Yu, Tom Goldstein, and Furong Huang. Shadowcast: Stealthy Data Poisoning Attacks Against Vision-Language Models. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2024. 2

[72] Jun Yan, Vikas Yadav, SHIYANG LI, Lichang Chen, Zheng Tang, Hai Wang, Vijay Srinivasan, Xiang Ren, and Hong-Xia Jin. Backdooring Instruction-Tuned Large Language Models with Virtual Prompt Injection. In *Conference of the North American Chapter of the ACL (NAACL)*, 2023. 2

[73] Song-Lin Yang, Jan Kautz, and Ali Hatamizadeh. Gated Delta Networks: Improving Mamba2 with Delta Rule. In *International Conference on Learning Representations (ICLR)*, 2024. 4

[74] Yuanshun Yao, Huiying Li, Hai-Tao Zheng, and Ben Y. Zhao. Latent Backdoor Attacks on Deep Neural Networks. In *ACM SIGSAC Conference on Computer and Communications Security (CCS)*, 2019. 2

[75] Yi Zeng, Wei-Yu Sun, H. Tran, Dawn Song, Bo Li, and Ruo-Xi Jia. BEEAR: Embedding-based Adversarial Removal of Safety Backdoors in Instruction-tuned Language Models. In *Conference on Empirical Methods in Natural Language Processing (EMNLP)*, 2024. 1, 3, 8

[76] Xin-Yang Zhang, Zheng Zhang, Shou-Lin Ji, and Ting Wang. Trojaning Language Models for Fun and Profit. In *European Symposium on Security and Privacy*, 2020. 2

[77] Shuai Zhao, Meihuizi Jia, Zhong-Liang Guo, Leilei Gan, Xiao-Yu Xu, Xiao-Bao Wu, Jie Fu, Yichao Feng, Fengjun Pan, and Anh Tuan Luu. A Survey of Recent Backdoor Attacks and Defenses in Large Language Models. *arXiv preprint arXiv:2406.06852*, 2024. 2