# **Object-Oriented Programming**

David Carlson

February 3, 2020

Class and Instance

• Namespace: "mapping from names to objects"

- Namespace: "mapping from names to objects"
- Scope: level at which "a namespace is directly accessible"

- Namespace: "mapping from names to objects"
- Scope: level at which "a namespace is directly accessible"
- Python follows the hierarchy:

- Namespace: "mapping from names to objects"
- Scope: level at which "a namespace is directly accessible"
- Python follows the hierarchy:
  - Innermost scope: local names

- Namespace: "mapping from names to objects"
- Scope: level at which "a namespace is directly accessible"
- Python follows the hierarchy:
  - ▶ Innermost scope: local names
  - Scopes of enclosing functions, innermost first

- Namespace: "mapping from names to objects"
- Scope: level at which "a namespace is directly accessible"
- Python follows the hierarchy:
  - ► Innermost scope: local names
  - Scopes of enclosing functions, innermost first
  - ▶ Next-to-last scope: Global names in current module

- Namespace: "mapping from names to objects"
- Scope: level at which "a namespace is directly accessible"
- Python follows the hierarchy:
  - ► Innermost scope: local names
  - Scopes of enclosing functions, innermost first
  - Next-to-last scope: Global names in current module
  - Outermost scope: Built-in names such as int(), sum()

- Namespace: "mapping from names to objects"
- Scope: level at which "a namespace is directly accessible"
- Python follows the hierarchy:
  - ► Innermost scope: local names
  - Scopes of enclosing functions, innermost first
  - Next-to-last scope: Global names in current module
  - Outermost scope: Built-in names such as int(), sum()

```
>>> def print_int(int):
    ...: print('Here is an integer: %s' %int)
    ...:
```

 Although int is a built-in name, the function first searches local scope.

```
>>> def print_int(int):
    ...: print('Here is an integer: %s' %int)
    ...:
```

- Although int is a built-in name, the function first searches local scope.
- But, do not do this!

```
#Function that returns the product of random draws from a
    ...: uniform distribution

>>> def random_product(lower, upper):
    ...: random1
    ...: random2
    ...: return random1*random2
    ...:
>>> print(random_product(0,1))
```

```
#We need to define random1 and random2
#We need to import the random module
>>>
     import random
>>> def random_product(lower, upper):
            random1=uniform(lower,upper)
   . . . :
            random2=uniform(lower,upper)
   . . . :
   . . . :
            return random1*random2
   . . . :
   . . . :
     print(random_product(0,1))
#NameError: global name 'uniform' is not defined
```

```
#We need to add the module name before tha global name
     import random
>>> def random_product(lower,upper):
             random1=random.uniform(lower, upper)
    . . . :
             random2=random.uniform(lower, upper)
    . . . :
             return random1*random2
    . . . :
    . . . :
    . . . :
>>> print(random_product(0,1))
```

```
#Alternatively, we can import a particular function
>>> from random import uniform
>>> def random_product(lower,upper)
>>> def random_product(lower,upper):
            random1=uniform(lower, upper)
    . . . :
    ...: random2=uniform(lower, upper)
    ...: return random1*random2
>>> print(random_product(0,1))
```

• Classes helps you create objects with

- Classes helps you create objects with
  - certain attributes

- Classes helps you create objects with
  - certain attributes
  - ability to perform certain functions.

- Classes helps you create objects with
  - certain attributes
  - ability to perform certain functions.
- An instance is a particular realization of a class.

```
#Create a class
class human(object):
    latin_name='homo sapien' #Attribute for the class
#Create an instance of a class and name it 'me'.
me=human()
```

```
class human(object):
    latin_name='homo sapien' #Attribute for the class

#Add attributes for the instances.
    def __init__(self, age, sex, name): #initializer or constructor
        self.age = age
        self.name = name
        self.sex = sex
```

• You can set default values for attributes.

- You can set default values for attributes.
- Make sure you list non-default arguments first.

- You can set default values for attributes.
- Make sure you list non-default arguments first.

```
class human(object):
    latin_name='homo sapien' #Attribute for the class

#Add attributes for the instances.
    def __init__(self, age, sex, name=None): #initializer or constructor
        self.age = age
        self.name = name
        self.sex = sex
```

```
class human(object):
    latin_name='homo sapien' #Attribute for the class
    #Add attributes for the instances.
    def __init__(self, age, sex, name=None): #initializer or constructor
        self.age = age
        self.name = name
        self.sex = sex
    #Add some functions
    def speak(self, words):
        return words
    def introduce(self):
        if self.sex=='Female': return self.speak("Hello, I'm Ms, %s" % self.name)
        elif self.sex=='Male': return self.speak("Hello, I'm Mr. %s" % self.name)
        else: return self.speak("Hello, I'm %s" % name)
```

dir(human) lists all the methods of the class.

### Inheritance and Polymorphism

• Inheritance enables you to create sub-classes that inherit the methods of another class.

### Inheritance and Polymorphism

- Inheritance enables you to create sub-classes that inherit the methods of another class.
- Polymorphism adapts a given method of a class to its sub-classes.

### Inheritance and Polymorphism

- Inheritance enables you to create sub-classes that inherit the methods of another class.
- Polymorphism adapts a given method of a class to its sub-classes.
- Keep it DRY