

Primitives

Literals

Literals	Nil: nil Integer: 150I Long: 1500 Double: 3.569 Boolean: true, false BigDecimal: 6.897M String: "abcd", "ab\"cd", "PI: \u03C0" String: ""{"age": 42 }""
----------	--

Numbers

Arithmetic	+ - * / mod inc dec min max abs negate sqrt
Convert	int long double decimal
Compare	== != < > <= >= compare
Test	zero? pos? neg? even? odd? number? int? long? double? decimal?
Random	rand-long rand-double rand- gaussian
BigDecimal	dec/add dec/sub dec/mul dec/div dec/scale

Strings

Create	str str/format str/quote str /double-quote
Use	count compare empty-to-nil first last nth str/index-of str/last-index-of str/replace- first str/replace-last str /replace-all str/lower-case str /upper-case str/join str/subs str/split str/split-lines str /strip-start str/strip-end str /strip-indent str/strip-margin str/repeat str/truncate str /char str/lorem-ipsum
Regex	match? not-match?
Trim	str/trim str/trim-to-nil
Hex	str/hex-to-bytebuf str/bytebuf- to-hex str/format-bytebuf

Collections

Collections

Generic	count compare empty-to-nil empty into conj remove repeat repeatedly replace range group-by get-in seq
Tests	empty? not-empty? coll? list? vector? set? sorted-set? map? sequential? hash-map? ordered-map? sorted-map? mutable-map? bytebuf?
Process	map filter reduce keep docoll

Lists

Create	() list list*
Access	first second third nth last peek rest butlast nfirst nlast
Modify	cons conj rest pop into concat interpose interleave mapcat flatten reverse sort sort-by take take- while drop drop-while split-at split-with
Test	every? not-every? any? not-any?

Vectors

Create	[] vector mapv
Access	first second third nth last peek butlast rest nfirst nlast subvec
Modify	cons conj rest pop into concat distinct dedupe partition interpose interleave mapcat flatten reverse sort sort-by take take-while drop drop-while assoc-in get-in update update! split-with
Test	contains? every? not-every? any? not-any?

Sets

Create	#{} set sorted-set
Modify	cons conj disj difference union intersection

Encode/Decode	str/encode-base64 str/decode-base64 str/encode-url str/decode-url str/escape-html str/escape-xml
Test	string? empty? str/blank? str/starts-with? str/ends-with? str/contains? str>equals-ignore-case? str/digit? str/letter? str/whitespace? str/linefeed?
Other	
Keywords	:a :blue keyword? keyword
Symbols	'a 'blue symbol? symbol
Boolean	boolean not boolean? true? false?

Byte Buffer

Create	bytebuf bytebuf-from-string
Test	empty? not-empty? bytebuf?
Use	count bytebuf-to-string bytebuf-sub
Base64	str/encode-base64 str/decode-base64
Hex	str/hex-to-bytebuf str/bytebuf-to-hex str/format-bytebuf

Time

Date	time/date time/date?
Local Date	time/local-date time/local-date? time/local-date-parse
Local Date Time	time/local-date-time time/local-date-time? time/local-date-time-parse
Zoned Date Time	time/zoned-date-time time/zoned-date-time? time/zoned-date-time-parse
Fields	time/year time/month time/hour time/minute time/second time/length-of-year time/length-of-month time/day-of-week time/day-of-month time/day-of-year time/zone time/zone-offset
Format	time/formatter time/format
Test	time/after? time/not-after? time/before? time/not-before? time/within? time/leap-year?

Test	contains? every? not-every? any? not-any?
------	--

Maps

Create	{ } hash-map ordered-map sorted-map mutable-map zipmap
Access	find get keys vals key val
Modify	cons conj assoc assoc! assoc-in get-in update update! dissoc dissoc! into concat flatten reduce-kv merge map-invert
Test	contains?

Stack

Create	stack
Access	peek pop! push! count
Test	empty? stack?

Queue

Create	queue
Access	peek poll! offer! count
Test	empty? queue?

Arrays

Create	make-array object-array string-array int-array long-array float-array double-array
Use	aget aset alength asub acopy amap

Regex

General	regex/pattern regex/matcher regex/find regex/find-all regex/find-group regex/find-all-groups regex/reset regex/find? regex/matches regex/matches? regex/group regex/groupcount
---------	--

Concurrency

Atoms	atom atom? deref reset! swap! compare-and-set! add-watch remove-watch
Futures	

Miscellaneous	time/with-time	time/plus	time/minus	time/period	time/first-day-of-month	time/last-day-of-month	time/earliest	time/latest
Util	time/zone-ids	time/to-millis						

Functions

Create	fn	defn	defn-partial	defn-memoize	identity	comp		
Call	apply	->	->>					
Test	fn?							
Exception	throw							
Misc	nil?	some?	doc	eval	name	type	instance?	callstack
Meta	meta	with-meta	vary-meta					

Macros

Create	defn	defn-macro	defmacro	macroexpand	
Branch	and	or	when	when-not	if-let
Loop	list-comp	dotimes	while		
Call	doto	->	->>	-<>	as->
Loading	load-string	load-file	load-classpath-file	load-module	
Test	macro?	cond	case		
Assert	assert				
Util	comment	gensym	time	with-out-str	
Profiling	time	perf			

Transducers

Run	transduce				
Functions	map	filter	drop	drop-while	take
		take-while	keep	dedupe	

Special Forms

Forms	def	defonce	defmethod	defdynamic	defmulti	if	do	let	binding	fn
		loop	recur	set!	try	try-with				

	future	future?	future-done?	future-cancel	future-cancelled?	deref	realized?					
Promises	promise	promise?	deliver	realized?								
Delay	delay	delay?	deref	force	realized?							
Agents	agent	send	send-off	restart-agent	set-error-handler!	agent-error	await	await-for	shutdown-agents	shutdown-agents?	await-termination-agents	await-termination-agents?
Scheduler	schedule-delay	schedule-at-fixed-rate										
ThreadLocal	thread-local	thread-local?	thread-local-clear	assoc	dissoc	get						
Util	thread-id	thread-name										

System

Test	sandboxed?	os-type?										
Other	version	os-type	system-prop	java-version	uuid	sleep	gc	pid	shutdown-hook	current-time-millis	nano-time	coalesce
Shell	sh	with-sh-dir	with-sh-env	with-sh-throw								

Java Interoperability

General	.	proxify	import	java-obj?	java-iterator-to-list	java-enumeration-to-list
	Invoke	constructors				
	Invoke	static	or	instance	methods	
	Access	static	or	instance	fields	

IO

to	print	println	printf	flush	newline
to-str	pr-str	with-out-str			
from	readline	read-string			
file-io	io/file	io/file-parent	io/file-name	io/file-path	io/file-absolute-path
	io/file-canonical-path	io/list-files			
	io/file-size	io/delete-file	io		

Miscellaneous		
JSON	json/write-str json/read-str json/spit json/slurp json /pretty-print	
XML	xml/parse-str xml/parse xml /path-> xml/children xml/text	
PDF	pdf/available? pdf/render pdf /watermark pdf/merge pdf/copy pdf/pages pdf/text-to-pdf	
Cryptography	crypt/md5-hash crypt/sha512-hash crypt/pbkdf2-hash crypt/encrypt crypt/decrypt	

	/delete-file-on-exit io/copy-file io/move-file io/mkdir io/mkdirs io/slurp io/slurp-lines io/spit io/download io/tmp-dir io/user-dir io/temp-file
file-io test	io/file? io/exists-file? io/exists- dir? io/file-can-read? io/file-can- write? io/file-can-execute? io /file-hidden?
stream-io	io/copy-stream io/slurp-stream io /spit-stream io/uri-stream io/wrap- os-with-buffered-writer io/wrap-os- with-print-writer io/wrap-is-with- buffered-reader
zip	io/zip io/zip-file io/zip-list io /zip-append io/zip-remove io/zip? io/unzip io/unzip-first io/unzip- nth io/unzip-all io/unzip-to-dir
gzip	io/gzip io/gzip-to-stream io/gzip? io/ungzip io/ungzip-to-stream
other	io/load-classpath-resource io/mime- type io/default-charset with-out- str

Embedding in Java

Eval

```
import com.github.jlangch.venice.Venice;

public class Example {
    public static void main(String[] args) {
        Venice venice = new Venice();

        Long val = (Long)venice.eval("(+ 1 2)");
    }
}
```

Passing parameters

```
import com.github.jlangch.venice.Venice;
import com.github.jlangch.venice.Parameters;

public class Example {
    public static void main(String[] args) {
        Venice venice = new Venice();

        Long val = (Long)venice.eval(
            "(+ x y 3)",
            Parameters.of("x", 6, "y", 3L));
    }
}
```

Precompiled

```
import com.github.jlangch.venice.Venice;
import com.github.jlangch.venice.PreCompiled;

public class Example {
    public static void main(String[] args) {
        Venice venice = new Venice();

        PreCompiled precompiled = venice.precompile("example", "(+ 1 x)");

        for(int ii=0; ii<100; ii++) {
            venice.eval(precompiled, Parameters.of("x", ii));
        }
    }
}
```

Java Interop

```
import java.time.ZonedDateTime;
import com.github.jlangch.venice.Venice;

public class Example {
    public static void main(String[] args) {
        Venice venice = new Venice();

        Long val = (Long)venice.eval("(.:java.lang.Math :min 20 30)");

        ZonedDateTime ts = (ZonedDateTime)venice.eval(
```

```

        "(. (. :java.time.ZonedDateTime :now) :plusDays 5)");
    }
}

```

Sandbox

```

import com.github.jlangch.venice.Venice;
import com.github.jlangch.venice.javainterop.*;

public class Example {
    public static void main(String[] args) {
        final IInterceptor interceptor =
            new SandboxInterceptor(
                new SandboxRules()
                    .rejectAllVeniceIoFunctions()
                    .allowAccessToStandardSystemProperties()
                    .withClasses(
                        "java.lang.Math:min",
                        "java.time.ZonedDateTime:*",
                        "java.util.ArrayList:new",
                        "java.util.ArrayList:add"));

        final Venice venice = new Venice(interceptor);

        // => OK (static method)
        venice.eval("(. :java.lang.Math :min 20 30)");

        // => OK (constructor & instance method)
        venice.eval("(. (. :java.time.ZonedDateTime :now) :plusDays 5)");

        // => OK (constructor & instance method)
        venice.eval(
            "(doto (. :java.util.ArrayList :new) " +
            "      (. :add 1) " +
            "      (. :add 2))");

        // => FAIL (invoking non whitelisted static method)
        venice.eval("(. :java.lang.System :exit 0)");

        // => FAIL (invoking rejected Venice I/O function)
        venice.eval("(io/slurp \"/tmp/file\")");

        // => FAIL (accessing non whitelisted system property)
        venice.eval("(system-prop \"db.password\")");
    }
}

```

Function details

top

!=

(!= x y)

Returns true if both operands do not have the equivalent type

(!= 0 1)
=> true

(!= 0 0)
=> false

(!= 0 0.0)
=> true

top

#{ }

Creates a set.

#{10 20 30}
=> #{10 20 30}

top

()

Creates a list.

'(10 20 30)
=> (10 20 30)

top

*

(*)
(* x)
(* x y)
(* x y & more)

Returns the product of numbers. (*) returns 1

```
(*)
=> 1

(* 4)
=> 4

(* 4 3)
=> 12

(* 4 3 2)
=> 24

(* (int 4) (int 3))
=> 12I

(* 6.0 2)
=> 12.0

(* 6 1.5M)
=> 9.0M
```

[top](#)

+

```
(+)
(+ x)
(+ x y)
(+ x y & more)
```

Returns the sum of the numbers. (+) returns 0.

```
(+)
=> 0

(+ 1)
=> 1

(+ 1 2)
=> 3

(+ 1 2 3 4)
=> 10

(+ (int 1) (int 2))
=> 3I

(+ 1 2.5)
=> 3.5

(+ 1 2.5M)
=> 3.5M
```

[top](#)

-

```
(- x)
(- x y)
```



```
(- x y & more)
```

If one number is supplied, returns the negation, else subtracts the numbers from x and returns the result.

```
(- 4)
```

```
=> -4
```

```
(- 8 3 -2 -1)
```

```
=> 8
```

```
(- (int 5) (int 2))
```

```
=> 3I
```

```
(- 8 2.5)
```

```
=> 5.5
```

```
(- 8 1.5M)
```

```
=> 6.5M
```

[top](#)

```
-<>
```

```
(-<> x & forms)
```

Threads the x through the forms. Inserts x at position of the <> symbol of the first form, making a list of it if it is not a list already. If there are more forms, inserts the first form at position of the <> symbol in second form, etc.

```
(-<> 5
```

```
  (+ <> 3)
```

```
  (/ 2 <>)
```

```
  (- <> 1))
```

```
=> -1
```

[top](#)

```
->
```

```
(-> x & forms)
```

Threads the x through the forms. Inserts x as the second item in the first form, making a list of it if it is not a list already. If there are more forms, inserts the first form as the second item in second form, etc.

```
(-> 5 (+ 3) (/ 2) (- 1))
```

```
=> 3
```

```
(do
```

```
  (def person
```

```
    {:name "Peter Meier"
```

```
     :address {:street "Lindenstrasse 45"
```

```
               :city "Bern"
```

```
               :zip 3000}})
```

```
  (-> person :address :street))
```

```
=> "Lindenstrasse 45"
```

[top](#)

->>

```
(->> x & forms)
```

Threads the x through the forms. Inserts x as the last item in the first form, making a list of it if it is not a list already. If there are more forms, inserts the first form as the last item in second form, etc.

```
(->> 5 (+ 3) (/ 32) (- 1))  
=> -3
```

```
(->> [ {:a 1 :b 2} {:a 3 :b 4} {:a 5 :b 6} {:a 7 :b 8} ]  
      (map (fn [x] (get x :b)))  
      (filter (fn [x] (> x 4)))  
      (map inc)))  
=> (7 9)
```

top

.

```
(. classname :new args)  
(. classname method-name args)  
(. classname field-name)  
(. classname :class)  
(. object method-name args)  
(. object field-name)  
(. object :class)
```

Java interop. Calls a constructor or an class/object method or accesses a class/instance field. The function is sandboxed.

```
;; invoke constructor  
(. :java.lang.Long :new 10)  
=> 10  
  
;; invoke static method  
(. :java.time.ZonedDateTime :now)  
=> 2019-07-14T16:09:08.092+02:00[Europe/Zurich]  
  
;; invoke static method  
(. :java.lang.Math :min 10 20)  
=> 10  
  
;; access static field  
(. :java.lang.Math :PI)  
=> 3.141592653589793  
  
;; invoke method  
(. (. :java.lang.Long :new 10) :toString)  
=> "10"  
  
;; get class name  
(. :java.lang.Math :class)  
=> class java.lang.Math  
  
;; get class name  
(. (. :java.io.File :new "/temp") :class)  
=> class java.io.File
```

/

```
(/ x)
(/ x y)
(/ x y & more)
```

If no denominators are supplied, returns 1/numerator, else returns numerator divided by all of the denominators.

```
(/ 2.0)
=> 0.5

(/ 12 2 3)
=> 2

(/ 12 3)
=> 4

(/ (int 12) (int 3))
=> 4I

(/ 6.0 2)
=> 3.0

(/ 6 1.5M)
=> 4.0000000000000000M
```

<

```
(< x y)
```

Returns true if x is smaller than y

```
(< 2 3)
=> true

(< 2 3.0)
=> true

(< 2 3.0M)
=> true
```

<=

```
(<= x y)
```

Returns true if x is smaller or equal to y

```
(<= 2 3)
=> true

(<= 3 3)
```

```
=> true

(<= 2 3.0)
=> true

(<= 2 3.0M)
=> true
```

[top](#)

==

```
(== x y)
```

Returns true if both operands have the equivalent type

```
(== 0 0)
=> true

(== 0 1)
=> false

(== 0 0.0)
=> false
```

[top](#)

>

```
(> x y)
```

Returns true if x is greater than y

```
(> 3 2)
=> true

(> 3 3)
=> false

(> 3.0 2)
=> true

(> 3.0M 2)
=> true
```

[top](#)

>=

```
(>= x y)
```

Returns true if x is greater or equal to y

```
(>= 3 2)
=> true
```

```
(>= 3 3)
=> true

(>= 3.0 2)
=> true

(>= 3.0M 2)
=> true
```

[top](#)

Creates a vector.

```
[10 20 30]
=> [10 20 30]
```

[top](#)

abs

```
(abs x)
```

Returns the absolute value of the number

```
(abs 10)
=> 10
```

```
(abs -10)
=> 10
```

```
(abs (int -10))
=> 10I
```

```
(abs -10.1)
=> 10.1
```

```
(abs -10.12M)
=> 10.12M
```

[top](#)

acopy

```
(acopy src src-pos dest dest-pos dest-len)
```

Copies an array from the src array, beginning at the specified position, to the specified position of the dest array. Returns the modified destination array

```
(acopy (long-array '(1 2 3 4 5)) 2 (long-array 20) 10 3)
=> [0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 3, 4, 5, 0, 0, 0, 0, 0, 0]
```

[top](#)

add-watch

```
(add-watch ref key fn)
```

Adds a watch function to an agent/atom reference. The watch fn must be a fn of 4 args: a key, the reference, its old-state, its new-state.

```
(do
  (def x (agent 10))
  (defn watcher [key ref old new]
    (println "watcher: " key))
  (add-watch x :test watcher))
=> nil
```

[top](#)

agent

```
(agent state & options)
```

Creates and returns an agent with an initial value of state and zero or more options.

Options:

```
:error-handler handler-fn
:error-mode mode-keyword
```

The handler-fn is called if an action throws an exception. It's a function taking two args the agent and the exception. The mode-keyword may be either :continue (the default) or :fail

```
(do
  (def x (agent 100))
  (send x + 5)
  (sleep 100)
  (deref x))
=> 105
```

[top](#)

agent-error

```
(agent-error agent)
```

Returns the exception thrown during an asynchronous action of the agent if the agent is failed. Returns nil if the agent is not failed.

```
(do
  (def x (agent 100 :error-mode :fail))
  (send x (fn [n] (/ n 0)))
  (sleep 500)
  (agent-error x))
=> com.github.jlangch.venice.VncException: / by zero
```

[top](#)

aget

```
(aget array idx)
```

Returns the value at the index of an array of Java Objects

```
(aget (long-array '(1 2 3 4 5)) 1)
=> 2
```

[top](#)

alength

```
(alength array)
```

Returns the length of an array

```
(alength (long-array '(1 2 3 4 5)))
=> 5
```

[top](#)

amap

```
(amap f arr)
```

Applies *f* to each item in the array *arr*. Returns a new array with the mapped values.

```
(str (amap (fn [x] (+ 1 x)) (long-array 6 0)))
=> "[1, 1, 1, 1, 1, 1]"
```

[top](#)

and

```
(and x)
(and x & next)
```

Ands the predicate forms

```
(and true true)
=> true
```

```
(and true false)
=> false
```

[top](#)

any?

```
(any? pred coll)
```

Returns true if the predicate is true for at least one collection item, false otherwise

aset

```
(aset array idx val)
```

Sets the value at the index of an array

```
(aset (long-array '(1 2 3 4 5)) 1 20)
=> [1, 20, 3, 4, 5]
```

[top](#)

assert

```
(assert expr)
(assert expr message)
```

Evaluates `expr` and throws an exception if it does not evaluate to logical true.

[top](#)

assoc

```
(assoc coll key val)
(assoc coll key val & kvs)
```

When applied to a map, returns a new map of the same type, that contains the mapping of key(s) to val(s). When applied to a vector, returns a new vector that contains val at index. Note - index must be <= (count vector).

```
(assoc {} :a 1 :b 2)
=> {:a 1 :b 2}
```

```
(assoc nil :a 1 :b 2)
=> {:a 1 :b 2}
```

```
(assoc [1 2 3] 0 10)
=> [10 2 3]
```

```
(assoc [1 2 3] 3 10)
=> [1 2 3 10]
```

[top](#)

assoc!

```
(assoc! coll key val)
(assoc! coll key val & kvs)
```

Associates key/vals with a mutable map, returns the map

```
(assoc! (mutable-map) :a 1 :b 2)
=> {:a 1 :b 2}
```

```
(assoc! nil :a 1 :b 2)
=> {:a 1 :b 2}
```

[top](#)

assoc-in

```
(assoc-in m ks v)
```

Associates a value in a nested associative structure, where `ks` is a sequence of keys and `v` is the new value and returns a new nested structure. If any levels do not exist, hash-maps or vectors will be created.

```
(do
  (def users [{:name "James" :age 26} {:name "John" :age 43}])
  (assoc-in users [1 :age] 44))
=> [{:age 26 :name "James"} {:age 44 :name "John"}]

(do
  (def users [{:name "James" :age 26} {:name "John" :age 43}])
  (assoc-in users [2] {:name "Jack" :age 19}) )
=> [{:age 26 :name "James"} {:age 43 :name "John"} {:age 19 :name "Jack"}]
```

[top](#)

asub

```
(asub array start len)
```

Returns a sub array

```
(asub (long-array '(1 2 3 4 5)) 2 3)
=> [3, 4, 5]
```

[top](#)

atom

```
(atom x)
```

Creates an atom with the initial value `x`

```
(do
  (def counter (atom 0))
  (deref counter))
=> 0
```

[top](#)

atom?

```
(atom? x)
```

Returns true if `x` is an atom, otherwise false

```
(do
  (def counter (atom 0))
  (atom? counter))
=> true
```

[top](#)

await

```
(await agents)
```

Blocks the current thread (indefinitely) until all actions dispatched thus far (from this thread or agent) to the agents have occurred.

```
(do
  (def x1 (agent 100))
  (def x2 (agent 100))
  (await x1 x2))
=> true
```

[top](#)

await-for

```
(await-for timeout-ms agents)
```

Blocks the current thread until all actions dispatched thus far (from this thread or agent) to the agents have occurred, or the timeout (in milliseconds) has elapsed. Returns logical false if returning due to timeout, logical true otherwise.

```
(do
  (def x1 (agent 100))
  (def x2 (agent 100))
  (await-for 500 x1 x2))
=> true
```

[top](#)

await-termination-agents

```
(shutdown-agents )
```

Blocks until all actions have completed execution after a shutdown request, or the timeout occurs, or the current thread is interrupted, whichever happens first.

```
(do
  (def x1 (agent 100))
  (def x2 (agent 100))
  (shutdown-agents )
  (await-termination-agents 1000))
```

[top](#)

await-termination-agents?

```
(await-termination-agents?)
```

Returns true if all tasks have been completed following agent shut down

```
(do
  (def x1 (agent 100))
  (def x2 (agent 100))
  (shutdown-agents )
  (await-termination-agents 1000))
(sleep 300)
(await-termination-agents? ))
```

[top](#)

binding

```
(binding [bindings*] exprs*)
```

Evaluates the expressions and binds the values to dynamic (thread-local) symbols

```
(do
  (binding [x 100]
    (println x)
    (binding [x 200]
      (println x))
    (println x)))
100
200
100
=> nil
```

[top](#)

boolean

```
(boolean x)
```

Converts to boolean. Everything except 'false' and 'nil' is true in boolean context.

```
(boolean false)
=> false
```

```
(boolean true)
=> true
```

```
(boolean nil)
=> false
```

[top](#)

boolean?

```
(boolean? n)
```

Returns true if n is a boolean

```
(boolean? true)
=> true

(boolean? false)
=> true

(boolean? nil)
=> false

(boolean? 0)
=> false
```

[top](#)

butlast

```
(butlast coll)
```

Returns a collection with all but the last list element

```
(butlast nil)
=> nil

(butlast [])
=> []

(butlast [1])
=> []

(butlast [1 2 3])
=> [1 2]

(butlast '())
=> ()

(butlast '(1))
=> ()

(butlast '(1 2 3))
=> (1 2)
```

[top](#)

bytebuf

```
(bytebuf x)
```

Converts to bytebuf. x can be a bytebuf, a list/vector of longs, or a string

```
(bytebuf [0 1 2])
=> [0 1 2]

(bytebuf '(0 1 2))
=> [0 1 2]

(bytebuf "abc")
=> [97 98 99]
```

bytebuf-from-string

```
(bytebuf-from-string s encoding)
```

Converts a string to a bytebuf using an optional encoding. The encoding defaults to :UTF-8

```
(bytebuf-from-string "abcdef" :UTF-8)  
=> [97 98 99 100 101 102]
```

bytebuf-sub

```
(bytebuf-sub x start) (bytebuf-sub x start end)
```

Returns a byte buffer of the items in buffer from start (inclusive) to end (exclusive). If end is not supplied, defaults to (count bytebuffer)

```
(bytebuf-sub (bytebuf [1 2 3 4 5 6]) 2)  
=> [3 4 5 6]
```

```
(bytebuf-sub (bytebuf [1 2 3 4 5 6]) 4)  
=> [5 6]
```

bytebuf-to-string

```
(bytebuf-to-string buf encoding)
```

Converts a bytebuf to a string using an optional encoding. The encoding defaults to :UTF-8

```
(bytebuf-to-string (bytebuf [97 98 99]) :UTF-8)  
=> "abc"
```

bytebuf?

```
(bytebuf? x)
```

Returns true if x is a bytebuf

```
(bytebuf? (bytebuf [1 2]))  
=> true
```

```
(bytebuf? [1 2])  
=> false
```

```
(bytebuf? nil)  
=> false
```

callstack

```
(callstack )
```

Returns the current callstack.

```
(do
  (defn f1 [x] (f2 x))
  (defn f2 [x] (f3 x))
  (defn f3 [x] (f4 x))
  (defn f4 [x] (callstack))
  (f1 100))
=> [[:fn-name "callstack" :file "example" :line 5 :col 18] {:fn-name "f4" :file "example" :line 4 :col 18} {:fn-
name "f3" :file "example" :line 3 :col 18} {:fn-name "f2" :file "example" :line 2 :col 18} {:fn-name "f1" :file
"example" :line 6 :col 5}]
```

case

```
(case expr & clauses)
```

Takes an expression and a set of clauses. Each clause takes the form of test-constant result-expr

```
(case (+ 1 9)
  10 :ten
  20 :twenty
  30 :thirty
  :dont-know)
=> :ten
```

coalesce

```
(coalesce args*)
```

Returns the first non nil arg

```
(coalesce )
=> nil

(coalesce 1 2)
=> 1

(coalesce nil)
=> nil

(coalesce nil 1 2)
=> 1
```

coll?

```
(coll? obj)
```

Returns true if obj is a collection

```
(coll? {:a 1})  
=> true
```

```
(coll? [1 2])  
=> true
```

[top](#)

comment

```
(comment & body)
```

Ignores body, yields nil

```
(comment  
  (println 1)  
  (println 5))  
=> nil
```

[top](#)

comp

```
(comp f*)
```

Takes a set of functions and returns a fn that is the composition of those fns. The returned fn takes a variable number of args, applies the rightmost of fns to the args, the next fn (right-to-left) to the result, etc.

```
((comp str +) 8 8 8)  
=> "24"
```

```
(map (comp - (partial + 3) (partial * 2)) [1 2 3 4])  
=> (-5 -7 -9 -11)
```

```
((reduce comp [(partial + 1) (partial * 2) (partial + 3)]) 100)  
=> 207
```

```
(filter (comp not zero?) [0 1 0 2 0 3 0 4])  
=> [1 2 3 4]
```

```
(do  
  (def fifth (comp first rest rest rest rest))  
  (fifth [1 2 3 4 5]))  
=> 5
```

[top](#)

compare


```
(compare x y)
```

Comparator. Returns -1, 0, or 1 when x is logically 'less than', 'equal to', or 'greater than' y. For list and vectors the longer sequence is always 'greater' regardless of its contents. For sets and maps only the size of the collection is compared.

```
(compare nil 0)
=> -1

(compare 0 nil)
=> 1

(compare 1 0)
=> 1

(compare 1 1)
=> 0

(compare 1M 2M)
=> -1

(compare 1 nil)
=> 1

(compare nil 1)
=> -1

(compare "aaa" "bbb")
=> -1

(compare [0 1 2] [0 1 2])
=> 0

(compare [0 1 2] [0 9 2])
=> -1

(compare [0 9 2] [0 1 2])
=> 1

(compare [1 2 3] [0 1 2 3])
=> -1

(compare [0 1 2] [3 4])
=> 1
```

[top](#)

compare-and-set!

```
(compare-and-set! atom oldval newval)
```

Atomically sets the value of atom to newval if and only if the current value of the atom is identical to oldval. Returns true if set happened, else false

```
(do
  (def counter (atom 2))
  (compare-and-set! counter 2 4)
  (deref counter))
=> 4
```

concat

```
(concat coll)
(concat coll & colls)
```

Returns a collection of the concatenation of the elements in the supplied colls.

```
(concat [1 2])
=> (1 2)

(concat [1 2] [4 5 6])
=> (1 2 4 5 6)

(concat '(1 2))
=> (1 2)

(concat '(1 2) [4 5 6])
=> (1 2 4 5 6)

(concat {:a 1})
=> ([:a 1])

(concat {:a 1} {:b 2 :c 3})
=> ([:a 1] [:b 2] [:c 3])

(concat "abc")
=> ("a" "b" "c")

(concat "abc" "def")
=> ("a" "b" "c" "d" "e" "f")
```

cond

```
(cond & clauses)
```

Takes a set of test/expr pairs. It evaluates each test one at a time. If a test returns logical true, cond evaluates and returns the value of the corresponding expr and doesn't evaluate any of the other tests or exprs. (cond) returns nil.

```
(let [n 5]
  (cond
    (< n 0) "negative"
    (> n 0) "positive"
    :else "zero"))
=> "positive"
```

conj

```
(conj)
(conj x)
(conj coll x)
```

```
(conj coll x & xs)
```

Returns a new collection with the x, xs 'added'. (conj nil item) returns (item). The 'addition' may happen at different 'places' depending on the concrete type.

```
(conj [1 2 3] 4)
=> [1 2 3 4]
```

```
(conj '(1 2 3) 4)
=> (4 1 2 3)
```

```
(conj (set 1 2 3) 4)
=> #{1 2 3 4}
```

```
(conj )
=> []
```

```
(conj 4)
=> 4
```

[top](#)

cons

```
(cons x coll)
```

Returns a new collection where x is the first element and coll is the rest

```
(cons 1 '(2 3 4 5 6))
=> (1 2 3 4 5 6)
```

```
(cons [1 2] [4 5 6])
=> [[1 2] 4 5 6]
```

```
(cons 3 (set 1 2))
=> #{1 2 3}
```

[top](#)

contains?

```
(contains? coll key)
```

Returns true if key is present in the given collection, otherwise returns false.

```
(contains? {:a 1 :b 2} :a)
=> true
```

```
(contains? [10 11 12] 1)
=> true
```

```
(contains? [10 11 12] 5)
=> false
```

```
(contains? "abc" 1)
=> true
```

```
(contains? "abc" 5)
=> false
```

count

```
(count coll)
```

Returns the number of items in the collection. (count nil) returns 0. Also works on strings, and Java Collections

```
(count {:a 1 :b 2})
=> 2
```

```
(count [1 2])
=> 2
```

```
(count "abc")
=> 3
```

crypt/decrypt

```
(crypt/decrypt algorithm passphrase & options)
```

Returns a new function to decrypt a string or a bytebuf given the algorithm and passphrase. If a string is passed it is base64 decoded, decrypted, and returned as string. If a bytebuf is passed the decrypted bytebuf is returned.

Supported algorithms: "DES", "3DES", "AES256"

Options:

:url-safe enabled

The boolean option directs the base64 decoder to decode standard or URL safe base64 encoded strings.

If enabled (true) the base64 decoder will convert '-' and '_' characters back to '+' and '/' before decoding.

Defaults to false.

```
(do
  (load-module :crypt)
  (def decrypt (crypt/encrypt "3DES" "secret" :url-safe true))
  (decrypt "ndmW1NLSdHA") ; => "hello"
  (decrypt "KPYjndkZ8vM") ; => "world"
  (decrypt (bytebuf [234 220 237 189 12 176 242 147])))
=> [192 19 255 241 144 162 159 77 53 176 196 254 163 194 211 219]
```

crypt/encrypt

```
(crypt/encrypt algorithm passphrase & options)
```

Returns a new function to encrypt a string or a bytebuf given the algorithm and passphrase. If a string is passed it is encrypted and returned as a base64 encoded string. If a bytebuf is passed the encrypted bytebuf is returned.

Supported algorithms: "DES", "3DES", "AES256"

Options:

`:url-safe` enabled

The boolean option directs the base64 encoder to emit standard or URL safe base64 encoded strings.

If enabled (true) the base64 encoder will emit '-' and '_' instead of the usual '+' and '/' characters.

Defaults to false.

Note: no padding is added when encoding using the URL-safe alphabet.

```
(do
  (load-module :crypt)
  (def encrypt (crypt/encrypt "3DES" "secret" :url-safe true))
  (encrypt "hello") ; => "ndmW1NLsDHA"
  (encrypt "world") ; => "KPYjndkZ8vM"
  (encrypt (bytebuf [1 2 3 4 5])))
=> [234 220 237 189 12 176 242 147]
```

[top](#)

crypt/md5-hash

(crypt/md5-hash data)

Hashes a string or a bytebuf using MD5. Note: MD5 is not safe any more use PBKDF2.

```
(do
  (load-module :crypt)
  (str/bytebuf-to-hex
    (crypt/md5-hash "hello world")
    :upper))
=> "5EB63BBBE01EEED093CB22BB8F5ACDC3"
```

[top](#)

crypt/pbkdf2-hash

(crypt/pbkdf2-hash text salt)
(crypt/pbkdf2-hash text salt iterations key-length)

Hashes a string using PBKDF2. iterations default to 1000, key-length defaults to 256

```
(do
  (load-module :crypt)
  (str/bytebuf-to-hex
    (crypt/pbkdf2-hash "hello world" "-salt-")
    :upper))
=> "54F2B4411E8817C2A0743B2A7DD7EAE5AA3F748D1DDDC00766380914AFFE995"
```

```
(do
  (load-module :crypt)
  (str/bytebuf-to-hex
    (crypt/pbkdf2-hash "hello world" "-salt-" 1000 256)
    :upper))
=> "54F2B4411E8817C2A0743B2A7DD7EAE5AA3F748D1DDDC00766380914AFFE995"
```

[top](#)

crypt/sha512-hash

```
(crypt/sha512-hash data)
(crypt/sha512-hash data salt)
```

Hashes a string or a bytebuf using SHA512 with an optional salt.

```
(do
  (load-module :crypt)
  (str/bytebuf-to-hex
    (crypt/sha512-hash "hello world")
    :upper))
=>
"309ECC489C12D6EB4CC40F50C902F2B4D0ED77EE511A7C7A9BCD3CA86D4CD86F989DD35BC5FF499670DA34255B45B0CFD830E81F605DCF7DC55"
```

[top](#)

current-time-millis

```
(current-time-millis)
```

Returns the current time in milliseconds.

```
(current-time-millis)
=> 1563113348073
```

[top](#)

dec

```
(dec x)
```

Decrements the number x

```
(dec 10)
=> 9
```

```
(dec (int 10))
=> 9I
```

```
(dec 10.1)
=> 9.1
```

```
(dec 10.12M)
=> 9.12M
```

[top](#)

dec/add

```
(dec/add x y scale rounding-mode)
```

Adds two decimals and scales the result. rounding-mode is one of (:CEILING, :DOWN, :FLOOR, :HALF_DOWN, :HALF_EVEN, :HALF_UP, :UNNECESSARY, :UP)

```
(dec/add 2.44697M 1.79882M 3 :HALF_UP)
=> 4.246M
```

[top](#)

dec/div

```
(dec/div x y scale rounding-mode)
```

Divides x by y and scales the result. rounding-mode is one of (:CEILING, :DOWN, :FLOOR, :HALF_DOWN, :HALF_EVEN, :HALF_UP, :UNNECESSARY, :UP)

```
(dec/div 2.44697M 1.79882M 5 :HALF_UP)
=> 1.36032M
```

[top](#)

dec/mul

```
(dec/mul x y scale rounding-mode)
```

Multiplies two decimals and scales the result. rounding-mode is one of (:CEILING, :DOWN, :FLOOR, :HALF_DOWN, :HALF_EVEN, :HALF_UP, :UNNECESSARY, :UP)

```
(dec/mul 2.44697M 1.79882M 5 :HALF_UP)
=> 4.40166M
```

[top](#)

dec/scale

```
(dec/scale x scale rounding-mode)
```

Scales a decimal. rounding-mode is one of (:CEILING, :DOWN, :FLOOR, :HALF_DOWN, :HALF_EVEN, :HALF_UP, :UNNECESSARY, :UP)

```
(dec/scale 2.44697M 0 :HALF_UP)
=> 2M
```

```
(dec/scale 2.44697M 1 :HALF_UP)
=> 2.4M
```

```
(dec/scale 2.44697M 2 :HALF_UP)
=> 2.45M
```

```
(dec/scale 2.44697M 3 :HALF_UP)
=> 2.447M
```

```
(dec/scale 2.44697M 10 :HALF_UP)
=> 2.4469700000M
```

[top](#)

dec/sub

```
(dec/sub x y scale rounding-mode)
```

Subtract y from x and scales the result. rounding-mode is one of (:CEILING, :DOWN, :FLOOR, :HALF_DOWN, :HALF_EVEN, :HALF_UP, :UNNECESSARY, :UP)

```
(dec/sub 2.44697M 1.79882M 3 :HALF_UP)
=> 0.648M
```

[top](#)

decimal

```
(decimal x) (decimal x scale rounding-mode)
```

Converts to decimal. rounding-mode is one of (:CEILING, :DOWN, :FLOOR, :HALF_DOWN, :HALF_EVEN, :HALF_UP, :UNNECESSARY, :UP)

```
(decimal 2)
=> 2M
```

```
(decimal 2 3 :HALF_UP)
=> 2.000M
```

```
(decimal 2.5787 3 :HALF_UP)
=> 2.579M
```

```
(decimal 2.5787M 3 :HALF_UP)
=> 2.579M
```

```
(decimal "2.5787" 3 :HALF_UP)
=> 2.579M
```

```
(decimal nil)
=> 0M
```

[top](#)

decimal?

```
(decimal? n)
```

Returns true if n is a decimal

```
(decimal? 4.0M)
=> true
```

```
(decimal? 4.0)
=> false
```

```
(decimal? 3)
=> false
```

```
(decimal? 3I)
=> false
```

[top](#)

dedupe

```
(dedupe coll)
```

Returns a collection with all consecutive duplicates removed. Returns a transducer when no collection is provided.

```
(dedupe [1 2 2 2 3 4 4 2 3])  
=> [1 2 3 4 2 3]
```

```
(dedupe '(1 2 2 2 3 4 4 2 3))  
=> (1 2 3 4 2 3)
```

[top](#)

def

```
(def name expr)
```

Creates a global variable.

```
(def x 5)  
=> 5
```

```
(def sum (fn [x y] (+ x y)))  
=> function anonymous-6a1b2762-c089-48fb-a562-0ef1f6040fec {visibility :public, module "example"}
```

[top](#)

def-dynamic

```
(def-dynamic name expr)
```

Creates a dynamic variable that starts off as a global variable and can be bound with 'binding' to a new value on the local thread.

```
(do  
  (def-dynamic x 100)  
  (println x)  
  (binding [x 200]  
    (println x))  
  (println x))  
100  
200  
100  
=> nil
```

[top](#)

defmacro

```
(defmacro name [params*] body)
```

Macro definition

```
(defmacro unless [pred a b]
  `(if (not ~pred) ~a ~b))
=> macro unless {visibility :public, module "example"}
```

[top](#)

defmethod

```
(defmethod multifn-name dispatch-val & fn-tail)
```

Creates a new method for a multimethod associated with a dispatch-value.

```
(do
  ;;defmulti with dispatch function
  (defmulti salary (fn[amount] (amount :t)))

  ;;defmethod provides a function implementation for a particular value
  (defmethod salary "com" [amount] (+ (:b amount) (/ (:b amount) 2)))
  (defmethod salary "bon" [amount] (+ (:b amount) 99))
  (defmethod salary :default [amount] (:b amount))

  [(salary {:t "com" :b 1000})
   (salary {:t "bon" :b 1000})
   (salary {:t "xxx" :b 1000})]
)
=> [1500 1099 1000]
```

[top](#)

defmulti

```
(defmulti name dispatch-fn)
```

Creates a new multimethod with the associated dispatch function.

```
(do
  ;;defmulti with dispatch function
  (defmulti salary (fn[amount] (amount :t)))

  ;;defmethod provides a function implementation for a particular value
  (defmethod salary "com" [amount] (+ (:b amount) (/ (:b amount) 2)))
  (defmethod salary "bon" [amount] (+ (:b amount) 99))
  (defmethod salary :default [amount] (:b amount))

  [(salary {:t "com" :b 1000})
   (salary {:t "bon" :b 1000})
   (salary {:t "xxx" :b 1000})]
)
=> [1500 1099 1000]
```

[top](#)

defn

```
(defn name [args*] condition-map? expr*)
(defn name ([args*] condition-map? expr*)+)
```

Same as (def name (fn name [args*] condition-map? expr*)) or (def name (fn name ([args*] condition-map? expr*) +))

```
(defn sum [x y] (+ x y))  
=> function sum {visibility :public, module "example"}
```

```
(defn sum [x y] { :pre [(> x 0)] } (+ x y))  
=> function sum {visibility :public, module "example"}
```

[top](#)

defn-

```
(defn- name [args*] condition-map? expr*)  
(defn- name ([args*] condition-map? expr*)+)
```

Same as defn, yielding non-public def

```
(defn- sum [x y] (+ x y))  
=> function sum {visibility :private, module "example"}
```

[top](#)

defonce

```
(defonce name expr)
```

Creates a global variable that can not be overwritten

```
(defonce x 5)  
=> 5
```

[top](#)

delay

```
(delay & body)
```

Takes a body of expressions and yields a Delay object that will invoke the body only the first time it is forced (with force or deref/@), and will cache the result and return it on all subsequent force calls

```
(do  
  (def x (delay (println "working...") 100))  
  (deref x))  
working...  
=> 100
```

[top](#)

delay?

```
(delay? x)
```

Returns true if x is a Delay created with delay

```
(do
  (def x (delay (println "working...") 100))
  (delay? x))
=> true
```

[top](#)

deliver

```
(deliver ref value)
```

Delivers the supplied value to the promise, releasing any pending derefs. A subsequent call to deliver on a promise will have no effect.

```
(do
  (def p (promise))
  (deliver p 123))
=> nil
```

[top](#)

deref

```
(deref x)
(deref x timeout-ms timeout-val)
```

Dereferences an atom or a Future object. When applied to an atom, returns its current state. When applied to a future, will block if computation not complete. The variant taking a timeout can be used for futures and will return timeout-val if the timeout (in milliseconds) is reached before a value is available. Also reader macro: @atom/@future/@promise.

```
(do
  (def counter (atom 10))
  (deref counter))
=> 10

(do
  (def counter (atom 10))
  @counter)
=> 10

(do
  (def task (fn [] 100))
  (let [f (future task)]
    (deref f)))
=> 100

(do
  (def task (fn [] 100))
  (let [f (future task)]
    @f))
=> 100

(do
  (def task (fn [] 100))
  (let [f (future task)]
    (deref f 300 :timeout)))
```

```
=> 100
```

```
(do
  (def x (delay (println "working...") 100))
  @x)
working...
=> 100
```

[top](#)

difference

```
(difference s1)
(difference s1 s2)
(difference s1 s2 & sets)
```

Return a set that is the first set without elements of the remaining sets

```
(difference (set 1 2 3))
=> #{1 2 3}

(difference (set 1 2) (set 2 3))
=> #{1}

(difference (set 1 2) (set 1) (set 1 4) (set 3))
=> #{2}
```

[top](#)

disj

```
(disj coll x)
(disj coll x & xs)
```

Returns a new set with the x, xs removed.

```
(disj (set 1 2 3) 3)
=> #{1 2}
```

[top](#)

dissoc

```
(dissoc coll key)
(dissoc coll key & ks)
```

Returns a new coll of the same type, that does not contain a mapping for key(s)

```
(dissoc {:a 1 :b 2 :c 3} :b)
=> {:a 1 :c 3}

(dissoc {:a 1 :b 2 :c 3} :c :b)
=> {:a 1}
```

[top](#)

dissoc!

```
(dissoc! coll key)
(dissoc! coll key & ks)
```

Dissociates keys from a mutable map, returns the map

```
(dissoc! (mutable-map :a 1 :b 2 :c 3) :b)
=> {:a 1 :c 3}

(dissoc! (mutable-map :a 1 :b 2 :c 3) :c :b)
=> {:a 1}
```

[top](#)

distinct

```
(distinct coll)
```

Returns a collection with all duplicates removed

```
(distinct [1 2 3 4 2 3 4])
=> [1 2 3 4]

(distinct '(1 2 3 4 2 3 4))
=> (1 2 3 4)
```

[top](#)

do

```
(do exprs)
```

Evaluates the expressions in order and returns the value of the last.

```
(do (println "Test...") (+ 1 1))
Test...
=> 2
```

[top](#)

doc

```
(doc name)
```

Prints documentation for a var or special form given its name

```
(doc +)
(+), (+ x), (+ x y), (+ x y & more)
```

Returns the sum of the numbers. (+) returns 0.

Examples:
(+)

```
(+ 1)

(+ 1 2)

(+ 1 2 3 4)

(+ (int 1) (int 2))

(+ 1 2.5)

(+ 1 2.5M)
```

```
=> nil
```

[top](#)

docoll

```
(docoll f coll)
```

Applies `f` to the items of the collection presumably for side effects. Returns `nil`.

```
(docoll #(println %) [1 2 3 4])
1
2
3
4
=> nil

(docoll
  (fn [[k v]] (println (pr-str k v))))
{:a 1 :b 2 :c 3 :d 4})
:a 1
:b 2
:c 3
:d 4
=> nil
```

[top](#)

dorun

```
(dorun count expr)
```

Runs the `expr` `count` times in the most effective way. It's main purpose is supporting performance test.

```
(dorun 10 (+ 1 1))
=> 2
```

[top](#)

dotimes

```
(dotimes bindings & body)
```

Repeatedly executes body with name bound to integers from 0 through n-1.

```
(dotimes [n 3] (println (str "n is " n)))  
n is 0  
n is 1  
n is 2  
=> nil
```

[top](#)

doto

(doto x & forms)

Evaluates x then calls all of the methods and functions with the value of x supplied at the front of the given arguments. The forms are evaluated in order. Returns x.

```
(doto (. :java.util.HashMap :new)  
      (. :put :a 1)  
      (. :put :b 2))  
=> {"a" 1 "b" 2}
```

[top](#)

double

(double x)

Converts to double

```
(double 1)  
=> 1.0  
  
(double nil)  
=> 0.0  
  
(double false)  
=> 0.0  
  
(double true)  
=> 1.0  
  
(double 1.2)  
=> 1.2  
  
(double 1.2M)  
=> 1.2  
  
(double "1.2")  
=> 1.2
```

[top](#)

double-array

(double-array coll)
(double-array len)


```
(double-array len init-val)
```

Returns an array of Java primitive doubles containing the contents of coll or returns an array with the given length and optional init value

```
(double-array '(1.0 2.0 3.0))  
=> [1.0, 2.0, 3.0]
```

```
(double-array '(1I 2 3.2 3.56M))  
=> [1.0, 2.0, 3.2, 3.56]
```

```
(double-array 10)  
=> [0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0]
```

```
(double-array 10 42.0)  
=> [42.0, 42.0, 42.0, 42.0, 42.0, 42.0, 42.0, 42.0, 42.0, 42.0]
```

[top](#)

double?

```
(double? n)
```

Returns true if n is a double

```
(double? 4.0)  
=> true
```

```
(double? 3)  
=> false
```

```
(double? 3I)  
=> false
```

```
(double? 3.0M)  
=> false
```

```
(double? true)  
=> false
```

```
(double? nil)  
=> false
```

```
(double? {})  
=> false
```

[top](#)

drop

```
(drop n coll)
```

Returns a collection of all but the first n items in coll. Returns a transducer when no collection is provided.

```
(drop 3 [1 2 3 4 5])  
=> [5]
```

```
(drop 10 [1 2 3 4 5])  
=> []
```

drop-while

```
(drop-while predicate coll)
```

Returns a list of the items in `coll` starting from the first item for which `(predicate item)` returns logical false. Returns a transducer when no collection is provided.

```
(drop-while neg? [-2 -1 0 1 2 3])  
=> [0 1 2 3]
```

empty

```
(empty coll)
```

Returns an empty collection of the same category as `coll`, or `nil`

```
(empty {:a 1})  
=> {}
```

```
(empty [1 2])  
=> []
```

```
(empty '(1 2))  
=> ()
```

empty-to-nil

```
(empty-to-nil x)
```

Returns `nil` if `x` is empty

```
(empty-to-nil "")  
=> nil
```

```
(empty-to-nil [])  
=> nil
```

```
(empty-to-nil '())  
=> nil
```

```
(empty-to-nil {})  
=> nil
```

empty?

```
(empty? x)
```

Returns true if x is empty

```
(empty? {})  
=> true
```

```
(empty? [])  
=> true
```

```
(empty? '())  
=> true
```

```
(empty? "")  
=> true
```

[top](#)

eval

```
(eval form)
```

Evaluates the form data structure (not text!) and returns the result.

```
(eval '(let [a 10] (+ 3 4 a)))  
=> 17
```

```
(eval (list + 1 2 3))  
=> 6
```

```
(let [s "(+ 2 x)" x 10]  
      (eval (read-string s)))  
=> 12
```

[top](#)

even?

```
(even? n)
```

Returns true if n is even, throws an exception if n is not an integer

```
(even? 4)  
=> true
```

```
(even? 3)  
=> false
```

```
(even? (int 3))  
=> false
```

[top](#)

every?

```
(every? pred coll)
```

Returns true if the predicate is true for all collection items, false otherwise

```
(every? number? nil)
=> false

(every? number? [])
=> false

(every? number? [1 2 3 4])
=> true

(every? number? [1 2 3 :a])
=> false

(every? #(>= % 10) [10 11 12])
=> true
```

[top](#)

false?

```
(false? x)
```

Returns true if x is false, false otherwise

```
(false? true)
=> false

(false? false)
=> true

(false? nil)
=> false

(false? 0)
=> false

(false? (== 1 2))
=> true
```

[top](#)

filter

```
(filter predicate coll)
```

Returns a collection of the items in coll for which (predicate item) returns logical true. Returns a transducer when no collection is provided.

```
(filter even? [1 2 3 4 5 6 7])
=> [2 4 6]
```

[top](#)

find

```
(find map key)
```

Returns the map entry for key, or nil if key not present.

```
(find {:a 1 :b 2} :b)
=> [:b 2]
```

```
(find {:a 1 :b 2} :z)
=> nil
```

[top](#)

first

```
(first coll)
```

Returns the first element of coll.

```
(first nil)
=> nil
```

```
(first [])
=> nil
```

```
(first [1 2 3])
=> 1
```

```
(first '())
=> nil
```

```
(first '(1 2 3))
=> 1
```

```
(first "abc")
=> "a"
```

[top](#)

flatten

```
(flatten coll)
```

Takes any nested combination of collections (lists, vectors, etc.) and returns their contents as a single, flat sequence. (flatten nil) returns an empty list.

```
(flatten [])
=> []
```

```
(flatten [[1 2 3] [4 5 6] [7 8 9]])
=> [1 2 3 4 5 6 7 8 9]
```

[top](#)

float-array

```
(float-array coll)
```

```
(float-array len)
(float-array len init-val)
```

Returns an array of Java primitive floats containing the contents of `coll` or returns an array with the given length and optional `init` value

```
(float-array '(1.0 2.0 3.0))
=> [1.0, 2.0, 3.0]

(float-array '(1I 2 3.2 3.56M))
=> [1.0, 2.0, 3.200000047683716, 3.559999942779541]

(float-array 10)
=> [0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0]

(float-array 10 42.0)
=> [42.0, 42.0, 42.0, 42.0, 42.0, 42.0, 42.0, 42.0, 42.0, 42.0]
```

[top](#)

flush

```
(flush)
(flush os)
```

Without `arg` flushes the output stream that is the current value of `*out*`. With `arg` flushes the passed output stream

```
(flush)
=> nil

(flush *out*)
=> nil
```

[top](#)

fn

```
(fn name? [params*] condition-map? expr*)
```

Defines an anonymous function.

```
(do (def sum (fn [x y] (+ x y))) (sum 2 3))
=> 5

(map (fn double [x] (* 2 x)) (range 1 5))
=> (2 4 6 8)

(map #(* 2 %) (range 1 5))
=> (2 4 6 8)

(map #(* 2 %1) (range 1 5))
=> (2 4 6 8)

;; anonymous function with two params, the second is destructured
(reduce (fn [m [k v]] (assoc m v k)) {} {:b 2 :a 1 :c 3})
=> {1 :a 2 :b 3 :c}

;; defining a pre-condition
```

```
(do
  (def square-root
    (fn [x]
      { :pre [(>= x 0)] }
      (. :java.lang.Math :sqrt x)))
  (square-root 4))
=> 2.0

;; higher-order function
(do
  (def discount
    (fn [percentage]
      { :pre [(and (>= percentage 0) (<= percentage 100))] }
      (fn [price] (- price (* price percentage 0.01)))))
  ((discount 50) 300))
=> 150.0
```

[top](#)

fn?

```
(fn? x)
```

Returns true if x is a function

```
(do
  (def sum (fn [x] (+ 1 x)))
  (fn? sum))
=> true
```

[top](#)

force

```
(force x)
```

If x is a Delay, returns its value, else returns x

```
(do
  (def x (delay (println "working...") 100))
  (force x))
working...
=> 100
```

[top](#)

future

```
(future fn)
```

Takes a function and yields a future object that will invoke the function in another thread, and will cache the result and return it on all subsequent calls to deref. If the computation has not yet finished, calls to deref will block, unless the variant of deref with timeout is used. Thread local vars will be inherited by the future child thread. Changes of the child's thread local vars will not be seen on the parent.

```
(do
  (def wait (fn [] (do (sleep 500) 100)))
  (let [f (future wait)]
    (deref f)))
=> 100

;; demonstrates the use of thread locals with futures
(do
  ;; parent thread locals
  (binding [a 10 b 20]
    ;; future with child thread locals
    (let [f (future (fn [] (binding [b 90] {:a a :b b})))
          {:child @f :parent {:a a :b b}})])
=> {:parent {:a 10 :b 20} :child {:a 10 :b 90}}
```

[top](#)

future-cancel

```
(future-cancel f)
```

Cancels the future

```
(do
  (def wait (fn [] (do (sleep 400) 100)))
  (let [f (future wait)]
    (sleep 50)
    (printf "After 50ms: cancelled=%b\n" (future-cancelled? f))
    (future-cancel f)
    (sleep 100)
    (printf "After 150ms: cancelled=%b\n" (future-cancelled? f))))
After 50ms: cancelled=false
After 150ms: cancelled=true
=> nil
```

[top](#)

future-cancelled?

```
(future-cancelled? f)
```

Returns true if f is a Future is cancelled otherwise false

```
(future-cancelled? (future (fn [] 100)))
=> false
```

[top](#)

future-done?

```
(future-done? f)
```

Returns true if f is a Future is done otherwise false

```
(do
  (def wait (fn [] (do (sleep 200) 100)))
```



```
(let [f (future wait)]
  (sleep 50)
  (printf "After 50ms: done=%b\n" (future-done? f))
  (sleep 300)
  (printf "After 300ms: done=%b\n" (future-done? f)))
After 50ms: done=false
After 300ms: done=true
=> nil
```

[top](#)

future?

```
(future? f)
```

Returns true if f is a Future otherwise false

```
(future? (future (fn [] 100)))
=> true
```

[top](#)

gc

```
(gc)
```

Run the Java garbage collector. Runs the finalization methods of any objects pending finalization prior to the GC.

```
(gc)
=> nil
```

[top](#)

gensym

```
(gensym)
(gensym prefix)
```

Generates a symbol.

```
(gensym )
=> G__3
```

```
(gensym "prefix_")
=> prefix_4
```

[top](#)

get

```
(get map key)
(get map key not-found)
```

Returns the value mapped to key, not-found or nil if key not present.

```
(get {:a 1 :b 2} :b)
=> 2
```

```
;; keywords act like functions on maps
(:b {:a 1 :b 2})
=> 2
```

[top](#)

get-in

```
(get-in m ks)
(get-in m ks not-found)
```

Returns the value in a nested associative structure, where ks is a sequence of keys. Returns nil if the key is not present, or the not-found value if supplied.

```
(get-in {:a 1 :b {:c 2 :d 3}} [:b :c])
=> 2
```

```
(get-in [:a :b :c] [0])
=> :a
```

```
(get-in [:a :b [:c :d :e]] [2 1])
=> :d
```

```
(get-in {:a 1 :b {:c [4 5 6]}} [:b :c 1])
=> 5
```

[top](#)

group-by

```
(group-by f coll)
```

Returns a map of the elements of coll keyed by the result of f on each element. The value at each key will be a vector of the corresponding elements, in the order they appeared in coll.

```
(group-by count ["a" "as" "asd" "aa" "asdf" "qwer"])
=> {1 ["a"] 2 ["as" "aa"] 3 ["asd"] 4 ["asdf" "qwer"]}
```

```
(group-by odd? (range 10))
=> {false [0 2 4 6 8] true [1 3 5 7 9]}
```

[top](#)

hash-map

```
(hash-map & keyvals)
(hash-map map)
```

Creates a new hash map containing the items.

```
(hash-map :a 1 :b 2)
=> {:a 1 :b 2}

(hash-map (sorted-map :a 1 :b 2))
=> {:a 1 :b 2}
```

[top](#)

hash-map?

```
(hash-map? obj)
```

Returns true if obj is a hash map

```
(hash-map? (hash-map :a 1 :b 2))
=> true
```

[top](#)

identity

```
(identity x)
```

Returns its argument.

```
(identity 4)
=> 4
```

```
(filter identity [1 2 3 nil 4 false true 1234])
=> [1 2 3 4 true 1234]
```

[top](#)

if

```
(if test true-expr false-expr)
```

Evaluates test.

```
(if (< 10 20) "yes" "no")
=> "yes"
```

[top](#)

if-let

```
(if-let bindings then)
(if-let bindings then else)
```

bindings is a vector with 2 elements: binding-form test.
If test is true, evaluates then with binding-form bound to the value of test, if not, yields else

```
(if-let [value (* 100 2)]
  (str "The expression is true. value=" value))
```

```
(str "The expression is false.")(
=> "The expression is true. value=200"
```

[top](#)

import

```
(import class)
```

Imports a Java class

```
(do
  (import :java.lang.Long)
  (. :Long :new 10))
=> 10
```

[top](#)

inc

```
(inc x)
```

Increments the number x

```
(inc 10)
=> 11
```

```
(inc (int 10))
=> 11I
```

```
(inc 10.1)
=> 11.1
```

```
(inc 10.12M)
=> 11.12M
```

[top](#)

instance?

```
(instance? type x)
```

Returns true if x is an instance of the given type

```
(instance? :venice.Long 500)
=> true
```

```
(instance? :java.math.BigInteger 500)
=> false
```

[top](#)

int

```
(int x)
```

Converts to int

```
(int 1)
```

```
=> 1I
```

```
(int nil)
```

```
=> 0I
```

```
(int false)
```

```
=> 0I
```

```
(int true)
```

```
=> 1I
```

```
(int 1.2)
```

```
=> 1I
```

```
(int 1.2M)
```

```
=> 1I
```

```
(int "1")
```

```
=> 1I
```

[top](#)

int-array

```
(int-array coll)
```

```
(int-array len)
```

```
(int-array len init-val)
```

Returns an array of Java primitive ints containing the contents of coll or returns an array with the given length and optional init value

```
(int-array '(1I 2I 3I))
```

```
=> [1I, 2I, 3I]
```

```
(int-array '(1I 2 3.2 3.56M))
```

```
=> [1I, 2I, 3I, 3I]
```

```
(int-array 10)
```

```
=> [0I, 0I, 0I, 0I, 0I, 0I, 0I, 0I, 0I, 0I]
```

```
(int-array 10 42I)
```

```
=> [42I, 42I, 42I, 42I, 42I, 42I, 42I, 42I, 42I, 42I]
```

[top](#)

int?

```
(int? n)
```

Returns true if n is an int

```
(int? 4I)
```

```
=> true
```

```
(int? 4)
=> false

(int? 3.1)
=> false

(int? true)
=> false

(int? nil)
=> false

(int? {})
=> false
```

[top](#)

interleave

```
(interleave c1 c2)
(interleave c1 c2 & colls)
```

Returns a collection of the first item in each coll, then the second etc.

```
(interleave [:a :b :c] [1 2])
=> (:a 1 :b 2)
```

[top](#)

interpose

```
(interpose sep coll)
```

Returns a collection of the elements of coll separated by sep.

```
(interpose ", " [1 2 3])
=> (1 ", " 2 ", " 3)
```

```
(apply str (interpose ", " [1 2 3]))
=> "1, 2, 3"
```

[top](#)

intersection

```
(intersection s1)
(intersection s1 s2)
(intersection s1 s2 & sets)
```

Return a set that is the intersection of the input sets

```
(intersection (set 1))
=> #{1}
```

```
(intersection (set 1 2) (set 2 3))
=> #{2}
```

```
(intersection (set 1 2) (set 3 4))
=> #{} 
```

[top](#)

into

```
(into to-coll from-coll)
```

Returns a new coll consisting of to-coll with all of the items of from-coll conjoined.

```
(into (sorted-map) [ [:a 1] [:c 3] [:b 2] ] )
=> {:a 1 :b 2 :c 3}
```

```
(into (sorted-map) [ {:a 1} {:c 3} {:b 2} ] )
=> {:a 1 :b 2 :c 3}
```

```
(into [] {1 2, 3 4})
=> [[1 2] [3 4]]
```

```
(into '() '(1 2 3))
=> (3 2 1)
```

```
(into [1 2 3] '(4 5 6))
=> [1 2 3 4 5 6]
```

```
(into '() (bytebuf [0 1 2]))
=> (0 1 2)
```

```
(into [] (bytebuf [0 1 2]))
=> [0 1 2]
```

```
(into '() "abc")
=> ("a" "b" "c")
```

```
(into [] "abc")
=> ["a" "b" "c"]
```

```
(into (sorted-map) {:b 2 :c 3 :a 1})
=> {:a 1 :b 2 :c 3}
```

```
(do
  (into (. :java.util.concurrent.CopyOnWriteArrayList :new)
    (doto (. :java.util.ArrayList :new)
      (. :add 3)
      (. :add 4))))

=> (3 4)
```

```
(do
  (into (. :java.util.concurrent.CopyOnWriteArrayList :new)
    '(3 4)))

=> (3 4)
```

[top](#)

io/copy-file

```
(io/copy-file source dest)
```

Copies source to dest. Returns nil or throws IOException. Source must be a file or a string (file path), dest must be a file, a string (file path), or an OutputStream.

[top](#)

io/copy-stream

```
(io/copy-file in-stream out-stream)
```

Copies input stream to an output stream. Returns nil or throws IOException. Input and output must be a java.io.InputStream and java.io.OutputStream.

[top](#)

io/default-charset

```
(io/default-charset)
```

Returns the default charset.

[top](#)

io/delete-file

```
(io/delete-file f & files)
```


Downloads the content from the uri and reads it as text (string) or binary (bytebuf).

Options:

:binary true/false - e.g :binary true, defaults to false
:encoding enc - e.g :encoding :utf-8, defaults to :utf-8

[top](#)

io/exists-dir?

```
(io/exists-dir? f)
```

Returns true if the file f exists and is a directory. f must be a file or a string (file path).

```
(io/exists-dir? (io/file "/temp"))  
=> false
```

[top](#)

io/exists-file?

```
(io/exists-file? f)
```

Returns true if the file f exists. f must be a file or a string (file path).

```
(io/exists-file? "/temp/test.txt")  
=> false
```

[top](#)

io/file

```
(io/file path) (io/file parent child)
```

Returns a java.io.File. path, parent, may be a file or a string (file path) child must be a string

```
(io/file "/temp/test.txt")  
=> /temp/test.txt
```

```
(io/file "/temp" "test.txt")  
=> /temp/test.txt
```

```
(io/file (io/file "/temp") "test.txt")  
=> /temp/test.txt
```

```
(io/file (. :java.io.File :new "/temp/test.txt"))  
=> /temp/test.txt
```

[top](#)

io/file-absolute-path

```
(io/file-absolute-path f)
```

Returns the absolute path of the file `f`. `f` must be a file or a string (file path).

```
(io/file-absolute-path (io/file "/tmp/test/x.txt"))  
=> "/tmp/test/x.txt"
```

[top](#)

io/file-can-execute?

```
(io/file-can-execute? f)
```

Returns true if the file or directory `f` exists and can be executed. `f` must be a file or a string (file path).

```
(io/file-can-execute? "/temp/test.txt")
```

[top](#)

io/file-can-read?

```
(io/file-can-read? f)
```

Returns true if the file or directory `f` exists and can be read. `f` must be a file or a string (file path).

```
(io/file-can-read? "/temp/test.txt")
```

[top](#)

io/file-can-write?

```
(io/file-can-write? f)
```

Returns true if the file or directory `f` exists and can be written. `f` must be a file or a string (file path).

```
(io/file-can-write? "/temp/test.txt")
```

[top](#)

io/file-canonical-path

```
(io/file-canonical-path f)
```

Returns the canonical path of the file `f`. `f` must be a file or a string (file path).

```
(io/file-canonical-path (io/file "/tmp/test/../x.txt"))  
=> "/private/tmp/x.txt"
```

[top](#)

io/file-hidden?

```
(io/file-hidden? f)
```

Returns true if the file or directory `f` exists and is hidden. `f` must be a file or a string (file path).

```
(io/file-hidden? "/tmp/test.txt")
```

[top](#)

io/file-name

```
(io/file-name f)
```

Returns the name of the file `f`. `f` must be a file or a string (file path).

```
(io/file-name (io/file "/tmp/test/x.txt"))  
=> "x.txt"
```

[top](#)

io/file-parent

```
(io/file-parent f)
```

Returns the parent file of the file `f`. `f` must be a file or a string (file path).

```
(io/file-path (io/file-parent (io/file "/tmp/test/x.txt")))  
=> "/tmp/test"
```

[top](#)

io/file-path

```
(io/file-path f)
```

Returns the path of the file `f`. `f` must be a file or a string (file path).

```
(io/file-path (io/file "/tmp/test/x.txt"))  
=> "/tmp/test/x.txt"
```

[top](#)

io/file-size

```
(io/file-size f)
```

Returns the size of the file `f`. `f` must be a file or a string (file path).

```
(io/file-size "/bin/sh")  
=> 618480
```

[top](#)

io/file?

```
(io/file? x)
```

Returns true if x is a java.io.File.

```
(io/file? (io/file "/temp/test.txt"))  
=> true
```

[top](#)

io/gzip

```
(io/gzip f)
```

gzipt f. f may be a file, a string (file path), a bytebuf or an InputStream. Returns a bytebuf.

```
(->> (io/gzip "a.txt")  
      (io/spit "a.gz"))
```

```
(io/gzip (bytebuf-from-string "abcdef" :utf-8))
```

[top](#)

io/gzip-to-stream

```
(io/gzip f os)
```

gzipt f to the OutputStream os. f may be a file, a string (file path), a bytebuf, or an InputStream.

```
(do  
  (import :java.io.ByteArrayOutputStream)  
  (try-with [os (. :ByteArrayOutputStream :new)]  
    (-> (bytebuf-from-string "abcdef" :utf-8)  
          (io/gzip-to-stream os))  
    (-> (. os :toByteArray)  
          (io/ungzip)  
          (bytebuf-to-string :utf-8))))  
=> "abcdef"
```

[top](#)

io/gzip?

```
(io/gzip? f)
```

Returns true if f is a gzipped file. f may be a file, a string (file path), a bytebuf, or an InputStream

```
(-> (io/gzip (bytebuf-from-string "abc" :utf-8))    (io/gzip?))  
=> true
```

[top](#)

io/list-files

```
(io/list-files dir filterFn?)
```

Lists files in a directory. `dir` must be a file or a string (file path). `filterFn` is an optional filter that filters the files found.

[top](#)

io/load-classpath-resource

```
(io/load-classpath-resource name)
```

Loads a classpath resource.

[top](#)

io/mime-type

```
(io/mime-type file)
```

Returns the mime-type for the file if available else nil.

```
(io/mime-type "document.pdf")  
=> "application/pdf"
```

```
(io/mime-type (io/file "document.pdf"))  
=> "application/pdf"
```

[top](#)

io/mkdir

```
(io/mkdir dir)
```

Creates the directory. `dir` must be a file or a string (file path).

[top](#)

io/mkdirs

```
(io/mkdirs dir)
```

Creates the directory including any necessary but nonexistent parent directories. `dir` must be a file or a string (file path).

[top](#)

io/move-file

```
(io/move-file source target)
```

Moves source to target. Returns nil or throws IOException. Source and target must be a file or a string (file path).

[top](#)

io/slurp

```
(io/slurp f & options)
```

Reads the content of file f as text (string) or binary (bytebuf). f may be a file, a string file path, a Java InputStream, or a Java Reader.

Options:

- :binary true/false - e.g :binary true, defaults to false
- :encoding enc - e.g :encoding :utf-8, defaults to :utf-8

[top](#)

io/slurp-lines

```
(io/slurp-lines file & options)
```

Read all lines from f. f may be a file, a string file path, a Java InputStream, or a Java Reader.

Options:

- :encoding enc - e.g :encoding :utf-8, defaults to :utf-8

[top](#)

io/slurp-stream

```
(io/slurp-stream is & options)
```

Slurps binary or string data from a Java InputStream. Supports the option :binary to either slurp binary or string data. For string data an optional encoding can be specified.

Options:

- :binary true/false - e.g :binary true, defaults to false
- :encoding enc - e.g :encoding :utf-8, defaults to :utf-8

```
(do
  (import :java.io.FileInputStream)
  (let [file (io/temp-file "test-", ".txt")]
    (io/delete-file-on-exit file)
    (io/spit file "123456789" :append true)
    (try-with [is (. :FileInputStream :new file)]
```

```
(io/slurp-stream is :binary false)))
)
=> "123456789"
```

[top](#)

io/spit

```
(io/spit f content & options)
```

Opens `f`, writes `content`, and then closes `f`. `f` may be a file or a string (file path). The content may be a string or a bytebuf.

Options:

- `:append true/false` - e.g `:append true`, defaults to `false`
- `:encoding enc` - e.g `:encoding :utf-8`, defaults to `:utf-8`

[top](#)

io/spit-stream

```
(io/spit-stream os content & options)
```

Writes `content` (string or bytebuf) to the Java `OutputStream` `os`. If `content` is of type string an optional encoding (defaults to UTF-8) is supported. The stream can optionally be flushed after the operation.

Options:

- `:flush true/false` - e.g `:flush true`, defaults to `false`
- `:encoding enc` - e.g `:encoding :utf-8`, defaults to `:utf-8`

```
(do
  (import :java.io.FileOutputStream)
  (let [file (io/temp-file "test-", ".txt")]
    (io/delete-file-on-exit file)
    (try-with [os (. :FileOutputStream :new file)]
      (io/spit-stream os "123456789" :flush true)))
)
=> nil
```

[top](#)

io/temp-file

```
(io/temp-file prefix suffix)
```

Creates an empty temp file with prefix and suffix.

```
(do
  (let [file (io/temp-file "test-", ".txt")]
    (io/spit file "123456789" :append true)
    (io/slurp file :binary false :remove true))
)
=> "123456789"
```

[top](#)

io/tmp-dir

```
(io/tmp-dir)
```

Returns the tmp dir as a `java.io.File`.

```
(io/tmp-dir )  
=> /var/folders/rm/pjqr5pln3db4mxh5qq1j5yh80000gn/T
```

[top](#)

io/ungzip

```
(io/ungzip f)
```

ungzips `f`. `f` may be a file, a string (file path), a bytebuf, or an `InputStream`. Returns a bytebuf.

```
(-> (bytebuf-from-string "abcdef" :utf-8)  
    (io/gzip)  
    (io/ungzip))  
=> [97 98 99 100 101 102]
```

[top](#)

io/ungzip-to-stream

```
(io/ungzip-to-stream buf)
```

ungzips a bytebuf returning an `InputStream` to read the deflated data from.

```
(-> (bytebuf-from-string "abcdef" :utf-8)  
    (io/gzip)  
    (io/ungzip-to-stream)  
    (io/slurp-stream :binary false :encoding :utf-8))  
=> "abcdef"
```

[top](#)

io/unzip

```
(io/unzip f entry-name)
```

Unzips an entry from zip `f` the entry's data as a bytebuf. `f` may be a bytebuf, a file, a string (file path) or an `InputStream`.

```
(-> (io/zip "a.txt" (bytebuf-from-string "abcdef" :utf-8))  
    (io/unzip "a.txt"))  
=> [97 98 99 100 101 102]
```

[top](#)

io/unzip-all


```
(io/unzip-all f)
```

Unzips all entries of the zip `f` returning a map with the entry names as key and the entry data as `bytebuf` values. `f` may be a `bytebuf`, a file, a string (file path) or an `InputStream`.

```
(-> (io/zip "a.txt" (bytebuf-from-string "abc" :utf-8)
          "b.txt" (bytebuf-from-string "def" :utf-8)
          "c.txt" (bytebuf-from-string "ghi" :utf-8))
    (io/unzip-all))
=> {"a.txt" [97 98 99] "b.txt" [100 101 102] "c.txt" [103 104 105]}
```

[top](#)

io/unzip-first

```
(io/unzip-first zip)
```

Unzips the first entry of the zip `f` returning its data as a `bytebuf`. `f` may be a `bytebuf`, a file, a string (file path) or an `InputStream`.

```
(-> (io/zip "a.txt" (bytebuf-from-string "abc" :utf-8)
          "b.txt" (bytebuf-from-string "def" :utf-8))
    (io/unzip-first))
=> [97 98 99]
```

[top](#)

io/unzip-nth

```
(io/unzip-nth zip n)
```

Unzips the `nth` (zero.based) entry of the zip `f` returning its data as a `bytebuf`. `f` may be a `bytebuf`, a file, a string (file path) or an `InputStream`.

```
(-> (io/zip "a.txt" (bytebuf-from-string "abc" :utf-8)
          "b.txt" (bytebuf-from-string "def" :utf-8)
          "c.txt" (bytebuf-from-string "ghi" :utf-8))
    (io/unzip-nth 1))
=> [100 101 102]
```

[top](#)

io/unzip-to-dir

```
(io/unzip-to-dir f dir)
```

Unzips `f` to a directory. `f` may be a file, a string (file path), a `bytebuf`, or an `InputStream`.

```
(-> (io/zip "a.txt" (bytebuf-from-string "abc" :utf-8)
          "b.txt" (bytebuf-from-string "def" :utf-8)
          "c.txt" (bytebuf-from-string "ghi" :utf-8))
    (io/unzip-to-dir "."))
```

[top](#)

io/uri-stream

```
(io/uri-stream uri)
```

Returns a Java InputStream from the uri.

[top](#)

io/user-dir

```
(io/user-dir)
```

Returns the user dir (current working dir) as a java.io.File.

[top](#)

io/wrap-is-with-buffered-reader

```
(io/wrap-is-with-buffered-reader is encoding?)
```

Wraps an InputStream with a BufferedReader using an optional encoding (defaults to :utf-8).

```
(do
  (import :java.io.ByteArrayInputStream)
  (let [data (byte-array [108 105 110 101 32 49 10 108 105 110 101 32 50])]
    is (. :ByteArrayInputStream :new data)
    rd (io/wrap-is-with-buffered-reader is :utf-8)]
  (println (. rd :readLine))
  (println (. rd :readLine))))
line 1
line 2
=> nil
```

[top](#)

io/wrap-os-with-buffered-writer

```
(io/wrap-os-with-buffered-writer os encoding?)
```

Wraps an OutputStream with a BufferedWriter using an optional encoding (defaults to :utf-8).

```
(do
  (import :java.io.ByteArrayOutputStream)
  (let [os (. :ByteArrayOutputStream :new)
        wr (io/wrap-os-with-buffered-writer os :utf-8)]
    (. wr :write "line 1")
    (. wr :newLine)
    (. wr :write "line 2")
    (. wr :flush)
    (. os :toArray)))
=> [108 105 110 101 32 49 10 108 105 110 101 32 50]
```

io/wrap-os-with-print-writer

```
(io/wrap-os-with-print-writer os encoding?)
```

Wraps an OutputStream with a PrintWriter using an optional encoding (defaults to :utf-8).

```
(do
  (import :java.io.ByteArrayOutputStream)
  (let [os (. :ByteArrayOutputStream :new)
        wr (io/wrap-os-with-print-writer os :utf-8)]
    (. wr :println "line 1")
    (. wr :println "line 2")
    (. wr :flush)
    (. os :toByteArray)))
=> [108 105 110 101 32 49 10 108 105 110 101 32 50 10]
```

io/zip

```
(io/zip & entries)
```

Creates a zip containing the entries. An entry is given by a name and data. The entry data may be nil, a bytebuf, a file, a string (file path), or an InputStream. An entry name with a trailing '/' creates a directory. Returns the zip as bytebuf.

```
; single entry
(->> (io/zip "a.txt" (bytebuf-from-string "abc" :utf-8))
      (io/spit "test.zip"))

; multiple entries
(->> (io/zip "a.txt" (bytebuf-from-string "abc" :utf-8)
           "b.txt" (bytebuf-from-string "def" :utf-8)
           "c.txt" (bytebuf-from-string "ghi" :utf-8))
      (io/spit "test.zip"))

; multiple entries with subdirectories
(->> (io/zip "a.txt" (bytebuf-from-string "abc" :utf-8)
           "x/b.txt" (bytebuf-from-string "def" :utf-8)
           "x/y/c.txt" (bytebuf-from-string "ghi" :utf-8))
      (io/spit "test.zip"))

; empty directory z/
(->> (io/zip "a.txt" (bytebuf-from-string "abc" :utf-8)
           "z/" nil)
      (io/spit "test.zip"))
```

io/zip-append

```
(io/zip-append f & entries)
```

Appends entries to an existing zip file `f`. Overwrites existing entries. An entry is given by a name and data. The entry data may be `nil`, a `bytebuf`, a `file`, a `string` (file path), or an `InputStream`. An entry name with a trailing `'/'` creates a directory.

```
(let [data (bytebuf-from-string "abc" :utf-8)]
  ; create the zip with a first file
  (->> (io/zip "a.txt" data)
        (io/spit "test.zip"))
  ; add text files
  (io/zip-append "test.zip" "b.txt" data "x/c.txt" data)
  ; add an empty directory
  (io/zip-append "test.zip" "x/y/" nil)))
```

[top](#)

io/zip-file

```
(io/zip-file options* zip-file & files)
```

Zips files. The zip-file may be a file, a string (file path) or an `OutputStream`.

Options:

`:filter-fn fn` - filters the files to be added to the zip.

```
(io/zip-file "test.zip" "a.txt" "x/b.txt")
```

```
(io/zip-file "test.zip" "dir")
```

```
(io/zip-file :filter-fn (fn [dir name] (str/ends-with? name ".txt"))
             "test.zip"
             "test-dir")
```

[top](#)

io/zip-list

```
(io/zip-list f & options)
```

List the content of a the zip `f`. `f` may be a `bytebuf`, a `file`, a `string` (file path), or an `InputStream`.

Options:

`:verbose true/false` - e.g `:verbose true`, defaults to `false`

```
(io/zip-list "test-file.zip")
```

```
(io/zip-list "test-file.zip" :verbose true)
```

[top](#)

io/zip-remove

```
(io/zip-remove f & entry-names)
```

Remove entries from a zip file `f`.

```
; remove files from zip
(io/zip-remove "test.zip" "x/a.txt" "x/b.txt")
```

```
; remove directory from zip
(io/zip-remove "test.zip" "x/y/")
```

[top](#)

io/zip?

```
(io/zip? f)
```

Returns true if `f` is a zipped file. `f` may be a file, a string (file path), a bytebuf, or an InputStream

```
(-> (io/zip "a" (bytebuf-from-string "abc" :utf-8))    (io/zip?))
=> true
```

[top](#)

java-enumeration-to-list

```
(java-enumeration-to-list e)
```

Converts a Java enumeration to a list

[top](#)

java-iterator-to-list

```
(java-iterator-to-list e)
```

Converts a Java iterator to a list

[top](#)

java-obj?

```
(java-obj? obj)
```

Returns true if `obj` is a Java object

```
(java-obj? (. :java.math.BigInteger :new "0"))
=> true
```

[top](#)

java-version

```
(java-version)
```

Returns the Jvav VM version.

```
(java-version)
=> "1.8.0_201"
```

[top](#)

json/pretty-print

```
(json/pretty-print s)
```

Pretty prints a JSON string

```
(json/pretty-print (json/write-str {:a 100 :b 100}))
=> "{\n  \"a\": 100,\n  \"b\": 100\n}"
```

[top](#)

json/read-str

```
(json/read-str s & options)
```

Reads a JSON string and returns it as a Venice datatype.

Options are:

:key-fn fn

Single-argument function called on JSON property names;
return value will replace the property names in the output.
Default is 'identity', use 'keyword' to get keyword
properties.

:value-fn fn

Function to transform values in JSON objects in
the output. For each JSON property, value-fn is called with
two arguments: the property name (transformed by key-fn) and
the value. The return value of value-fn will replace the value
in the output. The default value-fn returns the value unchanged.

:decimal boolean

If true use BigDecimal for decimal numbers instead of Double.
Default is false.

```
(json/read-str (json/write-str {:a 100 :b 100}))
=> {"a" 100 "b" 100}
```

```
(json/read-str (json/write-str {:a 100 :b 100}) :key-fn keyword)
=> {:a 100 :b 100}
```

```
(json/read-str (json/write-str {:a 100 :b 100})
                :value-fn (fn [k v] (if (== "a" k) (inc v) v)))
=> {"a" 101 "b" 100}
```

[top](#)

json/slurp

```
(json/slurp in & options)
```

Slurps a JSON string from the input and returns it as a Venice datatype.
in maybe a Java InputStream or a Java Reader.

Options are:

`:key-fn fn`

Single-argument function called on JSON property names;
return value will replace the property names in the output.
Default is 'identity', use 'keyword' to get keyword
properties.

`:value-fn fn`

Function to transform values in JSON objects in
the output. For each JSON property, value-fn is called with
two arguments: the property name (transformed by key-fn) and
the value. The return value of value-fn will replace the value
in the output. The default value-fn returns the value unchanged.

`:decimal boolean`

If true use BigDecimal for decimal numbers instead of Double.
Default is false.

```
(let [json (json/write-str {:a 100 :b 100})
      data (bytebuf-from-string json :utf-8)
      in (. :java.io.ByteArrayInputStream :new data)]
  (str (json/slurp in)))
=> "{a 100 b 100}"
```

[top](#)

json/spit

`(json/spit out val & options)`

Spits the JSON converted val to the output.
out maybe a Java OutputStream or a Java Writer.

Options are:

`:pretty boolean`

Enables/disables pretty printing.
Defaults to false.

`:decimal-as-double boolean`

If true emit a decimal as double else as string.
Defaults to false.

```
(let [out (. :java.io.ByteArrayOutputStream :new)]
  (json/spit out {:a 100 :b 100 :c [10 20 30]})
  (. out :flush)
  (. :java.lang.String :new (. out :toByteArray) "utf-8"))
=> "{\a\":100,\b\":100,\c\":[10,20,30]}"
```

[top](#)

json/write-str

`(json/write-str val & options)`

Writes the val to a JSON string.

Options are:

`:pretty boolean`

Enables/disables pretty printing.
Defaults to false.

`:decimal-as-double boolean`

If true emit a decimal as double else as string.
Defaults to false.

```
(json/write-str {:a 100 :b 100})  
=> "{\"a\":100,\"b\":100}"
```

```
(json/write-str {:a 100 :b 100} :pretty true)  
=> "{\n  \"a\": 100,\n  \"b\": 100\n}"
```

[top](#)

keep

```
(keep f coll)
```

Returns a sequence of the non-nil results of (f item). Note, this means false return values will be included. f must be free of side-effects. Returns a transducer when no collection is provided.

```
(keep even? (range 1 4))  
=> (false true false)
```

```
(keep (fn [x] (if (odd? x) x)) (range 4))  
=> (1 3)
```

[top](#)

key

```
(key e)
```

Returns the key of the map entry.

```
(key (find {:a 1 :b 2} :b))  
=> :b
```

[top](#)

keys

```
(keys map)
```

Returns a collection of the map's keys.

```
(keys {:a 1 :b 2 :c 3})  
=> (:a :b :c)
```

[top](#)

keyword

```
(keyword name)
```

Returns a keyword from the given name


```
(keyword "a")  
=> :a
```

```
(keyword :a)  
=> :a
```

[top](#)

keyword?

```
(keyword? x)
```

Returns true if x is a keyword

```
(keyword? (keyword "a"))  
=> true
```

```
(keyword? :a)  
=> true
```

```
(keyword? nil)  
=> false
```

```
(keyword? 'a)  
=> false
```

[top](#)

last

```
(last coll)
```

Returns the last element of coll.

```
(last nil)  
=> nil
```

```
(last [])  
=> nil
```

```
(last [1 2 3])  
=> 3
```

```
(last '())  
=> nil
```

```
(last '(1 2 3))  
=> 3
```

```
(last "abc")  
=> "c"
```

[top](#)

let

```
(let [bindings*] exprs*)
```

Evaluates the expressions and binds the values to symbols to new local context

```
(let [x 1] x))
=> 1

;; destructured map
(let [{:keys [width height title ]
      :or {width 640 height 500}
      :as styles}
      {:width 1000 :title "Title"}]
  (println "width: " width)
  (println "height: " height)
  (println "title: " title)
  (println "styles: " styles))
width: 1000
height: 500
title: Title
styles: {:width 1000 :title Title}
=> nil
```

[top](#)

list

```
(list & items)
```

Creates a new list containing the items.

```
(list )
=> ()

(list 1 2 3)
=> (1 2 3)

(list 1 2 3 [:a :b])
=> (1 2 3 [:a :b])
```

[top](#)

list*

```
(list* args)
(list* a args)
(list* a b args)
(list* a b c args)
(list* a b c d & more)
```

Creates a new list containing the items prepended to the rest, the last of which will be treated as a collection.

```
(list* 1 [2 3])
=> (1 2 3)

(list* 1 2 3 [4])
=> (1 2 3 4)

(list* '(1 2) 3 [4])
=> ((1 2) 3 4)
```

```
(list* nil)
=> nil

(list* nil [2 3])
=> (nil 2 3)

(list* 1 2 nil)
=> (1 2)
```

[top](#)

list-comp

```
(list-comp seq-exprs body-expr)
```

List comprehension. Takes a vector of one or more binding-form/collection-expr pairs, each followed by zero or more modifiers, and yields a collection of evaluations of expr. Supported modifiers are: :when test.

```
(list-comp [x (range 10)] x)
=> (0 1 2 3 4 5 6 7 8 9)

(list-comp [x (range 5)] (* x 2))
=> (0 2 4 6 8)

(list-comp [x (range 10) :when (odd? x)] x)
=> (1 3 5 7 9)

(list-comp [x (range 10) :when (odd? x)] (* x 2))
=> (2 6 10 14 18)

(list-comp [x (list "abc") y [0 1 2]] [x y])
=> (["abc" 0] ["abc" 1] ["abc" 2])
```

[top](#)

list?

```
(list? obj)
```

Returns true if obj is a list

```
(list? (list 1 2))
=> true

(list? '(1 2))
=> true
```

[top](#)

load-classpath-file

```
(load-classpath-file name)
```

Sequentially read and evaluate the set of forms contained in the classpath file. The function is restricted to classpath files with the extension '.venice'.

```
(do
  (load-classpath-file "com/github/jlangch/venice/test.venice")
  (test/test-fn "hello"))
=> "test: hello"
```

[top](#)

load-file

```
(load-file name)
```

Sequentially read and evaluate the set of forms contained in the file.

[top](#)

load-module

```
(load-module s)
```

Loads a Venice predefined extension module.

```
(do
  (load-module :math))
=> function math/bigint-to-long {visibility :public, module "math"}
```

[top](#)

load-string

```
(load-string s)
```

Sequentially read and evaluate the set of forms contained in the string.

```
(do
  (load-string "(def x 1)")
  (+ x 2))
=> 3
```

[top](#)

long

```
(long x)
```

Converts to long

```
(long 1)
=> 1
```

```
(long nil)
=> 0
```

```
(long false)
=> 0

(long true)
=> 1

(long 1.2)
=> 1

(long 1.2M)
=> 1

(long "1")
=> 1
```

[top](#)

long-array

```
(long-array coll)
(long-array len)
(long-array len init-val)
```

Returns an array of Java primitive longs containing the contents of `coll` or returns an array with the given length and optional init value

```
(long-array '(1 2 3))
=> [1, 2, 3]

(long-array '(1I 2 3.2 3.56M))
=> [1, 2, 3, 3]

(long-array 10)
=> [0, 0, 0, 0, 0, 0, 0, 0, 0, 0]

(long-array 10 42)
=> [42, 42, 42, 42, 42, 42, 42, 42, 42, 42]
```

[top](#)

long?

```
(long? n)
```

Returns true if `n` is a long

```
(long? 4)
=> true

(long? 4I)
=> false

(long? 3.1)
=> false

(long? true)
=> false

(long? nil)
```

```
=> false
```

```
(long? {})  
=> false
```

[top](#)

loop

```
(loop [bindings*] exprs*)
```

Evaluates the `exprs` and binds the `bindings`. Creates a recursion point with the `bindings`.

```
;; tail recursion  
(loop [x 10]  
  (when (> x 1)  
    (println x)  
    (recur (- x 2)))))  
10  
8  
6  
4  
2  
=> nil  
  
;; tail recursion  
(do  
  (defn sum [n]  
    (loop [cnt n acc 0]  
      (if (zero? cnt)  
          acc  
          (recur (dec cnt) (+ acc cnt))))))  
  (sum 10000))  
=> 50005000
```

[top](#)

macro?

```
(macro? x)
```

Returns true if `x` is a macro

```
(macro? and)  
=> true
```

[top](#)

macroexpand

```
(macroexpand form)
```

If `form` represents a macro form, returns its expansion, else returns `form`

```
(macroexpand (-> c (+ 3) (* 2)))  
=> (* (+ c 3) 2)
```

make-array

```
(make-array type len)
(make-array type dim &more-dims)
```

Returns an array of the given type and length

```
(str (make-array :long 5))
=> "[0, 0, 0, 0, 0]"
```

```
(str (make-array :java.lang.Long 5))
=> "[nil, nil, nil, nil, nil]"
```

```
(str (make-array :long 2 3))
=> "[[0 0 0], [0 0 0]]"
```

```
(aset (make-array :java.lang.Long 5) 3 9999)
=> [nil, nil, nil, 9999, nil]
```

map

```
(map f coll colls*)
```

Applies `f` to the set of first items of each `coll`, followed by applying `f` to the set of second items in each `coll`, until any one of the `colls` is exhausted. Any remaining items in other `colls` are ignored. Returns a transducer when no collection is provided.

```
(map inc [1 2 3 4])
=> (2 3 4 5)
```

```
(map + [1 2 3 4] [10 20 30 40])
=> (11 22 33 44)
```

map-invert

```
(map-invert m)
```

Returns the map with the vals mapped to the keys.

```
(map-invert {:a 1 :b 2 :c 3})
=> {1 :a 2 :b 3 :c}
```

map?

```
(map? obj)
```

Returns true if obj is a map

```
(map? {:a 1 :b 2})  
=> true
```

[top](#)

mapcat

```
(mapcat fn & colls)
```

Returns the result of applying concat to the result of applying map to fn and colls. Thus function fn should return a collection.

```
(mapcat reverse [[3 2 1 0] [6 5 4] [9 8 7]])  
=> (0 1 2 3 4 5 6 7 8 9)
```

[top](#)

mapv

```
(mapv f coll colls*)
```

Returns a vector consisting of the result of applying f to the set of first items of each coll, followed by applying f to the set of second items in each coll, until any one of the colls is exhausted. Any remaining items in other colls are ignored.

```
(mapv inc [1 2 3 4])  
=> [2 3 4 5]
```

```
(mapv + [1 2 3 4] [10 20 30 40])  
=> [11 22 33 44]
```

[top](#)

match?

```
(match? s regex)
```

Returns true if the string s matches the regular expression regex

```
(match? "1234" "[0-9]+")  
=> true
```

```
(match? "1234ss" "[0-9]+")  
=> false
```

[top](#)

max

```
(max x)  
(max x y)  
(max x y & more)
```


Returns the greatest of the values

```
(max 1)
=> 1

(max 1 2)
=> 2

(max 4 3 2 1)
=> 4

(max (int 1) (int 2))
=> 2I

(max 1.0)
=> 1.0

(max 1.0 2.0)
=> 2.0

(max 4.0 3.0 2.0 1.0)
=> 4.0

(max 1.0M)
=> 1.0M

(max 1.0M 2.0M)
=> 2.0M

(max 4.0M 3.0M 2.0M 1.0M)
=> 4.0M

(max 1.0M 2)
=> 2
```

[top](#)

memoize

```
(memoize f)
```

Returns a memoized version of a referentially transparent function.

```
(do
  (def fibonacci
    (memoize
      (fn [n]
        (cond
          (<= n 0) 0
          (< n 2) 1
          :else (+ (fibonacci (- n 1)) (fibonacci (- n 2)))))))

  (time (fibonacci 25)))
Elapsed time: 8.41 ms
=> 75025
```

[top](#)

merge

(merge & maps)

Returns a map that consists of the rest of the maps conj-ed onto the first. If a key occurs in more than one map, the mapping from the latter (left-to-right) will be the mapping in the result.

```
(merge {:a 1 :b 2 :c 3} {:b 9 :d 4})  
=> {:a 1 :b 9 :c 3 :d 4}
```

```
(merge {:a 1} nil)  
=> {:a 1}
```

```
(merge nil {:a 1})  
=> {:a 1}
```

```
(merge nil nil)  
=> nil
```

[top](#)

meta

(meta obj)

Returns the metadata of obj, returns nil if there is no metadata.

[top](#)

min

```
(min x)  
(min x y)  
(min x y & more)
```

Returns the smallest of the values

```
(min 1)  
=> 1
```

```
(min 1 2)  
=> 1
```

```
(min 4 3 2 1)  
=> 1
```

```
(min (int 1) (int 2))  
=> 1I
```

```
(min 1.0)  
=> 1.0
```

```
(min 1.0 2.0)  
=> 1.0
```

```
(min 4.0 3.0 2.0 1.0)  
=> 1.0
```

```
(min 1.0M)
=> 1.0M

(min 1.0M 2.0M)
=> 1.0M

(min 4.0M 3.0M 2.0M 1.0M)
=> 1.0M

(min 1.0M 2)
=> 1.0M
```

[top](#)

mod

```
(mod n d)
```

Modulus of n and d.

```
(mod 10 4)
=> 2
```

```
(mod (int 10) (int 4))
=> 2I
```

[top](#)

module

```
(module fn)
```

Returns the module a function/macro has been defined in.

```
(module +)
=> "core"
```

[top](#)

mutable-map

```
(mutable-map & keyvals)
(mutable-map map)
```

Creates a new mutable threadsafe map containing the items.

```
(mutable-map :a 1 :b 2)
=> {:a 1 :b 2}
```

```
(mutable-map (hash-map :a 1 :b 2))
=> {:a 1 :b 2}
```

[top](#)

mutable-map?

```
(mutable-map? obj)
```

Returns true if obj is a mutable map

```
(mutable-map? (mutable-map :a 1 :b 2))  
=> true
```

[top](#)

name

```
(name x)
```

Returns the name String of a string, symbol, keyword, or function/macro.

```
(name :x)  
=> "x"
```

```
(name 'x)  
=> "x"
```

```
(name "x")  
=> "x"
```

[top](#)

nano-time

```
(nano-time)
```

Returns the current value of the running Java Virtual Machine's high-resolution time source, in nanoseconds.

```
(nano-time)  
=> 1051550314131341
```

[top](#)

neg?

```
(neg? x)
```

Returns true if x smaller than zero else false

```
(neg? -3)  
=> true
```

```
(neg? 3)  
=> false
```

```
(neg? (int -3))  
=> true
```

```
(neg? -3.2)  
=> true
```

```
(neg? -3.2M)
=> true
```

[top](#)

negate

```
(negate x)
```

Negates *x*

```
(negate 10)
=> -10
```

```
(negate (int 10))
=> -10I
```

```
(negate 1.23)
=> -1.23
```

```
(negate 1.23M)
=> -1.23M
```

[top](#)

newline

```
(newline)
```

Writes a platform-specific newline to **out**

```
(newline)
```

```
=> nil
```

[top](#)

nfirst

```
(nfirst coll n)
```

Returns a collection of the first *n* items

```
(nfirst nil 2)
=> ()
```

```
(nfirst [] 2)
=> []
```

```
(nfirst [1] 2)
=> [1]
```

```
(nfirst [1 2 3] 2)
=> [1 2]
```

```
(nfirst '() 2)
=> ()

(nfirst '(1) 2)
=> (1)

(nfirst '(1 2 3) 2)
=> (1 2)
```

[top](#)

nil?

```
(nil? x)
```

Returns true if x is nil, false otherwise

```
(nil? nil)
=> true
```

```
(nil? 0)
=> false
```

```
(nil? false)
=> false
```

[top](#)

nlast

```
(nlast coll n)
```

Returns a collection of the last n items

```
(nlast nil 2)
=> ()
```

```
(nlast [] 2)
=> []
```

```
(nlast [1] 2)
=> [1]
```

```
(nlast [1 2 3] 2)
=> [2 3]
```

```
(nlast '() 2)
=> ()
```

```
(nlast '(1) 2)
=> (1)
```

```
(nlast '(1 2 3) 2)
=> (2 3)
```

[top](#)

not

```
(not x)
```

Returns true if x is logical false, false otherwise.

```
(not true)
=> false
```

```
(not (== 1 2))
=> true
```

[top](#)

not-any?

```
(not-any? pred coll)
```

Returns false if the predicate is true for at least one collection item, true otherwise

```
(not-any? number? nil)
=> true
```

```
(not-any? number? [])
=> true
```

```
(not-any? number? [1 :a :b])
=> false
```

```
(not-any? number? [1 2 3])
=> false
```

```
(not-any? #(>= % 10) [1 5 10])
=> false
```

[top](#)

not-empty?

```
(not-empty? x)
```

Returns true if x is not empty

```
(not-empty? {:a 1})
=> true
```

```
(not-empty? [1 2])
=> true
```

```
(not-empty? '(1 2))
=> true
```

[top](#)

not-every?

```
(not-every? pred coll)
```

Returns false if the predicate is true for all collection items, true otherwise

```
(not-every? number? nil)
=> true
```

```
(not-every? number? [])
=> true
```

```
(not-every? number? [1 2 3 4])
=> false
```

```
(not-every? number? [1 2 3 :a])
=> true
```

```
(not-every? #(>= % 10) [10 11 12])
=> false
```

[top](#)

not-match?

```
(not-match? s regex)
```

Returns true if the string s does not match the regular expression regex

```
(not-match? "1234" "[0-9]+")
=> false
```

```
(not-match? "1234ss" "[0-9]+")
=> true
```

[top](#)

nth

```
(nth coll idx)
```

Returns the nth element of coll.

```
(nth nil 1)
=> nil
```

```
(nth [1 2 3] 1)
=> 2
```

```
(nth '(1 2 3) 1)
=> 2
```

```
(nth "abc" 2)
=> "c"
```

[top](#)

number?


```
(number? n)
```

Returns true if n is a number (int, long, double, or decimal)

```
(number? 4I))  
=> true
```

```
(number? 4)  
=> true
```

```
(number? 4.0M)  
=> true
```

```
(number? 4.0)  
=> true
```

```
(number? true)  
=> false
```

```
(number? "a")  
=> false
```

[top](#)

object-array

```
(object-array coll)  
(object-array len)  
(object-array len init-val)
```

Returns an array of Java Objects containing the contents of coll or returns an array with the given length and optional init value

```
(object-array '(1 2 3 4 5))  
=> [1, 2, 3, 4, 5]
```

```
(object-array '(1 2.0 3.45M "4" true))  
=> [1, 2.0, 3.45M, "4", true]
```

```
(object-array 10)  
=> [nil, nil, nil, nil, nil, nil, nil, nil, nil]
```

```
(object-array 10 42)  
=> [42, 42, 42, 42, 42, 42, 42, 42, 42, 42]
```

[top](#)

odd?

```
(odd? n)
```

Returns true if n is odd, throws an exception if n is not an integer

```
(odd? 3)  
=> true
```

```
(odd? 4)
```

```
=> false
```

```
(odd? (int 4))  
=> false
```

[top](#)

offer!

```
(offer! queue v)  
(offer! queue timeout v)
```

Offers an item to a queue with an optional timeout in milliseconds.

```
(let [s (queue)]  
  (offer! s 4)  
  (offer! s 3)  
  (poll! s)  
  s)  
=> (3)
```

[top](#)

or

```
(or x)  
(or x & next)
```

Ors the predicate forms

```
(or true false)  
=> true
```

```
(or false false)  
=> false
```

[top](#)

ordered-map

```
(ordered-map & keyvals)  
(ordered-map map)
```

Creates a new ordered map containing the items.

```
(ordered-map :a 1 :b 2)  
=> {:a 1 :b 2}
```

```
(ordered-map (hash-map :a 1 :b 2))  
=> {:a 1 :b 2}
```

[top](#)

ordered-map?

```
(ordered-map? obj)
```

Returns true if obj is an ordered map

```
(ordered-map? (ordered-map :a 1 :b 2))  
=> true
```

[top](#)

os-type

```
(os-type)
```

Returns the OS type

```
(os-type)  
=> :mac-osx
```

[top](#)

os-type?

```
(os-type? type)
```

Returns true if the OS id of the type otherwise false. Type is one of :windows, :mac-osx, or :linux

```
(os-type? :mac-osx)  
=> true
```

```
(os-type? :windows)  
=> false
```

[top](#)

partial

```
(partial f args*)
```

Takes a function f and fewer than the normal arguments to f, and returns a fn that takes a variable number of additional args. When called, the returned function calls f with args + additional args.

```
((partial * 2) 3)  
=> 6
```

```
(map (partial * 2) [1 2 3 4])  
=> (2 4 6 8)
```

```
(do  
  (def hundred-times (partial * 100))  
  (hundred-times 5))  
=> 500
```

[top](#)

partition

```
(partition n coll)
(partition n step coll)
(partition n step padcoll coll)
```

Returns a collection of lists of `n` items each, at offsets `step` apart. If `step` is not supplied, defaults to `n`, i. e. the partitions do not overlap. If a `padcoll` collection is supplied, use its elements as necessary to complete last partition upto `n` items. In case there are not enough padding elements, return a partition with less than `n` items.

```
(partition 4 (range 20))
=> ((0 1 2 3) (4 5 6 7) (8 9 10 11) (12 13 14 15) (16 17 18 19))
```

```
(partition 4 6 (range 20))
=> ((0 1 2 3) (6 7 8 9) (12 13 14 15) (18 19))
```

```
(partition 3 6 ["a"] (range 20))
=> ((0 1 2) (6 7 8) (12 13 14) (18 19 "a"))
```

```
(partition 4 6 ["a" "b" "c" "d"] (range 20))
=> ((0 1 2 3) (6 7 8 9) (12 13 14 15) (18 19 "a" "b"))
```

[top](#)

pdf/available?

```
(pdf/available?)
```

Checks if the 3rd party libraries required for generating PDFs are available.

```
(pdf/available?)
```

[top](#)

pdf/copy

```
pdf/copy pdf & page-nr
```

Copies pages from a PDF to a new PDF.

```
; copy the first and second page
(pdf/copy pdf :1 :2)
```

```
; copy the last and second last page
(pdf/copy pdf :-1 :-2)
```

```
; copy the pages 1, 2, 6-10, and 12
(pdf/copy pdf :1 :2 :6-10 :12)
```

[top](#)

pdf/merge

pdf/merge pdfs

Merge multiple PDFs into a single PDF.

```
(pdf/merge pdf1 pdf2)
```

```
(pdf/merge pdf1 pdf2 pdf3)
```

[top](#)

pdf/pages

pdf/pages pdf

Returns the number of pages of a PDF.

```
(pdf/pages pdf)
```

[top](#)

pdf/render

```
(pdf/render xhtml & options)
```

Renders a PDF.

Options:

- :base-url url - a base url. E.g.: "classpath:/"
- :resources resmap - a resource map for dynamic resources

```
(pdf/render xhtml :base-url "classpath:/")
```

```
(pdf/render xhtml
  :base-url "classpath:/"
  :resources {"/chart_1.png" (chart-create :2018)
              "/chart_2.png" (chart-create :2019) })
```

[top](#)

pdf/text-to-pdf

pdf/text-to-pdf text & options

Creates a PDF from simple text. The tool process line-feeds '\n' and form-feeds. To start a new page just insert a form-feed marker "<form-feed>".

Options:

- :font-size n - font size in pt (double), defaults to 9.0
- :font-weight n - font weight (0...1000) (long), defaults to 200
- :font-monospace b - monospaced font (true/false) (boolean), defaults to false

```
(->> (pdf/text-to-pdf "Lorem Ipsum...")
      (io/spit "text.pdf"))
```

[top](#)

pdf/watermark

```
(pdf/watermark pdf options-map)
(pdf/watermark pdf & options)
```

Adds a watermark text to the pages of a PDF. The passed PDF pdf is a bytebuf. Returns the new PDF as a bytebuf.

Options:

:text s	- watermark text (string), defaults to "WATERMARK"
:font-size n	- font size in pt (double), defaults to 24.0
:font-char-spacing n	- font character spacing (double), defaults to 0.0
:color s	- font color (HTML color string), defaults to #000000
:opacity n	- opacity 0.0 ... 1.0 (double), defaults to 0.4
:angle n	- angle 0.0 ... 360.0 (double), defaults to 45.0
:over-content b	- print text over the content (boolean), defaults to true
:skip-top-pages n	- the number of top pages to skip (long), defaults to 0
:skip-bottom-pages n	- the number of bottom pages to skip (long), defaults to 0

```
(pdf/watermark pdf :text "CONFIDENTIAL" :font-size 64 :font-char-spacing 10.0)
```

```
(let [watermark { :text "CONFIDENTIAL"
                  :font-size 64
                  :font-char-spacing 10.0 } ]
  (pdf/watermark pdf watermark))
```

[top](#)

peek

```
(peek coll)
```

For a list, same as first, for a vector, same as last, for a stack the top element

```
(peek '(1 2 3 4))
=> 1
```

```
(peek [1 2 3 4])
=> 4
```

```
(let [s (stack)]
  (push! s 4)
  (peek s))
=> 4
```

[top](#)

perf

```
(perf expr warmup-iterations test-iterations)
```

Performance test with the given expression.

Runs the test in 3 phases:

1. Runs the expr in a warmup phase to allow the HotSpot compiler to do optimizations.
2. Runs the garbage collector
3. Runs the expression under profiling.

Returns nil.

After a test run metrics data can be printed with `(println (prof :data-formatted))`

```
(do
  (perf (+ 120 200) 12000 1000)
  (println (prof :data-formatted)))
```

[top](#)

pid

```
(pid)
```

Returns the PID of this process.

```
(pid)
=> "38228"
```

[top](#)

poll!

```
(poll! queue)
(poll! queue timeout)
```

Polls an item from a queue with an optional timeout in milliseconds.

```
(let [s (queue)]
  (offer! s 4)
  (offer! s 3)
  (poll! s)
  s)
=> (3)
```

[top](#)

pop

```
(pop coll)
```

For a list, returns a new list without the first item, for a vector, returns a new vector without the last item.

```
(pop '(1 2 3 4))
=> (2 3 4)
```

```
(pop [1 2 3 4])
=> [1 2 3]
```

[top](#)

pop!

```
(pop! stack)
```

Pops an item from a stack.

```
(let [s (stack)]
  (push! s 4)
  (push! s 3)
  (pop! s)
  s)
=> (4)
```

top

pos?

```
(pos? x)
```

Returns true if x greater than zero else false

```
(pos? 3)
=> true
```

```
(pos? -3)
=> false
```

```
(pos? (int 3))
=> true
```

```
(pos? 3.2)
=> true
```

```
(pos? 3.2M)
=> true
```

top

pr-str

```
(pr-str & xs)
```

With no args, returns the empty string. With one arg x, returns `x.toString()`. With more than one arg, returns the concatenation of the str values of the args with delimiter ' '.

```
(pr-str )
=> ""
```

```
(pr-str 1 2 3)
=> "1 2 3"
```

top

print

```
(print & xs)
```

Prints to stdout, with no args, prints the empty string. With one arg x, prints `x.toString()`. With more than one arg, prints the concatenation of the str values of the args with delimiter ' '. Returns nil.


```
(print [10 20 30])
[10 20 30]
=> nil
```

[top](#)

printf

```
(printf fmt & args)
```

Prints formatted output, as per format

```
(printf "%s: %d" "abc" 100)
abc: 100
=> nil
```

[top](#)

println

```
(println & xs)
```

Prints to stdout with a trailing linefeed, with no args, prints the empty string. With one arg x, prints x.toString(). With more than one arg, prints the concatenation of the str values of the args with delimiter ' '. Returns nil.

```
(do (println 200) (println [10 20 30]))
200
[10 20 30]
=> nil
```

[top](#)

prof

```
(prof opts)
```

Controls the code profiling. See the companion functions/macros 'dorun' and 'perf'. The perf macro is built on prof and dorun and provides all to do simple Venice profiling.

```
(do
  (prof :on)    ; turn profiler on
  (prof :off)   ; turn profiler off
  (prof :status) ; returns the profiler on/off status
  (prof :clear)  ; clear profiler data captured so far
  (prof :data)   ; returns the profiler data as map
  (prof :data-formatted) ; returns the profiler data as formatted text
  (prof :data-formatted "Metrics test") ; returns the profiler data as formatted text with a title
  nil)
=> nil
```

[top](#)

promise

```
(promise)
```

Returns a promise object that can be read with `deref`, and `set`, once only, with `deliver`. Calls to `deref` prior to delivery will block, unless the variant of `deref` with `timeout` is used. All subsequent derefs will return the same delivered value without blocking.

```
(do
  (def p (promise))
  (def task (fn []
              (do
                (sleep 500)
                (deliver p 123)))))

  (future task)
  (deref p))
=> 123
```

[top](#)

promise?

```
(promise? p)
```

Returns true if `f` is a Promise otherwise false

```
(promise? (promise))
=> true
```

[top](#)

proxify

```
(proxify classname method-map)
```

Proxies a Java interface to be passed as a Callback object to Java functions. The interface's methods are implemented by Venice functions.

```
(do
  (import :java.io.File :java.io.FilenameFilter)

  (def file-filter
    (fn [dir name] (str/ends-with? name ".xxx")))

  (let [dir (io/tmp-dir )]
    ;; create a dynamic proxy for the interface FilenameFilter
    ;; and implement its function 'accept' by 'file-filter'
    (. dir :list (proxify :FilenameFilter {:accept file-filter})))
  )
=> []
```

[top](#)

push!

```
(push! stack v)
```

Pushes an item to a stack.

```
(let [s (stack)]
  (push! s 4)
  (push! s 3)
  (pop! s)
  s)
=> (4)
```

[top](#)

queue

```
(queue )
(queue 100)
```

Creates a new mutable threadsafe bounded or unbounded queue.

```
;unbounded queue
(let [q (queue)]
  (offer! q 1)
  (offer! q 2)
  (offer! q 3)
  (poll! q)
  q)
=> (2 3)

;bounded queue
(let [q (queue 10)]
  (offer! q 1000 1)
  (offer! q 1000 2)
  (offer! q 1000 3)
  (poll! q 1000)
  q)
=> (2 3)
```

[top](#)

queue?

```
(queue? obj)
```

Returns true if obj is a queue

```
(queue? (queue))
=> true
```

[top](#)

rand-double

```
(rand-double)
(rand-double max)
```

Without argument returns a double between 0.0 and 1.0. With argument max returns a random double between 0.0 and max.
This function is based on a cryptographically strong random number generator (RNG).

```
(rand-double)
=> 0.6813878640867438
```

```
(rand-double 100.0)
=> 34.85858278691782
```

[top](#)

rand-gaussian

```
(rand-gaussian)
(rand-gaussian mean stddev)
```

Without argument returns a Gaussian distributed double value with mean 0.0 and standard deviation 1.0. With argument mean and stddev returns a Gaussian distributed double value with the given mean and standard deviation.
This function is based on a cryptographically strong random number generator (RNG)

```
(rand-gaussian)
=> 0.21255874954750006
```

```
(rand-gaussian 0.0 5.0)
=> 3.325738475039897
```

[top](#)

rand-long

```
(rand-long)
(rand-long max)
```

Without argument returns a random long between 0 and MAX_LONG. With argument max returns a random long between 0 and max exclusive.
This function is based on a cryptographically strong random number generator (RNG).

```
(rand-long)
=> 7589901423733128066
```

```
(rand-long 100)
=> 38
```

[top](#)

range

```
(range end)
(range start end)
(range start end step)
```

Returns a collection of numbers from start (inclusive) to end (exclusive), by step, where start defaults to 0 and step defaults to 1. When start is equal to end, returns empty list.

```
(range 10)
=> (0 1 2 3 4 5 6 7 8 9)

(range 10 20)
=> (10 11 12 13 14 15 16 17 18 19)

(range 10 20 3)
=> (10 13 16 19)

(range (int 10) (int 20))
=> (10I 11I 12I 13I 14I 15I 16I 17I 18I 19I)

(range (int 10) (int 20) (int 3))
=> (10I 13I 16I 19I)

(range 10 15 0.5)
=> (10 10.5 11.0 11.5 12.0 12.5 13.0 13.5 14.0 14.5)

(range 1.1M 2.2M 0.1M)
=> (1.1M 1.2M 1.3M 1.4M 1.5M 1.6M 1.7M 1.8M 1.9M 2.0M 2.1M)
```

[top](#)

read-string

```
(read-string x)
```

Reads from x

[top](#)

readline

```
(readline prompt)
```

Reads the next line from stdin. The function is sandboxed

[top](#)

realized?

```
(realized? x)
```

Returns true if a value has been produced for a promise, delay, or future.

```
(do
  (def task (fn [] 100))
  (let [f (future task)]
    (println (realized? f))
    (println @f)
    (println (realized? f))))

false
100
true
```

```

=> nil

(do
  (def p (promise))
  (println (realized? p))
  (deliver p 123)
  (println @p)
  (println (realized? p)))
false
123
true
=> nil

(do
  (def x (delay 100))
  (println (realized? x))
  (println @x)
  (println (realized? x)))
false
100
true
=> nil

```

[top](#)

recur

```
(recur expr*)
```

Evaluates the `exprs` and rebinds the bindings of the recursion point to the values of the `exprs`. The `recur` expression must be at the tail position. The tail position is a position which an expression would return a value from.

```

;; tail recursion
(loop [x 10]
  (when (> x 1)
    (println x)
    (recur (- x 2))))
10
8
6
4
2
=> nil

;; tail recursion
(do
  (defn sum [n]
    (loop [cnt n acc 0]
      (if (zero? cnt)
        acc
        (recur (dec cnt) (+ acc cnt))))))
  (sum 10000))
=> 50005000

```

[top](#)

reduce

```
(reduce f coll)
(reduce f val coll)
```

`f` should be a function of 2 arguments. If `val` is not supplied, returns the result of applying `f` to the first 2 items in `coll`, then applying `f` to that result and the 3rd item, etc. If `coll` contains no items, `f` must accept no arguments as well, and `reduce` returns the result of calling `f` with no arguments. If `coll` has only 1 item, it is returned and `f` is not called. If `val` is supplied, returns the result of applying `f` to `val` and the first item in `coll`, then applying `f` to that result and the 2nd item, etc. If `coll` contains no items, returns `val` and `f` is not called.

```
(reduce (fn [x y] (+ x y)) [1 2 3 4 5 6 7])
=> 28
```

```
(reduce (fn [x y] (+ x y)) 10 [1 2 3 4 5 6 7])
=> 38
```

```
((reduce comp [(partial + 1) (partial * 2) (partial + 3)]) 100)
=> 207
```

```
(reduce (fn [m [k v]] (assoc m v k)) {} {:b 2 :a 1 :c 3})
=> {1 :a 2 :b 3 :c}
```

```
(reduce (fn [m c] (assoc m (first c) c)) {} [[:a 1] [:b 2] [:c 3]])
=> {:a [:a 1] :b [:b 2] :c [:c 3]}
```

[top](#)

reduce-kv

```
(reduce-kv f init coll)
```

Reduces an associative collection. `f` should be a function of 3 arguments. Returns the result of applying `f` to `init`, the first key and the first value in `coll`, then applying `f` to that result and the 2nd key and value, etc. If `coll` contains no entries, returns `init` and `f` is not called. Note that `reduce-kv` is supported on vectors, where the keys will be the ordinals.

```
(reduce-kv (fn [x y z] (assoc x z y)) {} {:a 1 :b 2 :c 3})
=> {1 :a 2 :b 3 :c}
```

[top](#)

regex/find

```
(regex/find matcher)
```

Returns the next regex match

```
(let [m (regex/matcher "[0-9]+" "672-345-456-3212")]
  (println (regex/find m))
  (println (regex/find m))
  (println (regex/find m))
  (println (regex/find m))
  (println (regex/find m)))
```

```
672
345
456
```

```
3212
nil
=> nil
```

[top](#)

regex/find-all

```
(regex/find-all matcher)
```

Returns all regex matches

```
(let [m (regex/matcher "[0-9]+" "672-345-456-3212")]
      (regex/find-all m))
=> ("672" "345" "456" "3212")
```

[top](#)

regex/find-all-groups

```
(regex/find-all-groups matcher)
```

Returns the all regex matchws and returns the groups

```
(let [m (regex/matcher "[0-9]+" "672-345-456-3212")]
      (regex/find-all-groups m))

=> ({:group "672" :start 0 :end 3} {:group "345" :start 4 :end 7} {:group "456" :start 8 :end 11} {:group
"3212" :start 12 :end 16})
```

[top](#)

regex/find-group

```
(regex/find-group matcher)
```

Returns the next regex match and returns the group

```
(let [m (regex/matcher "[0-9]+" "672-345-456-3212")]
      (println (regex/find-group m))
      (println (regex/find-group m))
      (println (regex/find-group m))
      (println (regex/find-group m))
      (println (regex/find-group m)))

{:group 672 :start 0 :end 3}
{:group 345 :start 4 :end 7}
{:group 456 :start 8 :end 11}
{:group 3212 :start 12 :end 16}
nil
=> nil
```

[top](#)

regex/find?


```
(regex/find matcher)
```

Attempts to find the next subsequence that matches the pattern. If the match succeeds then more information can be obtained via the `regex/group` function

```
(let [p (regex/pattern "[0-9]+")
      m (regex/matcher p "100")]
  (regex/find? m))
=> true
```

[top](#)

regex/group

```
(regex/group matcher group)
```

Returns the input subsequence captured by the given group during the previous match operation.

```
(let [p (regex/pattern "([0-9]+)(.*)")
      m (regex/matcher p "100abc")]
  (if (regex/matches? m)
      [(regex/group m 1) (regex/group m 2)]
      []))
=> ["100" "abc"]
```

[top](#)

regex/groupcount

```
(regex/groupcount matcher)
```

Returns the matcher's group count.

```
(let [p (regex/pattern "([0-9]+)(.*)")
      m (regex/matcher p "100abc")]
  (regex/groupcount m))
=> 2
```

[top](#)

regex/matcher

```
(regex/matcher pattern str)
```

Returns an instance of `java.util.regex.Matcher`. The pattern can be either a string or a pattern created by `(regex/pattern s)`

```
(regex/matcher "[0-9]+" "100")
=> java.util.regex.Matcher[pattern=[0-9]+ region=0,3 lastmatch=]
```

```
(let [p (regex/pattern "[0-9]+")]
  (regex/matcher p "100"))
=> java.util.regex.Matcher[pattern=[0-9]+ region=0,3 lastmatch=]
```

regex/matches

```
(regex/matches pattern str)
```

Returns the match, if any, of string to pattern, using `java.util.regex.Matcher.matches()`. Returns the groups.

```
(regex/matches "hello, (.*)" "hello, world")  
=> ("hello, world" "world")  
  
(regex/matches "([0-9]+)-([0-9]+)-([0-9]+)-([0-9]+)" "672-345-456-212")  
=> ("672-345-456-212" "672" "345" "456" "212")
```

regex/matches?

```
(regex/matches matcher)
```

Attempts to match the entire region against the pattern. If the match succeeds then more information can be obtained via the `regex/group` function

```
(let [p (regex/pattern "[0-9]+")  
      m (regex/matcher p "100")]  
  (regex/matches? m))  
=> true
```

regex/pattern

```
(regex/pattern s)
```

Returns an instance of `java.util.regex.Pattern`.

```
(regex/pattern "[0-9]+")  
=> [0-9]+
```

regex/reset

```
(regex/reset matcher str)
```

Resets the matcher with a new string

```
(let [p (regex/pattern "[0-9]+")  
      m1 (regex/matcher p "100")  
      m2 (regex/reset m1 "200")]  
  (regex/find? m2))  
=> true
```

remove

```
(remove predicate coll)
```

Returns a collection of the items in coll for which (predicate item) returns logical false. Returns a transducer when no collection is provided.

```
(remove even? [1 2 3 4 5 6 7])  
=> [1 3 5 7]
```

[top](#)

remove-watch

```
(remove-watch ref key)
```

Removes a watch function from an agent/atom reference.

```
(do  
  (def x (agent 10))  
  (defn watcher [key ref old new]  
    (println "watcher: " key))  
  (add-watch x :test watcher)  
  (remove-watch x :test))  
=> nil
```

[top](#)

repeat

```
(repeat n x)
```

Returns a collection with the value x repeated n times

```
(repeat 5 [1 2])  
=> ([1 2] [1 2] [1 2] [1 2] [1 2])
```

[top](#)

repeatedly

```
(repeatedly n fn)
```

Takes a function of no args, presumably with side effects, and returns a collection of n calls to it

```
(repeatedly 5 #(rand-long 11))  
=> (10 9 6 6 8)
```

```
;; compare with repeat, which only calls the 'rand-long'  
;; function once, repeating the value five times.  
(repeat 5 (rand-long 11))  
=> (0 0 0 0 0)
```

replace

```
(replace smap coll)
```

Given a map of replacement pairs and a collection, returns a collection with any elements that are a key in smap replaced with the corresponding value in smap.

```
(replace {2 :two, 4 :four} [4 2 3 4 5 6 2])  
=> [:four :two 3 :four 5 6 :two]
```

```
(replace {2 :two, 4 :four} #{1 2 3 4 5})  
=> #{1 3 5 :four :two}
```

```
(replace [{:a 10] [:c 30]} {:a 10 :b 20})  
=> {:b 20 :c 30}
```

reset!

```
(reset! atom newval)
```

Sets the value of atom to newval without regard for the current value. Returns newval.

```
(do  
  (def counter (atom 0))  
  (reset! counter 99)  
  (deref counter))  
=> 99
```

resolve

Resolves a symbol.

```
(resolve '+)  
=> function + {visibility :public, module "core"}
```

```
(resolve (symbol "+"))  
=> function + {visibility :public, module "core"}
```

rest

```
(rest coll)
```

Returns a collection with second to list element

```
(rest nil)
=> nil

(rest [])
=> []

(rest [1])
=> []

(rest [1 2 3])
=> [2 3]

(rest '())
=> ()

(rest '(1))
=> ()

(rest '(1 2 3))
=> (2 3)
```

[top](#)

restart-agent

```
(restart-agent agent state)
```

When an agent is failed, changes the agent state to new-state and then un-fails the agent so that sends are allowed again.

```
(do
  (def x (agent 100))
  (restart-agent x 200)
  (deref x))
=> 200
```

[top](#)

reverse

```
(reverse coll)
```

Returns a collection of the items in coll in reverse order

```
(reverse [1 2 3 4 5 6])
=> [6 5 4 3 2 1]
```

[top](#)

sandboxed?

```
(sandboxed? )
```

Returns true if there is a sandbox otherwise false

```
(sandboxed? )  
=> false
```

[top](#)

schedule-at-fixed-rate

```
(schedule-at-fixed-rate fn initial-delay period time-unit)
```

Creates and executes a periodic action that becomes enabled first after the given initial delay, and subsequently with the given period.
Returns a future. (future? f), (future-cancel f), and (future-done? f) will work on the returned future.
Time unit is one of :milliseconds, :seconds, :minutes, :hours, or :days.

```
(schedule-at-fixed-rate (fn[] (println "test")) 1 2 :seconds)
```

```
(let [s (schedule-at-fixed-rate (fn[] (println "test")) 1 2 :seconds)]  
  (sleep 16 :seconds)  
  (future-cancel s))
```

[top](#)

schedule-delay

```
(schedule-delay fn delay time-unit)
```

Creates and executes a one-shot action that becomes enabled after the given delay.
Returns a future. (deref f), (future? f), (future-cancel f), and (future-done? f) will work on the returned future.
Time unit is one of :milliseconds, :seconds, :minutes, :hours, or :days.

```
(schedule-delay (fn[] (println "test")) 1 :seconds)
```

```
(deref (schedule-delay (fn [] 100) 2 :seconds))
```

[top](#)

second

```
(second coll)
```

Returns the second element of coll.

```
(second nil)  
=> nil
```

```
(second [])  
=> nil
```

```
(second [1 2 3])  
=> 2
```

```
(second '())  
=> nil
```

```
(second '(1 2 3))  
=> 2
```

[top](#)

send

```
(send agent action-fn args)
```

Dispatch an action to an agent. Returns the agent immediately. The state of the agent will be set to the value of:

```
(apply action-fn state-of-agent args)
```

```
(do  
  (def x (agent 100))  
  (send x + 5)  
  (sleep 100)  
  (deref x))  
=> 105
```

[top](#)

send-off

```
(send-off agent fn args)
```

Dispatch a potentially blocking action to an agent. Returns the agent immediately. The state of the agent will be set to the value of:

```
(apply action-fn state-of-agent args)
```

```
(do  
  (def x (agent 100))  
  (send-off x + 5)  
  (sleep 100)  
  (deref x))  
=> 105
```

[top](#)

seq

```
(seq coll)
```

Returns a seq on the collection. If the collection is empty, returns nil. (seq nil) returns nil. seq also works on Strings.

```
(seq nil)  
=> nil
```

```
(seq [1 2 3])  
=> (1 2 3)
```

```
(seq '(1 2 3))  
=> (1 2 3)
```

```
(seq {:a 1 :b 2})
=> ([:a 1] [:b 2])

(seq "abcd")
=> ("a" "b" "c" "d")
```

[top](#)

sequential?

```
(sequential? obj)
```

Returns true if obj is a sequential collection

```
(sequential? '(1))
=> true
```

```
(sequential? [1])
=> true
```

```
(sequential? {:a 1})
=> false
```

```
(sequential? nil)
=> false
```

```
(sequential? "abc")
=> false
```

[top](#)

set

```
(set & items)
```

Creates a new set containing the items.

```
(set )
=> #{} 
```

```
(set nil)
=> #{nil}
```

```
(set 1)
=> #{1}
```

```
(set 1 2 3)
=> #{1 2 3}
```

```
(set [1 2] 3)
=> #{[1 2] 3}
```

[top](#)

set!

```
(set! var-symbol expr)
```


Sets a global or thread-local variable to the value of the expression.

```
(do
  (def x 10)
  (set! x 20)
  x)
=> 20

(do
  (def-dynamic x 100)
  (set! x 200)
  x)
=> 200

(do
  (def-dynamic x 100)
  (without-str
    (print x)
    (binding [x 200]
      (print (str "-" x))
      (set! x (inc x))
      (print (str "-" x)))
    (print (str "-" x))))
=> "100-200-201-100"
```

[top](#)

set-error-handler!

```
(set-error-handler! agent handler-fn)
```

Sets the error-handler of an agent to handler-fn. If an action being run by the agent throws an exception handler-fn will be called with two arguments: the agent and the exception.

```
(do
  (def x (agent 100))
  (defn err-handler-fn [ag ex]
    (println "error occured: "
      (:message ex)
      " and we still have value"
      @ag))
  (set-error-handler! x err-handler-fn)
  (send x (fn [n] (/ n 0))))
=> (agent :value 100)
```

[top](#)

set?

```
(set? obj)
```

Returns true if obj is a set

```
(set? (set 1))
=> true
```

[top](#)

sh

```
(sh & args)
```

Passes the given strings to `Runtime.exec()` to launch a sub-process.

Options are

- `:in` may be given followed by input source as `InputStream`, `Reader`, `File`, `ByteBuf`, or `String`, to be fed to the sub-process's `stdin`.
- `:in-enc` option may be given followed by a `String`, used as a character encoding name (for example `"UTF-8"` or `"ISO-8859-1"`) to convert the input string specified by the `:in` option to the sub-process's `stdin`. Defaults to `UTF-8`. If the `:in` option provides a byte array, then the bytes are passed unencoded, and this option is ignored.
- `:out-enc` option may be given followed by `:bytes` or a `String`. If a `String` is given, it will be used as a character encoding name (for example `"UTF-8"` or `"ISO-8859-1"`) to convert the sub-process's `stdout` to a `String` which is returned. If `:bytes` is given, the sub-process's `stdout` will be stored in a `Bytebuf` and returned. Defaults to `UTF-8`.
- `:env` override the process `env` with a map.
- `:dir` override the process `dir` with a `String` or `java.io.File`.
- `:throw-ex` If true throw an exception if the exit code is not equal to zero, if false returns the exit code. Defaults to false. It's recommended to use (`with-sh-throw (sh "foo")`) instead.

You can bind `:env`, `:dir` for multiple operations using `with-sh-env` or `with-sh-dir`. `with-sh-throw` is binds `:throw-ex` as true.

sh returns a map of

- `:exit` => sub-process's exit code
- `:out` => sub-process's `stdout` (as `Bytebuf` or `String`)
- `:err` => sub-process's `stderr` (`String` via platform default encoding)

```
(println (sh "ls" "-l"))

(println (sh "ls" "-l" "/tmp"))

(println (sh "sed" "s/[aeiou]/oo/g" :in "hello there\n"))

(println (sh "cat" :in "x\u25bax\n"))

(println (sh "echo" "x\u25bax"))

(println (sh "/bin/sh" "-c" "ls -l"))

;; reads 4 single-byte chars
(println (sh "echo" "x\u25bax" :out-enc "ISO-8859-1"))

;; reads binary file into bytes[]
(println (sh "cat" "birds.jpg" :out-enc :bytes))

;; working directory
(println (with-sh-dir "/tmp" (sh "ls" "-l") (sh "pwd")))

(println (sh "pwd" :dir "/tmp"))
```

```
;; throw an exception if the shell's subprocess exit code is not equal to 0
(println (with-sh-throw (sh "ls" "-l")))

(println (sh "ls" "-l" :throw-ex true))

;; windows
(println (sh "cmd" "/c dir 1>&2"))
```

[top](#)

shutdown-agents

```
(shutdown-agents )
```

Initiates a shutdown of the thread pools that back the agent system. Running actions will complete, but no new actions will be accepted

```
(do
  (def x1 (agent 100))
  (def x2 (agent 100))
  (shutdown-agents ))
```

[top](#)

shutdown-agents?

```
(shutdown-agents?)
```

Returns true if the thread-pool that backs the agents is shut down

```
(do
  (def x1 (agent 100))
  (def x2 (agent 100))
  (shutdown-agents )
  (sleep 300)
  (shutdown-agents? ))
```

[top](#)

shutdown-hook

```
(shutdown-hook f)
```

Registers the function `f` as JVM shutdown hook.

```
(shutdown-hook (fn [] (println "shutdown")))
=> nil
```

[top](#)

sleep

```
(sleep n)
(sleep n time-unit)
```

Sleep for the time n. The default time unit is milliseconds
Time unit is one of :milliseconds, :seconds, :minutes, :hours, or :days.

```
(sleep 30)
=> nil
```

```
(sleep 30 :milliseconds)
=> nil
```

```
(sleep 5 :seconds)
=> nil
```

[top](#)

some?

```
(some? x)
```

Returns true if x is not nil, false otherwise

```
(some? nil)
=> false
```

```
(some? 0)
=> true
```

```
(some? 4.0)
=> true
```

```
(some? false)
=> true
```

```
(some? [])
=> true
```

```
(some? {})
=> true
```

[top](#)

sort

```
(sort coll)
(sort comparefn coll)
```

Returns a sorted list of the items in coll. If no compare function comparefn is supplied, uses the natural compare. The compare function takes two arguments and returns -1, 0, or 1

```
(sort [3 2 5 4 1 6])
=> [1 2 3 4 5 6]
```

```
(sort compare [3 2 5 4 1 6])
=> [1 2 3 4 5 6]
```

```
; reversed
(sort (comp (partial * -1) compare) [3 2 5 4 1 6])
=> [6 5 4 3 2 1]
```

```
(sort {:c 3 :a 1 :b 2})
=> ([:a 1] [:b 2] [:c 3])
```

[top](#)

sort-by

```
(sort-by keyfn coll)
(sort-by keyfn compfn coll)
```

Returns a sorted sequence of the items in `coll`, where the sort order is determined by comparing `(keyfn item)`. If no comparator is supplied, uses `compare`.

```
(sort-by count ["aaa" "bb" "c"])
=> ["c" "bb" "aaa"]
```

```
; reversed
(sort-by count (comp (partial * -1) compare) ["aaa" "bb" "c"])
=> ["aaa" "bb" "c"]
```

```
(sort-by first [[1 2] [3 4] [2 3]])
=> [[1 2] [2 3] [3 4]]
```

```
; reversed
(sort-by first (comp (partial * -1) compare) [[1 2] [3 4] [2 3]])
=> [[3 4] [2 3] [1 2]]
```

```
(sort-by (fn [x] (get x :rank)) [{:rank 2} {:rank 3} {:rank 1}])
=> [{:rank 1} {:rank 2} {:rank 3}]
```

```
; reversed
(sort-by (fn [x] (get x :rank)) (comp (partial * -1) compare) [{:rank 2} {:rank 3} {:rank 1}])
=> [{:rank 3} {:rank 2} {:rank 1}]
```

[top](#)

sorted-map

```
(sorted-map & keyvals)
(sorted-map map)
```

Creates a new sorted map containing the items.

```
(sorted-map :a 1 :b 2)
=> {:a 1 :b 2}
```

```
(sorted-map (hash-map :a 1 :b 2))
=> {:a 1 :b 2}
```

[top](#)

sorted-map?

```
(sorted-map? obj)
```

Returns true if `obj` is a sorted map

```
(sorted-map? (sorted-map :a 1 :b 2))  
=> true
```

[top](#)

sorted-set

```
(sorted-set & items)
```

Creates a new sorted-set containing the items.

```
(sorted-set )  
=> #{} 
```

```
(sorted-set nil)  
=> #{nil} 
```

```
(sorted-set 1)  
=> #{1} 
```

```
(sorted-set 6 2 4)  
=> #{2 4 6} 
```

```
(str (sorted-set [2 3] [1 2]))  
=> "##[[1 2] [2 3]]" 
```

[top](#)

sorted-set?

```
(sorted-set? obj)
```

Returns true if obj is a sorted-set

```
(sorted-set? (set 1))  
=> false 
```

[top](#)

split-at

```
(split-at n coll)
```

Returns a vector of [(take n coll) (drop n coll)]

```
(split-at 2 [1 2 3 4 5])  
=> [(1 2) (3 4 5)] 
```

```
(split-at 3 [1 2])  
=> [(1 2) ()] 
```

[top](#)

split-with

```
(split-with pred coll)
```

Splits the collection at the first false/nil predicate result in a vector with two lists

```
(split-with odd? [1 3 5 6 7 9])  
=> [(1 3 5) (6 7 9)]
```

```
(split-with odd? [1 3 5])  
=> [(1 3 5) ()]
```

```
(split-with odd? [2 4 6])  
=> [()] (2 4 6)]
```

[top](#)

sqrt

```
(sqrt x)
```

Square root of x

```
(sqrt 10)  
=> 3.1622776601683795
```

```
(sqrt (int 10))  
=> 3.1622776601683795
```

```
(sqrt 10.23)  
=> 3.1984371183438953
```

```
(sqrt 10.23M)  
=> 3.198437118343895324557024650857783854007720947265625M
```

[top](#)

stack

```
(stack )
```

Creates a new mutable threadsafe stack.

```
(let [s (stack)]  
  (push! s 4)  
  (push! s 3)  
  (pop! s)  
  s)  
=> (4)
```

[top](#)

stack?

```
(stack? obj)
```

Returns true if obj is a stack

```
(stack? (stack))  
=> true
```

[top](#)

str

```
(str & xs)
```

With no args, returns the empty string. With one arg x, returns x.toString(). (str nil) returns the empty string. With more than one arg, returns the concatenation of the str values of the args.

```
(str )  
=> ""
```

```
(str 1 2 3)  
=> "123"
```

```
(str +)  
=> "function + {visibility :public, module \"core\"}"
```

```
(str [1 2 3])  
=> "[1 2 3]"
```

[top](#)

str/blank?

```
(str/blank? s)
```

True if s is blank.

```
(str/blank? nil)  
=> true
```

```
(str/blank? "")  
=> true
```

```
(str/blank? " ")  
=> true
```

```
(str/blank? "abc")  
=> false
```

[top](#)

str/bytebuf-to-hex

```
(str/bytebuf-to-hex data)  
(str/bytebuf-to-hex data :upper)
```

Converts byte data to a hex string using the hexadecimal digits: 0123456789abcdef. If the :upper options is passed the hex digits 0123456789ABCDEF are used.

```
(str/bytebuf-to-hex (bytebuf [0 1 2 3 4 5 6]))  
=> "00010203040506"
```


[top](#)

str/char

```
(str/char n)
```

Converts a number to a single char string.

```
(str/char 65)  
=> "A"
```

[top](#)

str/contains?

```
(str/contains? s substr)
```

True if s contains with substr.

```
(str/contains? "abc" "ab")  
=> true
```

[top](#)

str/decode-base64

```
(str/decode-base64 s)
```

Base64 decode.

```
(str/decode-base64 (str/encode-base64 (bytebuf [0 1 2 3 4 5 6])))  
=> [0 1 2 3 4 5 6]
```

[top](#)

str/decode-url

```
(str/decode-url s)
```

URL decode.

```
(str/decode-url "The+string+%C3%BC%40foo-bar")  
=> "The string ü@foo-bar"
```

[top](#)

str/digit?

```
(str/digit? s)
```

True if s is a single char string and the char is a digit. Defined by Java Character.isDigit(ch).

```
(str/digit? "8")  
=> true
```

[top](#)

str/double-quote

```
(str/double-quote str)
```

Double quotes a string.

```
(str/double-quote "abc")  
=> "\"abc\""
```

```
(str/double-quote "")  
=> "\"\""
```

[top](#)

str/encode-base64

```
(str/encode-base64 data)
```

Base64 encode.

```
(str/encode-base64 (bytebuf [0 1 2 3 4 5 6]))  
=> "AAECAwQFBg=="
```

[top](#)

str/encode-url

```
(str/encode-url s)
```

URL encode.

```
(str/encode-url "The string ü@foo-bar")  
=> "The+string+%C3%BC%40foo-bar"
```

[top](#)

str/ends-with?

```
(str/ends-with? s substr)
```

True if s ends with substr.

```
(str/starts-with? "abc" "bc")  
=> false
```

[top](#)

str/equals-ignore-case?

```
(str/equals-ignore-case? s1 s2)
```

Compares two strings ignoring case. True if both are equal.

```
(str/equals-ignore-case? "abc" "abC")  
=> true
```

[top](#)

str/escape-html

```
(str/escape-html s)
```

HTML escape. Escapes &, <, >, ", ', and the non blocking space U+00A0

```
(str/escape-html "1 2 3 & < > \" ' \u00A0")  
=> "1 2 3 &amp; &lt; &gt; &quot; &apos; &nbsp;"
```

[top](#)

str/escape-xml

```
(str/escape-xml s)
```

XML escape. Escapes &, <, >, ", ' ,

```
(str/escape-xml "1 2 3 & < > \" ' ")  
=> "1 2 3 &amp; &lt; &gt; &quot; &apos;"
```

[top](#)

str/format

```
(str/format format args*)  
(str/format locale format args*)
```

Returns a formatted string using the specified format string and arguments.

```
(str/format "value: %.4f" 1.45)  
=> "value: 1.4500"
```

```
(str/format (. :java.util.Locale :new "de" "DE") "value: %.4f" 1.45)  
=> "value: 1,4500"
```

```
(str/format (. :java.util.Locale :GERMANY) "value: %.4f" 1.45)  
=> "value: 1,4500"
```

```
(str/format [ "de"] "value: %.4f" 1.45)  
=> "value: 1,4500"
```

```
(str/format [ "de" "DE"] "value: %.4f" 1.45)  
=> "value: 1,4500"
```

str/format-bytebuf

(str/format-bytebuf data delimiter & options)

Formats a bytebuffer.

Options

:prefix0x - prefix with 0x

```
(str/format-bytebuf (bytebuf [0 34 67 -30 -1]) nil)
=> "002243E2FF"
```

```
(str/format-bytebuf (bytebuf [0 34 67 -30 -1]) "")
=> "002243E2FF"
```

```
(str/format-bytebuf (bytebuf [0 34 67 -30 -1]) ", ")
=> "00, 22, 43, E2, FF"
```

```
(str/format-bytebuf (bytebuf [0 34 67 -30 -1]) ", " :prefix0x)
=> "0x00, 0x22, 0x43, 0xE2, 0xFF"
```

str/hex-to-bytebuf

(str/hex-to-bytebuf hex)

Converts a hex string to a bytebuf

```
(str/hex-to-bytebuf "005E4AFF")
=> [0 94 74 255]
```

```
(str/hex-to-bytebuf "005e4aff")
=> [0 94 74 255]
```

str/index-of

(str/index-of s value)
(str/index-of s value from-index)

Return index of value (string or char) in s, optionally searching forward from from-index. Return nil if value not found.

```
(str/index-of "abcdefabc" "ab")
=> 0
```

str/join

```
(str/join coll)
(str/join separator coll)
```

Joins all elements in coll separated by an optional separator.

```
(str/join [1 2 3])
=> "123"
```

```
(str/join "-" [1 2 3])
=> "1-2-3"
```

[top](#)

str/last-index-of

```
(str/last-index-of s value)
(str/last-index-of s value from-index)
```

Return last index of value (string or char) in s, optionally searching backward from from-index. Return nil if value not found.

```
(str/last-index-of "abcdefabc" "ab")
=> 6
```

[top](#)

str/letter?

```
(str/letter? s)
```

True if s is a single char string and the char is a letter. Defined by Java Character.isLetter(ch).

```
(str/letter? "x")
=> true
```

[top](#)

str/linefeed?

```
(str/linefeed? s)
```

True if s is a single char string and the char is a linefeed.

```
(str/linefeed? "
")
=> true
```

[top](#)

str/lorem-ipsum

```
(str/lorem-ipsum & options)
```

Creates an arbitrary length Lorem Ipsum text.

Options:

- :chars n - returns n characters (limited to 1000000)
- :paragraphs n - returns n paragraphs (limited to 100)

```
(str/lorem-ipsum :chars 250)
```

```
=> "Lorem ipsum dolor sit amet, consectetur adipiscing elit. Praesent ac iaculis turpis. Duis dictum id sem et  
consectetur. Nullam lobortis, libero non consequat aliquet, lectus diam fringilla velit, finibus eleifend ipsum  
urna at lacus. Phasellus sit am"
```

```
(str/lorem-ipsum :paragraphs 1)
```

```
=> "Lorem ipsum dolor sit amet, consectetur adipiscing elit. Praesent ac iaculis turpis. Duis dictum id sem et  
consectetur. Nullam lobortis, libero non consequat aliquet, lectus diam fringilla velit, finibus eleifend ipsum  
urna at lacus. Phasellus sit amet nisl fringilla, cursus est in, mollis lacus. Proin dignissim rhoncus dolor.  
Cras tellus odio, elementum sed erat sit amet, euismod tincidunt nisl. In hac habitasse platea dictumst. Duis  
aliquam sollicitudin tempor. Sed gravida tincidunt felis at fringilla. Morbi tempor enim at commodo vulputate.  
Aenean et ultrices lorem, placerat pretium augue. In hac habitasse platea dictumst. Cras fringilla ligula quis  
interdum hendrerit. Etiam at massa tempor, facilisis lacus placerat, congue erat."
```

[top](#)

str/lower-case

```
(str/lower-case s)
```

Converts s to lowercase

```
(str/lower-case "aBcDeF")  
=> "abcdef"
```

[top](#)

str/quote

```
(str/quote str q)  
(str/quote str start end)
```

Quotes a string.

```
(str/quote "abc" "-")  
=> "-abc-"
```

```
(str/quote "abc" "<" ">")  
=> "<abc>"
```

[top](#)

str/repeat

```
(str/repeat s n)  
(str/repeat s n sep)
```

Repeats s n times with an optional separator.

```
(str/repeat "abc" 0)
=> ""

(str/repeat "abc" 3)
=> "abccabccabc"

(str/repeat "abc" 3 "-")
=> "abc-abc-abc"
```

[top](#)

str/replace-all

```
(str/replace-all s search replacement)
```

Replaces the all occurrences of search in s. The search arg may be a string or a regex pattern

```
(str/replace-all "abcdefabc" "ab" "__")
=> "__cdef__c"

(str/replace-all "a0b01c012d" (regex/pattern "[0-9]+") "_")
=> "a_b_c_d"
```

[top](#)

str/replace-first

```
(str/replace-first s search replacement)
```

Replaces the first occurrence of search in s. The search arg may be a string or a regex pattern

```
(str/replace-first "abcdefabc" "ab" "XYZ")
=> "XYZdefabc"

(str/replace-first "a0b01c012d" (regex/pattern "[0-9]+") "_")
=> "a_b01c012d"
```

[top](#)

str/replace-last

```
(str/replace-last s search replacement)
```

Replaces the last occurrence of search in s

```
(str/replace-last "abcdefabc" "ab" "XYZ")
=> "abcdeXYZ"
```

[top](#)

str/split

```
(str/split s regex)
```

Splits string on a regular expression.

```
(str/split "abc,def,ghi" ",")  
=> ("abc" "def" "ghi")  
  
(str/split "abc , def , ghi" "[ *],[ *]")  
=> ("abc" "def" "ghi")  
  
(str/split "abc,def,ghi" "((?<=,)|(?=,))")  
=> ("abc" ", " "def" ", " "ghi")
```

[top](#)

str/split-lines

```
(str/split-lines s)
```

Splits `s` into lines.

```
(str/split-lines "line1  
line2  
line3")  
=> ("line1" "line2" "line3")
```

[top](#)

str/starts-with?

```
(str/starts-with? s substr)
```

True if `s` starts with `substr`.

```
(str/starts-with? "abc" "ab")  
=> true
```

[top](#)

str/strip-end

```
(str/strip-end s substr)
```

Removes a `substr` only if it is at the end of a `s`, otherwise returns `s`.

```
(str/strip-end "abcdef" "def")  
=> "abc"
```

```
(str/strip-end "abcdef" "abc")  
=> "abcdef"
```

[top](#)

str/strip-indent

```
(str/strip-indent s)
```


Strip the indent of a multi-line string. The first line's leading whitespaces define the indent.

```
(str/strip-indent "  line1
  line2
  line3")
=> "line1\n  line2\n  line3"
```

[top](#)

str/strip-margin

```
(str/strip-margin s)
```

Strips leading whitespaces upto and including the margin '|' from each line in a multi-line string.

```
(str/strip-margin "line1
|  line2
|  line3")
=> "line1\n  line2\n  line3"
```

[top](#)

str/strip-start

```
(str/strip-start s substr)
```

Removes a substr only if it is at the beginning of a s, otherwise returns s.

```
(str/strip-start "abcdef" "abc")
=> "def"
```

```
(str/strip-start "abcdef" "def")
=> "abcdef"
```

[top](#)

str/subs

```
(str/subs s start)
(str/subs s start end)
```

Returns the substring of s beginning at start inclusive, and ending at end (defaults to length of string), exclusive.

```
(str/subs "abcdef" 2)
=> "cdef"
```

```
(str/subs "abcdef" 2 5)
=> "cde"
```

[top](#)

str/trim

```
(str/trim s)
```

Trims leading and trailing spaces from s.

```
(str/trim " abc ")  
=> "abc"
```

[top](#)

str/trim-to-nil

```
(str/trim-to-nil s)
```

Trims leading and trailing spaces from s. Returns nil if the resulting string is empty

```
(str/trim-to-nil "")  
=> nil
```

```
(str/trim-to-nil "  ")  
=> nil
```

```
(str/trim-to-nil nil)  
=> nil
```

```
(str/trim-to-nil " abc ")  
=> "abc"
```

[top](#)

str/truncate

```
(str/truncate s maxlen marker)
```

Truncates a string to the max length maxlen and adds the marker to the end if the string needs to be truncated

```
(str/truncate "abcdefghij" 20 "...")  
=> "abcdefghij"
```

```
(str/truncate "abcdefghij" 9 "...")  
=> "abcdef..."
```

```
(str/truncate "abcdefghij" 4 "...")  
=> "a..."
```

[top](#)

str/upper-case

```
(str/upper-case s)
```

Converts s to uppercase

```
(str/upper-case "aBcDeF")  
=> "ABCDEF"
```

str/whitespace?

```
(str/whitespace? s)
```

True if `s` is a single char string and the char is a whitespace. Defined by `Java Character.isWhitespace(ch)`.

```
(str/whitespace? " ")
=> true
```

string-array

```
(string-array coll)
(string-array len)
(string-array len init-val)
```

Returns an array of Java strings containing the contents of `coll` or returns an array with the given length and optional init value

```
(string-array '("1" "2" "3"))
=> ["1", "2", "3"]
```

```
(string-array 10)
=> [nil, nil, nil, nil, nil, nil, nil, nil, nil, nil]
```

```
(string-array 10 "42")
=> ["42", "42", "42", "42", "42", "42", "42", "42", "42", "42"]
```

string?

```
(string? x)
```

Returns true if `x` is a string

```
(string? "abc")
=> true
```

```
(string? 1)
=> false
```

```
(string? nil)
=> false
```

subvec

```
(subvec v start) (subvec v start end)
```

Returns a vector of the items in vector from start (inclusive) to end (exclusive). If end is not supplied, defaults to (count vector)

```
(subvec [1 2 3 4 5 6] 2)
=> [3 4 5 6]
```

```
(subvec [1 2 3 4 5 6] 4)
=> [5 6]
```

[top](#)

swap!

```
(swap! atom f & args)
```

Atomically swaps the value of atom to be: (apply f current-value-of-atom args). Note that f may be called multiple times, and thus should be free of side effects. Returns the value that was swapped in.

```
(do
  (def counter (atom 0))
  (swap! counter inc)
  (deref counter))
=> 1
```

[top](#)

symbol

```
(symbol name)
```

Returns a symbol from the given name

```
(symbol "a")
=> a
```

```
(symbol 'a)
=> a
```

[top](#)

symbol?

```
(symbol? x)
```

Returns true if x is a symbol

```
(symbol? (symbol "a"))
=> true
```

```
(symbol? 'a)
=> true
```

```
(symbol? nil)
=> false
```

```
(symbol? :a)
=> false
```

[top](#)

system-prop

```
(system-prop name default-val)
```

Returns the system property with the given name. Returns the default-val if the property does not exist or it's value is nil

```
(system-prop :os.name)
=> "Mac OS X"
```

```
(system-prop :foo.org "abc")
=> "abc"
```

```
(system-prop "os.name")
=> "Mac OS X"
```

[top](#)

take

```
(take n coll)
```

Returns a collection of the first n items in coll, or all items if there are fewer than n. Returns a transducer when no collection is provided.

```
(take 3 [1 2 3 4 5])
=> [1 2 3]
```

```
(take 10 [1 2 3 4 5])
=> [1 2 3 4 5]
```

[top](#)

take-while

```
(take-while predicate coll)
```

Returns a list of successive items from coll while (predicate item) returns logical true. Returns a transducer when no collection is provided.

```
(take-while neg? [-2 -1 0 1 2 3])
=> [-2 -1]
```

[top](#)

third

```
(third coll)
```

Returns the third element of coll.

```
(third nil)
=> nil
```

```
(third [])
=> nil
```

```
(second [1 2 3])
=> 2
```

```
(third '())
=> nil
```

```
(third '(1 2 3))
=> 3
```

[top](#)

thread-id

```
(thread-id)
```

Returns the identifier of this Thread. The thread ID is a positive number generated when this thread was created. The thread ID is unique and remains unchanged during its lifetime. When a thread is terminated, this thread ID may be reused.

```
(thread-id)
=> 1
```

[top](#)

thread-local

```
(thread-local)
```

Creates a new thread-local accessor

```
(thread-local :a 1 :b 2)
=> ThreadLocal
```

```
(thread-local { :a 1 :b 2 })
=> ThreadLocal
```

```
(do
  (thread-local-clear)
  (assoc (thread-local) :a 1 :b 2)
  (dissoc (thread-local) :a)
  (get (thread-local) :b 100)
)
=> 2
```

[top](#)

thread-local-clear

```
(thread-local-clear)
```

Removes all thread local vars

```
(thread-local-clear)
=> function thread-local-clear {visibility :public, module "core"}
```

[top](#)

thread-local?

```
(thread-local? x)
```

Returns true if x is a thread-local, otherwise false

```
(do
  (def x (thread-local))
  (thread-local? x))
=> true
```

[top](#)

thread-name

```
(thread-name)
```

Returns this thread's name.

```
(thread-name)
=> "main"
```

[top](#)

throw

```
(throw)
(throw x)
```

Throws exception with passed value x

```
(do
  (try
    (+ 100 200)
    (catch :Exception ex (:message ex))))
=> 300

(do
  (try
    (throw 100)
    (catch :ValueException ex (:value ex))))
=> 100

(do
  (try
    (throw [100 {:a 3}])
    (catch :ValueException ex (:value ex))))
```

```

        (finally (println "#finally")))))
#finally
=> [100 {:a 3}]

(do
  (import :java.lang.RuntimeException)
  (try
    (throw (. :RuntimeException :new "#test"))
    (catch :RuntimeException ex (:message ex))))
=> "#test"

;; Venice wraps thrown checked exceptions with a RuntimeException!
(do
  (import :java.lang.RuntimeException)
  (import :java.io.IOException)
  (try
    (throw (. :IOException :new "#test"))
    (catch :RuntimeException ex (:message (:cause ex)))))
=> "#test"

```

[top](#)

time

```
(time expr)
```

Evaluates expr and prints the time it took. Returns the value of expr.

```

(time (+ 100 200))
Elapsed time: 10.61 us
=> 300

```

[top](#)

time/after?

```
(time/after? date1 date2)
```

Returns true if date1 is after date2 else false

```

(time/after? (time/local-date) (time/minus (time/local-date) :days 2))
=> true

```

[top](#)

time/before?

```
(time/before? date1 date2)
```

Returns true if date1 is before date2 else false

```

(time/before? (time/local-date) (time/minus (time/local-date) :days 2))
=> false

```

[top](#)

time/date

```
(time/date)  
(time/date x)
```

Creates a new date. A date is represented by 'java.util.Date'

```
(time/date)  
=> Sun Jul 14 16:08:57 CEST 2019
```

[top](#)

time/date?

```
(time/date? date)
```

Returns true if date is a date else false

```
(time/date? (time/date))  
=> true
```

[top](#)

time/day-of-month

```
(time/day-of-month date)
```

Returns the day of the month (1..31)

```
(time/day-of-month (time/local-date))  
=> 14
```

```
(time/day-of-month (time/local-date-time))  
=> 14
```

```
(time/day-of-month (time/zoned-date-time))  
=> 14
```

[top](#)

time/day-of-week

```
(time/day-of-week date)
```

Returns the day of the week (:MONDAY ... :SUNDAY)

```
(time/day-of-week (time/local-date))  
=> :SUNDAY
```

```
(time/day-of-week (time/local-date-time))  
=> :SUNDAY
```

```
(time/day-of-week (time/zoned-date-time))  
=> :SUNDAY
```

[top](#)

time/day-of-year

```
(time/day-of-year date)
```

Returns the day of the year (1..366)

```
(time/day-of-year (time/local-date))  
=> 195
```

```
(time/day-of-year (time/local-date-time))  
=> 195
```

```
(time/day-of-year (time/zoned-date-time))  
=> 195
```

[top](#)

time/earliest

```
(time/earliest coll)
```

Returns the earliest date from a collection of dates. All dates must be of equal type. The coll may be empty or nil.

```
(time/earliest [(time/local-date 2018 8 4) (time/local-date 2018 8 3)])  
=> 2018-08-03
```

[top](#)

time/first-day-of-month

```
(time/first-day-of-month date)
```

Returns the first day of a month as a local-date.

```
(time/first-day-of-month (time/local-date))  
=> 2019-07-01
```

```
(time/first-day-of-month (time/local-date-time))  
=> 2019-07-01
```

```
(time/first-day-of-month (time/zoned-date-time))  
=> 2019-07-01
```

[top](#)

time/format

```
(time/format date format locale?)  
(time/format date formatter locale?)
```

Formats a date with a format

```
(time/format (time/local-date) "dd-MM-yyyy")
=> "14-07-2019"

(time/format (time/zoned-date-time) "yyyy-MM-dd'T'HH:mm:ss.SSSz")
=> "2019-07-14T16:08:58.016CEST"

(time/format (time/zoned-date-time) :ISO_OFFSET_DATE_TIME)
=> "2019-07-14T16:08:58.021+02:00"

(time/format (time/zoned-date-time) (time/formatter "yyyy-MM-dd'T'HH:mm:ss.SSSz"))
=> "2019-07-14T16:08:58.025CEST"

(time/format (time/zoned-date-time) (time/formatter :ISO_OFFSET_DATE_TIME))
=> "2019-07-14T16:08:58.03+02:00"
```

[top](#)

time/formatter

(time/formatter format locale?)

Creates a formatter

```
(time/formatter "dd-MM-yyyy")
=> Value(DayOfMonth,2)'-'Value(MonthOfYear,2)'-'Value(YearOfEra,4,19,EXCEEDS_PAD)

(time/formatter "dd-MM-yyyy" :en_EN)
=> Value(DayOfMonth,2)'-'Value(MonthOfYear,2)'-'Value(YearOfEra,4,19,EXCEEDS_PAD)

(time/formatter "dd-MM-yyyy" "en_EN")
=> Value(DayOfMonth,2)'-'Value(MonthOfYear,2)'-'Value(YearOfEra,4,19,EXCEEDS_PAD)

(time/formatter "yyyy-MM-dd'T'HH:mm:ss.SSSz")
=> Value(YearOfEra,4,19,EXCEEDS_PAD)'-'Value(MonthOfYear,2)'-'Value(DayOfMonth,2)'T'Value(HourOfDay,2)':'Value(MinuteOfHour,2)':'Value(SecondOfMinute,2)'. 'Fraction(NanoOfSecond,3,3)ZoneText(SHORT)

(time/formatter :ISO_OFFSET_DATE_TIME)
=> ParseCaseSensitive(false)(ParseCaseSensitive(false)(Value(Year,4,10,EXCEEDS_PAD)'-'Value(MonthOfYear,2)'-'Value(DayOfMonth,2))'T'(Value(HourOfDay,2)':'Value(MinuteOfHour,2)['Value(SecondOfMinute,2)[Fraction(NanoOfSecond,0,9,DecimalPoint)]))Offset(+HH:MM:ss,'Z')
```

[top](#)

time/hour

(time/hour date)

Returns the hour of the date 1..24

```
(time/hour (time/local-date))
=> 0

(time/hour (time/local-date-time))
=> 16

(time/hour (time/zoned-date-time))
=> 16
```

time/last-day-of-month

```
(time/last-day-of-month date)
```

Returns the last day of a month as a local-date.

```
(time/last-day-of-month (time/local-date))  
=> 2019-07-31
```

```
(time/last-day-of-month (time/local-date-time))  
=> 2019-07-31
```

```
(time/last-day-of-month (time/zoned-date-time))  
=> 2019-07-31
```

time/latest

```
(time/latest coll)
```

Returns the latest date from a collection of dates. All dates must be of equal type. The coll may be empty or nil.

```
(time/latest [(time/local-date 2018 8 1) (time/local-date 2018 8 3)])  
=> 2018-08-03
```

time/leap-year?

```
(time/leap-year? date)
```

Checks if the year is a leap year.

```
(time/leap-year? 2000)  
=> true
```

```
(time/leap-year? (time/local-date 2000 1 1))  
=> true
```

```
(time/leap-year? (time/local-date-time))  
=> false
```

```
(time/leap-year? (time/zoned-date-time))  
=> false
```

time/length-of-month

```
(time/length-of-month date)
```

Returns the length of the month represented by this date.

```
(time/length-of-month (time/local-date 2000 2 1))  
=> 29
```

```
(time/length-of-month (time/local-date 2001 2 1))  
=> 28
```

```
(time/length-of-month (time/local-date-time))  
=> 31
```

```
(time/length-of-month (time/zoned-date-time))  
=> 31
```

[top](#)

time/length-of-year

```
(time/length-of-year date)
```

Returns the length of the year represented by this date.

```
(time/length-of-year (time/local-date 2000 1 1))  
=> 366
```

```
(time/length-of-year (time/local-date 2001 1 1))  
=> 365
```

```
(time/length-of-year (time/local-date-time))  
=> 365
```

```
(time/length-of-year (time/zoned-date-time))  
=> 365
```

[top](#)

time/local-date

```
(time/local-date)  
(time/local-date year month day)  
(time/local-date date)
```

Creates a new local-date. A local-date is represented by 'java.time.LocalDate'

```
(time/local-date)  
=> 2019-07-14
```

```
(time/local-date 2018 8 1)  
=> 2018-08-01
```

```
(time/local-date "2018-08-01")  
=> 2018-08-01
```

```
(time/local-date 1375315200000)  
=> 2013-08-01
```

```
(time/local-date (. :java.util.Date :new))  
=> 2019-07-14
```

[top](#)

time/local-date-parse

```
(time/local-date-parse str format locale?)
```

Parses a local-date.

```
(time/local-date-parse "2018-08-01" "yyyy-MM-dd")  
=> 2018-08-01
```

[top](#)

time/local-date-time

```
(time/local-date-time)  
(time/local-date-time year month day)  
(time/local-date-time year month day hour minute second)  
(time/local-date-time year month day hour minute second millis)  
(time/local-date-time date)
```

Creates a new local-date-time. A local-date-time is represented by 'java.time.LocalDateTime'

```
(time/local-date-time)  
=> 2019-07-14T16:08:57.744
```

```
(time/local-date-time 2018 8 1)  
=> 2018-08-01T00:00
```

```
(time/local-date-time 2018 8 1 14 20 10)  
=> 2018-08-01T14:20:10
```

```
(time/local-date-time 2018 8 1 14 20 10 200)  
=> 2018-08-01T14:20:10.200
```

```
(time/local-date-time "2018-08-01T14:20:10.200")  
=> 2018-08-01T14:20:10.200
```

```
(time/local-date-time 1375315200000)  
=> 2013-08-01T02:00
```

```
(time/local-date-time (. :java.util.Date :new))  
=> 2019-07-14T16:08:57.762
```

[top](#)

time/local-date-time-parse

```
(time/local-date-time-parse str format locale?)
```

Parses a local-date-time.

```
(time/local-date-time-parse "2018-08-01 14:20" "yyyy-MM-dd HH:mm")
=> 2018-08-01T14:20

(time/local-date-time-parse "2018-08-01 14:20:01.000" "yyyy-MM-dd HH:mm:ss.SSS")
=> 2018-08-01T14:20:01
```

[top](#)

time/local-date-time?

```
(time/local-date-time? date)
```

Returns true if date is a local-date-time else false

```
(time/local-date-time? (time/local-date-time))
=> true
```

[top](#)

time/local-date?

```
(time/local-date? date)
```

Returns true if date is a locale date else false

```
(time/local-date? (time/local-date))
=> true
```

[top](#)

time/minus

```
(time/minus date unit n)
```

Subtracts the n units from the date. Units: { :years :months :weeks :days :hours :minutes :seconds :milliseconds }

```
(time/minus (time/local-date) :days 2)
=> 2019-07-12
```

```
(time/minus (time/local-date-time) :days 2)
=> 2019-07-12T16:08:58.105
```

```
(time/minus (time/zoned-date-time) :days 2)
=> 2019-07-12T16:08:58.110+02:00[Europe/Zurich]
```

[top](#)

time/minute

```
(time/minute date)
```

Returns the minute of the date 0..59

```
(time/minute (time/local-date))  
=> 0  
  
(time/minute (time/local-date-time))  
=> 8  
  
(time/minute (time/zoned-date-time))  
=> 8
```

[top](#)

time/month

```
(time/month date)  
  
Returns the month of the date 1..12  
  
(time/month (time/local-date))  
=> 7  
  
(time/month (time/local-date-time))  
=> 7  
  
(time/month (time/zoned-date-time))  
=> 7
```

[top](#)

time/not-after?

```
(time/not-after? date1 date2)  
  
Returns true if date1 is not-after date2 else false  
  
(time/not-after? (time/local-date) (time/minus (time/local-date) :days 2))  
=> false
```

[top](#)

time/not-before?

```
(time/not-before? date1 date2)  
  
Returns true if date1 is not-before date2 else false  
  
(time/not-before? (time/local-date) (time/minus (time/local-date) :days 2))  
=> true
```

[top](#)

time/period

```
(time/period from to unit)
```


Returns the period interval of two dates in the specified unit. Units: { :years :months :weeks :days :hours :minutes :seconds :milliseconds }

```
(time/period (time/local-date) (time/plus (time/local-date) :days 3) :days)
=> 3
```

```
(time/period (time/local-date-time) (time/plus (time/local-date-time) :days 3) :days)
=> 3
```

```
(time/period (time/zoned-date-time) (time/plus (time/zoned-date-time) :days 3) :days)
=> 3
```

[top](#)

time/plus

```
(time/plus date unit n)
```

Adds the n units to the date. Units: { :years :months :weeks :days :hours :minutes :seconds :milliseconds }

```
(time/plus (time/local-date) :days 2)
=> 2019-07-16
```

```
(time/plus (time/local-date-time) :days 2)
=> 2019-07-16T16:08:58.093
```

```
(time/plus (time/zoned-date-time) :days 2)
=> 2019-07-16T16:08:58.097+02:00[Europe/Zurich]
```

[top](#)

time/second

```
(time/second date)
```

Returns the second of the date 0..59

```
(time/second (time/local-date))
=> 0
```

```
(time/second (time/local-date-time))
=> 57
```

```
(time/second (time/zoned-date-time))
=> 57
```

[top](#)

time/to-millis

```
(time/to-millis date)
```

Converts the passed date to milliseconds since epoch

```
(time/to-millis (time/local-date))
=> 1563055200000
```

time/with-time

```
(time/with-time date hour minute second)
(time/with-time date hour minute second millis)
```

Sets the time of a date. Returns a new date

```
(time/with-time (time/local-date) 22 00 15 333)
=> 2019-07-14T22:00:15.333
```

```
(time/with-time (time/local-date-time) 22 00 15 333)
=> 2019-07-14T22:00:15.333
```

```
(time/with-time (time/zoned-date-time) 22 00 15 333)
=> 2019-07-14T22:00:15.333+02:00[Europe/Zurich]
```

time/within?

```
(time/within? date start end)
```

Returns true if the date is after or equal to the start and is before or equal to the end. All three dates must be of the same type. The start and end date may each be nil meaning start is -infinity and end is +infinity.

```
(time/within? (time/local-date 2018 8 4) (time/local-date 2018 8 1) (time/local-date 2018 8 31))
=> true
```

```
(time/within? (time/local-date 2018 7 4) (time/local-date 2018 8 1) (time/local-date 2018 8 31))
=> false
```

time/year

```
(time/year date)
```

Returns the year of the date

```
(time/year (time/local-date))
=> 2019
```

```
(time/year (time/local-date-time))
=> 2019
```

```
(time/year (time/zoned-date-time))
=> 2019
```

time/zone

```
(time/zone date)
```

Returns the zone of the date

```
(time/zone (time/zoned-date-time))  
=> :Europe/Zurich
```

[top](#)

time/zone-ids

```
(time/zone-ids)
```

Returns all available zone ids with time offset

```
(nfirst (seq (time/zone-ids)) 10)  
=> ([:Africa/Abidjan "+00:00"] [:Africa/Accra "+00:00"] [:Africa/Addis_Ababa "+03:00"] [:Africa/Algiers "+01:  
00"] [:Africa/Asmara "+03:00"] [:Africa/Asmera "+03:00"] [:Africa/Bamako "+00:00"] [:Africa/Bangui "+01:00"] [:  
Africa/Banjul "+00:00"] [:Africa/Bissau "+00:00"])
```

[top](#)

time/zone-offset

```
(time/zone-offset date)
```

Returns the zone-offset of the date in minutes

```
(time/zone-offset (time/zoned-date-time))  
=> 120
```

[top](#)

time/zoned-date-time

```
(time/zoned-date-time )  
(time/zoned-date-time year month day)  
(time/zoned-date-time year month day hour minute second)  
(time/zoned-date-time year month day hour minute second millis)  
(time/zoned-date-time date)  
(time/zoned-date-time zone-id)  
(time/zoned-date-time zone-id year month day)  
(time/zoned-date-time zone-id year month day hour minute second)  
(time/zoned-date-time zone-id year month day hour minute second millis)  
(time/zoned-date-time zone-id date)
```

Creates a new zoned-date-time. A zoned-date-time is represented by 'java.time.ZonedDateTime'

```
(time/zoned-date-time)  
=> 2019-07-14T16:08:57.774+02:00[Europe/Zurich]
```

```
(time/zoned-date-time 2018 8 1)  
=> 2018-08-01T00:00+02:00[Europe/Zurich]
```

```
(time/zoned-date-time 2018 8 1 14 20 10)  
=> 2018-08-01T14:20:10+02:00[Europe/Zurich]
```

```
(time/zoned-date-time 2018 8 1 14 20 10 200)
=> 2018-08-01T14:20:10.200+02:00[Europe/Zurich]

(time/zoned-date-time "2018-08-01T14:20:10.200+01:00")
=> 2018-08-01T14:20:10.200+01:00

(time/zoned-date-time 1375315200000)
=> 2013-08-01T02:00+02:00[Europe/Zurich]

(time/zoned-date-time (. :java.util.Date :new))
=> 2019-07-14T16:08:57.793+02:00[Europe/Zurich]

(time/zoned-date-time :UTC)
=> 2019-07-14T14:08:57.796Z[UTC]

(time/zoned-date-time :UTC 2018 8 1)
=> 2018-08-01T00:00Z[UTC]

(time/zoned-date-time :UTC 2018 8 1 14 20 10)
=> 2018-08-01T14:20:10Z[UTC]

(time/zoned-date-time :UTC 2018 8 1 14 20 10 200)
=> 2018-08-01T14:20:10.200Z[UTC]

(time/zoned-date-time :UTC "2018-08-01T14:20:10.200+01:00")
=> 2018-08-01T14:20:10.200Z[UTC]

(time/zoned-date-time :UTC 1375315200000)
=> 2013-08-01T00:00Z[UTC]

(time/zoned-date-time :UTC (. :java.util.Date :new))
=> 2019-07-14T14:08:57.818Z[UTC]
```

[top](#)

time/zoned-date-time-parse

```
(time/zoned-date-time-parse str format locale?)
```

Parses a zoned-date-time.

```
(time/zoned-date-time-parse "2018-08-01T14:20:01+01:00" "yyyy-MM-dd'T'HH:mm:ssz")
=> 2018-08-01T14:20:01+01:00

(time/zoned-date-time-parse "2018-08-01T14:20:01.000+01:00" "yyyy-MM-dd'T'HH:mm:ss.SSSz")
=> 2018-08-01T14:20:01+01:00

(time/zoned-date-time-parse "2018-08-01T14:20:01.000+01:00" :ISO_OFFSET_DATE_TIME)
=> 2018-08-01T14:20:01+01:00

(time/zoned-date-time-parse "2018-08-01 14:20:01.000 +01:00" "yyyy-MM-dd' 'HH:mm:ss.SSS' 'z")
=> 2018-08-01T14:20:01+01:00
```

[top](#)

time/zoned-date-time?

```
(time/zoned-date-time? date)
```

Returns true if date is a zoned-date-time else false

```
(time/zoned-date-time? (time/zoned-date-time))  
=> true
```

[top](#)

transduce

```
(transduce xform f coll)  
(transduce xform f init coll)
```

Reduce with a transformation of a reduction function `f` (`xf`). If `init` is not supplied, (`f`) will be called to produce it. `f` should be a reducing step function that accepts both 1 and 2 arguments. Returns the result of applying (the transformed) `xf` to `init` and the first item in `coll`, then applying `xf` to that result and the 2nd item, etc. If `coll` contains no items, returns `init` and `f` is not called.

```
(do  
  (def xf (map #(+ % 1)))  
  (transduce xf + [1 2 3 4]))  
=> 14  
  
(do  
  (def xf (map #(+ % 1)))  
  (transduce xf conj [1 2 3 4]))  
=> [2 3 4 5]  
  
(do  
  (def xf (comp (drop 2) (take 3)))  
  (transduce xf conj [1 2 3 4 5 6]))  
=> [3 4 5]
```

[top](#)

true?

```
(true? x)
```

Returns true if `x` is true, false otherwise

```
(true? true)  
=> true  
  
(true? false)  
=> false  
  
(true? nil)  
=> false  
  
(true? 0)  
=> false  
  
(true? (== 1 1))  
=> true
```

[top](#)

try

```
(try expr)
(try expr (catch exClass exSym expr))
(try expr (catch exClass exSym expr) (finally expr))
```

Exception handling: try - catch -finally

```
(try (throw))
=> JavaValueException: Venice value exception
```

```
(try
  (throw "test message"))
=> JavaValueException: Venice value exception
```

```
(try
  (throw 100)
  (catch :java.lang.Exception ex -100))
=> -100
```

```
(try
  (throw 100)
  (finally (println "...finally")))
...finally
=> JavaValueException: Venice value exception
```

```
(try
  (throw 100)
  (catch :java.lang.Exception ex -100)
  (finally (println "...finally")))
...finally
=> -100
```

```
(do
  (import :java.lang.RuntimeException)
  (try
    (throw (. :RuntimeException :new "message"))
    (catch :RuntimeException ex (:message ex))))

=> "message"
```

```
(do
  (try
    (throw [1 2 3])
    (catch :ValueException ex (str (:value ex)))
    (catch :RuntimeException ex "runtime ex")
    (finally (println "...finally"))))
...finally
=> "[1 2 3]"
```

[top](#)

try-with

```
(try-with [bindings*] expr)
(try-with [bindings*] expr (catch :java.lang.Exception ex expr))
(try-with [bindings*] expr (catch :java.lang.Exception ex expr) (finally expr))
```

try-with resources allows the declaration of resources to be used in a try block with the assurance that the resources will be closed after execution of that block. The resources declared must implement the Closeable or

```
(do
  (import :java.io.FileInputStream)
  (let [file (io/temp-file "test-", ".txt")]
    (io/spit file "123456789" :append true)
    (try-with [is (. :FileInputStream :new file)]
      (io/slurp-stream is :binary false))))
=> "123456789"
```

[top](#)

type

```
(type x)
```

Returns the type of x.

```
(type 5)
=> :venice.Long
```

```
(type [1 2])
=> :venice.Vector
```

```
(type (. :java.math.BigInteger :valueOf 100))
=> :java.math.BigInteger
```

[top](#)

union

```
(union s1)
(union s1 s2)
(union s1 s2 & sets)
```

Return a set that is the union of the input sets

```
(union (set 1 2 3))
=> #{1 2 3}
```

```
(union (set 1 2) (set 2 3))
=> #{1 2 3}
```

```
(union (set 1 2 3) (set 1 2) (set 1 4) (set 3))
=> #{1 2 3 4}
```

[top](#)

update

```
(update m k f)
```

Updates a value in an associative structure, where k is a key and f is a function that will take the old value return the new value. Returns a new structure.

```
(update [] 0 (fn [x] 5))
=> [5]

(update [0 1 2] 0 (fn [x] 5))
=> [5 1 2]

(update [0 1 2] 0 (fn [x] (+ x 1)))
=> [1 1 2]

(update {} :a (fn [x] 5))
=> {:a 5}

(update {:a 0} :b (fn [x] 5))
=> {:a 0 :b 5}

(update {:a 0 :b 1} :a (fn [x] 5))
=> {:a 5 :b 1}
```

[top](#)

update!

```
(update! m k f)
```

Updates a value in a mutable map, where `k` is a key and `f` is a function that will take the old value return the new value.

```
(update! (mutable-map) :a (fn [x] 5))
=> {:a 5}

(update! (mutable-map :a 0) :b (fn [x] 5))
=> {:a 0 :b 5}

(update! (mutable-map :a 0 :b 1) :a (fn [x] 5))
=> {:a 5 :b 1}
```

[top](#)

uuid

```
(uuid)
```

Generates a UUID.

```
(uuid )
=> "ae01d08a-351f-43e2-834b-eeeeae53d8f91"
```

[top](#)

val

```
(val e)
```

Returns the `val` of the map entry.


```
(val (find {:a 1 :b 2} :b))  
=> 2
```

[top](#)

vals

```
(vals map)
```

Returns a collection of the map's values.

```
(vals {:a 1 :b 2 :c 3})  
=> (1 2 3)
```

[top](#)

vary-meta

```
(vary-meta obj f & args)
```

Returns a copy of the object obj, with (apply f (meta obj) args) as its metadata.

[top](#)

vector

```
(vector & items)
```

Creates a new vector containing the items.

```
(vector )  
=> []
```

```
(vector 1 2 3)  
=> [1 2 3]
```

```
(vector 1 2 3 [:a :b])  
=> [1 2 3 [:a :b]]
```

[top](#)

vector?

```
(vector? obj)
```

Returns true if obj is a vector

```
(vector? (vector 1 2))  
=> true
```

```
(vector? [1 2])  
=> true
```

version

```
(version)
```

Returns the version.

```
(version )  
=> "1.6.0"
```

when

```
(when test & body)
```

Evaluates test. If logical true, evaluates body in an implicit do.

```
(when (== 1 1) true)  
=> true
```

when-not

```
(when-not test & body)
```

Evaluates test. If logical false, evaluates body in an implicit do.

```
(when-not (== 1 2) true)  
=> true
```

while

```
(while test & body)
```

Repeatedly executes body while test expression is true. Presumes some side-effect will cause test to become false/nil. Returns nil

```
(do  
  (def a (atom 5))  
  (while (pos? (deref a))  
    (do (println (deref a)) (swap! a dec))))  
5  
4  
3  
2  
1  
=> nil
```

with-meta

```
(with-meta obj m)
```

Returns a copy of the object `obj`, with a map `m` as its metadata.

with-out-str

```
(with-out-str & forms)
```

Evaluates `exprs` in a context in which `*out*` is bound to a capturing output stream. Returns the string created by any nested printing calls.

```
(with-out-str (println "a string"))  
=> "a string\n"
```

with-sh-dir

```
(with-sh-dir dir & forms)
```

Sets the directory for use with `sh`, see `sh` for details.

```
(with-sh-dir "/tmp" (sh "ls" "-l"))
```

with-sh-env

```
(with-sh-env env & forms)
```

Sets the environment for use with `sh`, see `sh` for details.

```
(with-sh-env {"NAME" "foo"} (sh "ls" "-l"))
```

with-sh-throw

```
(with-sh-throw forms)
```

If `true` throws an exception if the spawned shell process returns an exit code other than 0. If `false` return the exit code. Defaults to `false`. For use with `sh`, see `sh` for details.

```
(with-sh-throw (sh "ls" "-l"))
```

xml/children

(xml/children nodes)

Returns the children of the XML nodes collection

```
(do
  (load-module :xml)
  (xml/children
    (list (xml/parse-str "<a><b>B</b></a>"))))
=> ({:content ["B"] :tag "b"})
```

xml/parse

(xml/parse s)
(xml/parse s handler)

Parses and loads the XML from the source `s` with the parser `XMLHandler` handler. The source may be an `InputSource`, an `InputStream`, a `File`, or a string describing an URI. Returns a tree of XML element maps with the keys `:tag`, `:attrs`, and `:content`.

xml/parse-str

(xml/parse-str s)
(xml/parse-str s handler)

Parses an XML from the string `s`. Returns a tree of XML element maps with the keys `:tag`, `:attrs`, and `:content`.

```
(do
  (load-module :xml)
  (xml/parse-str "<a><b>B</b></a>"))
=> {:content [{:content ["B"] :tag "b"}] :tag "a"}
```

xml/path->

(xml/path-> path nodes)

Applies the path to a node or a collection of nodes

```
(do
  (load-module :xml)
```

```
(let [nodes (xml/parse-str "<a><b><c>C</c></b></a>")
      path [(xml/tag= "b")
            (xml/tag= "c")
            xml/text
            first]]
      (xml/path-> path nodes)))
=> "C"
```

[top](#)

xml/text

```
(xml/text nodes)
```

Returns a list of text contents of the XML nodes collection

```
(do
  (load-module :xml)
  (let [nodes (xml/parse-str "<a><b>B</b></a>")
        path [(xml/tag= "b")
              xml/text]]
    (xml/path-> path nodes)))
=> ("B")
```

[top](#)

zero?

```
(zero? x)
```

Returns true if x zero else false

```
(zero? 0)
=> true
```

```
(zero? 2)
=> false
```

```
(zero? (int 0))
=> true
```

```
(zero? 0.0)
=> true
```

```
(zero? 0.0M)
=> true
```

[top](#)

zipmap

```
(zipmap keys vals)
```

Returns a map with the keys mapped to the corresponding vals.

```
(zipmap [:a :b :c :d :e] [1 2 3 4 5])  
=> {:a 1 :b 2 :c 3 :d 4 :e 5}
```

```
(zipmap [:a :b :c] [1 2 3 4 5])  
=> {:a 1 :b 2 :c 3}
```

[top](#)

Creates a hash map.

```
{:a 10 :b 20}  
=> {:a 10 :b 20}
```