

Collections

Generic	<u>count</u>	<u>empty-to-nil</u>	<u>empty</u>	<u>into</u>	<u>conj</u>	<u>remove</u>
	<u>repeat</u>	<u>repeatedly</u>	<u>range</u>	<u>group-by</u>	<u>get-in</u>	
	<u>seq</u>					
Tests	<u>empty?</u>	<u>not-empty?</u>	<u>coll?</u>	<u>list?</u>	<u>vector?</u>	<u>set?</u>
	<u>map?</u>	<u>sequential?</u>	<u>hash-map?</u>	<u>ordered-map?</u>		
	<u>sorted-map?</u>	<u>bytebuf?</u>				
Process	<u>map</u>	<u>filter</u>	<u>reduce</u>	<u>keep</u>	<u>docoll</u>	

Create	() list
Access	first second nth last peek rest butlast nfirst nlast
Modify	cons conj rest pop into concat interpose interleave mapcat flatten reverse sort sort- by take take-while drop drop-while split- with
Test	every? any?

Byte Buffer

Create	<u>bytebuf</u>	<u>bytebuf-from-string</u>	
Test	<u>empty?</u>	<u>not-empty?</u>	<u>bytebuf?</u>
Use	<u>count</u>	<u>bytebuf-to-string</u>	<u>bytebuf-sub</u>

Time

Date	time/date	time/date?
Local Date	time/local-date	time/local-date? time/local-date-parse
Local Date Time	time/local-date-time	time/local-date-time? time/local-date-time-parse
Zoned Date Time	time/zoned-date-time	time/zoned-date-time? time/zoned-date-time-parse
Fields	time/year time/month time/day-of-week time/day-of-month time/day-of-year time/hour time/minute time/second time/zone time/zone-offset	
Format	time/formatter	time/format
Test	time/after? time/not-after? time/before? time/not-before? time/within?	
Miscellaneous	time/with-time time/plus time/minus time/period time/first-day-of-month time/last-day-of-month time/earliest time/latest	
Util	time/zone-ids	time/to-millis

Functions

Create	identity			
Call	apply	comp	partial	memoize
Test	fn2			
Exception	throw			
Misc	class	type	eval	name
Meta	meta	with-meta	vary-meta	

Macros

Create	defn	defmacro			
Debug	macroexpand				
Branch	and	or	when	when-not	if-let
Loop	list-comp	dotimes	while		

Access	find	get	keys	vals	key	val								
Modify	cons	conj	assoc	assoc-in	get-in	update	update!	dissoc	into	concat	flatten	reduce-	kv	merge
Test	contains?													

Concurrency

Atoms	<u>atom</u>	<u>atom?</u>	<u>deref</u>	<u>reset!</u>	<u>swap!</u>	<u>compare-and-set!</u>
Futures	<u>future</u>	<u>future?</u>	<u>future-done?</u>	<u>future-cancel</u>	<u>future-cancelled?</u>	<u>deref</u>
Promises	<u>promise</u>	<u>promise?</u>	<u>deliver</u>			
ThreadLocal	<u>thread-local</u>	<u>thread-local?</u>	<u>thread-local-clear</u>	<u>assoc</u>	<u>dissoc</u>	<u>get</u>

System

Test	sandboxed?	os?								
Other	version	os	system-prop	uuid	sleep	current-time-millis	nano-time	coalesce		
Shell	sh									

Java Interoperability

General	.	proxify
	Invoke constructors	
	Invoke static or instance methods	
	Access static or instance fields	

IO

to	print	println	flush	newline									
to-str	pr-str												
from	readline	read-string											
file-io	io/file	io/file?	io/exists-file?	io/exists-dir?	io/list-files	io/delete-file	io/delete-file-on-exit	io/copy-file	io/move-file	io/slurp	io/spit	io/tmp-dir	io/user-dir
stream-io	io/slurp-stream	io/spit-stream											
file-io temp	io/temp-file	io/slurp-temp-file	io/spit-temp-file										
other	io/load-classpath-resource	io/mime-type											

Call	doto	->	->>	as->
Loading	load-string	load-file	load-module	load-classpath-file
Test	macro?	cond	case	
Assert	assert			
Util	comment	gensym	time	

Special Forms

Forms	def	if	do	let	fn	loop	recur	try	try-with
-------	---------------------	--------------------	--------------------	---------------------	--------------------	----------------------	-----------------------	---------------------	--------------------------

Miscellaneous

JSON [json/pretty-print](#) [json/to-json](#) [json/to-pretty-json](#)
[json/parse](#)
[json/avail?](#) [json/avail-jdk8-module?](#)
Available if Jackson libs are on runtime classpath

Embedding in Java

Eval

```
import com.github.jlangch.venice.Venice;

public class Example {
    public static void main(String[] args) {
        Venice venice = new Venice();

        Long val = (Long)venice.eval("(+ 1 2)");
    }
}
```

Passing parameters

```
import com.github.jlangch.venice.Venice;
import com.github.jlangch.venice.Parameters;

public class Example {
    public static void main(String[] args) {
        Venice venice = new Venice();

        Long val = (Long)venice.eval(
            "(+ x y 3)",
            Parameters.of("x", 6, "y", 3L));
    }
}
```

Precompiled

```
import com.github.jlangch.venice.Venice;
import com.github.jlangch.venice.PreCompiled;

public class Example {
    public static void main(String[] args) {
        Venice venice = new Venice();

        PreCompiled precompiled = venice.precompile("example", "(+ 1 x)");

        for(int ii=0; ii<100; ii++) {
            venice.eval(precompiled, Parameters.of("x", ii));
        }
    }
}
```

Java Interop

```
import java.time.ZonedDateTime;
import com.github.jlangch.venice.Venice;

public class Example {
    public static void main(String[] args) {
        Venice venice = new Venice();

        Long val = (Long)venice.eval("( . :java.lang.Math :min 20 30)");

        ZonedDateTime ts = (ZonedDateTime)venice.eval(
```

```

        "(. (. :java.time.ZonedDateTime :now) :plusDays 5)");
    }
}

```

Sandbox

```

import com.github.jlangch.venice.Venice;
import com.github.jlangch.venice.javainterop.*;

public class Example {
    public static void main(String[] args) {
        final IInterceptor interceptor =
            new SandboxInterceptor(
                new SandboxRules()
                    .rejectAllVeniceIoFunctions()
                    .allowAccessToStandardSystemProperties()
                    .withClasses(
                        "java.lang.Math:min",
                        "java.time.ZonedDateTime:*",
                        "java.util.ArrayList:new",
                        "java.util.ArrayList:add"));

        final Venice venice = new Venice(interceptor);

        // => OK (static method)
        venice.eval("(. :java.lang.Math :min 20 30)");

        // => OK (constructor & instance method)
        venice.eval("(. (. :java.time.ZonedDateTime :now) :plusDays 5)");

        // => OK (constructor & instance method)
        venice.eval(
            "(doto (. :java.util.ArrayList :new) " +
            "  (. :add 1)          " +
            "  (. :add 2))      ");

        // => FAIL (invoking non whitelisted static method)
        venice.eval("(. :java.lang.System :exit 0)");

        // => FAIL (invoking rejected Venice I/O function)
        venice.eval("(io/slurp \"tmp/file\")");

        // => FAIL (accessing non whitelisted system property)
        venice.eval("(system-prop \"db.password\")");
    }
}

```

Function details

<code>!=</code>
<code>(!= x y)</code>
Returns true if both operands do not have the equivalent type
<code>(!= 0 1)</code> <code>=> true</code>
<code>(!= 0 0)</code> <code>=> false</code>
<code>(!= 0 0.0)</code> <code>=> true</code>

<code>()</code>
Creates a list.
<code>'(10 20 30)</code> <code>=> (10 20 30)</code>

<code>*</code>
<code>(*)</code> <code>(* x)</code> <code>(* x y)</code> <code>(* x y & more)</code>
Returns the product of numbers. <code>(*)</code> returns 1
<code>(*)</code> <code>=> 1</code>
<code>(* 4)</code> <code>=> 4</code>
<code>(* 4 3)</code> <code>=> 12</code>
<code>(* 4 3 2)</code> <code>=> 24</code>
<code>(* 6.0 2)</code> <code>=> 12.0</code>

(* 6 1.5M)
=> 9.0M

+

(+)
(+ x)
(+ x y)
(+ x y & more)

Returns the sum of the numbers. (+) returns 0.

(+)
=> 0

(+ 1)
=> 1

(+ 1 2)
=> 3

(+ 1 2 3 4)
=> 10

-

(- x)
(- x y)
(- x y & more)

If one number is supplied, returns the negation, else subtracts the numbers from x and returns the result.

(- 4)
=> -4

(- 8 3 -2 -1)
=> 8

(- 8 2.5)
=> 5.5

(- 8 1.5M)
=> 6.5M

->

(-> x & forms)

Threads the expr through the forms. Inserts x as the second item in the first form, making a list of it if it is not a list already. If there are more forms, inserts the first form as the second item in second form, etc.

```
(-> 5 (+ 3) (/ 2) (- 1))  
=> 3
```

```
(do  
  (def person  
    {:name "Peter Meier"  
     :address {:street "Lindenstrasse 45"  
               :city "Bern"  
               :zip 3000}})  
  
  (-> person :address :street))  
=> "Lindenstrasse 45"
```

->>

(->> x & forms)

Threads the expr through the forms. Inserts x as the last item in the first form, making a list of it if it is not a list already. If there are more forms, inserts the first form as the last item in second form, etc.

```
(->> 5 (+ 3) (/ 32) (- 1))  
=> -3  
  
(->> [ {:a 1 :b 2} {:a 3 :b 4} {:a 5 :b 6} {:a 7 :b 8} ]  
  (map (fn [x] (get x :b)))  
  (filter (fn [x] (> x 4)))  
  (map inc))))  
=> (7 9)
```

•

```
(. classname :new args)  
(. classname method-name args)  
(. classname field-name)  
(. classname :class)  
(. object method-name args)  
(. object field-name)  
(. object :class)
```

Java interop. Calls a constructor or an class/object method or accesses a class/instance field. The function is sandboxed.

```
:: invoke constructor  
(. :java.lang.Long :new 10)  
=> 10  
  
:: invoke static method  
(. :java.time.ZonedDateTime :now)  
=> 2018-10-18T10:10:07.409+02:00[Europe/Zurich]  
  
:: invoke static method  
(. :java.lang.Math :min 10 20)  
=> 10  
  
:: access static field  
(. :java.lang.Math :PI)  
=> 3.141592653589793
```



```
:: invoke method
(. (. :java.lang.Long :new 10) :toString)
=> "10"
```

```
:: get class name
(. :java.lang.Math :class)
=> class java.lang.Math
```

```
:: get class name
(. (. :java.io.File :new "/temp") :class)
=> class java.io.File
```

/

```
(/ x)
(/ x y)
(/ x y & more)
```

If no denominators are supplied, returns 1/numerator, else returns numerator divided by all of the denominators.

```
(/ 2.0)
=> 0.5
```

```
(/ 12 2 3)
=> 2
```

```
(/ 12 3)
=> 4
```

```
(/ 6.0 2)
=> 3.0
```

```
(/ 6 1.5M)
=> 4.0000000000000000M
```

<

```
(< x y)
```

Returns true if x is smaller than y

```
(< 2 3)
=> true
```

```
(< 2 3.0)
=> true
```

```
(< 2 3.0M)
=> true
```

<=

`(<= x y)`

Returns true if x is smaller or equal to y

`(<= 2 3)`

`=> true`

`(<= 3 3)`

`=> true`

`(<= 2 3.0)`

`=> true`

`(<= 2 3.0M)`

`=> true`

`==`

`(== x y)`

Returns true if both operands have the equivalent type

`(== 0 0)`

`=> true`

`(== 0 1)`

`=> false`

`(== 0 0.0)`

`=> false`

`>`

`(> x y)`

Returns true if x is greater than y

`(> 3 2)`

`=> true`

`(> 3 3)`

`=> false`

`(> 3.0 2)`

`=> true`

`(> 3.0M 2)`

`=> true`

`>=`

`(>= x y)`

Returns true if x is greater or equal to y

```
(>= 3 2)  
=> true
```

```
(>= 3 3)  
=> true
```

```
(>= 3.0 2)  
=> true
```

```
(>= 3.0M 2)  
=> true
```

[]

Creates a vector

```
[10 20]  
=> [10 20]
```

abs

```
(abs x)
```

Returns the absolute value of the number

```
(abs 10)  
=> 10
```

```
(abs -10)  
=> 10
```

```
(abs -10.1)  
=> 10.1
```

```
(abs -10.12M)  
=> 10.12M
```

and

```
(and x)  
(and x & next)
```

Ands the predicate forms

```
(and true true)  
=> true
```

```
(and true false)
=> false
```

any?

```
(any? pred coll)
```

Returns true if the predicate is true for at least one collection item, false otherwise

```
(any? (fn [x] (number? x)) nil)
=> false
```

```
(any? (fn [x] (number? x)) [])
=> false
```

```
(any? (fn [x] (number? x)) [1 :a :b])
=> true
```

```
(any? (fn [x] (number? x)) [1 2 3])
=> true
```

```
(any? (fn [x] (>= x 10)) [1 5 10])
=> true
```

apply

```
(apply f args* coll)
```

Applies f to all arguments composed of args and coll

```
(apply str [1 2 3 4 5])
=> "12345"
```

as->

```
(as-> expr name & forms)
```

Binds name to expr, evaluates the first form in the lexical context of that binding, then binds name to that result, repeating for each successive form, returning the result of the last form. This allows a value to thread into any argument position.

```
(as-> [:foo :bar] v
  (map name v)
  (first v)
  (str/subs v 1))
=> "oo"
```

assert

```
(assert expr)
(assert expr message)
```

Evaluates `expr` and throws an exception if it does not evaluate to logical true.

assoc

```
(assoc coll key val)
(assoc coll key val & kvs)
```

When applied to a map, returns a new map of the same type, that contains the mapping of key(s) to val(s). When applied to a vector, returns a new vector that contains val at index. Note - index must be <= (count vector).

```
(assoc {} :a 1 :b 2)
=> {:a 1 :b 2}
```

```
(assoc nil :a 1 :b 2)
=> {:a 1 :b 2}
```

```
(assoc [1 2 3] 0 10)
=> [10 2 3]
```

```
(assoc [1 2 3] 3 10)
=> [1 2 3 10]
```

assoc-in

```
(assoc-in m ks v)
```

Associates a value in a nested associative structure, where `ks` is a sequence of keys and `v` is the new value and returns a new nested structure. If any levels do not exist, hash-maps or vectors will be created.

```
(do
  (def users [{:name "James" :age 26} {:name "John" :age 43}])
  (assoc-in users [1 :age] 44))
=> [{:age 26 :name "James"} {:age 44 :name "John"}]
```

```
(do
  (def users [{:name "James" :age 26} {:name "John" :age 43}])
  (assoc-in users [2] {:name "Jack" :age 19}))
=> [{:age 26 :name "James"} {:age 43 :name "John"} {:age 19 :name "Jack"}]
```

atom

```
(atom x)
```

Creates an atom with the initial value `x`

```
(do
  (def counter (atom 0)))
```

```
(deref counter))  
=> 0
```

atom?

```
(atom? x)
```

Returns true if x is an atom, otherwise false

```
(do  
  (def counter (atom 0))  
  (atom? counter))  
=> true
```

boolean

```
(boolean x)
```

Converts to boolean. Everything except 'false' and 'nil' is true in boolean context.

```
(boolean false)  
=> false
```

```
(boolean true)  
=> true
```

```
(boolean nil)  
=> false
```

boolean?

```
(boolean? n)
```

Returns true if n is a boolean

```
(boolean? true)  
=> true
```

```
(boolean? false)  
=> true
```

```
(boolean? nil)  
=> false
```

```
(boolean? 0)  
=> false
```

butlast

```
(butlast coll)
```

Returns a collection with all but the last list element

```
(butlast nil)
```

```
=> nil
```

```
(butlast [])
```

```
=> []
```

```
(butlast [1])
```

```
=> []
```

```
(butlast [1 2 3])
```

```
=> [1 2]
```

```
(butlast '())
```

```
=> ()
```

```
(butlast '(1))
```

```
=> ()
```

```
(butlast '(1 2 3))
```

```
=> (1 2)
```

bytebuf

```
(bytebuf x)
```

Converts to bytebuf. x can be a bytebuf, a list/vector of longs, or a string

```
(bytebuf [0 1 2])
```

```
=> [0 1 2]
```

```
(bytebuf '(0 1 2))
```

```
=> [0 1 2]
```

```
(bytebuf "abc")
```

```
=> [97 98 99]
```

bytebuf-from-string

```
(bytebuf-from-string s encoding)
```

Converts a string to a bytebuf using an optional encoding. The encoding defaults to UTF-8

```
(bytebuf-from-string "abcdef" :UTF-8)
```

```
=> [97 98 99 100 101 102]
```

bytebuf-sub

(bytebuf-sub x start) (bytebuf-sub x start end)

Returns a byte buffer of the items in buffer from start (inclusive) to end (exclusive). If end is not supplied, defaults to (count bytebuffer)

```
(bytebuf-sub (bytebuf [1 2 3 4 5 6]) 2)
=> [3 4 5 6]
```

```
(bytebuf-sub (bytebuf [1 2 3 4 5 6]) 4)
=> [5 6]
```

bytebuf-to-string

(bytebuf-to-string buf encoding)

Converts a bytebuf to a string using an optional encoding. The encoding defaults to UTF-8

```
(bytebuf-to-string (bytebuf [97 98 99]) :UTF-8)
=> "abc"
```

bytebuf?

(bytebuf? x)

Returns true if x is a bytebuf

```
(bytebuf? (bytebuf [1 2]))
=> true
```

```
(bytebuf? [1 2])
=> false
```

```
(bytebuf? nil)
=> false
```

case

(case expr & clauses)

Takes an expression and a set of clauses. Each clause takes the form of test-constant result-expr

```
(case (+ 1 9)
  10 :ten
  20 :twenty
  30 :thirty
  :dont-know)
=> :ten
```

class


```
(class x)
```

Returns the class of x

```
(class 5)
=> "venice.Long"
```

```
(class [1 2])
=> "venice.Vector"
```

```
(class (. :java.time.ZonedDateTime :now))
=> "venice.JavaObject(java.time.ZonedDateTime)"
```

coalesce

```
(coalesce args*)
```

Returns the first non nil arg

```
(coalesce )
=> nil
```

```
(coalesce 1 2)
=> 1
```

```
(coalesce nil)
=> nil
```

```
(coalesce nil 1 2)
=> 1
```

coll?

```
(coll? obj)
```

Returns true if obj is a collection

```
(coll? {:a 1})
=> true
```

```
(coll? [1 2])
=> true
```

comment

```
(comment & body)
```

Ignores body, yields nil

```
(comment
  (println 1))
```

```
(println 5))  
=> nil
```

comp

```
(comp f*)
```

Takes a set of functions and returns a fn that is the composition of those fns. The returned fn takes a variable number of args, applies the rightmost of fns to the args, the next fn (right-to-left) to the result, etc.

```
((comp str +) 8 8 8)  
=> "24"
```

```
(map (comp - (partial + 3) (partial * 2)) [1 2 3 4])  
=> (-5 -7 -9 -11)
```

```
((reduce comp [(partial + 1) (partial * 2) (partial + 3)]) 100)  
=> 207
```

```
(filter (comp not zero?) [0 1 0 2 0 3 0 4])  
=> [1 2 3 4]
```

```
(do  
  (def fifth (comp first rest rest rest rest))  
  (fifth [1 2 3 4 5]))  
=> 5
```

compare

```
(compare x y)
```

Comparator. Returns -1, 0, or 1 when x is logically 'less than', 'equal to', or 'greater than' y.

```
(compare nil 0)  
=> -1
```

```
(compare 0 nil)  
=> 1
```

```
(compare 1 0)  
=> 1
```

```
(compare 1 1)  
=> 0
```

```
(compare 1 2)  
=> -1
```

compare-and-set!

```
(compare-and-set! atom oldval newval)
```

Atomically sets the value of atom to newval if and only if the current value of the atom is identical to oldval. Returns true if set happened, else false

```
(do
  (def counter (atom 2))
  (compare-and-set! counter 2 4)
  (deref counter))
=> 4
```

concat

```
(concat coll)
(concat coll & colls)
```

Returns a collection of the concatenation of the elements in the supplied colls.

```
(concat [1 2])
=> (1 2)

(concat [1 2] [4 5 6])
=> (1 2 4 5 6)

(concat '(1 2))
=> (1 2)

(concat '(1 2) [4 5 6])
=> (1 2 4 5 6)

(concat {:a 1})
=> ([:a 1])

(concat {:a 1} {:b 2 c: 3})
=> ([:a 1] [:b 2] [c: 3])

(concat "abc")
=> ("a" "b" "c")

(concat "abc" "def")
=> ("a" "b" "c" "d" "e" "f")
```

cond

```
(cond & clauses)
```

Takes a set of test/expr pairs. It evaluates each test one at a time. If a test returns logical true, cond evaluates and returns the value of the corresponding expr and doesn't evaluate any of the other tests or exprs. (cond) returns nil.

```
(let [n 5]
  (cond
    (< n 0) "negative"
    (> n 0) "positive"
    :else "zero"))
=> "positive"
```

conj

```
(conj coll x)
(conj coll x & xs)
```

Returns a new collection with the x, xs 'added'. (conj nil item) returns (item). The 'addition' may happen at different 'places' depending on the concrete type.

```
(conj [1 2 3] 4)
=> [1 2 3 4]
```

```
(conj '(1 2 3) 4)
=> (4 1 2 3)
```

cons

```
(cons x coll)
```

Returns a new collection where x is the first element and coll is the rest

```
(cons 1 '(2 3 4 5 6))
=> (1 2 3 4 5 6)
```

```
(cons [1 2] [4 5 6])
=> ([1 2] 4 5 6)
```

contains?

```
(contains? coll key)
```

Returns true if key is present in the given collection, otherwise returns false.

```
(contains? {:a 1 :b 2} :a)
=> true
```

```
(contains? [10 11 12] 1)
=> true
```

```
(contains? [10 11 12] 5)
=> false
```

```
(contains? "abc" 1)
=> true
```

```
(contains? "abc" 5)
=> false
```

count

```
(count coll)
```

Returns the number of items in the collection. (count nil) returns 0. Also works on strings, and Java Collections

```
(count {:a 1 :b 2})
```

```
=> 2
```

```
(count [1 2])
```

```
=> 2
```

```
(count "abc")
```

```
=> 3
```

current-time-millis

```
(current-time-millis)
```

Returns the current time in milliseconds.

```
(current-time-millis)
```

```
=> 1539850207398
```

dec

```
(dec x)
```

Decrements the number x

```
(dec 10)
```

```
=> 9
```

```
(dec 10.1)
```

```
=> 9.1
```

```
(dec 10.12M)
```

```
=> 9.12M
```

dec/add

```
(dec/add x y scale rounding-mode)
```

Adds two decimals and scales the result. rounding-mode is one of (:CEILING, :DOWN, :FLOOR, :HALF_DOWN, :HALF_EVEN, :HALF_UP, :UNNECESSARY, :UP)

```
(dec/add 2.44697M 1.79882M 3 :HALF_UP)
```

```
=> 4.246M
```

dec/div

(dec/div x y scale rounding-mode)

Divides x by y and scales the result. rounding-mode is one of (:CEILING, :DOWN, :FLOOR, :HALF_DOWN, :HALF_EVEN, :HALF_UP, :UNNECESSARY, :UP)

(dec/div 2.44697M 1.79882M 5 :HALF_UP)
=> 1.36032M

dec/mul

(dec/mul x y scale rounding-mode)

Multiplies two decimals and scales the result. rounding-mode is one of (:CEILING, :DOWN, :FLOOR, :HALF_DOWN, :HALF_EVEN, :HALF_UP, :UNNECESSARY, :UP)

(dec/mul 2.44697M 1.79882M 5 :HALF_UP)
=> 4.40166M

dec/scale

(dec/scale x scale rounding-mode)

Scales a decimal. rounding-mode is one of (:CEILING, :DOWN, :FLOOR, :HALF_DOWN, :HALF_EVEN, :HALF_UP, :UNNECESSARY, :UP)

(dec/scale 2.44697M 0 :HALF_UP)
=> 2M

(dec/scale 2.44697M 1 :HALF_UP)
=> 2.4M

(dec/scale 2.44697M 2 :HALF_UP)
=> 2.45M

(dec/scale 2.44697M 3 :HALF_UP)
=> 2.447M

(dec/scale 2.44697M 10 :HALF_UP)
=> 2.4469700000M

dec/sub

(dec/sub x y scale rounding-mode)

Subtract y from x and scales the result. rounding-mode is one of (:CEILING, :DOWN, :FLOOR, :HALF_DOWN, :HALF_EVEN, :HALF_UP, :UNNECESSARY, :UP)

(dec/sub 2.44697M 1.79882M 3 :HALF_UP)
=> 0.648M

decimal?

```
(decimal? n)
```

Returns true if n is a decimal

```
(decimal? 4.0M)
```

```
=> true
```

```
(decimal? 4.0)
```

```
=> false
```

```
(decimal? 3)
```

```
=> false
```

dedupe

```
(dedupe coll)
```

Returns a collection with all consecutive duplicates removed

```
(dedupe [1 2 2 2 3 4 4 2 3])
```

```
=> [1 2 3 4 2 3]
```

```
(dedupe '(1 2 2 2 3 4 4 2 3))
```

```
=> (1 2 3 4 2 3)
```

def

```
(def name expr)
```

Creates a global variable.

```
(def val 5)
```

```
=> 5
```

defmacro

```
(defmacro name [params*] body)
```

Macro definition

```
(defmacro unless [pred a b]
```

```
  `(if (not ~pred) ~a ~b))
```

```
=> unless
```

defn

```
(defn name args body)
```

Same as (def name (fn [args*] body))

```
(defn sum [x y] (+ x y))
```

deliver

```
(deliver ref value)
```

Delivers the supplied value to the promise, releasing any pending derefs. A subsequent call to deliver on a promise will have no effect.

```
(do
  (def p (promise))
  (deliver p 123))
=> nil
```

deref

```
(deref ref)
(deref ref timeout-ms timeout-val)
```

Dereferences an atom or a Future object. When applied to an atom, returns its current state. When applied to a future, will block if computation not complete. The variant taking a timeout can be used for futures and will return timeout-val if the timeout (in milliseconds) is reached before a value is available.

```
(do
  (def counter (atom 0))
  (deref counter))
=> 0

(do
  (def task (fn [] 100))
  (let [f (future task)] (deref f)))
=> 100

(do
  (def task (fn [] 100))
  (let [f (future task)] (deref f 300 :timeout)))
=> 100
```

difference

```
(difference s1)
(difference s1 s2)
(difference s1 s2 & sets)
```


Return a set that is the first set without elements of the remaining sets

```
(difference (set 1 2 3))  
=> #{1 2 3}
```

```
(difference (set 1 2) (set 2 3))  
=> #{1}
```

```
(difference (set 1 2) (set 1) (set 1 4) (set 3))  
=> #{2}
```

dissoc

```
(dissoc coll key)  
(dissoc coll key & ks)
```

Returns a new coll of the same type, that does not contain a mapping for key(s)

```
(dissoc {:a 1 :b 2 :c 3} :b)  
=> {:a 1 :c 3}
```

```
(dissoc {:a 1 :b 2 :c 3} :c :b)  
=> {:a 1}
```

distinct

```
(distinct coll)
```

Returns a collection with all duplicates removed

```
(distinct [1 2 3 4 2 3 4])  
=> [1 2 3 4]
```

```
(distinct '(1 2 3 4 2 3 4))  
=> (1 2 3 4)
```

do

```
(do exprs)
```

Evaluates the expressions in order and returns the value of the last.

```
(do (println "Test...") (+ 1 1))  
Test...  
=> 2
```

docoll

```
(docoll f coll)
```

Applies f to the items of the collection presumably for side effects. Returns nil.

```
(docoll
  (fn [x] (println x))
  [1 2 3 4])
1
2
3
4
=> nil

(docoll
  (fn [[k v]] (println (pr-str k v)))
  {:a 1 :b 2 :c 3 :d 4})
:a 1
:b 2
:c 3
:d 4
=> nil
```

dotimes

```
(dotimes bindings & body)
```

Repeatedly executes body with name bound to integers from 0 through n-1.

```
(dotimes [n 3] (println (str "n is " n)))
n is 0
n is 1
n is 2
=> nil
```

doto

```
(doto x & forms)
```

Evaluates x then calls all of the methods and functions with the value of x supplied at the front of the given arguments. The forms are evaluated in order. Returns x.

```
(doto (. :java.util.HashMap :new)
  (. :put :a 1)
  (. :put :b 2))
=> {"a" 1 "b" 2}
```

double?

```
(double? n)
```

Returns true if n is a double

```
(double? 4.0)
=> true
```

```
(double? 3)
=> false
```

```
(double? true)
=> false
```

```
(double? nil)
=> false
```

```
(double? {})
=> false
```

drop

```
(drop n coll)
```

Returns a collection of all but the first n items in coll

```
(drop 3 [1 2 3 4 5])
=> [5]
```

```
(drop 10 [1 2 3 4 5])
=> []
```

drop-while

```
(drop-while predicate coll)
```

Returns a list of the items in coll starting from the first item for which (predicate item) returns logical false.

```
(drop-while neg? [-2 -1 0 1 2 3])
=> [0 1 2 3]
```

empty

```
(empty coll)
```

Returns an empty collection of the same category as coll, or nil

```
(empty {:a 1})
=> {}
```

```
(empty [1 2])
=> []
```

```
(empty '(1 2))
=> ()
```

empty-to-nil

(empty-to-nil x)

Returns nil if x is empty

(empty-to-nil "")
=> nil

(empty-to-nil [])
=> nil

(empty-to-nil '())
=> nil

(empty-to-nil {})
=> nil

empty?

(empty? x)

Returns true if x is empty

(empty? {})
=> true

(empty? [])
=> true

(empty? '())
=> true

eval

(eval form)

Evaluates the form data structure (not text!) and returns the result.

(eval '(let [a 10] (+ 3 4 a)))
=> 17

(eval (list + 1 2 3))
=> 6

even?

(even? n)

Returns true if n is even, throws an exception if n is not an integer

```
(even? 4)  
=> true
```

```
(even? 3)  
=> false
```

every?

```
(every? pred coll)
```

Returns true if the predicate is true for all collection items, false otherwise

```
(every? (fn [x] (number? x)) nil)  
=> false
```

```
(every? (fn [x] (number? x)) [])  
=> false
```

```
(every? (fn [x] (number? x)) [1 2 3 4])  
=> true
```

```
(every? (fn [x] (number? x)) [1 2 3 :a])  
=> false
```

```
(every? (fn [x] (>= x 10)) [10 11 12])  
=> true
```

false?

```
(false? x)
```

Returns true if x is false, false otherwise

```
(false? true)  
=> false
```

```
(false? false)  
=> true
```

```
(false? nil)  
=> false
```

```
(false? 0)  
=> false
```

```
(false? (== 1 2))  
=> true
```

filter

```
(filter predicate coll)
```

Returns a collection of the items in coll for which (predicate item) returns logical true.

```
(filter even? [1 2 3 4 5 6 7])  
=> [2 4 6]
```

find

```
(find map key)
```

Returns the map entry for key, or nil if key not present.

```
(find {:a 1 :b 2} :b)  
=> [:b 2]
```

```
(find {:a 1 :b 2} :z)  
=> nil
```

first

```
(first coll)
```

Returns the first element of coll.

```
(first nil)  
=> nil
```

```
(first [])  
=> nil
```

```
(first [1 2 3])  
=> 1
```

```
(first '())  
=> nil
```

```
(first '(1 2 3))  
=> 1
```

flatten

```
(flatten coll)
```

Takes any nested combination of collections (lists, vectors, etc.) and returns their contents as a single, flat sequence. (flatten nil) returns an empty list.

```
(flatten [])  
=> []
```

```
(flatten [[1 2 3] [4 5 6] [7 8 9]])  
=> [1 2 3 4 5 6 7 8 9]
```

flush

```
(flush)
(flush os)
```

Without arg flushes the output stream that is the current value of *out*. With arg flushes the passed output stream

```
(flush)
=> nil

(flush *out*)
=> nil
```

fn

```
(fn [params*] condition-map? exprs*)
```

Defines an anonymous function.

```
(do (def sum (fn [x y] (+ x y))) (sum 2 3))
=> 5
```

```
(map (fn [x] (* 2 x)) (range 1 5))
=> (2 4 6 8)
```

```
;; anonymous function with two params, the second is destructured
(reduce (fn [m [k v]] (assoc m v k)) {} {:b 2 :a 1 :c 3})
=> {3 :c 1 :a 2 :b}
```

```
;; defining a pre-condition
(do
  (def sqrt
    (fn [x]
      { :pre [(>= x 0)] }
      (. :java.lang.Math.sqrt x)))
  (sqrt -4))
=> AssertionError: pre-condition assert failed: (>= x 0). File <unknown> (5,21)
```

```
;; higher-order function
(do
  (def discount
    (fn [percentage]
      { :pre [(and (>= percentage 0) (<= percentage 100))] }
      (fn [price] (- price (* price percentage 0.01)))))
  ((discount 50) 300))
=> 150.0
```

fn?

```
(fn? x)
```



```
(future-done? (future (fn [] 100)))  
=> false
```

future?

```
(future? f)
```

Returns true if f is a Future otherwise false

```
(future? (future (fn [] 100)))  
=> true
```

gensym

```
(gensym)  
(gensym prefix)
```

Generates a symbol.

```
(gensym )  
=> G__3
```

```
(gensym "prefix_")  
=> prefix_4
```

get

```
(get map key)  
(get map key not-found)
```

Returns the value mapped to key, not-found or nil if key not present.

```
(get {:a 1 :b 2} :b)  
=> 2
```

```
;; keywords act like functions on maps  
(:b {:a 1 :b 2})  
=> 2
```

get-in

```
(get-in m ks)  
(get-in m ks not-found)
```

Returns the value in a nested associative structure, where ks is a sequence of keys. Returns nil if the key is not present, or the not-found value if supplied.

```
(get-in {:a 1 :b {:c 2 :d 3}} [:b :c])  
=> 2  
  
(get-in [:a :b :c] [0])  
=> :a  
  
(get-in [:a :b [:c :d :e]] [2 1])  
=> :d  
  
(get-in {:a 1 :b {:c [4 5 6]}} [:b :c 1])  
=> 5
```

group-by

```
(group-by f coll)
```

Returns a map of the elements of coll keyed by the result of f on each element. The value at each key will be a vector of the corresponding elements, in the order they appeared in coll.

```
(group-by count ["a" "as" "asd" "aa" "asdf" "qwer"])  
=> {1 ["a"] 2 ["as" "aa"] 3 ["asd"] 4 ["asdf" "qwer"]}  
  
(group-by odd? (range 10))  
=> {false [0 2 4 6 8] true [1 3 5 7 9]}
```

hash-map

```
(hash-map & keyvals)  
(hash-map map)
```

Creates a new hash map containing the items.

```
(hash-map :a 1 :b 2)  
=> {:a 1 :b 2}  
  
(hash-map (sorted-map :a 1 :b 2))  
=> {:a 1 :b 2}
```

hash-map?

```
(hash-map? obj)
```

Returns true if obj is a hash map

```
(hash-map? (hash-map :a 1 :b 2))  
=> true
```

identity

```
(identity x)
```

Returns its argument.

```
(identity 4)
```

```
=> 4
```

```
(filter identity [1 2 3 nil 4 false true 1234])
```

```
=> [1 2 3 4 true 1234]
```

if

```
(if test true-expr false-expr)
```

Evaluates test.

```
(if (< 10 20) "yes" "no")
```

```
=> "yes"
```

if-let

```
(if-let bindings then)
```

bindings is a vector with 2 elements: binding-form test.

If test is true, evaluates then with binding-form bound to the value of test, if not, yields else

```
(if-let [value (* 100 2)]
```

```
  (str "The expression is true. value=" value)
```

```
  (str "The expression is false value=" value))
```

```
=> "The expression is true. value=200"
```

inc

```
(inc x)
```

Increments the number x

```
(inc 10)
```

```
=> 11
```

```
(inc 10.1)
```

```
=> 11.1
```

```
(inc 10.12M)
```

```
=> 11.12M
```

interleave

```
(interleave c1 c2)
(interleave c1 c2 & colls)
```

Returns a collection of the first item in each coll, then the second etc.

```
(interleave [:a :b :c] [1 2])
=> (:a 1 :b 2)
```

interpose

```
(interpose sep coll)
```

Returns a collection of the elements of coll separated by sep.

```
(interpose " " [1 2 3])
=> (1 " " 2 " " 3)

(apply str (interpose " " [1 2 3]))
=> "1, 2, 3"
```

intersection

```
(intersection s1)
(intersection s1 s2)
(intersection s1 s2 & sets)
```

Return a set that is the intersection of the input sets

```
(intersection (set 1))
=> #{1}

(intersection (set 1 2) (set 2 3))
=> #{2}

(intersection (set 1 2) (set 3 4))
=> #{} 
```

into

```
(into to-coll from-coll)
```

Returns a new coll consisting of to-coll with all of the items of from-coll conjoined.

```
(into (sorted-map) [[:a 1] [:c 3] [:b 2]] )
=> {:a 1 :b 2 :c 3}

(into (sorted-map) [ {:a 1} {:c 3} {:b 2} ] )
=> {:a 1 :b 2 :c 3}

(into [] {1 2, 3 4})
=> [[1 2] [3 4]]
```

```
(into '() '(1 2 3))  
=> (3 2 1)  
  
(into [1 2 3] '(4 5 6))  
=> [1 2 3 4 5 6]  
  
(into '() (bytebuf [0 1 2]))  
=> (0 1 2)  
  
(into [] (bytebuf [0 1 2]))  
=> [0 1 2]  
  
(into '() "abc")  
=> ("a" "b" "c")  
  
(into [] "abc")  
=> ["a" "b" "c"]  
  
(into (sorted-map) {:b 2 :c 3 :a 1})  
=> {:a 1 :b 2 :c 3}
```

io/copy-file

(io/copy-file input output)

Copies input to output. Returns nil or throws IOException. Input and output must be a java.io.File.

io/delete-file

(io/delete-file x)

Deletes a file. x must be a java.io.File.

io/delete-file-on-exit

(io/delete-file-on-exit x)

Deletes a file on JVM exit. x must be a string or java.io.File.

io/exists-dir?

(io/exists-dir? x)

Returns true if the file x exists and is a directory. x must be a java.io.File.

```
(io/exists-dir? (io/file "/temp"))  
=> false
```

io/exists-file?

```
(io/exists-file? x)
```

Returns true if the file x exists. x must be a java.io.File.

```
(io/exists-file? (io/file "/temp/test.txt"))  
=> false
```

io/file

```
(io/file path) (io/file parent child)
```

Returns a java.io.File. path, parent, and child can be a string or java.io.File

```
(io/file "/temp/test.txt")  
=> /temp/test.txt
```

```
(io/file "/temp" "test.txt")  
=> /temp/test.txt
```

```
(io/file (io/file "/temp") "test.txt")  
=> /temp/test.txt
```

io/file?

```
(io/file? x)
```

Returns true if x is a java.io.File.

```
(io/file? (io/file "/temp/test.txt"))  
=> true
```

io/list-files

```
(io/list-files dir filterFn?)
```

Lists files in a directory. dir must be a java.io.File. filterFn is an optional filter that filters the files found

io/load-classpath-resource

(io/load-classpath-resource name)

Loads a classpath resource.

io/mime-type

(io/mime-type file)

Returns the mime-type for the file if available else nil

```
(io/mime-type "document.pdf")  
=> "application/pdf"
```

```
(io/mime-type (io/file "document.pdf"))  
=> "application/pdf"
```

io/move-file

(io/move-file source target)

Moves source to target. Returns nil or throws IOException. Source and target must be a java.io.File.

io/slurp

(io/slurp file & options)

Returns the file's content as text (string) or binary (bytebuf).
Defaults to binary=false and encoding=UTF-8.
Options: :encoding "UTF-8" :binary true/false.

io/slurp-stream

(io/slurp-stream is & options)

Slurps binary or string data from an input stream. Supports the option :binary to either slurp binary or string data. For string data an optional encoding can be specified.
Options: :encoding "UTF-8" :binary true/false.

```
(do  
  (import :java.io.FileInputStream)  
  (let [file (io/temp-file "test-", ".txt")]  
    (io/delete-file-on-exit file)  
    (io/spit file "123456789" :append true)
```

```
(try-with [is (. :FileInputStream :new file)]
  (io/slurp-stream is :binary false)))
)
=> "123456789"
```

io/slurp-temp-file

(io/slurp-temp-file file & options)

Slurps binary or string data from a previously created temp file. Supports the option :binary to either slurp binary or string data. For string data an optional encoding can be specified.

Ensures that the caller can only read back files he previously created, but no other files. This allows callers to work with files without escaping the sandbox. The file must have been created with io/temp_file.

Options: :encoding "UTF-8" :binary true/false.

```
(do
  (let [file (io/temp-file "test-", ".txt")]
    (io/spit-temp-file file "123456789" :append true)
    (io/slurp-temp-file file :binary false :remove true))
)
=> "123456789"
```

io/spit

(io/spit f content & options)

Opens f, writes content, and then closes f.

Options default to append=true and encoding=UTF-8.

Options: :append true/false, :encoding "UTF-8"

io/spit-stream

(io/spit-stream os content & options)

Writes content (string or bytebuf) to the output stream os. If content is of type string an optional encoding (defaults to UTF-8) is supported. The stream can optionally be flushed after the operation.

Options: :flush true/false :encoding "UTF-8"

```
(do
  (import :java.io.FileOutputStream)
  (let [file (io/temp-file "test-", ".txt")]
    (io/delete-file-on-exit file)
    (try-with [os (. :FileOutputStream :new file)]
      (io/spit-stream os "123456789" :flush true)))
)
=> nil
```

io/spit-temp-file

(io/spit-temp-file f content & options)

Spits binary or string data from to previously created temp file.

Ensures that the caller can only write to files he previously created, but no other files. This allows callers to work with files without escaping the sandbox. The file must have been created with io/temp_file.

Defaults to append=true and encoding=UTF-8.

Options: :append true/false, :encoding "UTF-8"

io/temp-file

(io/temp-file prefix suffix)

Creates an empty temp file with prefix and suffix.

io/temp-file with its companions io/spit-temp-file and io/slurp-temp-file provide safe file access in sandboxed environments.

```
(do
  (let [file (io/temp-file "test-", ".txt")]
    (io/spit-temp-file file "123456789" :append true)
    (io/slurp-temp-file file :binary false :remove true))
  )
=> "123456789"
```

io/tmp-dir

(io/tmp-dir)

Returns the tmp dir as a java.io.File.

```
(io/tmp-dir )
=> /var/folders/rm/pjqr5pln3db4mxh5qq1j5yh80000gn/T
```

io/user-dir

(io/user-dir)

Returns the user dir (current working dir) as a java.io.File.

json/avail-jdk8-module?

(json/avail-jdk8-module?)

Returns true if JSON jdk8 is available otherwise false

(json/avail-jdk8-module?)

json/avail?

```
(json/avail?)
```

Returns true if JSON is available (Jackson libs on classpath) otherwise false

```
(json/avail?)
```

json/parse

```
(json/parse s)
```

Parses a JSON string

```
(json/parse (json/to-json [{:a 100 :b 100}]))
```

json/pretty-print

```
(json/pretty-print json)
```

Pretty prints JSON

```
(json/pretty-print (json/to-json {:a 100 :b 100}))
```

json/to-json

```
(json/to-json val)
```

Converts the val to JSON

```
(json/to-json {:a 100 :b 100})
```

json/to-pretty-json

```
to-pretty-json val
```

Converts the val to pretty printed JSON

```
(json/to-pretty-json {:a 100 :b 100})
```

keep

```
(keep f coll)
```

Returns a sequence of the non-nil results of (f item). Note, this means false return values will be included. f must be free of side-effects.

```
(keep even? (range 1 4))  
=> (false true false)
```

```
(keep (fn [x] (if (odd? x) x)) (range 4))  
=> (1 3)
```

key

```
(key e)
```

Returns the key of the map entry.

```
(key (find {:a 1 :b 2} :b))  
=> :b
```

keys

```
(keys map)
```

Returns a collection of the map's keys.

```
(keys {:a 1 :b 2 :c 3})  
=> (:a :b :c)
```

keyword

```
(keyword name)
```

Returns a keyword from the given name

```
(keyword "a")  
=> :a
```

```
(keyword :a)  
=> :a
```

keyword?

```
(keyword? x)
```

Returns true if x is a keyword

```
(keyword? (keyword "a"))  
=> true
```

```
(keyword? :a)  
=> true
```

```
(keyword? nil)  
=> false
```

```
(keyword? 'a)  
=> false
```

last

```
(last coll)
```

Returns the last element of coll.

```
(last nil)  
=> nil
```

```
(last [])  
=> nil
```

```
(last [1 2 3])  
=> 3
```

```
(last '())  
=> nil
```

```
(last '(1 2 3))  
=> 3
```

let

```
(let [bindings*] exprs*)
```

Evaluates the expressions and binds the values to symbols to new local context

```
(let [x 1] x)  
=> 1
```

;; destructured map

```
(let [{:keys [width height title ]  
      :or {width 640 height 500}  
      :as styles}  
      {:width 1000 :title "Title"}]  
  (println "width: " width)  
  (println "height: " height)  
  (println "title: " title)  
  (println "styles: " styles))
```

width: 1000

height: 500

title: Title

```
styles: {:width 1000 :title Title}
=> nil
```

list

(list & items)

Creates a new list containing the items.

```
(list )
=> ()
```

```
(list 1 2 3)
=> (1 2 3)
```

```
(list 1 2 3 [:a :b])
=> (1 2 3 [:a :b])
```

list-comp

(list-comp seq-exprs body-expr)

List comprehension. Takes a vector of one or more binding-form/collection-expr pairs, each followed by zero or more modifiers, and yields a collection of evaluations of expr. Supported modifiers are: :when test.

```
(list-comp [x (range 10)] x)
=> (0 1 2 3 4 5 6 7 8 9)
```

```
(list-comp [x (range 5)] (* x 2))
=> (0 2 4 6 8)
```

```
(list-comp [x (range 10) :when (odd? x)] x)
=> (1 3 5 7 9)
```

```
(list-comp [x (range 10) :when (odd? x)] (* x 2))
=> (2 6 10 14 18)
```

```
(list-comp [x (list "abc") y [0 1 2]] [x y])
=> (["abc" 0] ["abc" 1] ["abc" 2])
```

list?

(list? obj)

Returns true if obj is a list

```
(list? (list 1 2))
=> true
```

```
(list? '(1 2))
=> true
```

load-classpath-file

(load-classpath-file name)

Sequentially read and evaluate the set of forms contained in the classpath file. The function is restricted to classpath files with the extension '.venice'.

```
(do
  (load-classpath-file "com/github/jiangch/venice/test.venice")
  (test/println "hello"))
test: hello
=> nil
```

load-file

(load-file name)

Sequentially read and evaluate the set of forms contained in the file.

load-module

(load-module s)

Loads a Venice predefined extension module.

```
(do
  (load-module :logger))
=> anonymous-910fa1b6-ab51-4d32-8529-ee65b1f3f993
```

load-string

(load-string s)

Sequentially read and evaluate the set of forms contained in the string.

```
(do
  (load-string "(def x 1)")
  (+ x 2))
=> 3
```

long?

(long? n)

Returns true if n is a long

```
(long? 4)
=> true
```

```
(long? 3.1)
=> false
```

```
(long? true)
=> false
```

```
(long? nil)
=> false
```

```
(long? {})
=> false
```

loop

```
(loop [bindings*] exprs*)
```

Evaluates the exprs and binds the bindings. Creates a recursion point with the bindings.

```
;; tail recursion
(loop [x 10]
  (when (> x 1)
    (println x)
    (recur (- x 2))))
10
8
6
4
2
=> nil
```

```
;; tail recursion
(do
  (def sum
    (fn [n]
      (loop [cnt n acc 0]
        (if (zero? cnt)
          acc
          (recur (dec cnt) (+ acc cnt))))))
    (sum 10000))
=> 50005000
```

macro?

```
(macro? x)
```

Returns true if x is a macro

```
(macro? and)
=> true
```

macroexpand

(macroexpand form)

If form represents a macro form, returns its expansion, else returns form

```
(macroexpand (-> c (+ 3) (* 2)))  
=> (* (+ c 3) 2)
```

map

(map f coll colls*)

Applies f to the set of first items of each coll, followed by applying f to the set of second items in each coll, until any one of the colls is exhausted. Any remaining items in other colls are ignored.

```
(map inc [1 2 3 4])  
=> (2 3 4 5)
```

map?

(map? obj)

Returns true if obj is a map

```
(map? {:a 1 :b 2})  
=> true
```

mapcat

(mapcat fn & colls)

Returns the result of applying concat to the result of applying map to fn and colls. Thus function fn should return a collection.

```
(mapcat reverse [[3 2 1 0] [6 5 4] [9 8 7]])  
=> (0 1 2 3 4 5 6 7 8 9)
```

mapv

(mapv f coll colls*)

Returns a vector consisting of the result of applying f to the set of first items of each coll, followed by applying f to the set of second items in each coll, until any one of the colls is exhausted. Any remaining items in other colls are ignored.


```
(mapv inc [1 2 3 4])  
=> [2 3 4 5]
```

match

```
(match s regex)
```

Returns true if the string s matches the regular expression regex

```
(match "1234" "[0-9]+")  
=> true
```

```
(match "1234ss" "[0-9]+")  
=> false
```

match-not

```
(match-not s regex)
```

Returns true if the string s does not match the regular expression regex

```
(match-not "1234" "[0-9]+")  
=> false
```

```
(match-not "1234ss" "[0-9]+")  
=> true
```

max

```
(max x)  
(max x y)  
(max x y & more)
```

Returns the greatest of the values

```
(max 1)  
=> 1
```

```
(max 1 2)  
=> 2
```

```
(max 4 3 2 1)  
=> 4
```

```
(max 1.0)  
=> 1.0
```

```
(max 1.0 2.0)  
=> 2.0
```

```
(max 4.0 3.0 2.0 1.0)  
=> 4.0
```

```
(max 1.0M)
=> 1.0M

(max 1.0M 2.0M)
=> 2.0M

(max 4.0M 3.0M 2.0M 1.0M)
=> 4.0M

(max 1.0M 2)
=> 2
```

memoize

```
(memoize f)
```

Returns a memoized version of a referentially transparent function.

```
(do
  (def fibonacci
    (memoize
      (fn [n]
        (cond
          (<= n 0) 0
          (< n 2) 1
          :else (+ (fibonacci (- n 1)) (fibonacci (- n 2)))))))

  (time (fibonacci 25)))
Elapsed time: 9 msec
=> 75025
```

merge

```
(merge & maps)
```

Returns a map that consists of the rest of the maps conj-ed onto the first. If a key occurs in more than one map, the mapping from the latter (left-to-right) will be the mapping in the result.

```
(merge {:a 1 :b 2 :c 3} {:b 9 :d 4})
=> {:a 1 :b 9 :c 3 :d 4}
```

```
(merge {:a 1} nil)
=> {:a 1}
```

```
(merge nil {:a 1})
=> {:a 1}
```

```
(merge nil nil)
=> nil
```

meta

(meta obj)

Returns the metadata of obj, returns nil if there is no metadata.

min

(min x)
(min x y)
(min x y & more)

Returns the smallest of the values

(min 1)
=> 1

(min 1 2)
=> 1

(min 4 3 2 1)
=> 1

(min 1.0)
=> 1.0

(min 1.0 2.0)
=> 1.0

(min 4.0 3.0 2.0 1.0)
=> 1.0

(min 1.0M)
=> 1.0M

(min 1.0M 2.0M)
=> 1.0M

(min 4.0M 3.0M 2.0M 1.0M)
=> 1.0M

(min 1.0M 2)
=> 1.0M

mod

(mod n d)

Modulus of n and d.

(mod 10 4)
=> 2

name

(name x)

Returns the name String of a string, symbol or keyword.

(name :x)

=> "x"

(name 'x)

=> "x"

(name "x")

=> "x"

nano-time

(nano-time)

Returns the current value of the running Java Virtual Machine's high-resolution time source, in nanoseconds.

(nano-time)

=> 687733001891400

neg?

(neg? x)

Returns true if x smaller than zero else false

(neg? -3)

=> true

(neg? 3)

=> false

(neg? -3.2)

=> true

(neg? -3.2M)

=> true

negate

(negate x)

Negates x

```
(negate 10)
```

```
=> -10
```

```
(negate 1.23)
```

```
=> -1.23
```

```
(negate 1.23M)
```

```
=> -1.23M
```

newline

```
(newline)
```

Writes a platform-specific newline to *out*

```
(newline)
```

```
=> nil
```

nfirst

```
(nfirst coll n)
```

Returns a collection of the first n items

```
(nfirst nil 2)
```

```
=> ()
```

```
(nfirst [] 2)
```

```
=> []
```

```
(nfirst [1] 2)
```

```
=> [1]
```

```
(nfirst [1 2 3] 2)
```

```
=> [1 2]
```

```
(nfirst '() 2)
```

```
=> ()
```

```
(nfirst '(1) 2)
```

```
=> (1)
```

```
(nfirst '(1 2 3) 2)
```

```
=> (1 2)
```

nil?

```
(nil? x)
```

Returns true if x is nil, false otherwise

```
(nil? nil)
```

```
=> true
```

```
(nil? 0)
```

```
=> false
```

```
(nil? false)
```

```
=> false
```

nlast

```
(nlast coll n)
```

Returns a collection of the last n items

```
(nlast nil 2)
```

```
=> ()
```

```
(nlast [] 2)
```

```
=> []
```

```
(nlast [1] 2)
```

```
=> [1]
```

```
(nlast [1 2 3] 2)
```

```
=> [2 3]
```

```
(nlast '() 2)
```

```
=> ()
```

```
(nlast '(1) 2)
```

```
=> (1)
```

```
(nlast '(1 2 3) 2)
```

```
=> (2 3)
```

not

```
(not x)
```

Returns true if x is logical false, false otherwise.

```
(not true)
```

```
=> false
```

```
(not (== 1 2))
```

```
=> true
```

not-empty?

```
(not-empty? x)
```

Returns true if x is not empty

```
(empty? {:a 1})  
=> false
```

```
(empty? [1 2])  
=> false
```

```
(empty? '(1 2))  
=> false
```

nth

```
(nth coll idx)
```

Returns the nth element of coll.

```
(nth nil 1)  
=> nil
```

```
(nth [1 2 3] 1)  
=> 2
```

```
(nth '(1 2 3) 1)  
=> 2
```

number?

```
(number? n)
```

Returns true if n is a number (long, double, or decimal)

```
(number? 4.0M)  
=> true
```

```
(number? 4.0)  
=> true
```

```
(number? 3)  
=> true
```

```
(number? true)  
=> false
```

```
(number? "a")  
=> false
```

odd?

```
(odd? n)
```

Returns true if n is odd, throws an exception if n is not an integer

```
(odd? 3)
=> true
```

```
(odd? 4)
=> false
```

or

```
(or x)
(or x & next)
```

Ors the predicate forms

```
(or true false)
=> true
```

```
(or false false)
=> false
```

ordered-map

```
(ordered-map & keyvals)
(ordered-map map)
```

Creates a new ordered map containing the items.

```
(ordered-map :a 1 :b 2)
=> {:a 1 :b 2}
```

```
(ordered-map (hash-map :a 1 :b 2))
=> {:a 1 :b 2}
```

ordered-map?

```
(ordered-map? obj)
```

Returns true if obj is an ordered map

```
(ordered-map? (ordered-map :a 1 :b 2))
=> true
```

OS

```
(os)
```

Returns the OS type


```
(os)
=> :mac-osx
```

os?

```
(os? type)
```

Returns true if the OS id of the type otherwise false. Type is one of :windows, :mac-osx, or :linux

```
(os? :mac-osx)
=> true
```

```
(os? :windows)
=> false
```

partial

```
(partial f args*)
```

Takes a function f and fewer than the normal arguments to f, and returns a fn that takes a variable number of additional args. When called, the returned function calls f with args + additional args.

```
((partial * 2) 3)
=> 6
```

```
(map (partial * 2) [1 2 3 4])
=> (2 4 6 8)
```

```
(do
  (def hundred-times (partial * 100))
  (hundred-times 5))
=> 500
```

partition

```
(partition n coll)
(partition n step coll)
(partition n step padcoll coll)
```

Returns a collection of lists of n items each, at offsets step apart. If step is not supplied, defaults to n, i.e. the partitions do not overlap. If a padcoll collection is supplied, use its elements as necessary to complete last partition upto n items. In case there are not enough padding elements, return a partition with less than n items.

```
(partition 4 (range 20))
=> ((0 1 2 3) (4 5 6 7) (8 9 10 11) (12 13 14 15) (16 17 18 19))
```

```
(partition 4 6 (range 20))
=> ((0 1 2 3) (6 7 8 9) (12 13 14 15) (18 19))
```

```
(partition 3 6 ["a"] (range 20))
=> ((0 1 2) (6 7 8) (12 13 14) (18 19 "a"))
```

```
(partition 4 6 ["a" "b" "c" "d"] (range 20))  
=> ((0 1 2 3) (6 7 8 9) (12 13 14 15) (18 19 "a" "b"))
```

peek

```
(peek coll)
```

For a list, same as first, for a vector, same as last

```
(peek '(1 2 3 4))  
=> 1
```

```
(peek [1 2 3 4])  
=> 4
```

pop

```
(pop coll)
```

For a list, returns a new list without the first item, for a vector, returns a new vector without the last item.

```
(pop '(1 2 3 4))  
=> (2 3 4)
```

```
(pop [1 2 3 4])  
=> [1 2 3]
```

pos?

```
(pos? x)
```

Returns true if x greater than zero else false

```
(pos? 3)  
=> true
```

```
(pos? -3)  
=> false
```

```
(pos? 3.2)  
=> true
```

```
(pos? 3.2M)  
=> true
```

pr-str

```
(pr-str & xs)
```

With no args, returns the empty string. With one arg x, returns x.toString(). With more than one arg, returns the concatenation of the str values of the args with delimiter ' '.

```
(pr-str )
```

```
=> ""
```

```
(pr-str 1 2 3)
```

```
=> "1 2 3"
```

print

```
(print & xs)
```

Prints to stdout, with no args, prints the empty string. With one arg x, prints x.toString(). With more than one arg, prints the concatenation of the str values of the args with delimiter ' '. Returns nil.

```
(print [10 20 30])
```

```
[10 20 30]
```

```
=> nil
```

println

```
(println & xs)
```

Prints to stdout with a trailing newline, with no args, prints the empty string. With one arg x, prints x.toString(). With more than one arg, prints the concatenation of the str values of the args with delimiter ' '. Returns nil.

```
(do (println 200) (println [10 20 30]))
```

```
200
```

```
[10 20 30]
```

```
=> nil
```

promise

```
(promise)
```

Returns a promise object that can be read with deref, and set, once only, with deliver. Calls to deref prior to delivery will block, unless the variant of deref with timeout is used. All subsequent derefs will return the same delivered value without blocking.

```
(do
  (def p (promise))
  (def task (fn []
              (do
                (sleep 500)
                (deliver p 123)))))
```

```
(future task)
```

```
(deref p))
```

```
=> 123
```

promise?

```
(promise? p)
```

Returns true if f is a Promise otherwise false

```
(promise? (promise)))  
=> true
```

proxify

```
(proxify classname method-map)
```

Proxifies a Java interface to be passed as a Callback object to Java functions. The interface's methods are implemented by Venice functions.

```
(do  
  (import :java.io.File :java.io.FilenameFilter)  
  
  (def file-filter  
    (fn [dir name] (str/ends-with? name ".xxx")))  
  
  (let [dir (io/tmp-dir )]  
    ;; create a dynamic proxy for the interface FilenameFilter  
    ;; and implement its function 'accept' by 'file-filter'  
    (. dir :list (proxify :FilenameFilter {:accept file-filter})))  
  )  
=> []
```

rand-double

```
(rand-double)  
(rand-double max)
```

Without argument returns a double between 0.0 and 1.0. Without argument max returns a random double between 0.0 and max.

```
(rand-double)  
=> 0.21426651113898498
```

```
(rand-double 100.0)  
=> 26.617347985073224
```

rand-gaussian

```
(rand-gaussian)  
(rand-gaussian mean stddev)
```

Without argument returns a Gaussian distributed double value with mean 0.0 and standard deviation 1.0. With argument mean and stddev returns a Gaussian distributed double value with the given mean and standard deviation.

```
(rand-gaussian)
=> 0.7741912531440284
```

```
(rand-gaussian 0.0 5.0)
=> 2.9755972687701924
```

rand-long

```
(rand-long)
(rand-long max)
```

Without argument returns a random long between 0 and MAX_LONG. Without argument max returns a random long between 0 and max exclusive.

```
(rand-long)
=> 1785046696409847631
```

```
(rand-long 100)
=> 74
```

range

```
(range end)
(range start end)
(range start end step)
```

Returns a collection of numbers from start (inclusive) to end (exclusive), by step, where start defaults to 0 and step defaults to 1. When start is equal to end, returns empty list.

```
(range 10)
=> (0 1 2 3 4 5 6 7 8 9)
```

```
(range 10 20)
=> (10 11 12 13 14 15 16 17 18 19)
```

```
(range 10 20 3)
=> (10 13 16 19)
```

```
(range 10 15 0.5)
=> (10 10.5 11.0 11.5 12.0 12.5 13.0 13.5 14.0 14.5)
```

```
(range 1.1M 2.2M 0.1M)
=> (1.1M 1.2M 1.3M 1.4M 1.5M 1.6M 1.7M 1.8M 1.9M 2.0M 2.1M)
```

read-string

```
(read-string x)
```

Reads from x

readline

(readline prompt)

Reads the next line from stdin. The function is sandboxed

recur

(recur expr*)

Evaluates the exprs and rebinds the bindings of the recursion point to the values of the exprs.

reduce

(reduce f coll)

(reduce f val coll)

f should be a function of 2 arguments. If val is not supplied, returns the result of applying f to the first 2 items in coll, then applying f to that result and the 3rd item, etc. If coll contains no items, f must accept no arguments as well, and reduce returns the result of calling f with no arguments. If coll has only 1 item, it is returned and f is not called. If val is supplied, returns the result of applying f to val and the first item in coll, then applying f to that result and the 2nd item, etc. If coll contains no items, returns val and f is not called.

```
(reduce (fn [x y] (+ x y)) [1 2 3 4 5 6 7])
```

```
=> 28
```

```
(reduce (fn [x y] (+ x y)) 10 [1 2 3 4 5 6 7])
```

```
=> 38
```

```
((reduce comp [(partial + 1) (partial * 2) (partial + 3)]) 100)
```

```
=> 207
```

```
(reduce (fn [m [k v]] (assoc m v k)) {} {:b 2 :a 1 :c 3})
```

```
=> {3 :c 1 :a 2 :b}
```

reduce-kv

(reduce-kv f init coll)

Reduces an associative collection. f should be a function of 3 arguments. Returns the result of applying f to init, the first key and the first value in coll, then applying f to that result and the 2nd key and value, etc. If coll contains no entries, returns init and f is not called. Note that reduce-kv is supported on vectors, where the keys will be the ordinals.

```
(reduce-kv (fn [x y z] (assoc x z y)) {} {:a 1 :b 2 :c 3})
```

```
=> {3 :c 1 :a 2 :b}
```

remove

```
(remove predicate coll)
```

Returns a collection of the items in coll for which (predicate item) returns logical false.

```
(filter even? [1 2 3 4 5 6 7])  
=> [2 4 6]
```

repeat

```
(repeat n x)
```

Returns a collection with the value x repeated n times

```
(repeat 5 [1 2])  
=> ([1 2] [1 2] [1 2] [1 2] [1 2])
```

repeatedly

```
(repeatedly n fn)
```

Takes a function of no args, presumably with side effects, and returns a collection of n calls to it

```
(repeatedly 5 (fn [] (rand-long 11)))  
=> (5 10 7 5 3)
```

```
;; compare with repeat, which only calls the 'rand-long'  
;; function once, repeating the value five times.  
(repeat 5 (rand-long 11))  
=> (6 6 6 6 6)
```

reset!

```
(reset! atom newval)
```

Sets the value of atom to newval without regard for the current value. Returns newval.

```
(do  
  (def counter (atom 0))  
  (reset! counter 99)  
  (deref counter))  
=> 99
```

rest

```
(rest coll)
```

Returns a collection with second to list element

```
(rest nil)  
=> nil
```

```
(rest [])  
=> []
```

```
(rest [1])  
=> []
```

```
(rest [1 2 3])  
=> [2 3]
```

```
(rest '())  
=> ()
```

```
(rest '(1))  
=> ()
```

```
(rest '(1 2 3))  
=> (2 3)
```

reverse

```
(reverse coll)
```

Returns a collection of the items in coll in reverse order

```
(reverse [1 2 3 4 5 6])  
=> [6 5 4 3 2 1]
```

sandboxed?

```
(sandboxed? )
```

Returns true if there is a sandbox otherwise false

```
(sandboxed? )  
=> false
```

second

```
(second coll)
```

Returns the second element of coll.

```
(second nil)  
=> nil
```



```
(second [])  
=> nil  
  
(second [1 2 3])  
=> 2  
  
(second '())  
=> nil  
  
(second '(1 2 3))  
=> 2
```

seq

```
(seq coll)
```

Returns a seq on the collection. If the collection is empty, returns nil. (seq nil) returns nil. seq also works on Strings.

```
(seq nil)  
=> nil  
  
(seq [1 2 3])  
=> (1 2 3)  
  
(seq '(1 2 3))  
=> (1 2 3)  
  
(seq {:a 1 :b 2})  
=> ([:a 1] [:b 2])  
  
(seq "abcd")  
=> ("a" "b" "c" "d")
```

sequential?

```
(sequential? obj)
```

Returns true if obj is a sequential collection

```
(sequential? '(1))  
=> true  
  
(sequential? [1])  
=> true  
  
(sequential? {:a 1})  
=> false  
  
(sequential? nil)  
=> false  
  
(sequential? "abc")  
=> false
```

set

(set & items)

Creates a new set containing the items.

```
(set )
```

```
=> #{} 
```

```
(set nil)
```

```
=> #{nil} 
```

```
(set 1)
```

```
=> #{1} 
```

```
(set 1 2 3)
```

```
=> #{1 2 3} 
```

```
(set [1 2] 3)
```

```
=> #{[1 2] 3} 
```

set?

(set? obj)

Returns true if obj is a set

```
(set? (set 1))
```

```
=> true 
```

sh

(sh & args)

Passes the given strings to `Runtime.exec()` to launch a sub-process.

Options are

`:in` may be given followed by input source as `InputStream`, `Reader`, `File`, `ByteBuf`, or `String`, to be fed to the sub-process's `stdin`.

`:in-enc` option may be given followed by a `String`, used as a character encoding name (for example "UTF-8" or "ISO-8859-1") to convert the input string specified by the `:in` option to the sub-process's `stdin`. Defaults to UTF-8.

If the `:in` option provides a byte array, then the bytes are passed unencoded, and this option is ignored.

`:out-enc` option may be given followed by `:bytes` or a `String`. If a `String` is given, it will be used as a character encoding name (for example "UTF-8" or "ISO-8859-1") to convert the sub-process's `stdout` to a `String` which is returned.

If `:bytes` is given, the sub-process's `stdout` will be stored in a `Bytebuf` and returned. Defaults to UTF-8.

`:env` override the process `env` with a map.

`:dir` override the process `dir` with a `String` or `java.io.File`.

You can bind `:env` or `:dir` for multiple operations using `with-sh-env` and `with-sh-dir`.

`sh` returns a map of

`:exit` => sub-process's exit code

`:out` => sub-process's stdout (as `Bytebuf` or `String`)

`:err` => sub-process's stderr (String via platform default encoding)

```
(println (sh "ls" "-l"))
```

```
(println (sh "ls" "-l" "/tmp"))
```

```
(println (sh "sed" "s/[aeiou]/oo/g" :in "hello there\n"))
```

```
(println (sh "cat" :in "\u25bax\n"))
```

```
(println (sh "echo" "\u25bax"))
```

```
(println (sh "/bin/sh" "-c" "ls -l"))
```

```
:: reads 4 single-byte chars
```

```
(println (sh "echo" "\u25bax" :out-enc "ISO-8859-1"))
```

```
:: reads binary file into bytes[]
```

```
(println (sh "cat" "birds.jpg" :out-enc :bytes))
```

```
:: working directory
```

```
(println (with-sh-dir "/tmp" (sh "ls" "-l") (sh "pwd")))
```

```
:: windows
```

```
(println (sh "cmd" "/c dir 1>&2"))
```

sleep

```
(sleep n)
```

Sleep for `n` milliseconds.

```
(sleep 30)
```

```
=> nil
```

some?

```
(some? x)
```

Returns true if `x` is not nil, false otherwise

```
(some? nil)
```

```
=> false
```

```
(some? 0)
```

```
=> true
```

```
(some? 4.0)
```

```
=> true
```

```
(some? false)
=> true
```

```
(some? [])
=> true
```

```
(some? {})
=> true
```

sort

```
(sort coll)
(sort comparefn coll)
```

Returns a sorted list of the items in coll. If no compare function comparefn is supplied, uses the natural compare. The compare function takes two arguments and returns -1, 0, or 1

```
(sort [3 2 5 4 1 6])
=> [1 2 3 4 5 6]
```

```
(sort compare [3 2 5 4 1 6])
=> [1 2 3 4 5 6]
```

```
; reversed
(sort (comp (partial * -1) compare) [3 2 5 4 1 6])
=> [6 5 4 3 2 1]
```

```
(sort {:c 3 :a 1 :b 2})
=> ([:a 1] [:b 2] [:c 3])
```

sort-by

```
(sort-by keyfn coll)
(sort-by keyfn compfn coll)
```

Returns a sorted sequence of the items in coll, where the sort order is determined by comparing (keyfn item). If no comparator is supplied, uses compare.

```
(sort-by count ["aaa" "bb" "c"])
=> ["c" "bb" "aaa"]
```

```
; reversed
(sort-by count (comp (partial * -1) compare) ["aaa" "bb" "c"])
=> ["aaa" "bb" "c"]
```

```
(sort-by first [[1 2] [3 4] [2 3]])
=> [[1 2] [2 3] [3 4]]
```

```
; reversed
(sort-by first (comp (partial * -1) compare) [[1 2] [3 4] [2 3]])
=> [[3 4] [2 3] [1 2]]
```

```
(sort-by (fn [x] (get x :rank)) [{:rank 2} {:rank 3} {:rank 1}])
=> [{:rank 1} {:rank 2} {:rank 3}]
```

```
; reversed
(sort-by (fn [x] (get x :rank)) (comp (partial * -1) compare) [{:rank 2} {:rank 3} {:rank 1}])
=> [{:rank 3} {:rank 2} {:rank 1}]
```

sorted-map

```
(sorted-map & keyvals)
(sorted-map map)
```

Creates a new sorted map containing the items.

```
(sorted-map :a 1 :b 2)
=> {:a 1 :b 2}
```

```
(sorted-map (hash-map :a 1 :b 2))
=> {:a 1 :b 2}
```

sorted-map?

```
(sorted-map? obj)
```

Returns true if obj is a sorted map

```
(sorted-map? (sorted-map :a 1 :b 2))
=> true
```

split-with

```
(split-with pred coll)
```

Splits the collection at the first false/nil predicate result in a vector with two lists

```
(split-with odd? [1 3 5 6 7 9])
=> [(1 3 5) (6 7 9)]
```

```
(split-with odd? [1 3 5])
=> [(1 3 5) ()]
```

```
(split-with odd? [2 4 6])
=> [()] (2 4 6)]
```

str

```
(str & xs)
```

With no args, returns the empty string. With one arg x, returns x.toString(). (str nil) returns the empty string. With more than one arg, returns the concatenation of the str values of the args.

```
(str )  
=> ""
```

```
(str 1 2 3)  
=> "123"
```

str/blank?

```
(str/blank? s)
```

True if s is blank.

```
(str/blank? nil)  
=> true
```

```
(str/blank? "")  
=> true
```

```
(str/blank? " ")  
=> true
```

```
(str/blank? "abc")  
=> false
```

str/char

```
(str/char n)
```

Converts a number to a single char string.

```
(str/char 65)  
=> "A"
```

str/contains?

```
(str/contains? s substr)
```

True if s contains with substr.

```
(str/contains? "abc" "ab")  
=> true
```

str/ends-with?

```
(str/ends-with? s substr)
```

True if s ends with substr.

```
(str/starts-with? "abc" "bc")  
=> false
```

str/format

```
(str/format format args*)
```

Returns a formatted string using the specified format string and arguments.

```
(str/format "%s: %d" "abc" 100)  
=> "abc: 100"
```

str/index-of

```
(str/index-of s value)  
(str/index-of s value from-index)
```

Return index of value (string or char) in s, optionally searching forward from from-index. Return nil if value not found.

```
(str/index-of "abcdefabc" "ab")  
=> 0
```

str/join

```
(str/join coll)  
(str/join separator coll)
```

Joins all elements in coll separated by an optional separator.

```
(str/join [1 2 3])  
=> "123"
```

```
(str/join "-" [1 2 3])  
=> "1-2-3"
```

str/last-index-of

```
(str/last-index-of s value)  
(str/last-index-of s value from-index)
```

Return last index of value (string or char) in s, optionally searching backward from from-index. Return nil if value not found.

```
(str/last-index-of "abcdefabc" "ab")  
=> 6
```

str/lower-case

```
(str/lower-case s)
```

Converts s to lowercase

```
(str/lower-case "aBcDeF")  
=> "abcdef"
```

str/quote

```
(str/quote str q)  
(str/quote str start end)
```

Quotes a string.

```
(str/quote "abc" "-")  
=> "-abc-"
```

```
(str/quote "abc" "<" ">")  
=> "<abc>"
```

str/repeat

```
(str/repeat s n)  
(str/repeat s n sep)
```

Repeats s n times with an optional separator.

```
(str/repeat "abc" 0)  
=> ""
```

```
(str/repeat "abc" 3)  
=> "abcabcabc"
```

```
(str/repeat "abc" 3 "-")  
=> "abc-abc-abc"
```

str/replace-all

```
(str/replace-all s search replacement)
```

Replaces the all occurrences of search in s

```
(str/replace-all "abcdefabc" "ab" "XYZ")  
=> "XYZcdefXYZc"
```


str/replace-first

(str/replace-first s search replacement)

Replaces the first occurrence of search in s

```
(str/replace-first "abcdefabc" "ab" "XYZ")  
=> "XYZdefabc"
```

str/replace-last

(str/replace-last s search replacement)

Replaces the last occurrence of search in s

```
(str/replace-last "abcdefabc" "ab" "XYZ")  
=> "abcdefXYZ"
```

str/split

(str/split s regex)

Splits string on a regular expression.

```
(str/split "abc , def , ghi" "[ *],[ *]")  
=> ("abc" "def" "ghi")
```

str/split-lines

(str/split-lines s)

Splits s into lines.

```
(str/split-lines "line1  
line2  
line3")  
=> ("line1" "line2" "line3")
```

str/starts-with?

(str/starts-with? s substr)

True if s starts with substr.

```
(str/starts-with? "abc" "ab")  
=> true
```

str/strip-end

```
(str/strip-end s substr)
```

Removes a substr only if it is at the end of a s, otherwise returns s.

```
(str/strip-end "abcdef" "def")  
=> "abc"
```

```
(str/strip-end "abcdef" "abc")  
=> "abcdef"
```

str/strip-indent

```
(str/strip-indent s)
```

Strip the indent of a multi-line string. The first line's leading whitespaces define the indent.

```
(str/strip-indent " line1  
  line2  
  line3")  
=> "line1\n line2\n line3"
```

str/strip-margin

```
(str/strip-margin s)
```

Strips leading whitespaces upto and including the margin '|' from each line in a multi-line string.

```
(str/strip-margin "line1  
  line2  
  line3")  
=> "line1\n line2\n line3"
```

str/strip-start

```
(str/strip-start s substr)
```

Removes a substr only if it is at the beginning of a s, otherwise returns s.

```
(str/strip-start "abcdef" "abc")  
=> "def"
```

```
(str/strip-start "abcdef" "def")  
=> "abcdef"
```

str/subs

```
(str/subs s start)
(str/subs s start end)
```

Returns the substring of s beginning at start inclusive, and ending at end (defaults to length of string), exclusive.

```
(str/subs "abcdef" 2)
=> "cdef"
```

```
(str/subs "abcdef" 2 5)
=> "cde"
```

str/trim

```
(str/trim s substr)
```

Trims leading and trailing spaces from s.

```
(str/trim " abc ")
=> "abc"
```

str/trim-to-nil

```
(str/trim-to-nil s substr)
```

Trims leading and trailing spaces from s. Returns nil if the resulting string is empty

```
(str/trim "")
=> ""
```

```
(str/trim " ")
=> ""
```

```
(str/trim nil)
=> nil
```

```
(str/trim " abc ")
=> "abc"
```

str/truncate

```
(str/truncate s maxlen marker)
```

Truncates a string to the max length maxlen and adds the marker to the end if the string needs to be truncated

```
(str/truncate "abcdefghij" 20 "...")  
=> "abcdefghij"
```

```
(str/truncate "abcdefghij" 9 "...")  
=> "abcdef..."
```

```
(str/truncate "abcdefghij" 4 "...")  
=> "a..."
```

str/upper-case

```
(str/upper-case s)
```

Converts s to uppercase

```
(str/upper-case "aBcDeF")  
=> "ABCDEF"
```

string?

```
(string? x)
```

Returns true if x is a string

```
(bytebuf? (bytebuf [1 2]))  
=> true
```

```
(bytebuf? [1 2])  
=> false
```

```
(bytebuf? nil)  
=> false
```

subvec

```
(subvec v start) (subvec v start end)
```

Returns a vector of the items in vector from start (inclusive) to end (exclusive). If end is not supplied, defaults to (count vector)

```
(subvec [1 2 3 4 5 6] 2)  
=> [3 4 5 6]
```

```
(subvec [1 2 3 4 5 6] 4)  
=> [5 6]
```

swap!

```
(swap! atom f & args)
```

Atomically swaps the value of atom to be: (apply f current-value-of-atom args). Note that f may be called multiple times, and thus should be free of side effects. Returns the value that was swapped in.

```
(do
  (def counter (atom 0))
  (swap! counter inc)
  (deref counter))
=> 1
```

symbol

(symbol name)

Returns a symbol from the given name

```
(symbol "a")
=> a
```

```
(symbol 'a)
=> a
```

symbol?

(symbol? x)

Returns true if x is a symbol

```
(symbol? (symbol "a"))
=> true
```

```
(symbol? 'a)
=> true
```

```
(symbol? nil)
=> false
```

```
(symbol? :a)
=> false
```

system-prop

(system-prop name default-val)

Returns the system property with the given name. Returns the default-val if the property does not exist or it's value is nil

```
(system-prop :os.name)
=> "Mac OS X"
```

```
(system-prop :foo.org "abc")
=> "abc"
```

```
(system-prop "os.name")  
=> "Mac OS X"
```

take

```
(take n coll)
```

Returns a collection of the first *n* items in *coll*, or all items if there are fewer than *n*.

```
(take 3 [1 2 3 4 5])  
=> [1 2 3]
```

```
(take 10 [1 2 3 4 5])  
=> [1 2 3 4 5]
```

take-while

```
(take-while predicate coll)
```

Returns a list of successive items from *coll* while *(predicate item)* returns logical true.

```
(take-while neg? [-2 -1 0 1 2 3])  
=> [-2 -1]
```

thread-local

```
(thread-local)
```

Creates a new thread-local accessor

```
(thread-local :a 1 :b 2)  
=> ThreadLocal
```

```
(thread-local { :a 1 :b 2 })  
=> ThreadLocal
```

```
(do  
  (thread-local-clear)  
  (assoc (thread-local) :a 1 :b 2)  
  (dissoc (thread-local) :a)  
  (get (thread-local) :b 100)  
)  
=> 2
```

thread-local-clear

```
(thread-local-clear)
```

Removes all thread local vars

(thread-local-clear)
=> thread-local-clear

do (+ 0 2) -1ararar))Tj ET BT /F1 7.5 Tf 1 0 0 1 45.38043.17 Tm (=-1))Tj ET BT /F1 7.5 Tf 1 0 0 1 45.35705.62 Tm (y))Tj ET BT /F1 7.5 Tf 1 0 0 1 45.34654.4

```
(time/after? date1 date2)
```

Returns true if date1 is after date2 else false

```
(time/after? (time/local-date) (time/minus (time/local-date) :days 2))  
=> true
```

time/before?

```
(time/before? date1 date2)
```

Returns true if date1 is before date2 else false

```
(time/before? (time/local-date) (time/minus (time/local-date) :days 2))  
=> false
```

time/date

```
(time/date)  
(time/date x)
```

Creates a new date. A date is represented by 'java.util.Date'

```
(time/date)  
=> Thu Oct 18 10:10:05 CEST 2018
```

time/date?

```
(time/date? date)
```

Returns true if date is a date else false

```
(time/date? (time/date))  
=> true
```

time/day-of-month

```
(time/day-of-month date)
```

Returns the day of the month (1..31)

```
(time/day-of-month (time/local-date))  
=> 18
```

```
(time/day-of-month (time/local-date-time))  
=> 18
```



```
(time/day-of-month (time/zoned-date-time))  
=> 18
```

time/day-of-week

```
(time/day-of-week date)
```

Returns the day of the week (:MONDAY ... :SUNDAY)

```
(time/day-of-week (time/local-date))  
=> :THURSDAY
```

```
(time/day-of-week (time/local-date-time))  
=> :THURSDAY
```

```
(time/day-of-week (time/zoned-date-time))  
=> :THURSDAY
```

time/day-of-year

```
(time/day-of-year date)
```

Returns the day of the year (1..366)

```
(time/day-of-year (time/local-date))  
=> 291
```

```
(time/day-of-year (time/local-date-time))  
=> 291
```

```
(time/day-of-year (time/zoned-date-time))  
=> 291
```

time/earliest

```
(time/earliest coll)
```

Returns the earliest date from a collection of dates. All dates must be of equal type. The coll may be empty or nil.

```
(time/earliest [(time/local-date 2018 8 4) (time/local-date 2018 8 3)])  
=> 2018-08-03
```

time/first-day-of-month

```
(time/first-day-of-month date)
```

Returns the first day of a month as a local-date.

```
(time/first-day-of-month (time/local-date))  
=> 2018-10-01
```

```
(time/first-day-of-month (time/local-date-time))  
=> 2018-10-01
```

```
(time/first-day-of-month (time/zoned-date-time))  
=> 2018-10-01
```

time/format

```
(time/format date format locale?)  
(time/format date formatter locale?)
```

Formats a date with a format

```
(time/format (time/local-date) "dd-MM-yyyy")  
=> "18-10-2018"
```

```
(time/format (time/zoned-date-time) "yyyy-MM-dd'T'HH:mm:ss.SSSz")  
=> "2018-10-18T10:10:05.531CEST"
```

```
(time/format (time/zoned-date-time) :ISO_OFFSET_DATE_TIME)  
=> "2018-10-18T10:10:05.533+02:00"
```

```
(time/format (time/zoned-date-time) (time/formatter "yyyy-MM-dd'T'HH:mm:ss.SSSz"))  
=> "2018-10-18T10:10:05.535CEST"
```

```
(time/format (time/zoned-date-time) (time/formatter :ISO_OFFSET_DATE_TIME))  
=> "2018-10-18T10:10:05.537+02:00"
```

time/formatter

```
(time/formatter format locale?)
```

Creates a formatter

```
(time/formatter "dd-MM-yyyy")  
=> Value(DayOfMonth,2)('-'Value(MonthOfYear,2)('-'Value(YearOfEra,4,19,EXCEEDS_PAD)
```

```
(time/formatter "dd-MM-yyyy" :en_EN)  
=> Value(DayOfMonth,2)('-'Value(MonthOfYear,2)('-'Value(YearOfEra,4,19,EXCEEDS_PAD)
```

```
(time/formatter "dd-MM-yyyy" "en_EN")  
=> Value(DayOfMonth,2)('-'Value(MonthOfYear,2)('-'Value(YearOfEra,4,19,EXCEEDS_PAD)
```

```
(time/formatter "yyyy-MM-dd'T'HH:mm:ss.SSSz")  
=> Value(YearOfEra,4,19,EXCEEDS_PAD)('-'Value(MonthOfYear,2)('-'Value(DayOfMonth,2)'T'Value(HourOfDay,2)':'Value(MinuteOfHour,2)':'Value(SecondOfMinute,2)':'Fraction(NanoOfSecond,3,3)ZoneText(SHORT)
```

```
(time/formatter :ISO_OFFSET_DATE_TIME)  
=> ParseCaseSensitive(false)(ParseCaseSensitive(false)(Value(Year,4,10,EXCEEDS_PAD)('-'Value(MonthOfYear,2)('-'Value(DayOfMonth,2))'T'(Value(HourOfDay,2)':'Value(MinuteOfHour,2)[':'Value(SecondOfMinute,2)[Fraction(NanoOfSecond,0,9,DecimalPoint)]))Offset(+HH:MM:ss,'Z')
```

time/hour

(time/hour date)

Returns the hour of the date 1..24

(time/hour (time/local-date))

=> 0

(time/hour (time/local-date-time))

=> 10

(time/hour (time/zoned-date-time))

=> 10

time/last-day-of-month

(time/last-day-of-month date)

Returns the last day of a month as a local-date.

(time/last-day-of-month (time/local-date))

=> 2018-10-31

(time/last-day-of-month (time/local-date-time))

=> 2018-10-31

(time/last-day-of-month (time/zoned-date-time))

=> 2018-10-31

time/latest

(time/latest coll)

Returns the latest date from a collection of dates. All dates must be of equal type. The coll may be empty or nil.

(time/latest [(time/local-date 2018 8 1) (time/local-date 2018 8 3)])

=> 2018-08-03

time/local-date

(time/local-date)

(time/local-date year month day)

(time/local-date date)

Creates a new local-date. A local-date is represented by 'java.time.LocalDate'

(time/local-date)

=> 2018-10-18

```
(time/local-date 2018 8 1)
=> 2018-08-01

(time/local-date "2018-08-01")
=> 2018-08-01

(time/local-date 1375315200000)
=> 2013-08-01

(time/local-date (. :java.util.Date :new))
=> 2018-10-18
```

time/local-date-parse

(time/local-date-parse str format locale?)

Parses a local-date.

```
(time/local-date-parse "2018-08-01" "yyyy-MM-dd")
=> 2018-08-01
```

time/local-date-time

```
(time/local-date-time)
(time/local-date-time year month day)
(time/local-date-time year month day hour minute second)
(time/local-date-time year month day hour minute second millis)
(time/local-date-time date)
```

Creates a new local-date-time. A local-date-time is represented by 'java.time.LocalDateTime'

```
(time/local-date-time)
=> 2018-10-18T10:10:05.411

(time/local-date-time 2018 8 1)
=> 2018-08-01T00:00

(time/local-date-time 2018 8 1 14 20 10)
=> 2018-08-01T14:20:10

(time/local-date-time 2018 8 1 14 20 10 200)
=> 2018-08-01T14:20:10.200

(time/local-date-time "2018-08-01T14:20:10.200")
=> 2018-08-01T14:20:10.200

(time/local-date-time 1375315200000)
=> 2013-08-01T02:00

(time/local-date-time (. :java.util.Date :new))
=> 2018-10-18T10:10:05.429
```

time/local-date-time-parse

(time/local-date-time-parse str format locale?)

Parses a local-date-time.

(time/local-date-time-parse "2018-08-01 14:20" "yyyy-MM-dd HH:mm")

=> 2018-08-01T14:20

(time/local-date-time-parse "2018-08-01 14:20:01.000" "yyyy-MM-dd HH:mm:ss.SSS")

=> 2018-08-01T14:20:01

time/local-date-time?

(time/local-date-time? date)

Returns true if date is a local-date-time else false

(time/local-date-time? (time/local-date-time))

=> true

time/local-date?

(time/local-date? date)

Returns true if date is a locale date else false

(time/local-date? (time/local-date))

=> true

time/minus

(time/minus date unit n)

Subtracts the n units from the date. Units: { :years :months :weeks :days :hours :minutes :seconds :milliseconds }

(time/minus (time/local-date) :days 2)

=> 2018-10-16

(time/minus (time/local-date-time) :days 2)

=> 2018-10-16T10:10:05.558

(time/minus (time/zoned-date-time) :days 2)

=> 2018-10-16T10:10:05.560+02:00[Europe/Zurich]

time/minute

(time/minute date)

Returns the minute of the date 0..59

(time/minute (time/local-date))

=> 0

(time/minute (time/local-date-time))

=> 10

(time/minute (time/zoned-date-time))

=> 10

time/month

(time/month date)

Returns the month of the date 1..12

(time/month (time/local-date))

=> 10

(time/month (time/local-date-time))

=> 10

(time/month (time/zoned-date-time))

=> 10

time/not-after?

(time/not-after? date1 date2)

Returns true if date1 is not-after date2 else false

(time/not-after? (time/local-date) (time/minus (time/local-date) :days 2))

=> false

time/not-before?

(time/not-before? date1 date2)

Returns true if date1 is not-before date2 else false

(time/not-before? (time/local-date) (time/minus (time/local-date) :days 2))

=> true

time/period

(time/period from to unit)

Returns the period interval of two dates in the specified unit. Units: { :years :months :weeks :days :hours :minutes :seconds :milliseconds }

(time/period (time/local-date) (time/plus (time/local-date) :days 3) :days)
=> 3

(time/period (time/local-date-time) (time/plus (time/local-date-time) :days 3) :days)
=> 3

(time/period (time/zoned-date-time) (time/plus (time/zoned-date-time) :days 3) :days)
=> 3

time/plus

(time/plus date unit n)

Adds the n units to the date. Units: { :years :months :weeks :days :hours :minutes :seconds :milliseconds }

(time/plus (time/local-date) :days 2)
=> 2018-10-20

(time/plus (time/local-date-time) :days 2)
=> 2018-10-20T10:10:05.554

(time/plus (time/zoned-date-time) :days 2)
=> 2018-10-20T10:10:05.555+02:00[Europe/Zurich]

time/second

(time/second date)

Returns the second of the date 0..59

(time/second (time/local-date))
=> 0

(time/second (time/local-date-time))
=> 5

(time/second (time/zoned-date-time))
=> 5

time/to-millis

(time/to-millis date)

Converts the passed date to milliseconds since epoch

(time/to-millis (time/local-date))
=> 1539813600000

time/with-time

(time/with-time date hour minute second)
(time/with-time date hour minute second millis)

Sets the time of a date. Returns a new date

(time/with-time (time/local-date) 22 00 15 333)
=> 2018-10-18T22:00:15.333

(time/with-time (time/local-date-time) 22 00 15 333)
=> 2018-10-18T22:00:15.333

(time/with-time (time/zoned-date-time) 22 00 15 333)
=> 2018-10-18T22:00:15.333+02:00[Europe/Zurich]

time/within?

(time/within? date start end)

Returns true if the date is after or equal to the start and is before or equal to the end. All three dates must be of the same type.

(time/within? (time/local-date 2018 8 4) (time/local-date 2018 8 1) (time/local-date 2018 8 31))
=> true

(time/within? (time/local-date 2018 7 4) (time/local-date 2018 8 1) (time/local-date 2018 8 31))
=> false

time/year

(time/year date)

Returns the year of the date

(time/year (time/local-date))
=> 2018

(time/year (time/local-date-time))
=> 2018

(time/year (time/zoned-date-time))
=> 2018

time/zone

(time/zone date)

Returns the zone of the date

```
(time/zone (time/zoned-date-time))  
=> :Europe/Zurich
```

time/zone-ids

(time/zone-ids)

Returns all available zone ids with time offset

```
(nfirst (seq (time/zone-ids)) 10)  
=> ([[:Africa/Abidjan "+00:00"] [:Africa/Accra "+00:00"] [:Africa/Addis_Ababa "+03:00"] [:Africa/Algiers "+01:00"] [:Africa/Asmara "+03:00"] [:Africa/Asmera "+03:00"] [:Africa/Bamako "+00:00"] [:Africa/Bangui "+01:00"] [:Africa/Banjul "+00:00"] [:Africa/Bissau "+00:00"]])
```

time/zone-offset

(time/zone-offset date)

Returns the zone-offset of the date in minutes

```
(time/zone-offset (time/zoned-date-time))  
=> 120
```

time/zoned-date-time

```
(time/zoned-date-time )  
(time/zoned-date-time year month day)  
(time/zoned-date-time year month day hour minute second)  
(time/zoned-date-time year month day hour minute second millis)  
(time/zoned-date-time date)  
(time/zoned-date-time zone-id)  
(time/zoned-date-time zone-id year month day)  
(time/zoned-date-time zone-id year month day hour minute second)  
(time/zoned-date-time zone-id year month day hour minute second millis)  
(time/zoned-date-time zone-id date)
```

Creates a new zoned-date-time. A zoned-date-time is represented by 'java.time.ZonedDateTime'

```
(time/zoned-date-time)  
=> 2018-10-18T10:10:05.439+02:00[Europe/Zurich]
```

```
(time/zoned-date-time 2018 8 1)  
=> 2018-08-01T00:00+02:00[Europe/Zurich]
```

```
(time/zoned-date-time 2018 8 1 14 20 10)  
=> 2018-08-01T14:20:10+02:00[Europe/Zurich]
```

```
(time/zoned-date-time 2018 8 1 14 20 10 200)  
=> 2018-08-01T14:20:10.200+02:00[Europe/Zurich]
```

```
(time/zoned-date-time "2018-08-01T14:20:10.200+01:00")
```

```
=> 2018-08-01T14:20:10.200+01:00

(time/zoned-date-time 1375315200000)
=> 2013-08-01T02:00+02:00[Europe/Zurich]

(time/zoned-date-time (. :java.util.Date :new))
=> 2018-10-18T10:10:05.457+02:00[Europe/Zurich]

(time/zoned-date-time :UTC)
=> 2018-10-18T08:10:05.459Z[UTC]

(time/zoned-date-time :UTC 2018 8 1)
=> 2018-08-01T00:00Z[UTC]

(time/zoned-date-time :UTC 2018 8 1 14 20 10)
=> 2018-08-01T14:20:10Z[UTC]

(time/zoned-date-time :UTC 2018 8 1 14 20 10 200)
=> 2018-08-01T14:20:10.200Z[UTC]

(time/zoned-date-time :UTC "2018-08-01T14:20:10.200+01:00")
=> 2018-08-01T14:20:10.200Z[UTC]

(time/zoned-date-time :UTC 1375315200000)
=> 2013-08-01T00:00Z[UTC]

(time/zoned-date-time :UTC (. :java.util.Date :new))
=> 2018-10-18T08:10:05.468Z[UTC]
```

time/zoned-date-time-parse

(time/zoned-date-time-parse str format locale?)

Parses a zoned-date-time.

```
(time/zoned-date-time-parse "2018-08-01T14:20:01+01:00" "yyyy-MM-dd'T'HH:mm:ssz")
=> 2018-08-01T14:20:01+01:00
```

```
(time/zoned-date-time-parse "2018-08-01T14:20:01.000+01:00" "yyyy-MM-dd'T'HH:mm:ss.SSSz")
=> 2018-08-01T14:20:01+01:00
```

```
(time/zoned-date-time-parse "2018-08-01T14:20:01.000+01:00" :ISO_OFFSET_DATE_TIME)
=> 2018-08-01T14:20:01+01:00
```

```
(time/zoned-date-time-parse "2018-08-01 14:20:01.000 +01:00" "yyyy-MM-dd' 'HH:mm:ss.SSS' 'z")
=> 2018-08-01T14:20:01+01:00
```

time/zoned-date-time?

(time/zoned-date-time? date)

Returns true if date is a zoned-date-time else false

```
(time/zoned-date-time? (time/zoned-date-time))
=> true
```

true?

```
(true? x)
```

Returns true if x is true, false otherwise

```
(true? true)
=> true
```

```
(true? false)
=> false
```

```
(true? nil)
=> false
```

```
(true? 0)
=> false
```

```
(true? (== 1 1))
=> true
```

try

```
(try expr)
(try expr (catch exClass exSym expr))
(try expr (catch exClass exSym expr) (finally expr))
```

Exception handling: try - catch -finally

```
(try (throw))
=> JavaValueException: null
```

```
(try
  (throw "test message"))
=> JavaValueException: null
```

```
(try
  (throw 100)
  (catch :java.lang.Exception ex -100)))
=> -100
```

```
(try
  (throw 100)
  (finally (println "...finally")))
...finally
=> JavaValueException: null
```

```
(try
  (throw 100)
  (catch :java.lang.Exception ex -100)
  (finally (println "...finally")))
...finally
=> -100
```

```
(do
  (import :java.lang.RuntimeException)
```

```

    (try
      (throw (. :RuntimeException :new "message"))
      (catch :RuntimeException ex (:message ex)))
    )
  => "message"

  (do
    (import :com.github.jlangch.venice.ValueException)
    (try
      (throw [1 2 3])
      (catch :ValueException ex (str (:value ex)))
      (catch :RuntimeException ex "runtime ex")
      (finally (println "...finally")))
    )
    ...finally
  => "[1 2 3]"

```

try-with

```

(try-with [bindings*] expr)
(try-with [bindings*] expr (catch :java.lang.Exception ex expr))
(try-with [bindings*] expr (catch :java.lang.Exception ex expr) (finally expr))

```

try-with resources allows the declaration of resources to be used in a try block with the assurance that the resources will be closed after execution of that block. The resources declared must implement the Closeable or AutoCloseable interface.

```

(do
  (import :java.io.FileInputStream)
  (let [file (io/temp-file "test-", ".txt")]
    (io/spit file "123456789" :append true)
    (try-with [is (. :FileInputStream :new file)]
      (io/slurp-stream is :binary false)))
  )
  => "123456789"

```

type

```

(type x)

```

Returns the type of x.

```

(type 5)
=> "venice.Long"

```

```

(type (. :java.time.ZonedDateTime :now))
=> "venice.JavaObject(java.time.ZonedDateTime)"

```

union

```

(union s1)
(union s1 s2)
(union s1 s2 & sets)

```

Return a set that is the union of the input sets

```
(union (set 1 2 3))
```

```
=> #{1 2 3}
```

```
(union (set 1 2) (set 2 3))
```

```
=> #{1 2 3}
```

```
(union (set 1 2 3) (set 1 2) (set 1 4) (set 3))
```

```
=> #{1 2 3 4}
```

update

```
(update m k f)
```

Updates a value in an associative structure, where k is a key and f is a function that will take the old value return the new value. Returns a new structure.

```
(update [] 0 (fn [x] 5))
```

```
=> [5]
```

```
(update [0 1 2] 0 (fn [x] 5))
```

```
=> [5 1 2]
```

```
(update [0 1 2] 0 (fn [x] (+ x 1)))
```

```
=> [1 1 2]
```

```
(update {} :a (fn [x] 5))
```

```
=> {:a 5}
```

```
(update {:a 0} :b (fn [x] 5))
```

```
=> {:a 0 :b 5}
```

```
(update {:a 0 :b 1} :a (fn [x] 5))
```

```
=> {:a 5 :b 1}
```

update!

```
(update! m k f)
```

Updates a value in an associative structure, where k is a key and f is a function that will take the old value return the new value.

```
(update! [] 0 (fn [x] 5))
```

```
=> [5]
```

```
(update! [0 1 2] 0 (fn [x] 5))
```

```
=> [5 1 2]
```

```
(update! [0 1 2] 0 (fn [x] (+ x 1)))
```

```
=> [1 1 2]
```

```
(update! {} :a (fn [x] 5))
```

```
=> {:a 5}
```

```
(update! {:a 0} :b (fn [x] 5))
```

```
=> {:a 0 :b 5}
```

```
(update! {:a 0 :b 1} :a (fn [x] 5))
```

```
=> {:a 5 :b 1}
```

uuid

```
(uuid)
```

Generates a UUID.

```
(uuid )
```

```
=> "a7b3e2f6-045f-4fb0-97ea-3ccc33ff6c79"
```

val

```
(val e)
```

Returns the val of the map entry.

```
(val (find {:a 1 :b 2} :b))
```

```
=> 2
```

vals

```
(vals map)
```

Returns a collection of the map's values.

```
(vals {:a 1 :b 2 :c 3})
```

```
=> (1 2 3)
```

vary-meta

```
(vary-meta obj f & args)
```

Returns a copy of the object obj, with (apply f (meta obj) args) as its metadata.

vector

```
(vector & items)
```

Creates a new vector containing the items.

```
(vector )  
=> []  
  
(vector 1 2 3)  
=> [1 2 3]  
  
(vector 1 2 3 [:a :b])  
=> [1 2 3 [:a :b]]
```

vector?

```
(vector? obj)
```

Returns true if obj is a vector

```
(vector? (vector 1 2))  
=> true
```

```
(vector? [1 2])  
=> true
```

version

```
(version)
```

Returns the version.

```
(version )  
=> "0.9.9"
```

when

```
(when test & body)
```

Evaluates test. If logical true, evaluates body in an implicit do.

```
(when (== 1 1) true)  
=> true
```

when-not

```
(when-not test & body)
```

Evaluates test. If logical false, evaluates body in an implicit do.

```
(when-not (== 1 2) true)  
=> true
```

while

(while test & body)

Repeatedly executes body while test expression is true. Presumes some side-effect will cause test to become false/nil. Returns nil

```
(do
  (def a (atom 5))
  (while (pos? (deref a))
    (do (println (deref a)) (swap! a dec))))
5
4
3
2
1
=> nil
```

with-meta

(with-meta obj m)

Returns a copy of the object obj, with a map m as its metadata.

zero?

(zero? x)

Returns true if x zero else false

```
(zero? 0)
=> true
```

```
(zero? 2)
=> false
```

```
(zero? 0.0)
=> true
```

```
(zero? 0.0M)
=> true
```

zipmap

(zipmap keys vals)

Returns a map with the keys mapped to the corresponding vals.


```
(zipmap [:a :b :c :d :e] [1 2 3 4 5])  
=> {:a 1 :b 2 :c 3 :d 4 :e 5}
```

```
(zipmap [:a :b :c] [1 2 3 4 5])  
=> {:a 1 :b 2 :c 3}
```



Creates a hash map.

```
{:a 10 b: 20}  
=> {:a 10 b: 20}
```