

## PRODUCT CONFIGURATION

# Actuator LA12

Item No: J33558

Item Name: 121K00-11002408

Protection Class: IPX1

Load Type: Push/Pull

Load: Push 750 N / Pull 750 N

Self Lock: 750 N

Speed: 6,00 mm/s

Stroke length: 100 mm.  $\pm$  2 mm

Installation Dimension: 245 mm.  $\pm$  2 mm

Voltage: 24V

Colour: Black (RAL 9005)

End-Stop Type: Signal Switch

Feedback: HallPotentiometer 0.5 - 4.5V

Endstop Signals Output: Yes

Piston Rod Eye: With slot  $\varnothing$ 10,2

Piston Rod Eye with Bushing: No

Piston Rod Eye Material: Plastic

Back Fixture: With slot  $\varnothing$ 10,2

Back Fixture material: Plastic

Back Fixture Orientation: 0 degrees

Cable: Yes

Plug Type : OpenEnds

Cable Length : 2300 mm



Packing: Number LA12 on  $\frac{1}{2}$  pallet: 132 pcs.

Number LA12 on 1/1 pallet: 264 pcs.

### Terms of use

The user is responsible for determining the suitability of LINAK products for specific application. LINAK takes great care in providing accurate and up-to-date information on its products.

However, due to continuous development in order to improve its products, LINAK products are subject to frequent modifications and changes without prior notice. Therefore, LINAK cannot guarantee the correct and actual status of said information on its products. While LINAK uses its best efforts to fulfil orders, LINAK cannot, for the same reasons as mentioned above, guarantee the availability of any particular product. Therefore, LINAK reserves the right to discontinue the sale of any product displayed on its website or listed in its catalogues or other written material drawn up by LINAK.

All sales are subject to the Standard Terms of Sale and Delivery for LINAK. For a copy hereof, please contact LINAK.



WE IMPROVE YOUR LIFE

PLEASE SEE THE RELEVANT DATA SHEET OR USER MANUAL ON OUR WEBSITE [WWW.LINAK.COM](http://WWW.LINAK.COM)