REPUBLIC OF THE PHILIPPINES
DEPARTMENT OF TRANSPORTATION

**MARITIME INDUSTRY AUTHORITY**
**STCW OFFICE**

# GUIDE QUESTIONNAIRES

*for seafarers*

The Annual Publication of Database of Questionnaires is mandated in Republic Act 10635 or the Act Establishing the Maritime Industry Authority (MARINA) as the Single Maritime Administration Responsible for the Implementation and Enforcement of the 1978 International Convention on Standards of Training, Certification and Watchkeeping for Seafarers, 1978, as amended and International Agreements or Covenants related thereto and its Implementing Rules and Regulations.

These questions have been reviewed and validated by our Board of Examiners.

You may access these guide questionnaires with your smart gadgets anywhere and anytime at your convenience. Please consider the environment before printing.

Thank you.

**A Publication of the MARINA STCW Office**

# OIC NAVIGATIONAL WATCH

| Nr | Questions | Choice1 | Choice2 | Choice3 | Choice4 |
|---|---|---|---|---|---|
| 1 | What is the position obtained by applying only your vessel's course and speed to a known position? | Fix | Applied position | Dead-reckoning | Probable position |
| 2 | What is the position obtained by applying estimated current and wind to your vessel's course and speed? | Estimated position | Applied position | Dead-reckoning position | Assumed position |
| 3 | A barometric pressure reading of 29.92 inches of mercury is equivalent to _____. | 1012.35 millibars | 1015.25 millibars | 1010.35 millibars | 1013.25 millibars |
| 4 | Apparent altitude is sextant altitude corrected for _____. | inaccuracies in the reading and reference level | double-second difference | chronometer error and dip | difference in assumed latitude and actual latitude |
| 5 | Where can the data relating to the direction and velocity of rotary tidal currents be found? | Tide Tables | Nautical Almanac | Mariner's Guide | Tidal Current Tables |
| 6 | What is the speed of sound in the water? | 1.5 kilometers per second | 0.8 kilometer per second | 1.1 kilometers per second | 1.3 kilometers per second |
| 7 | What is the frequency of the low frequency pulse of the echo sounder? | 33.3 kHz | 24 kHz | 18 kHz | 27.5 kHz |
| 8 | On an echo sounder, which of these is used to draw a line on the paper to mark a specific time of an occurrence? | Range switch | Unt selector switch | Event marker | Timing device |
| 9 | When the water salinity increases, what happens to the speed of sound? | It increases. | It decreases. | It fluctuates. | It remains the same. |
| 10 | What is the nature of the beam transmitted by echo sounder? | Linear | Hyperbolic | Parabolic | Directional |
| 11 | Which of these is an echo sounder transducer type? | Magnetostriction | Diesel-electric | Piezo-hydraulic | Blue-diode |
| 12 | Which of these may cause false echoes in an echo sounder? | Schools of big fish | Bioluminescent microorganisms in the water | Protruding rocks from the seabed | Turbulence from the interaction of tidal streams with solid particles in suspension |
| 13 | What is a phenomenon in which the axis of an object wobbles when torque is applied? | Torque-induced precession | Wobble parallax | Equinoctial eccentricity | Gyroscopic inertia |

NOT FOR SALE

OIC NAVIGATIONAL WATCH

| | | | | | |
|---|---|---|---|---|---|
| 14 | What is an error in a gyrocompass caused by rapid changes in course, speed and latitude causing deviation before the gyro can adjust itself? | Parallax error | Stream error | Error of collimation | Rapid error |
| 15 | Which statement about the Flinders bar on a magnetic compass is correct? | It compensates for the error caused by the vertical component of the earth's magnetic field. | It reduces the deviation into half. | It allows the magnetic compass to move freely in the fluid. | It corrects the semi-quadrantal error at intercardinal headings. |
| 16 | Your vessel's heading is 330°pgc and 345°psc with a 2°E gyro error. If there is a variation of 10°W, what is the deviation on this heading? | 4°E | 7°W | 3°W | 0° |
| 17 | Your vessel's heading is 330°pgc and 345°psc with a 2°E gyro error. If there is a variation of 6°W, what is the deviation on this heading? | 7°W | 4°E | 3°W | 0° |
| 18 | Your vessel's heading is 330°pgc and 345°psc with a 2°E gyro error. If there is a variation of 13°W, what is the deviation on this heading? | 4°E | 7°W | 3°W | 0° |
| 19 | The shortest distance between any two points on earth defines a _____. | Great circle | Rhumb line | Mercator | Small cirle |
| 20 | What is a chart that covers a large area? | General chart | Small scale chart | Coastal chart | Large scale chart |
| 21 | Isogonic lines are lines on a chart indicating: | Magnitic dip | the Magnetic Latitude | Ponits of Zero variation | Points of equal variation |
| 22 | The revision of a chart is printed on what area of the chart? | Lower left center | Top center | part of the title | any clear area around the neat line |
| 23 | The visibility of lights indicated in the charts is in nautical miles for: | height of the observer's eye 15 feet above the water | Luminous range of the light | Geographic range of the light | Charted range of the light |
| 24 | A Mercator Chart is a: | Cylindrical projection | Polyconic projection | Simple conic projection | Rectangular projection |
| 25 | Which chart symbol indicates that the bottom is coral? | R | Sh | Cl | Co |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 26 | What publication contains ocean current information for voyage planning from Tokyo to San Francisco? | Guide to port entry | Coast pilot | Sailing Directions | World port index |
| 27 | What do you call the altitude after applying the Dip and index error? | Apparent altitude | Observed Altitude | Sextant altitude | Computed altitude |
| 28 | A phase correction is applied to observations of: | Stars | The Moon | Planets | The sun |
| 29 | When using GPS, you may expect your position to be accurate 95% of the time within a radius of _____ meters. | 50 m | 20 m | 10 m | 100 m |
| 30 | When navigating using DGPS, you may expect your position to be accurate to within a radius of _____ meters. | 10 m | 20 m | 50 m | 100 m |
| 31 | The angle between the grid and magnetic meridians is called grid variations or _____ . | Declination | Variation | Grivation | Deviation |
| 32 | The reaction of a gyro compas to an applied force is known as: | Precession | Gyroscopic inertia | Earth rate | Gravity effect |
| 33 | What navigational instrument used to indicate direction by measuring course and bearing? | Pelorus | Sextant | Azimuth circle | Compass |
| 34 | The compass rose on a nautical chart indicates both variation and _____ . | Annual rate of variation change | Deviation | precession | Compass error |
| 35 | The standard atmospheric pressure in millimeters of mercury is: | 23.25 | 29.92 | 960 | 760 |
| 36 | Your ship is steaming at night with the gyro-pilot engaged when you notice that the vessel's course is slowly changing to the right. What action should you take FIRST? | Switch to hand steering. | Notify the engineroom. | Call the Master. | Shift steering to the emergency steering station. |
| 37 | How many degrees north or south of the Tropic of Cancer is the Arctic Circle? | 23° 27’ South | 44° 06’ North | 44° 06’ South | 23° 27’ North |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 38 | Automatic device for steering a vessel by means of control signals received from a gyro compass is called _____. | gyropilot | gyro repeater | automatic pilot | gyroscopic steering |
| 39 | What is the length of a nautical mile? | 5,280 meters | 1,760 yards | 6,076 feet | 1,850 meters |
| 40 | The interval between the sun's upper limb being in the horizon and its center being 12° below is called: | Nautical twilight | Astronomical twilight | Observational twilight | Civil twilight |
| 41 | The dividing meridian between zone descriptions +4 and +5 is _____. | 75° 00' E | 60° 00' E | 67° 30' W | 60° 30' W |
| 42 | Physical checks of gyro, azimuth circle and pelorus include the following, EXCEPT: | align peloruses with fore-and-aft line of the ship | synchronize gyro repeaters with master gyro | ensure azimuth circle and peloruses are in good condition | align the compass north to the fore and aft line of the ship |
| 43 | The bending of a wave as it passes an obstruction is called _____. | persistence | refraction | diffraction | attenuation |
| 44 | While voyage planning and navigating, a mariner must refer to both texts and tables. Tables includes the following EXCEPT: | Sailing Directions | Light Lists | Sight Reduction | Almanac |
| 45 | In the IALA Buoyage System, what is the color of an East Cardinal Mark? | Black band with above and below yellow band | Black band above yellow band | Black band below yellow band | Black band above and below yellow band |
| 46 | Who is responsible for the voyage plan? | The navigation officer | The owner | The person who has done the planning | The Master |
| 47 | When relieving the helm, the new helmsman should know the _____. | Variation | Gyro error | Course per magnetic steering compass | Maximum rudder angle previously used |
| 48 | Out of the 57 navigational stars tabulated in the Nautical Almanac, how many are of the first magnitude? | 23 | 21 | 6 | 19 |
| 49 | Out of the 57 navigational stars tabulated in the Nautical Almanac, how many are of the second magnitude? | 38 | 19 | 25 | 48 |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 50 | Which statement is TRUE concerning "night effect" and the reception of radio signals? | During "night effect", polarization is at a minimum | "Night effect" is caused by rapid changes in the ionosphere | "Night effect" is most prevalent late at night | "Night effect" is caused by all of the polarized ground waves being vertical |
| 51 | What is a common occurrence when a vessel is running into a shallow water? | "squat" will cause a decrease in bottom clearance and an increase in draft | "squat" will cause an increase in bottom clearance and an increase in draft | "squat" will cause an increase in bottom clearance and a decrease in draft | "squat" will cause a decrease in bottom clearance and a decrease in draft |
| 52 | Polaris is always within how many degrees of the north pole? | 0.1 degree | 0.2 degree | 1 degree | 0.5 degree |
| 53 | As a general rule, a ULCC should not have a speed in any direction greater than what speed when touching berth? | 0.10 knots | 0.20 knots | 0.25 knots | 0.15 knots |
| 54 | A vessel is following a range to keep herself within a narrow channel. The chart indicates the range to be 001deg. The vessel is "on range" when she is steering a course of: | 359deg. T | 000deg. T | 001deg. T | 180deg. T |
| 55 | The standard time meridian for zone description -1 is: | 15deg. E | 7 1/2deg. W | 0deg. | 7 1/2deg. E |
| 56 | The mean distance between the earth and the sun is: | 1 parsec | 4.3 light years | 1 astronomical unit ( AU ) | 1 celestial unit |
| 57 | One complete turn of the drum of the sextant moves the index arm along the arc is equal to: | 1 degree | 1/10th of a degree | 1 minute of arc | 1 second of arc |
| 58 | Out of the 57 navigational stars tabulated in the Nautical Almanac, how many are of the first magnitude? | 6 | 19 | 21 | 23 |
| 59 | Out of the 57 navigational stars tabulated in the Nautical Almanac, how many are of the second magnitude? | 38 | 19 | 25 | 48 |
| 60 | Polaris is always within how many degrees of the north pole? | 0.2 degree | 0.1 degree | 1 degree | 0.5 degree |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 61 | As a general rule, a ULCC should not have a speed in any direction greater than what speed when touching berth? | 0.15 knots | 0.25 knots | 0.20 knots | 0.10 knots |
| 62 | A vessel is following a range to keep herself within a narrow channel. The chart indicates the range to be 001deg. The vessel is "on range" when she is steering a course of: | 001deg. T | 359deg. T | 000deg. T | 180deg. T |
| 63 | The standard time meridian for zone description -1 is: | 0deg. | 7 1/2deg. E | 15deg. E | 7 1/2deg. W |
| 64 | The mean distance between the earth and the sun is: | 1 astronomical unit ( AU ) | 1 parsec | 1 celestial unit | 4.3 light years |
| 65 | One complete turn of the drum of the sextant moves the index arm along the arc is equal to: | 1 minute of arc | 1 degree | 1 second of arc | 1/10th of a degree |
| 66 | The sun is the central body of the solar system. It moves in the direction of Vega at: | 12 miles per second | 1,000,000 miles per second | 1,000 miles per second | 100 miles per second |
| 67 | A harbor chart could have a scale of: | not more than 1:25,000 | 1:35,000 | not less than 1:500,000 | 1:150,000 |
| 68 | A sailing chart could have a scale of: | 1:700,000 | not more than 1:25,000 | 1:35,000 | 1:100,000 |
| 69 | A general chart could have a scale of: | 1:1,000,000 | 1:200,000 | 1:50,000 | not more than 1:25,000 |
| 70 | The GPS provides 95% accuracy within a range of: | 100 meters | 300 meters | 10 meters | 150 meters |
| 71 | In Meteorology, the unit of atmospheric pressure used in synoptic charts is the hectoPascal. One hectoPascal (hPa) is equal to: | 100 millibars | 10 Pascals | 1000 millibars | 1 millibar |
| 72 | The standard sea level pressure of the atmosphere is: | 1013.25 millibars of mercury | 1013.52 millibars of mercury | 1012.35 millibars of mercury | 1012.45 millibars of mercury |
| 73 | The observer is at Equator and the celestial body is at the First Point of Capricorn, the bearing of the celestial body during meridian transit is: | 20 degrees South | 360 degrees | 180 degrees | 15 degrees North |

| | | | | | |
|---|---|---|---|---|---|
| 74 | A one knot current has approximately the same effect on a given surface area as a: | 10 knot wind | 15 knot wind | 20 knot wind | 30- knot wind |
| 75 | What is the circumference of the earth at the equator of the equatorial radius is taken at 3,444 nautical miles? | 21,739.29 miles | 22,439.29 miles | 22,639.29 miles | 21,639.29 miles |
| 76 | What is the latitude of a place where the sun is exactly at the zenith of the observer at Local Apparent Noon (LAN) of December 22? | 23deg. 27' S | Tropic of Cancer | 23deg. 27' N | at the equator |
| 77 | What is the latitude of a place where the sun is exactly at the zenith of the observer at Local Apparent Noon (LAN) of September 22 or 23? | 23deg. 27' S | South Pole | 0deg. Latitude | 23deg. 27' N |
| 78 | Determine the latitude of a place where the sun is exactly at the zenith of the observer at Local Apparent Noon (LAN) of September 22 or 23. | 23deg. 27' N | 0deg. Latitude | 23deg. 27' S | South Pole |
| 79 | What is the latitude of a place where the sun is exactly at the zenith of the observer at Local Apparent Noon (LAN) of June 21? | 23deg. 27' S | 0deg. | 90deg. | 23deg. 27' N |
| 80 | The arctic circle is how many degrees north or south of the tropic of cancer? | 44deg. 06' North | 44deg. 06' South | 23deg. 27' South | 23deg. 27' North |
| 81 | When the body is on the rational horizon, what is its zenith distance? | 270deg. | 000deg. | 180deg. | 090deg. |
| 82 | A vessel is following a range to keep herself within a narrow channel. The chart indicates the range to be 243deg. The vessel is "on range" when she is steering a course of: | 243deg. T | 063deg. T | 270deg. T | 234deg. T |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 83 | What is the geographical latitude of a body whose declination is 23deg. 27' N? | 27deg. 33' N | 23deg. 27' S | 23deg. 27' N | 66deg. 33' S |
| 84 | What is the highest sustained surface wind speed of a Tropical Storm? | 34 to 63 knots | 30 to 55 knots | 28 to 50 knots | more than 60 knots |
| 85 | The orbital speed of the earth is: | 18.5 nautical miles per second | 29.8 nautical miles per second | 16.1 nautical miles per second | 900 nautical miles per second |
| 86 | Heeling error is defined as the change of deviation for a heel of: | 1deg. while the vessel is on a compass heading of 000deg. | 2deg. while the vessel is on an intercardinal heading | 2deg. and is constant on all headings | 1deg. while the vessel is on a compass heading of 180deg. |
| 87 | Due to the revolution of the earth around the sun, a sidereal day is shorter than a solar day by about: | 3 mins and 26 secs | 3 mins and 06 secs | 3 mins and 36 secs | 3 mins and 56 secs |
| 88 | Tropical Depression has a maximum sustained surface wind speed of: | 33 knots | 28 knots | 30 knots | 35 knots |
| 89 | The visible diameter of the sun as seen from the Earth during perihelion is: | 42.0' | 10.0' | 32.6' | 51.5' |
| 90 | Polar distance can never be more than: | 180deg. from either poles | 90deg. N or S of the equator | 45deg. N or S of the equator | 360deg. only |
| 91 | Internationally used value of the atmospheric pressure in metric system. | 29.92 inches | 1,013 millibars | 760 mm column of mercury | 14.7 lbs per square inch |
| 92 | When the index mirror and the horizon mirror of the sextant are parallel, the sextant should read: | 0deg. | 60deg. | 90deg. | 120deg. |
| 93 | The apparent wind can be zero when the true wind is from: | ahead and equal to twice the ship's speed | astern and equal to twice the ship's speed | ahead and equal to the ship's speed | astern and equal to the ship's speed |
| 94 | You are proceeding along the right bank of a narrow channel aboard a right-handed single-screw vessel. The vessel starts to sheer due to bank suction/cushion effect. You should: | increase speed and put the rudder right full | back full with rudder amidships | decrease speed and put the rudder right full | stop engines and put the rudder left full |
| 95 | The effect we call "squat" occurs. Why? | Decreased velocity and increased water pressure around the ship's hull | The bow and stern wave make the ship sink lower in the water | Increased effect of gravity due to closeness of the seabed | Increased velocity and decreased water pressure around the ship's hull |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 96 | You are the Master of a single-screw vessel. You are docking at a port which has no tugs available. You decide to drop the offshore anchor to help in docking. The amount of chain you should pay out is: | 1 1/2 to 2 times the depth of the water | 5 to 7 times the depth of the water | equal to the depth of the water | you should NEVER use the anchor to help in docking |
| 97 | The squat effect of a large vessel travelling at high speed will caused an increased of her draft by: | in excess of one meters by mean | in excess of two meters by mean | in excess of two meters by foreward | in excess of two meters by astern |
| 98 | The rules concerning lights shall be complied with in all weathers from sunset to sunrise. The lights: | shall be displayed in restricted visibility during daylight hours | shall be set at low power when used during daylight hours | need not be displayed when no other vessels are in the area | need not be displayed by unmanned vessels |
| 99 | A coastal chart could have a scale of: | not more than 1:25,000 | 1:500,000 | 1:100,000 | 1:35,000 |
| 100 | Prior to getting underway in fresh or brackish water, the Master must: | log the density of the water | take on fresh water ballast | secure all overboard discharges | clean the sides with fresh water |
| 101 | If your vessel is dragging her anchor in a strong wind, you should: | dropped another anchor | increase the scope of anchor cable | put over a stern anchor | shorten the scope of anchor cable |
| 102 | The actual speed of the vessel over the surface of the earth at any given time. | speed over the ground | speed of intention | speed of advance | speed on the water |
| 103 | How will you define "squat"? | The speed of your ship will increase | Increase in draft to the point on your ship which is closest to the bottom | Decrease in draft of your ship | Squat is not relevant on your ship |
| 104 | From those listed, which would be the preferred method of position fixing for greatest accuracy and certainty of position? | Taking a radar range and visual bearing | Taking several radar bearings | Taking a radar range and radar bearing | taking several radar ranges |
| 105 | After sailing for several minutes (making 10 knots through the water) and in constant monitoring of your radar screen, you noticed that a contact has remained in the same position relative to yours, what could be the possible conclusion of the scenario? | the radar is showing false echoes and is probably defective | the contact is on the same course and speed as your vessel | the contact is dead in the water | the contact is on a reciprocal course at the same speed as your vessel |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 106 | The best time to work a boat into a slip is: | at slack water | with the current setting against you | when the wind is against you | with a cross current |
| 107 | A spinning wheel which is free to turn about two axis that are at right angles to each other and the spinning axis is known as a _____. | simple gyroscope | complex gyroscope | closed gyroscope | free gyroscope |
| 108 | In the time diagram , the angle at the pole between the hour circle of the First point of Aries to the meridian of the observer at Greenwich is called: | GHA of Aries | SHA of Aries | Sidereal Hour Angle | Right Ascension |
| 109 | Magnets in the binnacles of magnetic compasses are used to reduce the effect of _____. | variation | deviation | all of the choices | local attraction |
| 110 | Stage of tropical cyclone with decrease of pressure and no increase of wind force. | mature stage | decaying stage | immature stage | depression stage |
| 111 | The process of turning a gravity controlled gryroscope into a compass is called_____. | precession | damping | tilting | torque |
| 112 | Two navigational hazards are located near to each other, but each is marked by an individual cardinal buoyage system. The buoys of one cardinal system may be identified from the other system by _____. | one system using horizontal bands while the other system uses vertical stripes | the differing light colors | the difference in the periods of the light | one system having odd numbers while the other system has even numbers |
| 113 | Under the IALA cardinal system, a mark with quick white light showing 3 flashes every 10 seconds indicates that the safest water in the area is on the _____. | east side of the mark | west side of the mark | north side of the mark | south side of the mark |
| 114 | Which statement is NOT correct regarding the gyro compass? | its error is not affected by deviation and variation | its accuracy remains the same in all latitudes | it is electrically and mechanically operated | it seeks the true north |
| 115 | Which term refers to the direction a current is flowing? | Set | Drift | Stand | Vector direction |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 116 | Generally speaking, a ship steaming across the North Pacific from Japan to Seattle is likely to experience _____. | adverse currents for practically the entire crossing | variable currents having no significant effect on the total steaming time | favorable currents for practically the entire crossing | favorable currents in the summer months and adverse currents in the winter months |
| 117 | How many high waters usually occur each day on the East Coast of the United States? | Two | One | Three | Four |
| 118 | How many navigational planets are tabulated in the Almanac? | 5 | 9 | 4 | 2 |
| 119 | In a river subject to tidal currents, the best time to dock a ship without the assistance of tugs is _____. | at slack water | when there is a following current | at high water | at flood tide |
| 120 | The Flinders bar and the quadrantal spheres should be tested for permanent magnetism at what interval? | They are not subject to permanent magnetism | Annually | Semi annually | Every five years |
| 121 | The force that will cause the axis of a spinning. | Precession | Friction | Torque | Rigidity |
| 122 | The height of tide is the _____. | depth of water at a specific time due to tidal effect | difference between the depth of the water at high tide and the depth of the water at low tide | difference between the depth of the water and the high water tidal level | difference between the depth of the water and the areas tidal datum |
| 123 | The point where the vertical rise or fall of tide has stopped is referred to as _____. | the stand of the tide | the reverse of the tide | the rip tide | slack water |
| 124 | What does the term tide refer to? | Mixing tendency of the water | Horizontal movement of the water | Vertical movement of the water | Salinity content of the water |
| 125 | What is the category of a chart with a scale of 1:80,000? | coastal chart | sailing chart | general chart | harbor chart |
| 126 | What is the definition of height of tide? | The vertical difference between the heights of low and high water | The vertical distance from the tidal datum to the level of the water at any time | The vertical difference between a datum plane and the ocean bottom | The vertical distance from the surface of the water to the ocean floor |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 127 | When the moon is new or full, which type of tides occur? | Spring | Neap | Diurnal | Apogean |
| 128 | When there are small differences between the heights of two successive high tides or two low tides, in a tidal day, the tides are called _____. | solar | semidiurnal | diurnal | mixed |
| 129 | Where will you find the information about the duration of slack water? | Tidal Current Tables | Tide Tables | Sailing Directions | American Practical Navigator |
| 130 | Which information must automatic identification systems (AIS) automatically provide to appropriately equipped shore stations, vessels and aircraft? | ETA | Draught | Destination | Vessels course |
| 131 | A Binnacle is a stand used for housing a _____ so that they may be used conveniently? | compass | radio direction finder | steering wheel | radar |
| 132 | A flywheel in a universal mounting where the axis is free to point in any direction is the_____. | gyrosphere | phantom wheel | gyroscope | gimbals |
| 133 | A free gyroscope is said to have three degres of freedom . From those listed which is NOT one of these? | Spin axis. | Latitude axis. | Altitude axis | Azimuth axis. |
| 134 | A GPS satellite transmits a signal thru the first carrier on _____. | 1755.42 mHz | 1575.42 mHz | 1572.75 mHz | 1574.75 mHz |
| 135 | A GPS satellite transmits a signal thru the second carrier on _____. | 1227.60 mHz | 1272.60 mHz | 1722.60 mHz | 1727.60 mHz |
| 136 | A great circle track provides the maximum saving in distance on _____. | southerly courses in high latitudes | easterly courses in high latitudes | westerly courses in low latitudes | easterly courses in low latitudes that cross the equator |
| 137 | A gyro compass error in which damping is accompanied by offsetting the point of application of the force from a mercury ballistic is known as_____. | tangent latitude error | quadrantal error | damping error | ballistic error |
| 138 | A gyro compass has a feature that decreases with latitude being maximum at | precession | dip | directive force | attractive force |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| | the equator and zero at the geographical poles known as ____. | | | | |
| 139 | A hurricane has recurved to the northeast and its forward speed is 20 knots. Your MODU is located 600 miles northeast of the hurricane s center. How long will it take for the hurricane center to reach your position if it holds its present course and speed? | 30 hours | 10 hours | 50 hours | 80 hours |
| 140 | A knowledge regarding own ship various methods available and how to change over to secondary from primary methods is___. | steering and maneuvering | piloting and conning | steering and conning | steering and piloting |
| 141 | A line of position from a celestial observation is a segment of a _____. | circle of equal altitude | parallel of declination | parallel of altitude | vertical circle |
| 142 | A position adjusted for the estimated effects of leeway tidal stream currents and surface drift. | Set position | Estimated position | DR position | Fix position |
| 143 | A running fix is a position obtained by _____? | taking multiple lines of position from different objects at different times | a combination of a line position from one object and a range and distance from another object at different times | taking two lines of position from different points of one object at different times | taking multiple lines of position from one object at different times and advancing them to a common time |
| 144 | A sail plan including the vessel s itinerary name number and persons aboard should be filed with _____. | a responsible person | the FAA | U.S. Customs | the Coast Guard |
| 145 | A sextant having an index error that is on the arc has a _____. | positive correction | dip error | negative correction | semidiameter error |
| 146 | A ship has a _____ magnetism. | sub-permanent | permanent | induced | sub-induced |

| | | | | | |
|---|---|---|---|---|---|
| 147 | A single line of position combined with a dead-reckoning position results in a(n)_____ | estimated position | fix | running fix | assumed position |

| | | | | | |
|---|---|---|---|---|---|
| 148 | A sling psychrometer is a(n) _____. | instrument used in celestial navigation | type of cargo gear | instrument used to measure relative humidity | instrument used to measure specific gravity |
| 149 | A star is observed at lower transit. The line of position derived from this sight is _____. | a latitude line | of no special significance | on the prime vertical | a longitude line |
| 150 | A swift current occurring in a narrow passage connecting two large bodies of water which is produced by the continuously changing difference in height of tide at the two ends of the passage is called a _____. | rotary current | harmonic current | rectilinear current | hydraulic current |
| 151 | A tide is called diurnal when _____. | the high tide and low tide are exactly six hours apart | the high tide is higher and the low tide is lower than usual | only one high and one low water occur during a lunar day | two high tides occur during a lunar day |
| 152 | A tropical storm is a tropical cyclone that generates winds of _____. | between 34 and 63 knots | None of the stated options | over 63 knots | between 20 and 33 knots |
| 153 | A tropical storm is building strength some distance from your MODU. Waves are coming from the east with periods increasing from 5 seconds to 15 seconds. The swell is from the east. Where was the storm when these new swells were generated? | To the west of you | To the east of you | To the north of you | To the south of you |
| 154 | A vertically-striped buoy may be _____. | lighted with a white light | lighted with a red light | striped black and green | striped black and yellow |
| 155 | A yellow buoy may mark a(n) _____. | middle ground | wreck | anchorage area | shoal area |
| 156 | Advection fog a common occurrence on the Great Lakes forms when _____. | relatively warm air flows over cooler water | frigid arctic air moves across the lakes and becomes saturated | cool air contacts warm river currents | air comes in contact with a rapidly cooling land surface |
| 157 | An automatic identification system (AIS) transponder transmits and receives information broadcasts on: | UHF L-band | 10 cm S-band radar | 3 cm X-band radar | VHF maritime band |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 158 | An electronic depth finder operates on the principle that _____. | sound waves travel at a constant speed through water | radio signals reflect from a solid surface | radar signals travel at a constant speed through water | pressure increases with depth |
| 159 | The most probable position of the object of a search at any given time is the _____. | incident position | dead-reckoning position | reported position | datum position |
| 160 | You are on watch and the pilot has just anchored the vessel. The next thing that you should do after the anchor has been let go is to _____. | plot the vessels position on the chart | stop the engines | escort the pilot to the accommodation ladder | make a round of the weather decks |
| 161 | You are on watch at night in clear visibility and the vessel has just been anchored. The first thing that you should do after the anchor has been let go is to _____. | stop the engines | take bearings to obtain ships position | lower the accommodation ladder and illuminate it | turn off the running lights and turn on the anchor lights |
| 162 | The distance that a vessel travels from the time that the order to put engines full astern until the vessel is dead in the water is known as _____. | head reach | advance | surge | transfer |
| 163 | Which statement, concerning offshore supply vessel operations, correctly defines the length of a voyage? | The distance from the point of departure to the vessels first stop | The distance from the point of departure to the most distant point offshore | The total distance from the port of departure to the port of arrival, not including stops at offshore points | The shortest measurable distance from the port of departure to the port of arrival |
| 164 | The owner or Master of a towing vessel shall ensure that each person that directs and controls the movement of the vessel can accurately fix the vessels position using all of the following EXCEPT _____. | buoys alone | installed navigational equipment | all available aids to navigation | depths soundings and hydrographic contour lines |

| | | | | | |
|---|---|---|---|---|---|
| 165 | When the faces of the sextant shade glasses and mirrors are not parallel, the error is called | centering error | prismatic error | index error | graduation error |
| 166 | One of the two stars pointing to Polaris in the Ursa Major is the: | Dubhe | Alioth | Alphecca | Kochab |

OIC NAVIGATIONAL WATCH

| | | | | | |
|---|---|---|---|---|---|
| 167 | The horizontal direction of a point on the celestial sphere is called _____. | amplitude | prime vertical | zenith distance | azimuth angle |
| 168 | The tabulation data in the Nautical Almanac is for: | 3 days | 4 days | 2 days | 1 day |
| 169 | Apparent altitude is sextant altitude corrected for _____. | double-second difference | chronometer error and dip | difference in assumed latitude and actual latitude | inaccuracies in the reading and reference level |
| 170 | The opposite of the elevated pole is the _____. | depressed pole | centripetal pole | circumpolar pole | nadir |
| 171 | What is the difference between the observed altitude and the computed altitude? | Position line | Refraction | Dip | Intercept |
| 172 | This is the tabulated interpolated for increments of latitude, declination or hour angle. | Computed altitude | Apparent altitude | True altitude | Observed altitude |
| 173 | In the celestial equator system of coordinates of what is equivalent to the co-latitude of the Earth system of coordinates? | Declination | Co-altitude | Zenith distance | Polar distance |
| 174 | Vertical circle with passes through the east and west point of the horizon. | prime vertical circle | hour circle | vertical circle | principal vertical circle |
| 175 | Index error of a sextant is primarily caused by _____. | improperly correcting the errors in the sextant | the horizon glass not being parallel to the horizon mirror | human error in taking the celestial observation | the horizon glass not being parallel to the index mirror |
| 176 | Error in an instrument due to inaccurate pivoting of a moving part, as the index arm of a marine sextant. | Centering error | Index error | Graduation error | Prismatic error |
| 177 | In general, the most effective period for observing stars and planets occurs during the darker limit of ___. | sunset | astronomical twilight | nautical twilight | civil twilight |
| 178 | The most reliable form of navigational system in the high seas, is _____. | Nav satellite system | Celestial Navigation | Loran-C | Omega |
| 179 | A sextant having an index error that is on the arc has a _____. | negative correction | positive correction | dip error | semidiameter error |
| 180 | The index error is determined by adjusting the _____. | horizon glass | sextant frame | index mirror | micrometer drum |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 181 | The optical principle of a marine sextant is , when a ray of light is reflected from a plane surface, the angle of reflection is equal to the: | Angle of incidence | Angle of deflection | Angle of refraction | Angle of interaction |
| 182 | There are seven sources of errors in a marine sextant . Of the four errors listed, which one is adjustable? | Prismatic Error | Graduation Error | Centering Error | Error of Collimation |
| 183 | What sextant correction corrects the apparent altitude to the equivalent readings at the center of the Earth? | Parallax | Semi-Diameter | Augmentation | Phase |
| 184 | Zenith is the point on the _____vertically overhead of the observer. | celestial meridian | celestial equator | celestial pole | celestial sphere |
| 185 | At what season is the sun farthest from the Earth at northern hemisphere? | Summer | Winter | Fall | Spring |
| 186 | In the celestial equator system of coordinates of what is equivalent to the co-latitude of the Earth system of coordinates? | Declination | Zenith distance | Polar distance | Co-altitude |
| 187 | In the horizon system of coordinates what is equivalent to the meridian angle of the celestial equator system? | Azimuth angle | Zenith distance | Co-latitude | Altitude |
| 188 | In the time diagram , the angle at the pole between the hour circle of the First point of Aries to the meridian of the observer at Greenwich is called: | SHA of Aries | Right Ascension | GHA of Aries | Sidereal Hour Angle |
| 189 | In what order should the following sextant adjustment be made: I Make telescope parallel to frame of sextant II See horizon glass perpendicular to frame of sextant III Make index mirror and horizon glass parallel to frame of sextant when index arm is set to zero IV Set index mirror perpendicular to frame of sextant | I, II, III, IV | I, IV, II, III | III, II, IV, I | IV, II, III, I |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 190 | In the daily pages of the almanac, the un-shaded circle in the lower right hand corner of the almanac means; | Full moon | New moon | First quarter | Last quarter |
| 191 | One of the two stars in the Ursa Minor pointing to Polaris is: | Alioth | Alphecca | Dubhe | Kochab |
| 192 | Astronomical refraction causes a celestial body to appear _____. | higher than its actual position | to the left of its position in the Northern Hemisphere and to the right in the Southern Hemisphere | to the right of its position in the Northern Hemisphere and to the left in the Southern Hemisphere | lower than its actual position |
| 193 | At evening stars, the last stars that should be observed are those with an azimuth in what quadrant? | Eastern | Southern | Western | Northern |
| 194 | In which voyage, between two points, is the rhumbline distance NOT approximately the same as the great circle distance? | The two points are in high latitudes in the same hemisphere | The two points are in low latitudes in the same hemisphere | The two points is near the equator, but in different hemisphere | One point is near the equator, one point is in a high latitude and both are near the 180th meridian |
| 195 | What is a position obtained by applying estimated current and wind to your vessels course and speed? | Dead-reckoning position | Assumed position | Estimated positon | Estimated positon |

| | | | | | |
|---|---|---|---|---|---|
| 196 | Where can the data relating to the direction and velocity of rotary tidal currents be found? | Mariners Guide | Tide Tables | Nautical Almanac | Tidal Current Tables |
| 197 | What is a phenomenon in which the axis of an object wobbles when torque is applied? | Torque-induced precession | Wobble parallax | Equinoctial eccentricity | Gyroscopic inertia |
| 198 | When you are steering on a pair of range lights and find the upper light is above the lower light you should_____. | come right | continue on the present course | come left | wait until the lights are no longer in a vertical line |
| 199 | A single line of position combined with a dead-reckoning position results in a(n)_____ | estimated position | fix | running fix | assumed position |

| | | | | | |
|---|---|---|---|---|---|
| 200 | When using a buoy as aid to navigation which of the following should be considered? | The buoy should be considered to always be in the charted location | If the light is flashing, the buoy should be considered to be in the charted location | The buoy should be considered to be in the charted position if it has been freshly surveyed | The buoy may not be in the charted position |
| 201 | Why is the height of the tide in the Tide Table essential in determining the true depth of water at any time than shown in the chart? | The height of the tide may be checked readily by taking soundings to be sure of the keel clearance from the bottom | If the height of the tide is equal to the charted depth is an alarm that the ship may touch bottom | The depth of the water at any time is obtained by adding the height of the tide to the charted depth | The depth of the water at any time is obtained by subtracting the height of the tide if it is negative |
| 202 | The nominal range of a light may be accurately defined as a maximum distance at which a light may be seen: | under existing visibility conditions | with 10 miles visibility | with 15 miles visibility | under perfect visibility |
| 203 | In mercator sailing, distance is obtained by multiplying _____. | DMP and Cosine Course | Dlat and Cosine Course | Dlat and Sine Course | Dlat and Secant Course |
| 204 | The direction of tidal current in the open ocean is _____. | rotary | non-rotary | horizontal | vertical |
| 205 | Which is used to ensure that a ship remains within a safe area or is not approaching a danger? | geographical range | clearing mark | parallel indexing | head mark |
| 206 | A position adjusted for the estimated effects of leeway, tidal stream currents and surface drift. | Estimated position | Set position | Fix position | DR position |

| | | | | | |
|---|---|---|---|---|---|
| 207 | The visibility of the lights indicated in the charts is in nautical miles for: | geographic range of the light | luminous of light | charted range of the light | |
| 208 | A running fix is a position obtained by _____? | taking multiple lines of position from one object at different times and advancing them to a common time | taking two lines of position from different points of one object at different times | taking multiple lines of position from different objects at different times | a combination of a line position from one object and a range and distance from another object at different times |
| 209 | You plot a fix in three lines of position and find they intersect in a triangle. The actual position of the | is outside of the triangle | maybe anywhere in the triangle | may be inside or outside of the triangle | is the geometric center of the triangle |

OIC NAVIGATIONAL WATCH

| | | | | | |
|---|---|---|---|---|---|
| | vessel _____ . | | | | |
| 210 | For the deepest water when negotiationg a bend in a river, you should always navigate your vessel_____. | toward the outside bend of the river | toward the inside bend of the river | toward the center of the river just before the bend, then change course for the rivers center after the bend | toward inside or outside bend of the river |
| 211 | The water is said to be a slack when there is_____. | no vertical motion of the water | a weak ebb or flood current | no horizontal motion of the water | no horizontal and vertical motion of the water |
| 212 | Data relating to the direction and velocity of rotary tidal currents can be found in the _____. | Tidal Current Tables | Tide Tables | Nautical Almanac | Mariners Guide |
| 213 | On an Atlantic Ocean voyage from New York to Durban, South Africa, you should expect the Agulhas Current to present a strong _____. | onshore set | fair or following current | head current | offshore set |
| 214 | Under the IALA-A Buoyage System, a buoy indicating the preferred channel is to port would have _____. | horizontal bands | a pillar shape | an even number | an odd number |
| 215 | IN REGION A of the IALA Buoyage System, when entering from seaward, the starboard side of a channel would be marked by a _____. | green can buoy | red can buoy | red conical buoy | green conical buoy |
| 216 | A vertically-striped buoy may be _____. | lighted with a white light | lighted with a red light | striped black and green | striped black and yellow |
| 217 | At 0000 you fix your position and plot a new DR track line. At 0200 you again fix your position and it is 0.5 mile east of your DR. Which statement is TRUE? | You must increase speed to compensate for the current. | The drift is 0.25 knot. | The current cannot be determined. | The current is westerly at 0.5 knot. |
| 218 | Which statement about a gnomonic chart is CORRECT? | Meridians appear as curved lines converging toward the nearer pole. | A rhumbline appears as a straight line | Distance is measured at the mid-latitude of the track line | Parallels, except the equator, appear as curved lines. |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 219 | Chart legends printed in capital letters show that the associated landmark is _____. | conspicuous | a radio transmitter | a government facility or station | inconspicuous |
| 220 | A chart with a scale of 1:80,000 would fall into the category of a _____. | sailing chart | harbor chart | coastal chart | general chart |
| 221 | A sailing chart could have a scale of _____. | 1:700,000 | 1:100,000 | not more than 1:25,000 | 1:35,000 |
| 222 | Which nautical charts are intended for coastwise navigation outside of outlying reefs and shoals? | Approach charts | Sailing charts | Coast charts | General charts |
| 223 | What is the area wherein the dredged materials are thrown or dumped? | spoil ground | wrecked ground | dumping ground | hazardous ground |
| 224 | Magnets in the binnacles of magnetic compasses are used to reduce the effect of _____. | all of the choices | deviation | variation | local attraction |
| 225 | The datum from which the predicted heights of tides are reckoned in the tide tables is ____. | the same as that used for the charts of the locality | the highest possible level | given in table three of the tide tables | mean low water |
| 226 | Under the IALA Buoyage Systems, safe water marks may show a _____. | composite group-flashing, F1 (2+1), red light | composite group-flashing, F1 (2+1), green light | quick-flashing, Q (9)15s, white light | white Morse (A) light |
| 227 | One of these countries are marked with IALA-B buoyage system: | Brazil | Norway | Tanzania | New Zealand |
| 228 | A yellow buoy may mark a(n) _____. | shoal area | middle ground | anchorage area | wreck |

| | | | | | |
|---|---|---|---|---|---|
| 229 | In the IALA Buoyage System, what is the color of an East Cardinal Mark? | Black band above and below yellow band | Black band with above and below yellow band | Black band above yellow band | Black band below yellow band |
| 230 | In the IALA Buoyage System, buoys with alternating red and green horizontal bands are used to indicate _____. | spoil grounds | fishing areas | isolated danger | the preferred channel |
| 231 | Which information does the outer ring of a compass rose on a nautical chart provide? | True direction | Magnetic direction | Annual rate of variation change | Variation |
| 232 | You are planning a voyage from San Francisco to Japan. Which publication | Sailing Directions ( Enroute ) | Coast Pilot | Sailing Directions ( Planning Guide ) | World Port Index |

| | | | | | |
|---|---|---|---|---|---|
| | contains information on the ocean routes? | | | | |
| 233 | On a nautical chart, the inner ring of a compass rose indicates _____. | magnetic direction | true direction | compass error | deviation |
| 234 | On an admiralty chart, a line joining places of equal variation is known as an Isogonic line. On special charts, lines of equal change of variation may be printed. This is known as ___. | Aclinic lines | Isoclinic lines | Isallogonic lines | Isodynamic lines |
| 235 | You are required to enter a lock on your voyage. Information on the lock regulations, signals, and radio communications can be found in _____. | Corps of Engineers Information Bulletin | Bowditch | the publication Key to the Locks | Coast Pilot |
| 236 | The DGPS provides accuracy within a range of _____. | 10 meters | 150 meters | 100 meters | 300 meters |
| 237 | Which statement concerning GPS is TRUE? | Two position lines are used to give a 2D fix | It cannot be used in all parts of the world | There are 12 functioning GPS satellites at present. | It may be suspended without warning |
| 238 | The accuracy for civilian GPS users can be significantly improve by using: | Tri band GPS | Differential GPS | Integral GPS | Navsat GPS |
| 239 | It is a space-based navigation system providing global 24 hours a day, all weather access to precise position, velocity and time information to a properly equipped user. Its operating altitude in 3 orbital planes is at 19,000 kms. altitude. | Global Navigation Satellite System (GLONASS) | Global Positioning Satellites (GPS) | Differential Global Positioning System (DGPS) | NAVSTAR |
| 240 | Which theoretical minimum number of measurements from satellites does a GPS receiver need in order to provide an exact three-dimensional position? | Five | Three | Four | Two |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 241 | When using GPS, how many position lines are required for a 3D (dimensional) fix that takes into account altitude? | 1 | 4 | 2 | 3 |
| 242 | A vessel may use any sound or light signals to attract the attention of another vessel as long as _____. | the signal cannot be mistaken for a signal authorized by the Rules | red and green lights are not used | the vessel signals such intentions over the radiotelephone | it is one of those listed under Annex IV of the Collision Regulations |
| 243 | Which signal, other than a distress signal, can be used by a vessel to attract attention? | Searchlight beam | Burning barrel | Continuous sounding of a fog signal apparatus | Calling "Mayday" on the radiotelephone |
| 244 | Which light(s) is(are) AMONG those shown by a 200-meter vessel at anchor? | Any available working lights to illuminate the decks | In the forepart of the vessel, a 225° white light | In the after part of the vessel, a 135° white light | All-round red or green light |
| 245 | Which vessel would NOT sound a fog signal of one prolonged and two short blasts? | A vessel being towed | A vessel not under command | A vessel constrained by her draft | A vessel sailing |
| 246 | Which signal may be sounded ONLY by vessels in restricted visibility? | At least five short and rapid blasts | Four short blasts | Two short blasts | One prolonged, one short, one prolonged, and one short blast, in that order |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 247 | You are underway on the high seas in restricted visibility. You hear a fog signal of one prolonged and two short blasts. It could be any of the following EXCEPT a vessel _____. | being towed | minesweeping | engaged in fishing | constrained by her draft |
| 248 | Your vessel is backing out of a slip in a harbor. Visibility is restricted. You should sound _____. | one long blast only | the danger signal | one prolonged blast followed by three short blasts when leaving the slip | one prolonged blast only |
| 249 | You are in sight of a power-driven vessel that sounds two short blasts of the whistle. This signal means that _____. | the vessel is altering course to port | the vessel intends to leave you on her starboard side | you should alter course to port. | you should sound the danger signal |

| | | | | | |
|---|---|---|---|---|---|
| 250 | The light which may be used with a vessel's whistle must be _____. | used only at night | used when the whistle is broken | a white light | used prior to sounding the whistle |
| 251 | A light used to signal passing intentions must be an _____. | a searchlight or beam | an all-round white light | all-round white or yellow light | alternating white and yellow light |
| 252 | Which signal is sounded ONLY by a vessel in sight of another? | One short blast on the whistle | Four short blasts on the whistle | One short, one prolonged, and one short blast on the whistle | One prolonged blast on the whistle |
| 253 | Which whistle signal may be sounded by one of two vessels in sight of each other? | One prolonged blast | One short blast | Four short blasts | One short, one prolonged, and one short blast |
| 254 | Which signal is sounded ONLY by a vessel in sight of another and NOT in or near an area of restricted visibility? | One short blast | One short, one prolonged, and one short blast | One prolonged blast | Four short blasts |
| 255 | Which signal is required to be sounded by a power-driven vessel ONLY? | A signal meaning that the vessel sounding it is in doubt as to the other vessel's actions. | A signal meaning, "I intend to overtake you on your starboard side." | A signal meaning, "I am altering my course to starboard." | A signal sounded when approaching a bend. |
| 256 | Vessel "X" is overtaking vessel "Y" on open waters and will pass without changing course. Vessel "X" _____. | will not sound any whistle signals | should sound two short blasts | should sound one long blast | should sound the danger signal |
| 257 | When two vessels are in sight of one another and NOT in or near an area of restricted visibility, any of the following signals may be given EXCEPT _____. | two short whistle blasts | one prolonged, one short, one prolonged, and one short whistle blasts | four short whistle blasts | a light signal of at least five short and rapid flashes |
| 258 | What whistle signal, if any, would be sounded when two vessels are meeting, but will pass clear starboard to starboard? | Two short blasts | One short blast | Five or more short blasts | No signal is required. |
| 259 | You are in sight of another vessel in a crossing situation, and the other vessel sounds one short blast. You are going to hold course and speed. You should _____. | sound no whistle signal | answer with one short blast | answer with two short blasts | sound the danger signal |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 260 | Two power-driven vessels are crossing within one half mile of each other, with Vessel "P" as the stand-on vessel, and Vessel "Q" as the give-way vessel. Vessel "P" sounds two short blasts on the whistle. What signal should vessel "Q" sound? | None of these | Two short blasts | One short blast | Five short and rapid blasts |
| 261 | Vessel "A", a power driven vessel underway, sights vessel "B" which is a vessel underway and fishing. Which statement is TRUE? | Vessel "A" must keep out of the way of vessel "B" because "B" is fishing. | Vessel "A" must keep out of the way of vessel "B" because "B" is to port. | Vessel "B" must keep out of the way of vessel "A" because "A" is to starboard. | Both vessels are required by the Rules to keep clear of each other. |
| 262 | The prohibition against displaying lights which may be confused with required navigation lights applies _____. | Only when under tow | Only when other vessels are in the area | From sunset to sunrise and during restricted visibility | Only when operating in a traffic separation scheme |
| 263 | When can an officer of the watch deviate from the Rules of Road? | To avoid immediate danger. | Never | When the bearing of the vessel does not appreciably change. | Only if there is risk of collision. |
| 264 | Your intention is to overtake a vessel moving in a parallel course in a narrow channel. As you approach the other vessel's stern _____ | the vessel's will drift apart | the vessel will drift together | you will gain speed | both vessels will gain speed |
| 265 | You are transiting a narrow channel. What can happen in this situation? | The bow will be pushed away from the bank | The stern will be pushed away from the bank | The bow will be sucked towards the bank | None of the options |
| 266 | You intend to overtake a vessel in a narrow channel. As you approach the other vessel's stern _____. | both vessels will gain speed | the vessels will drift together | the vessels will drift apart | you will gain speed |
| 267 | A vessel heading SSE is on a course of: | 157.5deg. | 135.0deg. | 112.5deg. | 180.0deg. |
| 268 | What is the minimum sound signaling equipment required aboard a vessel 10-meters in length? | A whistle only | Any means of making an efficient sound signal | A bell and a whistle | A bell only |
| 269 | For a vessel constrained by its draught, describe the day signal with its corresponding size. | A black cylinder having a diameter of not less than 0.6 m and a height twice its diameter. | A black diamond having a diameter of not less than 0.6 m and a height twice its diameter. | A black cylinder having a diameter of not less than 0.5 m and a height twice its diameter. | A black cylinder having a diameter of not less than 0.6 m and a height equal to its diameter. |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 270 | A towing vessel pushing a barge ahead and rigidly connected in a composite unit shall show the lights of: | a barge being pushed ahead | a power driven vessel towing | a power driven vessel and a vessel being towed | a power driven vessel not towing |
| 271 | Whenever a course alteration is made to avoid collision, it should be: | a large change | a succession of small changes | supplemented by speed change | any of the choices is correct |
| 272 | A commercial airline in the water is: | A vessel | A special purpose vessel | In trouble and not specifically addressed by the navigation rules | A seaplane |
| 273 | Of the listed vessels, which is to be regarded as a vessel "restricted in her ability to maneuver" in accordance with the Navigation Rules? | A vessel with a draft of such depth that she cannot change her course | A vessel fishing with trawls | A vessel engaged in mineclearing | A vessel which has lost her rudder |
| 274 | As defined in the Rules, which vessel would qualify as a "vessel not under command" among the listed? | a vessel with her anchor down but not holding | a vessel having an accident in her machinery forcing her to reduce her speed drastically | a vessel affected by severe weather conditions | a vessel fishing with trolling lines |
| 275 | Which statement is TRUE regarding equipment for bell and gong signals? | Any vessel over 12-meters in length must be provided with a gong | A vessel of less than 12 meters in length need not have any sound signaling equipment | Signals must be able to be sounded manually and automatically | Manual sounding of the signals must always be possible |
| 276 | Of the listed, which vessel is NOT classified as vessel "restricted in her ability to maneuver" in accordance to the Rules? | A vessel picking up a navigation mark | A vessel whose anchor is fouled | A vessel engaged in mine clearance operations | A vessel transferring cargo while underway |
| 277 | A 95-meter vessel aground shall sound which fog signal? | A rapid ringing of a bell for 5 seconds, preceded and followed by 3 separate and distinct strokes on the bell | A whistle signal of 1 short, 1 prolonged and 1 short blast | A rapid ringing of a bell for 5 seconds, every 2 minutes | A long blast of the whistle at intervals to exceed 1 minute |
| 278 | The competence and vigilance of the officer of the watch provide the most direct means of: | avoiding close quarter situation | posting proper lookout | avoiding dangerous situations | adhering with the Master's order |
| 279 | The "collision avoidance rules" shall apply to which of the following vessels? | All vessels upon the high seas and in all waters connected therewith navigable by | All vessels upon the high seas ONLY | All power-driven vessels ONLY upon the high seas and in all waters | All power-driven and sailing vessels upon the high seas ONLY |

OIC NAVIGATIONAL WATCH

| | | | | | |
|---|---|---|---|---|---|
| | | seagoing vessels | | connected therewith navigable by seagoing vessels | |
| 280 | Your vessel is underway in fog and you hear two prolonged blast on your starboard quarter. What appropriate action should you do? | Alter course to port | Hold your course and speed | Stop your engine | Alter course to starboard |
| 281 | You are underway on a power driven vessel in open water when you observe a crossing power driven vessel approximately 8 miles away at 22 degrees on your port bow. Bearing steady, what action do you take? | Reduce speed to let him pass ahead | Call him on VHF before deciding on what action to take | | Maintain course and speed with caution as he is the give way vessel |
| 282 | In ANNEX III of the International Rules, if whistles are fitted at a distance apart of more than 100 meters, it shall be arranged that they: | are not sounded simultaneously | an be sounded simultaneously | can both be sounded at the same time | can be switched on only if the other in not in operation |
| 283 | To which of the following annexes of the Collision Regulations is titled as Additional Signals for Fishing Vessel Fishing in Close Proximity? | Annex 3 | Annex 4 | Annex 2 | Annex 1 |
| 284 | Which statement applies to Rule 8 (b) of the 1972 Colregs? | a succession of small alterations of course and/or speed should be avoided | any action to avoid a close quarter should not result in another close quarter situation | action taken to avoid collision with another vessel shall be such as to result in passing at a safe distance | when in sight of another vessel any action taken must be accompanied by sound signals |
| 285 | The word "seaplane" means it includes: | any airplane on a flight over a large body of water | any air craft designed to maneuver on the water | helicopter flying over water | commercial aircraft |
| 286 | Power-driven vessel "A" is fitted with radar and is making way in fog. Under the collision regulations, | a safe speed | any speed if there are no targets showing on the PPI | full speed only in open waters | full speed with the engines on stand-by, if a radar watch is |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| | vessel "A" should proceed at: | | | | kept |
| 287 | The presence of a pilot on board does not relieve the master and the officers of their responsibility for the safe the navigation of the vessel. If that notion is correct, what is the use of having pilot on board? | Required as per Charter Party | Pilotage is compulsory | Adviser to the Master because of his local knowledge | As customary port regulations |
| 288 | A vessel heading SSE is on a course of: | 157.5deg. | 135.0deg. | 112.5deg. | 180.0deg. |
| 289 | What is the minimum sound signaling equipment required aboard a vessel 10-meters in length? | A whistle only | A bell only | A bell and a whistle | Any means of making an efficient sound signal |
| 290 | For a vessel constrained by its draught, describe the day signal with its corresponding size. | A black cylinder having a diameter of not less than 0.6 m and a height twice its diameter. | A black diamond having a diameter of not less than 0.6 m and a height twice its diameter. | A black cylinder having a diameter of not less than 0.5 m and a height twice its diameter. | A black cylinder having a diameter of not less than 0.6 m and a height equal to its diameter. |
| 291 | A towing vessel pushing a barge ahead and rigidly connected in a composite unit shall show the lights of: | a barge being pushed ahead | a power driven vessel not towing | a power driven vessel and a vessel being towed | a power driven vessel towing |
| 292 | Whenever a course alteration is made to avoid collision, it should be: | a large change | a succession of small changes | supplemented by speed change | any of the choices is correct |
| 293 | A commercial airline in the water is: | In trouble and not specifically addressed by the navigation rules | A special purpose vessel | A seaplane | A vessel |
| 294 | Of the listed vessels, which is to be regarded as a vessel "restricted in her ability to maneuver" in accordance with the Navigation Rules? | A vessel engaged in mineclearing | A vessel fishing with trawls | A vessel which has lost her rudder | A vessel with a draft of such depth that she cannot change her course |
| 295 | As defined in the Rules, which vessel would qualify as a "vessel not under command" among the listed? | a vessel having an accident in her machinery forcing her to reduce her speed drastically | a vessel affected by severe weather conditions | a vessel fishing with trolling lines | a vessel with her anchor down but not holding |

NOT FOR SALE

# OIC NAVIGATIONAL WATCH

| | | | | | |
|---|---|---|---|---|---|
| 296 | Which statement is TRUE regarding equipment for bell and gong signals? | Manual sounding of the signals must always be possible | A vessel of less than 12 meters in length need not have any sound signaling equipment | Any vessel over 12-meters in length must be provided with a gong | Signals must be able to be sounded manually and automatically |
| 297 | Of the listed, which vessel is NOT classified as vessel "restricted in her ability to maneuver" in accordance to the Rules? | A vessel picking up a navigation mark | A vessel whose anchor is fouled | A vessel transferring cargo while underway | A vessel engaged in mine clearance operations |
| 298 | A 95-meter vessel aground shall sound which fog signal? | A rapid ringing of a bell for 5 seconds, every 2 minutes | A whistle signal of 1 short, 1 prolonged and 1 short blast | A rapid ringing of a bell for 5 seconds, preceded and followed by 3 separate and distinct strokes on the bell | A long blast of the whistle at intervals to exceed 1 minute |
| 299 | The competence and vigilance of the officer of the watch provide the most direct means of: | avoiding dangerous situations | adhering with the Master's order | avoiding close quarter situation | posting proper lookout |

| | | | | | |
|---|---|---|---|---|---|
| 300 | The "collision avoidance rules" shall apply to which of the following vessels? | All vessels upon the high seas ONLY | All power-driven vessels ONLY upon the high seas and in all waters connected therewith navigable by seagoing vessels | All vessels upon the high seas and in all waters connected therewith navigable by seagoing vessels | All power-driven and sailing vessels upon the high seas ONLY |
| 301 | Your vessel is underway in fog and you hear two prolonged blast on your starboard quarter. What appropriate action should you do? | Hold your course and speed | Alter course to port | Alter course to starboard | Stop your engine |
| 302 | You are underway on a power driven vessel in open water when you observe a crossing power driven vessel approximately 8 miles away at 22 degrees on your port bow. Bearing steady, what action do you take? | Call him on VHF before deciding on what action to take | Maintain course and speed with caution as he is the give way vessel | Reduce speed to let him pass ahead | Alter course to port and pass around his stern |

# OIC NAVIGATIONAL WATCH

| | | | | | |
|---|---|---|---|---|---|
| 303 | In ANNEX III of the International Rules, if whistles are fitted at a distance apart of more than 100 meters, it shall be arranged that they: | are not sounded simultaneously | an be sounded simultaneously | can both be sounded at the same time | can be switched on only if the other in not in operation |
| 304 | To which of the following annexes of the Collision Regulations is titled as Additional Signals for Fishing Vessel Fishing in Close Proximity? | Annex 1 | Annex 2 | Annex 4 | Annex 3 |
| 305 | Which statement applies to Rule 8 (b) of the 1972 Colregs? | a succession of small alterations of course and/or speed should be avoided | any action to avoid a close quarter should not result in another close quarter situation | action taken to avoid collision with another vessel shall be such as to result in passing at a safe distance | when in sight of another vessel any action taken must be accompanied by sound signals |
| 306 | The word "seaplane" means it includes: | helicopter flying over water | any air craft designed to maneuver on the water | commercial aircraft | any airplane on a flight over a large body of water |
| 307 | Power-driven vessel "A" is fitted with radar and is making way in fog. Under the collision regulations, vessel "A" should proceed at: | a safe speed | any speed if there are no targets showing on the PPI | full speed only in open waters | full speed with the engines on stand-by, if a radar watch is kept |
| 308 | The presence of a pilot on board does not relieve the master and the officers of their responsibility for the safe the navigation of the vessel. If that notion is correct, what is the use of having pilot on board? | As customary port regulations | Adviser to the Master because of his local knowledge | Required as per Charter Party | Pilotage is compulsory |
| 309 | Rule 10 states that is a vessel is obliged to cross a traffic lane then she shall do so: | on a heading as nearly as practicable at right angles to the general direction of traffic flow | at a speed and heading that will cause the least encounters with vessels within the lane | on a heading that will cause her to spend the least time in the lane | on a heading so that her track will be as nearly as practical at right angles to the general direction of traffic flow |
| 310 | A vessel shall navigate with caution at what speed? | At maneuvering speed | At slow speed | At a speed commensurate with steerage way | At moderate speed |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 311 | Under Annex III of the Collision Regulations, the sidelights of a vessel of 20 meters or more in length shall be fitted with inboard screens painted: | matt black | blue | the appropriate red and green colors | enamel black |
| 312 | In restricted visibility, a power-driven vessel underway but stopped and making no way through the water shall sound which of the following fog signals? | GOLF | CHARLIE | MIKE | BRAVO |
| 313 | Clear instructions are issued in writing by Master at night order book, which is the most important reminder that he always wrote? | Call the master in case of doubt | Call him to the bridge when meeting a vessel | Call the Master when you change your course | Call the Master when there is a distress alert |
| 314 | You are on a power driven vessel when you suddenly run into a fog bank. What action would you take? | Call the Master and wait for him to arrive before taking any action if it appears to be all clear | Commence sounding the fog signal, engines on standby, call for lookout, call Master | As the radar is clear proceed as normal for the time being as the fog will probably lift | Stop engines and call Master |
| 315 | What prudent action would you take if you are the officer on watch on board a power driven vessel and you suddenly run into a fog bank? | As the radar is clear proceed as normal for the time being as the fog will probably lift | Stop engines and call Master | Start sounding the fog signal, engines on standby, call for lookout, call Master | Call the Master and wait for him to arrive before taking any action if it appears to be all clear |
| 316 | Action to avoid collision. Any alteration of the course and or speed to avoid collision shall if the circumstances admit, be large enough to be readily apparent to another vessel. | Colreg 8(b) | Colreg 8(d) | Colreg 8(a) | Colreg 8(c) |
| 317 | A vessel transferring cargo while underway is classified by the Rules as a vessel: | in special circumstances | restricted in her ability to maneuver | constrained by her draft | not under command |
| 318 | What is the action to take while in fog if a vessel ahead is detected by radar? | each vessel to comply with the rules | contact the other vessel by VHF | determine if the other vessel is a give-way or a stand-on vessel | alter course to starboard if the other vessel is a stand-on vessel |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 319 | Under the Rules, any vessel may slacken her speed, stop, or reverse her engines to: | All of these | Create a crossing situation | Attract the attention of another vessel | Allow more time to asses the situation |
| 320 | A vessel is deemed to be in what situation when she approaches another vessel from more than 22.5 degrees abaft other vessel's beam? | overtaking | crossing | meeting | any of the choices is correct |
| 321 | When the range of the target is decreasing and the bearing remains constant, the ships are on: | parallel course | diverging course | collision course | opposite course |
| 322 | Looking straight ahead at night you observe the masthead lights and both side lights of another vessel. What action should be taken? | Each ship alter course to starboard | Each ship shall alter course to port | You stand on as the other ship will alter course | One ship shall alter course to starboard and the other to port |
| 323 | A vessel which is "restricted in her ability to maneuver" under the Rules, is a vessel which is: | not under command | mineclearing | at anchor | engaged in fishing |
| 324 | Rule 9 A vessel shall not cross a narrow channel or fairway if: | man of war | fishing vessel engaged in trawling | if such crossing impedes the passage of another vessel which can only safely navigate within the channel or fairway | fishing vessel engaged in fishing |
| 325 | The Night Orders Book includes the following except? | maintain ship's speed at all times | fix intervals | ship's navigation policy | minimum CPA |
| 326 | In addition to the required fog signal, pilot vessels may sound which of the listed? | four quick blasts | four short blasts | four prolonged blasts | four long blasts |
| 327 | All lights mentioned in the Rule be exhibited during what hours? | 24-hour period | From sunrise to sunset in restricted visibility only | From sunset to sunrise in clear weathers only | From sunset to sunrise in all weathers |
| 328 | From a fishing vessel by day, at what direction do long nets lie? | From the double cone towards the single cone | From the single cone towards the double cone | From the basket towards the single cone | Any direction is applicable |
| 329 | A light showing one or more flashes at regular intervals, the duration of light being less than that of darkness. | quick flashing | group occulting | occulting light | flashing light |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 330 | The vessels engaged in fishing with purse seine gears may exhibit two yellow lights in a vertical line. These lights shall flash alternately every second and wit equal light and occultation duration. These lights may be exhibited only when the vessel is: | hampered by its fishing gear | hampered by its tow | hampered by its steering gear | hampered by underwater operations |
| 331 | In order for a stand-on vessel to take action in a situation, she must first determine that the other vessel: | has not changed course since risk of collision was determined | is not taking appropriate action | has sounded the danger signal | is restricted in her ability to maneuver |

| | | | | | |
|---|---|---|---|---|---|
| 332 | A vessel engaged in trawling, in addition to its identity lights, is exhibiting two white lights in a vertical line. What is she doing? | shooting her nets | hauling her nets | her nets have come fast an obstruction | she is in distress |
| 333 | Which of the following is not true in respect to the OOW? | He should ensure that the planned passage is properly carried out during his watch | He should keep his watch on the bridge but can leave anytime if necessary | He should be aware of any work being carried out in vicinity of the radar and radio signals | He ensure that an efficient lookout is maintained at all times |
| 334 | A vessel is "engaged in fishing" when: | she has any fishing gear on board | her gear extends more than 100 meters from the vessel | she is using fishing apparatus which restricts her maneuverability | she is using any type of gear other than lines |
| 335 | A look-out is best posted in which location? | forward as low as possible | high on the mast | inside the bridge | in the bridge wings |
| 336 | Three short blasts on a whistle means: | I am going astern | I am moving astern | I plan to maneuver astern | I am a operating astern propulsion |
| 337 | What is the meaning of the two white lights displayed by a fishing vessel, visible all round the horizon, vertically disposed, in addition to normal fishing lights? | I am shooting nets | I am grabbing nets | I am hauling nets | any of the choices is correct |
| 338 | Which light(s) is (are) AMONG those shown by a 200-meter vessel at anchor? | In the after part of the vessel, a 135deg. white light | Any available working lights to illuminate the decks | In the forepart of the vessel, a 225deg. white light | In the forepart of the vessel, a 112.5deg. white light |

| | | | | | |
|---|---|---|---|---|---|
| 339 | As per Annex II of the Rules, the additional signals for trawlers when hauling their nets is: | International code flag "Z" | International code flag "P" | International code flag "H" | International code flag "G" |
| 340 | Vessels engaged in pair trawling show what day signals? | International code flag "T" flown at the foremost | International code flag "P" flown at the foremost | No necessary signal to be shown | International code flag "PT" flown at the foremost |
| 341 | As per Annex II of the Rules, which of the following is the additional day signal for trawlers when the net has come fast an obstruction? | International code flag "TANGO" | International code flag "PAPA" | International code flag "GOLF" | International code flag "ZULU" |
| 342 | While the Pilot is embarked he or she: | is a specialist hired for his or her local navigational knowledge | is solely responsible for the safe navigation of the vessel | relieves the officer of the watch | relieves the Master of his duties |
| 343 | What does this signal displayed by a small craft signify when in passage up a river, she is showing a rigid replica of the international code flag "A"? | It signifies, "I am maneuvering with difficulty, keep out of my way" | It signifies, "I have a diver down, I require assistance" | It signifies, "I have a diver down, I am proceeding at maneuvering speed, keep clear of me" | It signifies, "I have a diver down, keep well clear at slow speed" |
| 344 | Rule 9 A vessel proceeding along the course of narrow channel or fairway shall: | keep a near the outer limit of the channel | keep clear | maintain her speed | is privilege to keep her course and speed |
| 345 | A high intensity all-round flashing red light is exhibited by a WIG craft only when: | any of the choices is correct | taking off | landing | in flight near surface |
| 346 | Which of the following provisions pertains to PART B of the Rules of the Road? | Sound Signals | Lights and Shapes | General | Steering and Sailing Rules |
| 347 | What lights and shapes are to be shown if a vessel is aground? | Lights prescribed in Rule 30(d) | Lights prescribed in Rule 30(a) | Lights prescribed in Rule 31(a) | Lights prescribed in Rule 31(b) |
| 348 | As far as Rule 9 of the Rules of the Road is concerned, a vessel proceeding along the course of a narrow channel or fairway, shall: | all of the choices is correct | be privileged to keep her course and speed | maintain her course speed while in the channel | keep as near to the outer limit of the channel or fairway which lies on her starboard side |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 349 | One of the most important innovations in the 1972 Regulations (COLREG) was the recognition given to traffic separation schemes. Under Rule 10 of this Regulation states that in so far as practicable, a vessel must avoid: | crossing traffic lanes | maneuvering while inside traffic lanes | stopping in the traffic lanes | none of these choices |
| 350 | The stated limits of the danger area about a mine clearance vessel when engaged in minesweeping operations is: | Maximum of 1,000 m radius about the vessel | Maximum of 1,000 m diameter about the vessel | Minimum of 1,000 m diameter about the vessel | Minimum of 1,000 m radius about the vessel |
| 351 | In order to attract the attention of an approaching vessel, what lights may a vessel engaged in fishing show? | may direct the beam of their search light in the direction of a danger to the approaching vessel | may direct the high intensity light in the direction of a danger to the approaching vessel | may switch on the deck light to illuminate their decks | all of the choices |
| 352 | A vessel may exhibit lights other than those prescribed by the rules as long as the additional lights: | May impair the visibility or distinctive character of the prescribed lights | Do not interfere with the keeping of a proper lookout | Have a lesser range of visibility than the prescribed light | Are not the same color as either side light |
| 353 | A power-driven vessel is underway and fishing with trolling lines. This vessel: | Must keep out of the way of sailing vessel | Must sound a one and prolonged, two short blasts signal in restricted visibility | Is the stand-on vessel when overtaking a power-driven vessels | All of the above |
| 354 | For a vessel at anchor, what are the additional and optional fog-signals? | No additional and optional signal required | TANGO | ROMEO | SIERRA |
| 355 | Deviation from Colreg is: | allowed when necessary to avoid immediately danger | not allowed | unwise | unnecessary |
| 356 | What is the vertical distance between the shapes shown by a 50-meter passenger ferry that has lost her propulsion while underway and she has to display her signals by day? | not less than 2.5 m | No specified vertical spacing | not less than 1.5 m | not more than 1 m |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 357 | A bell or a gong, or other device having similar sound characteristics and at a distance of one meter from it, shall produce a sound pressure level of: | not less than 110 dB | not more than 210 dB | at least 160 dB | not less than 220 dB |
| 358 | The required audibility of whistles for vessels 75 meters but less than 200 meters in length as prescribed in Annex 3 is: | one nautical mile | two nautical miles | two and a half nautical miles | one and a half nautical miles |
| 359 | When pushing ahead in fog, a vessel towing shall sound: | one prolonged and two short blasts | one prolonged blast | one short blast | two prolonged blasts |
| 360 | Your vessel is proceeding along a narrow channel displaying the signal required by the rule 28. A small vessel commences to cross the channel from starboard to port. It appears that she will impede your passage. What signal should you give under the circumstances? | 1 prolonged, 1 short, 1 prolonged, 1 short | one short blast | three short blasts | at least 5 short and rapid blast |
| 361 | Fog signals, required under the Rules for vessel underway, shall be sounded: | At the intervals of not more than two minutes | Only on the approach of another vessel | Only when vessels are in sight of each other | At intervals of not more than one minute |
| 362 | The masthead light of an air-cushion vessel must be visible and shown over how many points of the compass? | air-cushion vessel does not require masthead light | Over an arc of the horizon of 20 points of the compass | Over an arc of the horizon of 10 points of the compass | Over an arc of the horizon of 12 points of the compass |
| 363 | In which of the following situations should a fishing vessel fishing in close proximity exhibits one white light over red light in vertical line? | Hauling her nets | pair trawling | Shooting her nets | any of the choices is correct |
| 364 | As prescribed in what rule shall a vessel aground give the bell signal and if required the gong signal? | paragraph (g) of Rule 35 | paragraph (f) of Rule 36 | paragraph (f) of Rule 35 | paragraph (h) of Rule 37 |
| 365 | As stated in the Collision Regulations, "Exemptions" is contained in what part? | Part E | Part F | Part D | Part C |
| 366 | Pre-departure Check List includes the following, EXCEPT: | Weather Report | Bridge standing Order | Passage Plan | Navigational Equipment |

OIC NAVIGATIONAL WATCH

| | | | | | |
|---|---|---|---|---|---|
| 367 | These are methods of Collision Avoidance, except: | Preserving course, maintaining speed | Preserving course and altering speed | Altering course, maintaining speed | Simultaneous alternation of course and speed |
| 368 | Being the OOW navigating in an area of restricted visibility, a single-letter signal "MIKE" was heard being sounded at an interval of not more than two minutes. You have determined that this signal is coming from a: | Vessel at anchor | power-driven vessel, not making way | NUC vessel | RAM vessel |
| 369 | The fog signal for a pilot vessel more than 100 meters in length at anchor, on station is: | Rapid ringing of a bell in the forepart of the vessel for about 5 seconds. She may also sound an identity signal of four short blasts | any of the choices is correct | Rapid ringing of a gong in the forepart of the vessel for about 5 seconds, and a bell signal sounded in the after part of the vessel. She may also sound an identity signal of four short blasts | Rapid ringing of a bell in the forepart of the vessel for about 5 seconds, and a gong signal sounded in the after part of the vessel. She may also sound an identity signal of four short blasts |
| 370 | What can be the possible course when you notice that the range between two ships is decreasing while their bearing remains constant? | converging course | reciprocal course | diverging course | parallel course |
| 371 | What action would you take as OOW, while in up-river passage you see a small craft showing a rigid replica International code flag ALPHA? | All of the choices | Give a wide berth to the craft, and reduce your own vessel's speed on approaching and passing the area | Keep your vessel to the starboard side of the river | Reduce your vessel to steerage way until the other vessel pass |
| 372 | What would an OIC-NW should do prior to relieving an officer incharge of navigational watch? | Report to the bridge in order to adjust his eyesight for at least 10 mins prior to taking the watch | Report to the bridge just on time | Report to the bridge in order to familiarize himself with the instruments and equipment | Read and sign the order book and check vessel's position |
| 373 | A stand-on vessel is: | Free to maneuver in any crossing or meeting situation as it has the right-of-way | Required to maintain course and speed in a crossing situation but may take action to avoid collision | Required to give way in a crossing situation | Required to sound the first passing signal in a meeting situation |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 374 | In what rule in the Collision Regulations can you find the provision made with respect when navigating in narrow channels by power-driven vessels? | Rule 9 | Rule 10 | Rule 11 | Rule 12 |
| 375 | This Rule states that any subsequent alteration of the bearing between two vessels shall not make the overtaking vessel a crossing vessel within the meaning of these Rules of relieve her of the duty keeping clear of the overtaken vessel until she is finally past and clear. | Rule 10 ( I ) | Rule 13 ( d ) | Rule 13 ( b) | Rule 13 ( a ) |
| 376 | A vessel restricted in her ability to maneuver when engaged in an operations for the maintenance of safety of navigation laying, serving or picking up a submarine cable is exempted from complying under: | Rule 10 | Rule 11 | Rule 12 | Rule 13 |
| 377 | Under what rule in the Rules of the Road contained this scenario when two sailing vessels are approaching one another so as to involve risk of collision? | Rule 18 | Rule 15 | Rule 13 | Rule 12 |
| 378 | What rule indicates the actions of a give-way vessel? | Rule 16 | Rule 13 | Rule 14 | Rule 15 |
| 379 | This rule states that when two power driven vessel are meeting on reciprocal or nearly reciprocal courses so as to involve risk of collision each shall alter he course to starboard so that they will pass port to port. | Rule 14 (c) | Rule 14 (d) | Rule 14 (b) | Rule 14 (a) |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 380 | Whilst calling attention to all the usual precautions to be taken, it also calls for the exercise of personal intelligence on the arising of any unforeseen circumstances. In what other rule conforms with this statement? | Rule 2(a) | Rule 2(b) | Rule 3(a) | Rule 3(b) |
| 381 | What rule applies when inspite all the precautions made the vessel can deviate from these rules necessary to avoid immediate danger? | Rule 2(b,i) | Rule 2(b,ii) | Rule 2(b) | Rule 2(b,iii) |
| 382 | In what rule in the Collision Regulations does the responsibilities of a seaplane on the water is stated? | Rule 18 | Rule 23 | Rule 31 | Nowhere in the Rules |
| 383 | The term "trawling" which means the dragging of the dredge net or other apparatus through the water is defined in which Rule? | Rule 28 | Rule 26 | Rule 27 | Rule 29 |
| 384 | In what Rule are the lights prescribed for a vessel is restricted in her ability to deviate from her course because of her draught and the available depth of water? | Rule 28 | Rule 27 | Rule 26 | Rule 29 |
| 385 | In what rule does it prescribes that a vessel engaged in dredging shall exhibit the lights and shapes to indicate to other vessels the obstructed area? | Rule 27(a) | Rule 28 | Rule 27(d) | Rule 27(e) |
| 386 | A vessel engaged in underwater operations and at anchor is required to sound the fog signal as contained in which rule? | Rule 35( c ) | Rule 33(d) | Rule 34(a) | Rule 34(e) |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 387 | The signal for a power-driven vessel required to make on her whistle when the vessels are in sight of one another are prescribed in what rule? | Rule 35 (b) | Rule 34(d) | Rule 34(a) | Rule 35(e) |
| 388 | In what rule can you find concerning the maneuvering light? | Rule 34(b) | Rule 35(d) | Rule 33(a) | Rule 32(e) |
| 389 | This rule states that, action taken to avoid collision with another vessel shall be such to result in passing distance. | Rule 8 (e) | Rule 8 (c) | Rule 8 (d) | Rule 8 (b) |
| 390 | The Rules of the Road stated that any alteration of course is made in good time, and substantial and does not result in close-quarters situation. | Rule 8 (c) | Rule 8 (d) | Rule 8 (b) | Rule 8 (e) |
| 391 | What rule is this "A vessel shall slacken her speed or take all way off by stopping or reversing her means of propulsion"? | Rule 8 (c) | Rule 8 (d) | Rule 8 (e) | Rule 8 (b) |
| 392 | Your vessel is proceeding along the course of a narrow channel, under this Rule your are mandated to keep near to the outer limit of the channel or fairway which lies on her starboard side as is safe and practicable, this is: | Rule 9 (a) | Rule 9 (b) | Rule 9 (c) | Rule 10 (a) |
| 393 | A single-letter signal "TANGO" was heard at an interval of not more than two minutes in restricted visibility. This means that the vessel is a: | sailing vessel, making way | towing vessel, not making way | power-driven vessel not making way | power-driven vessel, making way |
| 394 | A seaplane underway on the water shall carry which lights and shapes? | No lights and shapes prescribed for seaplanes | Same lights and shapes as prescribed in Rule 23 | Same lights and shapes as prescribed in Rule 31 | Same lights and shapes as prescribed in Rule 24 |
| 395 | The action necessary to transfer the steering control from the wheelhouse to local control in order to use the steering gear room trick wheel, is to: | align the trick wheel to the rudder angle position | set the six-way control valve in the trick wheel position | open the power transfer switch before engaging the trick wheel | always place the rudder in the midship position to engage the trick wheel |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 396 | A sailing vessel under 7 meters or a vessel under oars shall carry which light if she does not carry sidelights and a sternlight? | No necessary lights to carry | she must have a combined lantern showing red and green lights | she must have a combo lights showing red, white and green lights | she must have ready at hand a lighted lantern or an electric torch showing a white light |
| 397 | A vessel proceeding under sail and under power shall show which day signal? | Signal prescribed in Rule 23(d) | Signal prescribed in Rule 25(e) | Signal prescribed in Rule 25(a) | Signal prescribed in Rule 23(a) |
| 398 | Uncertain whether you are overtaking or in crossing situation, your are approaching another vessel, What would you do? | sound one long blast and turn to starboard | sound two blasts and turn to port | assumed that you are overtaking | maintain course and speed and establish communication with another vessel |
| 399 | In fog, you observe your radar and determine that a risk of collision exist with a vessel 2 miles off your port bow. You should: | Take proper and avoiding action as soon as possible | stop your engines | take all way off, immediately | sound the danger signal at two-minute intervals |
| 400 | A vessel navigating in separation scheme should NOT intervene the passage of: | submarine | naval vessel | fishing vessel | deep draught vessel |
| 401 | As prescribed in the Rules, Annex I of the Navigation Rules pertains to which of the following? | Technical Details of Sound Signal Appliances | Positioning and Technical Details of Lights and Shapes | Distress Signals | Additional Signals for Fishing Vessel Fishing in Close Proximity |
| 402 | What will be your first preparation one hour prior to your arrival at the anchorage area? | The arrival ckecklist is properly attended | That all navigation and maneuvering equipments are in order | The Master on the bridge | The engine room notified |
| 403 | Under COLREGS Annex III, a power-driven bell striker is recommended to ensure: | that it will not get rusty | it will surely hit the bell | it has a diameter of 300 mm | constant force |
| 404 | A vessel is equipped with twin propellers, both turning outboard with the engines half ahead. If there is no wind or current and the rudders are amidships, what will happen? | The vessel will steer a fairly straight course | The bow will swing to port | The vessel will steer a zigzag course | The bow will swing to starboard |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 405 | After sailing for several minutes (making 10 knots through the water) and in constant monitoring of your radar screen, you noticed that a contact has remained in the same position relative to yours, what could be the possible conclusion of the scenario? | the radar is showing false echoes and is probably defective | the contact is on a reciprocal course at the same speed as your vessel | the contact is dead in the water | the contact is on the same course and speed as your vessel |
| 406 | As a stand-on vessel in a crossing situation, you may hold your course and speed until: | action taken by the give way vessel alone will not prevent collision | the other vessel gets to within a quarter mile of your vessel | the other vessel gets to within half a mile of your vessel | the other vessel takes necessary action |
| 407 | A sailing vessel before reaching a bend in river shall sound what signal? | The signal prescribed in Rule 34(c) | The signal prescribed in Rule 34(e) | The signal prescribed in Rule 34(d) | The signal prescribed in Rule 34(a) |
| 408 | By day, a vessel servicing a buoy, when also at anchor shall display which shapes? | The three shapes prescribed in Rule 28 | The three shapes prescribed in Rule 29 | The three shapes prescribed in Rule 27 | The three shapes prescribed in Rule 30 |
| 409 | What does it mean when a fishing vessel exhibits two yellow lights, vertically disposed, and flashing alternately? | The vessel is fishing with seine nets | The vessel is fishing with nets fast on an obstruction | The vessel is fishing with an extended gear | The vessel is fishing with pair trawl |
| 410 | As an OOW, you heard a continuous sounding of a fog-signal apparatus. What does this indicate? | the vessel is warning other vessel of her passage | the vessel is in distress | the vessel has completed loading dangerous cargo | the vessel is anchored in fog |
| 411 | As defined in the Rules, which of the following statements is CORRECT concerning a "vessel engaged in fishing"? | the vessel may be using nets, lines or trawls | the vessel shows 2 lights in a vertical line, white over red | the vessel may be trolling | all of the choices is correct |
| 412 | By day, when it is impracticable for small vessels engaged in diving operations to display the shapes for a vessel engaged in underwater operations, she shall display: | two red balls in a vertical line | a rigid replica of the International Code flag "A" | a black cylinder | three black balls in a vertical line |
| 413 | You are underway and approaching a bend in the channel where vessels approaching from the opposite direction cannot be seen. What sound signal should you make? | one blast 4 to 6 seconds duration | three blast, 4 to 6 seconds duration | one continuous blast until you are able to see around the bend | one blast 8 to 10 seconds in duration |

| | | | | | |
|---|---|---|---|---|---|
| 414 | A vessel "restricted in her ability to maneuver" is one which: | has lost steering and is unable to maneuver | due to adverse weather conditions is unable to maneuver as required by the rules | through some exceptional circumstance is unable to maneuver as required by the rules | from the nature of her work is unable to maneuver as required by the rules |
| 415 | What lights may be shown by a vessel of 100 meters or more that is at anchor? | All available working lights to illuminate her decks | Two anchor lights | One anchor light | High intensity lights to illuminate her decks |
| 416 | You are towing a vessel and the total length of the tow is more than 200 meters. Which day shape must be exhibited? | Two diamond shape | No day shape | One diamond shape, and one black ball | Diamond shape |
| 417 | As stated in the Collision Regulations, which of the listed refers to Annex II? | Additional Signals for Fishing Vessel Fishing in Close Proximity | Vertical Positioning and Technical Details of Lights and Shapes | Vertical Positioning and Technical Details of Lights and Shapes | Technical Details of Sound and Light Signal Appliances |
| 418 | As prescribed in Annex III of Rule of the Roads, what does it pertain to? | Vertical Positioning and Technical Details of Lights and Shapes | Technical Details of Sound Signal Appliances | Additional Signals for Fishing Vessel Fishing in Close Proximity | Vertical Positioning and Technical Details of Lights and Shapes |
| 419 | Under Rule 3 ( i ) a vessel is underway when: | she is dragging her anchor | when her anchor is down and holding | when she is made fast | when she is riding at her anchor |
| 420 | When navigating in restricted visibility, a power-driven vessel shall: | operate at a speed to be able to stop in distance of her visibility | stop her engines when hearing a fog signal forward of her beam, even if risk of collision does not exist | when making way, sound 1 prolonged blast at intervals of not more than 1 minute | have her engines ready for immediate maneuver |
| 421 | The Master is allowed by the rules to depart from the normal requirements: | in order to meet charterer's order | None of the choices is correct | in order to avoid immediate danger | whenever he desires |
| 422 | As prescribed under paragraph (f) of Rule 35, a vessel aground shall give the bell signal and if required also the: | gong signal | whistle signal | light signal | bell signal |
| 423 | To attract the attention of other vessel, a vessel may use any sound or light signals as long as: | the vessel signals such intentions over the radiotelephone | the signal cannot be mistaken for a signal authorized by the Rules | white lights are not used | red and green lights are not used |

| | | | | | |
|---|---|---|---|---|---|
| 424 | Under COLREGS Annex IV, what does the orange flag, showing a black circle and a square shape indicate? | distress signal | signal asking to communicate with other vessel | signal indicating danger | signal indicating a course change |
| 425 | A 25-meter vessel trawling will show the dayshape(s) consisting of_. | a cone apex downward | a basket | two balls | two cones apexes together |
| 426 | A light signal consisting of three flashes means | My engines are full speed astern | I am operating astern propulsion | I am in doubt as to your actions | I desire to overtake you |
| 427 | A power-driven vessel not under command at night must show her sidelights when_. | making headway | moored to a buoy | at anchor | making no headway |
| 428 | A power-driven vessel making way through the water sounds a fog signal of_. | one prolonged blast at intervals of not more than one minute | two prolonged blasts at intervals of not more than one minute | two prolonged blasts at intervals of not more than two minutes | one prolonged blast at intervals of not more than two minutes |
| 429 | A rigid replica of the International Code flag A may be shown by a vessel_. | engaged in diving operations | engaged in underway replenishment | transferring explosives | pulling a submarine cable |
| 430 | A sailing vessel must keep course and speed when _____. | to leeward of another sailing vessel | crossing a vessel engaged in fishing | to windward of another sailing vessel | being overtaken |
| 431 | A single vessel being towed alongside shall show | only the outboard sidelight and a stern light | sidelights and a stern light | one all-round white light | a masthead light sidelights and a stern light |
| 432 | A traffic separation zone is that part of a traffic separation scheme which _____. | is designated as an anchorage area | is located between the scheme and the nearest land | separates traffic proceeding in one direction from traffic proceeding in the opposite direction | contains all the traffic moving in the same direction |
| 433 | A vessel 30 meters in length and aground would display a day-shape consisting of_. | three black balls in a vertical line | one black ball | two black balls in a vertical line | a cylinder |
| 434 | A vessel being towed astern where the length of the tow exceeds 200 meters will exhibit_. | two balls in a vertical line | a ball on each end of the tow | no day-shape | a diamond shape where it can best be seen |
| 435 | A vessel displaying three red lights in a vertical line is | constrained by her draft | aground | not under command | dredging |
| 436 | A vessel engaged in trawling will show identification lights of _____. | two red lights in a vertical line | a red light over a white light | a green light over a white light | a white light over a red light |

| | | | | | |
|---|---|---|---|---|---|
| 437 | A vessel is overtaking when she can see which light(s) of a vessel ahead? | Only the stern light of the vessel | The masthead lights of the vessel | Only a sidelight of the vessel | One sidelight and a masthead light of the vessel |
| 438 | A vessel not under command making way at night would show _____. | two all-round red lights in a vertical line sidelights and a stern light | anchor lights and sidelights | two all-round red lights in a vertical line | two all-round white lights in a vertical line sidelights and a stern light |
| 439 | A vessel proceeding along a narrow channel shall_. | not overtake any vessels within the channel | avoid crossing the channel at right angles | when nearing a bend in the channel sound a long blast of the whistle | keep as near as safe and practicable to the limit of the channel on her starboard side |
| 440 | A vessel showing a rigid replica of the International Code flag A is engaged in_. | mineclearance operations | fishing | diving operations | dredging |
| 441 | A vessel that is not equipped with towing lights should show that it has a vessel in tow by _____ . | shining a searchlight on the towline of the towed vessel | continuously sounding its horn | None of the above; a vessel shall not engage in towing at night without proper navigation lights | sounding one prolonged followed by two short blasts at intervals of not more than two minutes |
| 442 | A vessel underway and fishing shall keep out of the way of a_. | vessel engaged on pilotage duty | vessel not under command | power-driven vessel underway | vessel sailing |
| 443 | A vessel which is fishing is required to show sidelights and a stern light only when _____. | underway and making way | anchored | underway | dead in the water |
| 444 | A vessel which is unable to maneuver due to some exceptional circumstance shall exhibit_. | during the day three balls in a vertical line | when making way at night masthead lights sidelights and a stern light | when making way at night two all-round red lights sidelights and a stern light | during the day three shapes the highest and lowest being balls and the middle being a diamond |
| 445 | According to the Rules which vessel is NOT restricted in her ability to maneuver ? | A vessel servicing a navigation marker | A sailing vessel | A vessel dredging | A vessel mineclearing |
| 446 | AMVER is a system which provides _____. | position reporting service | weather information | navigational information | satellite communications |
| 447 | An icebreaker assisting a vessel through an ice field would display a visual signal consisting of the code letter S (Sierra) to signify that _____ . | My vessel is stopped and making no way through the water. | I am operating astern propulsion. | I am altering my course to starboard. | I am altering my course to port. |

| | | | | | |
|---|---|---|---|---|---|
| 448 | At night you observe a vessel ahead show three flashes of a white light. This signal indicates that the vessel ahead is _____ . | operating astern propulsion | intending to overtake another vessel | in distress | approaching a bend in the channel |
| 449 | At night which lights would you see on a vessel engaged in fishing other than trawling? | A white light over a red light | A red light over a white light | Two red lights one over the other | A green light over a red light |
| 450 | A sailing vessel with the wind coming from 220 deg relative would be _____. | close hauled on the port tack | close hauled on the starboard tack | on a broad reach | running before the wind |
| 451 | A sailing vessel with the wind coming from 090deg relative would be _____. | close hauled on the port tack | on a broad reach on the starboard tack | reaching on the starboard tack | close hauled on the starboard tack |
| 452 | A sailing vessel with the wind coming from 180deg relative would be _____. | running before the wind | close hauled on the port tack | on a broad reach on a port tack | close hauled on the starboard tack |
| 453 | A sailing vessel with the wind coming from 260deg relative would be _____. | running before the wind | on a starboard tack | on a broad reach | on a close reach |
| 454 | A 20-meter vessel is towing another vessel astern. The length of the tow from the stern of the towing vessel to the stern of the tow is 75 meters. How many white towing masthead lights shall the towing vessel show at night? | 2 | 1 | 3 | 4 |
| 455 | A towing vessel 35 meters in length with a tow 100 meters astern must show a minimum of how many masthead lights? | 3 | 2 | 1 | 4 |
| 456 | A towing vessel is towing two barges astern. The length of the tow from the stern of the tug to the stern of the last barge is 250 meters. The towing vessel is 45 meters in length. How many white masthead lights should be displayed on the tugboat at night? | 3 | 1 | 2 | 4 |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 457 | A list man would expect to see any of the following light signals EXCEPT _____. | one white light | two red lights | one green light | one amber light |
| 458 | A jack-up drilling rig being towed must _____. | turn off all lights that interfere with the navigation lights | display two black diamonds in a vertical line during the day | ring the bell rapidly for five seconds once a minute | turn on all available working lights on deck |
| 459 | A look-out at the bow sights an object on your port side. How many bell strokes should he sound? | One | Four | Two | Three |
| 460 | A lantern combining the two sidelights and stern light may be shown on a_. | 25-meter power-driven vessel engaged in trolling | 10-meter sailing vessel | 25-meter pilot vessel | 20-meter vessel engaged in fishing and making way |
| 461 | A short blast on the whistle has a duration of | 8 to 12 seconds | 4 to 6 seconds | 12 to 15 seconds | 1 second |
| 462 | A partly submerged vessel or object being towed which is not readily noticeable shall show _____. | a diamond shape | a black ball | yellow lights at each end | two red lights in a vertical line |
| 463 | A 20-meter power-driven vessel pushing ahead or towing alongside will display _____. | two towing lights in a vertical line | two all-round red lights where they can best be seen | two masthead lights in a vertical line | a single white light forward |
| 464 | A power-driven vessel pushing ahead or towing alongside will show sidelights a stern light and _____ . | two masthead lights in a vertical line | an all-round red light where it can best be seen | a single white light forward | two yellow masthead lights in a vertical line |
| 465 | A 30-meter tug is underway and NOT towing. At night this vessel must show sidelights and_. | two masthead lights and a stern light | three masthead lights and a stern light | a stern light ONLY | one masthead light and a stern light |
| 466 | A single towing light will be carried above a vessel s stern light under which of the following situations? | if the towing vessel is part of a composite unit | at any time when towing | only if she is towing astern | only if the tow exceeds 200 meters |
| 467 | A proper look-out shall be maintained | at all times | at night and during restricted visibility | only at night | only during restricted visibility |
| 468 | A 22-meter sailing vessel when also being propelled by machinery shall show during daylight hours a_. | black diamond | basket | black ball | black cone |
| 469 | A pilot vessel may continue to sound an identity signal if she is _____. | not under command | aground | at anchor | being towed |

| | | | | | |
|---|---|---|---|---|---|
| 470 | A 20-meter sailing vessel underway must exhibit a_. | stern light | combined lantern | red light over a green light at the masthead | All of the above |
| 471 | A signal of one prolonged one short one prolonged and one short blast in that order is given by a vessel _____ . | engaged on pilotage duty | in distress | at anchor | being overtaken in a narrow channel |
| 472 | A vessel approaching a narrow channel shall | avoid crossing the channel if it impedes another vessel navigating in the channel | keep as close as possible to the edge of the channel on her port side | anchor only in the middle of the channel | not overtake any vessels within the channel |
| 473 | A tug is towing three manned barges in line in fog. The third barge of the tow should sound_. | one prolonged one short and one prolonged blast | one prolonged and three short blasts | no fog signal | one prolonged and two short blasts |
| 474 | A self-propelled dredge not engaged in dredging but proceeding to a dredging location at night would_. | be required to show the lights of a power-driven vessel underway | not be required to show any lights | be required to show the lights characteristic of a dredge | be required to show the lights of a stationary dredge |
| 475 | You are navigating in a narrow channel and must remain in the channel for safe operation. Another vessel is crossing the channel ahead of you from your starboard and you doubt whether your vessel will pass safely. Which statement is TRUE? | You must stop your engines and you may sound the danger signal. | You must sound one short blast of the whistle and turn to starboard. | You must sound the danger signal. | You must stop your vessel, since the other vessel is the stand-on. |
| 476 | What is the required whistle signal for a power-driven vessel leaving a dock or berth? | One prolonged blast | Two short blasts | Two prolonged blasts | One short blast |
| 477 | In a narrow channel, you are underway on power driven vessel A and desire to overtake power driven vessel B . After you sound two short blasts on your whistle, vessel B sounds five short and rapid blasts on the whistle. You should _____. | pass with caution on the port side of vessel B | hold your relative position, and then sound another signal after the situation has stabilized | answer the five short blast signal then stop your vessel until the other vessel initiates a signal | slow or stop and expect radical maneuvers from B |
| 478 | You are overtaking a power-driven vessel in a narrow channel and wish to leave her on your starboard side. You may _____. | attempt to contact her on the radiotelephone to arrange for the passage | sound five short blasts | proceed to overtake her without sounding whistle signals | All of the above |

| | | | | | |
|---|---|---|---|---|---|
| 479 | When power-driven vessels are crossing, a signal of one short blast by either vessel means _____. | I intend to change course to starboard | I intend to leave you on my port side | I am altering course to starboard | I intend to hold course and speed |
| 480 | If you were coming up on another power-driven vessel from dead astern and desired to overtake on the other vessel s starboard side, which whistle signal would you sound? | Two short blasts | Two prolonged blasts followed by two short blasts | One short blast | One prolonged blast |
| 481 | Which statement is TRUE concerning narrow channels? | You should avoid anchoring in a narrow channel. | All of the above | A vessel having a following current will propose the manner of passage in any case where two vessels are meeting. | You should keep to that side of the channel which is on your port side. |
| 482 | When you are overtaking another power driven vessel and desire to pass on her left or port hand, you should sound _____. | one long blast | one short blast | two prolonged blasts followed by two short blasts | two short blasts |
| 483 | Your power driven vessel is meeting another vessel head-on. To comply with the steering and sailing rules, you should _____. | sound the danger signal | exchange two short blasts | exchange one short blast | sound one prolonged and two short blasts |
| 484 | You have made your vessel up to a tow and are moving from a pier out into the main channel. Your engines are turning ahead. What whistle signal should you sound? | One prolonged and two short blasts | Five or more short rapid blasts | Three long blasts | One prolonged blast |
| 485 | Under the Inland Navigation Rules, what is the meaning of the two short blasts signal used when meeting another vessel? | I intend to leave you on my starboard side. | I am turning to starboard. | I am turning to port. | I intend to leave you on my port side. |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 486 | Your vessel is proceeding down a channel, and can safely navigate only within the channel. Another vessel is crossing your bow from port to starboard, and you are in doubt as to her intentions. Which statement is TRUE? | The sounding of the danger signal is optional. | The sounding of the danger signal is mandatory. | You should sound two short blasts. | You should sound one prolonged and two short blasts. |
| 487 | The stand-on vessel in a crossing situation sounds one short blast of the whistle. This means that the vessel _____. | is changing course to starboard | is changing course to port | intends to hold course and speed | intends to leave the other on her port side |
| 488 | You are crossing the course of another vessel which is to your starboard. You have reached an agreement by radiotelephone to pass astern of the other vessel. You MUST _____. | None of the above | sound one short blast | sound two short blasts | change course to starboard |
| 489 | Passing signals shall be sounded on inland waters by _____. | a towing vessel when meeting another towing vessel on a clear day with a 0.6 mile CPA (Closest Point of Approach) | all vessels upon sighting another vessel rounding a bend in the channel | All of the above | a power-driven vessel when crossing less than half a mile ahead of another power-driven vessel |
| 490 | Your power driven vessel is meeting another vessel head-on. To comply with the rules, you should exchange _____. | one short blast, alter course to starboard, and pass port to port | one short blast, alter course to port, and pass starboard to starboard | two short blasts, alter course to starboard, and pass port to port | two short blasts, alter course to port, and pass starboard to starboard |
| 491 | Which signal must a power-driven vessel give, in addition to one prolonged blast, when backing out of a berth with another vessel in sight 0.5 nm away? | No additional signal | 3 short blasts | 1 blast | 2 short blasts |
| 492 | You are overtaking a power-driven vessel in a narrow channel and wish to leave her on your starboard side. You may _____. | All of the above | proceed to overtake her without sounding whistle signals | sound four short blasts | attempt to contact her on the radiotelephone to arrange for the passage |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 493 | You are on vessel B and vessel A desires to overtake you on your starboard side. After the vessels have exchanged one blast signals, you should _____. | hold course and speed | slow your vessel until vessel A has passed | alter course to the left | alter course to the left or right to give vessel A more sea room |
| 494 | You are operating a vessel through a narrow channel and your vessel must stay within the channel to be navigated safely. Another vessel is crossing your course from starboard to port, and you are in doubt as to her intentions. You _____. | are required to back down | should sound one short blast to show that you are holding course and speed | may sound the danger signal | must sound the danger signal |
| 495 | Your power driven vessel is meeting another vessel head-on. To comply with the rules, you should exchange _____. | one short blast, alter course to the left, and pass starboard to starboard | one short blast, alter course to the right, and pass port to port | two short blasts, alter course to the left, and pass starboard to starboard | two short blasts, alter course to the right, and pass port to port |
| 496 | Two vessels in a crossing situation have reached agreement by radiotelephone as to the intentions of the other. In this situation, whistle signals are _____. | required | required when crossing within one mile | not required, but may be sounded | required if crossing within half a mile |
| 497 | You are meeting another power driven vessel head-on and sound one short blast as a passing signal. The other vessel answers with two short blasts. What should be your next action? | Sound the danger signal. | Pass on the other vessel s starboard side. | Pass astern of the other vessel. | Hold your course and speed. |
| 498 | At night, a barge moored in a slip used primarily for mooring purposes shall _____. | show a white light at each corner | not be required to be lighted | show a flashing yellow light at each corner | show a red light at the bow and stern |
| 499 | A power-driven vessel, when leaving a dock or berth, is required to sound _____. | one prolonged blast | four short blasts | one long blast | No signal is required. |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 500 | You are on power driven vessel A and power driven vessel B desires to overtake you on the starboard side. After the vessels have exchanged one blast signals you should _____. | alter course to the left | slow your vessel until vessel B has passed | alter course to the left or right to give vessel B more sea room | hold course and speed |
| 501 | Your vessel must remain in a narrow channel for safe operation. Another vessel is crossing the channel from your starboard. You do not think she will pass safely. You MUST _____. | sound the danger signal | stop your vessel, since the other vessel has the right of way | sound one short blast of the whistle, and turn to starboard | stop your engines, and you may sound the danger signal |
| 502 | When power-driven vessels are in a crossing situation, one short blast by either vessel would mean _____. | I request a departure from the rules | I intend to leave you on my port side | I intend to hold course and speed | I intend to change course to starboard |
| 503 | Two power driven vessels are meeting on a clear day and will pass less than half a mile apart. In this situation whistle signals _____. | must be exchanged if passing agreements have not been made by radio | must be exchanged | may be exchanged | must be exchanged only if course changes are necessary by either vessel |
| 504 | A power-driven vessel intends to overtake another power-driven vessel on the overtaken vessel s port side. Which whistle signal should be sounded in order to state this intention? | 2 prolonged and 1 short blasts | 1 short blast | 2 prolonged and 2 short blasts | 2 short blasts |
| 505 | A power-driven vessel, when leaving a dock or berth, is required to sound _____. | one prolonged blast | two short blasts | one long blast | the danger signal |
| 506 | A light used to signal passing intentions must be an _____. | a searchlight or beam | an all-round white light | alternating white and yellow light | all-round white or yellow light |
| 507 | A vessel may use any sound or light signals to attract the attention of another vessel as long as _____. | the vessel signals such intentions over the radiotelephone | red and green lights are not used | it is one of those listed under Annex IV of the Collision Regulations | the signal cannot be mistaken for a signal authorized by the Rules |
| 508 | The light which may be used with a vessels whistle must be _____. | a white light | used only at night | used prior to sounding the whistle | used when the whistle is broken |

| | | | | | |
|---|---|---|---|---|---|
| 509 | Two power-driven vessels are crossing within one half mile of each other, with Vessel P as the stand-on vessel, and Vessel Q as the give-way vessel. Vessel P sounds two short blasts on the whistle. What signal should vessel Q sound? | Two short blasts | None of these | Five short and rapid blasts | One short blast |
| 510 | Vessel A, a power driven vessel underway, sights vessel B which is a vessel underway and fishing. Which statement is TRUE? | Vessel A must keep out of the way of vessel B because B is fishing. | Both vessels are required by the Rules to keep clear of each other. | Vessel A must keep out of the way of vessel B because B is to port. | Vessel B must keep out of the way of vessel A because A is to starboard. |
| 511 | Vessel X is overtaking vessel Y on open waters and will pass without changing course. Vessel X _____. | should sound the danger signal | should sound one long blast | will not sound any whistle signals | should sound two short blasts |
| 512 | When two vessels are in sight of one another and NOT in or near an area of restricted visibility, any of the following signals may be given EXCEPT _____. | one prolonged, one short, one prolonged, and one short whistle blasts | a light signal of at least five short and rapid flashes | two short whistle blasts | four short whistle blasts |
| 513 | Which signal is required to be sounded by a power-driven vessel ONLY? | A signal meaning, I am altering my course to starboard. | A signal meaning that the vessel sounding it is in doubt as to the other vessels actions. | A signal sounded when approaching a bend. | A signal meaning, I intend to overtake you on your starboard side. |
| 514 | Which signal is sounded ONLY by a vessel in sight of another and NOT in or near an area of restricted visibility? | One prolonged blast | One short blast | One short, one prolonged, and one short blast | Four short blasts |
| 515 | Which signal is sounded ONLY by a vessel in sight of another? | One short blast on the whistle | Four short blasts on the whistle | One short, one prolonged, and one short blast on the whistle | One prolonged blast on the whistle |
| 516 | Which signal may be sounded ONLY by vessels in restricted visibility? | At least five short and rapid blasts | Two short blasts | Four short blasts | One prolonged, one short, one prolonged, and one short blast, in that order |
| 517 | Which signal, other than a distress signal, can be used by a vessel to attract attention? | Searchlight beam | Burning barrel | Continuous sounding of a fog signal apparatus | Calling Mayday on the radiotelephone |

| | | | | | |
|---|---|---|---|---|---|
| 518 | Which vessel would NOT sound a fog signal of one prolonged and two short blasts? | A vessel sailing | A vessel not under command | A vessel constrained by her draft | A vessel being towed |
| 519 | Which whistle signal may be sounded by one of two vessels in sight of each other? | One prolonged blast | Four short blasts | One short blast | One short, one prolonged, and one short blast |
| 520 | You are in sight of a power-driven vessel that sounds two short blasts of the whistle. This signal means that _____. | the vessel is altering course to port | the vessel intends to leave you on her starboard side | you should alter course to port. | you should sound the danger signal |
| 521 | You are in sight of another vessel in a crossing situation, and the other vessel sounds one short blast. You are going to hold course and speed. You should _____. | answer with two short blasts | sound the danger signal | answer with one short blast | sound no whistle signal |
| 522 | You are underway on the high seas in restricted visibility. You hear a fog signal of one prolonged and two short blasts. It could be any of the following EXCEPT a vessel _____. | engaged in fishing | being towed | constrained by her draft | minesweeping |
| 523 | Your vessel is backing out of a slip in a harbor. Visibility is restricted. You should sound _____. | one prolonged blast only | one long blast only | one prolonged blast followed by three short blasts when leaving the slip | the danger signal |
| 524 | COLREG Rule No 35 specifies? | signals at anchor | proper look-out | sound signals during reduced visibility | safe speed during reduced visibility |
| 525 | The approach crossing TSS shall be: | diagonal | almost perpendicular | always with caution | parallel |
| 526 | The International Regulations for Preventing Collisions at Sea contain the requirements for _____. | signals that must be sounded when being towed in restricted visibility | minimum hawser lengths when being towed | lights that must be displayed on anchor buoys | mooring procedures for support vessels when transferring cargo |
| 527 | An overtaking situation at night would be one in which one vessel sees which light(s) of a vessel ahead? | Both sidelights | One sidelight, the masthead lights and stern light | Masthead lights and sidelights | Stern light |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 528 | It is an example of a vessel restricted in her ability to maneuver | vessel engage in dredging surveying or underwater operations | minesweeper | hospital ship | None of the stated options |
| 529 | Vessel when engaged in trawling, when net has come fast upon an obstruction may exhibit _____ | one red light (all round the horizon) | two red lights in a vertical line | one red light over white light in a vertical line | two white lights in a vertical line |
| 530 | An icebreaker assisting a vessel through an ice field would display a visual signal consisting of the code letter E (Echo) to signify that _____. | My vessel is stopped and making no way through the water | I am altering my course to port | I am operating astern propulsion | I am altering my course to starboard |
| 531 | An icebreaker assisting a vessel through an ice field would display a visual signal consisting of the code letter I (India) to signify that _____. | I am operating astern propulsion | I am altering my course to port | I am altering my course to starboard | My vessel is stopped and making no way through the water |
| 532 | An icebreaker assisting a vessel through an ice field would display a visual signal consisting of the code letter M (Mike) to signify that _____. | My vessel is stopped and making no way through the water. | I am altering my course to starboard. | I am altering my course to port. | I am operating astern propulsion. |
| 533 | An icebreaker assisting a vessel through an ice field would display a visual signal consisting of the code letter S (Sierra) to signify that _____. | I am altering my course to starboard. | My vessel is stopped and making no way through the water. | I am altering my course to port. | I am operating astern propulsion. |
| 534 | An icebreaker may use the code letter K to remind ships of their obligation to listen continuously on their radio. This signal may be made by any of the following EXCEPT _____. | radiotelephone | sound signal | light signal | visual signal |
| 535 | What is the daytime signal of a vessel at anchor? | The company flag | A special anchor flag | No particular | Anchor ball |
| 536 | A head-on or end-on situation shall be deemed to exist at night when a vessel sees the other vessel ahead, and | both sidelights are visible | the masthead lights of the other vessel are in line with one sidelight visible | all of the options | the masthead lights of the other vessel are not in line with both sidelights visible |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 537 | Which vessel is to keep out of the way of the others? | A vessel not under command | A vessel engaged in trawling | A vessel engaged in underwater operations | A vessel constrained by her draft |
| 538 | What lights must be shown on a barge being towed astern at night? | Sidelights and a stern light | A white light at each corner | A white light fore and aft | A stern light only |
| 539 | A vessel engaged in fishing during the day would show _____. | one black ball | a cone, apex downward | two cones with bases together | two cones, apexes together |
| 540 | Two navigational hazards are located near to each other, but each marked by an individual cardinal buoyage system. The buoys of one cardinal system may be identified from the other system by __. | one system using horizontal bands while the other system uses vertical stripes | the differing light colors | the difference in the periods of the light | one system having odd numbers while the other system has even numbers |
| 541 | What is the color of a west cardinal buoy? | Black bands with yellow bands above and below | Black and above and below yellow band | Black band below yellow band | Black band above yellow band |
| 542 | Which of the following features is not indicated by special marks? | Spoil grounds | Well defined channel | Cable or pipelines | Traffic separation |
| 543 | Which buoy is NOT numbered? | Preferred channel buoy | Red lighted buoy | Green gong buoy | Green can buoy |
| 544 | A symbol described as tint, 3 mm wide used in Traffic Separation Scheme (TSS) and between TSS and inshore traffic zone is called_____. | recommended routes | separation lines | separation scheme | established traffic flow |
| 545 | A system aimed at reducing risk of accidents including TSS 2-way routes, recommended tracks, areas to be avoided, inshore traffic zones, roundabouts, precautionary areas and deep water routes is called | Routing system | Ships routing | TSS | Separation zone or time |
| 546 | You are enroute to Jacksonville, FL, from San Juan, P.R. There is a fresh Nly wind blowing. As you cross the axis of the Gulf Stream you would expect to encounter _____. | cirrus clouds | smoother seas and warmer water | long swells | steeper waves, closer together |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 547 | You are enroute from Puerto Rico to New York. A hurricane makes up and is approaching. If the wind veers steadily, this indicates that your vessel is _____. | in the dangerous semicircle | in the navigable semicircle | directly in the path of the storm | in the storm center |
| 548 | Solid green arrows on the main body of a pilot chart indicate _____. | prevailing wind directions | probable surface current flow | shortest great circle routes | prevailing ocean current directions |
| 549 | General information on enroute weather and climate is found in _____. | the Sailing Directions and the Coast Pilot | a weather fax | the Local Notice to Mariners | the Light List |
| 550 | The safest and most prudent procedure to follow while navigating in the vicinity of a tropical cyclone is to _____. | batten down and prepare to ride out the storm | always navigate towards the coast by the most direct route | take positive steps to avoid it if possible | continue to navigate farther from the coast |
| 551 | You are planning a voyage from San Francisco to Japan. Which publication contains information on the ocean routes? | Coast Pilot | Sailing Directions (Enroute) | World Port Index | Sailing Directions (Planning Guide) |
| 552 | The Sailing Directions (Enroute) contain information on _____. | coastal anchorages | well-charted inner dangers | port facilities | offshore traffic separation schemes |
| 553 | You are planning a voyage from New York to Norway via the English Channel. Which publication contains information on the dangers to navigation in the English Channel? | Channel Pilots Guide | Coast Pilot | World Port Index | Sailing Directions (Enroute) |
| 554 | What is the purpose of the anti-clutter "sea" control on the radar? | Reduce the sea echoes | Remove wash return from the propeller | Intensify sea return | Increase brilliance of large echoes against sea |
| 555 | X-band radar is the name for _____ radar and S-band is the name for _____ radar. | 6 cm - 10 cm | 10 cm - 6 cm | 3 cm - 10 cm | 10 cm - 3 cm |
| 556 | What does RADAR stand for? | Radio detection and ranging | Radio detection and reconnaissance | Radio display and reconnaissance | Radio Director and reviewer |
| 557 | The components that generate the radio-frequency energy in the form of short powerful pulse is the: | Modulator | Receiver | Magnetron | Indicator |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 558 | What is the IMO requirement for ARPA detection? | Acquisition should be automatic | No special requirement | Performance not inferior to the radar display | Detection should be done manually |
| 559 | An increase in temperature with an increase in altitude would tend to cause: | Super-refraction | Sub-refraction | Attenuation | Diffraction |
| 560 | In a Polar region with very cold wind blowing over warmer sea, you would expect_____ . | Diffraction | Sub-refraction | Attenuation | Sub-refaction |
| 561 | A large ship close by may cause _____ . | Multiple echoes | Diffraction | Refraction | Increased range resolution |
| 562 | Which of the following radar displays is not stabilized? | North-up, Relative motion | North-up, True motion | Ship's head-up, Relative motion | True motion |
| 563 | Does the COLREGS give any preference to ships equipped with ARPA? | No | Yes | Only during reduced visibility | Only in Good visibility |
| 564 | With regards to ARPA, what does the "lost target" warning tell? | Display failure | Computer failure | Target can no longer be plotted | Radar failure |
| 565 | It is the term used at the instant an electro-magnetic wave is passing by an obstruction between two places? | Diffraction | ducting | Attenuation | Refraction |
| 566 | What is equivalent to one complete oscillation? | Frequency | amplitude | Cycle | One wavelength |
| 567 | An indirect radar echo is caused by a reflection of the main lobe of the radar beam of the observer's vessel. Which of the following is NOT a characteristic of indirect echoes? | They always appear on a bearing of 90º from the true bearing of the contact. | The indirect echoes usually appear in shadow sectors | When plotted, their movements are usually abnormal | Their bearing is almost constant, even when the true bearing of the contact changes appreciably. |
| 568 | When using the ARPA in heavy rain, which action should you take? | Increase the range of the inner and outer guard rings. | Increase the radar gain to pick up weak echoes through the rain. | Navigate as though the effective range of the radar has been reduced. | Increase the STC setting to reduce close-in spurious signals. |
| 569 | This is a radar transponder which emits a characteristics signal when triggered by ship's radar | None of the stated options | RACON | RECON | BEACON |
| 570 | How can rescue personnel detect that a SART is transmitting in the immediate vicinity? | The SART's blips on the PPI will become arcs and eventually become concentric circles. | The SART can provide an approximate location to within a two nautical mile radius, per IMO standards. | The SART signal appears as a target which comes and goes; the effect of heavy swells on a SART. | The DSC unit will react to the SART's signal and respond with the two-tone alarm. |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 571 | When using an ARPA, what should you consider in order to evaluate the information displayed? | You cannot determine if a small target has been lost due to sea return. | The target vessel's generated course and speed are based solely on radar inputs. | The trial maneuver feature will automatically determine a course that will clear all targets. | Navigational constraints may require a target vessel to change course. |
| 572 | The radar control that reduces weak echoes out to a limited distance from the ship is the _____._ | brilliance control | sensitivity time control (sea-clutter control) | fast time control | receiver gain control |
| 573 | Which ARPA data should you use in order to determine if a close quarters situation will develop with a target vessel? | Relative track information | Set and drift of the current | Predicted time of CPA | Initial range of acquisition |
| 574 | Your ARPA has automatic speed inputs from the log. Due to currents, the log is indicating a faster speed than the speed over the grounds. What should you expect under these circumstances? | The generated CPA will be than the actual CPA | The range on initial target acquisition will be less than normal | The generated TCPA will be later than the actual TCPA | The targets true course vector will be in error. |
| 575 | To ensure that a RACON signal is visible in the 3cm. radar, one should ensure that the: | gain control should be placed on maximum | rain clutter control should be placed on low if necessary or off | radar should be stabilized, head up | 10 cm radar should be placed on standby or turned off |
| 576 | As per Solas V regulations safety of navigation a ships of 10,000 gross tons and above shall be fitted, with radar capable of operating in the: | 12 GHz frequency band | 10 GHz frequency band | 9 GHz frequency band | 16 GHz frequency band |
| 577 | The common frequencies used in merchant radar are approximately: | 30,000 cycles | 3,000 and 9,000 mega cycles | 30,000 kilocycles | 3,000 and 9,000 micro cycles |
| 578 | What does an automatic identification system (AIS) transponder use to transmit and receive information broadcasts? | 3000 MHz and 9200 MHz | 2182 KHz and 2187.5 KHz | 1575.42 MHz and 1227.6 MHz | 156.525 MHz, 161.975 MHz and 162.025 MHz |

| | | | | | |
|---|---|---|---|---|---|
| 579 | If the Radar scanners of one vessel are in the same horizontal plane as the cargo deck of the other during transfer operations, which type of radar emissions would pose a greater danger of the induced ignition of flammable vapors? | a 10 cm radar | Both a 10 and a 3 cm radar | a 3 cm radar | Neither a 10 or a 3 cm radar |
| 580 | Which is the most accurate position by radar fixes? | intersection of two radar bearings | two radar ranges | a radar range and a radar bearing | radar range and visual bearings |
| 581 | This type of radar enhance to maximum visibility in marginal weather condition. | S-band | X-band | ARPA | Z-band |
| 582 | Echoes in radar from two or more targets close to each other at the same range may emerge to form a single echo. The ability of a radar to separate this is called: | attenuation in bearing | refraction in bearing | diffraction in bearing | resolution in bearing |
| 583 | The ability of a radar to separate targets close together on the same bearing is called: | resolution in range | diffraction in range | attenuation in range | refraction in range |
| 584 | Which is the most accurate position by radar fixes? | intersection of two radar bearings | radar range and visual bearings | two radar ranges | a radar range and a radar bearing |
| 585 | This type of radar enhance to maximum visibility in marginal weather condition. | ARPA | S-band | Z-band | X-band |
| 586 | Echoes in radar from two or more targets close to each other at the same range may emerge to form a single echo. The ability of a radar to separate this is called: | resolution in bearing | diffraction in bearing | attenuation in bearing | refraction in bearing |
| 587 | The ability of a radar to separate targets close together on the same bearing is called: | attenuation in range | refraction in range | resolution in range | diffraction in range |
| 588 | The characteristics on which bearing resolution depends is: | horizontal beam width | scanner speed of rotation | bearing to the target | range |
| 589 | Which indicates that your radar needs maintenance? | Indirect echoes | Blind sector | Serrated range rings | Multiple echoes |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 590 | Which radar control is used to shorten all echoes on the display and reduces the clutter caused by the snow or rain? | fast time constant | gain control | | brilliance |
| 591 | When navigating in coastal waters which of the following is not considered as a factor? | Position fixes should be taken at a regular interval | Charts used should be the most suitable for the planned passage | Radar is only supplement to visual fixing | OOW should be able to identify all relevant navigational marks |
| 592 | Raster-scan chart data is: | the only format recognized by IMO/IHO | composed of files that are smaller than vector files | organized into many separate files | a digitized "picture" of a chart in one format and one layer |
| 593 | This may occur when a strong echo is received from another ship at close range. | multiple echoes | false echo | diffraction | clutter |
| 594 | This is the decrease in the strength of a radar wave resulting from absorption, scattering and reflection by the medium as it passes the atmosphere. | Diffraction | Refraction | Persistence | Attenuation |
| 595 | The unit which sends returning target echoes to the receiver is the: | scanner unit | transmitter unit | display unit | power supply unit |
| 596 | What do you call the marker in the radar PPI which the operator can put in any direction to watch the incoming target? | PPI | EBL | Guard zone | Plotter |
| 597 | The difference in intensity of the illumination of the radar scope between radar images and the background of the screen. | contrast | brightness | focus | brilliance |
| 598 | In confined waters which of the following equipment becomes more reliable in obtaining vessel's position? | ECDIS | Radar X band and visual method | Radar S band and visual method | GPS |
| 599 | An identification of ships, coastal areas and other targets, good range and range resolution are important because they: | increase the range | make presentation brighter | help indicate maximum detail | decrease the range |
| 600 | Most commonly, ship's radar operates in the: | X- BAND | Q-BAND | L - BAND | S-BAND |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 601 | Which of the following is the best to obtain vessel's position during poor visibility? | Loran | Decca | Radar | GPS |
| 602 | Which bridge equipment is used in determining the distance to and direction of objects by sending out a beam of microwave radio energy and detecting the return reflections? | ECHO-SOUNDER | RADAR | LORAN | GPS |
| 603 | While underway, a vessel over 100,000 gross tons with an automatic identification systems (AIS) is expected to broadcast all of the following information every 1 to 10 seconds EXCEPT: | rate of turn | navigational status | name of vessel | ship's heading |
| 604 | On a relative motion radar, the closest point of approach (CPA) of a contact is determined: | after the contact has been marked at least twice | immediately when the contact is noted on radar | only if the radar scope is watched constantly | by an occasional glance at the radar |
| 605 | When may the automatic identification system (AIS) be switched off? | At anytime as long as it is properly logged | Only when the vessel is at anchor or in port | At the Master's professional judgement | Under no circumstance |
| 606 | This radar unit performs a dual function both in transmission and reception. | scanner | reflector | oscillator | duplexer |
| 607 | Navigation at coastal waters, radar is generally used to supplement | Echo sounder | Parallel indexing | Visual fixing | GPS |
| 608 | The intensity of the election beam in the C.R.T. is controlled by: | varying the potential on the grid | the action of the first anode | passing a current through the deflection coil | a signal from the time unit |
| 609 | The minimum range at which a target can be detected is basically determined by which of the following? | persistence | pulse length | rotation rate | pulse repetition rate |
| 610 | The transmission time duration of a single pulse of radio-frequency energy is a function of the: | pulse length | pulse repetition rate | persistence | resolution |
| 611 | In marine navigation, radar signal is: | pulse generated | antenna generated | pulse modulated | circuit generated |
| 612 | PPI display of a radar means: | plan position indicator | perimeter position indicator | pulse position indicator | practical power indicator |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 613 | The description "Racon" beside an illustration on a chart would mean a: | circular radio beacon | radar transponder beacon | radar conspicuous beacon | radar calibration beacon |
| 614 | Which of the following is NOT recommendable to obtain vessel's position as radar target? | Floating aids | Racons | Ramark | Lighthouse |
| 615 | Which of the following is correct concerning RAMARK? | Both B and C | Neither B or C | RAMARK is a radar transponder which emits a characteristics signal when triggered by a ship's radar | RAMARK is a radar beacon which transmits either continuously or at intervals |
| 616 | This is defined as the radar control that reduces weak echoes to a limited distance from the ship: | sensitivity time control (sea-clutter control) | brilliance control | receiver gain control | fast time constant (differentiator) |
| 617 | The scattering and absorption of the energy in the radar beam as it passes through the atmosphere is called: | diffraction | refraction | attenuation | resolution |
| 618 | Which is the name of movable, radial guide line used to measure direction in the radar? | VRM | PPI | RML | Cursor |
| 619 | Countries are producing unique digital charts based on their interpretation of IHO standards: | S-52 standards | S-100 standards | S-57 standards | S-75 standards |
| 620 | Which device emits a characteristic signal when triggered by a ship's radar? | RACON | Beacons | SART | RAMARK |
| 621 | This safety device when activated in a distress situation responds to radar interrogation by transmitting a swept frequency signal which generates 12 blips code on a radar screen. | Smoke signal | Epirb beacon | All of these | Search and rescue radar transponder |
| 622 | Which term refers to the combination of a Radar transmitter and receiver? | ARPA | T/R box | transceiver | remitter |
| 623 | Spoking would be indicated on the radar receiver by: | random, pie-shaped wedges on the PPI | no targets showing up beyond 3 miles | targets appearing 180 degrees from proper bearing | spiral lines or dots on the PPI |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 624 | In ARPA, which of the following is TRUE? | in a collision course observed in radar during fog, the vessel which has the right of way should continue her course and speed | the nearest target on the radar screen is the most critical one | once the targets are properly marked, course and speed of same can be deduced from these observations | successive bearings of a pip in radar does not necessarily give the course and speed of that pip |
| 625 | Which statement is TRUE concerning a vessel equipped with operational radar? | She must use this equipment to obtain early warning of risk collision | The radar equipment is only required to be used in restricted visibility | The use of a radar excuses a vessel from the need of a look-out | The safe speed of such a vessel will likely be greater than that of vessels without radar |
| 626 | The relative motion line, when extended past the represented position of the observer's ship, shows: | line of true movement of other ship | true speed of other ship | true course of other ship | CPA |
| 627 | This is a shadow area when ship structures at equal height with the scanner, causing areas behind scanner to be un-scanned. | blind sector | reflected sector | tuned | shadowed sector |
| 628 | Incoming target echoes are detected by the: | I.F amplifier | mixer crystal | Local oscillator | video amplifier |
| 629 | A choppy sea produces this unwanted echo. | Sea Clutter | Second trace echoes | Weather echoes | Normal radar echoes |
| 630 | The following are unwanted echoes, except: | Sea Cluster | Second Trace Echoes | Weather Echoes | Normal Radar Echoes |
| 631 | A useful method of monitoring cross track tendency in both poor and good visibility is | parallel indexing | maneuvering board | all of these | arpa mapping |
| 632 | Echoes in radar from two or more targets close to each other at the same range may emerge to form a single echo. The ability of a radar to separate this is called _____. | attenuation in bearing | resolution in bearing | refraction in bearing | diffraction in bearing |
| 633 | If a layer of cold moist air over rides a shallow layer of warm dry air which of the following may occur? | Sub-refraction | normal refraction | Increase of radar range | Optical horizon |
| 634 | If you turn on the fast time constant differentiator control of a radar it will: | suppress weak targets to a limited distance from the ship | reduce the beam width to provide a map-like presentation for navigation | reduce clutter for the entire PPI by shortening the echoes | enhance the weak target echoes and brighten them on the PPI |

| | | | | | |
|---|---|---|---|---|---|
| 635 | In confined waters WHICH of the following equiptment becomes more reliable in obtaining vessels position? | Radar X band and visual method | GPS | Radar S band and visual method | ECDIS |
| 636 | In modern fathometers the sonic or ultrasonic sound waves are produced electrically by means of a _____. | transceiver | transducer | transmitter | amplifier |
| 637 | Navigation at coastal waters radar is generally used to supplement the _____. | Visual fixing | parallel indexing | GPS | Echo sounder |
| 638 | Radar makes the most accurate determination of the _____. | size of a target | direction of a target | distance to a target | shape of a target |
| 639 | The ability of a radar to distinguish separate targets on the same bearing but having small differences in range is called which of the following? | Range resolution | Ranging resolution | Range elongation | Propagation |
| 640 | The characteristics on which bearing resolution depends is _____. | scanner speed of rotation | bearing to the target | horizontal beam width | range |
| 641 | The Component of the IBS that allows a navigator to see an integrated navigation and tactical display and to avoid navigational hazard is: | RADAR | System display unit | Control system | Tactical display unit |
| 642 | The radar control used to reduce sea return at close ranges is the _____. | gain control | fast time constant | sensitivity time control | pulse length control |
| 643 | What is the meaning of the flashing diamond in ARPA? | lost target | collision target | new target | target acquired |
| 644 | What is the purpose of digitizing the radar echoes in ARPA? | Increase accuracy of the system | The ARPA tracking only works with digital signals | Reduce number of radar echoes | No special purpose |
| 645 | What is TRUE of the history display of a targets past positions on an ARPA? | In the true presentation it provides a quick visual check to determine if a vessel has changed course. | It provides a graphic display to emphasize which vessel is on a collision course. | The display is one of the primary inputs and must be in use when using the trial maneuver capability. | It provides a graphic display of a target vessels relative course speed and CPA. |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 646 | When radar waves are trapped in a layer of the atmosphere called a surface radio duct which of the following would be created? | Decrease of radar range | Large loss of energy to the radio waves | Radar range of energy would remain | Increase of radar range |
| 647 | Which component of the RADAR system must a returning echo strikes first? | Antenna | Magnetron | Receiver | Wave guide |
| 648 | Which general statement concerning radar is FALSE? | Radar should be checked regularly during clear weather to ensure that it is operating properly. | The ability of radar to detect objects is unaffected by weather conditions. | Radar bearings are less accurate than radar ranges. | Raising the antenna height increases the radar range. |
| 649 | Which statement is TRUE concerning night effect and the reception of radio signals? | Night effect is most prevalent late at night | During night effect polarization is at a minimum | Night effect is caused by rapid changes in the ionosphere | Night effect is caused by all of the polarized ground waves being vertical |
| 650 | Which tend to cause the rapid decrease of temperature as the altitude increases? | Super-refraction | Attenuation | Sub-refraction | Diffusion |
| 651 | Which term refers to the bending of the wave as it passes an obstuction? | Diffraction | False Echo | Multiple Echoes | Clutter |
| 652 | You are underway at 10 knots. At 1800 you note a radar contact dead ahead at a range of 10 miles. At 1812 the contact is dead ahead at a range of 8 miles. The estimated speed of the contact is _____. | 15 knots | 5 knots | dead in the water | 10 knots |
| 653 | You are underway at 5 knots and see on your radar a contact 10 miles directly astern of you. 12 minutes later the contact is 8 miles directly astern of you. What is the estimated speed of the contact? | 15 knots | Dead in the water | 1 knot | 10 knots |
| 654 | A Doppler log in the bottom return mode indicates the _____. | depth of the water | bottom characteristics | speed over the ground | velocity of the current |
| 655 | A Doppler log in the volume reverberation mode indicates _____. | speed through the water | speed being made good | the set of the current | the depth of the water |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 656 | A Doppler speed log indicates speed over ground _____. | in the volume reverberation mode | at all times | in the bottom return mode | only when there is no current |
| 657 | A Doppler speed log indicates speed through the water _____. | in the volume reverberation mode | in the bottom return mode | at all times | only when there is no current |
| 658 | A line of position derived by radar range from an identified point on a coast will be a(n) _____. | parabola | line parallel to the coast | straight line | arc |
| 659 | A marine radar system for surface navigation must be fitted on all ocean or coastwise vessels of over _____. | 1 600 GT | 1 500 GT | 1 400 GT | 1 700 GT |
| 660 | A navigator fixing a vessel s position by radar _____. | must use information from targets forward of the beam | can use radar information from one object to fix the position | should only use radar bearings when the range exceeds the distance to the horizon | should never use radar bearings |
| 661 | A radar based constant up-date of cross track tendency. | Parallel Indexing | Clearing bearing | Track Made Good | Distance Off Danger |
| 662 | A radar contact will remain stationary on a relative motion radar display only when it is _____. | at the same speed as your vessel | on a reciprocal course at the same speed as your vessel | on the same course and speed as your vessel | on the same course as your vessel |
| 663 | A radar display in which North is always at the top of the screen is a(n) _____. | stabilized display | unstabilized display | composition display | relative display |
| 664 | A radar display which is oriented so that north is always at the top of the screen is called a(n) _____. | composite display | unstabilized display | stabilized display | relative display |
| 665 | A radar range to a small charted object such as a light will provide a line of position in which form? | Arc | Straight line | Parabola | Hyperbola |
| 666 | A wide vertical scanner beam is important in heavy weather to _____. | lower refraction | increase the range | decrease sea return | reduce loss of beam targets |

| | | | | | |
|---|---|---|---|---|---|
| 667 | After sailing for several minutes (making 10 knots through the water) and in constant monitoring of your radar screen you noticed that a contact has remained in the same position relative to yours; what could be the possible conclusion of the scenario? | the contact is on the same course and speed as your vessel | the contact is dead in the water | the contact is on a reciprocal course at the same speed as your vessel | the radar is showing false echoes and is probably defective. |
| 668 | An increase in temperature with an increase would tend to cause _____. | attenuation | sub-refraction | super-refraction | diffusion |
| 669 | An upper layer of warm dry air over a surface layer of a cold moist air causes which of the following? | super-refraction | normal refraction | sub-refraction | propagation |
| 670 | Coral atolls or a chain of islands at right angles to the radar beam may show as a long line rather than as individual targets due to _____. | limitations on range resolution | the pulse length of the radar | the effects of beam width | the multiple-target resolution factor |
| 671 | Gibraltar port Control or Lloyd signal station is controlled by United Kingdom. They normally monitor the vessel thru radar surveilance. What particular questions they do not require? | Vessel s name Nationality | Name of Ownerws/Operators | Vessels IMO number | If any dangerous cargo on board & quantity |
| 672 | How many targets can an Electronic Plotting Aid (EPA) track at the same time? | 20 | 10 | 5 | 2 |
| 673 | If a layer of cold moist air over rides a shallow layer of warm dry air which of the following may occur? | Sub-refraction | normal refraction | Increase of radar range | Optical horizon |
| 674 | If the Radar scanners of one vessel are in the same horizontal plane as the cargo deck of the other during transfer operations which type of radar emissions would pose a greater danger of the induced ignition of flammable vapours? | a 3 cm radar. | a 10 cm radar. | a 6 cm radar. | a 9 cm radar. |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 675 | The bending of a wave as it passes an obstruction is called _____. | diffraction | refraction | attenuation | persistence |
| 676 | What is the effect of super refraction? | Bend radar rays downward and decrease radar range | Bend radar rays upward and increase radar range | Bend radar rays downward and increase radar range | Bend radar rays upward and decrease radar range |
| 677 | A useful method of monitoring cross track tendency in both poor and good visibility is | maneuvering board | parallel indexing | arpa mapping | all of these |
| 678 | If there is any doubt as to the proper operation of a radar, which statement is TRUE? | A radar range compared to the actual range of a known object can be used to check the operation of the radar | The radar resolution detector must be energized to check the radar | Only a radar expert can determine if the radar is operating | All radars have indicator lights and alarms to signal improper operation |
| 679 | Which statement concerning the operation of radar in fog is TRUE? | Radar ranges are less accurate in fog | A sandy beach will show up clearer on radar than a rocky cliff | Navigation buoys will always show up on radar | Small wooden boats may not show up on radar |
| 680 | The 10 cm radar as compared to a 3 cm radar of similar specifications will _____. | have a wider horizontal beam width | have more sea return during rough sea conditions | be more suitable for river and harbor investigation | provide better range performance on low lying targets during good weather and calm seas |
| 681 | If you turn on the fast time constant differentiator control of a radar, it will: | reduce the beam width to provide a map-like presentation for navigation | enhance the weak target echoes and brighten them on the PPI | suppress weak targets to a limited distance from the ship | reduce clutter for the entire PPI by shortening the echoes |
| 682 | In order to insure that a RACON signal is displayed on the radar, you should __. | turn off the interference controls on the radar | switch off rain clutter control | adjust the effect of beam width | adjust the gain and brilliance |
| 683 | The PPI display of a radar mean ____. | practical power indicator | plan position indicator | pulse position indicator | perimeter position indicator |
| 684 | What is the effect of super refraction? | Bend radar rays downward and decrease radar range. | Bend radar rays upward and decrease radar range. | Bend radar rays downward and increase radar range. | Bend radar rays upward and increase radar range. |
| 685 | Surfaced radio ducts usually occur over land, at what time of the day? | night time | daytime | noontime | anytime |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 686 | An indirect radar echo is a cause by a reflection of the main lobe of the radar beams off the observers vessel. Which of the following is NOT a characteristics of indirect echoes? | Their bearing is almost constant, even when the true bearing of the contact changes appreciably | They always appear on a bearing of 90 degrees from the true bearing of the contact | The indirect echoes usually appear in shadow sectors | When plotted, their movements are usually abnormal |
| 687 | A navigator fixing a vessels position by radar _____. | should never use radar bearings | must use information from targets forward of the beam | can use radar information from one object to fix the position | should only use radar bearings when the range exceeds the distance to the horizon |
| 688 | A radar display in which north is always at the top of the screen is called a (n) | stabilized display | relative display | composite display | unstabilized display |
| 689 | The closest point of approach (CPA) of a contact on a relative motion radar may be determined _____. | only if the radar scope is watched constantly | after the contact has been marked at least twice | by an occasional glance at the radar | immediately when the contact is noted on radar |
| 690 | When using a radar in an unstabilized mode, fixes are determined most easily from _____. | ranges | center bearings | objects that are close aboard | tangent bearings |
| 691 | Your radar is set on a true motion display. Which of the following will appear to move across the PPI scope. | Echo from a ship at anchor | Own ships marker | all of the options | Echoes from land masses |
| 692 | Your radar displays your ship off center. As you proceed on your course, your ships marker moves on the PPI scope while echoes form land masses remain stationary. What is this display called? | true motion | head up | stabilized display | off center |
| 693 | You have been observing your radar screen and notice that a contact on the screen has remained in the same position, relative to you, for several minutes. Your vessel is making 10 knots through the water. Which statement is TRUE? | The contact is on a reciprocal course at the same speed as your vessel | The radar is showing false echoes and is probably defective | The contact is dead in the water | The contact is on the same course and speed as your vessel |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 694 | Your radar indicates a target, however, there is no visible at the point indicated. At large mountain, approximately 50 miles away on the same bearing as the target is bearing the horizon. You should suspect the radar target is caused by | ducting | Ionospheric skip waves | sub-refraction | a submerged submarine |
| 695 | You are scanning the radar screen for a buoy fitted with racon. How should this signal appear on the PPI display? | As a broken line from center of PPI to the target | Starting with a dot and extending radially inward from the target | Starting with a dash and extending to the right of the target | Starting with a dash and extending radially outward from the target |
| 696 | Which general statements concerning radar is FALSE? | radar should be checked regularly during clear weather to ensure that it is operating properly | raising the antenna height increases the radar range | the ability of radar to detect objects is unaffected by weather conditions | radar bearings are less accurate than radar ranges |
| 697 | This is a radar transponder which emits a characteristics signal when triggered by ships radar | BEACON | RECON | None of the stated options | RACON |
| 698 | A knowledge of the limitations of a radar equipment being used on a vessel is essential to enable the observer to estimate the danger of failure _____. | to detect targets | to distinguish between targets | to interpret data provided by ARPA | to acquire targets |
| 699 | The ARPA may swap targets when automatically tracking if two targets _____. | are tracked on the same bearing | are tracked at the same range | are tracked on reciprocal bearings | pass close together |
| 700 | Which ARPA data should you see in order to determine if a close quarters situation will develop with a target vessel? | relative track information | predicted time of CPA | set and drift of the current | initial range of acquisition |
| 701 | What is TRUE of the history display of a targets past positions on an ARPA? | the display is one of the primary inputs and must be in use when using the trial maneuver capability | it provides a graphic display of a target vessels relative course, speed and CPA | In the true presentation, it provides a quick visual check to determine if a vessel has changed course | it provides a graphic display to emphasize which vessel is on a collision course |

| | | | | | |
|---|---|---|---|---|---|
| 702 | What will cause the ARPA to emit a visual alarm, audible alarm, or both? | A target being initially detected within a guard zone | A tracked target entering your preset CPA-TCPA limits | An acquired target entering into a guard zone | A tracked target lost for one radar scan |
| 703 | What will cause the ARPA to emit a visual alarm, audible alarm or both? | an acquired target entering into a guard zone | a tracked target lost for one radar scan | a target being initially selected within a guard zone | a tracked target entering your preset CPA-TCPA limits |
| 704 | A type of radar required so the maximum visibility in marginal conditions is available is called? | S-band | X-band | Tri-band | Q-band |
| 705 | When fixing a vessel position by radar, a navigator: | should take as many bearings as he can | should take bearings only on stabilized mode | should take bearings only on un-stabilized mode | should use radar info from one object to fix the position |
| 706 | If there is any doubt as to the proper operation of a radar, which statement is TRUE? | A radar range compared to the actual range of a known object can be used to check the operation of the radar | The radar resolution detector must be energized to check the radar | Only a radar expert can determine if the radar is operating | All radars have indicator lights and alarms to signal improper operation |
| 707 | You are underway at 10 knots. At 1800 you note a radar contact dead ahead at a range of 10 miles. At 1812 the contact is dead ahead at a range of 8 miles. The estimated speed of the contact is _____. | 5 knots | 15 knots | dead in the water | 10 knots |
| 708 | You are underway at 5 knots and see on your radar a contact 10 miles directly astern of you. 12 minutes later, the contact is 8 miles directly astern of you. What is the estimated speed of the contact? | 15 knots | Dead in the water | 1 knot | 10 knots |
| 709 | The radar control that reduces weak echoes out to a limited distance from the ship is the _____. | receiver gain control | fast time constant ( differentiator ) | brilliance control | sensitivity time control ( sea-clutter control ) |
| 710 | When using a radar in a unstabilized mode, fixes are determined most easily from _____. | ranges | center bearings | tangent bearings | objects that are close aboard |
| 711 | Coral atolls, or a chain of islands at right angles to the radar beam, may show as a long line rather than as individual targets due to _____. | the multiple-target resolution factor | the pulse length of the radar | the effects of beam width | limitations on range resolution |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 712 | You are approaching a light fitted with a RACON. The light may be identified on the radar by _____. | a coded signal appearing on the same bearing at a greater range than the light | a dashed line running from the center of the scope to the light | an audible signal when the sweep crosses the light | a circle appearing on the scope surrounding the light |
| 713 | A line of position derived by radar range from an identified point on a coast will be a(n) _____. | line parallel to the coast | parabola | arc | straight line |
| 714 | With regards to ARPA, what does the lost target warning tell? | display failure | target can no longer be plotted | computer failure | radar failure |
| 715 | What is the purpose of digitizing the radar echoes in ARPA? | Increase accuracy of the system | No special purpose | Reduce number of radar echoes | The ARPA tracking only works with digital signals |
| 716 | What is the IMO requirement for ARPA detection? | Detection should be done manually | Detection should be done automatically | Performance not inferior to radar display | No special requirement |
| 717 | What is the meaning of the flashing diamond in ARPA? | lost target | new target | target acquired | collision target |
| 718 | If you input gyro course to the ARPA, what can you expect? | Error in other ships calculated speed | Error in other ships speed | Error in other ships calculated range | No problem |
| 719 | In ARPA, how many targets are the IMO minimum continuously tracking requirements? | 20 targets | 30 targets | 50 targets | 10 targets |
| 720 | With regards to ARPA, what is the difference between a tracking gate and a tracking window? | The tracking window is more accurate | The tracking gate is longer | The tracking gate is more accurate | It is the same thing |
| 721 | What is the meaning of XXT at the bottom of the display in ARPA? | ARPA in trial mode | Acquisition area active | Lost target | Approaching danger area |
| 722 | What is the most used geographical presentation of target speed and course in an ARPA? | Displaying predicted areas of danger | Relative or true speed vector | Digital presentation | Displaying predicted position areas |
| 723 | Your ARPA has been tracking a target and has generated the targets course and speed. The radar did not receive a target echo on its last two scans due to the weather. What should you expect under these circumstances? | The ARPA will give an audible and / or visual lost target alarm. | The ARPA has lost all memory of the target and must recompute the target data. | The ARPA will generate data based on sea return echoes from the vicinity where the target was lost. | The ARPA will generate data as if the target is still being tracked by radar. |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 724 | Vessels required to have an Automatic Radar Plotting Aid must have a device to indicate the_____. | speed of the vessel over the ground or through the water | distance to the next port | time of the next navigational satellite pass | ETA to the next port |
| 725 | What is the IMO minimum range requirement for ARPA? | 3, 6 and 18 NM | 1.5, 3 and 12 NM | 6, 12 and 24 NM | 3, 6 and 12 NM |
| 726 | Which ARPA data should you use in order to determine if a close quarter situation will develop with a target vessel? | Relative track information | Predicted time of CPA | Initial range of acquisition | Set a drift of the current |
| 727 | When using the ARPA in heavy rain, which action should you take? | Increase the STC setting to reduce close-in spurious signals. | Increase the range of the inner and outer guard rings. | Increase the radar gain to pick up weak echoes through the rain. | Navigate as though the effective range of the radar has been reduced. |
| 728 | The ARPA may swap targets when automatically tracking if two targets | pass close together | are tracked on the same bearing | are tracked on reciprocal bearings | are tracked at the same range |
| 729 | When using an ARPA, what should you consider in order to evaluate the information displayed? | The trial maneuver feature will automatically determine a course that will clear all targets. | You cannot determine if a small target has been lost due to sea return. | Navigational constraints may require a target vessel to change course. | The target vessels generated course and speed are based solely on radar inputs. |
| 730 | Your ARPA has automatic speed inputs from the log. Due to currents, the log is indicating a faster speed than the speed over the grounds. What should you expect under these circumstances? | The targets true course vector will be in error. | The range on initial target acquisition will be less than normal | The generated CPA will be less than the actual CPA | The generated TCPA will be later than the actual TCPA |
| 731 | Your ARPA has been tracking a target and has generated the targets course and speed. The radar did not receive a target echo on its last two scans due to the weather. What should you expect under these circumstances? | the ARPA will generate date based on sea return | the ARPA will generate date as if the target was still being tracked by radar | the ARPA will give an audible and/or visual lost target alarm | the ARPA has lost all memory of the target and must recomputed the target date |
| 732 | With regards to ARPA, what does the lost target warning tell? | Display failure | Radar failure | Computer failure | Target can no longer be plotted |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 733 | Your ARPA has automatic speed inputs from the log. Due to currents, the log is indicating a faster speed than the speed over the ground. What should you expect under these circumstances? | The targets true course vector will be in error. | The generated CPA will be less than the actual CPA. | The generated TCPA will be later than the actual TCPA. | The range of initial target acquisition will be less than normal. |
| 734 | Your ARPA has two guard zones. What is the purpose of the inner guard zone? | Sound an alarm for targets first detected within the zone. | Guard against target loss during critical maneuvering situations. | Warn of small targets that are initially detected closer than the outer guard zone. | Alert the watch officer that a vessel is approaching the preset CPA limit. |
| 735 | What is TRUE of the history display of a targets past positions on an ARPA? | In the true presentation, it provides a quick visual check to determine if a vessel has changed course. | It provides a graphic display to emphasize which vessel is on a collision course. | The display is one of the primary inputs and must be in use when using the trial maneuver capability. | It provides a graphic display of a target vessels relative course, speed, and CPA. |
| 736 | What does "ECDIS" mean? | Elecronic chart display and information system | Electronic chart data information system | Electronic chart digital and information system | Electronic chart direction and injection system |
| 737 | ECDIS is set with performance standard by IMO called: | TX 50 | DT 40 | DX 90 | DP 90 |
| 738 | This is the ship's electronic data base used in the ECDIS Sytem | maps | Digital Chart | Electronic Nautical Chart | Chart data base |
| 739 | The Component of the IBS which contains the heart of the whole sysytem is the: | Chart data base | Planning station | Control system | RADAR |
| 740 | The Component of the IBS that allows a navigator to see an integrated navigation and tactical display and to avoid navigational hazard is: | System display unit | Tactical display unit | Control system | RADAR |
| 741 | ECDIS must have the capability to preserve the record of the track for the previous _____. | 6 hours | 12 hours | 24 hours | 18 hours |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 742 | Which of the following statements is TRUE regarding automatic identification systems (AIS)? | AIS can be used to make passing arrangements via ship-to-ship text massaging thus relieving a vessel operator from making such arrangements via bridge-to-bridge radiotelephone or signaling intent to pass via whistle signals. | AIS cannot be used to make passing arrangements because the system is not capable of this type of ship-to-ship communications. | AIS can be used to make passing arrangements via ship-to-ship text messaging but a vessel operator is not relieved from the requirement to sound whistle signals or make arrangements via bridge-to-bridge radiotelephone. | AIS cannot be used to make passing arrangements because the ship-to-ship text messaging feature is for emergency use only. |
| 743 | An ECDIS is required to display which information? | Waypoints | Meteorological data | Radar targets | Soundings |
| 744 | Which of the following statements is TRUE regarding automatic identification systems (AIS)? | AIS will not provide information on another vessel if that vessel is indistinguishable in radar sea clutter. | AIS provides near real-time information regarding another vessel's speed over ground and heading regardless of visibility. | AIS can be relied upon as the sole means to determine course changes due to other AIS equipped traffic. | AIS is designed to replace ARPA, maneuvering boards, and visual bearings as a means to ascertain the risk of collision. |
| 745 | Chart information details to be used in ECDIS should be the latest edition of information originated by a government-authorized hydrographic office and conform to the standards of (the) _____. | NASA | US Coast Guard | International Hydrographic Organization | International Maritime Organization |
| 746 | The database information that should be shown when a chart is first displayed on ECDIS is the _____. | standard display information | chart display information | system electronic nautical chart | display base information |
| 747 | Which data must ECDIS be able to record at one-minute intervals? | Shaft RPM | Course made good history | Estimated time of arrival | Speed through the water |
| 748 | Which information must automatic identification systems (AIS) automatically provide to appropriately equipped shore stations, vessels and aircraft? | Vessel's course | ETA | Destination | Draught |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 749 | While underway, a vessel over 100,000 gross tons wi th an automatic identification systems (AIS) is expected to broadcast all of the following information every 1 to 10 seconds EXCEPT _____. | rate of turn | ship's heading | navigational status | name of vessel |
| 750 | While underway, automatic identificat ion systems (AIS) broadcast all of the following information every 1 to 10 seconds EXCEPT the _____. | course over ground | ship's scantlings | latitude and longitude | speed over ground |
| 751 | Chart information details to be used in ECDIS should be the latest edition of information originated by a government-authorized hydrographic office and conform to the standards of (the) _____. | International Hydrographic Organization | nternational Maritime Organization | NASA | US Coast Guard |
| 752 | Raster-scan chart data is _____. | the only format recognized by IMO/IHO | a digitized "picture" of a chart in one format and one layer | composed of files that are smaller than vector files | organized into many separate files |
| 753 | ECDIS units incorporate Digital Chart Data Formats, which include _____. | vector and raster | imposed viewing | raster only | vector only |
| 754 | An ECDIS is required to display which information? | Meteorological data | Soundings | Radar target | Waypoints |
| 755 | An ECDIS is required to display which information? | Hydrographic data, RADAR targets, ARPA vectors | Temperature, Density, Distance | Pressure, Vibration | Brightness, Darkness |
| 756 | An ECDIS is required to display which information? | ARPA vectors | Hydrographic data | Radar targets | All of these |
| 757 | The database information that should be shown when a chart is first displayed on ECDIS is the: | Chart display information | Standard display information | Standard Display | System electronic nautical chart |
| 758 | ECDIS must be able to perform all of the following EXCEPT: | Determine magnetic compass deviation | Convert "graphical coordinates" to "display coordinates" | Determine true bearing and distance between two geographical points | Transform a local datum to the WGS-'84 datum |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 759 | ECDIS means: | Electric Chart Display and Information System | Electronic Chart Display and Information System | Electronic Chart Data and Information System | Electric Chart Data and Information System |
| 760 | The primary function of ECDIS is to: | Contribute to safe navigation | Eliminate the need to use paper charts | Computerize shipboard navigation | Reduce the number of persons on the bridge. |
| 761 | It is define as the level of SENC info shown when ECDIS first turned on; used for route planning and can be modified by mariner depending on needs. | Standby Display | Full Display | Standard Display | Soundings |
| 762 | Which of the following data layer categories is NOT displayed on ECDIS? | SENC | Hydrographic Office data | Ship hydrodynamic information | Notice to Mariners information |
| 763 | With respect to automatic identification systems (AIS), which information is required to be broadcast every 1 to 10 seconds? | Location of antenna | Time stamp | None of the above | Destination |
| 764 | Chart data is organised into many separate files. It contains layer information to produce certain symbols, lines, area, colours, and other elements. With this data, it can change individual elements with additional data. | Vector Chart (ENC) | Chersoft VPF | Maptech BSB | Raster Chart (RNC) |
| 765 | With respect to automatic identification systems (AIS), which information is expected to be broadcast every 1 to 10 seconds? | Name of ship | Ship's heading | Vessel's draft | IMO number |
| 766 | An ECDIS is required to display which information? | Meteorological data | Soundings | Radar targets | Ship hydrodynamic information |
| 767 | Which of the following is mandatory equipment that must be connected to ECDIS? | Positional navigation sensors (e.g., GPS) | Radar/ARPA | Track control (autopilot) | AIS |
| 768 | Which of the following mode of operation for ECDIS has been recently approved by the IMO under Resolution MSC.86(7)? | NEC | DSRC | RSDC | RCDS |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 769 | ECDIS database issued by hydrographic office that contains all chart info needed for safe navigation and may contain supplemental info. | ENC | SENC | ECS | ECN |
| 770 | ECDIS level in info that cannot be removed from display; required at all times and not intended for safe navigation. | Standard Display | Standby Display | Display Base | Full Display |
| 771 | The level of database information which cannot be removed from the ECDIS display and consists of information which is required at all times in all geographic areas and under all circumstances is the: | Display base information | Standard display information | System electronic nautical chart | Chart display information |
| 772 | An ECDIS is required to display which information? | Climatology data | Water temperature | Speed of advance | Depth contours |
| 773 | An ECDIS is required to display which information? | Hydrographic data | ARPA vectors | Radar targets | All of these |
| 774 | The database information that should be shown when a chart is first displayed on ECDIS is the: | Standard display information | Standard Display | System electronic nautical chart | Chart display information |
| 775 | ECDIS must be able to perform all of the following EXCEPT: | Determine true bearing and distance between two geographical points | Transform a local datum to the WGS-'84 datum | Determine magnetic compass deviation | Convert "graphical coordinates" to "display coordinates" |
| 776 | ECDIS means: | Electronic Chart Display and Information System | Electric Chart Display and Information System | Electronic Chart Data and Information System | Electric Chart Data and Information System |
| 777 | The primary function of ECDIS is to: | Computerize shipboard navigation | Eliminate the need to use paper charts | Reduce the number of persons on the bridge. | Contribute to safe navigation |
| 778 | It is define as the level of SENC info shown when ECDIS first turned on; used for route planning and can be modified by mariner depending on needs. | Soundings | Full Display | Standard Display | Standby Display |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 779 | Which of the following data layer categories is NOT displayed on ECDIS? | Hydrographic Office data | Ship hydrodynamic information | SENC | Notice to Mariners information |
| 780 | With respect to automatic identification systems (AIS), which information is required to be broadcast every 1 to 10 seconds? | Time stamp | Location of antenna | None of the above | Destination |
| 781 | With respect to automatic identification systems (AIS), which information is expected to be broadcast every 1 to 10 seconds? | Name of ship | IMO number | Ship's heading | Vessel's draft |
| 782 | An ECDIS is required to display which information? | Ship hydrodynamic information | Radar targets | Soundings | Meteorological data |
| 783 | Which of the following mode of operation for ECDIS has been recently approved by the IMO under Resolution MSC.86(7)? | RSDC | NEC | RCDS | DSRC |
| 784 | ECDIS level in info that cannot be removed from display; required at all times and not intended for safe navigation. | Standard Display | Display Base | Standby Display | Full Display |
| 785 | The level of database information which cannot be removed from the ECDIS display and consists of information which is required at all times in all geographic areas and under all circumstances is the: | Chart display information | Standard display information | System electronic nautical chart | Display base information |
| 786 | An ECDIS is required to display which information? | Depth contours | Water temperature | Speed of advance | Climatology data |
| 787 | AIS stands for _____. | Auto Investigation System | Automatic Identification System | Automatic investigation Security | Automatic Identity System |
| 788 | ECDIS is set with a performance standard by IMO called _____. | DX90 | DT40 | DP90 | TX50 |
| 789 | GPS satellites continually transmit their own precise orbital data called _____. | SSM | Almanac | HDOP | ephemeris |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 790 | IMO Resolution A817 (19) recommends Governments to ensure that what chart used on ships entitles to fly their flag conform to the performance standards not inferior to those set out in annex to this resolution? | Electronic Chart | British Admiralty Chart | Hydrographic Chart | US chart |
| 791 | It describes the minimum Performance Standards for ECDIS systems references to both hardware and software ENC updates user interface and the integration of external devices. | ECDIS Certified Systems | IHO Special Publication S52 | IMO Resolution A.817(19) | International Electrotechnical Commission (IEC) standard 61174 |
| 792 | Raster -scan chart data is _____. | organized into many separate files | a digitized picture of a chart in one format and one layer | compose of files that are smaller than the vector files | the only format recognized by IMO/IHO |
| 793 | The following units of measure will appear on the ECDIS chart display except _____. | Depth | Height | Position | Course |
| 794 | The Integrated Bridge System that complies with the up-to-date chart carrying requirements of international law is _____. | ECDIS | ECDISK | ECDB | EK1S |
| 795 | The position obtain from GPS are normally referred to _____. | Wave and pulses of sattelite system | World Geodetic System 1984 datum | Sattelite transits | Cross position fixes with other sattelites |
| 796 | The purpose of this course is to enhance safety of navigation by providing the knowledge and skills necessary to fully utilize the features of ECDIS is called _____. | IMO Model Course 1.37 | IMO Model Course 1.47 | IMO Model Course 1.27 | IMO Model Course 1.07 |
| 797 | This is the digital picture of a chart _____. | ECDIS | Electronic chart system | ECDISK | Raster Chart Data |
| 798 | Those chart display that do not meet the IMO requirements for the ECDIS and cannot be used to replace a paper chart is the _____. | ECS | ECDIS | both a and b | neither a nor b |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 799 | What contains all the chart information necessary for safe navigation and may contain supplementary information in additioned to that contained in the paper chart (e.g. sailing directions)? | Electronic Chart Systems (ECS) | Standard display | Electronic Navigational Chart (ENC)-S-57 vector | Base display |
| 800 | What do you call this combination of systems which are interconnected to allow centralized access to sensor information or command/control from workstations? | Integrated Bridge System (IBS) | Local Area Network (LAN) | Electronic Chart System (ECS) | Raster Chart Display Systems (RCDS) |
| 801 | What does not contribute to the commercial GPS receiver position error? | Satellites orbits | Atmospheric/Ionospheric propagation | Ships speed | Satellite clock |
| 802 | What is define as the level of SENC info shown when ECDIS first turned on; used for route planning and can be modified by mariner depending on needs? | ENC display | Display Base | Standard Display | none of these |
| 803 | What is the level of database information which cannot be removed from the ECDIS display and consists of information which is required at all times in all geographic areas and under all circumstances? | Full display information | Display base information | Complicated display information | Standard display information |
| 804 | When navigating using GPS what is an indicator of the geometry of the satellites that your receiver is locked onto? | Horizontal Dilution of Precision | Selective Availability | Doppler Shifting | Precision Coding |
| 805 | When the electronic chart is part of an ECDIS it must display the minimum data required by IMO/IHO to include all of the following except _____. | Aids to navigation | Hydrography | Tidal currents | Regulatory boundaries |
| 806 | When the gyro-pilot is used for steering what control is adjusted to compensate for varying sea conditions? | Weather adjustment | Sea control | Lost motion adjustment | Rudder control |
| 807 | Which data must ECDIS be able to record at one-minute intervals? | Speed through the water | Estimated time of arrival | Course made good history | Shaft RPM |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 808 | Which is the basic operating principle of the satellite navigation system? | Doppler shift | Echo | Phase difference | Time difference |
| 809 | Which of the following is a performance standard for the display of SENC information? | The smaller the wavelength is the more intense radiation is | The smaller the wavelength is the weaker the signal | The selected safety contour is displayed with greater emphasis than other contours | When a chart is first displayed the Standard Display at the smallest scale is presented. |
| 810 | Which of the following is correct about GPS? ( I - it maybe suspended without warning ll - It can be used in all parts of the world) | I only | II only | none of the given | I and II |
| 811 | Aside from the requirements for the Display Base and Standard Display who selects the display categories of the All other information display level? | Port state control | The mariner | bosun | The hydrographic office issuing the ENC data |
| 812 | In terms of ECDIS voyage recording, what major types of data that must be recorded at one-minute intervals during the previous 12 hours?<br>I. Record of own ships track<br>II. Record of own ship's time, position, heading, speed<br>III. Record of official data used (e.g., ENC) | I only | I, II and III | I and II | I and III only |
| 813 | A facsimile image of an existing paper chart and all the information and symbology on the paper chart is reproduced identically on the electronic chart and this type of chart has no layering of information. | Mercator chart | Raster Chart | Composite chart | Vector chart |
| 814 | A large database of geographical information and accesses this database to create a custom electronic chart based on operator selected parameters. | Vector chart | Electronic Navigational Chart | Raster chart | Electronic chart system |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 815 | A navigational information system which with adequate back-up arrangements can be accepted as complying with the up-to-date chart required by regulation V/19_2.1.4 of the 1974 SOLAS Convention by displaying selected information from a system electronic navigational chart. | Navigational Satellite System | Integrated Bridge System (IBS) | Navigational Raster Type Systems | Electronic Chart Display and Information System (ECDIS) |
| 816 | An ECDIS is required to display which among the following information? | Hydrographic data | Radar targets | ARPA vectors | All of these |
| 817 | An electronic or electric device that indicates the rate of turn of a vessel defines a/an _____. | magnetic compass | gyro-compass | swing meter | odometer |
| 818 | Can be considered any other type of electronic charts that does not comply with the IMO Performance Standard for ECDIS. | Electronic Chart Systems (ECS) | Standard display | Vector chart | Electronic Navigational Chart (ENC)-S-57 vector |
| 819 | Chart informations details to be used in ECDIS should be the latest edition of information originated by the government-authorized hydrographic office and conform to the standards of(the)_____. | International Maritime Organization | NASA | International Hydrographic Office | US Coast Guard |
| 820 | Countries are producing unique digital charts based on their interpretation of IHO standards _____. | S-55 standards | S-57 standards | S-59 standards | S-52 standards |
| 821 | ECDIS level in info that cannot be removed from display; What required at all times and not intended for safe navigation? | Display Base | complicated displays | None of these | Standard Display |
| 822 | ECDIS means _____. | Electric Chart Data and Information System | Electronic Chart Data and Information System | Electronic Chart Display And Information System | Electric Chart Display and Information System |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 823 | ECDIS must be able to perform all of the following EXCEPT _____. | make navigation safer | make navigation more efficient | determine true bearing and distance between two geographical points | determine magnetic compass deviation |
| 824 | If it is thought or known that floating aids to navigation (buoys) have shifted how should this be interpreted on ECDIS? | Physical buoy positions may differ from charted locations on ECDIS as with any type of chart information. | Charted buoy locations are always more reliable than own ships GPS position information. | None of the given choices | ECDIS is not up to date it must be updated by the class |
| 825 | If the electronic chart is part of an ECDIS it must display the minimum data required by IMO/IHO to include all of the following EXCEPT _____. | aids to navigation | hydrography | regulatory boundaries | tidal currents |
| 826 | In the ECDIS what do you call this opportunity to and by scrolling through the charts to acquaint the OOW with potential danger areas alterations of course crossing traffic and so on? | Look ahead | Safety checking | Cross track Error | Chart selection |
| 827 | It describes the ECDIS operational and performance requirements and provide methods for the required results. | IHO Special Publication S52 | IMO Resolution A.817(19) | ECDIS Certified Systems | International Electrotechnical Commission (IEC) standard 61174 |
| 828 | ECDIS must have the capability to preserve the record of the track for the previous _____. | 6 hours | 24 hours | 12 hours | 18 hours |
| 829 | ECDIS units incorporate Digital Chart Data Formats, which include _____. | vector only | vector and raster | imposed viewing | raster only |
| 830 | Raster-scan chart data is _____. | a digitized picture of a chart in one format and one layer | the only format recognized by IMO/IHO | organized into many separate files | composed of files that are smaller than vector files |
| 831 | Which of the following data layer categories is NOT displayed on ECDIS? | Notice to Mariners information | ECDIS warnings and messages | Ship hydrodynamic information | Hydrographic Office data |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 832 | The database resulting from (1) the transformation of the electronic navigational chart (ENC) by ECDIS for appropriate use, (2) the updates to the ENC by appropriate means, and (3) the additional data added by the mariner, is called the ..? | Chart display information | Standard display information | Display base information | System electronic navigational chart |
| 833 | The database information that should be shown when a chart is first displayed on ECDIS is the..? | Standard display information | Display base information | System electronic nautical chart | Chart display information |
| 834 | The level of database information which cannot be removed from the ECDIS display and consists of information which is required at all times in all geographic areas and under all circumstances is the _____. | chart display information | display base information | standard display information | system electronic nautical chart |
| 835 | ECDIS must give an alarm for which of the following cases? | If the ship is going to reach a critical point on the planned route. | When the speed of a dangerous target exceeds a set limit. | If the ships ETA has changed beyond the set limit. | All of these choices |
| 836 | ECDIS must give an alarm for which of the following cases? | If the ships ETA has changed beyond the set limit. | When the speed of a dangerous target exceeds a set limit. | None of the above | When the specified limit for deviation from the planned route is exceeded. |
| 837 | Chart information details to be used in ECDIS should be the latest edition of information originated by a government-authorized hydrographic office and conform to the standards of (the) _____. | International Hydrographic Organization | International Maritime Organization | NASA | US Coast Guard |
| 838 | An ECDIS is required to display which information? | ARPA vectors | Radar targets | All of these choices | Hydrographic data |
| 839 | Which data must ECDIS be able to record at one-minute intervals? | Course made good history | Position | All of these choices | Electronic navigational chart source |
| 840 | An ECDIS is required to display which information? | Soundings | Waypoints | Meteorological data | Radar targets |
| 841 | An ECDIS is required to display which information? | Water temperature | Speed of advance | Depth contours | Climatology data |

| | | | | | |
|---|---|---|---|---|---|
| 842 | Which data must ECDIS be able to record at one-minute intervals? | Course made good history | Estimated time of arrival | Speed through the water | Shaft RPM |
| 843 | Which of the following must an ECDIS system be able to perform? | Conversion of graphical coordinates to display coordinates | All of these choices | Transformation of local datum to WGS-84 datum | Calculation of true azimuth and distance between two geographical points |
| 844 | ECDIS must be able to perform all of the following EXCEPT. | Determine magnetic compass deviation. | Determine true bearing and distance between two geographical points. | Convert graphical coordinates to display coordinates. | Transform a local datum to the WGS-84 datum. |
| 845 | Which of the following must the electronic chart of an ECDIS display, as required by IMO/IHO? | Regulatory boundaries | Ferry routes | Hydrography | All of these choices |
| 846 | Which of the following are data layer categories to be displayed on ECDIS? | All of these choices | Hydrographic Office data | Notice to Mariners information | ECDIS warnings and messages |
| 847 | ECDIS must give an alarm for which of the following cases? | When the specified limit for deviation from the planned route is exceeded. | All of these choices | If the ship, within a specified time set by the watch officer, is going to cross the boundary of a prohibited area. | If the ship, within a specified time set by the watch officer, is going to cross a safety contour. |
| 848 | An ECDIS is required to display which information? | radar targets | ARPA vectors | all of these | hydrographic data |
| 849 | The database information that should be shown when a chart is first displayed on ECDIS is the _____. | standard display information | chart display information | system electronic nautical chart | display base information |
| 850 | Which data must ECDIS be able to record at one-minute intervals? | Speed through the water | Course made good history | Estimated time of arrival | Shaft RPM |
| 851 | The database resulting from (1) the transformation of the electronic navigational chart (ENC) by ECDIS for appropriate use, (2) the updates to the ENC by appropriate means, and (3) the additional data added by the mariner, is called the _____. | display base information | standard display information | chart display information | system electronic navigational chart |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 852 | Which of the following data layer categories is NOT displayed on ECDIS? | Ship hydrodynamic information | Notice to Mariners information | ECDIS warnings and messages | Hydrographic Office data |
| 853 | ECDIS units incorporate Digital Chart Data Formats, which include _____. | vector only | raster only | imposed viewing | vector and raster |
| 854 | The level of database information which cannot be removed from the ECDIS display and consists of information which is required at all times in all geographic areas and under all circumstances is the _____. | display base information | standard display information | chart display information | system electronic nautical chart |
| 855 | If the electronic chart is part of an ECDIS, it must display the minimum data required by IMO/IHO, to include all of the following EXCEPT _____. | regulatory boundaries | aids to navigation | hydrography | tidal currents |
| 856 | ECDIS must give an alarm for which of the following cases? | When the speed of a dangerous target exceeds a set limit | all of the options | If the ship is going to reach a critical point on the planned route | If the ships ETA has changed beyond the set limit |
| 857 | Bridge officers have three main duties as set forth in the ECDIS and the integrated bridge system. Which of the following system is NOT included? I. Navigation II. Chart Work III. Ship Management | II only | III only | I and II only | I and III |
| 858 | Which of the following statement is/are true with regards to the ECDIS in the integrated Bridge System? I This will not lower the overall worked load of the bridge officer II It increases the percentage of the time that bridge officers can devote to collision avoidance | II only | Neither I nor II are true | I and II are true | I only |
| 859 | The following units of measure will appear on the ECDIS chart display EXCEPT: | Course | Position | Depth | Height |
| 860 | RNC charts can be used for voyage planning. | Only if approved by the flag state | Only together with paper charts | FALSE | TRUE |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 861 | What should you do when you see a person fall overboard at night? | Throw a red flare to the victim | Initiate a "Mayday" call to alert other vessels in the vicinity | Put the rudder hard over to the side where the victim fell and start the Scharnow turn | Call for help and keep the victim in sight |
| 862 | Immediately after abandoning a vessel, lookouts should be posted aboard liferafts to look for _____. | Survivors in the water | Food and water | Land | Bad weather |
| 863 | After abandoning ship, you should deploy the sea anchor from a liferaft to _____. | Navigate against the current | Keep personnel from getting seasick | Stay in the general location | keep the liferaft from capsizing |
| 864 | Which step should be taken, if possible, when the vessel must be abandoned because of a distress situation? | Program the SART and EPIRB to transmit the vessel's location and situation. | Place the SART and EPIRB in the "ON" position and secure them to the survival craft. | No additional steps are needed as the SART and EPIRB will both automatically float free and operate properly. | Alert the U.S. Coast Guard by using the survival craft's portable INMARSAT unit. |
| 865 | When abandoning ship, after launching the motor lifeboat you should _____. | plot a course for the nearest land | take a vote on which direction you should go | go in one direction until fuel runs out | stay in the immediate area |
| 866 | You must shore up the collision bulkhead due to solid flooding forward. The bulkhead approximates an inverted triangle. The center of pressure of the shores on the bulkhead should be located _____. | approximately two-thirds of the way up the bulkhead | at the bottom of the bulkhead | evenly over the surface of the bulkhead | approximately halfway up the bulkhead |
| 867 | You are trying to rescue survivors from a wrecked vessel on fire. You should approach _____. | at a speed of at least that of the wrecked vessel | at a speed of at most one-half that of the wrecked vessel | to windward of the wrecked vessel | to leeward of the wrecked vessel |
| 868 | You are underway when a fire breaks out in the forward part of your vessel. If possible you should _____. | put the vessel's stern into the wind | call for assistance | keep going at half speed | abandon ship to windward |
| 869 | A crew member has just fallen overboard off your port side. Which action should you take? | Immediately put the rudder over hardrigth. | Immediately put the engine astern. | Immediately put the rudder over hardleft. | Wait until the stern is well clear of the man and then put the rudder over hard right. |

# OIC NAVIGATIONAL WATCH

| | | | | | |
|---|---|---|---|---|---|
| 870 | A report of casualty to a vessel must include _____ .? | An evaluation of who was at fault | The amount of ballast on board | The estimated cost of damage | The name of the owner or agent of the vessel |
| 871 | Which situation requires you to furnish a notice of marine casualty to the coast guard? | Your vessel is at anchor and grounds at low tide with no apparent damage | Storm damage to the cargo winch motors requiring repairs costing $19,000 | A seaman slips on ice on deck and sprains his ankle, requiring an ace bandage | You collide with a buoy and drag it off station with no apparent damage to the vessel or to the buoy |
| 872 | The abbreviation HEL-H of helicopter radius of action for rescue purposes. What are the radius and evacuating capacity of the helicopter? | 100 nm and capacity for evacuating more than 10 persons. | 200 nm and capacity for evacuating more then 15 persons. | 500 nm and capacity for evacuating more than 25 persons. | 150 nm and capacity for evacuating more than 12 persons. |
| 873 | What will be the action of each vessel after the collision accident? | Reports to the Charterers the incident and continue the voyage | After logging the other vessel's name, leave and continue the voyage | Report to the Owners the incident and continue the voyage | The stable vessel should standby to assist the vessel in most distress |
| 874 | When a crew member who is conscious has fallen overboard is being picked up by a lifeboat, how should the boat approach with the wind? | Astern and the victim just off the bow | Just off the bow and the victim to leeward | Ahead and the victim just the bow | Just off the bow and the victim to windward |
| 875 | The shipboard general alarm system must receive its main source of power from which of the following? | a storage battery | the emergency generator | an auxiliary generator | the ship's service generator |
| 876 | A continuous sounding of a fog whistle by a vessel indicates that a vessel is: | anchored | in distress | requesting the draw span bridge to be opened | without engines and drifting |
| 877 | Which of the following smoke signals can be given off by a vessel in distress or in need of assistance? | orange colored smoke | green colored smoke | black smoke | blue smoke |
| 878 | When beaching a vessel and the vessel is heavily trimmed by the head, beaching _____ may be advantageous. | head on | bow first | parallel to the beach | stern first |
| 879 | What will be your first action to alarm the persons on board when your vessel runs aground? | Call the Master | Call the Bosun to dropped anchor | Sound the general alarm system | Call the Engine room |
| 880 | What would be your immediate action upon stranding your vessel? | stop engine and put engine astern, if tide is falling | call the coast guard | call your ship owner | call at tug boat |

# OIC NAVIGATIONAL WATCH

| | | | | | |
|---|---|---|---|---|---|
| 881 | When vessel is stranded, the engineers should be warned to: | always keep the engines at full astern | change from low level water intakes to high level water intakes | change from high level water intakes to low level water intakes | change watch every 4 hours |
| 882 | After grounding, the extent of the damage to the vessel can determined by: | checking if the engine room of flooded | taking sounding around the vessels | testing if the engine is still working | sounding of all compartments |
| 883 | Upon colliding with another vessel in calm weather, the engines should be stopped. Which of the following would NOT immediately be done? | close watertight doors | inform the crew of the situation | put the engines astern | sound general alarm |
| 884 | Your vessel have been in collision with an other vessel. You are taking in water and you have to prepare for leaving the vessel. How will you act? | Send a distress message and collect survival suits / thermal bags | Assist your friends to collect their personal belongings | Collect your own personal belongings | Just jump over board and be ready |
| 885 | If the ship's bow has penetrated the side of the other ship in a collision it would be safe to: | come astern in order to get clear of the other vessel to avoid further damage | stay in place in order to plug the hole on the other vessel | communicate with the other vessel | lower lifeboat in the water |
| 886 | Which of the following is NOT considered as distress signal? | Green star shells | Flames from the vessel | Continuous sounding of a whistle | A flag over a ball |
| 887 | Among the listed, which one is NOT a way to signal distress? | Flames from the vessel | A flag over a ball | Green star shells | Continuous sounding of a whistle |
| 888 | The abbreviation HEL-H of helicopter radius of action for rescue purposes. What are the radius and evacuating capacity of the helicopter? | 150 nm and capacity for evacuating more than 12 persons. | 200 nm and capacity for evacuating more then 15 persons. | 100 nm and capacity for evacuating more than 10 persons. | 500 nm and capacity for evacuating more than 25 persons. |
| 889 | What will be the action of each vessel after the collision accident? | The stable vessel should standby to assist the vessel in most distress | Reports to the Charterers the incident and continue the voyage | After logging the other vessel's name, leave and continue the voyage | Report to the Owners the incident and continue the voyage |
| 890 | When a crew member who is conscious has fallen overboard is being picked up by a lifeboat, how should the boat approach with the wind? | Just off the bow and the victim to windward | Astern and the victim just off the bow | Ahead and the victim just the bow | Just off the bow and the victim to leeward |
| 891 | The shipboard general alarm system must receive its main source of power from which of the following? | a storage battery | the emergency generator | an auxiliary generator | the ship's service generator |

# OIC NAVIGATIONAL WATCH

| | | | | | |
|---|---|---|---|---|---|
| 892 | A continuous sounding of a fog whistle by a vessel indicates that a vessel is: | without engines and drifting | in distress | requesting the draw span bridge to be opened | anchored |
| 893 | Which of the following smoke signals can be given off by a vessel in distress or in need of assistance? | blue smoke | green colored smoke | orange colored smoke | black smoke |
| 894 | When beaching a vessel and the vessel is heavily trimmed by the head, beaching _____ may be advantageous. | stern first | parallel to the beach | bow first | head on |
| 895 | What will be your first action to alarm the persons on board when your vessel runs aground? | Call the Bosun to dropped anchor | Call the Master | Sound the general alarm system | Call the Engine room |
| 896 | What would be your immediate action upon stranding your vessel? | call your ship owner | call the coast guard | call at tug boat | stop engine and put engine astern, if tide is falling |
| 897 | When vessel is stranded, the engineers should be warned to: | change from low level water intakes to high level water intakes | change from high level water intakes to low level water intakes | change watch every 4 hours | always keep the engines at full astern |
| 898 | After grounding, the extent of the damage to the vessel can determined by: | testing if the engine is still working | checking if the engine room of flooded | taking sounding around the vessels | sounding of all compartments |
| 899 | Upon colliding with another vessel in calm weather, the engines should be stopped. Which of the following would NOT immediately be done? | sound general alarm | put the engines astern | close watertight doors | inform the crew of the situation |
| 900 | Your vessel have been in collision with an other vessel. You are taking in water and you have to prepare for leaving the vessel. How will you act? | Send a distress message and collect survival suits / thermal bags | Assist your friends to collect their personal belongings | Collect your own personal belongings | Just jump over board and be ready |
| 901 | If the ship's bow has penetrated the side of the other ship in a collision it would be safe to: | lower lifeboat in the water | communicate with the other vessel | come astern in order to get clear of the other vessel to avoid further damage | stay in place in order to plug the hole on the other vessel |
| 902 | Which of the following is NOT considered as distress signal? | | Green star shells | A flag over a ball | Continuous sounding of a whistle |
| 903 | Among the listed, which one is NOT a way to signal distress? | Green star shells | Flames from the vessel | Continuous sounding of a whistle | A flag over a ball |

OIC NAVIGATIONAL WATCH

# OIC NAVIGATIONAL WATCH

| | | | | | |
|---|---|---|---|---|---|
| 904 | Which of the following information is NOT required in reporting danger messages? | Ice | direct dangers to navigation | derelicts | engine failure |
| 905 | What is the possible damaged of a vessel aground listing to starboard side? | Starboard tank / ballast is breached and taking in water | Center tank is breached and taking in water | Due to the wind blowing from portside | Normal causes for she is grounded |
| 906 | This system divides the crew into teams which should be trained in their various functions so that when an emergency occurs, the whole crew swings into actions. | emergency gear system | emergency maneuver system | back-up team | emergency segregation system |
| 907 | Your vessel has grounded on a bar. What should you do? | If you cannot get clear immediately, lighten the ship by pumping all ballast overboard. | Run the engine full astern to keep from being set further onto the bar. | all of the choices are correct | Switch to the high suction for condenser circulating water, if it is submerged. |
| 908 | While your vessel is underway at sea and one of your crew member falls overboard from the starboard side. What should be the FIRST thing to do? | immediately throw the crew member a life preserver | immediately begin backing your engines | immediately apply left rudder | immediately position your vessel to windward and begin recovery |
| 909 | Which of the following action should you take if a crew member has just fallen overboard off your port side? | Immediately put the engines astern | Immediately put the rudder over hard starboard | Wait until the stern is well clear of the man and then put the rudder over hard starboard | Immediately put the rudder over hard port |
| 910 | A person has just fallen overboard off your starboard side. Which action should you take? | Wait until the stern is well clear of the man and then put the rudder over hard port | Immediately put the engines astern | Immediately put the rudder over hard starboard | Immediately put the rudder over hard port |
| 911 | Upon stranding, the engines should be stopped. It should be put astern if the tide is falling to see if the engines will immediately re-float. However, under no circumstances will be engines be put astern for a long period. Why? | it may damage the rudder | it may stir up sands that may block condensers | it may make tremendous vibrations | it may damage the propeller |

NOT FOR SALE

# OIC NAVIGATIONAL WATCH

| | | | | | |
|---|---|---|---|---|---|
| 912 | You are Senior Deck Officer onboard a merchant vessel. During the night you have been in collision with a sail boat. There is no sign of life in the water. What will you do? | Alarm the rescue centre and commence searching for any survivals | Just wait for assistance | Leave the position as fast as possible | Call the company, explain the situation and ask for orders |
| 913 | What a rescue person use if he has to jump into the water in order to assist a survivor? | lifeline | survival suit | survival suit and lifeline | lifejacket |
| 914 | When vessel is stranded, discharge or probable discharge of harmful substances should be reported to the: | nearest coast radio station | nearest classification society | nearest NCB surveyor | nearest US coast guard |
| 915 | Which of the following actions is NOT to be taken following a collision: | discharge or probable discharge of harmful substances to be reported to the nearest coast radio station | survival craft should be made ready for abandoning ship or assisting crew of the other ship | immediately sail away from the scene | owners to be informed of all details about the collision |
| 916 | When a parallel track search pattern is being carried out, the course of the search units should normally be which of the following? | In the same direction as the anticipated drift | In the opposite direction of the anticipated drift | Perpendicular to the line of anticipated drift | Downwind |
| 917 | When beaching a ship to avoid immediate danger of foundering, it is ideal to do so at/on _____ so that the ship settles slowly, rather than drive her hard ashore and strain the bottom plating. | spring tide | full moon | neap tide | high water or falling tide |
| 918 | What action should the engineers take when your vessel is underway in a channel and all of a sudden the vessel runs a ground? | Stop main engine and engage turning gear | Check tank sounding to determine damages | Standby engine for any order from the bridge | Change over to do supply |
| 919 | This emergency team may be needed to provide support by carrying additional equipment to the fist team, to provide stretcher bearers and to relieve injured or tire men. | control team | if all efforts to save the vessel prove to be unsuccessful | support control team | reserve team |

| | | | | | |
|---|---|---|---|---|---|
| 920 | In the event of a collision, after the impact, which of the following should NOT be done? | transmit MAYDAY or PA_PAN signals, even if not in distress | close all watertight doors | swing out lifeboats, ensure that no premature abandonment takes place and prepare life rafts | hoist the three red lights in a vertical line, one above the other |
| 921 | Which of the following statements concerning a man overboard emergency is FALSE? | You should always place your vessel upwind of a survivor in the water to create a lee | In small, shallow-draft vessels, the man overboard should be picked up on the weather bow | The ship pickup is difficult with very large vessels due to the lack of maneuverability | The ship pickup is faster than using a small boat |
| 922 | If a crewmember has fallen overboard during the hours of darkness and you immediately execute a Williamson turn, what is the primary advantage of this maneuver under these circumstance exams? | The turn enables you to reverse course in the shortest possible time | The turn provides the maximum coverage of the area to be searched | You will have enough time to maneuver to close in on the man for rescue | You will be in a reciprocal course and nearly on the track line run during the night |
| 923 | In the event of collision in calm weather, the colliding ship should generally remain embedded: | to allow crew members and passengers to transfer from the holed vessel to the colliding vessel | the colliding ship must pull out immediately | to allow another ship time to assess the damage or prepare to abandon ship | to allow coast guards to assess who is to blame on the collision |
| 924 | What is NOT correct while the vessel is dealing with emergencies in stranding? | Report the accident to the Charterers | Engine stopped | Watertight doors closed | Lights / shapes exhibited |
| 925 | Your vessel has been involved in a collision. As master you have to write about the accident in the log-book. In order to only write the facts in the log-book, which of the following procedures do you find most correct? | Write down the story as favorable as possible seen from your own point of view. Make sure that your log-book tells your story | Write down all the facts you have collected, and also write down your own opinion about the circumstances | Write continually in the log-book as soon as the accidents happen | Find out from officers and crew who have been in connection with the collision, what they have seen, so that detailed and complete description of the sequence of events can be entered in the log-book |
| 926 | A report of casualty to a vessel must include _____. | The name of the owner or agent of the vessel | b. the amount of ballast on board | a. the estimated cost of damage | an evaluation of who was at fault |
| 927 | According to the rules of GMDSS the frequency 2187.5 kHz is used for _____. | piracy attack | regular communication | alerting | distress traffic |

| | | | | | |
|---|---|---|---|---|---|
| 928 | Fire in an engine compartment is best extinguished with carbon dioxide gas (CO2) and by _____. | Completely closing the compartment | Leaving the compartment open to the air | Closing the compartment except for the ventilators | Increasing the air flow to the compartment by blowers |
| 929 | If your ship is in collision in the waters of a foreign nations which of the following is NOT a legal responsibility for the MASTER? | Render assistance to the other ship if practicable | Inform the other vessel of the name of your ship and other details | Go as soon as possible to the nearest appropriate port to report to the authorities | Enter a witnessed statement in the official log book |
| 930 | On stranding the following are measures to be taken except _____. | Watertight doors be locked. | The general alarm be sounded. | On a falling tide the engines should be put full astern. | The engineers should not change to high level water intakes. |
| 931 | The Scharnow turn should be used in a man overboard situation only when? | There has been sufficient time elapsed since the man went over to complete the maneuver. | The vessel has twin screws to assist in making the turn. | The man can be kept in sight from the bridge while maneuvering. | The turn is started immediately when the man goes over. |
| 932 | What condition under the main propulsion plant boilers and auxiliaries are not in operation due to the absence of power? | low voltage condition | Dead ship condition | power surge condition | Critical condition |
| 933 | What is most important when preparing for emergencies? | That people know where to muster. | That people listen to orders given. | That people are well trained. | That people know where to find designated equipment. |
| 934 | What is one of the most dangerous state of a human being may suffer if in sea water awaiting rescue? | Hypothermia | Influenza | Cold | Broken limb |
| 935 | What must be accurately determined to assess the potential for progressive flooding after your vessel has been damaged? | The capacity of the water sprinkler system. | All of the above. | The integrity of the watertight boundaries. | The operation of the machinery space bilge level alarms. |
| 936 | What safety devise when activated in a distress situation responds to radar interrogation by transmitting a swept frequency signal which generates 12 blips code on a radar screen? | smoke signal | Search and rescue radar transponder | Epirb beacon | All of these |
| 937 | What sound signal shall be used on ships whistle when man-over-board? | 3 long blasts repeatedly. | 6 short blasts repeatedly. | 2 short blasts repeatedly. | 4 short blasts repeatedly. |

| | | | | | |
|---|---|---|---|---|---|
| 938 | When a rescue vessel approaches a lifeboat in heavy seas the person in charge of the lifeboat should : | approach on the windward side | do not approach the lifeboat | wait for calmer weather before transferring personnel | approach on the leeward side |
| 939 | When abandoning ship in cold waters what actions can be taken to minimize the effects of entering the water? | utilize embarcation ladders or a fire hose to lower yourself to a survival craft | wear a type II PFD and carry an immersion suit with you | inflate the life raft on deck board the raft and wait for the vessel to sink | do not abandon the vessel until help arrives on scene |
| 940 | When personnel are lifted by a helicopter from an inflatable liferaft the personnel on the raft should _____. | remove their life preservers to prepare for the transfer | take in the sea anchor to prevent fouling of the rescue sling | deflate the floor of the raft to reduce the danger of the raft overturning | inflate the floor of the raft to provide for additional stability |
| 941 | When receiving station can not distinguished the signal what signal flag is to be hoisted? | Keep Code pennant at the dip | Hoist ZL | Hoist ZQ | Raise and lower the answering pennant |
| 942 | Which emergency equipment should you keep near the towing bitts? | A self-contained breathing apparatus (SCBA) | A boat hook and a spanner wrench | A Stokes litter basket | A fire ax and/or cutting torch |
| 943 | Which type of emergency equipment is independent of outside air and suited for use in a compartment readiness for launching with oxygen? | AllService Gas Masks (Navy type) | service gas mask used by caost guards | face mask | Oxygen Breathing Apparatus |
| 944 | Who makes decisions on how the operation has to be carried out in a helicopter rescue? | Pilot of the helicopter | Master of the ship | Shipowner | Superintendent |
| 945 | You are attempting to take a dead ship in tow. All lines have been passed and secured. How should you get underway? | Order minimum turns until the towing hawser is taut and then continue at that speed until towing speed is attained. | Order minimum turns until the catenary almost breaks the water then stop. Order more turns as the hawser slackens but keep the catenary in the water. | If the towline is properly adjusted and weighted you can order slow or dead slow and the towline will act as a spring to absorb the initial shock. | Order minimum turns until the towing hawser is just clear of the water then reduce speed to that necessary to keep the line clear of the water. |
| 946 | You are on a vessel that has broken down and are preparing to be taken in tow. You will use your anchor cable as part of the towline. Which statement is TRUE? | The strain of the tow is taken by the riding pawl chain stopper and anchor windlass brake. | The anchor cable should be veered enough to allow the towline connection to be immediately astern of the towing vessel. | The anchor cable should be veered enough to allow the towline connection to be just forward of your bow. | The anchor cable should be led out through a chock if possible to avoid a sharp nip at the hawsepipe lip. |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 947 | You are proceeding to a distress site where the survivors are in liferafts. Which action will assist in making your vessel more visible to the survivors? | Steering a zigzag course with 5 to 10 minutes on each leg. | Steering a sinuous course. | Dumping debris over the side to make a trail to your vessel. | Making smoke in daylight. |
| 948 | You are proceeding to the area of reported distress. When you arrive at the reported position you find two other vessels have also arrived in the area but the vessel in distress is not sighted. What type of search should be conducted? | Parallel track search | Sector search | Expanding square | Track crawl |
| 949 | You are signing on a deck officer who will be designated as one of the GMDSS operators before sailing foreign. Which statement is true? | You must consult the List of Qualifications on the reverse of his/her FCC-issued license. | His/her Merchant Mariners Document must have an added endorsement as Radio Electronics Officer. | He/she must have an STCW certificate endorsed as Valid for Service on Vessels Operating in the GMDSS System. | He/she must present either an FCC-issued license or a Coast Guard-issued license. |
| 950 | You are the Senior Deck Officer of a vessel involved in a collision. All necessary actions to ensure safety of crew and vessel has been taken. What shall you then tell the Sen. Deck Off. on the other vessel? | That you are sorry for the collision. | Dont talk to the Sen. Deck Off. on the other vessel at all. | Check with the pilot or any witnesses about their consideration of whom to blame for the collision. | Name and Port of registry of your vessel. |
| 951 | Your sailing vessel is docked during a storm and is in continuous motion. If a mooring line parts due to vessel motion it will most likely do so _____. | at the chock | where it is made fast on the vessel | at the eye | midway between the vessel and the dock |
| 952 | Your ship has run aground and it is necessary to determine whether or not a compartment has flooded. Therefore you should _____. | feel the bulkhead to see if it is hot | open a hatch dog on the side of the hinges | open the watertight door and take a quick look | tap the bulkhead with a hammer to check for a water level |
| 953 | A DSC distress alert message received contains the information_____ GROUNDING. This means that _____. | For a good connection aerial transmitting has to be earthed | none of the above | The ship has grounded | For a good connection transmitting receiving has to be earthed |

| | | | | | |
|---|---|---|---|---|---|
| 954 | A proper working of the 406 MHz Cospas-Sarsat EPIRB can be tested: I. Monthly test transmissions from RCCs as per regulation II. Test-transmissions from Cospas-Sarsat satellites. | II only | Neither I nor II | I and II are correct | I only |
| 955 | A distress alert has accidentally been sent with the Inmarsat-C installation. One should now_____ | turn on alwys the transmitter | wait until an RCC reports | any of these options | turn off the transmitter |
| 956 | A distress alert on board may only be transmitted on explicit order of_____. | the captain | the navigating officer on duty | The chief officer | The Charterer |
| 957 | A distress alert sent by Inmarsat to an RCC is sent via_____. | NCS | LUT | VHF | INMARSAT |
| 958 | A distress-call onboard via RCC may only be given Receipt if_____. | the O.O.W deems it necessary | OSC from the RCC concerned invites the vessels | the master allows | all of the options |
| 959 | A DSC distress alert single frequency call attempt is awaiting acknowledgement_____. | not repeated automatically | automatically repeated after 2 to 1 and a half minutes | automatically repeated after 1 to 1 and a half minutes | automatically repeated after 3 to 1 and a half minutes |
| 960 | A DSC-notice should be sent on VHF-channel_____. | 16 | 37 | 57 | 67 |
| 961 | A MF/HF-DSC multi-frequency call attempt may_____. | be repeated after 1 to 1 and a half minutes | not be repeated | be repeated after 1 to 2 and a half minutes | be repeated after 2 to 3 and a half minutes |
| 962 | A person who sees someone fall overboard should _____. | go to the bridge for the distress flares | immediately jump in the water to assist the individual | run to the radio room to send an emergency message | call for help and keep the individual in sight |
| 963 | A received DSC distress alert contains the following information_____ UNDESIGNATED DISTRESS Of this distress case_____. | any of these options | the position is unknown | altitude is unknown | time is unknown |
| 964 | A SART must be visible on the ship s radar from a distance of at least_____. | 30 miles | 50 miles | 20 miles | 10 miles |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 965 | A ship in distress should transmit the appropriate alarm signal followed by the distress call and message on one or all of the international distress frequencies. Which of the frequencies are in accordance with the present recommendations? I. 500 kHz 2182 kHz and 156.8 MHz II. 550 kHz 2182 kHz and 121.5 MHz | Neither I nor II | I only | II only | I and II are correct |
| 966 | According to the rule of GMDSS channel 70 is used for_____. | on-scene communication | distress traffic | alerting | any of these options |
| 967 | According to the rules of GMDSS all vessels have to be equipped with_____ | on both sides an EPIRB | at least three mariphones | life rings on both side of the wings | all of the options |
| 968 | According to the rules of GMDSS the frequency 2187.5 kHz is used for_____. | piracy attack | regular communication | distress traffic | alerting |
| 969 | According to the rules of GMDSS the required radio-equipment depends mainly on_____. | the sea area of the vessel | their tonnage | type of vessel | the l.o.a. of the vessel |
| 970 | According to the rules of GMDSS vessels are equipped with certain radio-communication devices depending on_____. | the l.o.a. of the vessel | their tonnage | the sea area of the vessel | type of vessel |
| 971 | According to the rules of GMDSS on behalf of a safe navigation continuous listening service must be maintained on mariphone channel_____ | 16 | 70 | 15 | 87 |
| 972 | What condition does a weather-tight door on a vessel must not allow water to penetrate into the unit? | none of the above | In any sea condition | In 70 knot winds | In 100 knot winds |
| 973 | What is a maritime radio warning consisting of a series of coast stations transmitting radio teletype safety messages? | Digital Selective Calling (DSC) | Maritime Safety Information (MSI) | AMVER | NAVTEX |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 974 | What is the channel used for Digital selective calling for Distress Safety and Calling? | Channel 70 | Channel 16 | Channel 13 | Channel 69 |
| 975 | A person who sees someone fall overboard should _____. | go to the bridge for the distress flares | run to the radio room to send an emergency message | immediately jump in the water to assist the individual | call for help and keep the individual in sight |
| 976 | Seeing that all hands are familiar with their duties, as specified in the muster list, is the responsibility of the _____. | department heads | Chief Mate | Master | safety officer |
| 977 | Preparation of muster lists and signing of same is the responsibility of the _____. | Master of the vessel | Chief Officer of the vessel | owner of the vessel | United States Coast Guard |
| 978 | Which information MUST be entered on the muster list? | Listing of approved emergency equipment | Duties and station of each person during emergencies | Names of all crew members | Use and application of special equipment |
| 979 | When a man who is conscious has fallen overboard is being picked up by a lifeboat, the boat should approach with the wind _____. | just off the bow and the victim to leeward | astern and the victim just off the bow | ahead and the victim just off the bow | just off the bow and the victim to windward |
| 980 | You are picking up an unconscious person that has fallen overboard in a fresh breeze. For safety reasons a small craft should approach with the _____. | wind on your starboard side | victim to windward | victim to leeward | wind on your port side |
| 981 | Control of flooding should be addressed _____. | following restoration of vital services | only if a threat exists | following control of fire | first |
| 982 | A person has fallen overboard and is being picked up with a lifeboat. If the person appears in danger of drowning, the lifeboat should make _____. | the most direct approach | an approach from leeward | an approach from windward | an approach across the wind |
| 983 | The Muster List (Station Bill) shows each persons lifeboat station, duties during abandonment, basic instructions, and _____. | work schedule | all emergency signals | instructions for lowering the lifeboats | the time each weekly drill will be held |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 984 | Each crewmember has an assigned firefighting station. This assignment is shown on the _____. | muster list | fire fighting plan | shipping articles | Certificate of Inspection |
| 985 | The muster list must be posted in conspicuous locations and signed by the _____. | Coast Guard Officer approving the bill | safety officer | owner | Master |
| 986 | You are on watch at sea at night, and a fire breaks out in #3 hold. What would you NOT do immediately? | Proceed to the space and inspect the extent of the fire. | Shut down the cargo hold ventilation. | Sound the fire alarm signal to rouse out all hands. | Call the Master. |
| 987 | If you saw flames aboard a vessel but could see the vessel was not on fire, you would know that the _____. | crew was trying to get warm | vessel was attempting to attract the attention of a pilot boat | vessel required immediate assistance | vessel was being illuminated for identification by aircraft |
| 988 | Your vessel has grounded on a bar. What should you do? | All of the above | Switch to the high suction for condenser circulating water, if it is submerged. | If you cannot get clear immediately, lighten the ship by pumping all ballast overboard. | Run the engine full astern to keep from being set further onto the bar. |
| 989 | A crew member has just fallen overboard off your port side. Which action should you take? | Immediately put the rudder over hard left. | Immediately put the rudder over hard right. | Wait until the stern is well clear of the man and then put the rudder over hard right. | Immediately put the engines astern. |
| 990 | You receive word that a person has fallen overboard from the starboard side. You should FIRST _____. | sound the man overboard alarm | put the engines full astern | put the wheel hard right | notify the Master |
| 991 | Which action should be taken FIRST if your tow is sinking in shallow water? | Pay out the towline until the sunken tow reaches bottom. | Sever the towline. | Immediately head for the nearest shoreline. | Contact the Coast Guard. |
| 992 | If theres a fire aboard your vessel, you should FIRST _____. | have passengers put on life preservers | notify the Coast Guard | cut off air supply to the fire | sound the alarm |
| 993 | If you have a fire in the engine room, your FIRST act should be to _____. | secure the fuel supply and ventilation to the engine room | discharge the fixed CO2 system into the engine room | maneuver your vessel into the wind | have all of your crew get into the liferaft |
| 994 | What should be used to steer an open lifeboat if the rudder becomes lost or damaged? | Daggerboard | Steering oar | Spare rudder | Sea anchor |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 995 | A fire starts on your vessel while refueling. You should FIRST _____. | sound the general alarm | stop the ventilation | determine the source of the fire | attempt to extinguish the fire |
| 996 | There is a fire in the crews quarters of your vessel. You should _____. | prepare to abandon ship | ventilate the quarters as much as possible | close all ventilation to the quarters if possible | attempt to put the fire out yourself before sounding the alarm |
| 997 | If your vessel is aground at the bow, it would be preferable that any weight removals be made from the _____. | All of the above | stern | mid-section | bow |
| 998 | You have abandoned ship. There are several rafts in the water. One of the FIRST things to do is _____. | secure the rafts together to keep them from drifting apart | separate the rafts as much as possible to increase chances of detection | transfer all supplies to one raft | transfer all the injured to one raft |
| 999 | Your vessel has been holed in #1 hold and partially flooded. The hole is plugged against further flooding. In calculating the effect of the flooding on your transverse stability, you should use which method? | Factor of subdivision method | Lost buoyancy method | Compartment standard method | Added weight method |
| 1000 | Which statement concerning the sources of drinking water is FALSE? | Fresh water may be obtained from fish. | Lifeboat covers or canopies should be washed with rain before drinking water is collected. | Fresh water may be collected from condensation inside the liferaft. | Seawater should never be consumed. |
| 1001 | What should be your FIRST action if you discover a fire aboard ship? | Call the Master. | Attempt to put out the fire. | Sound the alarm. | Confine it by closing doors, ports, vents, etc. |
| 1002 | You are underway at sea when a fire is reported in the forward part of the vessel. The wind is from dead ahead at 20 knots. You should _____. | remain on course but decrease speed | remain on course and hold speed | change course to put the wind on either beam and increase speed | change course and put the stern to the wind |
| 1003 | After a collision or accident involving an uninspected vessel, regulations require that the operator assist persons affected, but only if the operator can do so without _____. | serious danger to his or her own vessel | further damaging the other vessel | undue delay | creating a panic on either vessel |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 1004 | You are Senior Deck Officer / Duty officer onboard one of the vessels involved in a collision. How will you act just after the collision? | Call the Company Office. | Continue the voyage to your destination. | Start an argument with the other vessel about fault. | Make sure your vessel and crew are safe and then offer your assistance to the other vessel. |
| 1005 | You are Senior Deck Officer on a laden tanker. You have just been in a collision, and have a big leakage under waterline. What should you do to reduce the pollution as much as possible? | Level in the tank to be reduced as much as possible to reduce/stop any further oil spill. | Shut down non-essential air intakes. | When wind and current are taken into consideration, estimate the expected oil slick movement. | Call company for advice. |
| 1006 | You are Senior Deck Officer on a vessel and you have been in collision with an other vessel. The other vessel is on fire. What will you do? | Stay close to the other vessel and commence fire fighting. | Check your own vessel for any loss of life, danger of explosion and offer your assistance to the other vessel. | Leave the other vessel because the other vessel was to blame for the collision. | Commence arguing with the other Sen.Off.Deck about the reason for the collision. |
| 1007 | You are Senior Deck Officer onboard a merchant vessel. During the night you have been in collision with a sail boat. There is no sign of life in the water. What will you do? | Alarm the rescue centre and commence searching for any survivals. | Leave the position as fast as possible. | Just do nothing on your own; wait for assistance. | Call the company, explain the situation and ask for orders. |
| 1008 | You are the Senior Deck Officer of a vessel involved in a collision. All necessary actions to ensure safety of crew and vessel has been taken. What shall you then tell the Sen. Deck Off. on the other vessel? | Dont talk to the Sen. Deck Off. on the other vessel at all. | That you are sorry for the collision. | Name and Port of registry of your vessel. | Check with the pilot, or any witnesses, about their consideration of whom to blame for the collision. |
| 1009 | You are the Senior Deck Officer on vessel A and you have been involved in collision with vessel B. Your cargo is fuel oil. The oil cargo is leaking out and the weather condition is good. What will you do to avoid the oil to reach and pollute the coast line? | Asking any other vessel for immediately help. | by throwing chemicals on the water. | By doing nothing and hope that the current will move the oil slick into the open sea. | By putting the vessel mooring ropes as an oil boom around the vessel and the oil slick. |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 1010 | Your vessel has been involved in a collision, and at first opportunity a lot of people from outsides parties are asking questions. What shall you tell them? | Do not reply to any questions from outside parties, except the Solicitor appointed by your company. | You shall only tell them the truth and nothing but the truth. | Do not tell anybody anything, except representatives from the main newspapers, radio and TV. Remember, the people have the right to know. | To make sure that all parties are informed about the facts, show them the extracts of the log-book. |
| 1011 | Your vessel has been involved in a collision. As master you have to write about the accident in the log-book. In order to only write the facts in the log-book, which of the following procedures do you find most correct? | Write down all the facts you have collected, and also write down your own opinion about the circumstances. | Write down the story as favourable as possible seen from your own point of view. Make sure that your log-book tells your story. | Write continually in the log-book as soon as the accidents happen. | Find out from officers and crew who have been in connection with the collision, what they have seen, so that detailed and complete description of the sequence of events can be entered in the log-book. |
| 1012 | Your vessel has run aground and is touching bottom for the first one-quarter of its length. What is the LEAST desirable method from the standpoint of stability to decrease the bottom pressure? | Flood an after double bottom tank. | Pump out the forepeak tank. | Shift deck cargo aft. | Discharge forward deck cargo. |
| 1013 | Your vessel has run hard aground in an area subject to heavy wave action. Backing full astern failed to free her. Which action should be taken next? | Shift weight aft to reduce the forward draft. | Flood empty tanks to increase bottom pressure and prevent inshore creep. | Continue backing to scour out the bottom. | Wait for high tide and then try backing. |
| 1014 | After grounding, the extent of the damage to the vessel can be determined by: | Sounding of all compartments. | Checking if the engine room is flooded. | Testing if the engine is still working. | Taking sounding around the vessels. |
| 1015 | On stranding, the following are measures to be taken EXCEPT: | Watertight doors be locked. | The engineers should not change to high level water intakes. | On a falling tide, the engines should be put full astern. | The general alarm be sounded. |
| 1016 | To turn over an inflatable liferaft that is upside down, you should pull on the _____. | righting strap | canopy | manropes | sea painter |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 1017 | What is one of the most dangerous state of a human being may suffer if in sea water awaiting rescue? | Influenza | Cold | Broken limb | Hypothermia |
| 1018 | When a rescue vessel approaches a lifeboat in heavy seas, the person in charge of the lifeboat should : | do not approach the lifeboat | approach on the windward side | wait for calmer weather before transferring personnel | approach on the leeward side |
| 1019 | What shall a rescue person use if he has to jump into the water in order to assist a survivor? | survival suit and lifeline | lifejacket | lifeline | survival suit |
| 1020 | When personnel are lifted by a helicopter from an inflatable life raft, the personnel on the raft should: | Take in the sea anchor to prevent fouling of the rescue sling. | Deflate the floor of the raft to reduce the danger of the raft. | Inflate the floor of the raft to provide for additional stability. | Remove their lifejackets to prepare for the transfer. |
| 1021 | You are approaching another vessel and see that it has the signal flag O hoisted. What is your next action? | Attempt to call the vessel on VHF radiotelephone and begin a search because the vessel has a man overboard. | Proceed on present course and speed since the vessel is requesting a pilot. | Attempt to call the vessel on VHF radiotelephone because it is disabled. | Approach with caution because the vessel is stopped and making no way through the water. |
| 1022 | Which statement about the Williamson turn is FALSE? | It is the slowest of the methods used in turning the vessel. | It is the best turn to use when the victim is not in sight due to reduced visibility. | It requires the highest degree of shiphandling skills to accomplish. | It returns the vessel to the original track-line on a reciprocal course. |
| 1023 | You are picking up an unconscious person that has fallen overboard in a fresh breeze. For safety reasons a small craft should approach with the _____. | wind on your starboard side | victim to windward | victim to leeward | wind on your port side |
| 1024 | While your vessel is docked port side to a wharf, a sudden gale force wind causes the vessels stern lines to part. The stern begins to fall away from the dock, and no tugs are immediately available. Which measure(s) should you take FIRST? | Shut down any cargo transfer thats in progress. | Let go the port anchor and veer to a short scope of chain. | Obtain assistance from the terminal to put new stern lines out. | Notify the engine room of the need for propulsion. |

# OIC NAVIGATIONAL WATCH

| | | | | | |
|---|---|---|---|---|---|
| 1025 | You are duty officer on the bridge. A person is reported missing. Which of the following actions are to be considered as the correct maneuver in this situation? | Williamson Turn | Direct Turn | Scharnow Turn | Evinrude Turn |
| 1026 | You are duty officer on the bridge. An eye-witness is reporting man-overboard. Which of the following actions are to be considered as the correct maneuver in this situation? | Williamson Turn | Direct Turn | Scharnow Turn | Evinrude Turn |
| 1027 | Distress signal is indicated by rockets or shell, throwing red stars fired one at a time at | 1 minute interval | 2 minutes interval | short interval | equally spaced intervals |
| 1028 | After start of man-over-board maneuver, whom shall be informed? | Engine Room | Chief Officer | Galley | Electrician |
| 1029 | The maneuver which will return your vessel to a person who has fallen overboard in the shortest time is: | Two 180 degree turns | A Williamson turn | Engine(s) crash astern, no turn | A single turn with hard rudder |
| 1030 | The Scharnow turn should be used in a man overboard situation only when? | There has been sufficient time elapsed since the man went over to complete the maneuver. | The vessel has twin screws to assist in making the turn. | The man can be kept in sight from the bridge while maneuvering. | The turn is started immediately when the man goes over. |
| 1031 | You are proceeding to a distress site and expect large numbers of people in the water. Which statement is TRUE? | Survivors in the water should never be permitted alongside due to the possibility of injury from the vessel. | An inflatable liferaft secured alongside can be an effective boarding station for transfer of survivors from the boats. | You should stop to windward of the survivors in the water and only use the ships boats to recover the survivors. | If the survivors are in inflatable rafts you should approach from windward to create a lee for the survivors. |
| 1032 | You are proceeding to a distress site where the survivors are in liferafts. Which action will assist in making your vessel more visible to the survivors? | Making smoke in daylight. | Steering a sinuous course. | Dumping debris over the side to make a trail to your vessel. | Steering a zigzag course with 5 to 10 minutes on each leg. |
| 1033 | You are proceeding to a distress site. The survivors are in liferafts. What will make your ship more visible to the survivors? | Steering a sinuous course. | Dumping debris over the side to make a trail to your vessel. | Steering a zig-zag course. | Turning on all available deck lights at night. |

# OIC NAVIGATIONAL WATCH

| | | | | | |
|---|---|---|---|---|---|
| 1034 | Attempts to sever the towing hawser are unsuccessful. Which action should now be taken? | Use a chain as a double to the towline to prevent it from breaking. | Slip the towline and allow it to run off the drum. | Throw a preventer under the towing hawser and engage it. | Pull the towing hawser to tighten. |
| 1035 | You are attempting to take a dead ship in tow. All lines have been passed and secured. How should you get underway? | Order minimum turns until the catenary almost breaks the water, then stop. Order more turns as the hawser slackens but keep the catenary in the water. | Order minimum turns until the towing hawser is taut and then continue at that speed until towing speed is attained. | Order minimum turns until the towing hawser is just clear of the water, then reduce speed to that necessary to keep the line clear of the water. | If the towline is properly adjusted and weighted you can order slow or dead slow and the towline will act as a spring to absorb the initial shock. |
| 1036 | You are on a vessel that has broken down and are preparing to be taken in tow. You will use your anchor cable as part of the towline. Which statement is TRUE? | The anchor cable should be veered enough to allow the towline connection to be just forward of your bow. | The strain of the tow is taken by the riding pawl, chain stopper, and anchor windlass brake. | The anchor cable should be veered enough to allow the towline connection to be immediately astern of the towing vessel. | The anchor cable should be led out through a chock, if possible, to avoid a sharp nip at the hawsepipe lip. |
| 1037 | What is the Masters main responsibility when receiving a distress signal from any source? | Proceed to nearest Coastal Radio Station. | Check if your ship has sufficient bunkers for a rescue operation. | Proceed at highest speed to the distress source position. | Informing Head Office. |
| 1038 | Any act or activity undertaken to assist a vessel or any property in danger in any navigable water is considered as: | Salvage operations | Emergency assistance | Distress assistance | Rescue operations |
| 1039 | At sea red rocket signals are seen. This is not reported by radio. You have to begin the distress alert procedure via VHF with the term_____ | MAYDAY | MAYDAY RECU | Dont know | MAYDAY RELAY |
| 1040 | You are berthed with a steady offshore beam wind of 30 knots. This wind suddenly increases to 60 knots. When this happens , the force driving the vessel off-berth will be_____ . | quadrupled | doubled | tripled | quintupled |

# OIC NAVIGATIONAL WATCH

| | | | | | |
|---|---|---|---|---|---|
| 1041 | While your vessel is docked port side to a wharf, a sudden gale force wind causes the vessels bow lines to part. The bow begins to fall away from the dock, and no tugs are immediately available. Which measure(s) should you take FIRST? | Call the Master and the deck gang. | Let go the starboard anchor. | Slip the stern lines, let the vessel drift into the river, and then anchor. | Obtain assistance and attempt to put some new bow lines out. |
| 1042 | What should be given to officers and crew when an emergency occur? | Direction/Instructions are given to officers and crew to manage the emergency. | Ask the opinion of officers and crew as to how to manage the emergency. | Give the crew safety equipments to protect them. | Give them food and blankets to keem them warm and contented. |
| 1043 | What is the smallest area containing all possible survivors and search object locations? | Possibility area | Expanding square | Dangerous semi-circle | Containment area |
| 1044 | When should you use distress flares and rockets? | At half-hour intervals | At one-hour intervals | Immediately upon abandoning the vessel | Only when there is a chance of their being seen by rescue vessels |
| 1045 | An airplane should NOT send which signal in reply to a surface craft? | Opening and closing the throttle | Rocking the wings | Flashing the navigational lights off and on | Flashing Morse T |
| 1046 | Which equipment is not a source of locating signals? | EPIRB's that transmit on 406 MHz | Survival craft VHF transceivers that provide a beacon on 121.5 MHz | COSPAS-SARSAT EPIRBs | SARTs operating on 9 GHz |
| 1047 | What is the action that a GMDSS Radio Operator should take when a DSC distress alert is received? | The Operator should immediately set continuous watch on the NBDP frequency that is associated with the frequency band on which the distress alert was received. | The Operator should immediately set continuous watch on VHF channel 70. | The operator should immediately set continuous watch on the radiotelephone frequency that is associated with the frequency band on which the distress alert was received. | No action is necessary, as the DSC control unit will automatically switch to the NBDP follow-on communications frequency. |
| 1048 | If there are a number of survivors in the water after abandoning ship, they should _____. | form a small circular group to create a warmer pocket of water in the center of the circle | tie themselves to the unit so they won't drift with the current | send the strongest swimmer to shore for assistance | form a raft by lashing their life preservers together |
| 1049 | Which signal is recognized as a distress signal? | International Code Signal "PAN" spoken | A smoke signal giving off orange colored smoke | Directing the beam of a searchlight at | A whistle signal of one prolonged and three short |

# OIC NAVIGATIONAL WATCH

| | | | | | |
|---|---|---|---|---|---|
| | | over the radiotelephone | | another vessel | blasts |
| 1050 | Which step should be taken, if possible, when the vessel must be abandoned because of a distress situation? | Program the SART and EPIRB to transmit the vessel's location and situation. | Alert the U.S. Coast Guard by using the survival craft's portable INMARSAT unit. | Place the SART and EPIRB in the "ON" position and secure them to the survival craft. | No additional steps are needed as the SART and EPIRB will both automatically float free and operate properly. |
| 1051 | You are trying to rescue survivors from a wrecked vessel on fire. You should approach _____. | at a speed of at least that of the wrecked vessel | at a speed of at most one-half that of the wrecked vessel | to leeward of the wrecked vessel | to windward of the wrecked vessel |
| 1052 | What is the smallest area containing all possible survivors and search object locations? | Possibility area | Expanding square | Dangerous semi-circle | Containment area |
| 1053 | When should you use distress flares and rockets? | Immediately upon abandoning the vessel | At half-hour intervals | Only when there is a chance of their being seen by rescue vessels | At one-hour intervals |
| 1054 | An airplane should NOT send which signal in reply to a surface craft? | Opening and closing the throttle | Rocking the wings | Flashing the navigational lights off and on | Flashing Morse T |
| 1055 | When sending a DSC call, the vessel's _____. | None of the above | position will automatically be sent if the vessel is sending a "Distress Hot Key" alert | position will automatically be sent | MMSI will indicate its ocean region |
| 1056 | What does the DSC control unit do if the GMDSS Radio Operator fails to insert updated information when initiating a DSC distress alert? | It will initiate the DSC distress alert but, as no information will be transmitted, rescue personnel will not be able to identify the vessel, its position or its situation. | It will abort the transmission and set off an audible alarm that must be manually reset. | . It will initiate the DSC distress alert, but any station receiving it will have to establish contact with the distressed vessel to determine its identity, position and situation. | It will initiate the DSC distress alert and default information will automatically be transmitted. |
| 1057 | If a GMDSS radio operator initiates a DSC distress transmission but does not insert a message, what happens? | The transmission will be made with "default" information provided automatically. | The transmission is aborted and an alarm sounds to indicate this data must be provided by the operator. | The transmission is not initiated and "ERROR" is indicated on the display readout. | The receiving station will poll the DSC unit of the vessel in distress to download the necessary information |

| | | | | | |
|---|---|---|---|---|---|
| 1058 | Which action should be taken on receipt of a GMDSS Distress alert? | Listen for any follow up voice/TELEX transmission on the appropriate frequency. | All of the above | Silence the alarm. | Read the display screen and/or printout. |
| 1059 | What is the fundamental purpose for imposing radio silence? | To ensure that only voice communications can be effected on the distress frequency or channel | To ensure that a distressed vessel will have a "window" twice each hour for transmitting routine messages | To ensure that interference to proprietary communications is minimized | To ensure that interference on a particular frequency or channel to communications concerning emergency traffic is minimized |
| 1060 | When can routine communications be resumed when radio silence has been imposed? | If, in the Master's opinion, communications on that frequency will interfere with emergency communications | Routine communications can resume after the Rescue Coordination Center transmits a message on the frequency or channel being used for emergency communications stating that such traffic has concluded. | After determining that geographic distance from the distress situation will prohibit any other signal from interfering with emergency communications | After determining that the frequency or channel appears to be no longer in use |
| 1061 | What is meant by the term "radio silence"? | Stations not directly involved with the on-going Distress communications may not transmit on the distress frequency or channel | Stations remaining off the air to safeguard proprietary information | Two three-minute silent periods, at 15 and 45 minutes after the hour, that provide a transmitting "window" for distressed vessels to transmit distress alerts using J3E | Communications on a distress frequency or channel is banned for 24 hours following the cessation of the distress traffic |
| 1062 | How is "radio silence" imposed? | It is imposed by the High Seas Service (HSS) controlling the distress communications on that frequency or channel | By the On Scene Coordinator (OSC) | It is imposed by the Public Correspondence Station (PCS) controlling the distress communications on that frequency or channel | By the Coast Earth Station (CES) controlling the Distress communications on that frequency |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 1063 | What is the most appropriate action for a GMDSS Radio Operator to take in a distress situation where immediate help is needed, but the vessel is not sinking nor needs to be abandoned? | Transmit Distress call by MF/HF, VHF or INMARSAT. | Switch off EPIRB and SART manually. | Notify the RCC (Rescue Coordination Center) through VHF FM on Channel 13. | Transmit Distress call by activating the radiotelegraph automatic alarm signal. |
| 1064 | To recover a man overboard in a racetrack turn, the vessel is steadied for the SECOND time after a turn of how many degrees from the original heading? | 180 degrees | 135 degrees | 60 degrees | 360 degrees |
| 1065 | The VHF radiotelephone frequency for Channel 14 is: | 156.0 MHz | 156.6 MHz | 156.7 MHz | 156.8 MHz |
| 1066 | The VHF radiotelephone frequency for Channel 13 is: | 156.65 MHz | 156.70 MHz | 156.60 MHz | 156.80 MHz |
| 1067 | Channel 70 for digital selective calling for Distress, Safety and Calling frequency operate at: | 159.526 MHz | 158.526 MHz | 157.526 MHz | 156.526 MHz |
| 1068 | Channel 16 - Safety and calling frequency which operates in: | 159.800 MHz | 156.800 MHz | 157.800 MHz | 158.800 MHz |
| 1069 | An urgent marine storm warning message would be broadcast on: | 157.10 MHz (VHF-FM Ch. 22A) | 156.80 MHz (VHF-FM Ch. 16) | 2670 KHz | None of the above |
| 1070 | When planning the search, the CSS will first need to plot the datum and the initial most probable area. The radius of the center of datum is: | 15 miles | 5 miles | 2 miles | only when there is chance of them being seen by rescue vessels |
| 1071 | To recover a man overboard in a racetrack turn, the vessel is steadied for the SECOND time after a turn of how many degrees from the original heading? | 135 degrees | 180 degrees | 360 degrees | 60 degrees |
| 1072 | The VHF radiotelephone frequency for Channel 14 is: | 156.7 MHz | 156.8 MHz | 156.6 MHz | 156.0 MHz |
| 1073 | The VHF radiotelephone frequency for Channel 13 is: | 156.70 MHz | 156.80 MHz | 156.65 MHz | 156.60 MHz |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 1074 | Channel 70 for digital selective calling for Distress, Safety and Calling frequency operate at: | 156.526 MHz | 158.526 MHz | 157.526 MHz | 159.526 MHz |
| 1075 | Channel 16 - Safety and calling frequency which operates in: | 159.800 MHz | 158.800 MHz | 156.800 MHz | 157.800 MHz |
| 1076 | An urgent marine storm warning message would be broadcast on: | None of the above | 156.80 MHz (VHF-FM Ch. 16) | 2670 KHz | 157.10 MHz (VHF-FM Ch. 22A) |
| 1077 | When planning the search, the CSS will first need to plot the datum and the initial most probable area. The radius of the center of datum is: | only when there is chance of them being seen by rescue vessels | 2 miles | 5 miles | 15 miles |
| 1078 | The Coordinator Surface Search (CSS) in a SAR situation should display by night: | a red light, white light, and blue light in a vertical line | deck lights forward and aft | a white light over two red lights | a distinctive signal promulgated by the CSS |
| 1079 | Digital selective calling for Distress, Safety and Calling. | Channel 70 | Channel 16 | Channel 13 | Channel 69 |
| 1080 | Distress, Safety and Calling Channel. | Channel 69 | Channel 16 | Channel 70 | Channel 13 |
| 1081 | The Coordinator Surface Search in a SAR situation should display by day: | Code flag Quebec over a black ball | A black ball over a black diamond shape | Two black diamond shapes in a vertical line | The code flags FR |
| 1082 | You saw a man aboard a vessel and he is raising and lowering his outstretched arms to each side. This means: | a distress signal | all is clear, it is safe to pass | danger, stay away | make a direct approach, the man is drowning |
| 1083 | When are the Silence Periods on 2182 kHz MF? | For 6 minutes starting on the hour and half hour. | For 3 minutes every hour on the hour | For 3 minutes after each Hour and Half hour | For 6 minutes starting at quarter past and 45 minutes past. |
| 1084 | An airplane wants a vessels to change course and proceed towards a vessel in distress. The actions of the aircraft to convey this message will NOT include: | crossing ahead and rocking the wings | flashing the navigation lights on and off | heading in the direction of the distress location | circling the vessel at least once |
| 1085 | How would the letter "I" be pronounced over the radiotelephone? | IN DEE AH | I VAN HO | IN DEE GO | I EE |

| | | | | | |
|---|---|---|---|---|---|
| 1086 | In a man overboard situation, besides saving distance along the track line, what is the other advantage of the Scharnow Turn over the Williamson Turn? | In fog, if the turn is started as soon as the man goes over, the vessel will be at the point where he went over when the turn is completed | It can be used in both the immediate action and the delayed action situations | It returns the vessel to the original track line on a reciprocal course | It is faster |
| 1087 | An aircraft has indicated that he wants you to change course and follow him. You cannot comply because of an emergency on board. What signal should you make? | Send the Morse signal "N" by flashing light | Fire a red flare at night or a red smoke signal by day | Make a round turn (360 degrees) and resume course | Make an "S" turn (hard right then hard left) and resume course |
| 1088 | What is the telephony urgency message like? | RESCUE-RESCUE | MAYDAY | SECURITE | PAN-PAN |
| 1089 | Using VHF 16 What would you say in a SAFETY call and message? | SECURITE SECURITE SECURITE All stations, all stations, all stations. This is SHIP X, SHIP X, SHIP X. For Navigational Warning listen _ _ (working frequency) This is SHIP X | Pan-Pan Pan-pan Pan-Pan All stations, all stations, all stations. This is SHIP X, SHIP X, SHIP X. For Navigational Warning listen _ _ (working frequency) This is SHIP X | MAYDAY MAYDAY MAYDAY All stations, all stations, all stations. This is SHIP X, SHIP X, SHIP X. For Navigational Warning listen _ _ (working frequency) This is SHIP X | Any of the choices |
| 1090 | What is the safety call when giving warning to the vessel in the vicinity when your vessel had the engine breakdown? | Mayday spoken 3 times at frequent intervals | Securities spoken 3 times at frequent intervals | PAN spoken 3 times at frequent intervals | Emergency spoken 3 times at frequent intervals |
| 1091 | During a search, a RU would like to communicate by VHF radio telephone on channel indicated, she must signal what code group? | YY | GH | MI | MG |
| 1092 | How should the letter "O" be pronounced over the radiotelephone? | OCK TOW BER | OSS CAH | OA KAM | O RIAN |
| 1093 | There are three levels of radio traffic which have priority over ordinary traffic. Which among these is TRUE in their decreasing order? | PAN-PAN, MAYDAY, SECURITE | MAYDAY, SECURITE, PAN-PAN | MAYDAY, PAN-PAN, SECURITE | SECURITE, MAYDAY, PAN-PAN |

| | | | | | |
|---|---|---|---|---|---|
| 1094 | How is the letter "Q" pronounced when spoken on the radiotelephone? | KEH BECK | QUE BACK | QWE BEK | QU UE |
| 1095 | What is the purpose of VHF Channel 06? | Public traffic channel | Don't know | R/T Primary Intership, Maybe used in co-ordination of SAR ship to ship only. | R/T Primary Intership, Maybe used in co-ordination of SAR ship to ship and ship to aircraft. |
| 1096 | One major advantage of the round turn maneuver in a man overboard situation is that it: | is the fastest method | is easy for a single-screw vessel to perform | requires the least shiphandling skills to perform | can be used in reduced visibility |
| 1097 | In a rescue operations, a helicopter uses a special device which patients, in most cases, are being disembarked. It can quickly and safely be hooked on and off. | rescue net | rescue litter | rescue basket | rescue seat |
| 1098 | In a distress situation, the two tone alarm signal should be followed immediately by the: | spoken words "Mayday, Mayday, Mayday" | ship's call letters and Flag of registry | ship's name and nature of distress | ship's last known distress position |
| 1099 | What is the telegraphy and telephony urgency message like? | FFF/ RESCUE-RESCUE | SOS/ MAYDAY | XXX/ PAN-PAN | TTT / SECURITE |
| 1100 | How is the letter "T" pronounced when spoken over the radiotelephone? | TEE | TEEE | TAHO | TANG GO |
| 1101 | On-scene communication among the rescue ships and aircraft in the vicinity of distress should be under the control of whom? | On-scene Commander | the Master of the ship in distress | the Master of the ship being rescued | the Master of the rescue ship |
| 1102 | What safety message prefix is used to include a ship has important message to transmit concerning safety of navigation or meteorological warming? | Mayday | Pan Pan | Urgent | 10 miles |
| 1103 | What should be used when language difficulties exist which cannot be resolved by the used of the IMO Standard Marine Communication Phrases? | VHF watchkeeping | International Code of Signals | Communicate to coast stations | Changing channels |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 1104 | When using the International Code of Signals to communicate, the end of a radio telephone transmission is indicated by the signal: | AR | CQ | YZ | WA |
| 1105 | If you are forced to abandon ship in a liferaft your course of action should be to _____. | let the persons in the boat vote on what to do | head for the nearest land | remain in the immediate vicinity | head for the closest sea-lanes |
| 1106 | If for any reason it is necessary to abandon ship while far out at sea it is important that the crew members should: | get away from the area because sharks will be attracted to the vessel | remain together in the area because rescuers will start searching at the vessels last known position | separate from each other as this will increase the chances of being rescued | immediately head for the nearest land |
| 1107 | On what wave band does the search and rescue radar transponder operate? | 9 GHz | 2182kHz | 6 GHz | 8 GHz |
| 1108 | The distress message of a ship should include considerable information which might facilitate the rescue. This information should _____. | include the vessels draft | be sent to a Coast Guard station FIRST | be transmitted as a series of short messages if time allows | ALWAYS be included in the initial distress message |
| 1109 | The procedure of strengthening damaged structures on a MODU by using wood or steel is called _____. | shoring | battening | blocking | bracing |
| 1110 | To assure safe boarding and launching of a davit-launched liferaft from a MODU preparation should include which of the following choices? | testing to assure that the required lamps are functioning properly | removing any side protective rails and checking that the overside and surface level are clear | load testing the davit arm and the painter system | testing the spring loaded drum to assure it will retract the fall release hook |
| 1111 | What are the conditions under GMDSS whereby a ship is NOT allowed to depart from any port? | The vessel is not capable of performing all required distress and safety functions. | The vessel is carrying more than the required number of qualified GMDSS radio operators. | The vessel has a temporary waiver of its radio license and Safety Certificate. | The vessel is not carrying a GMDSS radio maintainer but has provided for shoreside maintenance plus duplication of equipment if required. |
| 1112 | What is one of the methods used by an aircraft to attract a vessels attention for participation in a rescue operation? | Dropping smoke signal. | Circle the vessel. | Diving from high attitude. | Flashing landing lights. |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 1113 | What is the search pattern system called using more than one ship? | Parallel System | Cross System | Circle System | Triangle System |
| 1114 | What should you do if you have transmitted a distress call a number of times on channel 16 and have received no reply? | | Repeat the message using any other channel on which you might attract attention. | Turn up the volume on the receiver before transmitting again. | Key the microphone several times before transmitting again. |
| 1115 | What would most likely prevent a SARTs signal from being detected? | The rescue personnel were monitoring the 10-cm radar | Signal absorption by the ionosphere | Heavy sea swells | The rescue personnel were monitoring the 3-cm radar |
| 1116 | When a vessel signals her distress by means of a gun or other explosive signal the firing should be at intervals of approximately _____. | 1 hour | 3 minutes | 10 minutes | 1 minute |
| 1117 | When abandoning ship and jumping into the water from a substantial height without a life jacket you should _____. | jump feet first covering your nose and mouth with one hand and grasping the opposing upper arm with the other | jump feet first holding your knees to your chest | hold your arms firmly at your sides and jump feet first | dive head first using your hands to break the surface of the water |
| 1118 | When evacuating a seaman by helicopter lift which course should the ship take? | A course that will have the hoist area in the lee of the superstructure. | Downwind so that the apparent wind is close to nil. | With the wind dead ahead because the helicopter is more maneuverable when going into the wind. | A course that will keep a free flow of air clear of smoke over the hoist area. |
| 1119 | When will the float-free emergency position indicating radio beacon be activated after abandoning ship? | Immediately after floating free | After about one hour when the salt water activates the battery | Only when keyed by the radar of another vessel | Only when daylight activates the photovoltaic cell |
| 1120 | Which communications functions must all vessels be capable of performing under GMDSS as defined by the International Maritime Organization? | All communications possible within the International Safety-NET service | Radio direction finding | Distress alerting to and from vessels search and rescue coordination on-scene communications signals for locating Maritime Safety Information general and bridge-to-bridge communications. | Communications in each of the operational ocean areas |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 1121 | Which of the following statements about transmitting distress messages by radiotelephone is INCORRECT? | It is advisable to follow a distress message on 2182 kHz by two dashes of 10 to 15 seconds duration. | If no answer is received on the designated distress frequencies repeat the distress call on any frequency available. | Channel 16 (156.8) may be used for distress messages. | Distress messages should first be transmitted on 2182 kHz. |
| 1122 | Which statement about the Williamson turn is FALSE? | It is the slowest of the methods used in turning the vessel. | It returns the vessel to the original track-line on a reciprocal course. | It requires the highest degree of shiphandling skills to accomplish. | It is the best turn to use when the victim is not in sight due to reduced visibility. |
| 1123 | Which statement concerning GMDSS Radio Operator requirements is FALSE? | Communications involving safety of life at sea do not have to be logged as long as the compulsory vessel was not involved in such communications . | Each compulsory vessel must carry at least two licensed Radio Operators at all times while at sea and may elect to carry a GMDSS Radio Maintainer as well. | Each compulsory vessel must carry at least two licensed GMDSS Radio Operators at all times while at sea. | While at sea adjustments to and the maintaining of GMDSS equipment may be performed by the GMDSS Radio operator as long as the work is supervised by an onboard licensed GMDSS Radio Maintainer. |
| 1124 | Which step should normally be taken FIRST by those who have boarded a liferaft in an emergency? | Check pyrotechnic supplies. | Ration food and water supplies. | Determine position and closest point of land. | Take anti-seasickness pills if available. |
| 1125 | Which system provides maximum communications range? | INMARSAT | Digital Selective Calling on 8414.5KHz | MF SITOR | VHF ARQ |
| 1126 | Which task is NOT the responsibility of the GMDSS Radio Operator? | Ensuring the SARTs batteries are replaced before their expiration date. | Inspecting and cleaning the SARTs container and clearing the immediate storage area of any debris or obstacles. | Placing the SART in the test mode and verifying that the nearby PPI shows concentric circles. | Measuring the SARTs transmitted frequency. |
| 1127 | You are in a lifeboat broadcasting a distress message. What information would be essential to your rescuers? | The nature of the distress | Your position by latitude and longitude | Your radio call sign | The time of day |
| 1128 | You are on watch and receive word that a person has fallen overboard from the starboard side. What should your first action be? | put the wheel hard right | put the engines full astern | notify the Master | sound the man overboard alarm |

| | | | | | |
|---|---|---|---|---|---|
| 1129 | You have abandoned your vessel. You are in a liferaft and have cleared away from your vessel. One of your FIRST actions should be to _____. | take measures to maintain morale | search for survivors | identify the person in charge of liferaft | prepare and use radio equipment |
| 1130 | You have hand launched an inflatable liferaft. What should be one of your FIRST actions after all persons have boarded the liferaft? | Open the equipment pack. | Decide on food and water rations. | Inflate the liferaft floor. | Cut the sea painter and clear the vessel. |
| 1131 | A crew member has just fallen overboard off your port side. Which action should you take? | Immediately put the rudder over hard left. | Immediately put the rudder over hard right. | Immediately put the engines astern. | Wait until the stern is well clear of the man and then put the rudder over hard right. |
| 1132 | A distress alert has accidentally been sent with the Inmarsat-C installation. One should now: | make contact with an RCC | wait until an RCC reports | turn of the transmitter | Any of the above |
| 1133 | A distress alert sent by Inmarsat to an RCC is sent via: | Any of the above | NCS | LUT | LES |
| 1134 | A distress frequency used on radiotelephone is _____. | 2182 kilohertz | 400 kilohertz | 8221 kilohertz | 2728 kilohertz |
| 1135 | A distress signal _____. | is used to indicate doubt about another vessel's intentions | consists of 5 or more short blasts of the fog signal apparatus | consists of the raising and lowering of a large white flag | may be used individually or in conjunction with other distress signals |
| 1136 | A distress-alert call from an RCC or coast-station, preceding distress alert relay, begins with: | MAYDAY PRUDENCE (3x) | Any of the above | MAYDAY RELAY (3x) | PAN PAN (3x) |
| 1137 | A DSC distress alert single frequency call attempt is awaiting acknowledgement: | automatically repeated after 1 to 1 and a half minutes | not repeated automatically | automatically repeated after 3 and a half to 4 and a half minutes | All of the above |
| 1138 | A DSC-message of the safety category is received by another vessel on 70. Conform to the GMDSS rules, for the continuation of the safety traffic, change to VHF-channel: | 70 | 7 | 16 | Any of the above |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 1139 | A man aboard a vessel, signaling by raising and lowering his outstretched arms to each side, is indicating _____. | a distress signal | danger, stay away | all is clear, it is safe to pass | all is clear, it is safe to approach |
| 1140 | A man was sighted as he fell overboard. After completing a Williamson turn, the man is not sighted. What type of search should be conducted? | Parallel track pattern | Datum-drift search | Sector search | Expanding circle |
| 1141 | A message giving warning of a hurricane should have which prefix when sent by radiotelephone? | Pan-Pan (3 times) | No special prefix | TTT TTT TTT | Securite Securite Securite |
| 1142 | A message warning of a tropical storm or ice in the area should be sent as a(n): | distress message | safety message | urgency message | routine message |
| 1143 | A person who observes an individual fall overboard should do which of the following? | call for help and keep the individual in sight | go to the control room for the distress flares | run to the radio room to send an emergency message | immediately jump into the water to assist the individual |
| 1144 | A plane circles your vessel, crosses your course at a low altitude opening and closing his throttle and heads off in a direction which you are to be directed. How you indicate your INABILITY to comply? | Hoist the answering pennant. | Flash the Morse Code procedure signal T. | Emit large quantities of black smoke from your stack. | Hoist the international code flag November (N) |
| 1145 | A racetrack turn would be better than a Williamson turn in recovering a man overboard if _____. | the sea water is very cold and the man is visible | the man has been missing for a period of time | there is thick fog | the wind was from astern on the original course |
| 1146 | A rescue helicopter's hoist should have a radius of at least_____? | 6 feet of clear deck | 10 feet of clear deck | 25 feet of clear deck | 50 feet of clear deck |
| 1147 | A seaman is reported missing in the morning and was last seen after coming off the mid-watch. Which type of turn would you use to return to the track-line steamed during the night? | Williamson | Racetrack | 180deg turn | Anderson |
| 1148 | A vessel is flying the signal BJ-1 from her starboard halyard. The signal means _____. | the aircraft is still afloat | an aircraft is ditched in position indicated | there is no danger of explosion | an aircraft is circling over an accident |
| 1149 | After abandoning ship which action should be taken IMMEDIATELY upon entering a liferaft? | Issue anti-seasickness medicine. | Dry the liferaft floor and inflate. | Get clear of the ship. | Open equipment pack. |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 1150 | After abandoning ship, you should deploy the sea anchor from a liferaft to _____. | navigate against the current | stay in the general location | keep personnel from getting seasick | keep the liferaft from capsizing |
| 1151 | After having activated the emergency position indicating radio beacon, you should _____. | leave it on continuously | turn it off and on at 5 minute intervals | turn it off during daylight hours | turn it off for 5 minutes every half-hour |
| 1152 | All designated SAR aircraft and civil aircraft carry equipment operating on the international aeronautical distress frequencies (amplitude modulation). The aeronautical distress frequencies are? | 127.8 MHz and/or 349.6 MHz | 121,3 MHz and/or 243,0 MHz | 123,8 MHz and/or 247,6 MHz | 243,1 MHz and/or 486,2 MHz |
| 1153 | All of the following are recognized distress signals under the Navigation Rules EXCEPT _____. | the repeated raising and lowering of outstretched arms | orange-colored smoke | red flares | a green star signal |
| 1154 | An aircraft passes nearby an isolated island and sees a flag V being signaled conspicuously ashore. What message is being sent? | Require assistance | Require food rations | Please acknowledge | Require medical assistance |
| 1155 | An uncontrolled flow of gas, oil, or other well fluids into the atmosphere is called a _____. | kick | blowout | breakout | flow |
| 1156 | If you are in urgent need of a helicopter, which signal code should you send? | BZ | BT1 | BR | BS |
| 1157 | A vessel is flying the signal BJ-1 from her starboard halyard. The signal means _____. | an aircraft is circling over an accident | an aircraft is ditched in position indicated | the aircraft is still afloat | there is no danger of explosion |
| 1158 | You are proceeding to the area of reported distress. When you arrive at the reported position, the vessel in distress is not sighted. What type of search should be conducted? | Sector search | Track crawl | Parallel track search | Expanding square search |
| 1159 | When is the appropriate time for setting off distress flares and rockets? | Only when there is chance of them being seen by rescue vessels. | During daytime only. | During night time only. | Anytime. |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 1160 | If, for any reason, it is necessary to abandon ship while far out at sea, it is important that the crew members should: | immediately head for the nearest land | get away from the area because sharks will be attracted to the vessel | separate from each other as this will increase the chances of being rescued | remain together in the area because rescuers will start searching at the vessels last known position |
| 1161 | You are the OOW at sea. During your watch, you collided with a sailing vessel and no sign of life seen in the water. What action would you do? | Stay calm and instruct your lookout to keep quiet | Alarm the rescue coordination center and commence searching for survivors | Call the company and ask for orders | Proceed to your voyage as if nothing has happened |
| 1162 | Who is the Co-ordinator Surface Search? (MERSAR 0.6) | A vessel, other than a rescue unit, designated to co-ordinate surface search and rescue operations within a specified area. | The first vessel arriving on the scene and starting the search and rescue operation. | The land based centre which are co-ordinating the search and rescue operation. | A rescue unit designated to co-ordinate surface search and rescue operations within a specified search area. |
| 1163 | During search and rescue operations an aircraft crosses the wake of your vessel close astern at low altitude. What does it indicate, if the aircraft rocks its wings, opens and closes the throttle or changes the propeller pitch? | Please call me on VHF 16 as you are not answering my calls | Your assistance is no longer required | Please remain where you are and await further instructions | Follow my direction to the ship in distress |
| 1164 | Several merchant ships are arriving at the scene of a distress incident. One of the them must assume the duties of the Coordinator Surface Search (CSS). Which of the following statements is TRUE? | CSS duties are always assumed by passenger vessels, dry cargo vessels, or tankers in that order of precedence. | A tank vessel should never be assigned CSS duties unless only tank vessels are present. | The CSS must be established by mutual agreement between the ships concerned. | The first vessel to arrive at the distress incident is designated as the CSS. |
| 1165 | When no RU (Rescue Unit), but a number of merchant vessels are participating in a search and rescue operation, one of the vessels should be designated as CSS ( Co-ordinator Surface Search), Which practice should be followed in designation of the CSS? | Mutual agreement between participating vessels. | RCC (Rescue Co-ordination Centre). | First vessel arriving on the scene. | RSC (Rescue Sub-Centre) |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 1166 | Where several rescue units (RU) are engaged in a search and rescue operation, one of the RU should be designated as OSC (On Scene Commander). Which one of the listed practices for designating an OSC does correspond to the guidance provided by MERSAR? | OSC to be the ship with the best maneuvering performance. | OSC to be the first rescue unit to arrive at the scene. | OCS to be permanently appointed within each SRR (Search and Rescue Region). | OSC to be designated by an appropriate RCC or RSC. |
| 1167 | What is a Search and Rescue Region (SRR)? | An area of defined dimensions within which search and rescue services are provided. | An area where a search and rescue operation is ongoing. | An area of limited dimension in which rescue vessels are permanently stationed. | An area of defined dimension where an international organization is responsible for search and rescue operations. |
| 1168 | What is the search system pattern called using 1 vessel? | Square System | Sector System | Lonely System | Single System |
| 1169 | What is the search pattern system called using more than one ship? | Triangle System | Circle System | Parallel System | Cross System |
| 1170 | SART is short for_____ | Search and Rescue Radar Transponder | Search and Rescue Radar Transmitter | Dont know | Safety and Rescue Radar Transmitter |
| 1171 | A man was sighted as he fell over board. After completing a williamson turn, the man is not sighted. What type of search should be conducted? | Parallel track pattern | Datum-drift search | Expanding circle | Sector search |
| 1172 | You have abandoned ship and after two days in a raft, you can see an aircraft near the horizon apparently carrying out a search pattern. You should: | Turn on the strobe light on the top of the EPIRB | Use visual distress signals in conjunction with the EPIRB | Use the voice transmission capability of the EPIRB to guide the aircraft to your raft | Switch the EPIRB to the homing signal mode |
| 1173 | The Coordinator Surface Search (CSS) in a SAR situation should display by night _____. | a distinctive signal promulgated by the CSS | a white light over two red lights | a red light, white light, and blue light in a vertical line | deck lights forward and aft |

| | | | | | |
|---|---|---|---|---|---|
| 1174 | When a number of merchant vessels, but no rescue units or warships, are participating in a search and rescue operation, one of the vessels will have to assume the duty as co-ordinator (CSS). Which one of the listed items is most important when designating a CSS? | The maneuvering of the vessels. | Senior deck officers rescue operations experience. | Service speed of the vessels. | Good radio communication facilities (preferable 2182 kHz and/or 156.8 MHz (channel 16) radiotelephony and 500 kHz radiotelegraphy). |
| 1175 | You are proceeding to the area of reported distress. When you arrive at the reported position, the vessel in distress is not sighted. What type of search should be conducted? | Expanding square | Parallel track search | Sector search | Track crawl |
| 1176 | You are proceeding of the area of reported distress. When you arrived at the reported position, the vessel in distress is not sighted. What type of search should be conducted? | Track crawl | Sector search | Initial search | Expanding square |
| 1177 | Your vessel have been in collision and you are not sure if your vessel is sinking or not. How will you handle this situation? | Search for missing persons. Continue to monitor situation and prepare for abandonment in case it become necessary. | Wait and see how the situation is developing. | Leave the vessel and stay not closer than 5 nautical miles. | Make sure that the life boat has as much bunker as possible and make you course for nearest land. |
| 1178 | The MERSAR is_____ | Dont know | a fully automated system for mutual assistance and rescue of persons at sea | a survey of vessels favourably located for possible rescue during SAR operations | a book of directions for search and rescue at sea |
| 1179 | When carrying out a parallel track search pattern, the course of the search unit normally be which of the following? | In the same direction as the anticipated drift | Perpendicular to the line of anticipated drift | Downwind | In the opposite direction of the anticipated drift |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 1180 | In establishing the most probable area within the search target is most likely to be, and all, a radius of _____ miles is drawn from the datum and squaring it off with tangents. | 15 miles | 20 miles | 5 miles | 10 miles |
| 1181 | The Coordinator Surface Search in a SAR situation should display by day _____. | The code flags FR | A black ball over a black diamond shape | Code flag Quebec over a black ball | Two black diamond shapes in a vertical line |
| 1182 | The most probable position of the object of a search at any given time is the _____. | dead-reckoning position | datum position | reported position | incident position |
| 1183 | You should conduct a sector search under which of the following circumstances? | An aircraft is available to assist a surface vessel. | More than one vessel is available for a search. | The search object is a target that will be readily detected by radar. | The search target is sighted and then lost. |
| 1184 | If more than one raft is manned after the vessel has sunk, you should _____. | tie the rafts together and try to stay in a single group | go in a different direction in search of land | spread out to increase the possibility of a search aircraft finding you | reduce the number of rafts by getting as many people as possible into as few rafts as possible |
| 1185 | For short range communication, which of the following VHF channel frequency is used for distress, search and rescue and on-scene coordination by radio telephony? | 518kHZ | 2182kHZ | 1568kHZ | 500kHZ |
| 1186 | On what wave band does the search and rescue radar transponder operate? | 6 GHz | 9 GHz | 2182kHz | 8 GHz |
| 1187 | Responsible for the on-scene coordination during search and rescue operations is_____ | On Scene Commander | On Scene Coordinator | Flight Information Rescue-coordinator | Dont know |
| 1188 | What is a Rescue Sub-Centre (RSC)? | A center established to assist the main national rescue centre. | A centre for underwater search and rescue operation. | A unit subordinate to a rescue co-ordinating centre. | A national search and rescue centre subordinate to an international search and rescue co-ordinating centre. |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 1189 | What is a Rescue Unit (RU)? | A permanently manned rescue vessel. | A unit composed of trained personnel suitably equipped for expeditious search and rescue operations. | A unit specializing in search and rescue operations at sea. | |
| 1190 | You are doing a Williamson turn. Your vessel has swung about 60degrees from the original course heading. You should: | Shift your rudder | Put the rudder amidships and check the swing | Stop the engines and prepare to maneuver to pick up the man in the water | Increase to maximum speed |
| 1191 | You should conduct a sector search under which of the following circumstances? | The search object is a target that will be readily detected by radar. | The search target is sighted and then lost. | An aircraft is available to assist a surface vessel. | More than one vessel is available for a search. |
| 1192 | A rescue helicopters hoist area should have a radius of at least _____. | 10 feet of clear deck | 25 feet of clear deck | 6 feet of clear deck | 50 feet of clear deck |
| 1193 | HEL-H is the abbreviation of a heavy helicopter radius of action for rescue purposes. What do you think the radius and evacuating capacity of the helicopter is? | 200 nm and capacity for evacuating more then 15 persons. | 500 nm and capacity for evacuating more than 25 persons. | 150 nm and capacity for evacuating more than 12 persons. | 100 nm and capacity for evacuating more than 10 persons. |
| 1194 | If a helicopter is going to land on board your ship, what measure should you take? | Stop your ship and pour fuel to dampen the sea. | Clear the landing site and mark it with a large white H. | Sail into the wind at the highest speed possible. | Have a rescue team ready in case the helicopter falls into the sea. |
| 1195 | If requested by a coastal radio station to participate in a rescue operation, what is the most important information you may give? | Your position, name, call sign and speed | Your own cargo owner | Your crews nationality | Your destination |
| 1196 | Inflatable rescue boats shall be so constructed as to be capable of withstanding exposure for _____ in all sea condition. | 50 days | 30 days | 15 days | 40 days |
| 1197 | Under the GMDSS, to avoid all ships in a large sea area being alerted, a transmission mode is made by the rescue coordinating center so that only those ships in vicinity of distress are alerted. This is called _____. | Selective distress alerting | Area check | Distress vicinity message | Area call |

| | | | | | |
|---|---|---|---|---|---|
| 1198 | What is one of the methods used by an aircraft to attract a vessels attention for participation in a rescue operation? | Circle the vessel. | Dropping smoke signal. | Flashing landing lights. | Diving from high attitude. |
| 1199 | What is the centre for overall co-ordination of rescue operations called? | Maritime Rescue Co-ordination Centre | Ship Distress Centre | Emergency Ship Distress Centre | Rescue Co-ordination Centre |
| 1200 | What is the vessel that has the local command in a rescue operation called? | Commander of Operation | Local Rescue Commander | On Scene Commander | Commander of Rescue Operation |
| 1201 | If, for any reason, it is necessary to abandon ship while far out at sea, it is important that the crew members should _____. | remain together in the area because rescuers will start ing at the vessels last known position | separate from each other as this will increase the chances of being rescued | get away from the area because sharks will be attracted to the vessel | immediately head for the nearest land |
| 1202 | How can a SARTs effective range be maximized? | The SART should be placed in water immediately upon activation. | Switch the SART into the high power position. | The SART should be held as high as possible. | If possible, the SART should be mounted horizontally so that its signal matches that of the searching radar signal. |
| 1203 | A plane circles your vessel, crosses your course at a low altitude opening and closing his throttle and heads off in a direction which you are to be directed. How you indicate your INABILITY to comply? | Emit large quantities of black smoke from your stack. | Flash the Morse Code procedure signal T. | Hoist the answering pennant. | Hoist the international code flag November (N) |
| 1204 | All designated SAR aircraft and civil aircraft carry equipment operating on the international aeronautical distress frequencies (amplitude modulation). The aeronautical distress frequencies are? | 121,3 MHz and/or 243,0 MHz | 123,8 MHz and/or 247,6 MHz | 243,1 MHz and/or 486,2 MHz | 127.8 MHz and/or 349.6 MHz |
| 1205 | An airplane wants a vessel to change course and proceed towards a vessel in distress. The actions of the aircraft to convey this message will NOT include _____. | heading in the direction of the distress location | circling the vessel at least once | flashing the navigation lights on and off | crossing ahead and rocking the wings |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 1206 | During a helicopter evacuation, the helicopter lowers its winch wire to the deck. Which of the following should NOT be done with the winch wire? | Touch the wire with bare hands. | All of the mentioned actions. | Secure it to a strong point on deck. | Secure it to the deck with a weak link. |
| 1207 | During helicopter evacuation of an injured man, what course should the ship steer? | as instructed by the helicopter pilot | directly into the wind | With the wind fine on the bow opposite to the helicopter operating area | With the wind astern so that the effect of the wind is reduced as much as possible |
| 1208 | During helicopter winching operations over the deck of a vessel needing assistance, the handler should be equipped with electricians gloves and rubber soled shoes to avoid _____. | being grounded by helicopter currents | injury caused by the heat from helicopter engines | hock from static discharge | Injury caused by the winch lines |
| 1209 | When a helicopter is lifting a person from an enclosed lifeboat, the others in the boat should: | Remove their life jackets to prepare for their transfer to the helicopter | Remain seated inside to provide body weight for stability | Stand on the outside to prepare for their transfer to the helicopter | Enter the water in case the person being lifted slips from the sling |
| 1210 | When evacuating a seaman by helicopter lift, which course should the ship take? | A course that will keep a free flow of air, clear of smoke, over the hoist area. | With the wind dead ahead because the helicopter is more maneuverable when going into the wind. | Downwind so that the apparent wind is close to nil. | A course that will have the hoist area in the lee of the superstructure. |
| 1211 | When evacuating a seaman by helicopter lift, which statement is TRUE? | The drop line should be grounded first then secured as close to the hoist point as possible. | Flags should be flown to provide a visual reference as to the direction of the apparent wind. | The vessel should be stopped with the wind dead ahead during the hoisting operation. | The hoist area should be located as far as possible so the pilot will have a visual reference while approaching. |
| 1212 | When evacuating a seaman by helicopter lift, which statement is TRUE? | The litter should not be touched until it has been grounded. | The vessel should be slowed to bare steerageway. | If the hoist is at the stern, booms extending aft at the stern should be cradled with the topping lifts hove taut. | Evacuation should be from an area forward of the bridge. |

| | | | | | |
|---|---|---|---|---|---|
| 1213 | You must evacuate a seaman by helicopter lift. Which statement is TRUE? | The ship should be stopped with the wind off the beam while the helicopter is hovering overhead. | The tending line of the litter basket should be secured to the ship beyond the radius of the helicopter blades. | The basket or stretcher must not be allowed to touch the deck. | The hoist line should be slack before the basket or stretcher is hooked on. |
| 1214 | When rescuing persons from a disabled ship or a wreck, what is another option if you cannot launch your boats? | Use a scrambling net where they can climb to the rescuing vessel. | Woit for assistance from RCC. | Standby to throw fiber ropes to the persons in the water to pull them up. | Throw them lifejackets so they can float while waiting for rescue boats from other rescuers. |
| 1215 | The AMVER system for vessels in the Gulf of Mexico is administered by the _____. | Department of Energy | Corps of Engineers | Minerals Management Service | U.S. Coast Guard |
| 1216 | AMVER is a system which provides _____. | Position reporting service | Weather information | Navigational information | Satellite communications |
| 1217 | When making VHF radio calls to nearby stations, what level of transmitting power should you use? | Extra high power | Medium power | High power | Low power |
| 1218 | When sending and receiving messages on the marine radio, confusion over unusual words can be avoided by using the _____. | High power switch | Standard phonetic alphabet | Delimiter switch | Low power switch |
| 1219 | Which satellite system promulgated Maritime Safety Information? | SafetyNET | AMVER | NAVTEX | INMARSAT-M SES |
| 1220 | How is "radio silence" imposed? | By the High Seas Service (HSS) controlling the distress communications on that frequency or channel. | By the Rescue Coordination Center (RCC) controlling the distress communications on that frequency or channel | By the Public Correspondence Station (PCS), controlling the distress communications on that frequency or channel | By the Coast Earth Station (CES) controlling the distress communications on that frequency or channel |
| 1221 | How does a coast radio station communicating by HF radio normally identify itself? | By its MMSI | By its MID | By its call sign | By its subscriber number |
| 1222 | The AMVER system for vessels in the Gulf of Mexico is administered by the _____. | U.S. Coast Guard | Minerals Management Service | Department of Energy | Corps of Engineers |

| | | | | | |
|---|---|---|---|---|---|
| 1223 | When making VHF radio calls to nearby stations, what level of transmitting power should you use? | Extra high power | High power | Medium power | Low power |
| 1224 | When communicating on the radiotelephone using plain English, what procedure word indicates the end of my transmission and that a response is necessary? | Over | Out | Roger | Wilco |
| 1225 | If you are transmitting a distress message by radiotelephone you should _____. | preface it by the word "Interco" | follow the transmission with the radio alarm signal | always use the International Code | use English language |
| 1226 | Any person maintaining a listening watch on a bridge-to-bridge radiotelephone must be able to _____. | send Morse Code | speak a language the vessel's crew will understand | speak English | repair the unit |
| 1227 | You are piloting a vessel, which is required to have a radiotelephone, on the navigable waters of the United States. You must _____. | All of the above | have on board an operator who holds a restricted radiotelephone operator permit or higher license, as well as a FCC ship station license | use the bridge-to-bridge VHF-FM designated frequency only to exchange navigational information or necessary tests | maintain a listening watch and communicate in English |
| 1228 | You wish to communicate by radiotelephone with a foreign vessel using the International Code of Signals. This is indicated by the signal _____. | . "Code" | "Interco" | "Kilo" | "Charlie Quebec" |
| 1229 | What is the International Code signal for calling an unknown station using flashing light? | UNK | CQ | AA AA | STA |
| 1230 | The radiotelephone safety message urgently concerned with safety of a person would be prefixed by the word _____. | Pan | Mayday | Safety | Interco |
| 1231 | The signal "AS" when used in signaling by the International Code of Signals means "_____". | Over | Wait | Finished with transmission | Repeat this signal |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 1232 | When using the International Code of Signals to communicate, the end of a radiotelephone transmission is indicated by the signal _____. | YZ | WA | CQ | AR |
| 1233 | If you receive the signal over radiotelephone of "Romeo Papa Tango" while using the International Code of Signals, you should _____. | repeat your last transmission | report to the caller | continue since he received your last transmission | end the transmission |
| 1234 | You are calling another vessel by radiotelephone using the International Code of Signals. He responds with the words "Alpha Sierra". This indicates that _____. | you should send your message in plain language | you should send your message in International Code | he cannot accept traffic immediately | you should proceed with your message |
| 1235 | When signaling a course using the International Code of Signals, the signal _____. | should be preceded by the letters CSE | always indicates a true course unless indicated otherwise in the message | should include the compass deviation if a compass course is signaled | must be followed by "T", "M" or "C" to indicate if it is true, magnetic or compass |
| 1236 | In restricted visibility, a power-driven vessel underway but stopped and making no way through the water shall sound which of the following fog signals? | MIKE | BRAVO | GOLF | CHARLIE |
| 1237 | What is the fog-signal for a power-driven vessel underway but stopped and making no way through the water? | GOLF | CHARLIE | MIKE | BRAVO |
| 1238 | How should you, as helmsman, give feedback to the OOW (officer on watch) that his orders are understood? | By saying: "Yes Sir" | By repeating the order | By saying: "OK" | You don't have to give any feedback |
| 1239 | When you are steering on a pair of range lights and find the upper light is above the lower light you should: | continue on the present course | come left | come right | wait until the lights are no longer in a vertical line |
| 1240 | The fog-signal for a vessel being towed (last vessel of the tow, if manned) is: | PAPA | BRAVO | ECHO | No signal required |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 1241 | For a vessel engaged in fishing, what is her fog signal? | FOXTROT | MIKE | DELTA | No signal required |
| 1242 | What is the main purpose of seaspeak? | Reduce maritime communication problems | Improve the navigator's communication skills | Make more use of standard english | Improve the use of IMO Standard Vocabulary |
| 1243 | By day, vessels engaged in pair trawling may display which of the following? | International code flag "PT" flown at the foremost | International code flag "T" flown at the foremost | International code flag "P" flown at the foremost | No necessary signal to be shown |
| 1244 | If the helmsman changes from right rudder to left rudder, or vice versa, in equal number of degrees. What is the helm command? | shift your rudder | ease the rudder | swing your rudder | meet her |
| 1245 | What is the equivalent fog signal of a "power-driven vessel, making way" in the International Code single-letter Signal? | MIKE | ROMEO | TANGO | DELTA |
| 1246 | What will you do if you are helmsman and the OOW (officer on watch) gives you the order: "Port 20" and after a while the order: "Ease your helm" | Put the rudder to starboard to ease the turn | Turn the rudder towards midship, but normally not all the way to midship position | Put the rudder to midship position | Put the rudder all the way to starboard to stop the turn |
| 1247 | In a narrow channel or fairway, the maneuvering and warning signal of a vessel intending to overtake another vessel on her port side is: | single letter signal "ZULU" | single letter signal "TANGO" | single letter signal "ECHO" | single letter signal "BRAVO" |
| 1248 | The last vessel of the tow (if manned) shall sound which of the following fog signals? | Single letter signal GOLF | Single letter signal ECHO | Single letter signal BRAVO | Single letter signal DELTA |
| 1249 | A vessel approaching a bend shall sound which of the following signals where other vessels may be obscured by an intervening obstruction? | Single letter signal X-RAY | Single letter signal TANGO | Single letter signal WHISKEY | Single letter signal VICTOR |
| 1250 | In the following International Code single-letters, which is the equivalent fog signal of a "vessel restricted in her ability to maneuver"? | single-letter signal "DELTA" | single-letter signal "FOXTROT" | single-letter signal "JULIETTE" | single-letter signal "KILO" |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 1251 | A vessel when she is towing shall sound what fog-signals? | WHISKEY | TANGO | DELTA | VICTOR |
| 1252 | It is the equivalent fog signal of a "vessel not under command" in the International Code single-letter Signal. | MIKE | UNIFORM | SIERRA | DELTA |
| 1253 | What is/are the content of table #1 of radiotelephony procedures? I. Nature of distress in code from the International code of signals II. Phonetic alphabets and figure spelling III. Position in code from the International code of signals | I only | II only | III only | I, II & III |
| 1254 | In restricted visibility, a power-driven vessel underway but stopped and making no way through the water shall sound which of the following fog signals? | MIKE | BRAVO | GOLF | CHARLIE |
| 1255 | What is the fog-signal for a power-driven vessel underway but stopped and making no way through the water? | CHARLIE | BRAVO | MIKE | GOLF |
| 1256 | How should you, as helmsman, give feedback to the OOW (officer on watch) that his orders are understood? | You don't have to give any feedback | By saying: "Yes Sir" | By saying: "OK" | By repeating the order |
| 1257 | When you are steering on a pair of range lights and find the upper light is above the lower light you should: | continue on the present course | come left | come right | wait until the lights are no longer in a vertical line |
| 1258 | The fog-signal for a vessel being towed (last vessel of the tow, if manned) is: | ECHO | BRAVO | PAPA | No signal required |
| 1259 | For a vessel engaged in fishing, what is her fog signal? | DELTA | FOXTROT | MIKE | No signal required |
| 1260 | What is the main purpose of seaspeak? | Improve the navigator's communication skills | Reduce maritime communication problems | Improve the use of IMO Standard Vocabulary | Make more use of standard english |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 1261 | By day, vessels engaged in pair trawling may display which of the following? | International code flag "P" flown at the foremost | No necessary signal to be shown | International code flag "PT" flown at the foremost | International code flag "T" flown at the foremost |
| 1262 | If the helmsman changes from right rudder to left rudder, or vice versa, in equal number of degrees. What is the helm command? | shift your rudder | meet her | swing your rudder | ease the rudder |
| 1263 | What is the equivalent fog signal of a "power-driven vessel, making way" in the International Code single-letter Signal? | MIKE | DELTA | TANGO | ROMEO |
| 1264 | What will you do if you are helmsman and the OOW (officer on watch) gives you the order: "Port 20" and after a while the order: "Ease your helm" | Put the rudder to starboard to ease the turn | Put the rudder to midship position | Put the rudder all the way to starboard to stop the turn | Turn the rudder towards midship, but normally not all the way to midship position |
| 1265 | In a narrow channel or fairway, the maneuvering and warning signal of a vessel intending to overtake another vessel on her port side is: | single letter signal "ZULU" | single letter signal "TANGO" | single letter signal "ECHO" | single letter signal "BRAVO" |
| 1266 | The last vessel of the tow (if manned) shall sound which of the following fog signals? | Single letter signal DELTA | Single letter signal ECHO | Single letter signal GOLF | Single letter signal BRAVO |
| 1267 | A vessel approaching a bend shall sound which of the following signals where other vessels may be obscured by an intervening obstruction? | Single letter signal X-RAY | Single letter signal TANGO | Single letter signal WHISKEY | Single letter signal VICTOR |
| 1268 | In the following International Code single-letters, which is the equivalent fog signal of a "vessel restricted in her ability to maneuver"? | single-letter signal "KILO" | single-letter signal "FOXTROT " | single-letter signal "DELTA" | single-letter signal "JULIETTE" |
| 1269 | A vessel when she is towing shall sound what fog-signals? | DELTA | TANGO | VICTOR | WHISKEY |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 1270 | It is the equivalent fog signal of a "vessel not under command" in the International Code single-letter Signal. | MIKE | SIERRA | DELTA | UNIFORM |
| 1271 | What is/are the content of table #1 of radiotelephony procedures? I. Nature of distress in code from the International code of signals II. Phonetic alphabets and figure spelling III. Position in code from the International code of signals | II only | I only | III only | I, II & III |
| 1272 | A message warning of a tropical storm should be sent as a(n) _____. | distress message | safety message | routine message | urgent message |
| 1273 | All VHF marine band radios operate in the simplex mode which means that _____. | only one person may talk at a time | only two persons may talk at the same time | the radio only receives | the radio only transmits |
| 1274 | How should the number 1 be pronounced when spoken on the radiotelephone? | NEW-MAL-WON | NUM-EV-WUN | OO-NAH-WUN | OO-NO |
| 1275 | If a crew member that was ill has died which code should your message contain? | MPO | MPR | MPK | MPJ |
| 1276 | If any part of the message are considered sufficiently important to need safeguarding say: | Repeat ... - followed by the corresponding part of the message. | I say again ... - followed by the corresponding part of the message. | I reiterate ... - followed by the corresponding part of the message. | Take note ... - followed by the corresponding part of the message. |
| 1277 | It should be expressed in the 24 hour UTC notation; if local time will be used in ports or harbours it should clearly be stated. | Interval | Periods | Times | Phase |
| 1278 | Message Markers. This indicates that the following message is restricted to observed facts situations etc.. | Advice | Information | Warning | Instruction |
| 1279 | Preferably to be expressed in nautical miles or cables (tenths of a mile) otherwise in kilometres or metres the unit always to be stated. | Distances | Space | Expanse | Vastness |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 1280 | The Coordinator Surface Search in a SAR situation should display by day _____. | code flag Quebec over a black ball | a black ball over a black diamond shape | two black diamond shapes in a vertical line | the code flags FR |
| 1281 | The national distress safety and calling frequency is channel _____. | 16 | 22 | 13 | 18 |
| 1282 | The VHF radiotelephone calling/safety/distress frequency is _____. | 156.7 MHz (channel 14) | 156.65 MHz (channel 13) | 156.6 MHz (channel 12) | 156.8 MHz (channel 16) |
| 1283 | What is the calling and distress frequency on a single side band (SSB) marine radiotelephone? | 1492 kHz | 2182 kHz | 2082 kHz | 1892 kHz |
| 1284 | What is the lifesaving signal for You are seen - Assistance will be given as soon as possible ? | Horizontal motion with a white flag | Code letter K by blinker light | 3 white star signals | Vertical motion of a white light |
| 1285 | What is the radiotelephone urgency signal? | pan pan | mayday | securite | seelonce feenee |
| 1286 | What would be used to call all stations in your vicinity by radiotelephone? | Kilo | Charlie Quebec | Calling all stations | Alpha Alpha |
| 1287 | When evacuating a seaman by helicopter lift which statement is TRUE? | The drop line should be grounded first then secured as close to the hoist point as possible. | The vessel should be stopped with the wind dead ahead during the hoisting operation. | The hoist area should be located as far aft as possible so the pilot will have a visual reference while approaching. | Flags should be flown to provide a visual reference as to the direction of the apparent wind. |
| 1288 | When it is accepted to remain on the VHF channel / frequency indicated say: | Standing by on VHF Channel ... / frequency ... | Waiting on VHF Channel ... / frequency ... | Staying on VHF Channel ... / frequency ... | Keeping watch on VHF Channel ... / frequency ... |
| 1289 | When the information requested cannot be obtained say: | Information not available. | I do not know .... | Information cannot be obtained. | No information. |
| 1290 | Which of the signals listed is required to be displayed during the day while bunkering? | A red and yellow flag | A red light | A red flag | A yellow flag |
| 1291 | Which radiotelephone signal indicates receipt of a distress message? | Mayday roger | SOS acknowledged | Roger wilco | Received mayday |
| 1292 | Which spoken emergency signal would you use to call a boat to come assist a man overboard? | Urgency signal | Distress signal | Safety signal | None of the above |

| | | | | | |
|---|---|---|---|---|---|
| 1293 | While proceeding to a distress site you hear the words Seelonce mayday on the radiotelephone. Which action should you take? | Resume base course and speed as your assistance is no longer required. | Acknowledge receipt and advise your course speed and ETA. | Relay the original distress message as no other vessel has acknowledged it. | Monitor the radiotelephone but do not transmit. |
| 1294 | While proceeding towards a distress site you hear the message Seelonce Feenee over the radiotelephone. Which action should you take? | Resume base course and speed because the distress situation is over. | Resume normal communications on the guarded frequency. | Do not transmit over the radiotelephone. | Relay the initial distress message to the nearest shore station. |
| 1295 | You are the first vessel to arrive at the scene of a distress. Due to the volume of traffic on the radio you are unable to communicate with the vessel in distress. Which action should you take? | Broadcast Seelonce Distress . | Broadcast Charlie Quebec-Mayday-Quiet . | Switch to flag hoists. | Key the microphone three times in quick succession. |
| 1296 | You are using VHF channel 16 (156.8 MHz) or 2182 kHz. You need help but are not in danger. You should use the urgent signal _____. | MAYDAY | PAN-PAN | ASSISTANCE NEEDED | SECURITE |
| 1297 | A call between any two ship stations on an intership working frequency shall have a maximum duration of _____. | 3 minutes | 2 minutes | 4 minutes | 5 minutes |
| 1298 | A Coast Guard radiotelephone message about an aid to navigation that is off station is preceded by the word _____. | PAN-PAN | MAYDAY | SOS | SECURITY |
| 1299 | A crew member suddenly becomes blind in both eyes. Which code should your message contain? | MNI | MNJ | MNO | MNM |
| 1300 | A long pole with a hook at one end used to reach for lines is known as a _____. | pike pole | hooker | line rod | jack staff |
| 1301 | A message giving warning of a hurricane should have which prefix when sent by radiotelephone? | TTT TTT TTT | No special prefix | Pan-Pan (3 times) | Securite Securite Securite |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 1302 | A signal indicating Greenwich mean time would be preceded with _____. | the letters GT | the letter Z | a code hoist to indicate Greenwich mean time to follow | the letter G |
| 1303 | A vessel in distress should send by radio telephone the two tone alarm signal followed immediately by the _____. | distress position | ship s name | ship s call letters | spoken words Mayday Mayday Mayday |
| 1304 | A vessel which is being assisted by an icebreaker should indicate that he is ready to cast off the towline (if one is used) by _____. | displaying code letter Y (Yankee) | sounding five short blasts of his whistle | displaying code numeral 5 | sounding one prolonged blast of his whistle |
| 1305 | A vessel which is being assisted by an icebreaker would display a flag hoist consisting of the code numeral 4 when the vessel _____. | receives ice damage | speed begins to drop | stops | becomes icebound |
| 1306 | According to the Vessel Bridge-to-Bridge Radiotelephone Act what is NOT required in the radiotelephone log? | Times of beginning and end of watch period | Routine navigational traffic | Distress and alarm signals transmitted or intercepted | Daily statement about the condition of the required radiotelephone equipment |
| 1307 | All towing vessels of 26 feet or longer while navigating are required to carry which item? | At least two lifeboats | A radio direction finder | A radiotelephone | None of the above |
| 1308 | Always to be expressed in 360 degree notation from north (true north unless otherwise stated). Whether this is to TO or FROM a mark can be stated. | Route | Courses | Tract | Direction |
| 1309 | An icebreaker assisting a vessel through an ice field would display a visual signal consisting of the code letter S (Sierra) to signify that _____. | I am operating astern propulsion | I am altering my course to starboard | My vessel is stopped and making no way through the water | I am altering my course to port |
| 1310 | An intermediate spring is _____. | fitted in each leg of the towing bridle | usually made of manila hawser | secured at the H bitts | generally located between the fishplate and the main towing hawser |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 1311 | An oiler was badly burned and you are communicating with a passenger ship that has a doctor and hospital on board. You want to rendezvous in a certain position so the oiler can be evacuated for medical treatment. Which code should your message contain? | MAB | MAF | MAA | MAE |
| 1312 | By regulation you MUST keep a record of the use of your radiotelephone for a minimum of _____. | thirty months | six months | two years | one year |
| 1313 | Channel 13 (156.65 MHz) the designated bridge-to-bridge channel may NOT be used to _____. | exchange operating schedules with company dispatcher | exchange navigational information between a vessel and a shore station | conduct necessary tests | exchange navigational information between vessels |
| 1314 | Hanging a barge off means to _____. | remove and deliver a loaded barge from a multiple tow | remove a barge while locking through | tow an empty barge astern | moor a barge to the bank and leave |
| 1315 | How many VHF Survival Craft Transceivers are required aboard passenger ships? | 2 | 3 | 4 | 5 |
| 1316 | How should the letter Q be pronounced when spoken on the radiotelephone? | KEH BECK | QU UE | QWE BEC | QUE BACH |
| 1317 | How should the letter Z be pronounced when spoken on the radiotelephone? | ZEE BR AH | ZEE ZE | ZE HE | ZOO LOO |
| 1318 | How should the letter D be pronounced when spoken on the radiotelephone? | DA VID | DUKE | DELL TAH | DOG |
| 1319 | If you are transmitting a distress message by radiotelephone you should _____. | use English language | always use the International Code | preface it by the word Interco | follow the transmission with the radio alarm signal |
| 1320 | Any person maintaining a listening watch on a bridge-to-bridge radiotelephone must be able to _____. | repair the unit | send Morse Code | speak a language the vessels crew will understand | speak English |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 1321 | When establishing primary contact between vessels, if English is the language agreed upon for working and a minor understanding difficulty arises, which book would you use to help overcome this_____ . | Oxford Concise Dictionary. | Bridge Procedures Guide. | Standard Marine Navigational Vocabulary. | International Safety Guide for Tankers and Terminals. |
| 1322 | If you wished to transmit a message by voice concerning the safety of navigation, you would preface it by the word _____. | Securite | Mayday | Pan-pan | Safety |
| 1323 | In radiotelephone communications, the prefix PAN-PAN indicates that _____. | the message following the prefix will be about the safety of navigation | a ship is threatened by grave and imminent danger and requests immediate assistance | the message following is a meteorological warning | a calling station has an urgent message about the safety of a person |
| 1324 | In radio telephony what is the URGENCY CALL which should be used to indicate that you have a very urgent message to transmit concerning the safety of another vessel or person? | Victor Victor (3 times) | Pan Pan (3 times) | Securite Securite (3 times) | Mayday Mayday (3 times) |
| 1325 | A vessel in distress should send by radio telephone the two tone alarm signal followed immediately by the _____. | spoken words Mayday, Mayday, Mayday | distress position | ships name | ships call letters |
| 1326 | When the answer to a question is in the affirmative, say: | Right, .... - followed by the appropriate phrase in full. | Ok, .... - followed by the appropriate phrase in full. | Affirmative, .... - followed by the appropriate phrase in full. | Yes, .... - followed by the appropriate phrase in full. |
| 1327 | When the answer to a question is in the negative, say: | No, .... - followed by the appropriate phrase in full. | Negative, .... - followed by the appropriate phrase in full. | Not at all, .... - followed by the appropriate phrase in full. | I do not know, .... - followed by the appropriate phrase in full. |
| 1328 | When the information requested is not immediately available, say: | Wait - followed by the time interval within which the information will be available. | Wait a minute - followed by the time interval within which the information will be available. | Hold - followed by the time interval within which the information will be available. | Stand by - followed by the time interval within which the information will be available. |
| 1329 | When the information requested cannot be obtained, say: | No information. | Information not available. | Information cannot be obtained. | I do not know, .... |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 1330 | When an INSTRUCTION (e.g. by a VTS-Station, Naval vessel or other fully authorized personnel ) or an ADVICE is given, respond if in the affirmative: | Affirmative ... - followed by the instruction or advice in full. | Ok ... - followed by the instruction or advice in full. | Yes ... - followed by the instruction or advice in full. | I will/can ... - followed by the instruction or advice in full. |
| 1331 | It is use to announce a distress message. | MAYDAY | PAN - PAN | SECURITY | SOS |
| 1332 | It is use to announce an urgency message. | SOS | SECURITY | PAN - PAN | MAYDAY |
| 1333 | It is use to announce a safety message. | SECURITE | SOS | MAYDAY | PAN - PAN |
| 1334 | When it is advisable to remain on a VHF Channel / frequency say: | Wait on VHF Channel ... / frequency ... | Stand by on VHF Channel ... / frequency ... | Keep watch on VHF Channel ... / frequency ... | Stay on VHF Channel ... / frequency ... |
| 1335 | When it is accepted to remain on the VHF channel / frequency indicated, say: | Standing by on VHF Channel ... / frequency ... | Staying on VHF Channel ... / frequency ... | Keeping watch on VHF Channel ... / frequency ... | Waiting on VHF Channel ... / frequency ... |
| 1336 | When it is advisable to change to another VHF Channel / frequency, say: | Kindly shift to VHF Channel ... / frequency ... . | Please adjust to VHF Channel ... / frequency ... . | Advise (you) change to VHF Channel ... / frequency ... . | Please change to VHF Channel ... / frequency ... . |
| 1337 | When the changing of a VHF Channel / frequency is accepted, say: | Changing to VHF Channel ... / frequency ... . | Shifting to VHF Channel ... / frequency ... . | Going up / down to VHF Channel ... / frequency ... . | Moving to VHF Channel ... / frequency ... . |
| 1338 | If any part of the message are considered sufficiently important to need safeguarding, say: | I say again ... - followed by the corresponding part of the message. | Take note ... - followed by the corresponding part of the message. | Repeat ... - followed by the corresponding part of the message. | I reiterate ... - followed by the corresponding part of the message. |
| 1339 | Always to be expressed in 360 degree notation from north (true north unless otherwise stated). Whether this is to TO or FROM a mark can be stated. | Direction | Tract | Route | Courses |
| 1340 | Preferably to be expressed in nautical miles or cables (tenths of a mile) otherwise in kilometres or metres, the unit always to be stated. | Space | Distances | Vastness | Expanse |
| 1341 | To be expressed in knots: 15.1 without further notation meaning speed through the water. | Speed | Velocity | Rate | Momentum |

| | | | | | |
|---|---|---|---|---|---|
| 1342 | It should be expressed in the 24 hour UTC notation; if local time will be used in ports or harbours it should clearly be stated. | Periods | Times | Interval | Phase |
| 1343 | Place names used should be those on the chart or in Sailing Directions in use. Should these not be understood, latitude and longitude should be given. | Local names | Topographical names | Geographical names | Terrestial names |
| 1344 | It is used in order to especially facilitate shore-to-ship and ship-to-shore communication or when one of the Standard Marine Communication Phrases will not fit the meaning desired. | Message Markers | Message Indicator | Message Pointer | Message Symbol |
| 1345 | Message Markers. This indicates that the following message implies the intention of the sender to influence others by a Regulation. | Intention | Instruction | Advice | Information |
| 1346 | Message Markers. This indicates that the following message implies the intention of the sender to influence others by a Recommendation. | Warning | Instruction | Advice | Information |
| 1347 | Message Markers. This indicates that the following message implies the intention of the sender to inform others about danger. | Instruction | Intention | Advice | Warning |
| 1348 | Message Markers. This indicates that the following message is restricted to observed facts, situations, etc.. | Information | Warning | Advice | Instruction |
| 1349 | Message Markers. This indicates that the following message is of interrogative character. | Inquiry | Question | Request | Query |
| 1350 | Message Markers. This indicates that the following message is the reply to a previous question. | Answer | Response | Reply | Reaction |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 1351 | Message Markers. This indicates that the following message is asking for action from others with respect to the vessel. | Advice | Instruction | Order | Request |
| 1352 | Message Markers. This indicates that the following message informs others about immediate navigational action intended to be taken. | Plan | Information | Intention | Instruction |
| 1353 | If a receiving station cannot distinguish a signal sent by flag hoist it should _____. | Hoist ZQ | keep the answering pennant at the dip | Raise and lower the answering pennant | Hoist ZL |
| 1354 | A vessel in distress should send by radio telephone the two tone alarm signal followed immediately by the _____. | Distress position | Ships call letters | spoken words Mayday, Mayday, Mayday | Ships name |
| 1355 | According to the "Vessel Bridge-to-Bridge Radiotelephone Act", your radiotelephone log must contain _____. | a summary of all distress calls and messages | The home address of the vessel's Master or owner | A record of all routine calls | A record of your transmissions only |
| 1356 | Which statement about transmitting distress messages by radiotelephone is INCORRECT? | Channel 16 (156.8 MHz) may be used for distress messages. | It is advisable to follow a distress message on 2182 kHz by two dashes of 10 to 15 seconds duration. | If no answer is received on the designated distress frequencies, repeat the distress call on any frequency available. | Distress messages should first be transmitted on 2182 kHz. |
| 1357 | A message warning of a tropical storm should be sent as a(n) _____. | distress message | urgent message | routine message | safety message |
| 1358 | A message giving warning of a hurricane should have which prefix when sent by radiotelephone? | Securite Securite Securite | TTT TTT TTT | Pan-Pan (3 times) | No special prefix |
| 1359 | If you wished to transmit a message by voice concerning the safety of navigation, you would preface it by the word _____. | Mayday | Pan-pan | Safety | Securite |
| 1360 | The VHF radiotelephone calling/safety/distress frequency is _____. | 156.65 MHz (channel 13) | 156.8 MHz (channel 16) | 156.6 MHz (channel 12) | 156.7 MHz (channel 14) |

| | | | | | |
|---|---|---|---|---|---|
| 1361 | The radiotelephone safety message urgently concerned with safety of a person would be prefixed by the word _____. | Mayday | Interco | Pan pan | Safety |
| 1362 | How is the International Code Signal of distress indicated? | N.C | S.O.S | D.S | Interco |
| 1363 | A bell or gong, or other device having similar sound characteristics shall produce a sound pressure level of not less than _____ | 80 dB at 1 meter | 50 dB at a meter | 110 dB at 1 meter | 100 dB at 1 meter |
| 1364 | The Rules concerning the display of lights starts and ends under which of the following? | sunrise to sunrise | sunset to sunrise | sunrise to sunset | sunset to sunset |
| 1365 | Which is NOT a distress signal? | Vertical motion of a white lantern at night | Dye marker on the water | Code flags "November" and "Charlie" | Flames on a vessel |
| 1366 | Which communications functions must all vessels be capable of performing under GMDSS as defined by the International Maritime Organization? | Communications in each of the operational ocean areas | All communications possible within the International Safety-NET service | Radio direction finding | Distress alerting to and from vessels, search and rescue coordination, on-scene communications, signals for locating, Maritime Safety Information, general and bridge-to-bridge communications. |
| 1367 | The VHF radiotelephone frequency for Channel 14 is: | 156.8 MHz | 156.6 MHz | 156.7 MHz | 156.0 MHz |
| 1368 | The VHF radiotelephone frequency for Channel 13 is: | 156.65 MHz | 156.70 MHz | 156.60 MHz | 156.80 MHz |
| 1369 | Channel 70 for digital selective calling for Distress, Safety and Calling frequency operate at: | 158.526 MHz | 156.526 MHz | 157.526 MHz | 159.526 MHz |
| 1370 | Channel 16 - Safety and calling frequency which operates in: | 159.800 MHz | 157.800 MHz | 156.800 MHz | 158.800 MHz |
| 1371 | An urgent marine storm warning message would be broadcast on: | 157.10 MHz (VHF-FM Ch. 22A) | 156.80 MHz (VHF-FM Ch. 16) | 2670 KHz | None of the above |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 1372 | When bunkering at a dock which of the following signals must be displayed? | A yellow flag by day, red light by night | A red flag by day, red light by night | A green flag by day, green light by night | A red flag by day, a blue light by night |
| 1373 | In shore-ship use, what is useful range of VHF? | About 40-70 miles "Line of sight" | About 50-100 miles "Line of sight" | About 30-70 miles "Line of sight" | About 60-120 miles "Line of sight" |
| 1374 | In case a vessel seeks medical advice including the onward transmission of medical messages by radio or satellite communication between a ship and those ashore giving advice, how does the payment for such medical advice being made? | Shall be available free of charge to all ships | Per minute basis | According to the seriousness of the case | None of the choices |
| 1375 | In the International Code of Signals, the code signal meaning "I require immediate assistance" is: | DX | CB | CP | AE |
| 1376 | If you wanted to ask a nearby vessel if he had a doctor on board, you would hoist the flag signal: | AL | MA | AM | AN |
| 1377 | Approaching the anchorage to pick up pilot, what will be your required signal during daylight? | Golf flag | Hotel flag | Bravo flag | Nothing call the pilot thru VHF |
| 1378 | Distress, Safety and Calling Channel. | Channel 69 | Channel 16 | Channel 13 | Channel 70 |
| 1379 | When using the International Code of Signals to communicate, the end of a radiotelephone transmission is indicated by the signal: | WA | CQ | AR | YZ |
| 1380 | Hoist which relates to phrases that are very urgent, important and of common use is a: | Single letter hoist | Three letter hoist | Double letter hoist | Four letter hoist |
| 1381 | My ship is infected with infectious disease, what international flag signal will I hoist? | DQ | QQ | DR | QI |
| 1382 | The appropriate landing signals for small boats with crews or persons in distress to indicate "this the best place to land" is: | code flag S as a hoist | firing of a white star signal | letter K in Morse code given by light | horizontal motion of a white flag |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 1383 | How would the letter "I" be pronounced over the radiotelephone? | IN DEE AH | I VAN HO | IN DEE GO | I EE |
| 1384 | A high intensity all-round flashing red light is exhibited by a WIG craft only when: | any of the choices is correct | landing | taking off | in flight near surface |
| 1385 | The Master is allowed by the rules to depart from the normal requirements: | in order to meet charterer's order | in order to avoid immediate danger | whenever he desires | None of the choices is correct |
| 1386 | As per Annex II of the Rules, which of the following is the additional day signal for trawlers when the net has come fast an obstruction? | International code flag "PAPA" | International code flag "ZULU" | International code flag "GOLF" | International code flag "TANGO" |
| 1387 | As per Annex II of the Rules, the additional signals for trawlers when hauling their nets is: | International code flag "P" | International code flag "Z" | International code flag "G" | International code flag "H" |
| 1388 | What does this signal displayed by a small craft signify when in passage up a river, she is showing a rigid replica of the international code flag "A"? | It signifies, "I am maneuvering with difficulty, keep out of my way" | It signifies, "I have a diver down, I require assistance" | It signifies, "I have a diver down, I am proceeding at maneuvering speed, keep clear of me" | It signifies, "I have a diver down, keep well clear at slow speed" |
| 1389 | While at sea, a tug is seen displaying a black square flag below a black ball on its mast. What action should be done? | render assistance to the tug | keep well clear as the tug is restricted in her ability to maneuver | keep clear as she is towing a dracone | keep clear as she is escorting a submersible |
| 1390 | At sea you sight a tug displaying this signal. What should you do? | Keep well clear as she is towing a dracone | Keep well clear as the tug is restricted in her ability to maneuver | Give assistance as the tug is in distress | Keep well clear as she is escorting a submersible vessel |
| 1391 | Three letter hoists that begin with the code flag MIKE signifies: | Master's advise | Medical signals | Meteorological warnings | Maneuvering signals |
| 1392 | If a "man overboard" is heard over the radio, what precedes the message? | MAYDAY | CQ CQ | SECURITE | PAN PAN |
| 1393 | During a search, a RU would like to communicate by VHF radio telephone on channel indicated, she must signal what code group? | YY | GH | MI | MG |

| | | | | | |
|---|---|---|---|---|---|
| 1394 | In restricted visibility, a power-driven vessel making way through the water shall sound which of the following fog signals? | ROMEO | TANGO | ZULU | MIKE |
| 1395 | Vessels engaged in pair trawling show what day signals? | International code flag "PT" flown at the foremost | International code flag "P" flown at the foremost | No necessary signal to be shown | International code flag "T" flown at the foremost |
| 1396 | A vessel being towed shall sound a fog-signal of: | BRAVO | ECHO | No signal required | PAPA |
| 1397 | How should the letter "O" be pronounced over the radiotelephone? | O RIAN | OSS CAH | OA KAM | OCK TOW BER |
| 1398 | RT message giving warning of a hurricane should have which of the following prefixes: | Mayday, Mayday, Mayday | Pan -Pan (3 times) | Securite Securite Securite | CQ, CQ, CQ |
| 1399 | The signal consist of three letter signals "MCW" means: | Patient is found unconscious | Patient has mental symptoms | Patient is unable to sleep | Patient appears to be in a state of shock |
| 1400 | How is the letter "Q" pronounced when spoken on the radiotelephone? | KEH BECK | QUE BACK | QWE BEK | QU UE |
| 1401 | What is the purpose of VHF Channel 06? | R/T Primary Intership, Maybe used in co-ordination of SAR ship to ship only. | R/T Primary Intership, Maybe used in co-ordination of SAR ship to ship and ship to aircraft. | Don't know | Public traffic channel |
| 1402 | To attract the attention of other vessel, a vessel may use any sound or light signals as long as: | the vessel signals such intentions over the radiotelephone | red and green lights are not used | the signal cannot be mistaken for a signal authorized by the Rules | white lights are not used |
| 1403 | When a vessel is sounding a single-letter signal "ROMEO", this indicates that: | she is at anchor | she is in distress | she is towing | any of the choices is correct |
| 1404 | Signaling by flag hoist is completed by the vessel hoisting the: | signal AR | code flag R | answering pennant | code flag N |
| 1405 | The maneuvering and warning signal of a vessel intending to overtake another vessel on her port side when in a narrow channel or fairway shall be a: | single letter signal "TANGO" | single letter signal "ZULU" | single letter signal "ECHO" | single letter signal "BRAVO" |
| 1406 | Approaching a bend where other vessels may be obscured by an intervening obstruction, what signal shall a vessel sound? | Single letter signal TANGO | Single letter signal VICTOR | Single letter signal WHISKEY | Single letter signal X-RAY |

| | | | | | |
|---|---|---|---|---|---|
| 1407 | Determine among the International Code single-letters the equivalent fog signal of a "vessel restricted in her ability to maneuver". | single-letter signal "FOXTROT" | single-letter signal "KILO" | single-letter signal "DELTA" | single-letter signal "JULIETTE" |
| 1408 | In the event of a collision, after the impact, which of the following should NOT be done? | transmit MAYDAY or PA_PAN signals, even if not in distress | hoist the three red lights in a vertical line, one above the other | swing out lifeboats, ensure that no premature abandonment takes place and prepare life rafts | close all watertight doors |
| 1409 | How is the letter "T" pronounced when spoken over the radiotelephone? | TANG GO | TEE | TAHO | TEEE |
| 1410 | For a vessel at anchor, what are the additional and optional fog-signals? | TANGO | No additional and optional signal required | ROMEO | SIERRA |
| 1411 | A warship indicates that it wishes to communicate with a merchant ship by hoisting: | The flags MV close up until acknowledged and then lowering them to the dip | The merchant ship's identify signal and keeping it hoisted during the entire communication | The national ensign of the vessel at the starboard yard | The code pennant, and keeps it during the entire communication |
| 1412 | In the event of a collision, why is it important to transmit MAYDAY or PAN_PAN signals, even if not in distress? | it will alert shipping to a possible future distress call | to warn the other ship involved in the collision | to justify that you are not at fault | to alert the consignee/s that their cargoes may not arrive on time |
| 1413 | What channel is designated by the Radio Regulations for Bridge-to Bridge communications? | MF/HF Watchkeeping | VHF channel 16 | VHF channel 13 | DSC channel 70 |
| 1414 | What should be used when language difficulties exist which cannot be resolved by the used of the IMO Standard Marine Communication Phrases? | Changing channels | International Code of Signals | VHF watchkeeping | Communicate to coast stations |
| 1415 | An icebreaker assisting a vessel through an ice field would display a visual signal consisting of the code letter M (Mike) to signify that _____ . | my vessel is stopped and making no way through the water | I am operating astern propulsion | I am altering my course to port | I am altering my course to starboard |

| | | | | | |
|---|---|---|---|---|---|
| 1416 | For the purposes of distress signaling small passenger vessels that operate on runs of more than 30 minutes duration on lakes bays and sounds and river routes must carry _____. | A radiotelephone | A Very pistol and flare kit | Three hand red flare distress signals and three hand orange smoke distress signals | An approved noise-making device |
| 1417 | How should you signal the crane operator to swing? | Extend arm and point finger in the direction to move the boom. | Place both fists in front of the body with the thumbs pointing outward. | With arm extended downwards and forefinger pointing down move hand in small horizontal circles. | With both arms extended out and palms down move arms back and forth. |
| 1418 | If there is a possibility of confusion which signal should be used to send the group True Bearing 045 Degrees ? | B045T | 45 | B045 | A045 |
| 1419 | If you make an error while signaling by flashing light what action should you take? | EEE then send the word correctly | the correction signal and re-spell the word | the erase signal then continue the message with the last correctly spelled word | RPT then repeat the entire signal |
| 1420 | If you were being assisted by an icebreaker and he sent you the single letter Q what would he would be telling you? | to shorten the distance between vessels | that he has his engines in reverse | that his vessel is healthy | that he is shortening the distance between vessels |
| 1421 | In the International Code of signals what does a group of three letters indicates? | a group from the general signal code | the vessels national identity signal | a group from the medical signal code | urgency or an emergency |
| 1422 | Regardless of the method it is sent what does he signal K4 mean? | a distance of 4 miles | the wind is from the south | a speed of 4 knots | I wish to communicate with you by sound signals |
| 1423 | The color of the signal flare sent up by a submarine coming to periscope depth is _____. | green | red | yellow | white |
| 1424 | The flag hoist 62.2 would be sent as pennant 6 pennant 2 followed by what? | answering pennant second substitute | space second substitute | answering pennant third substitute | answering pennant first substitute |
| 1425 | The use of three (3) figure signals denotes _____. | longitude | bearing or azimuth | distance | time |
| 1426 | The vertical dimension of a flag is called _____. | Fly | Tabling | Hoist | Tack |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 1427 | What does the signal AS when used in signaling by the International Code of Signals mean? | Finished with transmission | Wait | Over | Repeat this signal |
| 1428 | What is indicated by the flag U or the letter U by blinker? | You are running into danger. | I require a tug. | I require assistance. | I have a fire on board. |
| 1429 | What is the international calling and distress channel found on all VHF-FM equipped drilling rigs? | Channel 10 | Channel 1 | Channel 68 | Channel 16 |
| 1430 | What is the lifesaving signal used to indicate Landing here is highly dangerous ? | firing of a white star signal | firing of a red star signal | vertical motion of a red light | code letter K given by light or sound signaling apparatus |
| 1431 | What is the meaning of the signal QU RQ when sent by the International Code of Signals? | Is anchoring prohibited? | Interrogative | Will you lead me to a safe anchorage? | This is the call sign of a vessel registered in Latvia. |
| 1432 | What is the primary purpose for Digital Selective Calling (DSC)? | DSC provides reception of weather and navigational warnings plus search and rescue information. | DSC is to be used for transmitting and receiving distress alerts to and from other ships or coast radio stations via radio. | This aids SAR authorities in tracking a vessels position by satellite. | DSC provides low-cost routine communications for the vessel operator. |
| 1433 | What is the unit of duration of a dash in Morse Code? | four times the length of a dot | one and one-half times the length of a dot | twice the length of a dot | three times the length of a dot |
| 1434 | When is the appropriate time for setting off distress flares and rockets? | During daytime only | Only when there is a chance of them being seen by rescue vessels. | Anytime | During night time only |
| 1435 | When signaling by flag hoist what signal indicates completion of the communication? | answering pennant | code flag N | code flag R | signal AR |
| 1436 | When the letter VICTOR is hoisted it means _____. | You are running into danger. | Do not pass ahead of me. | I require assistance. | I am disabled. |
| 1437 | Which distress signal is required for a liferaft in ocean service and could be effectively used to attract the attention of aircraft at night? | Red flares | The water light | Smoke marker | Orange dye marker |
| 1438 | Which one of the following signals is made at night by a lifesaving station to indicate Landing here highly dangerous ? | Vertical motion of a red light or flare | Horizontal motion of a white light or flare | Vertical motion of a white light or flare | White star rocket |

| | | | | | |
|---|---|---|---|---|---|
| 1439 | While communicating with a shore station concerning an injured female your message should indicate the subjects age is 32. Which code would your message contain? | MAJ 32 | MAO 32 | MAK 32 | MAL 32 |
| 1440 | You are approaching another vessel and see that she has the signal flag A hoisted. What should you do? | Stop your vessel instantly. | Give the vessel a wide berth as she is carrying dangerous goods. | Attempt to call the vessel on VHF radiotelephone because she is disabled. | Slow your vessel and keep well clear because she has a diver down. |
| 1441 | You are downbound in an ice filled channel. An icebreaker is meeting you and sounds two short one prolonged and two short blasts on the whistle. What action should you take? | Stop your headway and await further signals. | No action is required; the icebreaker will move out of the channel. | Move to the right hand side of the channel and slow to bare steerageway. | Slow to bare steerageway and be prepared to come ahead as the icebreaker commences escorting your vessel. |
| 1442 | A crew member suddenly becomes blind in both eyes. Which code should your message contain? | MNJ | MNI | MNO | MNM |
| 1443 | A distress signal _____. | may be used individually or in conjunction with other distress signals | consists of the raising and lowering of a large white flag | consists of 5 or more short blasts of the fog signal apparatus | is used to indicate doubt about another vessel s intentions |
| 1444 | A message by flashing light consists of four elements including the call the identity the text and what fourth element? | destination | ending | answer | time |
| 1445 | A radio telegraph message commencing with XXX has the same meaning as a message sent by radio-telephone commencing with: | TTT | The spoken word URGENCY | The spoken word PAN | SOS |
| 1446 | A set of code flags on a vessel totals _____. | 26 pieces | 40 pieces | 36 pieces | 60 pieces |
| 1447 | A vessel is flying the signal BJ-1 from her starboard halyard. What does this signal mean? | an aircraft is circling over an accident | the aircraft is still afloat | an aircraft is ditched in position indicated | there is no danger of explosion |
| 1448 | A vessel is signaling to you by flag hoist and the answer pennant is hoisted close-up. You should _____. | wait for further signals after a short delay | hoist flag C | expect no further flag hoists | hoist flag R |

| | | | | | |
|---|---|---|---|---|---|
| 1449 | A vessel which sound on her whistle 7 successive short blast and followed by 1 prolonged blast means: | Fire drill | Abandonship | Boat drill | Man overboard |
| 1450 | A warship indicates that it wishes to communicate with a merchant ship by hoisting _____. | the national ensign of the merchant vessel at the starboard yard | the merchant ship s identity signal and keeping it hoisted during the entire communication | the code pennant and keeping it flying during the entire communication | the flags MV close up until acknowledged and then lowering them to the dip |
| 1451 | A yellow signal floating in the air from a small parachute about 300 feet above the water would indicate that a submarine _____. | is about to rise to periscope depth | has fired a torpedo during a drill | is disabled and unable to surface | is on the bottom in distress |
| 1452 | After sending a message describing the symptoms of an ill crew member you receive a message containing the code MRL. What is the meaning of the message? | Pass catheter into bladder | Commence artificial respiration immediately | Apply ice-cold compress and renew every 4 hours | Give enema |
| 1453 | An airplane wants a vessel to change course and proceed towards a vessel in distress. The actions of the aircraft to convey this message will NOT include _____. | circling the vessel at least once | heading in the direction of the distress location | flashing the navigation lights on and off | crossing ahead and rocking the wings |
| 1454 | An all-round white light which flashes simultaneously with the ship s whistle when signifying a course change _____. | manuevering light | anchor light | Morse light | signal light |
| 1455 | An oiler was badly burned and you are communicating with a passenger ship that has a doctor and hospital on board. You want to rendezvous in a certain position so the oiler can be evacuated for medical treatment. Which code should your message contain? | MAF | MAE | MAB | MAA |

| | | | | | |
|---|---|---|---|---|---|
| 1456 | As per annex IV(2) the use or exhibition of any signals listed Annex IV(1) except for the purpose of indicating distress and need of assistance and the use of other signals that may be confused with those listed in (1) is _____. | not allowed | prohibited | not accepted | sometimes allowed |
| 1457 | By day the horizontal motion of a white flag or arms extended horizontally by a person on the beach indicates? | Negative | Haul away | Tail block is made fast | Affirmative |
| 1458 | By day the signal meaning This is the best place to land is a _____. | vertical motion of a red flag | white star rocket | white smoke signal | vertical motion of a white flag or the arms |
| 1459 | Date may be signaled by two four or six numerals preceded by flag _____. | Papa | Delta | Lima | Zulu |
| 1460 | During a training exercise a submarine indicating that a torpedo has been fired will send up smoke from a float. What color will the smoke be? | orange | yellow | black | red |
| 1461 | Figures preceeded by letter R indicate _____. | distance | latitude | bearing | none of these |
| 1462 | Figures preceeded by the letter S indicate _____. | ship s heading | destination | a question | speed |
| 1463 | Hoist which relates to phrases which are very urgent important and of common use _____. | single-letter hoist | three-letter hoist | four-letter hoist | none of these |
| 1464 | How does a warship indicates that it wishes to communicate with a merchant ship? | by hoisting the national ensign of the merchant vessel at the starboard yard | by hoisting the code pennant and keeping it flying during the entire communication | by hoisting the merchant ship s identity signal and keeping it hoisted during the entire communication | by hoisting the flags MV close up until acknowledged and then lowering them to the dip |
| 1465 | How is the call part of a signal by flashing light made? | | omitting the call if the name of the station is unknown | sending CQ | the identity signal of the station called |
| 1466 | How should a receiving station indicate that it cannot distinguish a signal sent by flag hoist? | keep the answering pennant at the dip | hoist ZQ | raise and lower the answering pennant | hoist ZL |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 1467 | How would the flag hoist 1.33 be sent? | 1 answer pennant 3 third substitute | 1 answer pennant 3 first substitute | N 1 answer pennant 3 | 1 answer pennant 3 second substitute |
| 1468 | If a crew member that was ill has died which code should your message contain? | MPR | MPO | MPK | MPJ |
| 1469 | What is the International Code signal for a decimal point between figures using flashing light? | TTTT | EEEEE | AAA | AS |
| 1470 | While using the International Code of Signals, if the receiving station can distinguish the flag signal of the transmitting station, but cannot understand the meaning of it, the station can hoist the flag signal _____. | ZL | ZP | ZR | ZK |
| 1471 | The letter HOTEL when hoisted means: | I require a doctor. | I have a doctor on board. | | I have a pilot on board. |
| 1472 | Figures preceeded by the letter S indicate: | speed | destination | ships heading | a question |
| 1473 | Figures preceeded by letter R indicate: | bearing | none of the options | distance | latitude |
| 1474 | In signaling by Internatinal Code Flags, what is the significance of four-letter signals? | common messages | geographical signal and signal station | general vocabulary | urgent messages |
| 1475 | When bunkering or loading explosives, my flaghoist should be: | Bravo | Charlie | Delta | November |
| 1476 | The call for unknown station and general call: | T | C | W | AA |
| 1477 | What will you hoist when you have a diver down and require ships to keep clear? | Charlie | Bravo | Alpha | Zulu |
| 1478 | When navigating at night, you see a vessel flashing by light the letter KILO, you will react by: | answering in the same manner | stopping your engine | calling the master | changing course to starboard |
| 1479 | Two flag signal QQ means: | My ship is healthy, I request free pratique. | My ship is infected, I had a case of infectious disease less than 5 days ago. | none of the options | My ship is suspected, I have a case of infectious disease more than five days ago. |

| | | | | | |
|---|---|---|---|---|---|
| 1480 | What international signal letter is used when calling another vessel by light signal? | Kilo | November | Delta | Bravo |
| 1481 | The signal of sound composed of dots and dashes is known as: | international code | telegraphic signals | telephonic signal | Morse Code |
| 1482 | A set of code flags on a vessel totals: | 40 pieces | 36 pieces | 26 pieces | 60 pieces |
| 1483 | In a set of code flags, how many substitute are there? | 2 pieces | 4 pieces | 3 pieces | 10 pieces |
| 1484 | When the code flag OSCAR is hoisted, it signifies: | A vessel in distress. | I am stopping my engine. | I am going astern. | A man overboard. |
| 1485 | When requesting for free pratique, which single hoist is exhibited? | Quebec | Lima | X-ray | Bravo |
| 1486 | When navigating in a roadstead, another vessel hoist the letter TANGO on her foremast. What does it mean? | none of the options | She is requesting not to pass ahead of her. | There is a man overboard. | She needs a doctor. |
| 1487 | The use of three (3) figure signals denotes: | bearing or azimuth | distance | longitude | time |
| 1488 | When the letter VICTOR is hoisted, it means: | I am disabled. | I require assistance. | You are running into danger. | Do not pass ahead of me. |
| 1489 | Hoist which relates to phrases which are very urgent, important and of common use: | single-letter hoist | three-letter hoist | four-letter hoist | none of the options |
| 1490 | An all-round white light which flashes simultaneously with the ships whistle when signifying a course change: | signal light | Morse light | manuevering light | anchor light |
| 1491 | The top letter of the numeral hoist when signalling longitude is: | Tango | X-ray | Lima | Golf |
| 1492 | The top letter of the numeral hoist when signalling azimuth or bearing is: | Charlie | Papa | Alpha | Bravo |
| 1493 | A vessel which sound on her whistle 7 successive short blast and followed by 1 prolonged blast means: | Abandonship | Man overboard | Boat drill | Fire drill |
| 1494 | Two prolonged blast followed by one short blast means: | I need a doctor. | I require assistance. | I am calling a pilot. | I request free pratique. |
| 1495 | The vertical dimension of a flag is called: | Hoist | Fly | Tack | Tabling |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 1496 | The horizontal dimension of a flag is called: | Wrap | Length | Fly | Hoist |
| 1497 | In undergoing a speed trial, what will you hoist? | Alpha | Bravo | Papa | Zulu |
| 1498 | What is indicated by the flag U or the letter U by blinker? | I require assistance. | You are running into danger. | I require a tug. | I have a fire on board. |
| 1499 | Date may be signaled by two, four or six numerals preceded by flag: | Delta | Lima | Papa | Zulu |
| 1500 | Time is denoted by the use of the 24-hour clock. Four numerals are used proceded by T (local time) or (GMT). | Alpha | Papa | Delta | Zulu |
| 1501 | How would 1030 GMT be sent by bllinker? | 1030Z | Z1030 | G1030 | 1030G |
| 1502 | Three-letter hoist begin with the letter M indicates: | Medical signals | Manuevering signals | Meteorological warnings | Masters advise |
| 1503 | In flag signaling the answering pennant could be used to: | Indicate meteorological warnings. | Indicate a decimal point. | Indicate medical signal. | Indicate manuevering signals. |
| 1504 | The word LOBITH is spelled conform to the international phonetic alphabet: | Lima, Oscar, Bravo, India, Tango, Hotel | Liverpool, Oslo, Bernhard, India, Taro, Hotel | Dont know | Lima, Oscar, Bernhard, Italia, Tripoli, Havana |
| 1505 | The word NAVTEX is spelled conform to the international phonetic alphabet: | Dont know | November, Anna, Victor, Tango, Eduard, X-ray | November, Able, Valencia, Tripoli, Echo, Xantippe | November, Alfa, Victor, Tango, Echo, X-ray |
| 1506 | What signal flag is the Pilot Flag (I have a pilot on board)? | Z | P | H | C |
| 1507 | Which is NOT a distress signal? | Vertical motion of a white lantern at night | Dye marker on the water | Code flags November and Charlie | Flames on a vessel |
| 1508 | As per annex IV(2), the use or exhibition of any signal listed Annex IV(1), except for the purpose of indicating distress and need of assistance and the use of other signals that may be confused with those listed in (1), is | not accepted | prohibited | not allowed | sometimes allowed |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 1509 | What does the DSC control unit do if the GMDSS radio operator fails to insert updated information when initiating a DSC distress alert? | It will abort the transmission and set off an audible alarm that must be manually reset. | It will initiate the DSL distress alert, but any station receiving it will have to establish contact with the distressed vessel to determine its identity, position and situation. | It will initiate the DSC distress alert but, as no information will be transmitted, rescue personnel will not be able to identify the vessel, its position or its situation. | It will initiate the DSC distress alert and default information will automatically be transmitted. |
| 1510 | What is EPIRB an abbreviation for? | Emergency Position Indicating Radio Beacon. | Emergency Position Indication Radio Buoy. | Electronic Purpose If Rescue Begins. | Electronic Pressure Indication Radar Buoy. |
| 1511 | When is the appropriate time for setting off distress flares and rockets? | During daytime only | During night time only | Only when there is a chance of them being seen by rescue vessels. | Anytime |
| 1512 | What is the primary purpose for Digital Selective Calling (DSC)? | DSC provides reception of weather and navigational warnings plus search and rescue information. | DSC is to be used for transmitting and receiving distress alerts to and from other ships or coast radio stations via radio. | DSC provides low-cost, routine communications for the vessel operator. | This aids SAR authorities in tracking a vessels position by satellite. |
| 1513 | What is the basic concept of GMDSS? | All of the options | Search and rescue authorities ashore can be alerted to a distress situation. | Shipping in the immediate vicinity of a ship in distress will be rapidly alerted. | Shoreside authorities and vessels can assist in a coordinated SAR operation with minimum delay. |
| 1514 | Which communications functions must all vessels be capable of performing under GMDSS as defined by the International Maritime Organization? | All communications possible within the International Safety-NET service | Communications in each of the operational ocean areas | Radio direction finding | Distress alerting to and from vessels, search and rescue coordination, on-scene communications, signals for locating, Maritime Safety Information, general and bridge-to-bridge communications. |
| 1515 | Which message categories cannot be disabled by the GMDSS Radio Operator? | Navigational warnings | Meteorological warnings | All of the options | Search and Rescue information |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 1516 | If you have to abandon ship, the EPIRB can be used to _____. | hold the survival crafts head up into the seas | seal leaks in rubber rafts | generate orange smoke | send radio homing signals to searching aircraft |
| 1517 | A distress signal _____. | may be used individually or in conjunction with other distress signals | consists of 5 or more short blasts of the fog signal apparatus | consists of the raising and lowering of a large white flag | is used to indicate doubt about another vessels intentions |
| 1518 | Which conditions will normally cause a SART to operate in the active mode? | It will respond only to interrogation by 9-Ghz radar signals. | All of the options | A SART will normally respond to interrogation from a searching aircrafts radar if the radars output power is at least 10,000 watts and the aircraft is at a height of 3000 feet and within 30 nautical miles. | A SART will normally respond to interrogation from a searching vessels radar if the radar antenna is at least 15 meters high. |
| 1519 | What is the international calling and distress channel found on all VHF-FM equipped drilling rigs? | Channel 16 | Channel 1 | Channel 10 | Channel 68 |
| 1520 | The distress message of a ship should include considerable information which might facilitate the rescue. This information should: | include the vessels draft | FIRST be transmitted as a series of short messages, if time allows | be sent to a Coast Guard station | ALWAYS be included in the initial distress message |
| 1521 | A vessel in distress should send by radio telephone the two tone alarm signal followed immediately by the: | distress position | spoken words Mayday, Mayday, Mayday | ships call letters | ships name |
| 1522 | A radio telegraph message commencing with XXX has the same meaning as a message sent by radio-telephone commencing with: | The spoken word PAN | The spoken word URGENCY | TTT | SOS |
| 1523 | In acknowledging receipt of a distress message, what code would be sent on the radiotelegraph to let the vessel in distress know that the message was received? | QRT | R | EL | OK |

| | | | | | |
|---|---|---|---|---|---|
| 1524 | What is the meaning of a flag hoist consisting of the code letters WM (Whiskey Mike) when displayed by an icebreaker? | You should stop your vessel instantly. | I am going ahead; follow me. | Icebreaker support is finished. | Icebreaker support is now commencing. |
| 1525 | In the International Code of Signals, the code signal meaning I require immediate assistance is _____. | CB | CP | AE | DX |
| 1526 | You are standing the wheelwatch when you hear the cry, "Man overboard, starboard side". You should instinctively _____. | Give full left rudder | Put the rudder amidships | Throw a life ring to mark the spot | Give full right rudder |
| 1527 | When making a Scharnow turn, the _____. | Man overboard must be not more than 300 feet astern when starting the turn | Rudder must be put over towards the side the man went over | Rudder is put hard over and the initial turn is maintained until about 240° from the original course | Initial turn direction is away from the side the man went over |
| 1528 | It is a particular professional knowledge regarding own ship various methods available and how to change over to secondary from primary methods. It is the knowledge on _____. | maneuvering | steering and conning | propulsion | ship handling |
| 1529 | In principle of shiphandling which factor that a master or a pilot has no direct control of the ship | Shallow water factor | reduced engine power | wind power | ship stops |
| 1530 | When going astern in a right-handed propeller ship and need to maintain the ship's heading, the rudder would be place at_____. | rudder to port to neutralize the swing | Rudder to starboard enough to compensate the swing | Rudder amidship to compensate the swing | hard port |
| 1531 | This type of screw is principally used by fast coastal craft and some classes of aircraft carriers. The propeller revolve in the same direction, so as to facilitate engine installation. This propeller is _____. | twin screw | single screw | Triple or multiple screw | quadruple screw |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 1532 | it is a propeller which is almost invariably right-handed. When the ship is driven ahead, the propeller revolves in a clockwise direction, when viewed from astern. To go astern the rotation os the propeller is reversed. It is _____. | twin screw | Single screw | triple crew | quadruple screw |
| 1533 | this propeller consist of the screws that are out-turning, are right-handed on the starboard side and left-handed on the port side, this type of propeller is _____. | Twin screw | quadruple screw | triple crew | single screw |
| 1534 | Using a sea anchor with the survival craft will _____. | aid in recovering the survival craft | increase your visibility | keep the survival craft from turning over | reduce your drift rate |
| 1535 | When steering a tow downstream around the shape of a sand bar, and staying on the proper side of the buoys, an operator should be cautious of _____. | swift current under the bar causing loss of control | eddies under the bar | cross-currents pushing the tow away from the bar | cross-currents pushing the tow into the bar |
| 1536 | A ship is having a slow speed, by using the backing maneuver, the ship is considered to be dead on the water when the | quick water reaches the amidships | quick water reaches the stern | quick water reaches about 1/4 distance from the stern | speed of the ship is the same speed as quick water |
| 1537 | A ship is not turning around the center of gravity, but another point. What is the point called? | point of no return | point of turning | point of radius | pivot point |
| 1538 | A ship is turning around a point called the "pivot point". What is the position of this invisible point when the ship is "dead" in the water? | near the stern of the ship | About same position as the center of gravity. | outside of the center line | near the bow |
| 1539 | A single-screw vessel going ahead tends to turn more rapidly to port because of propeller _____. | thrust | discharge current | suction current | sidewise force |
| 1540 | Your vessel is off a lee shore in heavy weather and laboring. Which action should you take? | Put the sea and wind about two points on either bow and reduce speed. | Put the sea and wind on either quarter and proceed at increased speed. | Put the bow directly into the sea and proceed at full speed. | Heave to in the trough of the sea. |

# OIC NAVIGATIONAL WATCH

| | | | | | |
|---|---|---|---|---|---|
| 1541 | Your vessel is backing on the starboard screw, and going ahead on the port screw. The bow will _____. | move ahead on a straight line | swing to port | back on a straight line | swing to starboard |
| 1542 | Your ship is going full astern and making sternway. Where will the "pivot point" be located? No wind, current. | At 1/6 of the ship's length from the stern | At 1/6 of the ship's length off the bow | Somewhere aft of the center of gravity, but it is impossible to pin-point the exact location | at the center of gravity |
| 1543 | Your ship is going full ahead as you start to slow down. Where is the position of the "pivot point" now? No wind, current. | It will move aft as the ship slows down | It will move to the side of the center line | Same position as when the ship is on full ahead | The "pivot point" will move to the stern |
| 1544 | Your ship is drifting in open sea with temporary engine malfunction. You are equipped with precise navigation equipment. What should you do in this situation? | ask the chief engineer when the engine will be ready | Use the opportunity to plot direction and rate of drift for later use | Go to bed and wait for the engine to be ready | call the company immediately |
| 1545 | Your ship is dead in the water with the rudder amidships. As the right-handed screw starts to turn ahead, the bow will tend to go _____. | as influenced by the tide and sea | to starboard | to port | straight ahead |
| 1546 | You have made a turning test on full speed in deep water. You are now going to make a test in shallow water. Do you think the turning diameter will be the same? | No, the turning diameter will be increased in shallow water. | Yes, the turning diameter will be the same for all depths. | No, the turning diameter will be smaller in shallow water. | Yes, it will be the same provided the UKC is 25 % - 50 %. |
| 1547 | Your ship is equipped with a single, right-handed fixed screw. Steaming full ahead you reverse the engine to stop the ship. How will the ship react? No wind or current. | She will stop on 1,5 times the ship's length | She will most likely sheer to starboard and gradually loose headway | She will most likely continue on a straight course | She will most likely sheer to port and stop rather quickly |
| 1548 | Your ship is equipped with a right-handed propeller. As you go full astern from full ahead, the ship is sheering to starboard. Is there anything you can do to reduce the change in heading? | I can swing the rudder from side to side | no, there is nothing I can do | Put the rudder hard to port to reduce the water flow to the right side of the propeller | Put the rudder hard to port to reduce the water flow to the left side of the propeller |

# OIC NAVIGATIONAL WATCH

# OIC NAVIGATIONAL WATCH

| | | | | | |
|---|---|---|---|---|---|
| 1549 | Your ship has right handed propeller and is on half ahead when you put her full astern to stop her. Do you think the rudder will have any effect while the ship is making headway? | Yes, by putting the rudder hard starboard. it will shield water flow to the starboard. side of the propeller and vice versa to port. This will effect turning of the ship. | No, the rudder should always be amidships when the propeller is going astern. | Yes, by putting the rudder hard to port the ship will go to port, even if the propeller is going astern. | No the rudder must be put midships, otherwise it could be destroyed. |
| 1550 | Your engine is going astern and you pick up sternway. The rudder is midships, and you are operating on a single, right-handed fixed screw. How will your ship react? | She will most likely change heading to port | She will most likely change heading to starboard | The stern will be lifted to starboard | She will most likely go straight astern |
| 1551 | You want to stop your ship as quickly as possible without too much change in the heading. What can you do to achieve this? | do a zig zag maneuver | make a complete turning circle | put the engine full astern | Use the rudder hard over both sides while reducing engine power, so-called "high frequency rudder cycling". |
| 1552 | You have made a turning test on full speed in deep water. You are now going to make a test in shallow water. Do you think the turning diameter will be the same? | No, the turning diameter will be increased in shallow water. | Yes, the turning diameter will be the same for all depths. | No, the turning diameter will be smaller in shallow water. | Yes, it will be the same provided the UKC is 25 % - 50 %. |
| 1553 | You have anchored in a mud and clay bottom. The anchor appears to be dragging in a storm. What action should you take? | Shorten the scope of the cable. | Drop the other anchor underfoot. | Veer cable to the anchor. | Drop the second anchor, veer to a good scope, then weigh the first anchor. |
| 1554 | You are sailing in shallow water, with 15% Under Keel Clearance. With full RPM, what will your speed be compared to deep water? | slower | faster | The RPM will drop with 15% of full | stay the same |
| 1555 | You are sailing in shallow water, with 15% Under Keel Clearance. How will the stopping distance be, compared to deep water? | The same as in all depths | about 1 ship-length longer | shorter | longer |
| 1556 | A nylon mooring rope undergoes a decrease in strength of how many percent if it gets wet by immersion? | 5% | 50% | 20% | 30% |

# OIC NAVIGATIONAL WATCH

| | | | | | |
|---|---|---|---|---|---|
| 1557 | A vessel's bow thruster is usually quite effective at a speed of up to how many knots? | 8 | 3 | 7 | 5 |
| 1558 | Find the scope of an anchor cable with eight shackles paid out in a depth of 96 feet. | 7.5 | 4.8 | 5.4 | 6.7 |
| 1559 | The aft emergency towing arrangement should be pre-rigged and be capable of being deployed in a controlled manner in harbor conditions in not more than: | 5 | 15 | 20 | 10 |
| 1560 | One shackle of anchor chain is equivalent to how many fathoms? | 6 | 60 | 15 | 90 |
| 1561 | Quickwater begins to move forward, up the ship's side, when the ship is making a speed approximately _____ knot, and the quickwater reaches the ship's midships section when the ship moving at a speed of _____ knots. | ( 1 / 0 ) | ( 2 / 0 ) | ( 2 / 1 ) | ( 3 / 1 ) |
| 1562 | As a general rule, a ULCC should not have a speed in any direction greater than what speed when touching berth? | 0.15 knots | 0.25 knots | 0.20 knots | 0.10 knots |
| 1563 | Aft towing arrangement should be rigged and be capable of being deployed in a controlled manner in harbor conditions in NOT more than: | 10 minutes | 30 minutes | 15 minutes | 20 minutes |
| 1564 | How long will a 12 knot steamer normally complete one circle turn at full rudder angle? | 8 minutes | 10 minutes | 13 minutes | 16 minutes |
| 1565 | The auxiliary steering gear shall be capable of putting the rudder over from 15 deg on one side to 15 deg on the other side in not more than _____ at its seagoing draft and service speed of 7 knots or half of the maximum ahead speed whichever is greater. | 15 seconds | 28 seconds | 38 seconds | 60 seconds |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 1566 | At the moment of impact of collision, the following should be noted: | cargo damage on the other ship | the Nationality of the other vessel | the compass heading and approximate angle between the two ships | the Nationality of the crew |
| 1567 | A nylon mooring rope undergoes a decrease in strength of how many percent if it gets wet by immersion? | 20% | 5% | 50% | 30% |
| 1568 | A vessel's bow thruster is usually quite effective at a speed of up to how many knots? | 8 | 7 | 5 | 3 |
| 1569 | Find the scope of an anchor cable with eight shackles paid out in a depth of 96 feet. | 4.8 | 5.4 | 7.5 | 6.7 |
| 1570 | The aft emergency towing arrangement should be pre-rigged and be capable of being deployed in a controlled manner in harbor conditions in not more than: | 5 | 10 | 20 | 15 |
| 1571 | One shackle of anchor chain is equivalent to how many fathoms? | 15 | 6 | 90 | 60 |
| 1572 | Quickwater begins to move forward, up the ship's side, when the ship is making a speed approximately _____ knot, and the quickwater reaches the ship's midships section when the ship moving at a speed of _____ knots. | ( 3 / 1 ) | ( 1 / 0 ) | ( 2 / 0 ) | ( 2 / 1 ) |
| 1573 | As a general rule, a ULCC should not have a speed in any direction greater than what speed when touching berth? | 0.20 knots | 0.25 knots | 0.15 knots | 0.10 knots |
| 1574 | Aft towing arrangement should be rigged and be capable of being deployed in a controlled manner in harbor conditions in NOT more than: | 30 minutes | 15 minutes | 20 minutes | 10 minutes |
| 1575 | How long will a 12 knot steamer normally complete one circle turn at full rudder angle? | 8 minutes | 10 minutes | 13 minutes | 16 minutes |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 1576 | The auxiliary steering gear shall be capable of putting the rudder over from 15 deg on one side to 15 deg on the other side in not more than _____ at its seagoing draft and service speed of 7 knots or half of the maximum ahead speed whichever is greater. | 28 seconds | 60 seconds | 38 seconds | 15 seconds |
| 1577 | At the moment of impact of collision, the following should be noted: | the Nationality of the crew | cargo damage on the other ship | the Nationality of the other vessel | the compass heading and approximate angle between the two ships |
| 1578 | The use of an anchor to assist in turning in restricted waters is: | good seamanship | a last resort | the sign of a novice shiphandler | to be used only with a single-screw vessel |
| 1579 | When proceeding with 8 knots and reversing to full astern, what will be the stopping distance of your ship? | quarter of a mile | 800 meters | I can find out from sea trials or test on my own | The stopping distance will be 8 ships length |
| 1580 | Most naval ships and some merchant vessels are fitted with steam turbines in which the astern power is equal to what part of the ahead power: | full | half | fourth | third |
| 1581 | In the event of collision in calm weather, the colliding ship should generally remain embedded: | to allow another ship time to assess the damage or prepare to abandon ship | to allow coast guards to assess who is to blame on the collision | to allow crew members and passengers to transfer from the holed vessel to the colliding vessel | the colliding ship must pull out immediately |
| 1582 | With rudders amidships and negligible wind, a twin-screw vessel moving astern with both engines backing will back: | to port | to starboard | in a circular motion | in a fairly straight line |
| 1583 | A twin-screw vessel moving astern with both engines backing, with rudders amidships and negligible wind, will back: | to starboard | in a fairly straight line | in a circular motion | to port |
| 1584 | An item of mooring equipment used to maintain or change the direction of a rope or wire in order to provide a straight lead to winch drum. | Fairlead | Topping wire | Windlass | Panting |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 1585 | For the deepest water when rounding a bend in a river, you should navigate your vessel: | toward the outside of the bend | toward the center of the river just before the bend, then change course for the river's center after the bend | toward the inside of the bend | in the river's center |
| 1586 | How many turns of wire normally mark either side of the shackle 105 fathoms from the anchor? | 7 turns | 3 turns | 2 turns | 6 turns |
| 1587 | The capability of towing vessel is BEST measured by maneuverability, horsepower, bollard pull and: | towrope pull | propeller design | stability | displacement |
| 1588 | From the point where the rudder is put over to any point on the turning circle, the distance a vessel moves parallel to the original course is known as: | transfer | kick | advance | head reach |
| 1589 | Before entering an ice area, the ship should be: | trimmed down by the head | on an even keel | either trimmed by the head or the stern | trimmed down by the stern |
| 1590 | When approaching squadrons, convoys, aircraft carriers under way or at anchor, and other warships at sea, what precautions would you take? | Adopt early measures to keep out of the way | Stop your vessel as soon as you see them approaching | Turn reciprocal to your original course | None of the choices is correct |
| 1591 | When steering a vessel, a good helmsman does NOT: | consider steering a vessel a highly responsible job | use as little rudder as possible to keep the vessel on course | use as much rudder as possible to keep the vessel on course | advise his relief of the course being steered |
| 1592 | The tendency of a vessel being attracted bodily towards the bank is known as: | Bank suction | squat | Veering | Bow cushion |
| 1593 | When maneuvering and you like to make short turning point, what should you do? | Wheel hard over slow ahead | Do sternway then wheel hard over full ahead | Wheel hard over full ahead | Wheel hard over half ahead |
| 1594 | The best time to work a boat into a slip is: | when the wind is against you | with the current setting against you | with a cross current | at slack water |
| 1595 | The helmsman should repeat the command given: | before the command | while the command is given | before executing the command | while executing the command |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 1596 | Over what length of time a diesel powered vessel should be slowed down from full sea-speed to maneuvering speed? | 1 hour | 4 hours | 20 minutes | 10 minutes |
| 1597 | You are drifting with a loaded VLCC in open sea. Can you do anything to change your direction and rate of drift? | You can change the angle of heel | You can trim the ship by the stern | You can apply rudder | No |
| 1598 | Your engine is going astern and you pick-up sternway. The rudder is amidships and you are operating on a single, right-handed fixed screw. How will your ship react? | You will change heading to port | You stern will be pushed to starboard | You will change heading to starboard | You will go straight astern |
| 1599 | You are on a large vessel fitted with a right-handed controllable-pitch propeller. When making large speed changes while decreasing pitch, which statement is TRUE? | You may lose rudder control until the ship's speed has dropped to correspond to propeller speed. | The stern will immediately slew to port due to unbalanced forces acting on the propeller. | You will probably have full directional control throughout the speed change. | The stern will immediately slew to starboard due to unbalanced forces acting on the propeller. |
| 1600 | A twin screw vessel is easier to maneuver than single-screw vessel with the engines half ahead. If there is no wind or current and the rudder is amidships, which of the following will happen? | Generates more power | Permits the rudder to move faster | Can suck the water away from the rudder | Can return without using her rudder |
| 1601 | How many degrees is the limit to avoid stalled condition in a rudder angle? | 35 degrees | 15 degrees | 25 degrees | 45 degrees |
| 1602 | What is the frequency of checking the steering gear and its auxiliaries prior to departure? | 6 hours before departure | 12 hours before departure | 1 hour before departure | 3 hours before departure |
| 1603 | If a ship of 15,000 tons deadweight fitted with steam turbine has an astern power of 60,000 knot tons, what is speed of the ship? | 8 knots | 16 knots | 12 knots | 4 knots |
| 1604 | In anchoring, using the scope of 6, determine the number of shackles to be used if the depth of water is 35 meters? | 5 shackles | 7.5 shackles | 6.5 shackles | 4 shackles |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 1605 | The length of mild steel cable to use in meters maybe taken as approximately 25 times the square root of the depth of the water in meters, thus for 90 meters depth the chain, to be laid out is? | 9.7 shackles | 6.7 shackles | 8.7 shackles | 7.7 shackles |
| 1606 | The anchor's holding power in tons on good anchoring ground is about: | 7 - 8 times the anchor's weight | dependent upon the size of the vessel | 9 - 10 times the anchor's weight | 5 - 6 times the anchor's weight |
| 1607 | When using anchor on conventional mooring buoy, anchor shots on the bottom should not be less than: | 8 shackles | 7 shackles | 10 shackles | 9 shackles |
| 1608 | Which statement concerning the handling characteristics of a fully loaded vessel as compared with those of a light vessel is FALSE? | A fully loaded vessel will be slower to respond to the engines. | A fully loaded vessel will maintain her headway further. | A light vessel loses more rudder effect in shallow water. | A light vessel will be more affected by the wind. |
| 1609 | The pivot point of a vessel when going ahead is located: | about one-third of the vessel's length from the bow | at the hawsepipe | about two-thirds of the vessel's length from the bow | at the bow |
| 1610 | In ship handling as the beam of the vessel increase for a given length , it is apparent that directional stability: | Remains the same | Decreases | Accelerates | Increases |
| 1611 | How will you act if you are helmsman and the OOW (officer on watch) gives you the order: "Nothing to port" | Alter course to starboard | Let the ship turn to starboard | Don't let the ship turn to port | Don't give port rudder |
| 1612 | You are coming to anchor in 8 fathoms of water. In this case, the: | anchor should be lowered to the bottom then the ship backed and the remainder of the cable veered | anchor should be lowered to within 2 fathoms of the bottom before being dropped | scope should be less than 3 times the depth of the water | anchor may be dropped from the hawsepipe |
| 1613 | When ship-to-ship operations are being carried out at anchor, irrespective of which ships anchor is down, anchor watch duties are as follows: | Anchor watch responsibility rests with both vessels, each with its own watch | Anchor watch responsibility rests with the discharging vessel (which, we shall assume, has its anchor down) | Anchor watch not kept as duty officer will be on deck | Anchor watch responsibility rests with the off take vessel |

OIC NAVIGATIONAL WATCH

| | | | | | |
|---|---|---|---|---|---|
| 1614 | While approaching berth without the assistance of tugs, what is the usual precautions made by pilot to make sure that your vessel is in safe situation? | stand by engine | Approach slowly with safe speed | Have both anchors ready | any of the choices |
| 1615 | A ship turns around a point called the 'pivot point'. What is the usual position of this point when the ship is at full sea speed? | At about 1/4 of he ship's length from the stern | Amidships | At the stern | At about 1/4 of the ship's from the bow |
| 1616 | What is the correct way in approaching the SPM, taking the prevailing wind, current and waves into consideration? | Current from aft with engine slightly backing | Heading the current with controlled speed | At any position with minimum tug assistance | Current from starboard by allowing the vessel to drift easily to the buoy |
| 1617 | When towing, a tow hook is used to: | provide quick release of the hawser | pull a tow alongside | attach a hawser to a tow which has no bitts or pad eyes | join two hawsers for lengthening a tow |
| 1618 | An example of a modern anchor which has a stock is a(n): | Baldt anchor | articulated anchor | Flipper Delta anchor | Danforth anchor |
| 1619 | An ocean towing bridle should: | have equal legs of sufficient length | never be made up of chain | be formed on a bight of cable through a ring | have a large angle between the legs |
| 1620 | You are meeting another ship in the confined waters. Which statement can happen away from the ship as they approached each other? | Both vessels will be affected by squat | Initially the bows of the ships will be pulled together | Initially the bows of the ship will be pushed away from each other | There will be no effect |
| 1621 | When you are steaming in a heavy seas and you decide to heave to, you have to reduce the speed to the minimum to hold that position and take the sea: | broad on the bow | fine on the bow | forward of the beam | abaft the beam |
| 1622 | A tug would NOT assist a ship to steer if the tug is made up to the large vessel in what area of the vessel? | approximately amidships of the vessel | forward on either bow of the vessel | by a tow line ahead of the vessel | on n the vessel's quarter |
| 1623 | You are a laden tanker which has collided with a smaller vessel. What should your first action be? | Call the company immediately and ask for further procedures | Make a statement and hold the other vessel responsible for the collision | Record the manoeuvre of the other vessel before the collision | Identify the extent of damage to own vessel and take necessary steps to safeguard the complement and the vessel |

# OIC NAVIGATIONAL WATCH

| | | | | | |
|---|---|---|---|---|---|
| 1624 | Your ship is steaming at night with the gyro pilot engaged when you notice that the vessel's course is slowly changing to the right. Which of the following actions should you take FIRST? | Call the Master | Change to telemotor steering | Notify the engine room of the steering malfunction | Send the Quartermaster to the emergency steering station |
| 1625 | It is the term used for the impact between two vessels when one of them is in motion and the other one is stationary. | Allision | Double banking | Collision | Side swipe |
| 1626 | Moving vessel striking against one that is stationary is called: | Collision | Allision | Impact | Accident |
| 1627 | During a rescue operations, a helicopter uses a special device for hoisting or lowering persons with rescue sling and a seating belt from the water or deck. This method is called: | multiple lift method | combo-lift method | double lift method | combined lift method |
| 1628 | Basic signals and maneuvers are common in any parts of the world. The use of ship's whistle to communicate with tugs, one long blast means: | come ahead full slow | tug dismissed | come astern slow | stop |
| 1629 | You are proceeding along the right bank of a narrow channel aboard a right-handed single-screw vessel. The vessel starts to sheer due to bank suction/cushion effect. You should: | back full with rudder amidships | stop engines and put the rudder left full | decrease speed and put the rudder right full | increase speed and put the rudder right full |
| 1630 | The effect we call "squat" occurs. Why? | Increased velocity and decreased water pressure around the ship's hull | Increased effect of gravity due to closeness of the seabed | Decreased velocity and increased water pressure around the ship's hull | The bow and stern wave make the ship sink lower in the water |
| 1631 | Prior entering an ice area, how should a vessel be trimmed? | either by the head or by the stern | down by the stern | evenly | down by the head |
| 1632 | Bilge keel are more effective at dampening rolls as the: | draft decrease | pitching increases | rolling increases | list increase |
| 1633 | The vessel is navigating parallel to the bank, her stern moves: | the way the pilot maneuvers | towards the bank | either sides | away from the bank |

NOT FOR SALE

# OIC NAVIGATIONAL WATCH

| | | | | | |
|---|---|---|---|---|---|
| 1634 | You are the Master on board a single-screw vessel. You are docking at a berth without tugs available. You decide to drop the offshore anchor to help in docking. What is the amount of chain you must pay out? | 1.5 to 2 times the depth of the water | 5 to 7 times the depth of the water | equal to the depth of the water | you must NEVER use the anchor to help in docking |
| 1635 | In the event of loss of rudder, what appropriate action should be done? | abandon ship | use the emergency steering wheel (trick wheel) | execute a Williamson turn | a jury may be achieved by providing a drag on each side of the ship |
| 1636 | During a stay in port, a towing wire is to be put out forward and aft. What is important to take care of regarding this wire? | For night-time use only | That the wires are just above the water line at all times | For daytime use only | The wires are just stand by on deck |
| 1637 | Your vessel is navigating along a narrow channel. The effect called "bank cushion" has which effect on the vessel? | Forces the stern away from the bank | Sucks the bow towards the bank | Forces the entire vessel bodily away from the bank | Forces the bow away from the bank |
| 1638 | A twin-screw vessel can clear the inboard propeller and maneuver off a pier best by holding a(n): | forward spring line and going slow ahead on the outboard engine | forward spring line and going slow ahead on both engines | forward spring line and going slow ahead on the inboard engine | after spring line and going slow astern on the outboard engine |
| 1639 | Your vessel is a large twin-screw ship. You are stopped at the pilot station with no way upon your vessel. You must come around 180deg. to board your Pilot. How must you use the engines and rudder to turn the ship fastest in the least amount of space? | Full ahead on the engines and hard over rudder | Half ahead with hard over rudder, then full astern on inboard engine | Full ahead on one engine, full astern on the other | Slow ahead with hard over rudder |
| 1640 | Your vessel is navigating along a narrow channel at a slow speed with your starboard side near the right bank of a channel. What would be the best maneuver if your vessel suddenly sheers toward the opposite bank? | full ahead, hard left rudder | full astern, hard right rudder | full astern, hard left rudder | full ahead, hard right rudder |
| 1641 | What does "Hard Starboard" mean? | Put the rudder full starboard | Do not come to port | Hard rocks on starboard | A ship is seen to starboard |

OIC NAVIGATIONAL WATCH

| | | | | | |
|---|---|---|---|---|---|
| 1642 | At seaway a thwarthship swinging of a vessel. | Heaving | Rolling | Pitching | Yawning |
| 1643 | A rudder with a blade fully unbalanced is the: | simple type | horn type | spade type | door type |
| 1644 | What would you expect your rudder response to be when you enter shallow water? | be sluggish and your speed to decrease | be sluggish and your speed to increase | improve and your speed to decrease | improve and your speed to increase |
| 1645 | The squat effect of a large vessel travelling at high speed will caused an increased of her draft by: | in excess of two meters by foreward | in excess of one meters by mean | in excess of two meters by mean | in excess of two meters by astern |
| 1646 | In shiphandling in heavy weather, you notice your vessel's screw is being lifted clear of the water and racing. One way to correct this would be to: | shift the rudder back and forth several times | decrease speed | move more weight forward | increase speed |
| 1647 | To prevent pounding, what should you do if you are underway in heavy weather and your bow is into the seas? | increase speed | secure all loose gear | change course, in order to take the seas at an 85 degree angle from the bow | decrease speed |
| 1648 | In the vicinity of a collision area, which of the following equipment should be ready? | firefighting equipment | an explosive gas meter | intercom telephone | oxygen analyzer |
| 1649 | The effect known as "bank cushion" acts in which of the following ways on a single-screw vessel proceeding along a narrow channel? | it forces the stern away from the bank | it forces the entire vessel away from the bank | it forces the bow away from the bank | it heels the vessel towards the bank |
| 1650 | Bow thrusters are essential propulsion device to make a vessel more maneuverable. However, the disadvantage is: | it is not effective on slow moving ship | it has no effect on headway to slow down or hold a ship | it has little effect on a fully loaded ship | it does not provide greater power than tug |
| 1651 | At sea you sight a tug displaying a black square flag below a black ball on its mast. You should: | render assistance to the tug | keep clear as she is towing a dracone | keep well clear as the tug is restricted in her ability to maneuver | keep clear as she is escorting a submersible |
| 1652 | What will you do if you are helmsman and the OOW (officer on watch) gives you the order: "Starboard ten" | Engage the automatic pilot and alter course | Put the rudder 10 degrees to starboard | Change course 10 degrees to starboard | Let the vessel drift 10 degrees to starboard |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 1653 | Your vessel is to turn in a narrow canal by use of one tug (turn to port with the bow). In which position and how would you use the tug? (Vessels engine will be used as well). | Make the tug fast on starboard shoulder to push | Make the tug fast aft for pulling | Make the tug fast in centre bow fairlead for pulling | Make the tug fast on port shoulder to pull |
| 1654 | When a vessel is using one anchor her bow and stern line to the "L" Jetty she said to be: | Mediterranean moor | Baltic moor | Open moor | Y moor |
| 1655 | What is the CORRECT way to do when making way in heavy seas and you notice that your vessel's screw is being lifted clear of the water and racing? | decrease speed | increase speed | move more weight forward | shift the rudder back and forth several times |
| 1656 | When making way in heavy seas you notice that your vessel's screw is being lifted clear of the water and racing. One way to correct this would be to: | increase speed | move more weight forward | decrease speed | shift the rudder back and forth several times |
| 1657 | When your ship is going full speed ahead with no wind and no current, where do you think the "pivot point" is located? | At about 1/6 of the ship's length from the stern | At about 1/6 of the ship's length from the bow | Amidships | Near the stern |
| 1658 | Vessels as far as possible should avoid anchoring: | in a traffic separation scheme or in areas near it's terminations | in a traffic separation zone | near the terminations of a traffic flow in a traffic separation scheme from either side shall do so | in a traffic separation scheme |
| 1659 | Do you think there is any reduction in the rudder lift force if the propeller is stopped? | No ,we will maintain about 90 % of the lift force | Yes, the lift force will be dramatically reduced | Yes ,we will loose about 10% of the lift force | No, the lift force is not effected by the propeller |
| 1660 | Does a vessel's trim has any influence on steering abilities? | No, it is usually best to have no trim at all | No, the vessel will have the same steering ability unaffected by trim | Yes, a vessel usually steer better if trimmed by the bow | Yes, the vessel usually steer better if trimmed by the stern |

NOT FOR SALE

# OIC NAVIGATIONAL WATCH

| | | | | | |
|---|---|---|---|---|---|
| 1661 | Your ship is making sternway of about 1.5 knots, with rudder hard to starboard. Will this rudder position have any effect on the ship's behavior? Choose the most complete answer. | Yes, it will give the stern a lift force to starboard | No, the rudder will have no effect when the ship is making sternway, it should be in midship position | No, the ship will go straight astern | Yes, it will give the stern a lift force to port |
| 1662 | You are in charge of a twin-screw vessel going ahead with rudders amidships. If suddenly the port screw stops turning, the bow will: | go to starboard | not veer to either side | go first to port and then to starboard | go to port |
| 1663 | A passenger vessel must have an emergency squad when: | on voyage in excess of 12 hours duration | more than 50 passengers are on board | the size of the crew permits | certificated for over 12 passengers |
| 1664 | Chafing gear is used to: | protect fiber rope from abrasion | anchor the boat | pick up heavy loads | strengthen mooring lines |
| 1665 | What is the diameter of a circle called which traversed by a vessel after running through 360 degrees and maintaining the same speed and rudder angle? | Turning circle | Tactical diameter | Final Diameter | Pivoting angle |
| 1666 | The best line for towing small vessels is: | polypropylene | double-braided nylon | three strand nylon | manila |
| 1667 | The purpose of establishing emergency towing arrangement onboard tankers is to facilitate salvage and towing operations and: | prevent risk of environmental pollution | ensure easier salvage works | protect the interests of cargo owners | prevent undue delays to ship during engine breakdowns |
| 1668 | What will you do if you are helmsman and the OOW (officer on watch) gives you the order: "Hard starboard" and after a while the order: "Meet her" | Put the rudder all the way to port to stop the turning | Put the rudder midship | Put the rudder about half way to port to slow down the turning rate | Put the rudder 15 degrees to starboard |
| 1669 | What will you do if you are helmsman and the OOW (officer on watch) gives you the order: "Port 20" and after a while the order: "Ease your helm" | Put the rudder to midship position | Put the rudder to starboard to ease the turn | Put the rudder all the way to starboard to stop the turn | Turn the rudder towards midship, but normally not all the way to midship position |
| 1670 | When a tow is trimmed by the stern it is said to: | sag | hog | drag | list |

NOT FOR SALE

# OIC NAVIGATIONAL WATCH

| | | | | | |
|---|---|---|---|---|---|
| 1671 | What maneuver will return your vessel in the shortest possible time to a person who has fallen overboard? | Anderson Turn | Williamson Turn | Scharnow turn | Any turn will do |
| 1672 | In towing, chocks are used to: | secure the end of the towline on the tug | absorb shock loading on the towline | protect the towline from chafing | stop off the towline while retrieving it |
| 1673 | A rudder with a fixed butt is the: | door type | horn type | spade type | simple type |
| 1674 | These propeller are in turning but the shaft revolves always in the same direction the astern power being obtained by reversing the pitch of the screws: | twin screw | controllable - pitch propeller | triple or multiple screw | single screw |
| 1675 | The propeller stopped with the rudder in hard over position. The vessel is turning slowly. In order to make her turn faster without increasing forward speed, give: | slow ahead and leave her in that position | full astern until ship is stopped, then full ahead again with rudder hard over | half astern as this will increase rate of turn | a kick ahead |
| 1676 | How will you define "squat"? | Increase in draft to the point on your ship which is closest to the bottom | Decrease in draft of your ship | Squat is not relevant on your ship | The speed of your ship will increase |
| 1677 | The anchor's holding capability is determined primarily by which of the following? | shape of the anchor | anchor's ability to dig in | stowage of the anchor on board | size of the vessel and its draft |
| 1678 | This term means the distance that a vessel travels from the time the engines were ordered and placed on full astern until the vessel is dead in the water. | transfer | advance | head reach | surge |
| 1679 | If the helmsman changes from right rudder to left rudder, or vice versa, in equal number of degrees. What is the helm command? | ease the rudder | swing your rudder | meet her | shift your rudder |
| 1680 | What is the correct way in approaching the SPM, taking the prevailing wind, current and waves into consideration? | Heading the current with controlled speed | Current from starboard by allowing the vessel to drift easily to the buoy | At any position with minimum tug assistance | Current from aft with engine slightly backing |

| | | | | | |
|---|---|---|---|---|---|
| 1681 | A motion of a ship in waves about the ship transverse axis. | yawing | Pitching | rolling | heaving |
| 1682 | Heave is the motion of a vessel along the: | longitudinal axis | centerline axis | transverse axis | vertical axis |
| 1683 | Horizontal fore or aft motion of a vessel is known as: | pitch | surge | sway | roll |
| 1684 | Horizontal transverse motion of a vessel is known as: | Heave | Sway | Surge | Pitch |
| 1685 | The oscillating of a vessel on her longitudinal axis is termed as: | yawing | pitching | rolling | heaving |
| 1686 | A synchronous rolling motion will occur when the encounter wave period is nearly equal to ship's: | natural rolling period | rolling period | natural pitching period | any of the above |
| 1687 | Motion of a vessel in waves about the vessel's vertical axis. | Pitching | Heaving | Yawning | Rolling |
| 1688 | At seaway a thwarthship swinging of a vessel. | Heaving | Rolling | Yawning | Pitching |
| 1689 | In bad weather what length of chain should be used with a single anchor? | 6 times the depth of water | 3 times the depth of water | 10 times the depth of water | 15 times the depth of water |
| 1690 | In securing a towing cable consideration must be given to letting go in an emergency. The possible whip of towlines when released can be overcome by _____. | using preventers | using a pelican hook for quick release | using a short chain for the lead through the stern chock | increasing the shaft RPM prior to release |
| 1691 | The biggest problem encountered when towing bridle legs are too short is _____. | hookup to main towline | adjusting tension | retrieval | excessive strain |
| 1692 | The effect of ocean current is usually more evident on a tug and tow than on a tug navigating independently because the _____. | towline catches the current | current causes yawing | speed of the tug and tow is less | current will offset the tow |
| 1693 | The effect of wind in an exposed areas of a ship is most noticeable when the vessel is _____. | backing | going slow ahead | going full ahead | turning |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 1694 | The major components which determine the length of a catenary in a deployed anchor cable are water depth cable weight and _____. | bottom conditions | water temperature | cable tension | water density |
| 1695 | The rudders are amidships and both screws are going ahead. What will happen if the starboard screw is stopped? | The bow will go to port. | The bow will remain steady. | The stern will go to starboard. | The bow will go to starboard. |
| 1696 | The static bollard pull of a tug is measured in tons and consists of the brake horsepower of the tugs engine divided by 100 and multiplied by a factor of _____. | 1.3 | 0.5 | 3 | 10 |
| 1697 | What are reef points used for? | Keep the sail taut in light airs | Reduce the draft if the boat runs aground | Increase the strength of the mast | Reduce the area of a sail |
| 1698 | What does in step refer to in regards to towing? | The towed vessel follows exactly in the wake of the towing vessel. | There is no catenary in the towing hawser. | Both the towed and towing vessels reach a wave crest or trough at the same time. | When turning both the towed and towing vessels turn at the same time. |
| 1699 | What does the term end-for-end refer to in regard to a wire towing hawser? | Removing the wire rope from the drum and reversing it so that the towing end becomes the bitter end | Cutting off the bitter and towing ends of the wire rope | Splicing two wire ropes together | Removing the wire rope from the drum and turning it over so that the wire bends in the opposite direction when rolled on a drum |
| 1700 | What is meant by veering the anchor chain | locking the windlass to prevent more chain from running out | paying out more chain | heaving in all chain | bringing the anchor to short stay |
| 1701 | What phenomenon shall a large vessel experience when entering a shallow water at high speed? | speed will increase | maneuverability will increase | vessel will rise slightly on the bow | the bow will squat further than the stern |
| 1702 | What precaution should be in mind when maneuvering a steam vessel? | the backing power is low in reacting | idle for few seconds | instant reversing | powerful |
| 1703 | When connecting the tow bridle to a tug the end of the bridle is passed with a _____. | shot line | heaving line | high line | messenger line |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 1704 | When must the owner or Master of a towing vessel retest a towline or remove it from service? | After it drags on the bottom. | When the record of its material condition lapses for 3 months or more. | When it has not been used for over 60 days. | After it jams on the towing winch. |
| 1705 | When towing astern what equipment should be stowed ready for use near the towline? | Axe or cutting torch | Chafing gear | Fire extinguisher | First aid kit |
| 1706 | When towing the least amount of tension will be on each bridle leg when the two legs _____. | form a large angle with each other | form a small angle with each other | are of unequal length | are joined by a fishplate |
| 1707 | When you have a tow alongside your stern should extend aft of the tow in order to _____. | provide a better lead for your lines | let the barge deflect floating objects from your propeller | obtain better steering control | avoid obscuring your stern light |
| 1708 | Which of the following is the effect of bank cushion on a single screw vessel proceeding along a narrow channel? | forces the bow away from the bank | decreases the draft at the bow | forces the entire vessel bodily away from the bank | forces the stern away from the bank |
| 1709 | Which of the following is the effect of depth of water on turning radius if the ship is at low speed? | the same turning radius | smaller turning radius a shallow water | larger turning radius at deep water | larger turning radius at shallow water |
| 1710 | While towing bridle legs of unequal lengths may cause _____. | a bent swivel | chafing on the fairlead or bitts | the shorter leg to fail | the bridle to foul |
| 1711 | With regard to aerodynamic lift which statement is TRUE? | If the thrust on a sail becomes excessive when close-hauled it is likely to capsize the vessel rather than drive it. | When a sail is trimmed too tight turbulence will break out on the windward side of the sail and cause a telltale there to flutter. | A properly trimmed sail should have laminar flow on the windward side and turbulent flow on the leeward side. | Adjusting the angle of attack on a mainsail is accomplished by adjusting the outhaul or the vang if fitted. |
| 1712 | You are aboard a right-handed single-screw vessel with headway on. The engine is put full astern and the rudder hard left. What will the bow do? | It will swing to the left and will swing left faster as the vessel loses way. | It will swing to the left without increasing or decreasing its swing. | It will swing to the left straighten out and then swing to the right as the vessel loses way. | The bow will swing to the right. |
| 1713 | You are aboard a single-screw vessel (right-hand propeller) going full ahead with good headway. The engine is put astern and the rudder is placed hard left. The stern of the vessel will swing to _____. | port slowly at first and then quickly to port | starboard until headway is lost and then to port | port until headway is lost and then may possibly swing to starboard | port |

| | | | | | |
|---|---|---|---|---|---|
| 1714 | A mooring line leading 45Deg to the keel, used to check forward or astern movement of a vessel, is called a _____. | breast line | warp line | spring line | bow line |
| 1715 | A loose tow may cause all of the following EXCEPT _____. | a saving in the transit time | loss of maneuverability | damage to the towing vessel and tow | lines to part |
| 1716 | A Mediterranean moor should be used when _____. | when anchoring in the Mediterranean | when anchoring in a strong current | when docking bow to a berth | when docking stern to a berth |
| 1717 | A reaching course is one in which the wind _____. | has no effect on the vessel | comes directly over the bow | comes over an area extending from broad on the bow to the quarter | comes directly over the stern |
| 1718 | A spring line is _____. | a mooring line running diagonally to the keel | a fire-warp | any wire rope used for mooring | a mooring line perpendicular to the keel |
| 1719 | A stopper is _____. | an engine order telegraph | the brake on a cargo winch | a short length of line used for temporarily holding another line | a snatch block for handling a topping lift |
| 1720 | A bollard is found on the _____. | towed vessel | deck | beach | pier |
| 1721 | A bow thruster _____? I. is effective in slowing down a vessel. II. Loses effectiveness when the vessel s speed exceeds 3 knots. III. Provides lateral control without affecting headway | I and II only | II and III only | I and III only | I II and III |
| 1722 | A bridle for an ocean tow consists of _____. | two chains of equal length | two long legs of wire rope shackled to a fishplate | a single nylon pendant rove through a heavy ring free to move on the pendant | a single length of heavy chain with both ends secured on deck to welded pad eyes |
| 1723 | A deep draft VLCC (100 000 DWT+) navigating in a narrow channel or canal _____. | draws less water with an increase in speed | steers better under full power | draws more water than when underway in deep water | requires less power for a given speed |
| 1724 | A large vessel entering shallow water at high speed experience a phenomenon such as ____. | the bow will squat further than the stern | speed will increase | vessel will rise slightly on the bow. | maneuverability will increase |
| 1725 | A lashing used to secure three or four barges at a common corner lashed in an X fashion is called a _____. | breast wire | towing wire | scissor wire | cross wire |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 1726 | A method used to make an eye in a bight of line where it cannot be spliced is known as _____. | serving | seizing | braiding | plaiting |
| 1727 | A monkey fist is found on a _____. | heaving line | manrope | mooring line | lead line |
| 1728 | A mooring line is described as being 6x24 1-3/4 inch wire rope. What do the above numbers refer to? | Strands circumference wires | Strands wires diameter | Wires yarns diameter | Strands yarns circumference |
| 1729 | A mooring line leading at nearly right angles to the keel is a _____. | spring line | stern line | bow line | breast line |
| 1730 | A mooring line that checks forward motion of a vessel at a pier is a _____. | stern line | stern breast line | bow line | forward bow line |
| 1731 | A mooring rope breaks close to the eye splice during cargo operations at night what action would you take? | Inform the stevedores | Replace it at once | Repair it in the morning | Inform the boatswain |
| 1732 | A rope made of a combination of wire and fiber is known as _____. | preformed | independent | lang lay | spring lay |
| 1733 | A six-strand composite rope made up of alternate fiber and wire strands around a fiber core is called _____. | spring lay | lang lay | cable lay | alternate lay |
| 1734 | A survival craft being used to pick up a person who has fallen overboard from a MODU should approach the person _____. | at a high rate of speed | with the wind | against the wind | under oars |
| 1735 | A term used to describe the dip in a towline that acts as a shock absorber is _____. | step | catenary | bight | shock dip |
| 1736 | A tow astern is veering from side to side on its towline. The best way of controlling the action is to _____. | trim the tow by the stern | adjust the length of the towing bridle | list the tow to windward | trim the tow by the bow |
| 1737 | A towing hawser is readied for service by _____. | coiling it in a counterclockwise direction on the fantail | spooling it on a reel lying on its side to prevent rolling | spooling it on a winch cathead | faking it on deck in a fore and aft direction |
| 1738 | A towing hawser should be stowed _____. | by hanging it in the engine room | by faking on a rack | in a sealed locker with adequate air circulation | by spooling it on the winch |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 1739 | A towing hook may be released from the _____. | pilot house or aft steering station | towing bitts by reaching over and releasing a lever | tug s engine room or the bow | forecastle |
| 1740 | A vessel reduces speed without backing. The rate that her speed through the water decreases depends primarily on the _____. | number of propellers | vessels horsepower | vessels displacement | sea state |
| 1741 | Which of the following is the effect of depth of water on turning radius if the ship is at low speed? | Larger turning radius at deep water | Larger turning radius at shallow water | Smaller turning radius a shallow water | The same turning radius |
| 1742 | How do we define the location of the pivot point? | The point where the sideways motion of the ship`s centreline is zero. | The point on the ship where the forward motion is at maximum | The point on the ship where you have maximum sideways motion in a turn | The point on the ship where the sideways motion forward is at maximum |
| 1743 | A ship is turning around a point called the pivot point. What is the position of this invisible point when the ship is dead in the water? | outside of the center line | About same position as the center of gravity. | near the stern of the ship | near the bow |
| 1744 | A bow thruster _____? I. is effective in slowing down a vessel. II. Loses effectiveness when the vessels speed exceeds 3 knots. III. Provides lateral control without affecting headway | I and II only | I and III only | I, II and III | II and III only |
| 1745 | A deep draft VLCC (100,000 DWT+) navigating in a narrow channel or canal _____. | draws more water than when underway in deep water | requires less power for a given speed | steers better under full power | draws less water with an increase in speed |
| 1746 | For a right handed single screw vessel it is easier to berth_____ | either side to the wharf | port side to the wharf | stern to the wharf | starboard side to the wharf |
| 1747 | The effects of shallow water with speed and rudder of the ship is great during maneuvering at high speed and becomes excessive if the depth is _____. | less than three and a half the draft | None of the stated options | less than one and a half the draft | less than two and a half the draft |
| 1748 | The pivoting point of a vessel going ahead is _____. | about one-third of the vessels length from the bow | at the hawsepipe | near the stern | about two-thirds of the vessels length from the bow |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 1749 | The rudder is in hard over position, propeller stopped. The ship is turning slowly. What can we do to make her turn faster without increasing forward speed? | Give slow ahead and leave her in that position. | Give half astern as this will increase rate of turn. | Give a kick ahead. | Give full astern until ship is stopped, then full ahead again with rudder hard over. |
| 1750 | The rudders are amidships and both screws are going ahead. What will happen if the starboard screw is stopped? | The stern will go to starboard. | The bow will go to starboard. | The bow will go to port. | The bow will remain steady. |
| 1751 | What phenomenon shall a large vessel experience when entering a shallow water at high speed? | the bow will squat further than the stern | speed will increase | vessel will rise slightly on the bow | maneuverability will increase |
| 1752 | What precaution should be in mind when maneuvering a steam vessel? | instant reversing | idle for few seconds | the backing power is low in reacting | powerful |
| 1753 | Your ship is going full ahead as you start to slow down. Where is the position of the pivot point now? No wind, current. | It will move aft as the ship slows down | It will move to the side of the center line | Same position as when the ship is on full ahead | The pivot point will move to the stern |
| 1754 | Your ship is going full astern and making sternway. Where will the pivot point be located? No wind, current. | At 1/6 of the ships length off the bow | Somewhere aft of the center of gravity, but it is impossible to pin-point the exact location | at the center of gravity | At 1/6 of the ships length from the stern |
| 1755 | The effect of wind in an exposed areas of a ship is most noticeable when the vessel is _____. | going slow ahead | going full ahead | backing | turning |
| 1756 | A vessel is equipped with twin propellers, both turning outboard with the engines half ahead. If there is no wind or current and the rudders are amidships, what will happen? | The vessel will steer a fairly straight course. | The vessel will steer a zigzag course. | The bow will swing to starboard. | The bow will swing to port. |
| 1757 | A wind has caused a difference between drafts starboard and port. This difference is _____. | flotation | trim | heel | list |
| 1758 | In a following sea, a wave has overtaken your vessel and thrown the stern to starboard. To continue along your original course, you should _____. | decrease speed | use more right rudder | increase speed | use more left rudder |

| | | | | | |
|---|---|---|---|---|---|
| 1759 | In a river subject to tidal currents, the best time to dock a ship without the assistance of tugs is _____. | at slack water | at flood | at high water | when there is a following current |
| 1760 | When making way in heavy seas you notice that your vessels screw is being lifted clear of the water and racing. One way to correct this would be to _____. | shift the rudder back and forth several times | decrease speed | increase speed | move more weight forward |
| 1761 | An execution by swinging out of the ship with maximum wheel either port or starboard, and subsequently reverse the wheel so that them ships head swings out to, but not beyond 60 from the original course, then continue to swing back with full wheel. | Double turn | Scharnow turn | Williamson turn | Single turn |
| 1762 | A large vessel, entering shallow water at high speed experience a phenomenon such as ____. | speed will increase | vessel will rise slightly on the bow. | maneuverability will increase | the bow will squat further than the stern |
| 1763 | A common occurrence when a vessel is running into shallow water is that _____. | squat will cause a decrease in bottom clearance and an increase in draft | the vessel is more responsive to the rudder | the wake is less pronounced | all of the options |
| 1764 | A vessel traveling down a narrow channel, especially if the draft is nearly equal to the depth of the water, may set off the nearer side. This effect is known as _____. | smelling the bottom | squatting | bank suction | bank cushion |
| 1765 | A vessel will squat when it proceeds underway _____. | only in shallow water | in all depths of water | only in deep water | only in narrow channels |
| 1766 | In principles of ship handling which factor that a master or a pilot has no direct control of the ship. | shallow water factor | speed factor | deep water factor | course factor |
| 1767 | When you enter shallow water, you would expect your rudder response to _____. | improve and your speed to decrease | be sluggish and your speed to increase | improve and your speed to increase | be sluggish and your speed to decrease |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 1768 | Which of the following is the effect of depth of water on turning radius if the ship is at low speed? | smaller turning radius a shallow water | larger turning radius at shallow water | the same turning radius | larger turning radius at deep water |
| 1769 | Which of the following is the effect of bank cushion on a single screw vessel proceeding along a narrow channel? | forces the bow away from the bank | decreases the draft at the bow | forces the entire vessel bodily away from the bank | forces the stern away from the bank |
| 1770 | Which of the following shallow water effect will increase dramatically if you increase your ships speed past its critical speed. | Sinkage | Smelling the bottom | Squat | Bank cushion |
| 1771 | You are on a single crew vessel with a right handed propeller vessel and you are making headway. When you come upon shallow water _____ | you will have better rudder response | your vessel will tend to ride higher | your speed will increase without a change in you throttle | your rudder response will become sluggish |
| 1772 | You have made a turning circle at full speed in deep water. You are now going to make one with initial speed, slow ahead. Do you think the diameter will differ from that of initial full ahead? | The diameter will be the same whatever initial speed we have when starting the turn. | Yes, it will be a large difference in the turning diameter between full and slow ahead. | Yes, it will be much smaller with slow ahead. | Yes, it will be much greater with slow ahead. |
| 1773 | You have made a turning test on full speed in deep water. You are now going to make a test in shallow water. Do you think the turning diameter will be the same? | Yes, it will be the same provided the UKC is 25 % - 50 %. | No, the turning diameter will be smaller in shallow water. | Yes, the turning diameter will be the same for all depths. | No, the turning diameter will be increased in shallow water. |
| 1774 | A ship is having a slow speed, by using the backing maneuver, the ship is considered to be dead on the water when the | quick water reaches the stern | quick water reaches about 1/4 distance from the stern | quick water reaches the amidships | speed of the ship is the same speed as quick water |
| 1775 | How many fathoms are in a shot of anchor cable? | 30 | 6 | 20 | 15 |
| 1776 | How many feet are there in 2 shots of anchor chain? | 60 | 50 | 180 | 360 |
| 1777 | If you shorten the scope of anchor cable, your anchors holding power _____. | decreases | has no relation to the scope | increases | remains the same |
| 1778 | If your vessel is dragging her anchor in a strong wind, you should _____. | put over a stern anchor | shorten the scope of anchor cable | increase the scope of anchor cable | put over the sea anchor |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 1779 | In an emergency and the anchor is dropped while at full ahead, do not slack the cable as soon as the anchor holds. | probably true | cannot determine | FALSE | TRUE |
| 1780 | In bad weather, what length of chain should be used with a single anchor? | 10 times the depth of water | 6 times the depth of water | 15 times the depth of water | 3 times the depth of water |
| 1781 | In determining the scope of cable to be used when anchoring, what would NOT be considered? | Type of anchor cable | maintenance cost for the chain | Depth of the water | Character of the holding ground |
| 1782 | In moderate wind and current what should be the length of chain with a single anchor? | 10 times the depth of the water in shallow water | 8 times the depth of the water in deep water | 2 times the depth of the water in poor holding ground | 5 times the depth of the water in good holding ground |
| 1783 | Before letting the anchor go, you should check that the _____. | all of the options | chain is clear | anchor is clear of obstructions | wildcat is disengaged |
| 1784 | Generally speaking, the most favorable bottom for anchoring is _____. | loose sand | a mixture of mud and clay | rocky | very soft mud |
| 1785 | The easiest way to anchor a vessel in a current is to _____. | stem the current and make very slow headway when the anchor is dropped | stem the current and endeavor to make neither headway nor sternway when the anchor is dropped | stop all headway through the water and keep the current astern when the anchor is dropped | stem the current and be falling aft very slowly when the anchor is dropped |
| 1786 | This is a modern method of welding where there is actual melting of the materials being joined although the weld metal is composed largely of added materials having the same characteristics as the metal being joined. | fusion weld | arc weld | butt weld | fillet weld |
| 1787 | What is the name called to a single fitting installed in a pipeline that either blanks off the pipe or allows a full flow passage of a liquid through the pipe? | Blind Flange | Spectacle Flange | Pivot coupling | Quick Release Coupling |
| 1788 | What kind of gauging is used in airtight enclosed cargo tanks? | Slip tubes | Sounding tape | Closed gauging | Float gauge |
| 1789 | Which factor is not important when calculating the best use of the cubic capacity of a ship's hold? | The value of the cargo | The proper use of filler cargo | The skill of the longshoremen | The choice of cargo to fit the hold |

NCLEX FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 1790 | These are devices which secure standing and running riggings that includes cleats, bitts, chocks, fairleads and pad eye. | deck device | deck fittings | deck store | deck gear |
| 1791 | When heating a metal and cooling it down for desired fashion. This is called: | strengthening | cooling | heating | annealing |
| 1792 | You are arriving at Edinburg to load 1,000 cases of Scotch whiskey. The cases are packed with 12 bottles of one liter each to a case. The flash point of the Scotch isº F. Which of the following is TRUE? | This cargo is not permitted to be towed on deck | The individual cases must be labeled with a red label reading "Combustible Liquid" | The Scotch is not required to be shipped under the requirements of the hazardous materials regulations | The optional shipping name that can be used on the manifest is "Intoxicant" |
| 1793 | In preparation for receiving chilled reefer cargo, the reefer space has been pre-cooled for over twenty-four hours. Loading may begin when the space has been cooled to a temperature between _____. | 28° F and 40° F | 12° F and 20° F | -10° F and + 10° F | 42° F and 55° F |
| 1794 | What is usually NOT required in preparing a hold for reception of a bulk grain cargo? | Remove loose rust and scale | Steam clean areas obstructed by structural members | Spray of fumigate any insect colonies | Remove residue of previous cargo |
| 1795 | Under normal weather and sea conditions when securing a stack of containers with non-locking fittings, lashings are required when the tier exceeds what height? | One container | Two containers | Lashing are always required | Three containers |
| 1796 | With the buttress securing system, containers of different height must be stowed _____. | on the top tier | in the hold | next to the buttress tower | on the bottom tier on deck |
| 1797 | When referring to dry bulk cargoes, the term “flow state”. | Relates to the minimum granule size of a particular product where it will flow like a | Refers to the saturation of dry a bulk product with water to the point where it acts as a liquid | Relates to the suitability of loading a cargo by flowing down inclined chutes. | Designates the state of a commodity when the ship is heeled past the angle of repose. |
| 1798 | When a two-leg sling attached to one hoist line is used to lift a load, a sling of 40 ft. in length is better than one of 30 ft. because the _____. | sling will easier to remove | sling will be easier to attach | load can be lifted higher | tension in the sling leg is less |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 1799 | Your ship has been holed in amidships compartment and partially flooded. If flooded compartment does not have free flow with the sea, you should use which of the following method to calculate the effect of flooding on your stability. | lost buoyancy method | added weight method | compartment standard method | all answers are correct |
| 1800 | Which of the following will NOT increase friction of a liquid flowing in a pipe and cause a loss of suction head? | Slowing the pumping rate | Pipeline valves | Bends in the piping | Backing rings for pipe welds |
| 1801 | When the dew point of the outside air is lower than or equal to the dew point of the air is cargo hold, you should _____. | Secure all ventialtion | Ventilate the cargo holds | Shut down the intake blowers | Shut down the exhaust blowers |
| 1802 | Which of the following statements is true? I. Dunnages should be cleaned and dried before being used in frozen compartments. II. Dunnages should not be pre-cooled prior loading in refrigerated compartments. | I and II are true | I and II are false | Only I is true | Only II is true |
| 1803 | Which of the following is one major advantage of the load-on-stop system? | Oil that was previously lost is recovered | Cargo tanks corrosion is reduced | Discharge time is significantly reduced | No danger of contamination |
| 1804 | Which of the following is not a precaution to be taken when topping off? | Give the operation undivided attention | Maintain communications with the dock man | Reduce the loading rate | Notify the engine room of procedure |
| 1805 | Which of the following contains all the information necessary to check that a proposed loading plan complies with the stability requirements of the regulations at all stages of the voyage. | hydrostatic curve | grain loading stability booklet and associated plans | Tank calibration curve | all the given choices are correct |
| 1806 | When viewed from above, the best position for the guy in relation to the boom is_____. | right angle | at 45 degrees angle | parallel to the boom | aft of the boom |
| 1807 | Under IMDG Code, acids are labeled with a _____ placard | red and white | skull an crossbones | white | red |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 1808 | This is a piece of securing dunnage that runs from a high supporting level down to the cargo to prevent shifting. | tomming | shoring | bracing | Cribbing |
| 1809 | Spontaneous heating of coal rapidly accelerates at the approximate minimum temperature of: | 88 degrees F | 100 degrees F | 119 degrees F | 111 degrees F |
| 1810 | Packages containing dangerous goods shall be provided with _____, as appropriate, so as to make clear the dangerous properties of the goods contained therein. | distinctive labels | stencils of the labels | Placards | all the given choices are correct |
| 1811 | On a manned ship carrying packaged hazardous cargo, the hazardous materials shall be inspected _____. | All of the above | Prior to the entry into a U.S. port | After stowage is complete | Every 24 hours. unless equipped with a fire detecting system |
| 1812 | If reefer spaces are not properly cleaned prior to loading cargo, it will most likely cause. | contamination of the insulation in the space | malfunction of the refrigeration equipment | all answers are correct | mold to develop on commodities |
| 1813 | Determine whether the following statements are true or false? I. The separation of odorous and sensitive cargo into separate airtight compartment would prohibit tainting. II. An odorous cargo may well leave a well tainted atmosphere behind after d | Only II is false | I and II are false | I and II are true | Only I is true |
| 1814 | Container spreader are used to _____. | Lift containers for loading and unloading | Keep the container in place during the voyage | To secure the containers in hold | Spread the contents of the containers for Customs Inspection |
| 1815 | Argon is classified as a _____. | flammable gas | corrosive | non flammable gas | flammable liquid |
| 1816 | A condition in which the oxygen content throughout the atmosphere of a tank has been reduced to 8%. | None of these | Inert gas condition | Safety condition | Poisonous condition |
| 1817 | IMO Grain Regulations assume a pattern of movement of grain in the void spaces above the grain surfaces which give _____. | rise to adverse heeling moment | increase of stability due to heeling moment | increase heeling angle | increase of GM |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 1818 | If you are on duty and observe any situation which presents a safety or pollution hazard during fuel transfer operations what action should you take first? | Close the valves at the manifold | Close the valves at the manifold | Notify the person in charge from shore | Shut down the transfer operation |
| 1819 | The IMDG Code ensures safety mainly by stipulating the packaging required and _____. | maximizing the most available space | maximizing the load capacity | segregation from other cargoes with which there could be an adverse action | all answers are correct |
| 1820 | The main function of a stripping system is on _____. | maintain the temperature of the cargo | dispose of dangerous vapors within the cargo tanks | increase the loading rate of the shore side pumps | discharged liquid left in the cargo after the main pumps have discharged the bulk |
| 1821 | Ullages are measured from the_____. | above deck datum | bushing | Tank ceiling | thievage mark |
| 1822 | The stowage factor for cargo is based upon _____. | one short metric ton | one long ton | one short ton | one long metric ton |
| 1823 | To “shore up” the main deck for, the stowage of deck cargo means to _____. | package the cargo in wooden crates so that it will not damage the deck | distribute the weight of the cargo by placing fore & aft planks on the main deck | strengthen the main deck by placing pillars underneath it in the tween deck | weld pad eyes on deck in proper position to secure the cargo |
| 1824 | Which material should not be used to secure cargo on deck for a voyage? | Steel chain | Wire rope | Steel strapping | Fiber rope |
| 1825 | With a given load on the cargo hook, the thrust on a cargo boom _____. | is greatest at an angle of 45º and decreases as the boom is raised or lowered | increases as the angle to the horizontal increases | increases as the angle to the horizontal decreases | is least at an angle of 45º and increases as the boom is raised or lowered |
| 1826 | A vessel has an amidships superstructure. Which location would be most suitable for on-deck stowage of automobiles? | Beside the hatches, forward of the midships house | On top of # 1 hatch | On top of the hatch immediately forward of the midships house | On top of the hatch immediately aft of the midships house |
| 1827 | Your ship has been holed in amidships compartment and partially flooded. If flooded compartment has free communication with the sea, you should use which of the following method to calculate the effect of flooding on your stability. | lost buoyancy method | compartment standard method | added weight method | all answers are correct |

| | | | | | |
|---|---|---|---|---|---|
| 1828 | The securing systems for containers were developed to prevent container movement during which of the following ship motions? | Yaw | Sway | Roll | Surge |
| 1829 | The weight of the container and its contents is supported on deck by what parts? | Bottom side and end rails | Bottom flooring only | Bottom flooring and end panels | Four lower corner casting |
| 1830 | Under normal weather and sea conditions when securing a stack of containers with twist locks, lashing are required when the tier exceeds what height? | Two containers | One container | Three containers | Lashing are always required |
| 1831 | What group of refrigerated cargoes requires oxygen and gives off carbon dioxide while in storage? | Inert commodities | None of these | Living cargoes | Non-living organic cargoes |
| 1832 | When loading containers into the cell guides in the hold of a container ship, which statement is true? | Containers must have vertical lashings if they do not have twist lock securing | The container must be locked into the cell guide | All containers must have vertical and horizontal lashings | No further securing is usually required |
| 1833 | Which of the following is not an advantage of filler cargo? | Overcarriage is reduced or eliminated | Voids in the cargo stow are filled | Dunnage costs are reduced | The hold space has maximum utilization |
| 1834 | A heated bulkhead has the effect on a hygroscopic commodity of: | lowering the vapor pressure of the commodity | causing moisture to accumulate against the bulkhead | lowering the dew point of the air | raising the vapor pressure of the commodity |
| 1835 | How should the first layer of the dunnage be laid for loading of bagged cargo in the lower hold of a ship equipped with side bilges? | At an angle to the keel with the forward end outboard | At an angle to the keel with the forward end inboard | Diagonally across the entire hold | In a fore and aft pattern |
| 1836 | Of the general methods of stowing bagged cargo, which method will allow for maximum ventilation? | Full bag method | Cross tier method | Brick method | Half-bag method |
| 1837 | Which factor is the most important in preventing sweat damage within a cargo hold? | Dew of the outside atmosphere | Outside air temperature | Dew point of the cargo hold | Temperature of the cargo |
| 1838 | Damage to cargo caused by dust is known as _____. | tainting | oxidation | Vaporization | contamination |
| 1839 | The heaviest type pallet is the _____. | stevedoring pallet | Shipping pallet | warehouse pallet | factory pallet |

| | | | | | |
|---|---|---|---|---|---|
| 1840 | Which of the following is the main purpose of ventilating cargo holds? | To warm the cargo | To remove oxygen | To prevent ship's sweat | All of these |
| 1841 | Which data cannot be found on a moisture equilibrium chart? | Wet bulb temperature | Vapor Pressure | Dry bulb temperature | Moisture content |
| 1842 | What International Code Flag is hoisted to denote loading of flammable liquid is going on? | Hotel | Bravo | Zebra | Golf |
| 1843 | Which term describes a part of a natural fiber line? | Marline | Lays | Strands | Reeves |
| 1844 | Which of the following is an example of a fundamental objective of cargo stowage? | Load so that trim does not exceed 3' by the stern | Separate wet and dry cargoes into separate hold | Prevent over carriage by block stowage | Make maximum use of existing dunnages |
| 1845 | Where will the Master find the detailed guidance for proper precaution prior loading a explosive cargoes ? A. Carriage of dangerous goods in vessels B. IMDG code | Both choices is correct | B only | Neither A nor B | A only |
| 1846 | Strips of timber fixed to the frames of a vessel, either in horizontal or vertical direction, which keep cargo away from the sides of the vessel. | pallet | cargo battens | limber boards | dunnages |
| 1847 | Signal man assisting the crane operator has his arm extended downwards, forefinger pointing down and moves his hand in small horizontal circles. This is the signal to; | lower the load | lower swing load | lower boom | lower |
| 1848 | The signal man assisting the crane operator has his arm extended with the palm down and holds this position rigidly. This is the signal to _____ | stop | extend boom | emergency stop | retract boom |
| 1849 | Precaution/s to be taken to avoid spontaneous heating when bulk cargoes are carried in a general cargo vessel? | Lowering the dew point of the air | Ensure fitness and safety of cargo spaces | Raising the vapor pressure of the commodity | Proper ventilations and surveillance of temperature |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 1850 | The measurement from the tank top to the beams beneath the overhead and from sweat batten to sweat batten is called a vessel's _____. | Net cubic | Gross cubic | Bale cubic | Grain cubic |
| 1851 | The label on a package of an oxidizing hazardous material is___. | Green | Yellow | Red | White |
| 1852 | The REID vapor pressure is used for the classification of: | grade E liquids only | grade D liquids only | flammable liquids | Combustible liquids |
| 1853 | If a fruit or other strong smelling cargo has been carried in the compartment previously, it is necessary to ____. | wash and deodorize it | wash and dry it with clean cloth | wash and make it air dry | wash and load it with a different cargo |
| 1854 | In case of loss overboard of packaged of marine pollutants into the sea what must be done? | Immediately conduct retrieval operation then report to the owners | Report the incident by the fastest telecom channel to the CSO and wait for others | Report the incident by the fastest telecommunication channel to nearest coastal state | Report to the owners first then to the nearest coastal state |
| 1855 | On a reefer vessel, the compartment has been prepared and cooled to the loading temperature. This makes the vessel ready for _____. | the loading of reefer cargoes | ocular inspection by Port State inspections | Inspection of reefer | classification society surveyor to carry out a loading port survey |
| 1856 | What is the proper method of lashing cars? | Weight of the body supported, brakes on engine gear, wheels lashed | Wheels lashed, wheels choked, hand brakes engaged | Brakes on engine gear, wheels choked, body unit lashed | Body unit lashed, brakes engaged, wheels choked |
| 1857 | What is the usual carrying temperature of frozen cargoes? | 0º C | - 30º C | -10º or - 15º C | - 20º C |
| 1858 | When chilled meat is to be carried, the requisite number of metal bars, hooks and chains will have to be placed in the compartment for pre-cooling. What important concern would you look into regarding the hooks and chains? | It should have been wrapped in plastic before use | It should have been dried by a clean cloth | It should be checked for it's tensile strength | It should have been sterilized on shore |
| 1859 | When loading Frozen beef it is necessary to put ( 75mms x 75 mms) dunnage on decks and inserted every five or six tiers. What is the purpose? | To segregate cargo systematically | All of the choices are correct | To allow proper air circulation | To spread out the vertical pressure evenly from top to bottom |

| | | | | | |
|---|---|---|---|---|---|
| 1860 | One of the major advantage of the "load-on-top" system is that: | the cargo that was previously lost is recovered | multiple product ships can use it without contamination problem | discharge time is significantly reduced | corrosion within the cargo tanks is reduced |
| 1861 | A most important consideration in loading cardboard cartons is to keep the tiers ____. | dunnaged | staggered at different levels | straight and clean | level |
| 1862 | A port mark shows; | the name of the shipper | where the cargo is going | where the cargo is coming from | the name of the consignee |
| 1863 | A reel;I. Should be stowed on its side whenever possible II. If not possible to stow flat, stow it with its axis running athwartships | I and II | II only | I only | None of the above |
| 1864 | Mousing a cargo with marline or small line: | increase the lifting capacity of the hook | protects the hook from the sling ring | prevents undue strain on the sling ring | prevents the sling ring from coming out of the hook |
| 1865 | Open or partially opened hatches should not be: | provided handrails or stanchions | provided with warning sign | covered with tarpaulins | Lighted |
| 1866 | Proper stowage for cardboard cartons is _____: | brick fashion, with an upper carton resting on two cartons below it | where one carton rests directly on top of another | with the large cartons on the bottom and small ones on top | with small cartons placed on top of and inside the perimeter of the top of large cartons |
| 1867 | Segregating a cargo of finished lumber is best done by _____: | painting stripes across the different cargo blocks | chalk or a marking pen | wire and staples | laying rope yarns athwartship |
| 1868 | Shoring under a deck load is usually required when the deck load exceeds how many pounds per square foot? | 350 | 200 | 500 | 100 |
| 1869 | The pre-wash procedure for ships carrying non-solidifying substances which have a viscosity equal to or greater than 25 mPa at 20º C is hot water wash of at least: | 100º C | 80º C | 60º C | 120º C |
| 1870 | The tendency of flammable liquid to vaporize is indicated by its: | convection index | Flammable Range | ignition temperature | flash point |
| 1871 | What percent of cargo in international trade moves by container ship? | 75% or over | Under 50% | Under 75% | under 25% |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 1872 | Which of the following could result in an incorrect oxygen concentration reading on the oxygen indicator? | Exposure to carbon dioxide for no more than 1 minute | Exposure to a very low concentration of sulfur dioxide for no more than 2 minutes | None of the above | Exposure to carbon dioxide for more than 10 minutes |
| 1873 | You are loaded with bundles of steel from Yokohama to Manila. On passing Northern Luzon, the dew point of the ambient air was observed to be higher than the dew point inside the cargo hold, under this condition, should you ventilate? | No, because steel products do not require air | No sweat will form on the steel bundles | Yes, but only if the air is free of moisture | Yes, the hold should be ventilated vigorously |
| 1874 | "Long Hatch is; | a hatch over 13 meters in length | a hatch with a large opening to accommodate cargo such as pipe and railroad | a hatch whose length is the same as the length of the cargo hold | when disproportionate amount of cargo for one port is stowed under anyone hatch |
| 1875 | "Optional Cargo" refers to cargo that; | may be all or partly discharged at one or more ports | may or may not be carried | maybe carried either on deck or below deck | the shipper may substitute for another |
| 1876 | "Overstowing" cargo occurs when; | excess cargo must be stowed on deck | more cargo is accepted than the vessel can carry | one cargo prevents unloading another cargo and must be moved before unloading can continue | one commodity is stowed above another |
| 1877 | What is the weight of the product carried at 15 deg. Celsius? | Net | Gross | Absolute | Relative |
| 1878 | Overcarriage is best prevented by_____. | assuming heavy cargo is stowed low in the vessel | inspection of the hold at completion of discharge | stowing the cargo which is to be discharged last on the bottom | checking the vessel's load line calculation carefully |
| 1879 | A heated bulkhead has the effect on a hygroscopic commodity of_____. | lowering the vapor pressure of the commodity | lowering the dew point of the air | raising the vapor pressure of the commodity | causing moisture to accumulate against the bulkhead. |
| 1880 | What is NOT a problem when carrying coal? | The requirement for through-ventilation | Generation of machine gas | Spontaneous heating | The corrosion for some types of coal will cause to the ship |
| 1881 | In a general cargo ship, bales of LINEN or FABRIC should not be stowed together with sacks of TEA because: | tea could damage the fabric by tainting | tea could contaminate the linen | tea could damage the linen by staining | tea is a food item |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 1882 | Liquids that evaporate readily are known as_____ liquids. Any petroleum product with a flash point below 60º C is classed as: | Flammable | non- volatile | volatile | combustible |
| 1883 | You are to load styrene in bulk, which is subject to self-polymerization. You must _____. | be furnished with a Certificate of Inhibition to be maintained on the bridge | inject nitrogen to pad any ullage above the styrene to prevent contact with oxygen. | not carry any cargo in the tanks surrounding the tank loaded with styrene | use heating coils to maintain the styrene within the temperatures specified by the shipper. |
| 1884 | In grain loading computations at all times during a voyage, the ship shall have sufficient intact stability to provide adequate dynamic stability after taking into account the _____. | effect of draft limit | maximum loadable grain | fore and aft | adverse heeling moment |
| 1885 | To remove any odor on your cargo holds after discharging refrigerated cargoes, you should . | wash down with fresh water then spray with solution | thoroughly ventilate, spray with solution of ½ lb. of chloride of lime to 3 gallons of fresh water | wash down and thoroughly ventilate the hold | wash down with fresh water, before spraying with a solution |
| 1886 | The first layer of dunnage should be laid down _____, if you are to load a bagged cargo in lower hold of a ship with drain wells at the after end of the hold. | fore and aft | transversely | vertically | horizontally |
| 1887 | If you are loading fruit in reefer spaces and you notice that the fruit is beginning to mold, you should: | Carry the cargo at a cooler temperature than originally planned | Refuse to carry the cargo | Write up exceptions on the cargo | Discharge C02 into the compartment after loading |
| 1888 | When carried at a lower temperature than required, bananas are chilled. At higher temperature, they ripen. What is the carrying temperature of bananas? | 13.3º C | 14.3º C | 12.2º C | 11.3º C |
| 1889 | Which of the following could result in an incorrect oxygen concentration reading on the oxygen indicator? | Exposure to carbon dioxide for no more than 1 minute | Exposure to carbon dioxide for more than 10 minutes | Exposure to a very low concentration of sulfur dioxide for no more than 2 minutes | None of the above |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 1890 | To separate different kinds of bulk grain stowed in the same hold separation cloths should_____. | be laid tight between the cargoes | not be used | placed next to the cargo | be laid slack between the cargoes |
| 1891 | What is the frequent incidents of tanker pollution? | Loading and discharging | Grounding | Routine discharge of oil during ballasting | Collision |
| 1892 | When loading a cargo of taconite, proper sequencing of loading by hatch number is necessary to: | Prevent excessive longitudinal stresses | Prevent negative stability from developing | Provide proper trim | Control list |
| 1893 | Which of the following is the advantage of having a (COW) crude oil washing? | increased work load in port | an effective monitoring system | an effective monitoring system | reduction in time of passage tank cleaning |
| 1894 | "Optional Cargo" refers to cargo that; | may or may not be carried | the shipper may substitute for another | may be all or partly discharged at one or more ports | maybe carried either on deck or below deck |
| 1895 | You are planning to use crude oil washing system. What precaution must be taken with the tank as the source for the washing machines? | It must be de-bottomed and the level lowered by at least 1 meter | The oil in the source tank must be sampled for compatibility | The source tank must have been crude | All of these choices are correct |
| 1896 | What will happen if the flash point of kerosene which is 100 deg F be heated above 110 deg F? | boil off to atmosphere | burn and explode | less volatile and easier to handle | nothing |
| 1897 | Before a tank is crude oil washed, the oxygen content in the tank must be measured at a position: | At the top of the tank | In the vent riser | One meter from the deck | Immediately above the level of the oil |
| 1898 | To remove the effects of free communication flooding, it would usually be most advantageous to: | Completely flood off-center deep tanks | Completely flood high center tanks | Ballast double bottom wing tanks | Completely flood the forepeak tank |
| 1899 | Some cargoes are stowed in a secured place. They are known as "special cargoes". What does "special cargoes" means? | They are cargoes that contains hydrogen sulfide | These cargoes give off toxic gases when heated | Periodic inspection is required while in transit to prevent spoilage | They are of high value and easily pilferable |
| 1900 | For package freight, an average allowance for "broken stowage" is. | 0.15 | 0.3 | 0.6 | 0.05 |
| 1901 | Good left over at the completion of discharging operation which is eventually sold by the ship owner to meet claims for short delivery are called: | remnants | oddments | Residue | excess cargo |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 1902 | To facilitate faster discharging operation, each port of discharge is allocated a distinctive color mark. | color coding | Ship markings | port markings | cargo coding |
| 1903 | Actions to take once cargo has shifted include the following EXCEPT: | de-ballast the area where the cargo has shifted | alterations of course to reduce accelerations | re-stowing or reset during the cargo and, where possible, increasing the friction | reduction of speed to reduce accelerations and vibrations |
| 1904 | You are on a fully loaded tanker on a even keel. Which of the following actions would create the biggest trim by the head? | Shifting 500 tons from the forepeak to afterpeak tank | Removing 400 tons from the afterpeak tank | Adding 350 tons to the forepeak | Shifting 300 tons from the afterpeak tank |
| 1905 | When fumigation with sulfur is performed, what will be the minimum time required allotted for preparing the materials before fumigating? | 12 hours | 15 hours | 10 hours | 8 hours |
| 1906 | Which of the following is an example of a fundamental objective of cargo stowage? | Load so that trim does not exceed 3' by the stern | Separate wet and dry cargoes into separate hold | Prevent over carriage by block stowage | Make maximum use of existing dunnages |
| 1907 | A spreader bar is used in handling cargoes in container to _____. | protect the slings | protect the upper part of the load | increase the lifting radius | increase the lifting capacity |
| 1908 | How do you arrange a suitable system of ventilation for cargoes of copra assuming that the vessel is not fitted with a mechanical ventilation system ? | A. Raise corner hatches and trim all vents which should also be covered with mesh | Ventilate only when going from cold to warm weather | Good ventilation is not required | Ventilate only when going from warm to cold weather |
| 1909 | Which factor is not important when calculating the best use of the cubic capacity of a ship's hold? | The proper use of filler cargo | The choice of cargo to fit the hold | The skill of the longshoremen | The value of the cargo |
| 1910 | Which of the following could result in an incorrect oxygen concentration reading on the oxygen indicator? | Exposure to a very low concentration of sulfur dioxide for no more than 2 minutes | Exposure to carbon dioxide for more than 10 minutes | Exposure to carbon dioxide for no more than 1 minute | None of the above |
| 1911 | Which of the two systems used in cargo handling considers the prevention of damage to cargo from heat, fire and water damage? I. Cargo Securing II. Cargo Stowage | II only | I only | Both I and II | Neither I or II |

| | | | | | |
|---|---|---|---|---|---|
| 1912 | You have a quantity of bagged cargo to stow in a block in #3 UTD. Which stow will provide the maximum block stability: | Half-bagged cargo | Bilge and cantline | Alternate layer direction | Bag on bag cargo |
| 1913 | With respect to "Cargo Securing", which type of cargo is subject to the sea motion of roll, pitch and heave? I. Standardized Cargo II. Non-Standardized Cargo | I & II | II | I | Neither I nor II |
| 1914 | What percent of cargo in international trade moves by container ship? | Under 50% | Under 25% | Under 75% | 75% or over |
| 1915 | When the dew point of the outside air is lower than or equal to the dew point of the air in the cargo hold, you should: | not ventilate the cargo | energize the exhaust blowers | ventilate the cargo | energize the intake blowers |
| 1916 | On the fully containerized ship, approximately one third or more of the cargo is on deckabove the rolling center. Top stowed containers are subject to. | accelerations greater than on conventional vessels | accelerations the same as on conventional vessels | accelerations less than on conventional vessels | no accelerations |
| 1917 | A high cube container is designed specifically to _____. | stow cargoes with concentrated weights such as machinery | protect fragile cargoes | carry low density | carry cargoes of very low stowage factors |
| 1918 | Cargo holds is to be washed down after all cargo residue were put on deck. Likewise, holds floorings and bilges should be dried. A cloth is place around the bilges cover for protection to other cargoes to be loaded. | net | Canvass | synthetic cloth | burlap cloth |
| 1919 | A vessel is proceeding along the English Coast when it sprang a leak on the hull below the waterline. Efforts to patch her proved futile. It was added to ditch her to the nearest shoal. This is termed as: | beaching | stranding | Ditching | grounding |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 1920 | You are in a containership. Which of the following statements about the stowage of hazardous materials in containers is True? | A. The containers provide automatic segregation of hazardous materials except for class A explosives | refrigerated container with a fuel tank containing a flammable liquid must be stowed on deck | A. All packages within a container must be mark this end up to indicate correct | A. Package liquids within a container should be stowed on top of packages of solids to prevent crushing |
| 1921 | Which of the following STATEMENTS regarding fumigation is NOT TRUE? I. Personnel employed in opening hatches should wear respirators II. The area should be checked for gas concentration with reading recorded in the log. | I only | Both I and II | Neither I nor II | II only |
| 1922 | In stowing carboys of acid which are not completely boxed, what is the maximum tiers permitted? | Not more than 2 tiers | Not less than 2 tiers | At least 1 tier | Just 3 tiers |
| 1923 | You are to load a bagged cargo in the lower hold of a ship equipped with drain walls in the after end of the hold. The first layer of dunnage should be laid down; | Diagonally across the entire hold | At an angle to the keel, with the forward end inboard | In the fore and aft pattern | At an angle to the keel, with forward end outboard |
| 1924 | When loading a container vessel, the operation is basically that of a vertical loading. The important factors to be considered when loading containers is port of discharge: | Weight and refrigeration | Crushability and inherent vice | Sweat and weight | Available dunnage and chocking |
| 1925 | A cargo of refrigerated fruit is packed in crates with transverse members dividing the crate in two equal parts. Which of the following is TRUE? | The crates should NEVER be stowed brick fashion | A. The cargo block should stowed with air channels built throughout the stowage cargo. | A. The cargo block should be tightly packed if the cargo suitably chilled upon delivery to the vessel. | Both side of each crate must be checked for the temperature and the appearance of the fruit. |
| 1926 | Hygroscopic cargoes should be ventilated in cases when_____? | The dew point of the air in the hold is very low | The dew point of the outside air is greater than the dew point of the air in the hold | The outside dew point is 60°F and the cargo temperature is 54°F | Going from a warm to a cold climate |
| 1927 | What purpose does a bridge fitting serve when lashing containers? | Restrains the container against horizontal motion | Ties a container to the container below it | Ties a container stack to the deck | Restrain racking loads |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 1928 | On a vessel proceeding from a very cold to a warm climate with a cargo of a non-hygroscopic nature in the holds, which is TRUE? | Danger of heavy ship sweat exists; constant and vigorous ventilation is required | There is little danger of ship's sweat, slight possibility of cargo sweat; moderate ventilation is needed | There is danger of heavy cargo sweat if outside air is introduced by ventilation | The possibility of any sweat problem, either cargo or ship, is remote |
| 1929 | The Master should be provided with sufficient information on any heavy cargo offered for shipment. The information should at least include the following EXCEPT: | lifting points or slinging positions | exact weight | securing points, where provided, including details of their strength | bedding areas and particular bedding precautions if applicable |
| 1930 | The timber deck cargo should be secured throughout independent lashing spaced not more than _____ apart. | 3 meters | 2 meters | 4 meters | 1 meter |
| 1931 | Some coals may be liable to react with water and produce acids which may cause corrosion. An odorless gas much lighter than air and has flammable limit in air of 4% to 75 % by volume has bcause this reaction. | carbon monoxide | methane | hydrogen | carbon dioxide |
| 1932 | What purpose does a bridge fitting serve when lashing containers? | Ties a container stack to the deck | Ties a container to the container below it | Restrains racking loads | Restrains the container against horizontal motion |
| 1933 | Cargo transport units, including freight containers shall be loaded, stowed and secured throughout the voyage in accordance with the cargo securing manual approved by the _____. | administration | classification society | IMO | Organization |
| 1934 | After loading or discharging cargoes, ventilation of the cargo space may be necessary except: | dissipate gasses | accommodate taint | removed heat | remove taint |
| 1935 | The certificate of loading required by each vessel carrying grain in bulk is issued by the ____. | American Bureau of Shipping | Owner or charterer of the vessel | National Cargo Bureau | Shipper of the cargo |
| 1936 | The most accurate account of cargo will be found in the _____. | Portage bill | Charter party | Manifest | Bill of ladings |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 1937 | On a vessel proceeding from a very cold to a warm climate with a cargo of non-hygroscopic nature in the holds. Which is True? | There is danger of heavy cargo sweat if outside air is introduced by ventilation | Danger of heavy ship sweat exists | There is little danger of ship sweat, slight possibility of cargo sweat; moderate ventilation is needed | The possibility of sweat problem, either cargo or ship, is remote |
| 1938 | A survey of refrigerated cargo, to certify that proper methods of stowage were utilized, can be conducted by the _____. | U.S. Coast Guard | Safety and Health Administration | National Cargo Bureau | American Bureau of Shipping |
| 1939 | Of the general methods of stowing bagged cargo, which allows maximum ventilation? | Cross tier method | Full-bag method | Half-bag method | Brick method |
| 1940 | Which can be prevented only by segregating two lots of cargo into separate holds? | Contamination of a food cargo by an odorous cargo | Contamination of a clean cargo by a dirty cargo | Contamination of dry cargo by a wet cargo | Overcarriage, overstowage, and short landing |
| 1941 | Rice cargo emits what form of gas? | Oxygen | Methane | Carbon monoxide | Carbon dioxide |
| 1942 | The process of removing cargo residues in preparation for the next cargo. | Hold washing | Hold cleaning | Hold Sweeping | Residue disposal |
| 1943 | Measurement for tonnage and issue of an International tonnage certificate is the responsibility of: | Flag State | Port State | Classification Society | International Maritime Organization |
| 1944 | When transporting heavy lift cargoes at the time of loading, certain conditions must be required except: | what additional lifting equipments are required to handle the load | maximum load of each specific support points | technique of moving the load vertically | where may the lifting attachments be made on the load |
| 1945 | The principal hazards associated with coal which are of importance when shipping the commodity except: | The potential for ship sweat is extreme | The potential to emit methane | The potential for self heating in extreme case to ignition | The potential to cause corrosion to the ship's structure |
| 1946 | When pre-cooling the holds in preparation to receiving refrigerated cargoes, the hold temperature must be: | at constant temperature within 24 hours | slightly above carrying temp. within 24 hours | at zero temperature within 24 hours | slightly below carrying temp. within 24 hours |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 1947 | Some of the material listed in BC Code also appear in IMDG Code. The material may at times reduce oxygen content of a cargo space or are prone to self heating and one of these cargo is: | woodchips | ore | fertilizer | phospate |
| 1948 | A. A grain filled cargo compartment has a permeability of about _____. | 1 | 0 | 60-65 % | 80-85 % |
| 1949 | Where should you pay particular attention to be able to maintain adequate stability in loading deck cargo? | The cargo in the lower hold | The vertical distribution of the deck cargo | The horizontal distribution of the deck cargo | The under deck cargo |
| 1950 | Which of the following is FALSE regarding the carriage of containers on ships not designed to carry containers? | Containers carried on deck or on hatches should preferably be stowed in the fore-and-aft direction | Containers should be stowed and secured so as to permit safe access for personnel | Containers do not overstress the deck or hatches on which they are stowed | Containers should not extend over the ship's sides |
| 1951 | The main advantage of a unitized cargo system such as pre-sling, palletization, or containerization is: | cost reduction in terms of cargo operation | avoid shifting of cargo at sea | cleaner operation | all of these |
| 1952 | What action would you not take in case of a coal gas fire or explosion occurs? | isolate for ½ miles in all directions if tank is involved in fire | keep unnecessary people away from the explosion | isolate hazard area and deny entry | stay at the direction of the wind |
| 1953 | Because of the arrangement of the cell guides, the MOST important factor while loading containers is the ___. | Weight of the container | List of the vessel | Contents of the container | Size of the shore side crane |
| 1954 | How long is the standard container used to measure equivalent units? | 6 meters | 7 meters | 5 meters | 3 meters |
| 1955 | When commencing cargo operations on a container ship, one cell at a hatch is generally discharged completely (to the bottom of the ship) before removing any containers from the adjoining cells to: | Allow longshoremen easy access to the hatch | Initiate loading in conjunction with unloading at the hatch. | Remove an existing list that would slow cargo operations. | Improve stability during cargo operations. |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 1956 | The timber deck cargo should be secured throughout independent lashing spaced not more than _____ apart. | 4 meters | 1 meter | 3 meters | 2meters |
| 1957 | The damage caused by insects, mice or rats is: | vermin damage | contamination | tainting damage | pilferage |
| 1958 | How should grain cargoes be ventilated? | Do Not Ventilate | Ventilate vigorously | Surface ventilation | Through ventilation |
| 1959 | It is a close container with doors at one end and others with doors in one end and sides, sometimes ventilated but not insulated. | General cargo container | Dry bulk container | Close container | Thermal container |
| 1960 | It is the movement of moisture contained in materials by settling and consolidation of the materials due to vibration and ship's motion. | moisture laden cargo | moisture content | moisture migration | moist cargo |
| 1961 | It means a log which is "slab-cut" or ripped lengthwise so that the resulting thick pieces have two opposing, parallel flat sides. | pulpwood | lumber | poles | cant |
| 1962 | A “Heterogeneous cargo” refer to: I. A bulk carrier loaded with steel II. A bulk carrier loaded with heavy ore | Both I and II | II only | I only | Neither I nor II |
| 1963 | What is the term used when a cargo of the same density throughout? | bulk cargoes other than grain | Homogeneous cargo | Grain cargo | Heterogeneous cargo |
| 1964 | Ship's officers should check every cargo compartment after it is filled with bulk grain to ensure _____. | The correct grade of cargo has been loaded | All lighting circuits are energized | The heavier grade of cargo is in the lower hold | All void spaces are filled |
| 1965 | A high cube container is often used to stow which of the following? | household appliances | dense bulk cargoes | fragile and breakable cargoes | industrial machineries |
| 1966 | A cargo compartment filled with grain has a permeability of about: | 1 | 0 | 80-85% | 60-85% |
| 1967 | This type of container is used transporting large, shapeless, or break bulk cargoes such as large machinery, pipes, vehicles etc. | Dry bulk container | Special container | Thermal container | General cargo container |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 1968 | Materials which at least contain some fine particles and some moisture, usually water,although they need not be visibly wet in appearance are called: | Cargoes which may liquefy | Wet cargoes | Flow state | Concentrates |
| 1969 | In containerization, what is meant by "Stuffing"? | putting bales of cotton in a container | placing foodstuffs in a tight container | unloading good inside a freight container | stowing good inside a freight container |
| 1970 | What type of a bulk carrier that has high freeboard and equipped with its own unloading equipments? | Cement Carrier | wood chip carrier | iron ore carrier | coal carrier |
| 1971 | On the fully containerized ship, approximately one-third or more of the cargo is on deck above the rolling center. Top stowed containers are subject to _____. | accelerations less than on conventional vessels | accelerations the same as on conventional vessels | accelerations greater than on conventional vessels | no accelerations |
| 1972 | It means a vehicle, container, flat, pallet, portable tank, packaged unit, or any other entity: | Hold unit | Cargo stowage unit | Cargo unit | Stowage unit |
| 1973 | The term use to denote a quality of change in some cargoes which damages the commodity itself is known as _____. | Tainting | Inherent vice | Deterioration | A latent defect |
| 1974 | How many emergency towing arrangement is required for tankers not less than 20000 tonnes deadweight? | 1 | 2 | 3 | 4 |
| 1975 | Intermediate bulk container means a rigid, semi rigid or flexible portable bulk container packaging of not more than _____ cubic meter? | 3 | 1 | 5 | 7 |
| 1976 | The angle of heel due to shift of the grain shall not be greater than: | 10 degrees | 5 degrees | 15 degrees | 12 degrees |
| 1977 | All lashings and components used for securing should possess a breaking strength of not less than: | 183Kn | 133 Kn | 123 Kn | 153 Kn |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 1978 | All lashings used for the securing of timber shall be tested by a competent person to determine whether they, in the case of flexible steel wire ropes, are at least _____ in diameter. | 16 mm | 0.16 mm | 160 mm | 0.016 mm |
| 1979 | The fresh water allowance being 6" for vessel M/V "DENSAN". What is the increase of draft allowed in water of 1010-oz density? | 2.5" | 3.5" | 3.0" | 2.0" |
| 1980 | What is the measurement of a standard shipping container that are specified by the International Standards Organization(ISO)? | 20 ft x 8 ft | 20 ft x 9.5 ft | 20 ft x 8.5 ft | 20 ft x 9 ft |
| 1981 | How many emergency towing arrangement is required for tankers not less than 20000 tonnes deadweight? | 2 | 4 | 1 | 3 |
| 1982 | Intermediate bulk container means a rigid, semi rigid or flexible portable bulk container packaging of not more than _____ cubic meter? | 7 | 3 | 5 | 1 |
| 1983 | The angle of heel due to shift of the grain shall not be greater than: | 15 degrees | 10 degrees | 5 degrees | 12 degrees |
| 1984 | All lashings and components used for securing should possess a breaking strength of not less than: | 133 Kn | 183Kn | 153 Kn | 123 Kn |
| 1985 | All lashings used for the securing of timber shall be tested by a competent person to determine whether they, in the case of flexible steel wire ropes, are at least _____ in diameter. | 0.016 mm | 160 mm | 0.16 mm | 16 mm |
| 1986 | What is the measurement of a standard shipping container that are specified by the International Standards Organization(ISO)? | 20 ft x 8.5 ft | 20 ft x 8 ft | 20 ft x 9.5 ft | 20 ft x 9 ft |

NOT FOR SALE

# OIC NAVIGATIONAL WATCH

| | | | | | |
|---|---|---|---|---|---|
| 1987 | About how many degrees does the optimum lashing angle against tipping it? | 30-45 degrees | 60-75 degrees | 45-60 degrees | 55-70 degrees |
| 1988 | Light poles of varying length: | Shooks | Wood-goods, Lights | Slats | Boards |
| 1989 | In a fixed hopper type of chip unloading equipment, what is the part in the system that conveys the wood chips to the main conveyor? | Feeder conveyor | Orange peel bucket | Shuttle conveyor | Hopper |
| 1990 | The stripping bell mouth on a tanker is usually placed: | about two inches below the bottom of a tank | on deck to strip off oil spills | six meters from the tank top inside the tank | about two inches above the bottom of a tank |
| 1991 | This type of container is used for bulk liquid, and compressed gas. | general cargo | tank container | special | thermal |
| 1992 | A ship designed to carry either oil or solid cargoes in bulk is known as: | combination carrier | general cargo vessel | special vessel | multi-purpose vessel |
| 1993 | What is meant by the term "topping the boom"? | Spotting the boom over the deck | Swinging the boom athwartships | Raising the boom | Lowering the boom |
| 1994 | A cargo that has a stowage factor over 40 is known as a: | Hygroscopic cargo | Measurement cargo | Weight cargo | Stowage cargo |
| 1995 | Designed to deliver water under high water pressure in rotating stream which are through every possible angle. | Booster Pump | Centrifugal pump | Stripping pump | Emergency pump |
| 1996 | These valves are normally situated near the bottom shell and are use to control intake and discharge of ballast water. | overboard discharge valves | discharge valves | suction valves | sea valves |
| 1997 | A vessel's stability is greatly reduced by liquid free surface. Which of the listed conditions would develop the greatest adverse effect? | Tanks which are 95% full. | Tanks which have been completely emptied. | Tanks which are 40% full. | Tanks which have been pressed up to full capacity. |
| 1998 | The best way to determine if a load is within maximum lift limits is to use: | a load weight indicator | prior experience with similar lifts | a boom angle indicator | material invoices for shipping weights |
| 1999 | What is the volume of a tank which can hold 1000 kilograms of fresh water? | six cubic meters | three cubic meters | ten cubic meters | one cubic meter |
| 2000 | A vessel with a large GM will: | have a small amplitude of roll in heavy weather | be subject to severe racking stresses | tend to ship water on deck in heavy weather | be less likely to have cargo shift |

# OIC NAVIGATIONAL WATCH

# OIC NAVIGATIONAL WATCH

| | | | | | |
|---|---|---|---|---|---|
| 2001 | A vessel loaded with steel coils is coming from Panama to Vancouver. On passing North California, the holds were ventilated. What happens under these circumstances? | No cargo sweat will occur | Cargo sweat will occur in the hold | The cargo will partly experience sweat | Amount of dew will increase |
| 2002 | A vessel continually lists to one side and has a normal rolling period. Which statement is TRUE? | The vessel has negative GM | The list can be corrected by reducing KM | The vessel has asymmetrical weight distribution | The center of gravity is on the centerline |
| 2003 | If a hydraulic pump on a winch accidentally stops while hoisting, the load will stay suspended because: | the electric pump motor will cut out | a check valve will close and prevent reverse circulation | the control lever will move to the stop position | a centrifugal counterweight counteracts the force of gravity |
| 2004 | Ullages are measured from: | an above deck datum | the tank top bushing | the thievage mark | the tank ceiling |
| 2005 | Name the three most common energy forms. | The three most common energy forms are temperature, pressure and electrical energy | The three most common energy forms are mechanical energy, chemical energy and electrical energy | The three most common energy forms are speed energy, rolling energy and electrical energy | The three most common energy forms are mass energy, physical energy and electrical energy |
| 2006 | An adverse effects due to free surface? | The vessel's draft increases this increasing the vessel's water plane area | The vessel's is draft is decreased exposing more surface are to the wind and current | A portion of the liquid is removed from a full tanks | The vessel is trimmed by the stern |
| 2007 | Adverse effects due to free surface will become apparent when: | a portion of liquid is removed from a full tank | the vessel is trimmed by the stern | the vessel's draft is decreased exposing more surface area to the wind and current | the vessel's draft is increased, thus increasing the vessel's wetted surface area |
| 2008 | How should coal cargoes be ventilated? | Surface ventilation | Through ventilation | Do not ventilate | Ventilate vigorously |
| 2009 | In the stowage of deck cargo. | The chains and shackles used to secure a deck cargo | A container or box where a deck cargo is packaged | A cardboard separation piece in the deck loads to prevent chaffing | Wooden blocks or dunnage place between a deck load and the deck |
| 2010 | A half-height container is used: | when stowage space is limited | to carry cargoes such as steel products or drums | to carry cargoes of low density | to double the stowage capacity of the vessel |
| 2011 | In Container Identification System, the Equipment Category Identifier represented by Capital letter "J" in Latin Alphabet means: | all freight containers | trailers and chassis | detachable freight container-related equipment | All of the choices |

# OIC NAVIGATIONAL WATCH

| | | | | | |
|---|---|---|---|---|---|
| 2012 | A vessel subject to sagging has what condition? | Bottom plating under tensile stress | Main deck under tensile stress | Transverse bending | Superstructure under tensile stress |
| 2013 | The unused volume between the surface of the liquid and the tank top of any cargo tank is _____? | Outage | Tankage | Innage | Ullage |
| 2014 | All of the following steps are taken in starting a centrifugal pump, EXCEPT to: | check the lubrication system | vent the pump casing | open the pump suction and discharge valves | set the relief valve |
| 2015 | How would you ventilate your cargo holds when sailing from cold climate to hot climate? | Ventilate at intervals during the night | No ventilation should be done | Ventilate at intervals during the day | Ventilate excessively |
| 2016 | In what kind of atmosphere should tank washing be carried out when no inert gas plant is in operation? | Too lean ( less than 2% by volume of hydrocarbons) or over rich ( in excess of 15% by volume of hydrocarbons ) | After having send a man down in the tank to check that there is no more oil left | Ventilate the tank up to 21% oxygen | After having aired the tank for at least 24 hours |
| 2017 | A term use onboard ship meaning, the process of replacing foul air in any of the ship's compartment with pure air. | Ventilating | Refrigerating | Purging | Purifying |
| 2018 | A volume multiplied by a distance cannot exert a force but, a volume of space divided by the Stowage Factor of the commodity which fills that space, equals a: | Length | Grain Heeling Moment | Volumetric Moment | Weight |
| 2019 | What is the meaning of "Slop Tank" as per Marpol? | A tank specifically designed for the collection of tank drainings, washings or other oily mixtures | Any tank where slops sludge's are collected | A tank used for tank cleaning provided with heat coils | The two most aftward fitted wing tanks or the most aftward fitted center tank |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 2020 | Sawn timber not less than 50 mm thick and 230 mm or 250 mm wide. A Petrograd "Standard Deal" is 1 piece, 75 mm x 280 mm x 1,830 mm. A "Slit-deal" is 30 mm thick. A "Whole deal" is 15 mm thick. A "Hundred deals" = 120 pieces, 150 mm x 75 mm x 280 mm x 165 cu.ft. | Baulks | Waney Timber | Deals | Baulks |
| 2021 | After loading operation, what is done to ensure the watertightness of the hatch cover during closing? | trimming all around the panel and coaming | air blowing all around the panel and coaming | washing all around the panel and coaming | sweeping all around the panel and coaming |
| 2022 | After you have washed the arrival ballast tanks, what is extremely important to do properly before arrival ballast is pumped into the arrival ballast tanks? | Washing just the lines properly. | Nothing in particular, just pump in. | To wash all lines and pumps properly. | To flush the pumps properly. |
| 2023 | Air gap' is the vertical distance between the bottom of the hull and the: | After you have washed the arrival ballast tanks, what is extremely important to do properly before arrival ballast is pumped into the arrival ballast tanks? | wave crest | wave crest plus the charted water depth and tidal corrections | wave crest plus the charted water depth, plus tidal correction and storm surge |
| 2024 | One ton per cubic meter refers to which of the following? | weight | specific gravity | mass density | specific volume |
| 2025 | The latch of a safety hook: | increases the strength of the hook | adds strength to the hook and other rigging | prevents the sling ring from coming out of the hook if there is a strain on the sling ring | prevents the sling ring from coming out of the hook if the strain is abruptly eased |
| 2026 | A vessel's bottom will be subjected to tension when weight is concentrated: | Amidships | forward | aft | at both ends of the vessel |
| 2027 | In Container Identification System, the Equipment Category Identifier represented by Capital letter "Z" in Latin Alphabet means: | all freight containers | detachable freight container-related equipment | All of the choices | trailers and chassis |

OIC NAVIGATIONAL WATCH

| | | | | | |
|---|---|---|---|---|---|
| 2028 | After it is filled with bulk grain, ship officers should check every cargo to ensure: | All the choices | All void spaces are filled | The correct cargo has been loaded | All lighting circuits are energized |
| 2029 | A shipboard oil pollution emergency plan (SOPEP) is required to which of the following? | an oil tanker of 150 gross tons or above, or other ship of 400 gross tons or above | all vessels, regardless of size and commercial application | any barge or other ship which is constructed or operated in such a manner that no oil in any form can be carried aboard | an oil tanker of 400 gross tons and above, or other ships of 150 gross tons and above |
| 2030 | A colorless gas with high carbon content, lighter than air with chemical formula of C2H2. | Acetone | Argon | Astatine | Acetylene |
| 2031 | A tackle is "two blocked" when the blocks are: | equally sharing the load | as far apart as possible | jammed together | rove to the highest mechanical advantage |
| 2032 | Sawn timber 50 mm thick and under, any width. Above 150 mm stow at 230/240 cu. Ft per Standard and 250/260 cu. Ft below 150 mm thick. | Boards | Baulks | Baulks | Waney Timber |
| 2033 | It is defined as a black solid residue, obtained mainly by cracking and carbonizing of residue feedstock, far and pitches in processes such as delayed coking or fluid coking. | Bitumen | Industrial Spirit | Petroleum Coke | White Spirit |
| 2034 | It is defined as non-condensable gas obtained during distillation of crude oil or treatment of oil products. | Industrial Spirit | Refinery gas | Bitumen | Naphtha |
| 2035 | To lay between tiers of green fruit or cartons of refrigerated cargo so as to assist in the circulation of air. Maybe of wood or polystyrene. Usually 9 mm (3/8") thick, 25mm or 50 mm (1' to 2") in width. | Laths | Hardboard | Boards | Dunnage |
| 2036 | Binder chains used to lash down deck cargo may be shortened by ? | bolting two links together | load binders or turnbuckles | Knotting | wiring, welding and pelican hooks |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 2037 | A venetian vent or rice ventilator is used in stowage of which cargo? | Refrigerated goods | Bulk grain | Bagged cargo | Bulk rice |
| 2038 | A wet cargo refers to: | Liquids in containers | A cargo that will be damaged if it gets wet | Bulk liquids | Cargoes that will cause condensation |
| 2039 | When loading bulk liquid cargo, what is the first action you should take if a cargo valve jammed open? | call the Master | Order the dock man to shut down | Call the owner, operator, or terminal supervisor | fix it immediately |
| 2040 | After a partial discharge and prior to sailing, it is important to: | redo the cargo plan | thoroughly ventilate | carry out a cargo survey | secure and shore the remaining cargo |
| 2041 | A noxious liquid substance which, if discharged into the sea from tank cleaning or deballasting operations, are deemed to present a minor hazard to either marine resources or human health. What is this category? | Category Z | Category A | Category X | Category Y |
| 2042 | A pipe to convey water from the pump discharge through the ship's side. | Centrifugal Pump | Centripetal Pump | Pump Dale | International Shore Connection |
| 2043 | The best way to ensure whether adequate oxygen is present for safe entry into a seldomly used cargo tank is: | Check for rust inside the tank | Open the air vent prior to entry | Test tank atmosphere using a combustible gas indicator | Ventilate the tank with fresh air and test with an oxygen indicator |
| 2044 | Of 50 mm x 50 mm (2" x 2") or 76 mm x 76 mm (3" x 3") used largely with refrigerated cargo. | Battens | Hardboard | Chipboard | Laths |
| 2045 | If the overflow tank high-level alarm sounds while the fuel oil tanks are being topped off, the engineer should: | close the overflow tank filling valve | close the static leg filling valve | reduce the fuel oil pumping rate | stop the fuel oil pumping operation |
| 2046 | Which of the following gas tankers is capable of carrying methane? | Chemical Gas Tanker | LNG | CNG | LPG |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 2047 | Generally of rough 150 mm x 25 mm (6" x 1") or 100 mm x 50 mm (4" x 2"); large used for 'tween deck dunnage, for laying over bulk and as a platform for the necessary tiers of bags to secure same, for making a platform over ores, wet goods such as oil barrels, jaggery, etc.; also for laying on bulkheads, spar ceiling, etc. | Boards | Battens | Coir | Bones |
| 2048 | The following are characteristics of Paraffin waxes, EXCEPT: | Odorless | Colorless | Melting Point below 45o C | Translucent |
| 2049 | During the entire voyage, the best way to prevent cargo from sweating or accumulation of: | Appropriate cover | Blow dry | Constant wiping | Proper ventilation |
| 2050 | An area clearly designated and set aside for the loading/unloading of containers to and from road transport vehicle using any of the various types of container lifting equipment. | Grid | Greed | Container Terminal | Special Area |
| 2051 | A type of vessel used for rapid loading and discharging cargo of trailer, automobile, odd shaped and other conventional cargo. | General cargo vessel | Container vessel | Ro-ro vessel | Car carrier vessel |
| 2052 | A thermal container with refrigerating appliances (mechanical compressor unit, absorption unit, etc.) to control the temperature of cargo. | Palletwide Container | Fully Refrigerated Cellular Container | Conventional Container | Reefer Container |
| 2053 | On an OBO or O/O carrier one frequently finds electrical sockets and switches on deck for use of lighting and other electrical apparatus when operating in the dry cargo mode. Before loading oil these should be: | Electrically isolated by special isolating switchboxes in the accommodation and the keys of these retained by a responsible officer? | Switched off locally on deck? | Covered securely with covers made of an electrically insulating material? | Hung with warning signs that they should not be used during the carriage of oil? |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 2054 | Cargo pump relief valves are piped to the: | atmosphere through pump vents | suction side of pumps | cargo pump pressure gauges | crossover lines interconnecting two pumps |
| 2055 | What type of line melts easiest? | Wire | Dacron | Polypropylene | Nylon |
| 2056 | The instrument that measures the density of any liquid is called a: | Hydrometer | Anemometer | Densometer | Manometer |
| 2057 | In Container Identification System, the Equipment Category Identifier represented by Capital letter "U" in Latin Alphabet means: | trailers and chassis | detachable freight container-related equipment | All of the choices | all freight containers |
| 2058 | A vessel loading cargo at the anchorage suddenly takes a list to port due to the center of gravity rising above the metacenter. Which of the following is the best action to correct the list? | Discharge a full portside wing tank | Discharge a center double bottom tank | Discharge a full double bottom tank on the portside. | None of these |
| 2059 | An acceptable method of dealing with accumulated oil found in the pump room bilges is to: | pump the oil into the slop tanks | transfer the oil to the sea chest | discharge the oil over the side on an outgoing tide | pump the oil into a clean ballast tank |
| 2060 | After loading of the stability requirements, the master shall ensure that the ship is _____ before proceeding to sea. | environmentally safe | seaworthy | upright | documented |
| 2061 | Cargo holds must be dry and free from dirt and foul odor, what must be determined when inspecting cargo holds before taking any cargo? | Watertight integrity | Ballast condition | Draft | All choices |
| 2062 | On board cargo ships, what is the most common type of dunnage used? | hard planks | soft planks | cotton wood | fiber wood |
| 2063 | A large heavy beam of timber - hewn or sawn. | Deals | Flooring | Laths | Baulks |
| 2064 | What is a wooden fid used for? | to pick up a strand and open rope to allow tucking | for hammering rope to make more liable | for cutting strand ends | none of these |
| 2065 | A type of ventilation where the flow of air is controlled by the proper trimming of ventilation. | Natural ventilation | Mechanical ventilation | Dehumidifier | Free flowing ventilation |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 2066 | What is an advantage of the 6 x 19 class of wire rope over the 6 x 37 class of wire rope of the same diameter? | More resistance to elongation | Better for towing | More resistance to corrosion | Greater holding power |
| 2067 | A vessel which is subjected to 'hogging': | has its main deck plating under tensile stress | has its main deck under compressive stress | has its bottom plate under tensile stress | has its bottom plating under ductile stress |
| 2068 | Holding a metal at a constant temperature for a specified time is called: | hardening | soaking | tempering | heating |
| 2069 | The movement of the crane that is not controlled by any wires is: | Lowering Operation | Hoisting Operation | Luffing Operation | Slewing Operation |
| 2070 | Development of molds on reefer cargo inside a refrigerated cargo hold is most likely caused by _____? | pre-cooling of holds not correctly attained | cargo not having the correct temperature | holds not properly cleaned prior to loading cargo | malfunction of the refrigeration machinery |
| 2071 | A moment is: I. A weight. II. A distance | II | Neither I nor II | Either I or II | I |
| 2072 | The definition of board feet is: I. The number of square feet of planking 1 inch in thickness II. The volume of the lumber multiplied by 12. | II only | I only | Both I and II | Neither I nor II |
| 2073 | Addition of weight to a vessel will ALWAYS: | reduce reserve buoyancy | increase GM | increase righting moments | All of the above |
| 2074 | As the beam of a vessel for a given length increases, it is apparent that directional stability: | Decreases | Increases | Remains the same | Accelerates |
| 2075 | Damage caused by excessive heating within the cargo is classified as: | Crushing damage | Tainting damage | Vermin damage | Inherent vice damage |
| 2076 | Before a motor vehicle that is carrying dangerous goods classified as Class I in the IMDG Code and is to be stowed under deck or towed on and off a closed vehicle deck, the vessel's master shall ensure that: | Its engine stopped | its ignition is switched off | its fuel tank not drain | its battery terminals connected and not taped |
| 2077 | The difference between the height of the metacenter and the height of the center of gravity is: | KB | KG | GM | KM |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 2078 | A thick wooden block built to take a rope whose circumference is half the length of the block? | Klamp block | Clam block | Clamp block | Clump block |
| 2079 | An absolute necessity for proper stowage of break bulk cargo and, when cargo damage occurs, may result in allegations of bad stowage by cargo claims being difficult to refute. | Dunnaging | Shoring | Lashing | Timbering |
| 2080 | Under identical load conditions, nylon, when compared with natural fiber line, will stretch: | less and have greater strength | more and have less strength | more and have greater strength | less and have less strength |
| 2081 | Adding weight on one side of a floating vessel, in the absence of external forces, causes the vessel to: | List to the side opposite TCG until all moments are equal | List until the center of buoyancy is aligned vertically with the center of gravity | Decrease the draft at the center of floatation | Heel until the angle of loll is reached |
| 2082 | An electro hydraulic grapple for handling logs in bundle. It grips only the uppermost logs in the bundle and is unaffected by submersion in the water. | Log slings | Log grab | Log lift | Log grapple |
| 2083 | Automatic shutdown of the inert gas blowers and gas regulating valve shall be arranged in case of faulty condition in the inert gas system. Which of the following conditions has not correct value (high/low) in relation to automatic stop according to present regulation? | High water level in the water seal | Low water level in the water seal | Low water pressure or low water flow rate to the flue gas scrubber | High water level in the flue gas scrubber |
| 2084 | The load chart of a crane enables the operator to combine the load radius with boom length to determine the: | hoist rope strength | maximum counter weight required | minimum horsepower required | allowable load |
| 2085 | For tankers of 20000 but less than 50000 tonnes deadweight, what should be the strength of the emergency towing arrangement? | at least 2000 kN | at least 1000 kN | more than 2000 kN | more than 1000 kN |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 2086 | For tankers of over 50,000 deadweight, what should be the strength of the emergency towing arrangement? | more than 2000 kN | at least 1000 kN | more than 1000 kN | at least 2000 kN |
| 2087 | The maximum draft to which a vessel can legally be submerged is indicated by the: | Certificate of Inspection | tonnage mark | load line mark | Muster List ("Station Bill") |
| 2088 | On the cargo manifest, the total weight of a box containing cargo is the: | net weight | gross weight | tare weight | cargo weight |
| 2089 | It is an inexact unit of cargo capacity often used to describe the capacity of container ships and container terminals. | TEU | Tare weight | Net Weight | Gross Weight |
| 2090 | A vessel that has a concentration of weight toward the top of the vessel is said to be: | Neutral | Stiff | Buoyant | Tender |
| 2091 | Which is the lowest temperature at which the liquid will flow when cooled under prescribed condition? | Newtonian flow | Pour point | Pumpability | Cloud point |
| 2092 | During the STS operations while underway, the following signals from the IMO's Collision Regulations must be displayed by both ships. | signals for vessels restricted in their ability to maneuver | no special signal required | signals for vessel not under command | signals for vessels towing |
| 2093 | Does a vessel's trim has any influence on steering abilities? | No, it is usually best to have no trim at all | Yes, the vessel usually steer better if trimmed by the stern | Yes, a vessel usually steer better if trimmed by the bow | No, the vessel will have the same steering ability unaffected by trim |
| 2094 | What is the meaning of "Harmful Substances" under Marpol? | Oils and Fuels | Petroleum products and petrochemicals | Any substances creating harm to health and life or able to damage amenities | Hydrocarbons in any form |
| 2095 | How often should the temperature inside the compartment with refrigerated cargo be checked and recorded? | Once in each four-hourly watch | Twice a day | Once a day | Every six hour |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 2096 | All gas carriers, when the design temperature is below -55 degrees C and the tank is not independent type C, what ballast tanks must we have? | top sided | open sided | wall sided | After you have washed the arrival ballast tanks, what is extremely important to do properly before arrival ballast is pumped into the arrival ballast tanks? |
| 2097 | Also called insulated or CONAIR containers, do not have their own refrigeration unit and thus reliant on an external supply of cold air. | porthole container | open-sided container | open-roof container | open-top container |
| 2098 | Any square, round, waney or other timber, or any pitch pine, mahogany, oak, teak or other heavy wood-goods, Whatever? | Pickets | Wood-goods, Heavy | Wood-goods, Lights | Boards |
| 2099 | This expression applies to the more valuable classes of timber, such as oak, mahogany, beech, whitewood, etc., used in the furniture and allied trades. | Prime-wood | Slats | Pit-props | Boards |
| 2100 | It is defined as the remnants of any cargo materials on board that cannot be placed in proper cargo holds and elsewhere after unloading operation is completed: | waste | cargo residues | oil residues | plastic residues |
| 2101 | Your vessel has been loaded in a sagging condition. Enroute you encounter heavy weather and notice buckling in the midship deck plating of your vessel. To relieve the strain you could: | Reduce speed | Pump in ballast in the center tanks | Pump out ballast in the peak tanks | Proceed to the nearest port |
| 2102 | The difference between the height of the metacenter and the metacentric height is termed: | height of the center of buoyancy | height of the center of gravity | metacentric radius | righting arm |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 2103 | After unloading of wood chips go through dust _____ to remove foreign matters before entering a pulp plant from a stockyard. | none of the choices | Screens | strainers | mesh |
| 2104 | Which is CORRECT to claims in respect of expenses incurred or sacrifice made by the owner voluntarily to prevent pollution damage? | shall rank more than half of other claims against the fund | shall rank at least two thirds of other claims against the fund | shall rank equally with other claims against the fund | shall rank one third of the total amount claims |
| 2105 | Result of two forces acting in opposite directions on the same line. | Compression Stress | Tension Stress | Sheer Stress | Structural Stress |
| 2106 | Argon is classified as a: | flammable liquid | alcohol | D flammable liquid | flammable gas |
| 2107 | Barium cyanide solid is classed as "poison B" and cannot be stowed near: | flammable solid | above 80deg. F but below 150deg. F | Flammable liquids | Flammable solids |
| 2108 | What is the required gas supply capacity of an inert gas system? | 125% of fan capacity | 125% of forced draft rate | 125% of cargo pump capacity | 125% of shore side loading rate |
| 2109 | What is the temperature at which a vapor mixture at a given pressure begins to condense? | dew point | boiling point | critical point | bubble point |
| 2110 | What normally helps in detecting escaping gas? | Running hand along pipe | Odor | Increase the line pressure | Red flame |
| 2111 | What should be the first consideration when discharging an oil cargo? | discharge from the wings first | discharge from amidships first | get the bow up | discharge from the centerline tanks first |
| 2112 | What should you do to a line to prevent fraying where it passes over the side of the vessel? | Install a cleat. | Splice that part of the line. | Worm that part of the line. | Cover it with chafing gear. |
| 2113 | What would have the greatest affect on a vessels longitudinal strength? | Grounding damage to the bilge strake just aft of midships | Damage to the side shell midway between the bilge and the stringer plate | Extensive corrosion to the centerline deck plating | Collision damage to the bow forward of the collision bulkhead |
| 2114 | When checking down a barge using a check line you should use _____. | one round turn and at least two figure-eights around the timber heads | at least three round turns around one timber head | at least three figure-eights around the timber heads | a clove hitch around one timber head |
| 2115 | When a wind force causes a vessel to heel to a static angle the _____. | centers of buoyancy and gravity are in the same vertical line | deck-edge immersion occurs | righting moment equals the wind-heeling moment | center of buoyancy remains the same |

| | | | | | |
|---|---|---|---|---|---|
| 2116 | When cargo is shifted from the lower hold to the main deck the _____. | All of the above | center of gravity will move upwards | GM will increase | center of buoyancy will move downward |
| 2117 | When discharging an oil cargo the first consideration is to _____. | get the bow up | discharge from the wings first | discharge from the centerline tanks first | discharge from amidships first |
| 2118 | When discharging cargo from a tank barge in which case may the cargo pass through or over the towing vessel? | With permission from the person in charge of the towing vessel | With permission from the person in charge of the shore facility | When off-loading grade C cargo | In no case |
| 2119 | When lifting loads from a boat in heavy weather the load should be taken when the boat _____. | reaches the crest | reaches the trough | begins to fall | begins to rise |
| 2120 | When loading or discharging dry mud or cement crew members should use facial respirator masks and _____. | ear plugs | goggles | firemans outfit | soft-soled boots |
| 2121 | When passing a hawser to the dock you would first use what line? | Warp | Preventer | Gantline | Heaving line |
| 2122 | When paying out nylon line from around the bitts _____. | no extra turns are necessary since nylon has a high coefficient of friction | you can surge the line even with a single turn | stand clear of the bitts and use two or more round turns under your figure eights | stand in the bight of the line |
| 2123 | When stripping a tank excessive air in the suction line may cause _____. | an over pressurized line | loss of suction | increase of suction | back pressure |
| 2124 | When taking a length of new manila rope from the coil you should _____. | roll the coil along the deck and allow the rope to fall off the coil | lay the coil on end with the inside end up then unwind the rope from the outside of the coil | lay the coil on end with the inside end down then pull the inside end up through the middle of the coil | mount the coil so it will turn like a spool and unreel from the outside |
| 2125 | When the forward drafts and the after drafts are averaged which of the following describes the result? | true mean draft | mean draft | mean of the calculated drafts | draft at the center of flotation |
| 2126 | When working with wire rope which must be considered? | The diameter of a sheave over which a rope is worked should be ten times that of the rope. | It should be lubricated annually. | Metal sheaves should be lined with wood or leather. | It needs better care than hemp or manila. |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 2127 | Where are ullages measured from? | an above deck datum | the tank ceiling | the thievage mark | the tank top bushing |
| 2128 | Which action must be taken when an individual cargo tank is closed off from the inert gas system by the tank isolation valve? | The bypass valve must also be closed. | The tank must be vented to the atmosphere. | The tank must be ballasted. | The tank must be gas freed. |
| 2129 | Which cargo is considered volatile? | Bunker C | Turkey-red oil | Sweet oil | iso-Propylamine |
| 2130 | Which factor is most likely to impair the strength and durability of synthetic line? | Sunlight | Washing with mild soap | Mildew | Dry rot |
| 2131 | Which is an example of failure to exercise due diligence? | Sailing short of union manning requirements | Sailing with less than 30% reserve fuel oil supply | Overloading | Sailing short of being full and down |
| 2132 | Which is an indication of reserve buoyancy? | Metacentric height | Freeboard | Rolling period | Righting moment |
| 2133 | Which line cannot be spliced? | Braided line with a hollow core | Any line can be spliced | Double-braided line | Braided line with a solid core |
| 2134 | Which method is used to detect rot in manila lines? | Measuring the reduction in circumference of the line | Observing for the appearance of mildew on the outer surface | Opening the strands and examining the inner fibers | Feeling the surface of the line for broken fibers |
| 2135 | Line Displacement is a procedure that is followed at an oil terminal facility, when there is a change of which of the following? | product during the final phase of loading | cargo lines at the terminal before loading | product before the start of loading | product after the final discharge |
| 2136 | How do you determine the weight of the vessel that is supported by the ground when a vessel has run aground? | This requires extensive calculation and is usually performed only by a naval architect not by a ship s officer. | Determine the point where aground and the draft at that point, then calculate it using the grounding formula. | Use the inclining experiment formula and substitute the change of trim for the angle of list. | Use the hydrostatic tables and enter with the mean draft before grounding and the mean draft after grounding. |
| 2137 | How does an inert gas system on a tanker function to prevent explosions in cargo tanks? | Maintains a positive pressure on the vent header to cool the flammable vapors. | De-energizes the charged mist effect. | Inert gas dilutes the flammable vapor and air concentrations to keep them below the lower explosive limit. | Inert gas filters out the flammable vapors from the cargo tank spaces. |
| 2138 | How is the minimum bursting pressure for each cargo hose assembly determined? | four times the sum of the relief valve setting and the static head | three times the sum of the relief valve setting and the static head | the sum of the relief valve setting and the static head | twice the sum of the relief valve setting and the static head |
| 2139 | How much weight can you lift by applying 100 lbs. of force to a twofold purchase rigged to disadvantage (do not consider friction)? | 300 lbs. | 400 lbs. | 200 lbs. | 500 lbs. |

| | | | | | |
|---|---|---|---|---|---|
| 2140 | How should pinching of the cargo hose between the vessel and the dock be prevented? | adjusting the hose supports | tying off the topping lifts and runners to winch heads | laying out an excess length of hose on deck | install hose preventers |
| 2141 | How will the draft at the center of floatation change after transferring a weight forward on a vessel? | it will change, depending on the location of the LCG | it will remain constant | it will decrease | it will increase |
| 2142 | What abbreviation represents the height of the center of buoyancy? | KB | BM | CB | BK |
| 2143 | What allows the liquid to flow into the suction side of the centrifugal pump? | Air | Gravity | Force inside the pump | Liquid inside the pump |
| 2144 | What are cargo tanks carrying grades D or E liquids on tank barges required to be ventillated with? | gooseneck vents and flame screens | pressure-vacuum relief valves | branch vent lines and a vent header | forced draft blowers |
| 2145 | What does it mean to shore up the main deck for the stowage of deck cargo? | package the cargo in wooden crates so it will not damage the deck | weld pad eyes on deck in proper position to secure the cargo | distribute the weight of the cargo by placing fore-and-aft planks on the main deck | strengthen the main deck by placing pillars underneath it in the tween-decks |
| 2146 | What form of venting of cargo tanks is allowed for a tank barge certificated to carry grade B petroleum products? | Individual pressure-vacuum relief valves with flame screens | Gooseneck vents with flame screens | Straight vents with flame screens | Gooseneck vents only |
| 2147 | What happens to steam that is produced by gas burning in excess of machinery plant demand? | recirculated to the first stage articulator | jettisoned overboard below the waterline | vented to the atmosphere | dumped to a condenser |
| 2148 | What happens to the volume of flammable and combustible liquids when temperature is increased? | it expands | it remains constant | it contracts | it remains constant if pressure remains constant |
| 2149 | What is a wet cargo? | A cargo particularly susceptible to damage by moisture | A liquid cargo carried in the deep tanks | A canned or bottled liquid such as beer | A cargo that contains hygroscopic moisture |
| 2150 | What is an advantage of having wire rope with a fiber core over that of a wire rope of the same size with a wire core? | Fiber core rope offers greater flexibility. | Fiber core rope is the only type authorized for cargo runners. | Fiber core rope offers greater strength. | Fiber core rope can be used at higher operating temperatures. |
| 2151 | What is an example of a fundamental objective of cargo stowage? | Load so the trim does not exceed 3 feet by the stern. | Separate wet and dry cargoes into separate holds. | Prevent overcarriage by block stowage. | Make maximum use of existing dunnage. |

| | | | | | |
|---|---|---|---|---|---|
| 2152 | What is an example of a grade A flammable liquid? | Ethylene dibromide | Pentane | Methyl alcohol | Nonyl phenol |
| 2153 | What is another description for a tandem crane lift? | All of the above | Twin cranes hoisting 60 tons | Single crane hoisting 30 tons | Quad lift hoisting 120 tons |
| 2154 | What is classified as a combustible liquid? | Tetraethylene glycol | Carbon tetrachloride | Acetaldehyde | Ethyl alcohol |
| 2155 | What is least likely to be used to strip a cargo tank? | Eductor | Rotary pump | Reciprocating pump | Centrifugal pump |
| 2156 | What is litmus paste is used to determine? | thievage | the tank datum point | ullage | innage |
| 2157 | What is meant by thieving a petroleum cargo? | Reducing the gross cargo calculations to net amounts | Adjusting the cargo figures to coincide with the draft | Siphoning off a few barrels of petroleum for shipboard use | Determining the amount of water (if any) in each cargo tank |
| 2158 | What is not a motion of the vessel? | Trim | Roll | Yaw | Pitch |
| 2159 | What is NOT a precaution to be taken when topping off? | Give the operation your undivided attention. | Reduce the loading rate. | Notify the engine room of the procedure. | Maintain communications with the dock man. |
| 2160 | What is NOT a requirement for the safe and effective use of a crude oil washing system? | Use portable washing machines to reach areas obscured by structural members in the tanks. | Decant one meter from the source tank for the tank cleaning machines. | Strip all tanks and remove the bottom residue. | Use an inert gas system while washing tanks. |
| 2161 | What is NOT an advantage of containership operations over conventional break-bulk operations? | Greater operational safety | Lower stevedoring costs | Flexibility of operation | Reduction of cargo damage |
| 2162 | Which vessel is most likely loaded full but not down ? | A bulk carrier loaded with heavy ore | A break bulk vessel loaded with palletized cargo | A bulk carrier loaded with steel | A tanker loaded with heavy grain |
| 2163 | To determine the weight capacity of a deck in a cargo hold, you would refer to the _____. | deck capacity plan | deadweight scale | cubic capacity tables | general arrangement plan |
| 2164 | The stowage factor for a cargo is based upon _____. | one long metric ton | one long ton | one short ton | one short metric ton |
| 2165 | You are planning the stowage of two incompatible products on your multiple-product tankship. What will NOT provide the minimum required segregation? | Tank containing a third cargo compatible with the other two | Empty tank | Solid (non-intercostal) bulkhead | Diagonally adjacent tanks |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 2166 | Your vessel has been loaded in a sagging condition. Enroute you encounter heavy weather and notice buckling in the midships deck plating of your vessel. To relieve the strain you could _____. | all options are correct | pump fuel oil from midships to the ends of the vessel | reduce speed | take a course which most eases the vessel |
| 2167 | A cargo that has a stowage factor over 40 is known as a _____. | weight cargo | measurement cargo | stowage cargo | hygroscopic cargo |
| 2168 | You are on a vessel designed to carry compressed gasses in bulk with a cargo of butadiene. Which statement is TRUE? | The shipping document must specify the exact quantity of butadiene being carried. | The cargo tank may be sampled only when the tank is being filled. | Silver and copper are prohibited in the parts of valves and fittings in contact with the cargo. | The ullage must be padded with compressed air at a minimum pressure of 2 psig. |
| 2169 | You are on a tankship designed to carry molten sulfur. Which statement is TRUE? | Cargo temperature may be taken by portable thermometers. | There must be two portable toxic vapor detectors on board. | The cargo tank ventilation system must maintain the H2S vapor concentration at 1.85% or more by volume. | The pressure in the heating coils in the tanks must be less than that of the cargo exerted on them. |
| 2170 | You are on a cargo vessel carrying portable tanks of dangerous cargoes in bulk. Which statement is TRUE? | If the tanks are pumped out while remaining on board, each hose connection must have a minimum of three bolts. | All electrical equipment within 10 feet horizontally must be explosion proof or intrinsically safe. | When transferring sulfuric acid, you must display a red flag by day whether at anchor or moored. | If the tanks are off loaded, no more than two tanks may be lifted together in a hoist. |
| 2171 | You start a centrifugal cargo pump to discharge cargo. The pump works for a while and then loses suction. This could be caused by _____. | the discharge head being too high | the pump running backwards | incomplete priming | All of the optons |
| 2172 | A hygroscopic cargo is defined as a cargo _____. | capable of absorbing moisture in the form of a gas | capable of giving off moisture in the form of a liquid | that is shipped in a liquid state | that will ignite in contact with water |
| 2173 | What is meant by thieving a petroleum cargo? | Adjusting the cargo figures to coincide with the draft | Determining the amount of water (if any) in each cargo tank | Reducing the gross cargo calculations to net amounts | Siphoning off a few barrels of petroleum for shipboard use |
| 2174 | What is meant by thieving a petroleum cargo? | Adjusting the cargo figures to coincide with the draft | Siphoning off a few barrels of petroleum for shipboard use | Determining the amount of water (if any) in each cargo tank | Reducing the gross cargo calculations to net amounts |

| | | | | | |
|---|---|---|---|---|---|
| 2175 | Which is characteristic of a special cargo? | It must be stowed on deck. | It is of high value or easily pilferable. | The cargo gives off toxic gases when heated. | Periodic inspection is required while in transit to prevent spoilage. |
| 2176 | Block stowage means _____. | stowing all the cargo for a port in the same area | having the cargo on pallets | using port marks on the cargo | using separation cloths to separate different kinds of cargo |
| 2177 | Which can be prevented only by segregating two lots of cargo into separate holds? | Contamination of a clean cargo by a dirty cargo | Contamination of a food cargo by an odorous cargo | Overcarriage, overstowage, and short landing | Contamination of dry cargo by a wet cargo |
| 2178 | You are on a vessel that carries liquefied gasses in bulk. The person on watch is required to have what information about the cargo easily accessible? | Name and address of consignee | Port of loading | Exact quantity on board | Firefighting procedures |
| 2179 | You are transporting dangerous cargo on your vessel. The Dangerous Cargo Manifest must be signed by the _____. | Master only | U.S. Coast Guard Marine Inspector | Master or his authorized representative | shipper |
| 2180 | What is the main purpose of dunnage? | To provide ventilation and drainage for cargo | To act as ballast for light vessels | To secure the tarpaulins in place | To support weakened bulkheads |
| 2181 | What refers to the depth of a petroleum product in a tank? | Ullage | Innage | Thievage | Outage |
| 2182 | A shore is a piece of securing dunnage that _____. | is run horizontally from a support to the cargo | is also known as a distance piece | runs from a low supporting level up to the cargo at an angle | is placed on the deck under the cargo to distribute its weight evenly |
| 2183 | The best way to lift many small articles aboard your vessel is with a _____. | pallet | barrel hook | spreader | snotter |
| 2184 | Dunnage may be used to protect a cargo from loss or damage by _____. | tainting | hygroscopic absorption | inherent vice | ships sweat |
| 2185 | When fruit is carried as refrigerated cargo, the most frequent cause of its being infected at the discharge port is _____. | improper cleaning of the cargo spaces | leaks in the ships refrigeration system | improper precooling of the cargo spaces | carriage at the wrong temperature |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 2186 | Mousing a cargo hook with marline or small line _____. | increases the lifting capacity of the hook | protects the hook from the sling ring | prevents the sling ring from coming out of the hook | All of the options |
| 2187 | The total weight of cargo, fuel, water, stores, passengers and crew, and their effects, that a ship can carry, is the _____. | loaded displacement | gross tonnage | bale cubic | deadweight |
| 2188 | Which statement is NOT true concerning the stowage of class 1 explosives? | Class 1.4 explosives may not be stowed in the same hold with class 6.1 poisons. | Class 1.1 explosives may be stowed with class 9 dangerous substances | Class 1.4 explosives must be separated from a stow of class 5.1 oxidizing materials. | Class 1.4 explosives must be separated from a stow of class 8 corrosive materials. |
| 2189 | When a deck cargo is secured with chain or wire lashings and grab (pear) links, which statement is FALSE? | The lashings should be inspected each day and any slack taken up. | The turnbuckle should be secured with a stick or lock nuts. | The amount of take-up is limited by the length of the turnbuckle. | At the grab (pear) link, the slack end of chain should be led back and secured to the chain above the link. |
| 2190 | When measuring the oxygen content of the cargo tanks prior to loading cargoes requiring vapor recovery, check it _____. | one meter from the tank bottom and one meter below the tank top | one half the ullage of the tank and one meter above the tank bottom | at three meter intervals from the tank top to the bottom | one half the ullage of the tank and one meter below the tank top |
| 2191 | On the cargo manifest, the weight of the cargo inside a box is called _____. | net weight | gross weight | light weight | rate weight |
| 2192 | Stress on the topping lift of a swinging boom can be reduced by _____. | rigging a back stay | raising the boom | taking all slack out of the preventer | increasing the mechanical advantage of the cargo purchase |
| 2193 | Displacement refers to the _____. | deadweight carrying capacity of a vessel | gross tonnage of a vessel | cubic capacity of a vessel | number of long tons of water displaced by a vessel afloat |
| 2194 | Cargo transfer operations on a tank vessel need NOT be stopped when _____. | a tug comes alongside while the tanker is loading grade D and E cargoes | a large, fresh oil spill is discovered immediately adjacent to the side of the tanker | there is an electrical storm in the vicinity | there is a fire on the dock or on a nearby vessel |
| 2195 | When planning the loading or discharging of a VLCC (100,000 DWT+) what is the most important consideration? | Rate of discharging | Limits of the bending moments | Draft and trim | Rate of loading |

| | | | | | |
|---|---|---|---|---|---|
| 2196 | You are transporting dangerous cargo on your vessel. The regulations require you to _____. | periodically inspect it and make an entry in a log | keep a warning sign posted nearby | keep a fire hose run out and ready for use if needed | allow no chipping or painting in the vicinity of the cargo |
| 2197 | You are on a multiple product tankship and carrying methyl acrylate, diethanolamine, and triethylamine. Which statement is TRUE? | Methyl acrylate may be loaded in a tank adjacent to diethanolamine but not triethylamine. | Each crew member working on deck must have an emergency escape breathing apparatus. | The heating coils to the cargo tank loaded with methyl acrylate must be blanked off. | Valve components made of aluminum, copper, or zinc may not be in contact with the cargoes. |
| 2198 | You have completed a Dangerous Cargo Manifest for dangerous cargoes loaded on board. It should be kept in a conspicuous location _____. | on or near the bridge | in the radio room | in the ships office | outside the Captains stateroom |
| 2199 | It is possible, and sometimes necessary, to strengthen the deck of a vessel for carriage of deck cargo by _____. | welding steel feet to the deck, on which the cargo is placed | erecting vertical pillars under the deck to support the cargo | building a stage on which to place the cargo | placing bunker on the deck |
| 2200 | A long ton is _____. | 2,240 pounds | 1,000 pounds | 2,000 pounds | 2,400 pounds |
| 2201 | What is the meaning of the term tare weight? | Total weight of a container and contents | Pounds of force necessary to damage a container | Weight of the contents of a container | Weight of a container |
| 2202 | You are loading a cargo tank on your container ship. The tank displays the red label shown. Which statement is TRUE? | The tank contains propylene. | The tanks volume is 1077 cubic feet. | There are three tanks in the shipment. | The tank contains an oxidizing material. |
| 2203 | Tonnage tax is officially based upon the figures obtained from the _____. | Load Line Certificate | deadweight scale | Admeasurement Certificate | displacement scale |
| 2204 | Peck and Hale gear is used most commonly for securing _____. | automobiles | baled cargo | large wooden crates | palletized cargo |
| 2205 | When hooking up a cargo hose to your vessels manifold, you should use a(n) _____. | international shore connection | self-contained breathing apparatus | oxygen analyzer | insulating flange or single length of non-conducting hose |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 2206 | On a vessel proceeding from a very cold to a warm climate with a cargo of a nonhygroscopic nature in the holds, which is TRUE? | There is danger of heavy cargo sweat if outside air is introduced by ventilation. | Danger of heavy ship sweat exists; constant and vigorous ventilation is required. | There is little danger of ships sweat, slight possibility of cargo sweat; moderate ventilation is needed. | The possibility of any sweat problem, either cargo or ship, is remote. |
| 2207 | Ballasting is performed once cargo on each hold is half-empty. A usual check on each deep tank cover to ensure that it's all watertight to prevent any flooding is due to: | leak at deep tank cover | water-ingress | loosen nuts | rusty bolts and nuts |
| 2208 | What is NOT an item requires the vessel to be dry-docked? | Verification of loadline measurement | Inspection of the tail shaft liner | Belt gauging | Repacking and grinding of skin valves |
| 2209 | Which type of hull damage should be repaired first? | damage in way of machinery room | damage at or just above waterline | damage below the water line | damage to interior watertight boundaries |
| 2210 | Ballasting is performed once cargo on each hold is half-empty. A usual check on each deep tank cover to ensure that it's all watertight to prevent any flooding is due to: | rusty bolts and nuts | leak at deep tank cover | Water- ingress | Loosen nuts |
| 2211 | The objective of shoring a damaged bulkhead is to _____. | support and hold the area in the damaged position | force the warped, bulged, or deformed sections back into place | withstand subsequent additional damage | make a watertight seal at the damaged area |
| 2212 | Control of flooding should be addressed _____. | first | following restoration of vital services | following control of fire | only if a threat exists |
| 2213 | You must shore up the collision bulkhead due to solid flooding forward. The bulkhead approximates an inverted triangle. The center of pressure of the shores on the bulkhead should be located _____. | at the bottom of the bulkhead | approximately two-thirds of the way up the bulkhead | approximately halfway up the bulkhead | evenly over the surface of the bulkhead |
| 2214 | While in drydock, your vessel will be belt-gauged. This process involves: | drilling a sonic-testing the hull to determined the plate thickness | testing and examining the anchor cables for detective links | measuring the thickness of the tail shaft liner | taking the vessel affect the deck for hull deterioration |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 2215 | This system has been used for many years. The fittings of these plates in way of bronze propellers and other immersed fittings is a common practice: | impressed current system | sacrificial anode system | electro-chemical system | cathodic protection system |
| 2216 | Extended cyclical variations in tensions will cause an anchor chain to break due to _____. | Fatigue | Corrosion | Distortion | Abrasion |
| 2217 | Which weld fault can only be detected by a method that examines the internal structure of a weld? | Undercut | Overlap | Lack of reinforcement | Lack of penetration |
| 2218 | A reinspection of the vessel shall be made between which of the following months while the Certificate of Inspection is valid? | 10 - 12 months | 10 - 14 months | 8 - 12 months | 12 - 14 months |
| 2219 | Your vessel has been damaged and you must shore a bulkhead. You should cut the shore _____. | approximately 1/2 inch shorter than the measured length to allow for wedges | approximately 1/2 inch longer than the measured length to allow for trimming | approximately 1/2 inch shorter per foot of shoring to allow for wet expansion | to the same length as the measured length |
| 2220 | Dunnage may be used to protect a cargo from loss or damage by _____. | hygroscopic absorption | inherent vice | tainting | ship's sweat |
| 2221 | Which type of hull damage should be repaired FIRST? | Damage to interior watertight boundaries | Damage below the waterline | Damage at or just above the waterline | Damage in way of machinery rooms |
| 2222 | What is the meaning of the term tare weight? | Pounds of force necessary to damage a container | Weight of a container | Weight of the contents of a container | Total weight of a container and contents |
| 2223 | Sweat damage will occur in a cargo hold containing cased machinery when the _____. | dew point of the outside air is lower than the temperature of the cargo | air temperature of the hold is higher than the temperature of the outside air | dew point of the hold is higher than the temperature of the ship's skin | outside air temperature is colder than the temperature of the cargo |
| 2224 | Sweat damage in a hatch full of canned goods in cartons will occur when the _____. | dew point is higher than the temperature of the cargo | air temperature is higher than the temperature of the cargo | air temperature is lower than the temperature of the cargo | dew point is lower than the temperature of the cargo |
| 2225 | When underway with a tow, you are required to notify the Coast Guard in which casualty situation? | An injury requiring first aid treatment | Accidental stranding or grounding | Damage to property amounting to $12,500 | Damage of bridge-to-bridge radio capability |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 2226 | What would NOT require that a detailed report of the release of hazardous cargo be made to the Local Authorities? | Heavy weather causes damage to packages of a hazardous liquid that is subsequently pumped out at sea through the bilge pumping system. | The valve on an empty portable tank that contained acetone is accidentally opened and some of the residue escapes to the open sea. | A carboy of nitric acid is broken on deck while loading and is flushed overboard with no injury or damage. | Part of your deck cargo of five gallon cans of paint is damaged and leaking so you jettison them to eliminate the fire hazard. |
| 2227 | Which factor is MOST important in preventing sweat damage within a cargo hold? | Dew point of the cargo hold | Dew point of the outside atmosphere | Temperature of the cargo | Outside air temperature |
| 2228 | Repairing damage to the hull at or above the waterline reduces the threat of _____. | wind heel | continued progressive flooding | capsizing | free surface effects |
| 2229 | A report of casualty to a vessel must include _____. | the estimated cost of damage | an evaluation of who was at fault | the amount of ballast on board | the name of the owner or agent of the vessel |
| 2230 | A vessel has sustained damage in a collision with another vessel. It is necessary to have a Seaworthy Certificate before the vessel sails. Who will issue this certificate? | Captain of the Port | American Consul | Officer in Charge, Marine Inspection | Classification Society |
| 2231 | Which factor(s) might indicate that a towline should be removed from service? | All of the above | A surface condition of corrosion and discoloration. | Measurements showing a decrease in diameter. | Visible damage to the towline, including fishhooks. |
| 2232 | The damage to a vessel is over $25,000. Who must notify the nearest Coast Guard Marine Safety or Marine Inspection Office as soon as possible? | All of the above | The Master of the vessel | The Chief Officer | The Radio Officer |
| 2233 | Which situation requires you to furnish a notice of marine casualty to the Coast Guard? | You collide with a buoy and drag it off station with no apparent damage to the vessel or the buoy. | Storm damage to the cargo winch motors requiring repairs costing $19,000. | Your vessel is at anchor and grounds at low tide with no apparent damage. | . A seaman slips on ice on deck and sprains his ankle, requiring an ace bandage. |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 2234 | A vessel loads 100 tons of glass jars. The mate on watch discovers that some of the cartons have been damaged and has an exception made on the Bill of Lading. What is this document called? | Letter of Indemnity | Damage Bill of Lading | Unclean Bill of Lading | Non-negotiable Bill of Lading |
| 2235 | Under the Carriage of Goods by Sea Act of 1936, a vessel will be liable for damage to a cargo when the damage arises from _____. | unseaworthiness when sailing | insufficient packing | quarantine delays | mismanagement of the vessel |
| 2236 | Under the Carriage of Goods by Sea Act of 1936, a vessel will be liable for damage to cargo when the damage arises from _____. | an error in navigation | perils of the sea | lack of ventilation in transit | an act of war |
| 2237 | A declaration made by the Master before a U.S. Consul, giving particulars regarding heavy weather or other incidents which may have caused damage to the vessel or cargo, through no fault of the vessel, her officers, or crew is a(n) _____. | cargo addendum | exception report | Master's declaration | note of protest |
| 2238 | The document that establishes the facts of a casualty and is the prima facie relief from liability for the damage is the _____. | adjuster's report | invoice | Master's protest | insurance policy |
| 2239 | A document used to indicate suspected cargo damage caused by rough weather would be the _____. | Master's Note of Protest | Unseaworthy Certificate | hull damage report | cargo report |
| 2240 | A Master should file a marine note of protest if _____. | . longshore labor went on strike in the port causing undue vessel delay | cargo was received at ship side which was damaged in land transit | the vessel encountered heavy weather which might have caused cargo damage | portions of his vessel's cargo were illegally impounded in a foreign port |
| 2241 | The declaration made by the Master when he anticipates hull and/or cargo damage due to unusual weather conditions is a _____. | Notice of Casualty | Portage Bill | Bottomry Bond | Note of Protest |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 2242 | Under the Carriage of Goods by Sea Act of 1936, a vessel will be liable for damage to cargo when the damage arises out of _____. | fire caused by lightning | overloading | inherent vice | poor stowage of cargo in a container |
| 2243 | While a vessel is at sea, the mate on watch discovers a fire in one of the hatches. Fire hoses are used to put the fire out and some of the cargo is damaged by water. In marine insurance terms, this partial loss by water is called _____. | general average | an Act of God | fire and water damage | particular average |
| 2244 | Under the Carriage of Goods by Sea Act of 1936, a vessel will be liable for damage to a cargo when the damage arises out of _____. | fire caused by fault of the carrier | improper stowage | strikes or lockouts | delays due to seizure of the vessel |
| 2245 | A fire has damaged 20 bales of cotton on a freighter loaded with general cargo. This claim would come under _____. | total loss of a part | constructive total loss | note of protest | particular average |
| 2246 | The two courses of action if the underwater hull is severely damaged are to plug the openings or to _____. | ballast to maintain even keel | establish and maintain flooding boundaries | dewater the compartment | secure power to the compartment |
| 2247 | Particular average is _____. | loss sustained by only one party | claimed after all liens against the vessel are settled | the average distance steamed per day over the duration of the voyage | charges against all parties in a marine venture to pay for damages |
| 2248 | A vessel has been damaged by fire. The survey shows the cost of repairs will exceed the value of the repaired vessel. This is an example of a(n) _____. | preferred loss | constructive total loss | actual loss | salvage loss |
| 2249 | A claim for cargo damages may be held against the shipowner if such damage is the result of failure of the ship's officers to _____. | prevent delays due to quarantine restrictions | ensure adequate packaging of the cargo | correct all defects in the ship's construction | ensure the fitness and safety of cargo spaces |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 2250 | When shoring a damaged bulkhead, effort should be taken to spread the pressure over the _____. | nearest watertight door | nearest longitudinal girder | maximum possible area | minimum possible area |
| 2251 | Which statement concerning sweat damage in containers is TRUE? | Containers should be ventilated, dehumidified, or the contents physically protected against sweat damage. | Sweat damage is not a problem except in insulated and refrigerated containers. | In general, containerized hygroscopic cargoes are the only ones subject to sweat damage. | Sweat damage in containers is unusual due to the small enclosed volume of air. |
| 2252 | A vessel is constructed with a steel hull and an aluminum superstructure. Which statement is TRUE? | The aluminum will provide greater resistance to the spread of fire by conduction. | The steel at the area of the aluminum-to-steel connection must be closely checked for galvanic corrosion. | If the superstructure is stressed, an aluminum structure requires additional expansion joints to prevent fracture. | The aluminum structure is usually attached to a steel coaming by a method that insulates the two metals. |
| 2253 | What would have the greatest affect on a vessel's longitudinal strength? | Extensive corrosion to the centerline deck plating | Grounding damage to the bilge strake, just aft of midships | Damage to the side shell, midway between the bilge and the stringer plate | Collision damage to the bow, forward of the collision bulkhead |
| 2254 | To enable pipes of reception facilities to be connected with the ships discharge pipelines for residues from machinery bilges. Pipelines should be standard with an outside diameter of: | 183 mm | 180 mm | 200 mm | 185 mm |
| 2255 | What is the bolt circle diameter of a standard pipeline to enable pipes of reception facilities to be connected for residue from machinery bilges is: | 190 mm | 200mm | 183mm | 195mm |
| 2256 | The oil record book maintained on a vessel not engaged in a foreign trade shall be maintained on board for not less than: | 12 months | 36 months | 48 months | 24 months |
| 2257 | Vessel underwater hull is submerged in water and needs corrosion protection for this area. | paint protection | cathodic protection | anti-fouling | anodes protection |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 2258 | The wooden plug inserted in the vent of a damaged vessel tank should be removed in case it is decided to _____. | pump from the damaged tank | fight a fire | abandon ship | use the crossover system |
| 2259 | The wooden plug inserted in the vent of a damaged tank should be removed if you are going to. | Use the crossover line | Fight a fire | Pump from the damage tank | Abandon ship |
| 2260 | Repair of emergency machinery and services should be accomplished after an explosion. | immediately, before the emergency is under control | after control of fire, flooding and structural repairs | after stability is restored | after control of fire, but before control of flooding |
| 2261 | A ship progressive flooding may be indicated. | a continual worsening of list or trim | excessive draft | ballast control alarms | excessive list or trim |
| 2262 | Considered longitudinal framing. | Stem post | Beam knees | Pillars | Floors |
| 2263 | An involuntary and dangerous change in heading produced by a severe following or quartering sea is called: | Bulk head | Forepeak | Broaching | Body plan |
| 2264 | The watertight integrity of a vessel must be intact, when? | When maneuvering | Can be relaxed during spells of fine weather | Can be relaxed in inshore waters | In open waters only |
| 2265 | Piping that routes an oil cargo from the manifold to under deck pipelines is known. | cargo fill | transfer | branch line | line drop |
| 2266 | Vessel's ballast tanks are subjected to sea water and therefore needs special corrosion protection, the most commonly used. | Cathodic protection only | Coating protection only | Cathodic and coating protection | Anode protection only |
| 2267 | Resultant of two forces acting together in opposite directions and along parallel lines, is an example of what type of stress? | Shear | Tensile | Compression | Strain |
| 2268 | Containing a damage control, the order of importance should be taken into account. | control the flooding, then control the fire, and repair structural damage | restore vital services, control the fire, then control the flooding | control the fire, restore the vital services, then control the flooding | control the fire, control the flooding, and repair the structural damage |
| 2269 | Vessel underwater hull is submerged in water and needs corrosion protection for this area. | anodes protection | paint protection | cathodic protection | anti-fouling |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 2270 | The wooden plug inserted in the vent of a damaged vessel tank should be removed in case it is decided to _____. | pump from the damaged tank | fight a fire | abandon ship | use the crossover system |
| 2271 | The wooden plug inserted in the vent of a damaged tank should be removed if you are going to. | Fight a fire | Pump from the damage tank | Abandon ship | Use the crossover line |
| 2272 | Repair of emergency machinery and services should be accomplished after an explosion. | after stability is restored | immediately, before the emergency is under control | after control of fire, but before control of flooding | after control of fire, flooding and structural repairs |
| 2273 | A ship progressive flooding may be indicated. | a continual worsening of list or trim | excessive draft | ballast control alarms | excessive list or trim |
| 2274 | Considered longitudinal framing. | Beam knees | Pillars | Stem post | Floors |
| 2275 | An involuntary and dangerous change in heading produced by a severe following or quartering sea is called: | Bulk head | Body plan | Broaching | Forepeak |
| 2276 | The watertight integrity of a vessel must be intact, when? | Can be relaxed during spells of fine weather | When maneuvering | Can be relaxed in inshore waters | In open waters only |
| 2277 | Piping that routes an oil cargo from the manifold to under deck pipelines is known. | line drop | transfer | cargo fill | branch line |
| 2278 | Vessel's ballast tanks are subjected to sea water and therefore needs special corrosion protection, the most commonly used. | Cathodic protection only | Anode protection only | Coating protection only | Cathodic and coating protection |
| 2279 | Resultant of two forces acting together in opposite directions and along parallel lines, is an example of what type of stress? | Shear | Tensile | Compression | Strain |
| 2280 | Containing a damage control, the order of importance should be taken into account. | restore vital services, control the fire, then control the flooding | control the fire, control the flooding, and repair the structural damage | control the fire, restore the vital services, then control the flooding | control the flooding, then control the fire, and repair structural damage |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 2281 | Ship is proceeding along the English Coast when sprang a leak on the hull below the waterline. Efforts to patch her proved futile It was decide to ditch her the nearest shoal This termed as _____. | beaching | stranding | ditching | grounding |
| 2282 | An acceptable method of temporarily sealing a crack formed in the hull of a vessel, is to: | drive in wedges | shore up the crack with welded braces | tack weld a doubler plate over the crack | apply a patch of sheet packing backed by a shole and shoring |
| 2283 | Deterioration of steel due to chemical and electro-chemical reaction to its environment. | Fouling | Corrosion | Degradation | Electrolysis |
| 2284 | In the maintenance of cargo handling equipment, how often should you grease the nipples on winches, blocks, derrick heels, crane turntables and similar equipment? | Weekly | Monthly | Every two months | Every two weeks |
| 2285 | A ship is holed in cargo hold and partially flooded. The hole is plugged against further floodin. In calculating for the effect of flooding on your transverse stability, you should use which method? | Compartment standard method | Added weight methods | Lost of buoyancy methods | Factor subdivision method |
| 2286 | Maximum length allowed between main transverse bulkheads on a vessel is referred to. | floodable length | factor of the subdivision | compartment standard | permissible length |
| 2287 | Panting frames are located. | after double bottoms | fore and after peaks | centerline tanks | forward double bottoms |
| 2288 | Most effective method of corrosion removal . | hydro blasting | manual preparation | abrasive blasting | power tool preparation |
| 2289 | Ship's flooding of any compartment in a ship that result in serious loss of reserve buoyancy will always_____. | cause a serious list | increase the trim | increase the ship stability | decrease the heeling moment |
| 2290 | NOT a division of lots in a survey of damage to facilitate drawing up of a fire damage report. | Collapse of package and stowage of commodity | Damage by smoke | Injuries in obtaining access to the seat of the fire | Damage by water in extinguishing of the fire |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 2291 | Ship's damaged bulkhead after takes a permanent set which is dependent of the panting or caused by water pressur To contol this you should_____. | Place sand bag by the bulk head | Install shoring to support the damage without pushing them | Install shoring so that it pushes on the bulkhead | Use jacks or chain falls to remove the set before installing shores |
| 2292 | It begins when the tank is almost empty. | Middle wash | Top wash | Deck wash | Bottom wash |
| 2293 | A vessel which carries a cargo of grain in bulk should not, at the same time, carry any solid bulk cargo which may _____ unless such cargo is tested and the moisture content is equal to or less than the transportable moisture limit. | Liquefy | danger | mix | contaminate |
| 2294 | Hull leaks can be temporarily repaired. | seizing | parceling | caulking | parbuckling |
| 2295 | Angular motion about the longitudinal axis of a vessel is known as: | pitch | sway | surge | roll |
| 2296 | To control a damaged bulkhead after takes a permanent set which is independent of the panting or bulge cause by water pressure. | install shoring so that it supports on the damaged bulkhead without pushing them | install shoring so that it pushes on the bulkhead | place sand bay by the bulkhead | use jacks or chain falls to remove the set before installing shores |
| 2297 | Damaged ship's bulkheads after collision take a permanent set which is independent of the panting or bulge cause by water pressur To control this, you should _____. | Placed sandbag by the bulkhead without installing shores | Usejacks or chain falls to remove the set before installing shores | Install shoring so that it pushes on the damaged bulkhead while supporting it | Install shoring so that it supports the damaged bulkhead without pushing them |
| 2298 | Vessel was damaged and there no list or trim.The rolling period is short. The freeboard before the damage was 3.75 meter. Action will you take first. | Pump out an amidship centerline ballast tank | Transfer ballast from fore peak to an amidship centerline tank | Press up the slack centerline double bottom tanks | Pump out wing tanks from the starboard side amidships |
| 2299 | Vessel has been damaged and is partially flooded. The first step to be taken in attempting to save the vessel. | Pump out water inside the vessel | Calculate the free surface effects and lost buoyancy to determine stability | Plug the holes in the outer shell | Establish flooding boundaries and prevent further spread of flood water |

| | | | | | |
|---|---|---|---|---|---|
| 2300 | The name called to a single fitting installed in a pipeline that either blanks off pipe or allows a full passage of liquid trough the pipe. | Blind flange | Spectacle flange | Pivot coupling | Quick release coupling |
| 2301 | Ship vertical distance between the bottom at the centerline and the bottom at any given point. | rise of bottom | deadrise | rake | camber |
| 2302 | Vessel has been in collision and after assessing the damage, you begin down flooding. This will cause the KB to do which of the following? | Remain stationary | Fall | Shift to the high side | Rise |
| 2303 | As the vessel displacement increase, the detrimental effect of free surface will _____. | decrease | none of these choices | remains the same | increase |
| 2304 | Ship's small hull leaks can be temporarily repaired. | seizing | parbuckling | caulking | parceiling |
| 2305 | Shell plating provides the greatest contribution to the longitudinal strength they are arranged in a fore and aft direction and welded together, horizontal welds. | Seams | Butts | Strakes | Tacks |
| 2306 | Vessel in a longitudinally framed, the longitudinal frames are held in place and supported by atwarship members called. | Margin plates | Floors | Web frames | Stringers |
| 2307 | Angular motion about the vertical axis of a vessel is called: | surge | yaw | sway | roll |
| 2308 | Main under deck pipeline on a tank ship is connected to individual tanks. | Branch line | Filler drops | Tanks drops | Crossover |
| 2309 | Vessel free surface effect in a slack tank reduced by subdividing the tank longitudinally fore and aft into two equal parts. | The free surface is reduce by one half | The free surface is eliminated | The free surface is reduce by three quarter | The free surface is reduce by one quarter |
| 2310 | If a small ship springs a leak, if possible, the initial action before making temporary repairs is to bring the leak above the water, while avoiding ____. | a list toward wind, sea or current | any adverse effects on stability | the jettisoning of cargo | a list away from the wind |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 2311 | A vessel was damaged and initially assumed a significant list and trim; however, further increase base on this data, what should you expect? | The vessel can probably be saved if further flooding can be stopped | The slowing is only temporary and the vessel will probably suddenly capsize or plunge from loss of stability due to change in the water plane area | The vessel will continue to slowly list and/ or trim due to the free surface effect and free communication effect | The vessel will suddenly flop to the same or greater angle of list on the other side and may capsize |
| 2312 | Vessel was damaged and initially assumed a significant list and trim; however, further increase has been also based on this data, what should you expect? | The slowing is only temporary and the vessel will probably suddenly capsize or plunge from loss of stability due to change in the waterplane are | The vessel can probably be saved if further flooding can be stopped | The vessel will suddenly flop to the same or greater angle of list on the other side may capsize | The vessel will continue to slowly list and/or trim due to the free surface effect and free communication effect |
| 2313 | NOT an advantage of centrifugal pumps over reciprocating pumps. | They require priming for stripping | They are smaller for equivalent pumping ability | They pump more cargo in less time | They are less expensive |
| 2314 | Two factors which make underwater hull repair difficult are accessibility and the _____. | availability of tools | threat of progressive flooding | pressure exerted by the water | shape of the hull |
| 2315 | Riveted joints occur at the ends of plating called. | Butts | Terminals | Trailers | Seams |
| 2316 | Name called for the pipe used to connect two separate piping system on a tank. | Junction | Connection | Crossover | Transfe |
| 2317 | A damagedship's bulkhead after takes a permanent set which is dependent of the panting or cause by water pressur To control you should _____. | install shoring so that it pushes on the damaged bulkhead while supporting it | install shoring so that it supports the damaged bulkhead without pushing them | placed sand bag by the bulkhead without installing shores | use jacks or chain falls to remove the set before installing shores |
| 2318 | Damaged caused by cargoes giving off fumes or odors stowed in the same compartment with fine goods or foodstuff. | Tainting damage | Inherent vice | Vermin damage | Vaporization |
| 2319 | What is the worst case consideration for a hull girder at sea? | When the wave crest is amidships | When the wave crest are in a fore and aft direction | When the wave length between the crest are equal to the length of the ship | When the wave length are unequal to the length of the ship |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 2320 | Statement(s) is (are) TRUE concerning wire rope? | Wire rope should be condemned if the fiber core appears moist | Wire rope should be condemned if the outside wires are worn to one-half their original diameter | Wire ropes should be used until 5% of strands are damage | Wire rope which is right-hand laid should be coiled counterclockwise to prevent kinking |
| 2321 | Free communication effect is in direct proportion to _____. | length and width of space | length of space only | width of space only | neither length nor width |
| 2322 | A Master should file a marine note of protest if _____. | cargo was received at ship side which was damaged in land transit | longshore labor went on strike in the port causing undue vessel delay | the vessel encountered heavy weather which might have caused cargo damage | portions of his vessels cargo were illegally impounded in a foreign port |
| 2323 | A product that most likely to accumulate static electricity is _____. | Hard asphalt | Residual fuel oil | Crude oil | Lubricating oil |
| 2324 | A shore is a piece of securing dunnage that _____. | runs from a low supporting level up to the cargo at an angle | is placed on the deck under the cargo to distribute its weight evenly | is also known as a distance piece | is run horizontally from a support to the cargo |
| 2325 | A short length of chain cable between anchor and windlass. | gaff | ginger | panama lead | ganger |
| 2326 | A tank vessel with an oil cargo capacity of 5000 barrels is required by regulations to have a fixed container or enclosed deck area under or around each oil loading manifold and each oil transfer connection point. The capacity of these containment areas is based upon _____. | number of cargo oil tank vents overflows and fill pipe connections | All of the mentioned answers | inside transfer hose diameter or loading arm nominal pipe size diameter | cargo oil service pressure |
| 2327 | A tank which has been sealed for a long period of time can be dangerous because _____. | steel surfaces consume oxygen by rusting | sealed tanks usually form a vacuum | moisture condenses in the tank displacing the oxygen | most tank coatings give off poisonous vapors in the presence of moisture |
| 2328 | A watertight compartment between the foremost watertight bulkhead and the stem. | Chain locker | Cofferdam | Bulbous bow | Fore peak |
| 2329 | Adverse effects due to free surface will become apparent when _____. | the vessels draft is decreased exposing more surface area to the wind and current | a portion of liquid is removed from a full tank | the vessel is trimmed by the stern | the vessels draft is increased thus increasing the vessels wetted surface area |

| | | | | | |
|---|---|---|---|---|---|
| 2330 | An adverse effects due to free surface? | A portion of the liquid is removed from a full tanks | The vessels is draft is decreased exposing more surface are to the wind and current | The vessels draft increases this increasing the vessels water plane area | The vessel is trimmed by the stern |
| 2331 | Before counterflooding to correct a list you must be sure the list is due to _____. | negative GM | off-center weight | flooding | reserve buoyancy |
| 2332 | Characterized by two ships at full speed two ships sideswiping each other or one ship sideswiping an object such as an iceberg. | moderate energy collision | all of the mentioned answers | low energy collision | high energy collision |
| 2333 | Control of flooding should be addressed _____. | following control of fire | first | following restoration of vital services | only if a threat exists |
| 2334 | Deficient oxygen content inside a confined space can be detected with _____. | an oxygen breathing apparatus | a combustible gas indicator | litmus paper | an oxygen indicator |
| 2335 | Due to solid flooding forward you must shore up a bulkhead which approximates a rectangle. The center of pressure of the shores on the bulkhead should be located _____. | approximately one-third of the way of the bulkhead | approximately halfway up the bulkhead | at the bottom of the bulkhead | evenly over the surface of the bulkhead |
| 2336 | Every ship that carries ballast water should be provided with a _____ to assist in the minimization of transfer of harmful aquatic organisms and pathogens. | Ballast Water Management Plan | Bilge Pump | Submersible Pump | Water Ballast Pump |
| 2337 | In and out motion of the plating in the bows of a ship and is caused by equal: | sagging | hogging | panting | Pounding |
| 2338 | In cases where ballast exchange or other treatment options are not possible ballast water may be _____ in tanks or holds. | retained | overflowed | All the mentioned are correct. | emptied |
| 2339 | Intact buoyancy is a term used to describe _____. | the space at which all the vertical upward forces of buoyancy are considered to be concentrated | the volume of all intact spaces above the waterline | an intact space below the surface of a flooded area | an intact space which can be flooded without causing a ship to sink |

| | | | | | |
|---|---|---|---|---|---|
| 2340 | The effects of free surface on a vessels initial stability do not depend upon the _____. | dimensions of the surface of the liquid | amount of liquid in slack tanks | specific gravity of the liquid in the tank | volume of displacement of the vessel |
| 2341 | The free surface effects of a partially full liquid tank decrease with increased _____. | size of the surface area in the tank | density of the liquid | displacement volume of the vessel | placement of the tank above the keel |
| 2342 | The two factors which make underwater hull repair difficult are accessibility and the _____. | pressure exerted by the water | threat of progressive flooding | availability of tools | shape of the hull |
| 2343 | To calculate the free surface correction it is necessary to divide the free-surface moments by the _____. | lightweight | deadweight | total weight of liquid loads | total displacement |
| 2344 | To increase the extent of flooding your vessel can suffer without sinking you could _____. | lower the center of gravity | increase reserve buoyancy | raise the center of gravity | ballast the vessel |
| 2345 | When patching holes in the hull pillows bedding and other soft materials can be used as _____. | Gaskets | Strongbacks | Wedges | Shores |
| 2346 | When plugging holes below the waterline you should _____. | Eliminate all water entering the hole | Reduce the entry of water as much as possible | Plug the largest holes first | Only plug holes in machinery or other vital spaces |
| 2347 | A Plan showing the location of cargoes stowed inside the hold: | Stowage plan | Loading plan | Discharging plan | General arrangement plan |
| 2348 | A point that temperature to which a combustible liquid must be heated for it to give off a vapour that will momentarily flash in presence of a naked light. | Flush point | Firing Point | Dew point | Flash point |
| 2349 | A portable traverse beam placed across a cargo hatchway that acts as a bearer to support the hatch covers. | Hatch Beams | Pontoons | Hatch Cleats | Hatch Boards |
| 2350 | A portion of the cargo of an LNG carrier boils off during each voyage. How is the cargo boil off normally handled? | Compressed condensed and return to the cargo tanks. | Vented to the atmosphere. | Burned in the boilers. | Mixed with nitrogen and recirculated through the primary barrier. |
| 2351 | A product can be wound immediately into coils from the rolling mill whilst still hot. | steel coil | steel plates | steel slab | wire rod coil |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 2352 | A product that most likely to accumulate static electricity is: | Lubricating oil | Residual fuel oil | Crude oil | Hard asphalt |
| 2353 | A property relating to the ability of a metal to withstand continuing changes in the direction of application of the stress. | Strength Equation | Fatigue Strength | Toughness | Hardness |
| 2354 | A prototype of each pressure or vacuum or pressure/vacuum venting device should be _____ tested for venting capacity by a test method acceptable to the Administration. | self | vench | vents | bench |
| 2355 | A reproductive health hazard listed on a Material Safety Data Sheet (MSDS) that can damage the fetus during development is called a: | teratogen | pyrophoric | mutagen | cryogenic |
| 2356 | A responsible officer should be appointed to maintain appropriate records and to ensure that ballast water management and/or treatment procedures are followed and: | reported | trained | recorded | listed |
| 2357 | A scale of values Tons per Centimeter Moment to Change Trim in Centimeters Displacement and Deadweight for all draft readings is: | Deadweight scale | Mean Draft values | Displacement scale | Draft Values |
| 2358 | A segregated ballast system is a system where: | all ballast is processed through the oily water separator | ballast is taken on and discharged through a separate main deck riser | ballast and cargo tanks are separated by cofferdams | all ballast lines tanks and pumps are independent of those used for oil |
| 2359 | A semi-automatic tool for handling unitized pulp bales w/out baskets. It has two locating tongues one at each end so that it cannot slip off. | Wire clamp | Multi grab | Bale clamp | Grab bucket |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 2360 | A vessel that has grounded may experience which of the following? I. An upward shift in the center of gravity. II. A capsizing. | II only | I only | Both I and II | Neither I or II |
| 2361 | A vessel which is subjected to sagging : | has its main deck in tensile stress | has its bottom plating under tensile stress | is supported on a wave whose crest is amidship | is said to be under a form of transverse bending |
| 2362 | A vessel whose fuel tanks are half full is subject to _____. | free surface effect | serious loss of reserve buoyancy | severe sagging | severe hogging |
| 2363 | A vessel s stability is greatly reduced by liquid free surface. Which of the listed conditions would develop the greatest adverse effect? | Tanks which have been pressed up to full capacity. | Tanks which are 95% full. | Tanks which are 40% full. | Tanks which have been completely emptied. |
| 2364 | A void or empty space between two bulkheads or floors which prevents leakage from one to the other is called a: | Cofferdam | Break | Bracket | Double hull |
| 2365 | A wooden plug fitted tightly in the vent of a damaged tank may prevent the tank from _____. | collapsing | filling completely | developing free surface | developing free surface moment |
| 2366 | After an emergency shoring installation has been completed the _____. | Shoring should be frequently inspected for looseness | Timbers are nailed in place to prevent looseness | Repair is completed and no further action is needed | Damaged plating should be straightened by heating |
| 2367 | After grounding extent of the damage to the ship can be determined by which of the following? | by checking the loadline | Taking sounding around the ship | Sounding of all compartments | by checking the summer line |
| 2368 | Air gap is the vertical distance between the bottom of the hull and the _____. | wave crest plus the charted water depth and tidal corrections | wave crest | wave crest plus the charted water depth plus tidal correction and storm surge | still water level |
| 2369 | All dedicated seawater ballast tanks shall have an _____ such as hard protective coatings or equivalent. | efficient anti freezing system | efficient corrosion prevention system | efficient anti-fouling system | efficient anti-scaling system |
| 2370 | The maximum length allowed between main, transverse bulkheads on a vessel is referred to as the _____. | permissible length | floodable length | factor of subdivision | compartment standard |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 2371 | Damaged bulkheads often take a permanent set which is independent of the panting or bulge caused by water pressure. To control this, you should _____. | install shoring so that it pushes on the damaged bulkhead while supporting it | use jacks or chain falls to remove the set before installing shores | install shoring so the shoring supports the damaged bulkheads without pushing on them | place sandbags by the bulkhead without installing shores |
| 2372 | Floors aboard ship are _____. | longitudinal angle bars fastened to a surface for strength | frames to which the tank top and bottom shell are fastened on a double bottomed ship | longitudinal beams in the extreme bottom of a ship from which the ships ribs start | transverse members of the ships frame which support the decks |
| 2373 | The vessels quarter is located _____. | on either side of the stern | abeam | dead astern | just forward of the beam on either side |
| 2374 | Odorous cargoes are those that _____. | are liquid but are in containers | give off fumes that may damage other cargoes | are exceptionally dusty and leave a residue | are susceptible to damage by tainting |
| 2375 | Ullages are measured from _____. | the tank top bushing | the tank ceiling | an above deck datum | the thievage mark |
| 2376 | Aboard ship, vertical flat plates running transversely and connecting the vertical keel to the margin plates are called _____. | floors | intercostals | girders | stringers |
| 2377 | Frames to which the tank top and bottom shell are fastened are called _____. | intercostals | stringers | tank top supports | floors |
| 2378 | Floors aboard ship are _____. | found in passenger and berthing spaces only | large beams fitted in various parts of the vessel for additional strength | vertical transverse plates connecting the vertical keel with the margin plates | also called decks |
| 2379 | The ceiling is _____. | a wooden protection placed over the tank top | the overhead in berthing compartments | material driven into seams or cracks to prevent leaking | None of the options are correct |
| 2380 | The wooden planking that protects the tank top from cargo loading is called _____. | shores | ceiling | toms | frames |
| 2381 | A set of interior steps on a ship leading up to a deck from below is know as _____. | a companion way | tween-decks | stairs | All of the options |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 2382 | Battens are fitted in cargo holds across the frames of the vessel from the turn of the bilge upward. The purpose of these cargo battens is _____. | to provide fittings to which cargo lashings may be secured | for securing a snatch block when snaking cargo into the wings of the hold | to support the dunnage floors which are laid down between tiers of cargo | to prevent cargo from coming in contact with the vessels frames or shell plating |
| 2383 | What is a cofferdam? | Void or empty space separating two tanks | Tube fitted to an ullage hole | Area the product is loaded into | Opening in the deck used for cleaning a tank |
| 2384 | Which refers to the depth of a petroleum product in a tank? | Ullage | Innage | Outage | Thievage |
| 2385 | The beam of a vessel refers to the _____. | width of the vessel | depth between decks | internal cubic capacity | molded depth of the vessel |
| 2386 | The space above the engine room is called the _____. | middle hatch | gold locker | noble | fidley |
| 2387 | A strongback refers to a _____. | centerline vertical bulkhead | bar securing a cargo port | spanner stay | deep beam |
| 2388 | A vessels quarter is that section which is _____. | on either side of the stern | abeam | dead astern | just aft of the bow |
| 2389 | Where should the foundation supports for towing bitts terminate? | On deck, aft of the towing winch | In the frames or other substantial structural members below decks | On the deck plates in the engineroom | Forward of the towing winch |
| 2390 | A vessel having continuous closely spaced transverse strength members is _____. | cellular framed | longitudinally framed | transversely framed | web framed |
| 2391 | Which structural members improve a towing vessels chance of surviving punctured shell plating? | Transverse watertight bulkheads | Stringers | Longitudinals | The rake |
| 2392 | When considering a vessels stability, which spaces in a general cargo vessel are the best locations for the carriage of bulk grain? | Tween-decks | Lower holds at the ends of the vessel | Deep tanks | Lower holds |
| 2393 | Ships officers should check every cargo compartment after it is filled with bulk grain to ensure _____. | all lighting circuits are energized | all void spaces are filled | the heavier grade is in the lower hold | the correct grade of cargo has been loaded |
| 2394 | Lighter longitudinal stiffening frames on the vessels side plating are called _____. | stringers | side frames | side stiffeners | intercostals |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 2395 | On a single-screw vessel the stern frame _____. | transfers the driving force of the propeller to the hull | provides foundations for the main propulsion engines | furnishes support to the rudder, propeller shaft, and transom frame | provides foundations for after mooring winches |
| 2396 | Insufficient space between the hull and bottom in shallow water will prevent normal screw currents resulting in _____. | All of the choices | waste of power | sudden sheering to either side | sluggish rudder response |
| 2397 | The terms cant frame and counter are associated with the vessels _____. | forecastle | steering engine | cargo hatch | stern |
| 2398 | Panting frames are located in the _____. | after double bottoms | forward double bottoms | fore and after peaks | centerline tanks on tankships |
| 2399 | The terms ceiling and margin plate are associated with the _____. | tank top | crews quarters | engine room | main deck |
| 2400 | The projecting lugs of the rudderpost which furnish support to the rudder are called _____. | bases | rudder lugs | pintles | gudgeons |
| 2401 | A term applied to the bottom shell plating in a double-bottom ship is _____. | outer bottom | tank top | shear plating | bottom floor |
| 2402 | The purpose of sheer in ship construction is to _____. | eliminate the need for butt straps | allow the ship to ride waves with drier decks | give greater strength at the deck edge | eliminate the need for margin plates |
| 2403 | The upward slope of a ships bottom from the keel to the bilge is known as _____. | camber | slope | deadrise | keel height |
| 2404 | When the longitudinal strength members of a vessel are continuous and closely spaced, the vessel is _____. | longitudinally framed | transversely framed | intermittently framed | web framed |
| 2405 | The margin plate is the _____. | uppermost continuous strake of plating on the shell of a vessel | plate which sits atop the center vertical keel | outer strake of plating on each side of the main deck of a vessel | outboard strake of plating on each side of an inner bottom |
| 2406 | The system of valves and cargo lines in the bottom piping network of a tanker that connects one section of cargo tanks to another section is called a _____. | runaround | come-along | crossover | manifold |

| | | | | | |
|---|---|---|---|---|---|
| 2407 | The inner bottom is the _____. | tank top | compartment between the tank top and shell of the vessel | inner side of the vessels shell | space between two transverse bottom frames |
| 2408 | One function of a bulwark is to _____. | prevent stress concentrations on the stringer plate | help keep the deck dry | reinforce the side stringers | protect against twisting forces exerted on the frame of the vessel |
| 2409 | In ship construction, frame spacing is _____. | uniform over the length of the vessel, with the exception of the machinery spaces, where it is reduced due to increased stresses | uniform over the length of the vessel | reduced at the bow and stern | greater at the bow and stern |
| 2410 | In a longitudinally-framed ship, the longitudinal frames are held in place and supported by athwartship members called _____. | margin plates | stringers | floors | web frames |
| 2411 | Transverse frames are more widely spaced on a ship that is designed with the _____. | longitudinal system of framing | centerline system of framing | isometric system of framing | transverse system of framing |
| 2412 | The floors in a vessels hull structure are kept from tripping, or folding over, by _____. | face plates | transverse deck beams | longitudinal deck beams | bottom longitudinals |
| 2413 | Vertical structural members attached to the floors that add strength to the floors are called _____. | breast hooks | stiffeners | buckler plates | boss plates |
| 2414 | What is NOT an advantage of double bottom ships? | The floors and longitudinals distribute the upward push of the water on the ships bottom. | The tank top forms a second skin for the vessel. | The center of gravity of a loaded bulk cargo ship may be raised to produce a more comfortable roll. | They are less expensive to construct because of increased access space. |
| 2415 | Tonnage openings must be closed by means of _____. | steel plates | press board | steel hatch boards | wooden hatch boards |
| 2416 | Reinforcing frames attached to a bulkhead on a vessel are called _____. | side longitudinals | brackets | stiffeners | intercostals |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 2417 | Which statement is TRUE concerning protection of double bottom tanks against excessive pressure? | The tanks must be protected by overflows. | The total area of the vents or the overflow shall be at least 125% of the area of the fill line. | There must be twice as much vent area as the area of the fill line. | Each vent for the tank must be equal to the area of the tank filling line. |
| 2418 | A cofferdam is _____. | made by placing two bulkheads a few feet apart | any deck below the main deck and above the lowest deck | a member that gives fore-and-aft strength | a heavy fore-and-aft beam under the deck |
| 2419 | To determine the weight capacity of a deck in a cargo hold, you would refer to the _____. | deadweight scale | cubic capacity tables | deck capacity plan | general arrangement plan |
| 2420 | A crack in the deck plating of a vessel may be temporarily prevented from increasing in length by _____. | slot-welding the crack | cutting a square notch at each end of the crack | welding a doubler over the crack | drilling a hole at each end of the crack |
| 2421 | Which statement about damage control is TRUE? | A hole in the hull at the waterline is more dangerous than a hole below the inner bottom. | The amount of water entering a ship through a hole varies inversely to the area of the hole | Water flowing into a lower compartment on a ship is more dangerous than water on deck or flowing into an upper compartment. | Water flowing over the focsle bulwark is more dangerous than a hole in the hull at the waterline. |
| 2422 | Repairing damage to the hull at or above the waterline reduces the threat of _____. | capsizing | wind heel | continued progressive flooding | free surface effects |
| 2423 | When bunkering is complete, the hoses should be _____. | stowed vertically and allowed to drain | washed out with hot soapy water | drained, blanked off, and stored securely | cleaned internally with a degreaser |
| 2424 | Small oil spills on deck can be kept from going overboard by _____: | plugging the scuppers | driving wooden plugs into the vents | closing the lids on the vents | plugging the sounding pipes |
| 2425 | The scuppers had been plugged as required at the time an oil spill occurs on deck. After shutting down the transfer, the engineroom should first be informed and then _____. | remove the plugs from the scuppers | rig a fire hose and call for water on deck | sound the general alarm | spread an absorbent material, such as sawdust |
| 2426 | A precaution you should take before bunkering is to _____ | plug the vents | plug the scuppers | plug the sounding pipes | close the lids on the vents |
| 2427 | Most minor spills of oil products are caused by _____. | human error | equipment failure | major casualties | unforeseeable circumstances |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 2428 | Which substance is NOT considered to be "Oil" under the pollution prevention regulations? | Petroleum and fuel oil | Oil refuse and oil mixed with wastes | Sludge | Oil mixed with dredge spoil |
| 2429 | When oil is accidentally discharged into the water, what should you do after reporting the discharge? | Obtain your permit from the Corps of Engineers | Contain the oil and remove as much of it as possible from the water. | Throw sand on the water to sink the oil. | Throw chemical agents on the water to disperse the oil. |
| 2430 | On a tankship, sanitary inspections of the crew's quarters are the responsibility of the _____. | Master and Chief Engineer | Master and Second Mate | Master and union delegate | Master and Chief Mate |
| 2431 | When a vessel violates the oil pollution laws, who may be held responsible? | Master only | Owners only | Any individual connected with the vessel involved in the operation | Licensed officers only |
| 2432 | Spreading oil on the open sea has the effect of _____. | diminishing the height of the seas | lengthening the distance between successive crests | increasing the height of the seas | preventing the wave crests from breaking |
| 2433 | The preferred type of pollution control for oil spills on the water is(are) _____. | booms | straw | skimmers | chemical dispersants |
| 2434 | Fueling results in the collection of waste oil in drip pans and containers. Which is an approved method of disposing of the waste oil? | Draining it overboard when the vessel gets underway | Adding sinking agents and discharging it into the water | Placing it in proper disposal facilities | Mixing it with dispersants before draining it overboard |
| 2435 | Plastic material may be discharged overboard from a vessel if it is _____. | 3 miles from shore | 25 miles from shore | 12 miles from shore | None of the above |
| 2436 | Why is it important for fuel oil tank not to be topped off when loading cold oil? | The change in its specific volume when heated may cause an overflow | Air pockets may cause the fuel oil to bubble out of the ullage hole | Increased viscosity of the product needs higher loading pressure which increases the chance of spill | The fuelling valve may become stuck closed and cause the fuel oil to spill before the valve can be opened |
| 2437 | SOPEP means _____. | Spill of Oil Prevention and Environmental Protection | Shipboard Oil Prevention and Environmental Protection | Shipboard Oil Pollution and Emergency Plans | Shipboard Oil Pollution Emergency Protection |
| 2438 | Before a vessel can pump oily water within a Special Area, it has to comply with the following conditions EXCEPT: | have an oily water separating system in operation | it must be more than 12 miles from the nearest coast | that the filter system have an automatic cut-off when the wastes are found to exceed 15 ppm of oily residue | be underway |

| | | | | | |
|---|---|---|---|---|---|
| 2439 | Which should be done with the ashes from your vessel's incinerator which has burned packages containing plastic? | discharge overboard provided you are not in a river or estuary | discharge at sea provided you are at least 12 miles offshore | discharge at sea provided you are more than 25 miles offshore | discharge to shore facility only |
| 2440 | The scuppers had been plugged as required at the time an oil spill occurs on deck. After shutting down the transfer, the engineroom should first be informed and then _____. | spread an absorbent material, such as sawdust | rig a fire hose and call for water on deck | remove the plugs from the scuppers | sound the general alarm |
| 2441 | The standard outside diameter pipelines to enable pipes of reception facilities to be connected with the ships discharge pipelines for residues from machinery bilges should be_____. | 225 mm | 235 mm | 215 mm | 250 mm |
| 2442 | Pipelines should be standard to enable pipes of reception facilities to be connected with the ships discharge pipelines for residues from machinery bilges. Its bolt circle diameter should be _____. | 181 mms. | 185 mms. | 179 mms. | 183 mms. |
| 2443 | To whom is the first report rendered in the oil pollution contingency plan of the vessel? | port authorities | Coast guard | Ship's agent | Ship's owner |
| 2444 | Most minor spills of oil products are caused by _____. | equipment failure | major casualties | unforeseeable circumstances | human error |
| 2445 | Which substance is NOT considered to be "Oil" under the pollution prevention regulations? | Oil refuse and oil mixed with wastes | Oil mixed with dredge spoil | Petroleum and fuel oil | Sludge |
| 2446 | When oil is accidentally discharged into the water, what should you do after reporting the discharge? | Contain the oil and remove as much of it as possible from the water. | Throw chemical agents on the water to disperse the oil. | Throw sand on the water to sink the oil. | Obtain your permit from the Corps of Engineers |
| 2447 | On a tankship, sanitary inspections of the crew's quarters are the responsibility of the _____. | Master and Chief Mate | Master and Second Mate | Master and union delegate | Master and Chief Engineer |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 2448 | Which substance is NOT considered to be "Oil" under the pollution prevention regulations? | Oil mixed with dredge spoil | Petroleum and fuel oil | Sludge | Oil refuse and oil mixed with wastes |
| 2449 | When a vessel violates the oil pollution laws, who may be held responsible? | Owners only | Master only | Licensed officers only | Any individual connected with the vessel involved in the operation |
| 2450 | Spreading oil on the open sea has the effect of _____. | lengthening the distance between successive crests | diminishing the height of the seas | preventing the wave crests from breaking | increasing the height of the seas |
| 2451 | The preferred type of pollution control for oil spills on the water is(are) _____. | booms | straw | skimmers | chemical dispersants |
| 2452 | Fueling results in the collection of waste oil in drip pans and containers. Which is an approved method of disposing of the waste oil? | Adding sinking agents and discharging it into the water | Placing it in proper disposal facilities | Mixing it with dispersants before draining it overboard | Draining it overboard when the vessel gets underway |
| 2453 | Plastic material may be discharged overboard from a vessel if it is _____. | 12 miles from shore | 3 miles from shore | 25 miles from shore | None of the above |
| 2454 | In reference to accidental oil pollution, the most critical time during bunkering is when _____. | hoses are being blown down | final topping off is occurring | hoses are being disconnected | you first start to receive fuel |
| 2455 | Which statement is TRUE of a gasoline spill? | It is visible for a shorter time than a fuel oil spill. | It is not covered by the pollution laws. | It does little harm to marine life. | It will sink more rapidly than crude oil. |
| 2456 | Which statement is TRUE concerning small oil spills? | They usually disappear quickly. | They usually stay in a small area. | They may cause serious pollution as the effect tends to be cumulative. | A small spill is not dangerous to sea life in the area. |
| 2457 | The term "discharge", as it applies to the pollution regulations, means _____. | Gassing Up &Incinerating | spilling, leaking, pumping | inerting & venting | ballasting & deballasting |
| 2458 | Pollution regulations require that each scupper in an enclosed deck area have a _____. | mechanical means of closing | wooden plug | soft rubber plug | two-piece soft patch |
| 2459 | The operator of a vessel subject to the pollution regulations shall keep a written record available for inspection by the COPT or OCMI containing _____. | the name of each person currently designated as a person in charge | the date and result of the most recent test on the system relief valves | hose information including the minimum design burst pressure for each hose | All of the above |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 2460 | The operator of each vessel subject to the pollution regulations is NOT required to keep written records of _____. | cargoes carried and dates delivered, including destinations | hose information not marked on the hose | the date and results of the most recent equipment inspection | the name of each person designated as a person in charge |
| 2461 | The term, "cargo tank length", as used in part 157 of the Pollution Regulations, means the _____. | diagonal measurement of a cargo tank | length from the forward bulkhead of the forwardmost cargo tanks to the after bulkhead of the aftermost cargo tanks | greatest distance between two opposite cargo tank bulkheads | length of any individual cargo space, from bulkhead to bulkhead |
| 2462 | the shipboard Oil Pollution Emergency Plan must include _____. | an explanation and purpose of the plan | all information ordinarily provided in the Oil Record Book | a one-line schematic of the plan to be implemented | the operating instructions for any and all oily-water separators installed aboard the vessel |
| 2463 | If you observe any situation which presents a safety or pollution hazard during fuel transfer operations, what action should you take FIRST? | Close the valves at the transfer manifold | Shut down the transfer operation | Notify the person in charge of the shore facility | Sound the fire alarm |
| 2464 | Under the Pollution Regulations, garbage disposal records must be kept _____. | one year | until the next Coast Guard inspection | two years | until the end of the voyage |
| 2465 | Which is NOT a mandatory part of the shipboard Oil Pollution Emergency Plan? | Diagrams | Reporting requirements | Steps to control a discharge | National and local coordination |
| 2466 | Which list is NOT required to be provided as part of the appendices of the Shipboard Oil Pollution Emergency Plan? | A list of agencies or officials of Coastal State Administrators responsible for receiving and processing incident reports. | A list specifying who will be responsible for informing the parties listed and the priority in which they must be notified. | A list of personnel duty assignments. | A list of agencies or officials in regularly visited ports. |
| 2467 | Which is a mandatory section of the shipboard Oil Pollution Emergency Plan? | Reporting requirements | Removal equipment list | Planned exercises | List of individuals required to respond |
| 2468 | The regulations that were passed to implement MARPOL 73/78 concerning oil pollution apply to a U.S. flag vessel that sails on which waters? | All of the above | International waters | Inland waters only | Great Lakes only |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 2469 | Under the Pollution Regulations, when you dump garbage in to the sea you must _____. | keep a record for two years | notify the U.S. Coast Guard | make an entry in the Official Logbook | No action is required if you are more than 25 miles from land and no plastic materials are dumped. |
| 2470 | When amendments are made to the Shipboard Oil Pollution Emergency Plan, the revisions must be submitted to the Coast Guard _____. | one month before the anniversary date of the plan | and cannot be implemented without approval | and can be implemented without immediate approval as long as final approval is received within six months of submission | six months before the end of the approval period |
| 2471 | A shipboard Oil Pollution Emergency Plan is required of _____. | an oil tanker of 400 gross tons and above, or other ships of 150 gross tons and above | any barge or ship constructed or operated in such a manner that no oil in any form can be carried aboard | all vessels, regardless of size and commercial application | an oil tanker of 150 gross tons and above, or other ship of 400 gross tons and above |
| 2472 | The approval period for a shipboard Oil Pollution Emergency Plan expires after _____. | three years | two years | five years | four years |
| 2473 | If you observe any situation which presents a safety or pollution hazard during fuel transfer operations which action should you take FIRST? | Shut down the operation. | Close the valves at the manifold. | Notify the person in charge of the shore facility. | Sound the general alarm. |
| 2474 | To enable pipes of reception facilities to be connected with the ships discharge pipelines for residues from machinery bilges. Pipelines should be standard with an outside diameter of: | 200 mm | 185 mm | 183 mm | 180 mm |
| 2475 | What is the bolt circle diameter of a standard pipeline to enable pipes of reception facilities to be connected for residue from machinery bilges is: | 190 mm | 200mm | 195mm | 183mm |
| 2476 | The oil record book maintained on a vessel not engaged in a foreign trade shall be maintained on board for not less than: | 12 months | 48 months | 36 months | 24 months |

| | | | | | |
|---|---|---|---|---|---|
| 2477 | To enable pipes of reception facilities to be connected with the ships discharge pipelines for residues from machinery bilges. Pipelines should be standard with an outside diameter of: | 200 mm | 183 mm | 185 mm | 180 mm |
| 2478 | What is the bolt circle diameter of a standard pipeline to enable pipes of reception facilities to be connected for residue from machinery bilges is: | 183mm | 190 mm | 200mm | 195mm |
| 2479 | The oil record book maintained on a vessel not engaged in a foreign trade shall be maintained on board for not less than: | 36 months | 24 months | 12 months | 48 months |
| 2480 | What is the meaning of "Slop Tank" as per Marpol? | A tank specifically designed for the collection of tank drainings, washings or other oily mixtures | Any tank where slops sludge's are collected | A tank used for tank cleaning provided with heat coils | The two most aftward fitted wing tanks or the most aftward fitted center tank |
| 2481 | In the Oil Record Book a comprehensive list of operational items are grouped into operational section codified by a/an: | symbols | number | letter | abbreviation |
| 2482 | The Oil Record Book must be maintained on board ship for: | not less than 3 years and be readily available for inspection | the duration of the ship's active employment | an annual inspection | 6 months and then submitted to the nearest Marine Safety Office |
| 2483 | Where do you record the discharged at sea of bilge water containing any oil from machinery spaces of a dry cargo vessel? | sounding book | maintenance record to | oil record book | appropriate log book |
| 2484 | When must the Master of a vessel log the position of load line marks in relation to the surface of the water in the Official Logbook? | At the change of every watch | Only when in fresh or brackish water | Once a day | Product carrier |
| 2485 | What is required for each scupper in an enclosed area, to prevent oil spill? | mechanical means of closing | wooden plug and cement | biogradable rubber plug | plastic plug attached to the ship by chain |
| 2486 | In cleaning up an oil spill, straw is an example of a: | blocker | sorbent | chemical agent | none of these |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 2487 | A noxious liquid substance which, if discharged into the sea from tank cleaning or deballasting operations, are deemed to present a minor hazard to either marine resources or human health. What is this category? | Category Z | Category A | Category X | Category Y |
| 2488 | The Oil Record Book must be available at all times for examination by _____ of any port when within the jurisdiction of the State. | Coastguard | Maritime industry Board Inspectors | Classification Society Inspectors under whom the vessel is classed | Port State control Inspectors |
| 2489 | Which oil spill clean-up technique remove the oil from the surface of the water by "mixing" it into the water column? | recover | disperse | in situ burning | containment |
| 2490 | When ballasting cargo tanks, _____ should be recorded in the Cargo Record Book for ships carrying noxious liquid substances. | Identity of tank(s) | Number of ballast tanks | Density of the ballast | Weight of ballast |
| 2491 | The oil record book shall be completed in every occasion on a tank to tank basis. For all ships regarding machinery space operations, the following takes place except: | Discharged overboard or disposal otherwise of bilge water | Ballasting and cleaning of fuel tanks | Disposal of oily residues (sludge) | Internal transfer of oil cargo during the voyage |
| 2492 | The water washing of cargo tanks and slop tanks containing residues of certain substances may produce dangerous reaction and should be carefully considered. | Discharge hazard | electrostatic hazard | reception facilities ashore | fumes hazard |
| 2493 | When topping off fuel tanks as a precautions against oil spill, you should: | notify the shore pumping station to reduce rate as tanks near full capacity | close the deck filling valve to reduce the pumping rate | fill the tank to the bottom of the expansion tank | close all tank vents to prevent overflow |
| 2494 | No person may transfer oil to or from a vessel unless the person in charge: | has in his or her possession a copy of the vessel's Oil Record Book | has in his or her possession a valid Certificate of Inspection or Tank Vessel Examination Letter | has notified the captain of the port at least 24 hours before beginning each oil transfer operation | is in the immediate vicinity and immediately available to the oil transfer personnel |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 2495 | The most critical time for preventing an accidental oil spill during bunkering is when the: | fuel begins to come aboard | hoses are being blown down | hoses are being disconnected | tanks are being topped off |
| 2496 | Which one need not be recorded when an oil tanker discharged water from slop tanks? | date and position of ship at finish of discharge to sea | identity of tank(s) | date and position of ship at start of discharge to sea | Date and time started and duration of operation |
| 2497 | What is the meaning IOPP Certificates issued by any government? | International Oil Pollution Prevention Certificate | International Oil Payment Provisional Certificate | International Oil Prevention and Pollution Cartel | International Oil Providers Provisionary certificate |
| 2498 | The guidelines developed to assist in the preparation of SOPEP comprise three primary sections EXCEPT: | mandatory provisions | Preface | non-mandatory provisions | Introduction |
| 2499 | Which is correct with regards to spillage of gasoline? | it will sink more rapidly than crude oil | it is not covered by pollution laws | it does little harm to marine life | visible for a shorter time than a fuel oil spill |
| 2500 | Which statement is true in a gasoline spill? | It does little harm to marine life | It will sink more rapidly oil | It is invisible for a shorter time than crude oil | It is not covered by pollution laws |
| 2501 | While leaving post, your vessel is involved in a collision resulting in a small spill of oil. What is true regarding the spill of the oil? | small oil spills disappear quickly | it will be confined in a small area because it is small | oil will sink so it will not be dangerous | small spills can cause danger to sea life |
| 2502 | When vessel violates the oil pollution laws, who may be held responsible? | Owners only | Any individual connected with the vessel involved in the operation | Master only | watch keeping officers/engineers only |
| 2503 | The transfer procedure for oil products are required to be posted: | Where they can be easily seen | Pump room | Mess hall | In the bridge |
| 2504 | When vessel is stranded, discharge or probable discharge of harmful substances should be reported to the: | nearest US coast guard | nearest classification society | nearest coast radio station | nearest NCB surveyor |
| 2505 | What is the meaning of "Harmful Substances" under Marpol? | Any substances creating harm to health and life or able to damage amenities | Hydrocarbons in any form | Oils and Fuels | Petroleum products and petrochemicals |
| 2506 | When ships are on short voyages, how often is the quantity residue recorded in the Machinery Space Oil Record Book? | Once a month | Once a week | Once every two weeks | Twice a week |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 2507 | When ballasting through cargo piping system to prevent escape of oil into the sea, the first thing to do is to: | Open the suction valve, then start the cargo pump | Open block valve, then start cargo the pump | Open sluice valve, then start the cargo pump | Start the cargo pump, then open sea suction valve |
| 2508 | "Peck and Hale" gear is mostly used for storing: | Automobiles | Baled cargoes | Palletized cargoes | Large wooden crates |
| 2509 | The Marpol Convention shall not apply to: | Warships | Passenger ships | mobile oil drilling units | vessels less than 500 gross tonnage |
| 2510 | The oil record book is required to be carried on board by: | all vessels exceeding 150 GRT and using fuel oil | tanker only | passengers vessels | cargo vessels |
| 2511 | The purpose of establishing emergency towing arrangement onboard tankers is to facilitate salvage and towing operations and: | protect the interests of cargo owners | prevent undue delays to ship during engine breakdowns | prevent risk of environmental pollution | ensure easier salvage works |
| 2512 | You are on board a dry cargo vessel and she is in port, if it becomes necessary to pump bilges, which of the following procedures should be followed? | pump overboard during the hour of darkness | pump only if discharged outlet is led to shore tank, barge or tank truck | Pump only on the outgoing tide | pump only as much as necessary |
| 2513 | Type of boom that is made of fibers that absorb oil but not water. | sorbent type | rapid deployment type | ro type | fence type |
| 2514 | Under marking and labeling, packages of harmful substance containing small quantities may be _____ from the marking requirements. | DOCUMENTED | EXEMPTED | PROVIDED WITH DETAILED STOWAGE PLAN | SEPARATED |
| 2515 | Spills of persistent oils with greater than 1.0 specific gravity: | should be easily dispersed with dispersants | should be recovered with skimmers | do not readily evaporate and are difficult to recover | dissipate with wind and current |
| 2516 | These are used to prevent from oil spreading. | dispersant | sorbents | skimmers | booms |
| 2517 | This reduces the size of oil droplets and the wave action keeps the tiny droplets in the water column eventually breaking down naturally. | dispersant | booms | sorbents | skimmers |
| 2518 | On the completion of oil transfer operation, pollution prevention regulation requires that all: | Soundings should be entered in the oil record book | Valves used during transfer shall be closed | All of the choices | Hose should be blown down with air |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 2519 | When using fuel composed of blends from hydrocarbons derived from petroleum refining, test procedures and measurement method shall be in accordance with the: | NOx Technical Code | all of these | SOx Technical Code | NOxSOx Technical Code |
| 2520 | With regards to accidental oil pollution, the most critical time during bunkering is when: | Start to receive fuel | Hoses are being blown down | When hoses are being disconnected | During final topping |
| 2521 | A sewage system shall be fitted with facilities to the satisfaction and approved by the Administration , for the temporary storage of sewage when the ship is less than 3 nautical miles from the nearest land. What do you call this system? | comminuting and disinfecting system | treatment plant | storage system | disinfecting system |
| 2522 | What does the Acronym SECA under Marpol Annex VI stand for? | Sulphur Emission Control Area | Sulfide Emission Control Area | Sox Emission Control Area | Sulphuric Extraction Command Area |
| 2523 | In the Oil record Book, each operation specifies in the regulation must be noted by the: | Officer or OIC of the operation and each completed page will be signed by the master | When the operations are completed will be signed by the Officer or OIC of the operation | The entries match operations completed after which is signed by the Master | The Chief Officer is to signed when the operations are completed and countersigned by the Master |
| 2524 | Two signatures are essential in the Oil Record Book of a dry-cargo vessel. These are: | the Master and the Chief Engineer | the Master and the Chief Mate | the Chief Mate and Chief Engineer | the Master and the Officer in charge of the operations |
| 2525 | The use of sinking and dispersing agents for removal of surface oil is: | the most common method used in the United States and European countries | too expensive for common use | generally harmful to sea life | generally safe to sea life |
| 2526 | Under the International Convention for the Prevention of Pollution from Ships,1973, it means the government of the state whose authority the ship is operating. | Administration | Treaty | U.S. Coast Guard | State |

| | | | | | |
|---|---|---|---|---|---|
| 2527 | A term that refers to any cargo space in which, after loading and trimming as required under A10.2, the bulk grain is at its highest possible. | Filled compartment, untrimmed | Unfilled compartment, trimmed | Unfilled compartment, untrimmed | Filled compartment, trimmed |
| 2528 | Which is NOT a type oil skimmer? | Fence | Oleophilic | Weir | Dynamic Incline Plane |
| 2529 | To enable pipes of reception facilities to be connected with the ships discharge pipelines for residues from machinery bilges. Pipelines should be standard with an outside diameter of: | 185 mm | 183 mm | 180 mm | 200 mm |
| 2530 | What is the bolt circle diameter of a standard pipeline to enable pipes of reception facilities to be connected for residue from machinery bilges is: | 190 mm | 200mm | 183mm | 195mm |
| 2531 | The oil record book maintained on a vessel not engaged in a foreign trade shall be maintained on board for not less than: | 36 months | 12 months | 48 months | 24 months |
| 2532 | What is the meaning of "Slop Tank" as per Marpol? | A tank specifically designed for the collection of tank drainings, washings or other oily mixtures | Any tank where slops sludge's are collected | A tank used for tank cleaning provided with heat coils | The two most aftward fitted wing tanks or the most aftward fitted center tank |
| 2533 | In the Oil Record Book a comprehensive list of operational items are grouped into operational section codified by a/an: | abbreviation | letter | symbols | number |
| 2534 | The Oil Record Book must be maintained on board ship for: | an annual inspection | the duration of the ship's active employment | 6 months and then submitted to the nearest Marine Safety Office | not less than 3 years and be readily available for inspection |
| 2535 | Where do you record the discharged at sea of bilge water containing any oil from machinery spaces of a dry cargo vessel? | appropriate log book | maintenance record to | oil record book | sounding book |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 2536 | When must the Master of a vessel log the position of load line marks in relation to the surface of the water in the Official Logbook? | Product carrier | Once a day | At the change of every watch | Only when in fresh or brackish water |
| 2537 | What is required for each scupper in an enclosed area, to prevent oil spill? | wooden plug and cement | plastic plug attached to the ship by chain | mechanical means of closing | biogradable rubber plug |
| 2538 | A noxious liquid substance which, if discharged into the sea from tank cleaning or deballasting operations, are deemed to present a minor hazard to either marine resources or human health. What is this category? | Category X | Category Y | Category A | Category Z |
| 2539 | The Oil Record Book must be available at all times for examination by _____ of any port when within the jurisdiction of the State. | Port State control Inspectors | Classification Society Inspectors under whom the vessel is classed | Coastguard | Maritime industry Board Inspectors |
| 2540 | Which oil spill clean-up technique remove the oil from the surface of the water by "mixing" it into the water column? | recover | disperse | containment | in situ burning |
| 2541 | When ballasting cargo tanks, _____ should be recorded in the Cargo Record Book for ships carrying noxious liquid substances. | Number of ballast tanks | Weight of ballast | Density of the ballast | Identity of tank(s) |
| 2542 | The oil record book shall be completed in every occasion on a tank to tank basis. For all ships regarding machinery space operations, the following takes place except: | Internal transfer of oil cargo during the voyage | Disposal of oily residues (sludge) | Discharged overboard or disposal otherwise of bilge water | Ballasting and cleaning of fuel tanks |
| 2543 | The water washing of cargo tanks and slop tanks containing residues of certain substances may produce dangerous reaction and should be carefully considered. | electrostatic hazard | reception facilities ashore | Discharge hazard | fumes hazard |
| 2544 | When topping off fuel tanks as a precautions against oil spill, you should: | fill the tank to the bottom of the expansion tank | close all tank vents to prevent overflow | close the deck filling valve to reduce the pumping rate | notify the shore pumping station to reduce rate as tanks near full capacity |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 2545 | No person may transfer oil to or from a vessel unless the person in charge: | is in the immediate vicinity and immediately available to the oil transfer personnel | has in his or her possession a copy of the vessel's Oil Record Book | has notified the captain of the port at least 24 hours before beginning each oil transfer operation | has in his or her possession a valid Certificate of Inspection or Tank Vessel Examination Letter |
| 2546 | The most critical time for preventing an accidental oil spill during bunkering is when the: | tanks are being topped off | hoses are being disconnected | hoses are being blown down | fuel begins to come aboard |
| 2547 | Which one need not be recorded when an oil tanker discharged water from slop tanks? | date and position of ship at finish of discharge to sea | identity of tank(s) | Date and time started and duration of operation | date and position of ship at start of discharge to sea |
| 2548 | What is the meaning IOPP Certificates issued by any government? | International Oil Pollution Prevention Certificate | International Oil Payment Provisional Certificate | International Oil Prevention and Pollution Cartel | International Oil Providers Provisionary certificate |
| 2549 | The guidelines developed to assist in the preparation of SOPEP comprise three primary sections EXCEPT: | mandatory provisions | Preface | Introduction | non-mandatory provisions |
| 2550 | Which is correct with regards to spillage of gasoline? | visible for a shorter time than a fuel oil spill | it is not covered by pollution laws | it does little harm to marine life | it will sink more rapidly than crude oil |
| 2551 | Which statement is true in a gasoline spill? | It is not covered by pollution laws | It will sink more rapidly oil | It is invisible for a shorter time than crude oil | It does little harm to marine life |
| 2552 | While leaving post, your vessel is involved in a collision resulting in a small spill of oil. What is true regarding the spill of the oil? | it will be confined in a small area because it is small | oil will sink so it will not be dangerous | small spills can cause danger to sea life | small oil spills disappear quickly |
| 2553 | When vessel violates the oil pollution laws, who may be held responsible? | Any individual connected with the vessel involved in the operation | watch keeping officers/engineers only | Master only | Owners only |
| 2554 | The transfer procedure for oil products are required to be posted: | In the bridge | Mess hall | Pump room | Where they can be easily seen |
| 2555 | When vessel is stranded, discharge or probable discharge of harmful substances should be reported to the: | nearest classification society | nearest US coast guard | nearest coast radio station | nearest NCB surveyor |
| 2556 | What is the meaning of "Harmful Substances" under Marpol? | Any substances creating harm to health and life or able to damage | Hydrocarbons in any form | Oils and Fuels | Petroleum products and petrochemicals |

| | | | | | |
|---|---|---|---|---|---|
| | | amenities | | | |
| 2557 | When ships are on short voyages, how often is the quantity residue recorded in the Machinery Space Oil Record Book? | Twice a week | Once every two weeks | Once a month | Once a week |
| 2558 | When ballasting through cargo piping system to prevent escape of oil into the sea, the first thing to do is to: | Open the suction valve, then start the cargo pump | Start the cargo pump, then open sea suction valve | Open sluice valve, then start the cargo pump | Open block valve, then start cargo the pump |
| 2559 | "Peck and Hale" gear is mostly used for storing: | Automobiles | Baled cargoes | Palletized cargoes | Large wooden crates |
| 2560 | The Marpol Convention shall not apply to: | Passenger ships | vessels less than 500 gross tonnage | Warships | mobile oil drilling units |
| 2561 | The oil record book is required to be carried on board by: | cargo vessels | tanker only | all vessels exceeding 150 GRT and using fuel oil | passengers vessels |
| 2562 | The purpose of establishing emergency towing arrangement onboard tankers is to facilitate salvage and towing operations and: | prevent risk of environmental pollution | ensure easier salvage works | protect the interests of cargo owners | prevent undue delays to ship during engine breakdowns |
| 2563 | You are on board a dry cargo vessel and she is in port, if it becomes necessary to pump bilges, which of the following procedures should be followed? | pump only as much as necessary | Pump only on the outgoing tide | pump overboard during the hour of darkness | pump only if discharged outlet is led to shore tank, barge or tank truck |
| 2564 | Type of boom that is made of fibers that absorb oil but not water. | fence type | rapid deployment type | sorbent type | ro type |
| 2565 | Under marking and labeling, packages of harmful substance containing small quantities may be _____ from the marking requirements. | EXEMPTED | DOCUMENTED | SEPARATED | PROVIDED WITH DETAILED STOWAGE PLAN |
| 2566 | Spills of persistent oils with greater than 1.0 specific gravity: | dissipate with wind and current | should be easily dispersed with dispersants | do not readily evaporate and are difficult to recover | should be recovered with skimmers |
| 2567 | These are used to prevent from oil spreading. | skimmers | booms | dispersant | sorbents |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 2568 | This reduces the size of oil droplets and the wave action keeps the tiny droplets in the water column eventually breaking down naturally. | dispersant | booms | sorbents | skimmers |
| 2569 | On the completion of oil transfer operation, pollution prevention regulation requires that all: | All of the choices | Valves used during transfer shall be closed | Hose should be blown down with air | Soundings should be entered in the oil record book |
| 2570 | When using fuel composed of blends from hydrocarbons derived from petroleum refining, test procedures and measurement method shall be in accordance with the: | NOxSOx Technical Code | all of these | SOx Technical Code | NOx Technical Code |
| 2571 | With regards to accidental oil pollution, the most critical time during bunkering is when: | During final topping | When hoses are being disconnected | Start to receive fuel | Hoses are being blown down |
| 2572 | A sewage system shall be fitted with facilities to the satisfaction and approved by the Administration , for the temporary storage of sewage when the ship is less than 3 nautical miles from the nearest land. What do you call this system? | disinfecting system | storage system | treatment plant | comminuting and disinfecting system |
| 2573 | What does the Acronym SECA under Marpol Annex VI stand for? | Sox Emission Control Area | Sulphur Emission Control Area | Sulphuric Extraction Command Area | Sulfide Emission Control Area |
| 2574 | In the Oil record Book, each operation specifies in the regulation must be noted by the: | The Chief Officer is to signed when the operations are completed and countersigned by the Master | When the operations are completed will be signed by the Officer or OIC of the operation | Officer or OIC of the operation and each completed page will be signed by the master | The entries match operations completed after which is signed by the Master |
| 2575 | Two signatures are essential in the Oil Record Book of a dry-cargo vessel. These are: | the Master and the Officer in charge of the operations | the Master and the Chief Engineer | the Master and the Chief Mate | the Chief Mate and Chief Engineer |
| 2576 | The use of sinking and dispersing agents for removal of surface oil is: | generally safe to sea life | the most common method used in the United States and European countries | too expensive for common use | generally harmful to sea life |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 2577 | Under the International Convention for the Prevention of Pollution from Ships,1973, it means the government of the state whose authority the ship is operating. | Administration | Treaty | U.S. Coast Guard | State |
| 2578 | A term that refers to any cargo space in which, after loading and trimming as required under A10.2, the bulk grain is at its highest possible. | Unfilled compartment, trimmed | Filled compartment, untrimmed | Unfilled compartment, untrimmed | Filled compartment, trimmed |
| 2579 | Which is NOT a type oil skimmer? | Fence | Oleophilic | Weir | Dynamic Incline Plane |
| 2580 | A oil tanker may not discharge an oily mixture into the sea from a cargo tank slop tank or cargo pump room bilge unless which of the following conditions is present? | more than 12 nautical miles from the nearest land | discharging at an instantaneous rate of oil content not exceeding 30 liters per nautical mile | is within Special Areas defined in Regulation 1 (10) of Annex I to MARPOL 73/78 | at anchor or stopped |
| 2581 | If you are bunkering and you close off one tank in the line of tanks being filled the rate of flow to other open tanks on the same line will _____. | increase | stop | decrease | remain constant |
| 2582 | Shipboard Oil Pollution Emergency Plans must be reviewed _____. | and the entire plan resubmitted for approval once every five years six months before expiration | annually by the owner with a letter submitted to the Coast Guard within one month of the anniversary date of the plan approval | annually by the owner with a letter submitted six months before expiration | only once every five years with a letter submitted six months before expiration |
| 2583 | What is the first action you should take to prevent oil from escaping into the sea when ballasting through the cargo piping system? | open block valves then start the cargo pump | open sea suction valves then start the cargo pump | open sluice valves then start the cargo pump | start the cargo pump then open sea suction valves |
| 2584 | Where are the transfer procedures for oil products are required to be posted? | Where they can be easily seen or readily available | In the upper pumproom flat | In the pilothouse | In the officers lounge |
| 2585 | You discharge garbage overboard at sea. When recording your vessels position as required you must include _____. | latitude longitude and approximate depth of water | latitude and longitude only | latitude longitude course speed and a copy of that days noon position slip | latitude longitude and estimated distance from shore |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 2586 | A dry cargo vessel is required to record in the Oil Record Book of the ship the discharge of dirty ballast or cleaning water from fuel oil tanks. Three of the following is essential and must be recorded. Which one is not? | the distance of the ship from the nearest land if not less than 50 miles | method of discharge (whether separator was used) | the distance of the ship from the nearest land if not less than 100 miles | the distance of the ship from the nearest land if not more than 50 miles |
| 2587 | A ship that at any time operates seaward of the outermost boundary of the territorial sea is required to prepare submit and maintain a(n) _____. | synthetic plastic discharge plan | shipboard oil pollution emergency plan | vapor recovery procedures plan | oil discharge plan |
| 2588 | After making the required notification that a large oil spill into the water has occurred the FIRST action should be to _____. | throw grains of sand into the oil | have the vessel move out of the spill area | contain the spread of the oil | apply straw or sawdust on the oil |
| 2589 | The equipment required to remove an on-deck oil spill on a barge transferring oil must either be carried on board or _____. | available by contract with the shore facility | kept at the shoreside hose connection during transfer | on a tug standing by | kept in a protected shoreside location readily accessible |
| 2590 | The purpose of inert gas systems aboard tank vessels is to _____. | provide increase in cargo discharge pressure | allow sufficient oxygen in the tank to sustain life | comply with double hull pollution prevention regulations | prevent outside air from entering the tank |
| 2591 | The ships operations that is required to be logged in the Oil Record Book is _. | Daily inspection of engine room bilges | none of the above | Cleaning of the fuel oil tanks | Shifting suction of main fuel pumpt to reserve fuel oil tank |
| 2592 | The transfer procedures required to be followed on tankships shall contain _____. | a line diagram of the vessels transfer piping | a list of each port of discharge | a current crew list | the duties by name of each person in charge required for each transfer operation |
| 2593 | This substance is soluble with water in all proportion at wash water temperature and is called _____. | liquifying substance | Solidifying substance | High viscosity substance | low viscosity substance |
| 2594 | To do in the event of a small bunker oil spill on deck while fueling is _. | all of these | Wash down the area immediately with a fire hose | none of the above | Cover the area with saw dust |

| | | | | | |
|---|---|---|---|---|---|
| 2595 | To ensure that there are not leakage of bilge of water contaminated by oil from machinery spaces it is required by regulations that the transfer of bilge water to slop tanks or holding tanks be recorded in the Machinery space oil record book. Listed are four information data. Which one is not required? | state quantity incinerated at reception facilities and port | indicate tank(s) | none of these | any of these |
| 2596 | Under MARPOL PROTOCOL II Article III the Tribunal shall consist of _____ members. | Nine | Six | Seven | Three |
| 2597 | What can be done to prevent small oil spills on deck from going overboard? | plugging the scuppers | plugging the sounding pipes | closing the lids on the vents | driving wooden plugs into the vents |
| 2598 | What is the minimum number of bolts required in a permanently connected flange oil hose coupling? | 3 | A bolt must be used in every hole. | 4 | 6 |
| 2599 | Which international body is responsible for drafting the convention prohibiting marine pollution (MARPOL) ? | International Maritime Organization | International Association of Shipping | Maritime Advisory Council | Association of Seafaring Nations |
| 2600 | which of the following is NOT required to be provided as part of the appendixes of the Shipboard Oil Pollution Emergency Plan? | a list of agencies or officials in regularly visited ports | a list of personnel duty assignments | a list which specifies who will be responsible for informing the parties listed and the priority in which they must be notified | a list of agencies or officials of Coastal State administrations responsible for receiving and processing incident reports |
| 2601 | Which vessel is required to have a shipboard oil pollution emergency plan? | any barge or other ship which is constructed or operated in such a manner that no oil in any form can be carried aboard | all vessels regardless of size and commercial application | an oil tanker of 400 gross tons and above or other ships of 150 gross tons and above | an oil tanker of 150 gross tons or above or other ship of 400 gross tons or above |
| 2602 | While operating your oceangoing vessel you must keep a record of any discharge or disposal of garbage. When should these entries be made? | at the time the garbage was disposed | before the end of the voyage | no later than 24 hours after disposal of the garbage | before arriving at your next port |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 2603 | A 30,000 DWT tankship is required to have an IOPP certificate when _____. | engaged in the coastwise trade | carrying cargoes listed in the MARPOL regulations | calling at ports in another country signatory to MARPOL 73/78 | going foreign |
| 2604 | A noxious liquid substance which is not a solidifying substance is: | Non-solidifying substance | solidifying substance | flammable substance | Liquefying substance |
| 2605 | A number of dangerous substances in various IMDG Code classes have been identified as a substance harmful to the: | plants | humans | living animals | marine environment |
| 2606 | A precaution you should take before bunkering is to _____. | plug the sounding pipes | plug the scuppers | plug the vents | close the lids on the vents |
| 2607 | A ship of 400 gross tonnage or more may discharge machinery space while enroute, and she is more than 12 miles from land provided the oil of the effluent is less than _____ parts per million. | 100 | 150 | 200 | 210 |
| 2608 | A ship of 400 gross tonnage or more than an oil tanker may discharge oily machinery space bilge provided she is enroute, more than 12 miles from shore and has in operation a/an _____. | COW facility | anode protection equipment | oil discharge monitoring and control equipment and oily-water separator | cathode protection equipment |
| 2609 | A shipboard Oil Pollution Emergency Plan is required of _____. | an oil tanker of 150 gross tons and above, or other ship of 400 gross tons and above | any barge or ship constructed or operated in such a manner that no oil in any form can be carried aboard | an oil tanker of 400 gross tons and above, or other ships of 150 gross tons and above | all vessels, regardless of size and commercial application |
| 2610 | A solidifying noxious substance with a melting point of less than 15 degrees Centigrade and a temperature of _____ above its melting point at the time of unloading. | not more than 3 degrees Centigrade | not less than 3 degrees Centigrade | not less than 5 degrees Centigrade | not more than 5 degrees Centigrade |
| 2611 | A towing vessel is NOT required to be fitted with radar if it is _____. | used solely for pollution response | used occasionally to assist vessels in distress | less than 49 feet in length | towing alongside |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 2612 | A vessel to which Annex V to MARPOL 73/78 applies is 24 nautical miles from the nearest land. Which type of garbage is prohibited from being discharged? | Metal | Crockery | Dunnage | Glass |
| 2613 | After each operation involving the transfer of oil or oily mixture, an entry shall be recorded in the Oil Record Book _____. | without delay | within 6 hours of completion of the operation | as the operation permits | within 1 hour of completion of the inspection |
| 2614 | After making the required notification that a large oil spill into the water has occurred, what is the FIRST action that should be taken? | throw grains of sand into the oil | contain the spread of the oil | have the vessel move out of the spill area | apply straw or sawdust on the oil |
| 2615 | An individual must be which of the following to serve as the person in charge of oil cargo transfer operations onboard a self-propelled tank vessel? | have a letter from the company stating his qualification | be 30 years old | be a certified tankerman (PIC) | be licensed only |
| 2616 | An ocean going ship of 4000 gross tons must be fitted with a standard discharge shore connection for the discharge of oily wastes to a reception facility. The dimensions for the connection are specified in the Pollution Prevention Regulations under Part _____. | 155 | 151 | 140 | 152 |
| 2617 | Annex V to MARPOL 73/78 contains requirements pertaining to the discharge into the marine environment of _____. | None of the above | oil | noxious liquid substances | garbage |
| 2618 | As soon as the officer in charge of the vessel has taken steps to stop the discharge of oil or oily mixture into a U.S. harbor, what must he do FIRST? | Call the Coast Guard. | Inform the Environmental Protection Agency. | Rig a boom for recovery. | Alert the fire department. |
| 2619 | At what distance from shore may plastic material may be thrown overboard from a vessel? | 25 miles from shore | 3 miles from shore | None of the above are correct. | 12 miles from shore |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 2620 | Coast Guard regulations require a shipboard Oil Pollution Emergency Plan to be reviewed _____. | once every two years | once every four years | once every five years | annually |
| 2621 | During oil transfer operations, who is responsible for ensuring that the posted transfer procedures are followed? | The designated person in charge | The tankerman | The senior able seaman | The oiler |
| 2622 | During transfer operations, a quantity of propylamine spills on deck. According to the Chemical Data Guide, the correct procedure would be to _____. | cover the contaminated surface with soda-ash-soaked lime solution | immediately flush the spill with large quantities of fresh water | add sodium bisulfate on the contaminated surface and spray it down with water | move to a position upwind of the spill and allow the product to boil off |
| 2623 | Heavy fuel oils when spilled are _____. | less harmful to sea life than lighter oils | not a real threat to marine life | more harmful to sea life than lighter oils | easier to clean up than lighter refined oils |
| 2624 | How long must the operator of each vessel engaged in a vessel-to-vessel oil transfer operation keep a signed copy of the declaration of inspection for? | 1 year | 1 month | 10 days | 6 months |
| 2625 | If you must pump bilges while a vessel is in port, you should pump only _____. | on the outgoing tide | during the hours of darkness | as much as is necessary | if discharge is led to a shore tank or barge |
| 2626 | If you observe any situation which presents a safety or pollution hazard during the fuel transfer operations, which action should you take FIRST? | Shut down the operation. | Close the valves at the manifold. | Notify the person in charge of the shore facility. | Sound the general alarm. |
| 2627 | On a passenger vessel over 400 gross tons, routine entries for the Oil Record Book are recorded in _____. | Part II (Cargo Oil/Ballast Operations) | Part I (Machinery Space Operations) | Part III (Emergency Discharge/Spillage) | Oil Record Book is not required |
| 2628 | Small oil spills on deck can be kept from going overboard by _____: | plugging the scuppers | driving wooden plugs into the vents | closing the lids on the vents | plugging the sounding pipes |
| 2629 | Before a vessel can pump oily water within a Special Area, it has to comply with the following conditions EXCEPT: | be underway | it must be more than 12 miles from the nearest coast | that the filter system have an automatic cut-off when the wastes are found to exceed 15 ppm of oily residue | have an oily water separating system in operation |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 2630 | The standard outside diameter pipelines to enable pipes of reception facilities to be connected with the ships discharge pipelines for residues from machinery bilges should be_____. | 250 mm | 235 mm | 215 mm | 225 mm |
| 2631 | One of the requirements for an oil tanker operating with Dedicated Clean Ballast shall be that it is equipped with_____. | An oil content meter | A COW system | Segregated Ballast Tanks and PL | Two separate slop tanks |
| 2632 | Pipelines should be standard to enable pipes of reception facilities to be connected with the ships discharge pipelines for residues from machinery bilges. Its bolt circle diameter should be _____. | 185 mms. | 181 mms. | 183 mms. | 179 mms. |
| 2633 | Why is it important for fuel oil tank not to be topped off when loading cold oil? | The fuelling valve may become stuck closed and cause the fuel oil to spill before the valve can be opened | Air pockets may cause the fuel oil to bubble out of the ullage hole | Increased viscosity of the product needs higher loading pressure which increases the chance of spill | The change in its specific volume when heated may cause an overflow |
| 2634 | SOPEP means _____. | Shipboard Oil Pollution and Emergency Plans | Shipboard Oil Pollution Emergency Protection | Shipboard Oil Prevention and Environmental Protection | Spill of Oil Prevention and Environmental Protection |
| 2635 | The standard unit of liquid volume used in the petroleum industry, as well as the tanker industry, is a _____. | liter | barrel | gallon | drum |
| 2636 | In controlling pollution, which action should be taken after all dirty ballast has been transferred to the slop tank and prior to discharge through the oily water separator? | The dirty ballast tank is crude oil washed. | Chemicals should be added to emulsify the oil. | The slops should be allowed time to settle. | The clean tanks should be ballasted. |
| 2637 | An IOPP Certificate on an inspected vessel is valid for what period of time? | 5 years | 6 months | 1 year | 2 years |
| 2638 | When oil is discharged overboard, an entry is required in the _____. | Official Logbook | engine rough log | Oil Record Book | deck rough log |

| | | | | | |
|---|---|---|---|---|---|
| 2639 | A precaution you should take before bunkering is to _____ | close the lids on the vents | plug the scuppers | plug the sounding pipes | plug the vents |
| 2640 | In which case is the IOPP Certificate of an inspected vessel NOT invalidated? | The required oily-water separator malfunctions. | The ship is transferred to Liberian registry. | An annual survey is conducted fifteen months after the date of certificate issuance. | A 15 ppm oily-water separator is replaced by a 100 ppm oily-water separator. |
| 2641 | The most likely time for oil pollution while bunkering is when _____. | hoses are disconnected and being capped | first starting to receive fuel | final topping off is occurring | hoses are being blown down |
| 2642 | When bunkering is complete, the hoses should be _____. | cleaned internally with a degreaser | stowed vertically and allowed to drain | washed out with hot soapy water | drained, blanked off, and stored securely |
| 2643 | After each operation involving the transfer of oil or oily mixture, an entry shall be recorded in the Oil Record Book _____. | without delay | within 1 hour of completion of the inspection | within 6 hours of completion of the operation | as the operation permits |
| 2644 | Container vessels are required to maintain an Oil Record Book when the vessel is _____? | 300 gross tons above | 200 gross tons and above | 400 gross tons and above | 150 gross tons and above |
| 2645 | According to Pollution Prevention Regulations (33CFR), after every designated operation, the Oil Record Book is to be signed by _____. | a licensed officer present at the operation designated by the master | person(s) in charge of the operation and a licensed officer present at the operation | the master | person(s) in charge of the operation |
| 2646 | A vessel to which Annex V to MARPOL 73/78 applies is located 10 nautical miles from the nearest land. Which type of garbage is prohibited from being discharged? | Food waste, not comminuted or ground | Rags ground to less than 1 | Paper ground to less than 1 | None of the options |
| 2647 | Which statement is TRUE? | You need not keep a record of dumping ground garbage in to the sea more than 25 miles offshore. | You must keep a record of garbage discharged in port to a shore facility. | You must keep a record of the approximate weight of the garbage dumped. | You need not keep a record of garbage incinerated on the ship. |
| 2648 | Your oceangoing vessel is required to have a waste management plan. This plan must be in writing and describe procedures for _____. | collecting and discharging garbage | disposing waste from marine sanitation devices | reducing the amount of shipboard waste | segregating the different types of shipboard waste |

| | | | | | |
|---|---|---|---|---|---|
| 2649 | Which is a mandatory section of the shipboard Oil Pollution Emergency Plan? | Removal equipment list | Reporting requirements | List of individuals required to respond | Planned exercises |
| 2650 | During oil transfer operations, who is responsible for ensuring that the posted transfer procedures are followed? | The oiler | The senior able seaman | The designated person in charge | The tankerman |
| 2651 | Which statement is TRUE concerning the short exposure tolerance for Benzene? | 3000 ppm is endurable for 30 - 60 minutes (single exposure) | 500 - 1000 ppm for 30 - 60 minutes will produce definite irritation to the trachea | 5.5 ppm for 1 minute is practically intolerable | No chronic effects noticed after 20,000 ppm exposure for 5 - 10 minutes |
| 2652 | What is NOT a requirement of cargo piping installed in tank vessels carrying grade D or E cargo ONLY? | Piping through bunker spaces may be run through a pipe tunnel. | Flanged joints shall be used for pipe sizes exceeding 2 inches in diameter. | Connections at bulkheads must be made so that the plating does not form part of a flanged joint. | The cargo piping system shall be fixed. |
| 2653 | You are keeping the required garbage disposal records. The amount of garbage disposed must be stated in _____. | barrels of 55 gallon capacity | both cubic meters and cubic feet | cubic meters | both kilos and pounds |
| 2654 | You are offloading garbage to another ship. Your records must identify that ship by name and show her _____. | official number | home port | Master | next port-of-call |
| 2655 | After making the required notification that a large oil spill into the water has occurred, the FIRST action should be to _____. | throw grains of sand into the oil | contain the spread of the oil | have the vessel move out of the spill area | apply straw or sawdust on the oil |
| 2656 | Which is NOT a mandatory part of the shipboard Oil Pollution Emergency Plan? | Diagrams | Reporting requirements | Steps to control a discharge | National and local coordination |
| 2657 | You discharge garbage overboard at sea. When recording your vessels position as required, you must include _____. | latitude and longitude only | latitude, longitude, and estimated distance from shore | latitude, longitude, and approximate depth of water | latitude, longitude, course, speed, and a copy of that days noon position slip |
| 2658 | A gas-free certificate would usually be issued by a(n) _____. | ABS marine surveyor | Coast Guard marine inspector | port engineer | certified marine chemist |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 2659 | Access to a cargo pumproom on a tank vessel carrying grades A, B, C or D liquid cargoes shall be _____. | from the open deck | at least 13.1 feet away from the galleys, living quarters or navigation spaces | only from areas equipped with power ventilation systems | isolated from any part of the vessel which normally contains sources of vapor ignition |
| 2660 | The shut off valve at the gasoline tank which can be operated from outside the tank space _____. | is used if the gasoline tank leaks | shuts off the gasoline supply at the tank | controls the amount of gasoline to the engine | All of the options |
| 2661 | Annex V of Marpol 73/78, applies to all vessel regarding strict prohibitions of discharging _____ anywhere at sea. | wood | Glass | vinyl | Plastic |
| 2662 | Annex III covering harmful substances carried in packaged form and turned into force on: | 01 July.1992 | 31 Dec.1988 | 27 Sep. 2003 | 19 May.2005 |
| 2663 | Your vessel is at a dock taking bunkers. If oil begins to flow out of a tank vent, what should you do FIRST? | Set out drip pans and sawdust and begin to mop up the spill. | Close the valve on the tank vent line. | Open the intake valve to an adjacent tank | Signal the shore control point to shut down |
| 2664 | Your vessel is taking on fuel oil when a small leak develops in the hose and you have ordered the pumping stopped. Before resuming pumping you should _____. | replace the hose | place a large drip pan under the leak and plug the scuppers | repair the hose with a patch | notify the terminal superintendent |
| 2665 | Freeboard is a measure of: | The initial stability of the vessel | The amount of reserve bouyancy | neither A nor B | both A & B |
| 2666 | GM is a measure of: | The initial stability of the vessel | The amount of reserve bouyancy | both A & B | neither A nor B |
| 2667 | When using stabilogauge, unless the density correction is applied, the center of gravity of a loadable compartment is assumed to be: | At 1/3 of the height of the compartment | At 1/2 of the height of the compartment | At the geometric centerof the compartment | On deck of the compartment |
| 2668 | The value of KM at any draft may be taken from the: | Stabilty Table | Trimming Table | Hydrostatic Table | Building plans of the ship |
| 2669 | The volume of all watertight enclosed spaces above water line is called: | Reserved bouyancy | Freeboard | Free surface | Marginal stability |

| | | | | | |
|---|---|---|---|---|---|
| 2670 | In regards to the center of bouyancy, which of the following statement is correct? | It is the measure of metacentric height | It moves toward the high side of an inclines vessel | It moves toward the low side of an inclines vessel | It is located in the same position regardless of displacement |
| 2671 | Which of the following will increase the height of the center of buoyancy of your vessel? | Shifting weight from upper to lower decks | Loading weight in upper decks | Discharging weight from lower decks | Shifting weight from lower to upper decks |
| 2672 | An intact bouyancy means: | An intact space below the flooded area | The volume of all intact spaces above the waterline | An intact space when flooded will not cause the vessel to sink | The space where all the vertical upward forces of buoyancy are considered to be concentrated |
| 2673 | Your vessel is damaged and partially flooded. It is listing 12 deg to port and trimmed 8 feet down by the head. It has a long, slow, sluggish roll. What action will you take first? | Pump-out forepeak tank | Jettison deck cargo from the port side | Jettison the anchors and anchor cables | Press up an after, slack, centerline double bottom tank |
| 2674 | The percentage of the total surface area or volume of a flooded compartment that can be occupied by water by damage is called: | Center of buoyancy | Permeability | One compartment standard | Form gain |
| 2675 | The inward curvature of the ship's side is the: | Tumble home | Flare | Hogging | Sagging |
| 2676 | In a longitudinally framed vessel, the longitudinal frames are held in place in a place and supported by athwartship members called: | Stringers | Floor | Web frames | Margin plates |
| 2677 | The elevated perforated bottom of a chain locker which prevents the chain from touching the bottom of the chain locker and allows water to flow to the drain is: | Draft | Craddle | Harping | Manger |
| 2678 | The strake next to the keel is: | Garboard | Gangplank | Gunwale | Keelson |
| 2679 | What is not usually a concern when loading a single-hulled tanker? | trim | Bending moments | Initial stability | draft |
| 2680 | Your vessel rolls slowly and sluggishly. This indicates that the vessel _____. | has a greater draft forward than aft | has poor stability | has off-center weights | has a greater draft forward than aft |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 2681 | A vessel is tender if cargo weight is _____. | concentrated high and the double bottoms empty | concentrated low and the double bottoms empty | evenly distributed vertically with the double bottoms full | concentrated and with the double bottoms full |
| 2682 | The purpose of the inclining experiment is to _____. | determine the lightweight center of gravity location | determine the location of the metacenter | verify data in the vessel's operating manual | verify the hydrostatic data |
| 2683 | Which technique could be used to give a more comfortable roll to a stiff vessel? | Add weight near the centerline of the lower hold | Move weights lower in the ship | Concentrate weights on upper decks | Ballast the peak tanks |
| 2684 | The point to which your vessel's center of gravity (G) may rise and still permit the vessel to have positive stability is called the _____. | metacentric radius | metacenter | tipping center | metacentric point |
| 2685 | A negative metacentric height _____. | will always cause a vessel to capsize | should always be immediately corrected | always results from off-center weights | All of the above are correct |
| 2686 | Addition of weight to a vessel will ALWAYS _____. | All of the above | reduce reserve buoyancy | increase righting moments | increase GM |
| 2687 | When making a turn (course change) on most merchant ships, the vessel will heel outwards if _____. | the vessel has very little draft | G is above the center of lateral resistance | the vessel is deeply laden | G is below the center of lateral resistance |
| 2688 | Which statement is TRUE of a stiff vessel? | She will pitch heavily. | Her period of roll will be large due to her large metacentric height. | She will have an unusually high center of gravity. | She will have a large metacentric height. |
| 2689 | A vessel would be referred to as "tender" when the weight of the cargo is _____. | concentrated high and the double bottoms are empty | concentrated low and the double bottoms are full | evenly distributed vertically and the double bottoms are full | concentrated low and the double bottoms are empty |
| 2690 | A vessel is tender if cargo weight is _____. | concentrated high and the double bottoms empty | concentrated low and the double bottoms empty | evenly distributed vertically with the double bottoms full | concentrated and with the double bottoms full |
| 2691 | Which abbreviation refers to the horizontal distance between perpendiculars taken at the forward-most and the after-most points on a small passenger vessel's waterline at her deepest operating draft? | LOA | LLL | LWL | LBP |

FOR SALE!

| | | | | | |
|---|---|---|---|---|---|
| 2692 | Which technique could be used to give a more comfortable roll to a stiff vessel? | Add weight near the centerline of the lower hold | Concentrate weights on upper decks | Ballast the peak tanks | Move weights lower in the ship |
| 2693 | Which statement is TRUE of a tender vessel? | It has a very low center of gravity. | It has a good transverse stability. | It has a large GM. | Its period of roll is long. |
| 2694 | Metacentric height is an indication of a vessel's stability _____. | in no case | for small angles of inclination | for large angles of inclination | for all angles of inclination |
| 2695 | Metacentric height is a measure of _____. | All of the above | maximum righting arm | initial stability only | stability through all angles |
| 2696 | Which statement about the free surface effect is TRUE? | It decreases in direct proportion to increasing specific gravity of the liquid in the tank. | It increases in direct proportion to the length of the tank times the breadth squared. | In practice, the correction is considered to be a virtual reduction of KG. | It decreases at increased angles of heel due to pocketing when a tank is 90% full. |
| 2697 | Free communication effect is in direct proportion to _____. | neither length nor width | length of space only | length and width of space | width of space only |
| 2698 | What does NOT affect the value of the free surface correction? | Specific gravity of the liquid in the tank | Registered tonnage | Width of the tank | Length of the tank |
| 2699 | When cargo is shifted from the lower hold to the main deck the _____. | All of the above | GM will increase | center of gravity will move upwards | center of buoyancy will move downward |
| 2700 | A negative metacentric height _____. | should always be immediately corrected | will always cause a vessel to capsize | always results from off-center weights | All of the above are correct |
| 2701 | What will happen when cargo is shifted from the main deck into the lower hold of a vessel? | The center of buoyancy will move upward. | All of the above | The metacenter will move upward. | The GM will increase. |
| 2702 | Which factor has the greatest effect on the value of the free surface correction? | The length of the tank | The draft of the vessel | The width of the tank | The specific gravity of the liquid in the tank |
| 2703 | As the displacement of a vessel increases, the detrimental effect of free surface _____. | decreases | may increase or decrease depending on the fineness of the vessel's form | remains the same | increases |
| 2704 | The most detrimental effect on initial stability is a result of liquids _____. | pocketing in a slack tank as a vessel heels | flowing from side to side within the vessel | flowing from fore to aft within a vessel | flowing in and out of a holed wing tank |
| 2705 | What is the principal danger from the liquid in a half full tank onboard a vessel? | Corrosion from the shifting liquid | Loss of stability from free surface effect | Rupturing of bulkheads from the shifting liquid | Holing of the tank bottom from the weight of the shifting liquid |

| | | | | | |
|---|---|---|---|---|---|
| 2706 | You are fighting a fire in a cargo hold on your vessel. Which action is most important concerning the stability of the vessel? | Removing burned debris from the cargo hold | Maneuvering the vessel so the fire is on the lee side | Draining fire-fighting water and pumping it overboard | Shutting off electricity to damaged cables |
| 2707 | A tank which carries liquid is dangerous to the stability of a vessel when it is _____. | completely empty | low in the vessel | completely full | slack |
| 2708 | Your vessel has been damaged and is partially flooded. The first step to be taken in attempting to save the vessel is to _____. | calculate the free surface effect and lost buoyancy to determine the vessel's stability | establish flooding boundaries and prevent further spread of flood water | plug the hole(s) in the outer shell | pump out the water inside the vessel |
| 2709 | What must be accurately determined to assess the potential for progressive flooding after a vessel has been damaged? | The integrity of the water tight boundaries | The capacity of the water sprinkler systems | The operation of emergency bilge system | The operation of the machinery space bilge level alarms |
| 2710 | Control of flooding should be addressed _____. | following control of fire | following restoration of vital services | first | only if a threat exists |
| 2711 | A stress called compression is being placed on the sheer strakes if the vessel is _____? | hogging | sagging | inclined | under shearing force |
| 2712 | Your vessel rolls slowly and sluggishly. This indicates that the vessel _____. | has poor stability | has off-center weights | has a greater draft forward than aft | is taking on water |
| 2713 | Your vessel is broken down and rolling in heavy seas. You can reduce the danger of capsizing by _____. | moving all passengers to the stern | constantly shifting the rudder | rigging a sea anchor | moving all passengers to one side of the boat |
| 2714 | This is a modern method of welding where there is actual melting of the materials being joined although the weld metal is composed largely of added materials having the same characteristics as the metal being joined. | fusion weld | fillet weld | butt weld | arc weld |
| 2715 | This is the underwater narrowing part of a ship's hull forward of the middle body section? | Run | Fine line | Double | Entrance |

NOT FOR SALE

# OIC NAVIGATIONAL WATCH

| | | | | | |
|---|---|---|---|---|---|
| 2716 | What bulkheads subdivide the ship into independent compartments to limit the extent for flooding? | Accomodation | Transverse watertight | Longitudinal | Compartment |
| 2717 | Which of the following component parts of cargo gear is associated with Topping Lifts? | Heel Block | Flounder Plate | Schooner Guy | Gooseneck |
| 2718 | This is the type of hatch cover which consist of single or multi-paneled covers operated by either a wire rope of the ship's gear or by an electro-hydraulic system. | Roll Stowing Hatch Covers | Hinged and Folding Hatch covers | Sliding hatch cover | Pontoon Hatch Cover |
| 2719 | What doors are classified the strongest doors among the doors? | Airtight | Sliding | Watertight | Non watertight |
| 2720 | Freeing ports on a vessel with solid bulwarks _____. | provide openings through the bulwarks for mooring lines | allow water shipped on deck to flow off rapidly | permit easy jettison of deck cargo in an emergency | prevent stress concentration in the bulwark |
| 2721 | A plate used vertically in the bottom of a ship running athwartship from bilged usually on every frame is the: | intercostals plates | frames | floor | double bottom |
| 2722 | Brackets joining the deck beam and the side frames are known as: | tripping bracket | deep web | Plate web | beam knees |
| 2723 | A thirty pound plate would be: | 1/4 inch thick | 5/8 inch thick | 1 inch thick | ¾ inch thick |
| 2724 | What is the uppermost continuous deck exposed to the weather and the sea which has permanent means of watertight closure? | Superstructure | Weather deck | Freeboard deck | Boat deck |
| 2725 | How long is the loadline mark across the loadline disk? | 400 mm | 450 mm | 425 mm | 350 mm |
| 2726 | The horizontal line 300mm by 25mm wide which is positioned amidship on port and starboard side. | Drop Line | summer line | deck line | loadline |
| 2727 | This is a part of a vessel's side projecting upwards along the line of the weather deck or uppermost deck. | bulwark | bulkhead | flush deck | transverse frame |

# OIC NAVIGATIONAL WATCH

| | | | | | |
|---|---|---|---|---|---|
| 2728 | When using clamp shell discharging of cargo, what damage to ship's structure it caused? | Damage on deck's railing when swinging | Cargo residue on top of the coaming | Hatch covers are commonly hit by clamp shell | Hatch coaming may suffer minor harmful knocks |
| 2729 | The curvature of the deck in the longitudinal direction. | baseline | sheer | camber | freeboard |
| 2730 | Lightening holes cut out of a solid floor allow for which of the following? I. Access during construction and maintenance of the double bottom II. A saving weight | II only | I only | Both I and II | Neither I nor II |
| 2731 | The weight of a vessel without a load. It includes hull and fittings, engines and boilers, shafting and propellers, water in boilers, permanent ballast, etc | Light displacement | Dead weight tonnage | Loaded displacement | Displacement tonnage |
| 2732 | Reference to freeboard categories, Type A ships are those designed specifically for the carriage of _____. | timber cargoes | liquid cargoes in bulk | Dry bulk cargoes | general cargoes |
| 2733 | A preventer guy_____. | is the same as the black smith | prevents anyone from working the cargo at unauthorized times | is a safety measure in case one of the outboard guys part | is a longshoreman who watches for accidents |
| 2734 | The enclosed area defined as the intersection of the surface of the water and the hull of a vessel is the _____. | amidship plane | baseline | waterplane | longitudinal reference plane |
| 2735 | The frame of the vessel that runs parallel to the keel is called_____. | Center frame | transverse frame | Parallel frame | Longitudinal frame |
| 2736 | Which of the following is not exempted when calculating gross tonnage? | Wheelhouse chart room | Passenger cabin | Steering gear room | Emergency generator room on upper deck |
| 2737 | When heating a metal and cooling it down for desired fashion. This is called: | annealing | heating | strengthening | cooling |
| 2738 | What do you call the distance from the keel to the upper deck? | Extreme depth | Extreme draft | Extreme breadth | Extreme freeboard |
| 2739 | The vertical plate of ship's girder is called: | flange | Knee | bracket | web |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 2740 | The tube leading from the foc'sle deck to the chain locker enclosing the anchor chain is called: | Spurling pipe | Hawse pipe | Fairlead | Scupper |
| 2741 | What kind of block is used as a cargo block? | Heel Block | Fiddle Block | Gin Block | Snatch Block |
| 2742 | A metal chimney or passage through which the smoke and gases are led from the uptakes to the open air: | funnel | Chimmey | pigment | smokestack |
| 2743 | The figure obtained by dividing the total volume of the ship in cubic feet (after omission of exempted spaces) by 100 is the _____. | Bale cubic | net tonnage | gross tonnage | light displacement |
| 2744 | It refers to any break or change in section thickness or amount of plating materials. | discontinuity | strength of materia | stiffening | framing |
| 2745 | The last link of the anchor chain attached to the pad eye in the chain locker is called: | Studlink | Bitter end | Anchor Shackle | Securing piece |
| 2746 | What is the purpose of the stripping bar on the anchor windlass? | Act as a fairlead | Clean of mud | Prevent chain from fouling the wildcat | Engaged and disengaged the wildcat |
| 2747 | It means that a piping on venting system, for example, is in no way connected to another system and that there are no provisions available for the potential connection to other system. | separate | self-contained | independent | Segregated |
| 2748 | The making of the load lines are painted in _____ in a dark ground. | white | red | yellow | black |
| 2749 | If the winch should fail while you are hauling in the anchor, what prevents the anchor cable from running out? | Riding Pawl | Devil's Claw | Chain stopper | Hawse Ratchet |
| 2750 | A vertical side battens is the same __. | Botton dunnage | a hook | horizontal battens | spar ceiling |
| 2751 | By definitions, a "SPAR DECK' is the: | after most weather deck above the main strength deck | deck of light construction below the main or strength deck | upper or weather deck above the main strength deck | lower most continuous deck broken by water tight |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 2752 | In the formula, I = L X B X K, what does “B” means? | Breadth of the vessel | Breadth of the waterplane | Breadth of ship | Breadth of the cargo |
| 2753 | What type of rudder may loose its effectiveness at angles of 10 or more degrees? | Unbalance | Flat plate | Contra-guide | Balance |
| 2754 | Which of the following is a bow shape of a ship constructed where the stern is at right angle to the keel? | Plumb | Ice breaker | Clipper | Raked |
| 2755 | Which of the following is the deep fore-and-aft member supporting the deck? | Pillar | Girder | Beam | Stanchion |
| 2756 | The ratio of the transverse area of the midship section to a rectangle having the same breadth and depth: | Prismatic coefficient | Block coefficient | Midship coefficient | Coefficient of fineness |
| 2757 | This is the type of hatch cover which are made of one or more separate covers each designed to be lifted independently to expose the entire hatch opening. They can be used for weather and ‘tween deck hatchways. | Hinged and Folding Hatch Covers | Pontoon Hatch Covers | Roll Stowing Hatch Covers | Sliding Hatch Cover |
| 2758 | What do you call the distance from the keel to the upper deck? | Extreme breadth | Extreme depth | Extreme draft | Extreme freeboard |
| 2759 | The deck plating nearest to the deck edges are termed: | transverse plates | Intercoastals plate | longitudinal plates | stringer plates |
| 2760 | Racking stress caused when ship rolls in a seaway is more severe or evident on: | top corner | bottom ports | middle top | fore and aft |
| 2761 | The ___ is an imaginary line, 75 mms below the bulkhead deck. It is assumed that the ship which is sunk to this line would still be navigable in fine weather. | margin line | surge line | statutory line | Deck Line |
| 2762 | Another name for the sheer strake is the _____. | Stringer plate | A strake | Z strake | Side keel plate |
| 2763 | The safety factors which must be considered both and when using a pair of derricks rigged to operate in union purchase? | Allow greater than normal loads to be handled by the gear. | Increase the mechanical advantages of the union purchase. | Guys tightly rigged and as mean as possible at 90° to the derrick. | Should be rigged at an angle of 70° to 90°. |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 2764 | What is the distance from the lower edge of the winter loadline permitted on ships 100 meters or less in length? | 75mms | 60mms | 30mms | 50mms |
| 2765 | If the winch should fail while you are hauling in the anchor, what prevents the anchor cable from running out? | Devil's Claw | Hawse Ratchet | Chain stopper | Riding Pawl |
| 2766 | Your vessel has amidship engine room, and the cargo is concentrated in the end holds. The vessel is said to be: | sagging with compressive stress on the main deck | hogging with compressive stress on the main deck | sagging with tensile stress on the main deck | hogging with tensile stress on the main deck |
| 2767 | Deep tanks are normally located aboard ship; | amidship | abaft engine space | any of the answer | abaft the peak tanks |
| 2768 | This is the ratio of the immersed volume to the area of the load waterplane multiplied by the mean draught: | Prismatic coefficient | Vertical Prismatic coefficient | Midship section area coefficient | Waterplane area coefficient |
| 2769 | It is the work of measuring the various dimension and capacities of the ship in order to get the tonnage for official registration. | Ship's plan | Measurement | Deck capacity plan | Dry dock plan |
| 2770 | The enclosed area defined as the intersection of the surface of the water and the hull of a vessel is the _____. | baseline | waterplane | Longitudinal reference plane | amidship plane |
| 2771 | What is the purpose of the stripping bar on the anchor windlass? | Engaged and disengaged the wildcat | Prevent chain from fouling the wildcat | Act as a fairlead | Clean of mud |
| 2772 | Floors aboard ship are _____. | Longitudinal angle bars fastened to a surface for strength | Longitudinal beams in the extreme bottom of a ship from which the ship's ribs start | Frames to which the tank top and bottom shell are fastened on a double bottomed ship | Transverse members of the ships frame which support the decks |
| 2773 | What term indicates the immersed body of the vessel aft of the parallel mid-body? | Run | Stem | Entrance | Stern |
| 2774 | What is called the upper horizontal member of the backbone of the ship? | Keel rider plate | Vertical keel | Keelson | Flat keel |
| 2775 | The rudder with small area forward of the turning axis is known as the: | unbalanced rudder | semi-balanced rudder | neutral rudder | balanced rudder |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 2776 | Concerning the use of stabilogauge, which of the following cannot be found? | Trim | Mean draft | Displacement | Deadweight |
| 2777 | When loading different cargo through the same pipeline, you should determine which cargo to load first EXCEPT: | Specific gravity | Cleanliness of commodity | Trim, hog and sag | Flash point |
| 2778 | How many cubic meters are there in 120 cubic foot? | 3.255 cubic meters | 3.598 cubic meters | 3.398 cubic meters | 3.410 cubic meters |
| 2779 | What authorities arranged the order of merit of ships built according to the standard of seaworthiness? | Port state control | Classification society | Port authorities | Government authorities |
| 2780 | Which of the following surveys is an initial other than the classification in survey for the first entry? | Docking | Classification during Construction | Intermediate | Annual Classification |
| 2781 | The piping that routes an oil cargo from the manifold to under deck pipelines is known as a: | Cargo fill | drop line | transfer | Branch line |
| 2782 | On a Tanker vessel, the cargo pump relief valves are piped to the: | crossover lines interconnecting two pumps | atmosphere through pump vents | cargo pump gauges | suction side of pump |
| 2783 | What is an arthwartship member supporting the deck? | Girder | Beam | Bulkhead | Frame |
| 2784 | Which part of the hull through which the section shape remains unchanged? | Fine form | Full form | Parallel middle body | Middle body section |
| 2785 | What is the “F” in ship’s construction refers? | Pillars | Girders | Beam | Floors |
| 2786 | Length overall (L.O.A) is measured_____? | from the hawse pipe to the aft perpendicular | from the forward most to the aftermost part of the vessel | from the forward most part of the vessel to the aftermost part of the rudder | from the forward perpendicular to the aft perpendicular |
| 2787 | How long is the loadline mark across the loadline disk? | 450mm | 400mm | 350mm | 425mm |
| 2788 | When a metal is tampered, it becomes: | More brittle | less brittle | softer | harder |
| 2789 | What is drawn to give the immersed area of transverse section to any draft and may be used to determine the longitudinal distribution of buoyancy? | Load curves | Buoyancy curves | Bonjean curves | Curves of shear force |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 2790 | Which doors usually have lever type, quick acting closures? | Sliding | Watertight | Airtight | Panel |
| 2791 | "Length between perpendiculars" is measured; I. Along the summer loadline II. From the forward stem to the after part of the rudder. III. Vertically | II only | I, II and III | I and II only | II and III only |
| 2792 | Your vessel midship draft is 30'-03" The mean draft is 29'-11". You have: I. 5" hog II. Concentration of weights fore and aft | Both I and II | II only | Neither I nor II | I only |
| 2793 | What kind of cargo weighing 2,240 lbs. occupies less than 40 cu.ft. of space? | advalorem cargo | special cargo | deadweight cargo | measurement cargo |
| 2794 | The term "CARGO TANK LENGTH" as used in part 157 of the Pollution Regulations, means the: | length from the collision bulkhead to the forward bulkhead of the machinery | greatest distance between two opposite cargo tank bulkhead | diagonal measurement of a cargo tank | length of any individual cargo space, from bulkhead to bulkhead |
| 2795 | This is the tonnage of the space below the tonnage deck. It is found by dividing the tonnage length into a specified number of parts. | Underdeck tonnage | Net tonnage | Tonnage deck | Gross tonnage |
| 2796 | Mainly used to hold the anchor cable in place while the ship is riding at anchor. | Chain locker | Windlass | Cable stopper | Chain stopper |
| 2797 | The ratio of the transverse area of the midship section to a rectangle having the same breadth and depth: | Block coefficient | Midship coefficient | Coefficient of fineness | Prismatic coefficient |
| 2798 | These are those portions of the accommodation spaces which are used for halls, dining rooms, lounges and similar permanently enclosed spaces. | service spaces | Passenger space | crew spaces | public spaces |
| 2799 | Watertight equipment means: | Enclosed equipment that can be submerged for a period of 30 minutes without leakage | Enclosed equipment so constructed that a steam of water from those under a head of 35 ft. can be played on the apparatus for 5 minutes without leakage | Enclosed equipment that can be submerged for a period of 1 hour without leakage | Enclosed equipment that a stream of water can be played for 5 minutes under full pressure without leakage |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 2800 | _____ may be closed by a vertical screw thread which is turned by a shaft extending above the bulkhead and fitted with a crane handle | vertical sliding door | Watertight door | door way | horizontal sliding door |
| 2801 | Which kind of pipe has the best resistance to internal and external combustion? | cast iron | centrifugally cast | cast-steel | spiral welded |
| 2802 | A welding process in which the arc is maintained within a blanket of granulated flux; a consumable filler wire is employed and the arc is maintained between this wire and parent wire is _____. | gravity welding | submerged arc welding | stud welding | tungsten inert gas welding |
| 2803 | In order to determine the heeling moment due to grain shift, the master must have the position above the bulkhead deck and powered by _____. sufficient grain loading information. The following information shall include except: | curves and tables of grain heeling moment for every compartment | details of scantlings of any temporary fittings | tables of maximum permissible heeling moment | tween deck compartment extend from deck to deck |
| 2804 | In passenger ship, watertight doors may be closed by remote control from central | all of these | hydraulic means | electrical means | hand pump |
| 2805 | There are two classification surveys, one is classification in survey for the first entry, that is initial survey and the other is _____. | intermediate survey | annual classification survey | classification survey under construction | Docking survey |
| 2806 | Which of the following condition will cause a vessel's bottom to be subjected to tension stresses? | concentration of weight forward | concentration of weight amidships | concentration of weight at both end of the vessel | concentration of weight aft |
| 2807 | The internal volume of a cargo hold measured from the inside of the side shell, the underside of the deck, and the tank top is known as _____. | Grain cubic | Gross cubic | Net cubic | Bale cubic |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 2808 | The internal volume of a cargo hold measured from the inside faces of the cargo battens, the lower side of the deck beams, and the top of the tank top ceiling is known as the _____. | Grain cubic | Bale cubic | Net cubic | Gross cubic |
| 2809 | What is the function of a CARLING? | To act as a vertical support for a deck | To act as a longitudinal and to add strength to the inner bottom | To act as girder in order to stiffen the deck | To act as a boundary stiffener for the hatches |
| 2810 | What is the TPC of a rectangular shaped vessel 80m x 14m floating in SW at an even keel draft of 4m? | 12.52 | 13.68 | 10.22 | 11.48 |
| 2811 | The instrument always used with the salinity indicator is the: | Manometer | Pyrometer | Thermometer | Hydrometer |
| 2812 | Where will be the center of gravity of a cargo compartment filled with general cargo with heavier items stowed on the bottom? | One-third the height of the compartment above its deck | One-quarter the height of the compartment above its deck | One-half the height of the compartment above its deck | At the top of the compartment |
| 2813 | What is not usually a concern when loading a single-hulled tanker? | Bending moments | trim | draft | Initial stability |
| 2814 | Your vessel rolls slowly and sluggishly. This indicates that the vessel _____. | has poor stability | has off-center weights | has a greater draft forward than aft | has a greater draft forward than aft |
| 2815 | A vessel is tender if cargo weight is _____. | concentrated low and the double bottoms empty | evenly distributed vertically with the double bottoms full | concentrated high and the double bottoms empty | concentrated and with the double bottoms full |
| 2816 | You are underway when a fire breaks out in the forward part of your vessel. If possible you should _____. | abandon ship to windward | keep going at half speed | put the vessel's stern into the wind | call for assistance |
| 2817 | The purpose of the inclining experiment is to _____. | verify the hydrostatic data | determine the location of the metacenter | determine the lightweight center of gravity location | verify data in the vessel's operating manual |
| 2818 | Which technique could be used to give a more comfortable roll to a stiff vessel? | Concentrate weights on upper decks | Ballast the peak tanks | Move weights lower in the ship | Add weight near the centerline of the lower hold |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 2819 | The point to which your vessel's center of gravity (G) may rise and still permit the vessel to have positive stability is called the _____. | tipping center | metacentric point | metacentric radius | metacenter |
| 2820 | A negative metacentric height _____. | will always cause a vessel to capsize | should always be immediately corrected | always results from off-center weights | All of the above are correct |
| 2821 | Addition of weight to a vessel will ALWAYS _____. | reduce reserve buoyancy | All of the above | increase GM | increase righting moments |
| 2822 | When making a turn (course change) on most merchant ships, the vessel will heel outwards if _____. | G is above the center of lateral resistance | the vessel is deeply laden | the vessel has very little draft | G is below the center of lateral resistance |
| 2823 | Which statement is TRUE of a stiff vessel? | She will pitch heavily. | Her period of roll will be large due to her large metacentric height. | She will have an unusually high center of gravity. | She will have a large metacentric height. |
| 2824 | A vessel would be referred to as "tender" when the weight of the cargo is _____. | concentrated low and the double bottoms are empty | evenly distributed vertically and the double bottoms are full | concentrated high and the double bottoms are empty | concentrated low and the double bottoms are full |
| 2825 | A vessel is tender if cargo weight is _____. | concentrated and with the double bottoms full | concentrated low and the double bottoms empty | evenly distributed vertically with the double bottoms full | concentrated high and the double bottoms empty |
| 2826 | In order to minimize the effects of a tender vessel, when carrying a cargo of lumber, you should _____. | keep the vessel's frame spaces free from lumber | maximize your deck load | place the heaviest woods in the lower holds | distribute lumber so that those stowing most compactly per unit of weight are in the upper holds |
| 2827 | Which abbreviation refers to the horizontal distance between perpendiculars taken at the forward-most and the after-most points on a small passenger vessel's waterline at her deepest operating draft? | LLL | LWL | LBP | LOA |
| 2828 | Which technique could be used to give a more comfortable roll to a stiff vessel? | Concentrate weights on upper decks | Move weights lower in the ship | Ballast the peak tanks | Add weight near the centerline of the lower hold |

| | | | | | |
|---|---|---|---|---|---|
| 2829 | Which statement is TRUE of a tender vessel? | Its period of roll is long. | It has a good transverse stability. | It has a very low center of gravity. | It has a large GM. |
| 2830 | Metacentric height is an indication of a vessel's stability _____. | in no case | for all angles of inclination | for large angles of inclination | for small angles of inclination |
| 2831 | Metacentric height is a measure of _____. | All of the above | stability through all angles | initial stability only | maximum righting arm |
| 2832 | Which statement about the free surface effect is TRUE? | It increases in direct proportion to the length of the tank times the breadth squared. | It decreases at increased angles of heel due to pocketing when a tank is 90% full. | In practice, the correction is considered to be a virtual reduction of KG. | It decreases in direct proportion to increasing specific gravity of the liquid in the tank. |
| 2833 | You are in a tank wearing the self-contained breathing apparatus and you desire to return topside. How many tugs of the lifeline mean to take up the slack? | Three | Two | One | Four |
| 2834 | Free communication effect is in direct proportion to _____. | length of space only | neither length nor width | length and width of space | width of space only |
| 2835 | What does NOT affect the value of the free surface correction? | Width of the tank | Registered tonnage | Specific gravity of the liquid in the tank | Length of the tank |
| 2836 | What is the minimum number of fire pumps required on a cargo vessel of 900 GT? | 2 | 3 | 4 | 1 |
| 2837 | When cargo is shifted from the lower hold to the main deck the _____. | center of gravity will move upwards | GM will increase | center of buoyancy will move downward | All of the above |
| 2838 | A negative metacentric height _____. | will always cause a vessel to capsize | always results from off-center weights | All of the above are correct | should always be immediately corrected |
| 2839 | What will happen when cargo is shifted from the main deck into the lower hold of a vessel? | The metacenter will move upward. | The GM will increase. | The center of buoyancy will move upward. | All of the above |
| 2840 | Which factor has the greatest effect on the value of the free surface correction? | The length of the tank | The draft of the vessel | The width of the tank | The specific gravity of the liquid in the tank |
| 2841 | As the displacement of a vessel increases, the detrimental effect of free surface _____. | decreases | may increase or decrease depending on the fineness of the vessel's form | remains the same | increases |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 2842 | The most detrimental effect on initial stability is a result of liquids _____. | flowing in and out of a holed wing tank | pocketing in a slack tank as a vessel heels | flowing from side to side within the vessel | flowing from fore to aft within a vessel |
| 2843 | What is the principal danger from the liquid in a half full tank onboard a vessel? | Corrosion from the shifting liquid | Rupturing of bulkheads from the shifting liquid | Loss of stability from free surface effect | Holing of the tank bottom from the weight of the shifting liquid |
| 2844 | You are fighting a fire in a cargo hold on your vessel. Which action is most important concerning the stability of the vessel? | Maneuvering the vessel so the fire is on the lee side | Draining fire-fighting water and pumping it overboard | Shutting off electricity to damaged cables | Removing burned debris from the cargo hold |
| 2845 | A tank which carries liquid is dangerous to the stability of a vessel when it is _____. | slack | low in the vessel | completely full | completely empty |
| 2846 | The number of fire detectors that a single power supply is capable to handle for continuous operation is limited to a maximum of _____. | 50 | 80 | 100 | 200 |
| 2847 | What is the bolt circle diameter of a standard pipeline to enable pipes of reception facilities to be connected for residue from machinery bilges is: | 190 mm | 200mm | 195mm | 183mm |
| 2848 | The pivot point of a vessel when going ahead is located: | at the bow | about one-third of the vessel's length from the bow | at the hawsepipe | about two-thirds of the vessel's length from the bow |
| 2849 | It forms the after bearing of the propeller shaft and incorporates the watertight gland through the intact hull. | Shaft | Bossing | Stern tube | A-frame |
| 2850 | To assess the damage of a beached vessel, what tanks or compartment should be sounded? | all bilges | all cargo compartments | all ballast tanks | all cargo tanks and compartments |
| 2851 | A tank or a compartment is said to be gas-free when there is an absence of dangerous concentration of which of the following? | any combustible liquid | residues from oil cargo | any inflammable liquid | flammable or toxic gases |
| 2852 | A tackle is "two blocked" when the blocks are: | equally sharing the load | jammed together | as far apart as possible | rove to the highest mechanical |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| | | | | | advantage |
| 2853 | How will a reverse current relay prevent DC generator system of the following? | Automatically securing the excites generator | Tripping the circuit breaker | Automatically redirecting the load | Automatically speeding up the prime mover |
| 2854 | Forces acting longitudinally and vertically in a beam is termed _____? | Compression stress | Bending stress | Combination stress | Tension stress |
| 2855 | A vessel has an amidships superstructure. Which location would be most suitable for on-deck stowage of automobiles? | On top of the hatch immediately forward of the midships house | On top of # 1 hatch | On top of the hatch immediately aft of the midships house | Beside the hatches, forward of the midships house |
| 2856 | Binder chains used to lash down deck cargo may be shortened by ? | wiring, welding and pelican hooks | bolting two links together | Knotting | load binders or turnbuckles |
| 2857 | It is an apparatus in which horizontal or vertical drums or gypsies and wildcats are operated by means of a steam engine or motor for the purpose of handling heavy anchor chains, hawsers, etc. | Deck Machinery | Capstan | Rollers | Windlass |
| 2858 | Cargo-handling equipment is provided in the form of pumps located in a _____, usually positioned between the machinery space and the cargo tanks. | Cargo Control Room | Pump Room | Cargo Handling Room | Engine Control Room |
| 2859 | A pipe to convey water from the pump discharge through the ship's side. | Centripetal Pump | International Shore Connection | Centrifugal Pump | Pump Dale |
| 2860 | The best way to ensure whether adequate oxygen is present for safe entry into a seldomly used cargo tank is: | Check for rust inside the tank | Test tank atmosphere using a combustible gas indicator | Open the air vent prior to entry | Ventilate the tank with fresh air and test with an oxygen indicator |
| 2861 | Strong twin posts for making fast mooring ropes. | bitts | mast | cleats | bollard |
| 2862 | Cargo pump relief valves are piped to the: | suction side of pumps | cargo pump pressure gauges | atmosphere through pump vents | crossover lines interconnecting two pumps |
| 2863 | These valves are at a higher level in the ship on the discharge side of the pump and are the route for pumping ballast water to the sea. | overboard discharge valves | discharge valves | suction valves | sea valves |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 2864 | The space around a pipe in a wellbore, the outer wall of which may be the wall of either the borehole or the casing, is the: | down hole | annulus | bore | open hole |
| 2865 | Cargo holds must be dry and free from dirt and foul odor, what must be determined when inspecting cargo holds before taking any cargo? | Draft | All choices | Watertight integrity | Ballast condition |
| 2866 | Bilge keel are more effective at dampening rolls as the: | list increase | draft decrease | rolling increases | pitching increases |
| 2867 | A vertical line on the ship's side, beside the plimsoll mark, with horizontal lines running from it denoting the depth to which the ship may load under varying conditions and seasons. | depth | draught mark | midship mark | loadline |
| 2868 | A type of condensation that forms on surfaces and on all goods in a compartment caused by the inability of cooled air to hold in suspension as much water vapor as warm air. | Condensation | Precipitation | Sweat | Evaporation |
| 2869 | Closing mechanism of water tight doors must be tested of its effective operation at what frequency? | every thrice a month | every month | every week | every twice a month |
| 2870 | A rectangular cross-section as on a tanker and has less reserve buoyancy with the same freeboard than a more rounded hull like that of a tugboat or liner. | foul | Sheer | Fowl | Full |
| 2871 | A type of ventilation where the flow of air is controlled by the proper trimming of ventilation. | Free flowing ventilation | Natural ventilation | Dehumidifier | Mechanical ventilation |
| 2872 | An electrically "charged mist" will be found in a: | diesel engine cylinder | fuel tank vent outlet | cargo tank during Butterworthing | flash evaporator flash chamber |
| 2873 | A large quarter circle on the rudder post head. | guard plate | quadrant | propeller | pelorus |
| 2874 | Which device is designed to automatically hold the load if power should fail to an electric winch? | Electromagnetic brake | Hand brake | Motor controller | Pneumatic brake |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 2875 | At seaway a thwarthship swinging of a vessel. | Yawning | Heaving | Rolling | Pitching |
| 2876 | Motion of a vessel in waves about the vessel's vertical axis. | Pitching | Rolling | Yawning | Heaving |
| 2877 | At seaway a thwarthship swinging of a vessel. | Heaving | Rolling | Yawning | Pitching |
| 2878 | Bilge keels are fitted on ships to: | assists in drydock alignment | improve the vessel's stability | protect from slamming against piers | reduce the rolling of the vessel |
| 2879 | The bilge main is arranged to drain any watertight compartment, _____ ballast, oil or water tanks and to discharge the contents overboard. | in addition that | other than | except | supplementary to |
| 2880 | A "liner" in riveted construction of a vessel is a(n): | backing plate which is used to level the strakes while riveting, and then removed | seam that is welded after riveting is completed | internal frame to which the side shell is riveted | small plate which fills the aperture between riveted strakes and the vessel framing |
| 2881 | Forces which result from the ship's motion in the sea and the actions of the waves is termed as: | kinetic force | dynamic force | static force | hydraulic force |
| 2882 | Automatic shutdown of the inert gas blowers and gas regulating valve shall be arranged in case of faulty condition in the inert gas system. Which of the following conditions has not correct value (high/low) in relation to automatic stop according to present regulation? | Low water level in the water seal | High water level in the water seal | Low water pressure or low water flow rate to the flue gas scrubber | High water level in the flue gas scrubber |
| 2883 | Which bulkhead is the vessels immediate protection in the event of a broken stern tube? | machinery space | aft collision | after peak | stern frame |
| 2884 | In regard to fire protection, which spaces shall be separated from the rest of the ship by thermal and structural boundaries? | Cargo compartments | Storage rooms for inflammable materials | Machinery spaces | Accommodation |
| 2885 | If you were to pass a stopper on a wire rope, what should the stopper be made of? | Nylon | Chain | Manila | Wire |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 2886 | A _____ frequency electric current causes a quartz crystal to vibrate at a high pitch. | very low | low | medium | high |
| 2887 | A tank which has been sealed for a long time can be dangerous for human entry because: | tank coating gives off toxic fumes | moisture displaces oxygen | steel surfaces consumes oxygen by rusting | sealed tank usually form a vacuum |
| 2888 | An alarm be required an overflow control system to the ship's operator? | Malfunction alarm | Monitoring alarm system | Deadman alarm system | Audible task overflow alarms |
| 2889 | A ship is turning around a point called the "pivot point". What is the position of this invisible point when the ship is "dead" in the water? | About same position as the center of gravity | Near the bow | Outside of the center line | Near the stern of the ship |
| 2890 | What should be carried out before entering the pump room? | Notify the Chief Officer or officer on duty and run the ventilation for at least 15 minutes. | notify the Chief Officer or officer on duty | run the ventilation for at least 15 minutes | Always carry a walkie talkie with you into the pump room and call for help immediately if you start feeling dizzy |
| 2891 | A vessel has an amidships superstructure. Which location would be most suitable for main deck stowage of vehicles? | on top of the hatch immediately aft of the midships house | on top of no. 1 hatch | beside the hatches, forward of midships house | on top of the aftermost hatch on the vessel |
| 2892 | The oscillating of a vessel on her longitudinal axis is termed as: | rolling | pitching | yawing | heaving |
| 2893 | A vertical division of a vessel, used as a part of the indication of a stowage place for containers. | Bay | Tier | Row | Column |
| 2894 | Which spaces may be excepted from protection by a fixed fire detection and fire alarm system? | service spaces | stairways | control spaces | sanitary spaces |
| 2895 | This type of screw is principally used by fast coastal craft and some classes of aircraft carriers. The propeller revolves in the same direction, so as to facilitate engine installation. This propeller is: | twin screw | controllable - pitch propeller | single crew | triple or multiple screw |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 2896 | All bilge suctions must be fitted with suitable _____, which in the machinery space would be mud boxes positioned at floor plate level for easy access. | relief valves | strainers | stringers | emergency valves |
| 2897 | These valves are normally situated near the bottom shell and are use to control intake and discharge of ballast water. | sea valves | suction valves | discharge valves | overboard discharge valves |
| 2898 | A line 1/48 of the summer draft of the vessel above the summer load line. | Lumber summer load line | Tropical load line | Summer Freeboard | Lumber tropical load line |
| 2899 | Horizontal transverse motion of a vessel is known as: | Heave | Surge | Sway | Pitch |
| 2900 | Horizontal fore or aft motion of a vessel is known as: | surge | sway | roll | pitch |
| 2901 | Which of the following is FALSE why there may not be enough oxygen in an enclosed space or tank? | cargo inside may have absorb the oxygen | oxygen is depleted as oxidation may have taken place | tank may have been coated with preservatives | enclosed as it is, no proper circulation of air |
| 2902 | Occasionally a MAcGregor hatch may pull from side to side. This could be due to: | the eccentric rollers not being in place | the locking cleats seizing | the cross wedges not being removed | the pulling chains being of unequal length |
| 2903 | From the point where the rudder is put over to any point on the turning circle, the distance a vessel moves parallel to the original course is known as: | kick | advance | transfer | head reach |
| 2904 | A thrust block is designed to: | transmit the thrust of the propeller to the vessel | be placed between the engines and the foundation to absorb the vibration | absorb the shock of wave pressure at the bow | transmit the thrust of the engine to the propeller |
| 2905 | Heave is the motion of a vessel along the: | transverse axis | longitudinal axis | centerline axis | vertical axis |
| 2906 | A vessel would most likely develop a list if you were: | using fuel from tanks on the port side only | burning fuel from a centerline tank | using water from the fore peak tank | using water from two equally sized tanks on either side of the centerline simultaneously |
| 2907 | According to the regulations in force, Which one of the following | Ejector. | Not any particular. | Vacuum strip. | Stripping pump. |

OIC NAVIGATIONAL WATCH

| | | | | | |
|---|---|---|---|---|---|
| | stripping device is a demand on an oil tanker? | | | | |
| 2908 | A motion of a ship in waves about the ship transverse axis. | yawing | Pitching | heaving | rolling |
| 2909 | Bilge keel are more effective at dampening rolls as the: | rolling increases | list increase | draft decrease | pitching increases |
| 2910 | Following a collision or accident the Master of each vessel involved must render assistance to persons affected by the collision or accident _____. | without regard to any danger to his vessel | if he can do so without serious danger to his vessel or to individuals on board | if he can do so without undue delay | if he can do so without any risk to his vessel |
| 2911 | The fitting at the end of a cargo line in a tank that allows suction to be taken close to the bottom of a tank is a _____. | vacuum valve | strainer | bell-mouth | suction end |
| 2912 | The total weight of cargo fuel water stores passengers and crew and their effects that a ship can carry is the _____. | deadweight | bale cubic | loaded displacement | gross tonnage |
| 2913 | Ultrasonic testing is used to determine the thickness of a vessels shell plating and to _____. | check the wear of the rudder carrier bearing | test welds for subsurface defects | test the links of the anchor cables while being ranged | provide tail shaft clearances |
| 2914 | What fitting on the mast works in conjunction with the shrouds to control side bend of the mast? | Chainplate | Crowfoot | Spreader | Hound |
| 2915 | What term indicates a curvature of the decks in a longitudinal direction? | Camber | Flare | Deadrise | Sheer |
| 2916 | Which of the following is the pipe used to connect two separate piping systems on a tank vessel? | transfer | connection | junction | crossover |
| 2917 | Which weld fault can only be detected by a method that examines the internal structure of a weld? | Lack of reinforcement | Overlap | Undercut | Lack of penetration |
| 2918 | A charterer is unable to complete the loading of a vessel during the lay days specified in the charter party. Under these circumstances the _____. | effective period of the charter is extended | ship is authorized extra time to discharge the cargo | harterer must pay dispatch money | vessel operator can collect demurrage |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 2919 | A term applied to the bottom shell plating in a double-bottom ship is _____. | shear plating | outer bottom | tank top | bottom floor |
| 2920 | A vessels quarter is that section which is _____. | abeam | just aft of the bow | on either side of the stern | dead astern |
| 2921 | Another name for the garboard strake is the _____. | side keel plate | stringer plate | A strake | Z strake |
| 2922 | Branch venting from safety relief valves on barges shall be constructed to discharge gas at what minimum vertical height above the weather deck? | 8 feet | 12 feet | 10 feet | 6 feet |
| 2923 | Mechanical gearing of deck machinery such as the windlass or boat hoists should _____. | not be operated if there is any crew within 10 feet of the machinery | be painted a contrasting color from the base color in order to call attention to the gearing | be open to view so if a foreign object gets in the gearing the operator can immediately stop the machinery | have a guard over the gearing |
| 2924 | On an inspected vessel which abbreviation refers to the horizontal distance between perpendiculars taken at the forward-most and the after-most points on the waterline at her deepest operating draft? | LBP | LOA | LLL | LWL |
| 2925 | The best information on the location of the blocks when dry docking a vessel is contained in the _____. | docking diagram | general arrangement plan | ships docking plan | shell expansion plan |
| 2926 | The horizontal flat surfaces where the upper stock joins the rudder are the _____. | lifting flanges | rudder keys | shoes of the rudder | rudder palms |
| 2927 | The point that is halfway between the forward and after perpendicular and is a reference point for vessel construction is the _____. | center line | half length | mid-body | amidships |
| 2928 | The purpose of a bilge well is to _____. | provide access for the pneumercator | afford access to the shell through the double bottoms | collect water to be pumped out | provide a base line for sounding measurements |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 2929 | The term pintle and gudgeon are associated with the _____. | jumbo boom | rudder | anchor windlass | steering engine |
| 2930 | The terms cant frame and counter are associated with the vessels _____. | stern | steering engine | cargo hatch | forecastle |
| 2931 | The welds used to join shell plates in flush construction are known as _____. | seam welds | fillet welds | butt welds | continuous welds |
| 2932 | The wooden planking that protects the tank top from cargo loading is called _____. | frames | ceiling | shores | toms |
| 2933 | What is the purpose of cant frames in steel vessels? | To support the plating of a cylindrical tank | To add strength to the deck beams which support the weather decks | To provide strength to shell plating at the stern | To support the overhang of the stern |
| 2934 | What is used to prevent accidental flooding of a double bottom or peak tanks in the event of a pipe rupture due to collision? | All tanks must be served by the fewest possible number of pipes to reduce the possibility of rupture. | Suction lines are fitted with a non-return valve | Separate lines are provided for filling and pumping these tanks. | Pipe lines must run vertically from the tank to a point above the margin line before turning fore or aft towards the pump. |
| 2935 | While in dry dock your vessel will be belt-gauged. This process involves _____. | drilling or sonic-testing the hull to determine the plate thickness | measuring the thickness of the tail shaft liner | taking the vessels offsets to check for hull deformation | testing and examining the anchor cables for defective links |
| 2936 | While in transit during heavy weather the crew aboard a semisubmersible should be alert to repeated pounding of waves on the lower bracing. If necessary the unit should be _____. | ballasted to a draft in which the KG exceeds the maximum allowed | deballasted to a shallower draft | towed in the trough of the waves | ballasted to survival draft |
| 2937 | Following a collision or accident the Master of each vessel involved must render assistance to persons affected by the collision or accident _____. | if he can do so without any risk to his vessel | without regard to any danger to his vessel | if he can do so without undue delay | if he can do so without serious danger to his vessel or to individuals on board |
| 2938 | The fitting at the end of a cargo line in a tank that allows suction to be taken close to the bottom of a tank is a _____. | strainer | vacuum valve | suction end | bell-mouth |

| | | | | | |
|---|---|---|---|---|---|
| 2939 | The total weight of cargo fuel water stores passengers and crew and their effects that a ship can carry is the _____. | loaded displacement | bale cubic | deadweight | gross tonnage |
| 2940 | Ultrasonic testing is used to determine the thickness of a vessel s shell plating and to _____. | provide tail shaft clearances | test welds for subsurface defects | test the links of the anchor cables while being ranged | check the wear of the rudder carrier bearing |
| 2941 | What fitting on the mast works in conjunction with the shrouds to control side bend of the mast? | Hound | Spreader | Crowfoot | Chainplate |
| 2942 | What term indicates a curvature of the decks in a longitudinal direction? | Camber | Sheer | Flare | Deadrise |
| 2943 | Which of the following is the pipe used to connect two separate piping systems on a tank vessel? | crossover | junction | connection | transfer |
| 2944 | Which weld fault can only be detected by a method that examines the internal structure of a weld? | Overlap | Lack of penetration | Undercut | Lack of reinforcement |
| 2945 | A charterer is unable to complete the loading of a vessel during the lay days specified in the charter party. Under these circumstances the _____. | harterer must pay dispatch money | vessel operator can collect demurrage | ship is authorized extra time to discharge the cargo | effective period of the charter is extended |
| 2946 | A term applied to the bottom shell plating in a double-bottom ship is _____. | outer bottom | bottom floor | shear plating | tank top |
| 2947 | A vessel s quarter is that section which is _____. | just aft of the bow | abeam | on either side of the stern | dead astern |
| 2948 | Another name for the garboard strake is the _____. | A strake | side keel plate | Z strake | stringer plate |
| 2949 | Branch venting from safety relief valves on barges shall be constructed to discharge gas at what minimum vertical height above the weather deck? | 8 feet | 6 feet | 12 feet | 10 feet |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 2950 | Mechanical gearing of deck machinery such as the windlass or boat hoists should _____. | be painted a contrasting color from the base color in order to call attention to the gearing | be open to view so if a foreign object gets in the gearing the operator can immediately stop the machinery | have a guard over the gearing | not be operated if there is any crew within 10 feet of the machinery |
| 2951 | On an inspected vessel which abbreviation refers to the horizontal distance between perpendiculars taken at the forward-most and the after-most points on the waterline at her deepest operating draft? | LWL | LLL | LOA | LBP |
| 2952 | The best information on the location of the blocks when dry docking a vessel is contained in the _____. | general arrangement plan | ship s docking plan | docking diagram | shell expansion plan |
| 2953 | The horizontal flat surfaces where the upper stock joins the rudder are the _____. | shoes of the rudder | rudder palms | lifting flanges | rudder keys |
| 2954 | The point that is halfway between the forward and after perpendicular and is a reference point for vessel construction is the _____. | half length | mid-body | center line | amidships |
| 2955 | The purpose of a bilge well is to _____. | provide a base line for sounding measurements | afford access to the shell through the double bottoms | provide access for the pneumercator | collect water to be pumped out |
| 2956 | The term pintle and gudgeon are associated with the _____. | anchor windlass | steering engine | jumbo boom | rudder |
| 2957 | The terms cant frame and counter are associated with the vessel s _____. | steering engine | forecastle | stern | cargo hatch |
| 2958 | The welds used to join shell plates in flush construction are known as _____. | continuous welds | seam welds | butt welds | fillet welds |
| 2959 | The wooden planking that protects the tank top from cargo loading is called _____. | frames | ceiling | shores | toms |
| 2960 | What is the purpose of cant frames in steel vessels? | To provide strength to shell plating at the stern | To support the plating of a cylindrical tank | To support the overhang of the stern | To add strength to the deck beams which support the weather decks |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 2961 | What is used to prevent accidental flooding of a double bottom or peak tanks in the event of a pipe rupture due to collision? | Suction lines are fitted with a non-return valve | Pipe lines must run vertically from the tank to a point above the margin line before turning fore or aft towards the pump. | Separate lines are provided for filling and pumping these tanks. | All tanks must be served by the fewest possible number of pipes to reduce the possibility of rupture. |
| 2962 | While in dry dock your vessel will be belt-gauged. This process involves _____. | measuring the thickness of the tail shaft liner | testing and examining the anchor cables for defective links | taking the vessel s offsets to check for hull deformation | drilling or sonic-testing the hull to determine the plate thickness |
| 2963 | While in transit during heavy weather the crew aboard a semisubmersible should be alert to repeated pounding of waves on the lower bracing. If necessary the unit should be _____. | deballasted to a shallower draft | towed in the trough of the waves | ballasted to a draft in which the KG exceeds the maximum allowed | ballasted to survival draft |
| 2964 | Limber is a term associated with _____. | drainage | emergency gear | deck cargo storage | securing gear |
| 2965 | A skiff hook is a device used to do which of the following? | attach a towline to the eye bolt to the bow of a trailer-able boat | join a towline to a pair of towing bridles | to create a temporary fairlead | shorten the length of catenary in the towline |
| 2966 | A strongback refers to a _____. | deep beam | centerline vertical bulkhead | spanner stay | bar securing a cargo port |
| 2967 | A ballasted vessel sinks enroute to a dry dock. Under these circumstances the vessel s owner can claim _____. | constructive total loss | general average | particular average | actual total loss |
| 2968 | A carling is used aboard ship _____. | to prevent the anchor from fouling when the brake is released | as a connecting strap between the butted ends of plating | to stiffen areas under points of great stress between beams | to provide an extra heavy fitting in a heavy lift cargo rig |
| 2969 | A crack in the deck plating of a vessel may be temporarily prevented from increasing in length by _____. | slot-welding the crack | cutting a square notch at each end of the crack | drilling a hole at each end of the crack | welding a doubler over the crack |
| 2970 | A relief valve for a cargo pump is generally installed _____. | after the suction valve | between the pump and suction valve | between the pump and discharge valve | after the discharge valve |
| 2971 | A set of interior steps on a ship leading up to a deck from below is known as _____. | stairs | tween-decks | All of the above are acceptable | a companion way |
| 2972 | A thirty pound plate would be _____. | 3/8 thick | 1/2 thick | 3/4 thick | 1 thick |

| | | | | | |
|---|---|---|---|---|---|
| 2973 | A vessel is constructed with a steel hull and an aluminum superstructure. Which statement is true? | The aluminum will provide greater resistance to the spread of fire by conduction. | The aluminum structure is usually attached to a steel coaming by a method that insulates the two metals. | If the superstructure is stressed an aluminum structure requires additional expansion joints to prevent fracture. | The steel at the area of the aluminum-to-steel connection must be closely checked for galvanic corrosion. |
| 2974 | A vessel is involved in a casualty. The cost of property damage includes the _____. | damage claims awarded to individuals or companies involved in the casualty up to a maximum of $50 000 | cost of labor and material to restore the vessel to the service condition which existed before the casualty | loss of revenue while the vessel is being repaired up to a maximum of $50 000 | All of the above |
| 2975 | A welded joint s effectiveness is considered _____. | 0.48 | 0.9 | 1.21 | 1 |
| 2976 | All electrical appliances aboard a vessel should be grounded to _____. | increase their operating efficiency | prevent unauthorized personnel from operating them | prevent them from falling when the vessel rolls | protect personnel from electrical shock |
| 2977 | An implied warranty of seaworthiness on the part of the vessel s owner lies in the _____. | Certificate of Inspection | Classification Certificate | contract of carriage i.e. Bill of Lading | Cargo Manifest |
| 2978 | Dead freight is the charge for the _____. | cost of transshipment of over-carried cargo | difference in the amount of cargo loaded and the amount of cargo booked through no fault of the vessel | carriage of demise cargo | difference in the amount of cargo loaded and the amount of cargo discharged |
| 2979 | Freeboard is measured from the upper edge of the _____. | sheer strake | bulwark | deck line | gunwale bar |
| 2980 | Gross tonnage indicates the vessel s _____. | draft in feet | total weight including cargo | displacement in metric tons | volume in cubic feet |
| 2981 | In a combination chain and wire rope mooring system the anchor chain is deployed at the anchor end of the line to _____. | reduce the time to retrieve the line | increase fatigue life of the system | reduce the catenary | increase the holding power |
| 2982 | In a combination chain and wire rope mooring system the chain is deployed at the anchor end of the line to _____. | eliminate the need for mooring buoys | increase fatigue life | increase the catenary | prevent the anchor from fouling |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 2983 | In a longitudinally-framed ship the longitudinal frames are held in place and supported by athwartship members called _____. | stringers | floors | margin plates | web frames |
| 2984 | In nautical terminology a dog is a _____. | wedge | crow bar | heavy steel beam | device to force a water tight door against the frame |
| 2985 | In vessel construction the garboard strake is _____. | another term for the bilge keel | located next to and parallel to the gunwale | located next to and parallel to the keel | another term for the rub rail |
| 2986 | Mechanical gearing of deck machinery such as the windlass or towing engine should _____. | be painted a contrasting color from the base color in order to call attention to the gearing | have a guard over the gearing | be open to view so if a foreign object gets in the gearing the operator can immediately stop the machinery | not be operated if there is any crew within 10 feet of the machinery |
| 2987 | Molded depth is measured from the _____. | inside of the shell | top of the garboard stake | top of the center vertical keel | outside of the shell |
| 2988 | On a tankship sanitary inspections of the crew s quarters are the responsibility of the _____. | Master and Chief Mate | Master and union delegate | Master and Second Mate | Master and Chief Engineer |
| 2989 | One function of a bulwark is to _____. | reinforce the side stringers | help keep the deck dry | prevent stress concentrations on the stringer plate | protect against twisting forces exerted on the frame of the vessel |
| 2990 | One of the requirements for a general average act is _____. | All of the above | a successful venture | no imminent peril | no losses |
| 2991 | GM is a measure of: | The amount of reserve bouyancy | The initial stability of the vessel | neither A nor B | both A & B |
| 2992 | When using stabilogauge, unless the density correction is applied, the center of gravity of a loadable compartment is assumed to be: | On deck of the compartment | At 1/3 of the height of the compartment | At 1/2 of the height of the compartment | At the geometric centerof the compartment |
| 2993 | The value of KM at any draft may be taken from the: | Stabilty Table | Building plans of the ship | Trimming Table | Hydrostatic Table |
| 2994 | The volume of all watertight enclosed spaces above water line is called: | Freeboard | Reserved bouyancy | Free surface | Marginal stability |

| | | | | | |
|---|---|---|---|---|---|
| 2995 | In regards to the center of bouyancy, which of the following statement is correct? | It is the measure of metacentric height | It moves toward the high side of an inclines vessel | It is located in the same position regardless of displacement | It moves toward the low side of an inclines vessel |
| 2996 | Which of the following will increase the height of the center of buoyancy of your vessel? | Loading weight in upper decks | Shifting weight from lower to upper decks | Discharging weight from lower decks | Shifting weight from upper to lower decks |
| 2997 | An intact bouyancy means: | An intact space when flooded will not cause the vessel to sink | The space where all the vertical upward forces of buoyancy are considered to be concentrated | An intact space below the flooded area | The volume of all intact spaces above the waterline |
| 2998 | The percentage of the total surface area or volume of a flooded compartment that can be occupied by water by damage is called: | One compartment standard | Form gain | Permeability | Center of buoyancy |
| 2999 | Your vessel has been damaged and is partially flooded. The first step to be taken in attempting to save the vessel is to _____. | plug the hole(s) in the outer shell | calculate the free surface effect and lost buoyancy to determine the vessels stability | pump out the water inside the vessel | establish flooding boundaries and prevent further spread of flood water |
| 3000 | The objective of shoring a damaged bulkhead is to _____. | force the warped, bulged, or deformed sections back into place | support and hold the area in the damaged position | make a watertight seal at the damaged area | withstand subsequent additional damage |
| 3001 | What must be accurately determined to assess the potential for progressive flooding after a vessel has been damaged? | The integrity of the water tight boundaries | The capacity of the water sprinkler systems | The operation of the machinery space bilge level alarms | The operation of emergency bilge system |
| 3002 | Control of flooding should be addressed _____. | following control of fire | only if a threat exists | first | following restoration of vital services |
| 3003 | In a longitudinally framed vessel, the longitudinal frames are held in place in a place and supported by athwartship members called: | Floor | Margin plates | Web frames | Stringers |
| 3004 | The strake next to the keel is: | Gangplank | Garboard | Keelson | Gunwale |
| 3005 | The bleeder plug, or docking plug located on a motor vessel double bottom tank is used to _____. | provide a secondary means of tank sounding | empty the tank when in drydock | vent air from the tank when bunkering | indicate when the tank is pressed up |

| | | | | | |
|---|---|---|---|---|---|
| 3006 | The bilge keel is for the purpose of: | Reducing rolling | Adding strength to main structural members | Acting bumper when vessel is on drydock | Strengthening the bilge |
| 3007 | The inward curvature of the ships side is the: | Sagging | Flare | Tumble home | Hogging |
| 3008 | The vessels quarter is located _____. | just forward of the beam either side | abeam | dead astern | on either side of the beam |
| 3009 | Displacement refers to the _____. | grss tonnage of a vessel | number of long tons of water displaced by a vessel afloat | cubic capacity of a vessel | deadweight carrying capacity of a vessel |
| 3010 | The extension of the after part of the keel in a single-screw vessel upon which the stern post rests is called_____. | strut | skeg | boss | knuckle |
| 3011 | On a single-screw vessel the stern frame _____. | furnishes support to the rudder, propeller shaft, and transom frame | transfer the driving force of the propeller to the hull | provides foundations for after mooring winches | provides foundations for the main propulsion engines |
| 3012 | Fire hose stations shall be marked in red letters and figures such as Fire Station No. "1", "2", "3", etc. The height of the letters and figures must be at least _____. | 1/2 inch | 1-1/2 inches | 2 inches | 1 inch |
| 3013 | When two fire hose teams are attacking a fire they should _____. | use different fire hose pressures | use fire hoses of different sizes | not attack the fire from opposite sides | not wear protective clothing |
| 3014 | You are fighting a fire in the electrical switchboard in the engine room. You should secure the power, then _____. | use a low-velocity fog adapter with the fire hose | determine the cause of the fire | use a portable CO2 extinguisher | use a portable foam extinguisher |
| 3015 | On cargo and miscellaneous vessels what is NOT a required part of the fireman's outfit? | Flame safety lamp | Rigid helmet, boots, and gloves | Combustible gas indicator | Self-contained breathing apparatus with a lifeline attached |
| 3016 | The minimum concentration of a vapor in air which can form an explosive mixture is called the _____. | threshold limit value (TLV) | flash point | auto-ignition point | lower explosive limit (LEL) |
| 3017 | Where on your vessel shall the recharge for each self-contained breathing apparatus be carried? | Bridge or pilothouse area | The same location as the equipment it reactivates | Where they can be readily found | Emergency gear locker |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 3018 | Fire hose couplings _____. | are made of bronze, brass, or soft alloy metals | are specially hardened to prevent crushing | should be greased frequently | should be painted red in order to identify hose lengths |
| 3019 | Each hand portable fire extinguisher must be marked with _____. | the date that it was installed | an identification number | the names of the individuals qualified to use it | the name of the vessel on which it is located |
| 3020 | A squeeze-grip type carbon dioxide portable fire extinguisher has been partially discharged. It should be _____. | replaced in its proper location regardless of weight | replaced in its proper location if weight loss is no more than 15% | replaced in its proper location if weight loss is no more than 25% | labeled empty and recharged as soon as possible |
| 3021 | Which extinguishing agent is most likely to allow reflash as a result of not cooling the fuel below its ignition temperature? | Water spray | Water stream | CO2 | Foam |
| 3022 | Except in rare cases, it is impossible to extinguish a shipboard fire by _____. | . interrupting the chain reaction | removing the oxygen | removing the heat | removing the fuel |
| 3023 | In the event of a fire, the doors to a stair tower must be closed to prevent the spread of fire by _____. | conduction | radiation | convection | ventilation |
| 3024 | Combustible gas indicators operate by drawing an air sample into the instrument _____. | where its specific gravity is measured | where it is ignited by a sparking device | over an electrically heated platinum filament | where it is mixed with nitrogen |
| 3025 | What is the function of the bypass valve on the self-contained breathing apparatus? | The valve reduces the high pressure in the bottle to about 3 psi above atmospheric pressure. | In the event of a malfunction in the equipment, the valve can be operated manually to give the wearer air. | When pressure in the apparatus exceeds 7 psi above atmospheric pressure, the valve opens to release pressure. | The valve opens in excessive heat to release the oxygen in the bottle and prevent the bottle from exploding. |
| 3026 | The function of the bypass valve on the self-contained breathing apparatus is to _____. | allow the wearer to manually give himself oxygen | control the pressure of the oxygen as it enters the body | allow exhaled gases to pass outside the bottle | release excess heat which would otherwise cause the bottle to explode |
| 3027 | You are underway when a fire breaks out in the forward part of your vessel. If possible you should _____. | call for assistance | keep going at half speed | put the vessel's stern into the wind | abandon ship to windward |
| 3028 | When two fire hose teams are attacking a fire they should _____. | not attack the fire from opposite sides | use different fire hose pressures | use fire hoses of different sizes | not wear protective clothing |

| | | | | | |
|---|---|---|---|---|---|
| 3029 | Fire alarm system thermostats are actuated by _____. | pressure loss due to air being heated | the difference in thermal expansion of two dissimilar metals | an electric eye which actuates when smoke interferes with the beam | smoke sensors |
| 3030 | A definite advantage of using water as a fire extinguishing agent is its characteristic of _____. | rapid expansion as water absorbs heat and changes to steam | alternate expansion and contraction as water in a liquid state becomes a vapor | absorption of smoke and gases as water is converted from a liquid to a vapor | rapid contraction as water is converted from a liquid to a vapor |
| 3031 | If a firefighting situation calls for low-velocity fog you would _____. | . order the engine room to reduce pressure on the fire pump | put the lever on an all-purpose fire nozzle all the way forward | attach a low-velocity fog applicator with the nozzle shut down | put the lever on an all-purpose fire nozzle all the way back |
| 3032 | The supply of carbon dioxide used in the fixed extinguishing system aboard a cargo vessel MUST be at least sufficient for _____. | the space requiring the largest amount | all cargo spaces | all the spaces of a vessel | the engine room and largest cargo space |
| 3033 | Valves on steam-smothering lines to cargo tanks shall be set with _____. | the master control valve shut and valves to individual cargo tanks shut | the master control valve open and valves to individual cargo tanks shut | the master control valve shut and valves to individual cargo tanks open | all valves open |
| 3034 | At the required fire drill, all persons must report to their stations and demonstrate their ability to perform duties assigned to them _____. | By the Coast Guard regulations | In the Muster List ("Station Bill") | At the previous safety meeting | By the person conducting the drill |
| 3035 | How often shall crew members participate in fire drills? | once every year | once every 6 months | once every month | once every week |
| 3036 | All of the following are part of the fire triangle EXCEPT _____. | oxygen | heat | fuel | electricity |
| 3037 | What is required in addition to the heat, fuel, and oxygen of the fire triangle to have a fire? | Electricity | Smoke | Chain reaction | Pressure |
| 3038 | How does foam extinguish an oil fire? | By cooling the oil below the ignition temperature | By increasing the weight of the oil | By excluding the oxygen from the fire | By removing the fuel source from the fire |
| 3039 | Extinguishing oil fire is very effective when: | Removing fuel | Spraying with water | Cooling below its ignition temperature | Cutting off oxygen source |

| | | | | | |
|---|---|---|---|---|---|
| 3040 | Fire alarm system thermostats are actuated by? | an electric eye which actuates when smoke interfere with the beam | difference in thermal expansion of two dissimilar metals | pressure loss due to air being heated | smoke sensors |
| 3041 | Fuel vents are fitted with corrosion resistant screen to prevent: | Damge to the ball check | Flames entering the tank vent | Escape of flammable vapors | Corrosion in the tank vent |
| 3042 | Foam extinguishes fire by: | Inerting the air | Cooling | Smoothering | Chemical action |
| 3043 | Which fire extinguishing agent has the greatest capacity for absorbing heat? | Water | Foam | Dry chemical | Carbon dioxide |
| 3044 | The smoke detector (fire indicator) indicates fire in a cargo hold loaded by general cargo. What first action should be taken? | Use the ship's gas extinguishing central system to put out the fire | Start the fire pumps, open the hatches and start fighting the fire by fire hoses | Inspect the scene before deciding the method to be used for fire-fighting | Close the ventilation system and other openings to the hold in order to choke the fire |
| 3045 | The total available supply of CO2 for use in a fixed extinguishing system of a cargo vessel shall be at least sufficient for_____. | Space requiring largest amount | All cargo-space | Engine room and largest cargo space | All the space of the vessel |
| 3046 | Which fire-fighting equipment is most efficient and with least side effects in case of a large fire in the engine room? | Sprinkler system | Central gas extinguishing system and/or water fog. | Powder extinguishing system | Central foam extinguishing system |
| 3047 | Which extinguishing agent is the best for use on electrical fires? | CO2 | Water fog | Foam | Dry chemical |
| 3048 | How does low expansion foam act as an extinguishing agent when dealing with oil fires? | By cooling only | The heat from the fire causes the foam to produce an inert gas which gradually extinguishes the fire. | By smothering and also providing some cooling | By smothering only |
| 3049 | One of the limitations of foam as an extinguishing agent is that foam | is heavier than oil and sinks below its surface | cannot be made with salt water | Conducts electricity | is corrosive and a hazard to fire fighters |
| 3050 | Which activity will have the greatest fire-fighting effect in case of a fire? | All possible fire-fighting equipment is brought to the scene | All fire-fighting teams are organized as soon as possible | Call the Chief Officer | Extinguishing attempt is started immediately |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 3051 | Fire in an engine compartment is best extinguished with carbon dioxide gas (CO2) and by _____. | Increasing the air flow to the compartment by blowers | Completely closing the compartment | Closing the compartment except for the ventilators | Leaving the compartment open to the air |
| 3052 | If heavy smoke is coming from the paint locker, the FIRST firefighting response should be to _____. | Enter and use a portable extinguisher | Release the CO2 flooding system | Open the door to evaluate the extent of the fire | Secure the ventilation |
| 3053 | There is a fire aft aboard your vessel. To help fight the fire, you should put the _____. | wind off either beam | Stern into the wind and decrease speed | Bow into the wind and decrease speed | Stern into the wind and increase speed |
| 3054 | Control of fire should be addressed _____. | Following establishment of fire boundaries | Immediately | Immediately after restoring vital services | Following control of flooding |
| 3055 | You are in a tank wearing the self-contained breathing apparatus and you desire to return topside. How many tugs of the lifeline mean to take up the slack? | Two | One | Four | Three |
| 3056 | Which statement is FALSE regarding Halon as a fire extinguishing agent? | It is noncorrosive. | It is more effective than CO2. | It leaves no residue. | It is always non-toxic. |
| 3057 | Fire hose stations shall be marked in red letters and figures such as Fire Station No. "1", "2", "3", etc. The height of the letters and figures must be at least _____. | 1/2 inch | 2 inches | 1 inch | 1-1/2 inches |
| 3058 | When two fire hose teams are attacking a fire they should _____. | use fire hoses of different sizes | not wear protective clothing | not attack the fire from opposite sides | use different fire hose pressures |
| 3059 | You are fighting a fire in the electrical switchboard in the engine room. You should secure the power, then _____. | determine the cause of the fire | use a low-velocity fog adapter with the fire hose | use a portable CO2 extinguisher | use a portable foam extinguisher |
| 3060 | On cargo and miscellaneous vessels what is NOT a required part of the fireman's outfit? | Self-contained breathing apparatus with a lifeline attached | Flame safety lamp | Combustible gas indicator | Rigid helmet, boots, and gloves |
| 3061 | The minimum concentration of a vapor in air which can form an explosive mixture is called the _____. | lower explosive limit (LEL) | threshold limit value (TLV) | auto-ignition point | flash point |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 3062 | Where on your vessel shall the recharge for each self-contained breathing apparatus be carried? | The same location as the equipment it reactivates | Emergency gear locker | Bridge or pilothouse area | Where they can be readily found |
| 3063 | Fire hose couplings _____. | are made of bronze, brass, or soft alloy metals | should be greased frequently | should be painted red in order to identify hose lengths | are specially hardened to prevent crushing |
| 3064 | Each hand portable fire extinguisher must be marked with _____. | an identification number | the date that it was installed | the name of the vessel on which it is located | the names of the individuals qualified to use it |
| 3065 | A squeeze-grip type carbon dioxide portable fire extinguisher has been partially discharged. It should be _____. | labeled empty and recharged as soon as possible | replaced in its proper location if weight loss is no more than 15% | replaced in its proper location regardless of weight | replaced in its proper location if weight loss is no more than 25% |
| 3066 | Which extinguishing agent is most likely to allow reflash as a result of not cooling the fuel below its ignition temperature? | Water spray | Water stream | CO2 | Foam |
| 3067 | On an inspection of your tankship you notice that there are no portable fire extinguishers in the pumproom. To comply with regulations, you _____. | should arrange to have a B-II extinguisher placed in the vicinity of the exit | should arrange to have a B-II extinguisher placed in the lower pumproom | need not be concerned since no portable extinguishers are required in the pumproom | may substitute sand for the required extinguishers |
| 3068 | Except in rare cases, it is impossible to extinguish a shipboard fire by _____. | removing the oxygen | removing the fuel | . interrupting the chain reaction | removing the heat |
| 3069 | In the event of a fire, the doors to a stair tower must be closed to prevent the spread of fire by _____. | radiation | convection | conduction | ventilation |
| 3070 | Combustible gas indicators operate by drawing an air sample into the instrument _____. | where it is mixed with nitrogen | where its specific gravity is measured | where it is ignited by a sparking device | over an electrically heated platinum filament |
| 3071 | What is the function of the bypass valve on the self-contained breathing apparatus? | The valve opens in excessive heat to release the oxygen in the bottle and prevent the bottle from exploding. | In the event of a malfunction in the equipment, the valve can be operated manually to give the wearer air. | When pressure in the apparatus exceeds 7 psi above atmospheric pressure, the valve opens to release pressure. | The valve reduces the high pressure in the bottle to about 3 psi above atmospheric pressure. |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 3072 | The function of the bypass valve on the self-contained breathing apparatus is to _____. | release excess heat which would otherwise cause the bottle to explode | allow the wearer to manually give himself oxygen | control the pressure of the oxygen as it enters the body | allow exhaled gases to pass outside the bottle |
| 3073 | You are underway when a fire breaks out in the forward part of your vessel. If possible you should _____. | abandon ship to windward | keep going at half speed | call for assistance | put the vessel's stern into the wind |
| 3074 | When two fire hose teams are attacking a fire they should _____. | use different fire hose pressures | not attack the fire from opposite sides | use fire hoses of different sizes | not wear protective clothing |
| 3075 | What is the minimum number of fire pumps required on a cargo vessel of 2,000 GT? | 1 | 4 | 3 | 2 |
| 3076 | Which vessel greater than 100 GT is NOT required to have an EPIRB. | A fishing vessel | A sailing vessel | A towing vessel | A non self-propelled vessel in tow |
| 3077 | Fire alarm system thermostats are actuated by _____. | an electric eye which actuates when smoke interferes with the beam | the difference in thermal expansion of two dissimilar metals | smoke sensors | pressure loss due to air being heated |
| 3078 | A definite advantage of using water as a fire extinguishing agent is its characteristic of _____. | rapid contraction as water is converted from a liquid to a vapor | absorption of smoke and gases as water is converted from a liquid to a vapor | rapid expansion as water absorbs heat and changes to steam | alternate expansion and contraction as water in a liquid state becomes a vapor |
| 3079 | If a firefighting situation calls for low-velocity fog you would _____. | . order the engine room to reduce pressure on the fire pump | attach a low-velocity fog applicator with the nozzle shut down | put the lever on an all-purpose fire nozzle all the way forward | put the lever on an all-purpose fire nozzle all the way back |
| 3080 | The supply of carbon dioxide used in the fixed extinguishing system aboard a cargo vessel MUST be at least sufficient for _____. | the space requiring the largest amount | the engine room and largest cargo space | all cargo spaces | all the spaces of a vessel |
| 3081 | Valves on steam-smothering lines to cargo tanks shall be set with _____. | the master control valve shut and valves to individual cargo tanks shut | all valves open | the master control valve shut and valves to individual cargo tanks open | the master control valve open and valves to individual cargo tanks shut |
| 3082 | The number of fire detectors that a single power supply is capable to handle for continuous operation is limited to a | 100 | 50 | 80 | 200 |

| | | | | | |
|---|---|---|---|---|---|
| | maximum of _____. | | | | |
| 3083 | What do you called an area defined as a contour of land or a physical barrier that retains a fuel to a depth greater than 1"? | Bund | Bond | Band | Bend |
| 3084 | Running on emergency power source, all connected visual and audible fire alarm signals on fixed fire detection system to be capable of operating for a period of at least _____. | 1 hour | 30mins | 1.5 hours | 15mins |
| 3085 | Smoke detectors required in all stairways, corridors and escape routes within accommodation spaces shall operate before the smoke density exceeds | 22.5% obscuration per metre, but not until the smoke density exceeds 2.5% obscuration per metre | 12.5% obscuration per metre, but not until the smoke density exceeds 2% obscuration per metre | 15% obscuration per metre, but not until the smoke density exceeds 2% obscuration per metre | 125% obscuration per metre, but not until the smoke density exceeds 2% obscuration per metre |
| 3086 | Foam expansion ratio of 8:1 means _____. | 800 gallons of water combined from 100 gallons of foam solution | 800 gallons of unfinished foam were created from 100 gallons of foam solution | 800 gallons of water mixed from 100 gallons of foam solution | 800 gallons of finished foam were created from 100 gallons of foam solution |
| 3087 | What is a device that siphons foam from a container to make a foam solution? | Angle proportioner | Line proportioner | Curve proportioner | Shape proportioner |
| 3088 | What is the meaning of ARC in foam? | Aqueous Resistance Concentrate | Alcohol Resistance Concentrate | Aspirate Resistance Concentrate | Adhesive Resistance Concentrate |
| 3089 | What do you called the violent ejection of flammable liquid from its container caused by the vaporization of water beneath a body of burning hydrocarbon liquid? | Hot over | Burning over | Cold over | Boil over |
| 3090 | What do you called the manual addition of foam concentrate to a water storage container or to make a foam solution? | Boil mix | Concentrate mix | Batch mix | Complete mix |

| | | | | | |
|---|---|---|---|---|---|
| 3091 | What is a chemical that, when added to water, reduces the surface tension and increases the wetting effectiveness of the solution and causes it to spread and penetrate exposed objects more effectively? | Mixing agent | Wetting agent | Concentrating agent | Drying agent |
| 3092 | Sread of fire may be prevented by which of the following? | heating the surface adjacent to the fire | throwing the burning material overboard | removing combustible materials from adjacent areas | covering the fire with cloth |
| 3093 | What do you called the decomposition by microbial action as with synthetic detergent or protein based agents? | Degradation | Micro Degradation | Biodegradation | Protein Degradation |
| 3094 | What is a negative change in the characteristics of qualities of foam? | Degraduation | Degradation | Drainage | Discharge |
| 3095 | What is an inert organic compound in which fluorine replaces hydrogen? | Hydrofluoro | Fluorohydro | Fluorocarbon | Fluoroprotein |
| 3096 | According to SOLAS convention, fired fire detection system cables must be _____. | Fire proof | Flame retardant | Heavily insulated | Heat proof |
| 3097 | Cables used for fixed fire detection system should be _____. | Heat proof | Fire proof | Heavily insulated | Flame retardant |
| 3098 | As far as practicable, every fire extinguisher on board ship shall be clearly marked of the following EXCEPT: | labeling of every fire extinguisher | name of manufacturer and inspector | date of expiry | pictorial and legible operating instructions |
| 3099 | In passenger ships fixed fire fighting system, a section of detectors and manually operated call points shall not be situated in more than one main vertical zone except on _____. | Mess hall | Pool area | Cabin balconies | Lounge |
| 3100 | Supplies for fixed fire detection system should have feeders that shall run to a switch situated in or adjacent to the control panel for the fire detection system, such switch must be _____. | automatic change-over | manual recovery | manual change over | automatic recovery |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 3101 | What do you called the ratio of volume of foam formed to the volume of solution used to generate the foam? | Expansion ratio | All of the above | Combination ratio | Mixed ratio |
| 3102 | Which faults would you consider less serious on a fire hydrant? | No volt | None of the above | Not greased | No hydrant cap fitted |
| 3103 | The main feeder for fixed fire detection system shall run from the main switchboard to the change-over switch passing through another distributing switchboard, it is _____ under SOLAS convention. | not stated | not regulated | allowed | not allowed |
| 3104 | What is a thin, durable, plastic layer formed on a polar solvent fuel surface protecting the foam cells from destruction by the fuel? | Polymeric membrane | Polydemeric membrane | Polygon membrane | Poly membrane |
| 3105 | Heat transfer includes convection. Convection spreads a fire by: | smoke sorrounding a compartment | heat from the fire | heated gases flowing through ventilation systems | the heat transfer across an unobstructed space |
| 3106 | describes a relationship between flash point and ignition temperature? | The ignition temperature is always lower | None of the above | The flash point is always higher | The ignition temperature is always higher |
| 3107 | What is a flammable liquid fire such as a spill on a solid surface where the liquid is not present in a depth exceeding one inch? | Skin fire | Half fire | Whole fire | Body fire |
| 3108 | The number of fire detectors that a single power supply is capable to handle for continuous operation is limited to a maximum of _____. | 100 | 50 | 80 | 200 |
| 3109 | What do you called an area defined as a contour of land or a physical barrier that retains a fuel to a depth greater than 1"? | Bend | Bond | Band | Bund |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 3110 | Running on emergency power source, all connected visual and audible fire alarm signals on fixed fire detection system to be capable of operating for a period of at least _____. | 1 hour | 1.5 hours | 30mins | 15mins |
| 3111 | Smoke detectors required in all stairways, corridors and escape routes within accommodation spaces shall operate before the smoke density exceeds | 125% obscuration per metre, but not until the smoke density exceeds 2% obscuration per metre | 22.5% obscuration per metre, but not until the smoke density exceeds 2.5% obscuration per metre | 15% obscuration per metre, but not until the smoke density exceeds 2% obscuration per metre | 12.5% obscuration per metre, but not until the smoke density exceeds 2% obscuration per metre |
| 3112 | Foam expansion ratio of 8:1 means _____. | 800 gallons of unfinished foam were created from 100 gallons of foam solution | 800 gallons of finished foam were created from 100 gallons of foam solution | 800 gallons of water combined from 100 gallons of foam solution | 800 gallons of water mixed from 100 gallons of foam solution |
| 3113 | What is a device that siphons foam from a container to make a foam solution? | Line proportioner | Shape proportioner | Curve proportioner | Angle proportioner |
| 3114 | What is the meaning of ARC in foam? | Aqueous Resistance Concentrate | Alcohol Resistance Concentrate | Aspirate Resistance Concentrate | Adhesive Resistance Concentrate |
| 3115 | What do you called the violent ejection of flammable liquid from its container caused by the vaporization of water beneath a body of burning hydrocarbon liquid? | Cold over | Boil over | Hot over | Burning over |
| 3116 | What do you called the manual addition of foam concentrate to a water storage container or to make a foam solution? | Boil mix | Concentrate mix | Complete mix | Batch mix |
| 3117 | What is a chemical that, when added to water, reduces the surface tension and increases the wetting effectiveness of the solution and causes it to spread and penetrate exposed objects more effectively? | Mixing agent | Drying agent | Wetting agent | Concentrating agent |
| 3118 | Sread of fire may be prevented by which of the following? | throwing the burning material overboard | covering the fire with cloth | heating the surface adjacent to the fire | removing combustible materials from adjacent areas |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 3119 | What do you called the decomposition by microbial action as with synthetic detergent or protein based agents? | Biodegradation | Protein Degradation | Micro Degradation | Degradation |
| 3120 | What is a negative change in the characteristics of qualities of foam? | Discharge | Degraduation | Drainage | Degradation |
| 3121 | What is an inert organic compound in which fluorine replaces hydrogen? | Fluoroprotein | Hydrofluoro | Fluorocarbon | Fluorohydro |
| 3122 | According to SOLAS convention, fired fire detection system cables must be _____. | Flame retardant | Heavily insulated | Fire proof | Heat proof |
| 3123 | Cables used for fixed fire detection system should be _____. | Heavily insulated | Fire proof | Heat proof | Flame retardant |
| 3124 | As far as practicable, every fire extinguisher on board ship shall be clearly marked of the following EXCEPT: | labeling of every fire extinguisher | pictorial and legible operating instructions | name of manufacturer and inspector | date of expiry |
| 3125 | In passenger ships fixed fire fighting system, a section of detectors and manually operated call points shall not be situated in more than one main vertical zone except on _____. | Mess hall | Lounge | Cabin balconies | Pool area |
| 3126 | Supplies for fixed fire detection system should have feeders that shall run to a switch situated in or adjacent to the control panel for the fire detection system, such switch must be _____. | automatic change-over | automatic recovery | manual recovery | manual change over |
| 3127 | What do you called the ratio of volume of foam formed to the volume of solution used to generate the foam? | All of the above | Mixed ratio | Expansion ratio | Combination ratio |
| 3128 | Which faults would you consider less serious on a fire hydrant? | None of the above | No hydrant cap fitted | No volt | Not greased |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 3129 | The main feeder for fixed fire detection system shall run from the main switchboard to the change-over switch passing through another distributing switchboard, it is _____ under SOLAS convention. | not regulated | not allowed | allowed | not stated |
| 3130 | What is a thin, durable, plastic layer formed on a polar solvent fuel surface protecting the foam cells from destruction by the fuel? | Polydemeric membrane | Polymeric membrane | Polygon membrane | Poly membrane |
| 3131 | Heat transfer includes convection. Convection spreads a fire by: | smoke sorrounding a compartment | the heat transfer across an unobstructed space | heat from the fire | heated gases flowing through ventilation systems |
| 3132 | describes a relationship between flash point and ignition temperature? | The ignition temperature is always higher | None of the above | The ignition temperature is always lower | The flash point is always higher |
| 3133 | What is a flammable liquid fire such as a spill on a solid surface where the liquid is not present in a depth exceeding one inch? | Half fire | Whole fire | Body fire | Skin fire |
| 3134 | The number of fire detectors that a single power supply is capable to handle for continuous operation is limited to a maximum of _____. | 80 | 50 | 100 | 200 |
| 3135 | Running on emergency power source, all connected visual and audible fire alarm signals on fixed fire detection system to be capable of operating for a period of at least _____. | 1.5 hours | 1 hour | 30mins | 15mins |
| 3136 | Smoke detectors required in all stairways, corridors and escape routes within accommodation spaces shall operate before the smoke density exceeds | 15% obscuration per metre, but not until the smoke density exceeds 2% obscuration per metre | 12.5% obscuration per metre, but not until the smoke density exceeds 2% obscuration per metre | 22.5% obscuration per metre, but not until the smoke density exceeds 2.5% obscuration per metre | 125% obscuration per metre, but not until the smoke density exceeds 2% obscuration per metre |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 3137 | Foam expansion ratio of 8:1 means _____. | 800 gallons of unfinished foam were created from 100 gallons of foam solution | 800 gallons of water mixed from 100 gallons of foam solution | 800 gallons of water combined from 100 gallons of foam solution | 800 gallons of finished foam were created from 100 gallons of foam solution |
| 3138 | What is a device that siphons foam from a container to make a foam solution? | Curve proportioner | Line proportioner | Angle proportioner | Shape proportioner |
| 3139 | What is the meaning of ARC in foam? | Aspirate Resistance Concentrate | Aqueous Resistance Concentrate | Alcohol Resistance Concentrate | Adhesive Resistance Concentrate |
| 3140 | What do you called the violent ejection of flammable liquid from its container caused by the vaporization of water beneath a body of burning hydrocarbon liquid? | Boil over | Hot over | Cold over | Burning over |
| 3141 | What do you called the manual addition of foam concentrate to a water storage container or to make a foam solution? | Batch mix | Boil mix | Concentrate mix | Complete mix |
| 3142 | What is a chemical that, when added to water, reduces the surface tension and increases the wetting effectiveness of the solution and causes it to spread and penetrate exposed objects more effectively? | Concentrating agent | Wetting agent | Mixing agent | Drying agent |
| 3143 | Sread of fire may be prevented by which of the following? | heating the surface adjacent to the fire | covering the fire with cloth | removing combustible materials from adjacent areas | throwing the burning material overboard |
| 3144 | What do you called the decomposition by microbial action as with synthetic detergent or protein based agents? | Biodegradation | Protein Degradation | Degradation | Micro Degradation |
| 3145 | What is a negative change in the characteristics of qualities of foam? | Discharge | Degraduation | Degradation | Drainage |
| 3146 | What is an inert organic compound in which fluorine replaces hydrogen? | Fluorohydro | Fluoroprotein | Hydrofluoro | Fluorocarbon |
| 3147 | According to SOLAS convention, fired fire | Fire proof | Heat proof | Flame retardant | Heavily insulated |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| | detection system cables must be _____. | | | | |
| 3148 | Cables used for fixed fire detection system should be _____. | Heavily insulated | Fire proof | Flame retardant | Heat proof |
| 3149 | As far as practicable, every fire extinguisher on board ship shall be clearly marked of the following EXCEPT: | labeling of every fire extinguisher | name of manufacturer and inspector | date of expiry | pictorial and legible operating instructions |
| 3150 | In passenger ships fixed fire fighting system, a section of detectors and manually operated call points shall not be situated in more than one main vertical zone except on _____. | Cabin balconies | Lounge | Pool area | Mess hall |
| 3151 | Supplies for fixed fire detection system should have feeders that shall run to a switch situated in or adjacent to the control panel for the fire detection system, such switch must be _____. | automatic change-over | manual recovery | manual change over | automatic recovery |
| 3152 | What do you called the ratio of volume of foam formed to the volume of solution used to generate the foam? | All of the above | Combination ratio | Mixed ratio | Expansion ratio |
| 3153 | Which faults would you consider less serious on a fire hydrant? | No volt | Not greased | No hydrant cap fitted | None of the above |
| 3154 | The main feeder for fixed fire detection system shall run from the main switchboard to the change-over switch passing through another distributing switchboard, it is _____ under SOLAS convention. | not stated | not regulated | allowed | not allowed |
| 3155 | What is a thin, durable, plastic layer formed on a polar solvent fuel surface protecting the foam cells from destruction by the fuel? | Polymeric membrane | Poly membrane | Polygon membrane | Polydemeric membrane |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 3156 | Heat transfer includes convection. Convection spreads a fire by: | heated gases flowing through ventilation systems | the heat transfer across an unobstructed space | heat from the fire | smoke sorrounding a compartment |
| 3157 | describes a relationship between flash point and ignition temperature? | None of the above | The ignition temperature is always higher | The ignition temperature is always lower | The flash point is always higher |
| 3158 | What is a flammable liquid fire such as a spill on a solid surface where the liquid is not present in a depth exceeding one inch? | Skin fire | Body fire | Whole fire | Half fire |
| 3159 | A fire in the galley ALWAYS poses the additional threat of _____. | a grease fire in the ventilation system | causing loss of stability | contaminating food with extinguishing agent | spreading through the engineering space |
| 3160 | Aboard a cargo vessel the carbon dioxide supply used in a fixed extinguishing system MUST at least be sufficient for what space(s)? | all cargo spaces | all the spaces of a vessel | the engine room and largest cargo space | the space requiring the largest amount |
| 3161 | As compared to carbon dioxide dry chemical has which advantage? | More cooling effect | Cleaner | Greater range | Effective on metal fires |
| 3162 | Each fireman s outfit and its spare equipment on a tankship must be stowed in a(n) _____. | unlocked cabinet in the machinery space | locked cabinet in the machinery space | location near a fire hydrant | separate and accessible location |
| 3163 | If heavy smoke is coming from the paint locker the FIRST firefighting response should be to _____. | secure the ventilation | open the door to evaluate the extent of the fire | release the CO2 flooding system | enter and use a portable extinguisher |
| 3164 | In the production of chemical foam by a continuous-type generator _____. | fresh water only should be used | the speed of foam production is slower at lower water temperatures | the maximum water pressure to be used is 50 psi | each pound of foam powder produces about 800 gallons of chemical foam |
| 3165 | No outlet on a fire hydrant may point above the horizontal in order to _____. | avoid personal injury during connection | make connecting easier | prevent spray on electrical equipment | avoid kinking the hose |
| 3166 | Spontaneous combustion is most likely to occur in _____. | overloaded electrical circuits | partially loaded fuel tanks | dirty swabs and cleaning gear | rags soaked in linseed oil |
| 3167 | The accumulation of dangerous fumes generated by the storage batteries is best prevented by _____. | mounting the batteries in a position as high as possible | securing the batteries to vibration reducing mounting brackets | covering the batteries in a nonconducting solid enclosure | natural or mechanical ventilation |

| | | | | | |
|---|---|---|---|---|---|
| 3168 | The required number and type of hand portable fire extinguishers required for a galley having an area of 3 500 square feet is _____. | one B-II | two B-II s or C-II s | two A-II s or B-II s | one C-II |
| 3169 | When discharging a portable CO2 fire extinguisher you should NOT hold the horn of the extinguisher because the horn _____. | becomes extremely hot | becomes extremely cold | could come off in your hands | is placed directly in the flames |
| 3170 | When fighting an oil or gasoline fire in the bilge which of the following should NOT be used? | Solid stream water nozzle | Foam | All-purpose nozzle | Carbon dioxide |
| 3171 | Which danger exists to people when CO2 is discharged into a small enclosed space? | Respiratory arrest | Damaged eardrums | Frostbite | Electric shock |
| 3172 | Which extinguishing agent is best for use on a magnesium fire? | CO2 | Sand | Dry chemical | Water |
| 3173 | Which of the following is the chief source of spontaneous combustion aboard tankers? | gasoline cargo | oil soaked rags or rubbish | kerosene cargo | JP4 cargo |
| 3174 | Why should foam be banked off a bulkhead when extinguishing an oil fire? | To cool the bulkhead closest to the fire | To prevent agitation of the oil and spreading the fire | To prevent any oil on the bulkheads from igniting | To coat the surrounding bulkheads with foam in case the fire spreads |
| 3175 | A combination or all-purpose nozzle produces _____. | low-velocity fog only | a solid stream and fog | a solid stream and foam | a solid stream only |
| 3176 | A fire starts on your vessel while refueling. You should first _____. | determine the source of the fire | stop the ventilation | sound the general alarm | attempt to extinguish the fire |
| 3177 | A fixed carbon dioxide extinguishing system for a machinery space designed without a stop valve in the line leading to the protected space is actuated by _____. | none of the above | two controls | one control | three controls |
| 3178 | A portable foam (stored-pressure type) fire extinguisher would be most useful in combating a fire in _____. | oil drums | generators | the bridge controls | combustible metals |

| | | | | | |
|---|---|---|---|---|---|
| 3179 | A safety outlet is provided on the CO2 discharge piping to prevent _____. | over pressurization of the space being flooded | over pressurization of the CO2 discharge piping | flooding of a space where personnel are present | rupture of cylinder due to temperature increase |
| 3180 | All fire hoses on mobile offshore drilling units must be tested to a pressure of at least _____. | 120 psi | 100 psi | 130 psi | 110 psi |
| 3181 | An important step in fighting any electrical fire is to _____. | stop the vessel | apply water to extinguish the fire | de-energize the circuit | stop ventilation |
| 3182 | Carbon dioxide cylinders which protect machinery spaces paint lockers and tanks may be located within those spaces when the amount of carbon dioxide does not exceed _____. | 600 lbs | 300 lbs | 150 lbs | 450 lbs |
| 3183 | A 2 000 GT tankship is required to carry _____. | two self-contained breathing apparati | two canister type gas masks if such vessel is authorized to carry grade A B C or D liquids | emergency outfits only on an international voyage | one oxygen breathing apparatus with enough lifeline to reach from the open deck to any part of the tanks |
| 3184 | A class B fire is most successfully fought by _____. | using the extinguishing agent to absorb the heat | using the extinguishing agent to make the burning material fire-resistant | cooling the burning material below its ignition temperature | preventing oxygen from reaching the burning material |
| 3185 | A class C fire would be burning _____. | celluloid | electrical insulation | wood | fuel oil |
| 3186 | A CO2 extinguisher which has lost 10% of its charge must be _____. | recharged | weighed again in one month | used at the earliest opportunity | hydro tested |
| 3187 | A double male coupling is one that _____. | has outside threads on both ends | takes two men to operate | has inside threads on both ends | has left hand twist |
| 3188 | A fire hose has a _____. | female coupling at the nozzle end and a male coupling at the hydrant end | male coupling at the nozzle end and a female coupling at the hydrant end | male coupling at both ends | female coupling at both ends |
| 3189 | A fire in a pile of canvas is classified as class _____. | B | C | A | D |
| 3190 | A fire in a pile of dunnage would be classified as class _____. | A | C | D | B |

| | | | | | |
|---|---|---|---|---|---|
| 3191 | A fire in a transformer terminal would be classified as class _____. | B | C | D | A |
| 3192 | A fire in electrical equipment should be extinguished by using _____. | CO2 | salt water | low-velocity fog | foam |
| 3193 | A fire in the radio transmitter would be of what class? | B | A | D | C |
| 3194 | A fire in trash and paper waste is classified as class _____. | A | D | C | B |
| 3195 | A fire main system must have enough fire hydrants so that each accessible space may be sprayed with _____. | a low velocity spray applicator | at least two spray patterns of water | at least 25 psi delivered pressure | a water spray or solid stream |
| 3196 | A fire pump may be used for other purposes if _____. | all of the above conditions are met | no relief valves are installed | one of the required pumps is kept available for use on the fire main system at all times | the other services are run off a reducing station with a pressure gage |
| 3197 | A fire starts in a switchboard due to a short circuit. This is which class of fire? | B | D | C | A |
| 3198 | A flame screen _____. | prevents inert gas from leaving a tank | permits vapors to exit but not enter a tank | permits the passage of vapor but not of flame | prevents the passage of flammable vapors |
| 3199 | A galley grease fire on the stove may be extinguished using _____. | the range hood extinguishing system | foam | fire dampers | water |
| 3200 | A magnesium fire is classified as class _____. | D | A | B | C |
| 3201 | A spanner is a _____. | None of the above | cross connection line between two main fire lines | special wrench for the couplings in a fire hose line | tackle rigged to support a fire hose |
| 3202 | A vessel must have at least two fireman s outfits aboard if she _____. | is under foreign articles | is documented | has more than 49 people aboard | is over 100 gross tons |
| 3203 | Actuating the CO2 fixed system causes the shutdown of the _____. | supply and exhaust ventilation | mechanical and natural ventilation | fuel supply | exhaust ventilation |
| 3204 | After extinguishing a paint locker fire using the fixed CO2 system the next action is to have the space _____. | checked for oxygen content | opened and burned material removed | remain closed with vents off until all boundaries are cool | doused with water to prevent reflash |

| | | | | | |
|---|---|---|---|---|---|
| 3205 | After using a CO2 portable extinguisher it should be _____. | hydrostatically tested | retagged | put back in service if some CO2 remains | recharged |
| 3206 | An oil fire is classified as class _____. | D | B | C | A |
| 3207 | Any extinguishing agent used on a Class C fire must have which important property? | Leaves no residue | Cooling ability | Penetrating power | Nonconductivity |
| 3208 | Any firefighting equipment that is carried in addition to the minimum required must _____. | be stowed in a separate area | be marked as additional equipment | All of the above | meet the applicable standards |
| 3209 | There are two disadvantages to CO2 as a firefighting agent. One of these is the limited quantity available, and the other is _____. | there is no effect on a class A fire even in an enclosed space | that it breaks down under extreme heat to form poisonous gases | that it cannot be used in a dead ship situation with no electrical power to the CO2 pump | the lack of cooling effect on heated materials |
| 3210 | Which toxic gas is a product of incomplete combustion, and is often present when a fire burns in a closed compartment? | Hydrogen sulfide | Carbon dioxide | Carbon monoxide | Nitric oxide |
| 3211 | The primary method by which water spray puts out fires is by _____. | cooling the fire below the ignition temperature | removing the oxygen | diluting combustible vapors | removing combustible material |
| 3212 | A large oil fire on the deck of a ship can be fought most effectively with _____. | foam | dry chemical | Water (cartridge-operated) | high-velocity fog |
| 3213 | The flammable limits of an atmosphere are the _____. | upper and lower percentage of vapor concentrations in an atmosphere which will burn if an ignition source is present | two temperatures between which an atmosphere will self ignite | upper and lower pressures between which an atmosphere will not burn | two temperatures between which an atmosphere will burn if an ignition source is present |
| 3214 | In the production of chemical foam by a continuous-type generator _____. | fresh water only should be used | the maximum water pressure to be used is 50 psi | each pound of foam powder produces about 800 gallons of chemical foam | the speed of foam production is slower at lower water temperatures |
| 3215 | The volatility of a flammable liquid is indicated by its _____. | conversion index | flammable range | ignition temperature | flash point |
| 3216 | The most effective way to apply a foam stream if the fire is on deck or is a running fire, is to direct the stream _____. | onto the surface of the burning liquid | ahead of the burning liquid and bounce it on the fire | at the base of the burning liquid in a sweeping motion | just above the surface of the burning liquid |

| | | | | | |
|---|---|---|---|---|---|
| 3217 | Which type of portable fire extinguishers is NOT designed for use on flammable liquid fires? | Foam (stored-pressure) | Carbon dioxide | Dry chemical | Water (cartridge-operated) |
| 3218 | When approaching a fire from leeward, you should shield firefighters from the fire by using _____. | foam spray | high-velocity fog | low-velocity fog | a straight stream of water |
| 3219 | The BEST method of applying foam to a fire is to _____. | spray directly on the surface of the fire | spray directly on the base of the fire | sweep the fire with the foam | flow the foam down a nearby vertical surface |
| 3220 | The water pockets located on the underside of inflatable liferafts _____. | hold the freshwater required by regulation to be provided in the raft when packed | stow rainwater; these 4 spaces do not take up valuable space | act as stabilizers by filling with sea water as soon as the raft is inflated and upright | none of the options |
| 3221 | When possible, what is the FIRST step in fighting an engine fuel-pump fire which results from a broken fuel line? | Secure all engine room doors, hatches, and vents. | Close the fuel line valve. | Check the spread of the fire with foam. | Cast the barge off the wharf. |
| 3222 | Which extinguishing agent is the best for use on electrical fires? | Foam | Water fog | CO2 | Dry chemical |
| 3223 | What is the MOST important consideration when determining how to fight an electrical fire? | Danger of shock to personnel | Maintaining electrical power | Whether the fire is in machinery or passenger spaces | The amount of toxic fumes created by the extinguisher |
| 3224 | What would be the most effective agent to use to extinguish a fire in drums of flammable liquids stowed on the weather deck of a vessel? | Water fog | Steam | Foam | Carbon dioxide |
| 3225 | The best method of extinguishing a class A fire is to _____. | smother with CO2 | smother fire with foam | remove oxygen from the area | cool fuel below ignition temperature |
| 3226 | The most effective way of applying carbon dioxide from a portable extinguisher to a fire is by _____. | forming a cloud cover over the flames | discharging the carbon dioxide into the heart of the flames | bouncing the discharge off an adjacent bulkhead just above the burning surface | directing the gas at the base of the flames in a slow sweeping motion |
| 3227 | Which extinguishing agent is best for use on a magnesium fire? | CO2 | Sand | Water | Dry chemical |
| 3228 | You will extinguish a fire when you remove _____. | nitrogen | carbon dioxide | oxygen | sodium |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 3229 | Why is carbon dioxide ($CO_2$) better than dry chemical for fighting a class C fire? | $CO_2$ will not dissipate in air. | The dry chemical is a conductor. | It takes smaller amounts of $CO_2$ to cover the same area. | The dry chemical leaves a residue. |
| 3230 | To prevent the spread of fire by convection you should _____. | shut off all electrical power | remove combustibles from direct exposure | cool the bulkhead around the fire | close all openings to the area |
| 3231 | A portable foam (stored-pressure type) fire extinguisher would be most useful in combating a fire in _____. | combustible metals | oil drums | generators | the bridge controls |
| 3232 | What are the most important reasons for using water fog to fight fires? | Allows fire to be attacked from leeward, saturates liquid surfaces | Reaches areas not protected by steam or $CO_2$ smothering systems | Smothers burning surfaces, organically destroys fuel | Cools fire and adjacent surfaces, provides protective barrier |
| 3233 | $CO_2$ extinguishes a fire by _____. | cooling | smothering | chemical action | all of the options |
| 3234 | How often shall crew members participate in fire drills? | once every month | once every week | once every year | once every 6 months |
| 3235 | The Chief Engineer belongs to what emergency team: | Engine Room team | Back-up team | Mobile Team | Command team |
| 3236 | How does foam extinguish an oil fire? | By cooling the oil below the ignition temperature | By increasing the weight of the oil | By removing the fuel source from the fire | By excluding the oxygen from the fire |
| 3237 | Extinguishing oil fire is very effective when: | Cutting off oxygen source | Cooling below its ignition temperature | Spraying with water | Removing fuel |
| 3238 | Fuel vents are fitted with corrosion resistant screen to prevent: | Escape of flammable vapors | Corrosion in the tank vent | Flames entering the tank vent | Damge to the ball check |
| 3239 | Foam extinguishes fire by: | Inerting the air | Cooling | Smoothering | Chemical action |
| 3240 | The smoke detector (fire indicator) indicates fire in a cargo hold loaded by general cargo. What first action should be taken? | Use the ships gas extinguishing central system to put out the fire | Inspect the scene before deciding the method to be used for fire-fighting | Close the ventilation system and other openings to the hold in order to choke the fire | Start the fire pumps, open the hatches and start fighting the fire by fire hoses |
| 3241 | For carbon dioxide fire-fighting systems for machinery spaces the fixed piping system shall be such that: (SOLAS II-2/5.2.4) | 100% of the gas can be discharged into the space within two minutes | 70% of the gas can be discharged into the space within one minute | 100% of the gas can be discharged into the space within three minutes | 85% of the gas can be discharged into the space within two minutes |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 3242 | The total available supply of CO2 for use in a fixed extinguishing system of a cargo vessel shall be at least sufficient for_____. | All the space of the vessel | All cargo-space | Engine room and largest cargo space | Space requiring largest amount |
| 3243 | How does low expansion foam act as an extinguishing agent when dealing with oil fires? | By cooling only | By smothering only | The heat from the fire causes the foam to produce an inert gas which gradually extinguishes the fire. | By smothering and also providing some cooling |
| 3244 | One of the limitations of foam as an extinguishing agent is that foam | Conducts electricity | is heavier than oil and sinks below its surface | is corrosive and a hazard to fire fighters | cannot be made with salt water |
| 3245 | At the required fire drill, all persons must report to their stations and demonstrate their ability to perform duties assigned to them _____. | At the previous safety meeting | By the person conducting the drill | In the Muster List (Station Bill) | By the Coast Guard regulations |
| 3246 | Each hand portable fire extinguisher must be marked with _____. | the name of the vessel on which it is located | an identification number | the names of the individuals qualified to use it | the date that it was installed |
| 3247 | A squeeze-grip type carbon dioxide portable fire extinguisher has been partially discharged. It should be _____. | labeled empty and recharged as soon as possible | replaced in its proper location if weight loss is no more than 25% | replaced in its proper location regardless of weight | replaced in its proper location if weight loss is no more than 15% |
| 3248 | Which extinguishing agent is most likely to allow reflash as a result of not cooling the fuel below its ignition temperature? | Water spray | CO2 | Water stream | Foam |
| 3249 | In the event of a fire, the doors to a stair tower must be closed to prevent the spread of fire by _____. | convection | radiation | conduction | ventilation |
| 3250 | Which activity will have the greatest fire-fighting effect in case of a fire? | All fire-fighting teams are organized as soon as possible | Call the Chief Officer | All possible fire-fighting equipment is brought to the scene | Extinguishing attempt is started immediately |
| 3251 | What is meant by the term overhaul in firefighting? | Slow down the spread of fire by cooling adjacent structures | Smother the fire with a blanket or similar object | Cover the fire with foam | Break up solid objects to ensure that any deep seated fires are extinguished |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 3252 | When two fire hose teams are attacking a fire they should _____. | use fire hoses of different sizes | use different fire hose pressures | not wear protective clothing | not attack the fire from opposite sides |
| 3253 | You are fighting a fire in the electrical switchboard in the engine room. You should secure the power, then _____. | use a portable foam extinguisher | determine the cause of the fire | use a portable CO2 extinguisher | use a low-velocity fog adapter with the fire hose |
| 3254 | A definite advantage of using water as a fire extinguishing agent is its characteristic of _____. | rapid contraction as water is converted from a liquid to a vapor | rapid expansion as water absorbs heat and changes to steam | absorption of smoke and gases as water is converted from a liquid to a vapor | alternate expansion and contraction as water in a liquid state becomes a vapor |
| 3255 | If a firefighting situation calls for low-velocity fog you would _____. | attach a low-velocity fog applicator with the nozzle shut down | put the lever on an all-purpose fire nozzle all the way forward | put the lever on an all-purpose fire nozzle all the way back | order the engine room to reduce pressure on the fire pump |
| 3256 | A cargo hold containing cargo such as nitrates, chlorates etc which produce oxygen under the influence of heat catches fire. How would you deal with this? | Apply boundary cooling | Close the hatches, apply boundary cooling and allow the fire to use up the oxygen and extinguish itself | Close the hatches and use the fixed CO2 system | With this type of material the hatches should not be battened down. The fire can only be extinguished by using large quantities of water. |
| 3257 | The order of importance in addressing damage control is: | Control flooding, control fire, repair structural damage | Control fire, restore services, control flooding | Restore vital services, control fire, control flooding | Control fire, control flooding, repair structural damage |
| 3258 | Which of the following is considered primary life-saving equipment? | Personal flotation device | Lifering | Lifeboat | Life Preserver |
| 3259 | The purpose of storm oil is to: | Weight down the sea anchor | Smooth the sea | Repel dangerous fish | Lubricate sea anchor |
| 3260 | An orage colored smoke signal or detonating luminous signals fired at interval of one minute means: | We see you, we will provide help as soon as possible | This is the most suitable place to embark | Man in the buoy | To embark here is dangerous |
| 3261 | A hydrostatic release mechanism for a liferaft: | Should be kept watertight before release | Wll inflate the liferaft | Must be submerged to a certain depth to release automatically | Must be wet before it will release |
| 3262 | Which of following items shall be included in an abandon ship drill? | Checking the distress signal rockets and other distress signals. | Checking that lifejackets are correctly donned. | Checking passenger's immersion suits. | Checking the lifeboat provisions and supplies. |

| | | | | | |
|---|---|---|---|---|---|
| 3263 | The Muster List shall show the duties assigned to members of the crew. Which of the following duties shall be included in the "muster list" according to present regulations? | Operation of the vessel's propulsion system. | Preparation of immersion suits and thermo protective aids for the ship's passengers. | Preparation of survival craft's Emergency Positions Indicating Radio Beacons. | Closing of watertight doors, fire doors, valves, scuppers, side scuttles, skylights. |
| 3264 | Which one of the given requirements regarding survival craft muster and embarkation arrangements corresponds to the present SOLAS regulations? | Muster and embarkation stations shall be readily accessible from accommodation and work areas. | Davit-launched survival craft muster and embarkation stations shall not be arranged to enable stretchers to be placed in survival craft. | Searchlights to be provided at the launching station. | Muster and embarkation stations are to be arranged separately to improve working conditions. |
| 3265 | You have abandoned ship in a life raft. Which of the following actions should you take? | Organize a watch system, post as a lookout, tie up with other survival craft if possible, and stream the sea anchor | start paddling in the direction of the nearest land | Join up with any other survival craft and stream the sea anchor | organize a lookout system |
| 3266 | A hydrostatic release mechanism for a liferaft: | Must be submerged to a certain depth to release automatically | Should be kept watertight before release | Must be wet before it will release | Wll inflate the liferaft |
| 3267 | One can check the functioning of the SART by_____ | activating the SART and checking the effect on the radar screen | Don't know | activating it by extracting the antenna | removing it from the holder and turning the SART upside down |
| 3268 | How often must inspection of proper working of the EPIRB ‘s and SART ’s take place on board? Once per_____ | month | week | 14 days | Don't know |
| 3269 | You have abandoned ship and after two days in a raft, you can see an aircraft near the horizon apparently carrying out a search pattern. You should: | Use visual distress signals in conjunction with the EPIRB | Use the voice transmission capability of the EPIRB to guide the aircraft to your raft | Switch the EPIRB to the homing signal mode | Turn on the strobe light on the top of the EPIRB |
| 3270 | Which is TRUE concerning immersion suits and their use? | A puncture in the suit will not appreciably reduce its value. | Only a light layer of clothing may be worn underneath. | They provide sufficient flotation to do away with the necessity of wearing a life jacket. | They should be tight fitting. |
| 3271 | After abandoning ship, you should deploy the sea anchor from a liferaft to _____. | Navigate against the current | keep the liferaft from capsizing | Stay in the general location | Keep personnel from getting seasick |

| | | | | | |
|---|---|---|---|---|---|
| 3272 | If you are forced to abandon ship in a lifeboat, you should _____. | head for the nearest land | vote on what to do, so all hands will have a part in the decision | head for the closest sea-lanes | remain in the immediate vicinity |
| 3273 | If an inflatable liferaft inflates upside down, you can right it by _____. | doing nothing; it will right itself after the canopy supports inflate | getting at least three or four men to push down on the side containing the CO2 cylinder | pushing up on one side | standing on the CO2 bottle, holding the bottom straps, and throwing your weight backwards |
| 3274 | You have abandoned ship and are in charge of a liferaft. How much water per day should you permit each occupant to drink after the first 24 hours? | 1 pint | 1 can | 1 gallon | 1 quart |
| 3275 | You have abandoned ship in tropical waters. Which procedure(s) should be used during a prolonged period in a raft? | Keep the entrance curtains open. | Get plenty of rest. | Wet clothes during the day to decrease perspiration. | All of the above |
| 3276 | If you reach shore in a liferaft, the first thing to do is _____. | drag the raft ashore and lash it down for a shelter | set the raft back out to sea so someone may spot it | find some wood for a fire | get the provisions out of the raft |
| 3277 | You are at sea in an inflatable liferaft. In high latitudes, the greatest danger is _____. | hypothermia caused by cold temperature | starvation | collapse of the raft due to cold temperatures | asphyxiation due to keeping the canopy closed |
| 3278 | While adrift in an inflatable liferaft in hot, tropical weather _____. | the entrance curtains should never be opened | the canopy should be deflated so that it will not block cooling breezes | deflating the floor panels may help to cool personnel | the pressure valve may be periodically opened to prevent excessive air pressure |
| 3279 | To turn over an inflatable liferaft that is upside down, you should pull on the _____. | righting strap | sea painter | manropes | canopy |
| 3280 | Your liferaft is to leeward of a fire on the water and riding to its sea anchor. You should FIRST _____. | splash water over the liferaft to cool it | paddle away from the fire | get out of the raft and swim to safety | boat the sea anchor |
| 3281 | A life float on a fishing vessel must be equipped with _____. | drinking water | pendants | a righting line | red hand flares |
| 3282 | Which is an indication of reserve buoyancy? | Metacentric height | Righting moment | Rolling period | Freeboard |

| | | | | | |
|---|---|---|---|---|---|
| 3283 | How are lifelines attached to a life float? | Securely attached around the outside in bights no longer than three feet | By serving | By splicing one end of the line around the apparatus | With an approved safety hook or shackle |
| 3284 | On an oceangoing vessel, for each person a lifeboat (without desalting kits) is certified to carry, the boat must be supplied with _____. | a signaling whistle | a life preserver | 2 pounds of condensed milk | 3 liters of water |
| 3285 | If an inflatable liferaft inflates upside down, you can right it by | getting at least three or four men to push down on the side containing the CO2 cylinder | standing on the CO2 bottle, holding the bottom straps, and throwing your weight backwards | doing nothing; it will right itself after the canopy supports inflate | pushing up on one side |
| 3286 | To disengage a survival craft suspended from the cable above the water, you must pull the safety pin and _____. | pull the hook release handle and depress the retainer | use the ratchet bar and depress the retainer | pull the hook release handle and use the ratchet bar | pull the hook release handle |
| 3287 | A liferaft which has inflated bottom-up on the water _____. | must be cleared of the buoyant equipment before it will right itself | will right itself when the canopy tubes inflate | should be righted by standing on the life line, holding the righting straps, and leaning backwards | should be righted by standing on the carbon dioxide cylinder, holding the righting straps, and leaning backwards |
| 3288 | If more than one raft is manned after the vessel has sunk, you should _____. | tie the rafts together and try to stay in a single group | go in a different direction in search of land | spread out to increase the possibility of a search aircraft finding you | reduce the number of rafts by getting as many people as possible into as few rafts as possible |
| 3289 | If, for any reason, it is necessary to abandon ship while far out at sea, it is important that the crew members should _____. | immediately head for the nearest land | remain together in the area because rescuers will start searching at the vessel's last known position | get away from the area because sharks will be attracted to the vessel | separate from each other as this will increase the chances of being rescued |
| 3290 | You are underway when a fire breaks out in the forward part of your vessel. If possible, you should _____. | keep going at half speed | abandon ship to windward | put the vessel's stern into the wind | call for assistance |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 3291 | You have just abandoned ship and boarded a raft. After the raft is completely inflated you hear a whistling noise coming from a safety valve. You should _____. | plug the safety valve | not become alarmed unless it continues for a long period of time | remove the safety valve and replace it with a soft patch | unscrew the deflation plugs |
| 3292 | Your small vessel is broken down and rolling in heavy seas. You can reduce the possibility of capsizing by _____. | constantly shifting the rudder | moving all personnel aft | rigging a sea anchor | moving all personnel forward and low |
| 3293 | You hear air escaping from the liferaft just after it has inflated. You should _____. | quickly hunt for the hole before the raft deflates | check the painter line attachment for a tear caused by the initial opening | check the sea anchor line attachment for a tear if the seas are rough | not panic since the safety valves allow excess pressure to escape |
| 3294 | If you are forced to abandon ship in a lifeboat, you should _____. | head for the nearest land | remain in the immediate vicinity | head for the closest sea-lanes | vote on what to do, so all hands will have a part in the decision |
| 3295 | If you reach shore in a liferaft, the first thing to do is _____. | find some wood for a fire | get the provisions out of the raft | drag the raft ashore and lash it down for a shelter | set the raft back out to sea so someone may spot it |
| 3296 | You are at sea in an inflatable liferaft. In high latitudes, the greatest danger is _____. | asphyxiation due to keeping the canopy closed | collapse of the raft due to cold temperatures | starvation | hypothermia caused by cold temperature |
| 3297 | While adrift in an inflatable liferaft in hot, tropical weather _____. | the entrance curtains should never be opened | deflating the floor panels may help to cool personnel | the pressure valve may be periodically opened to prevent excessive air pressure | the canopy should be deflated so that it will not block cooling breezes |
| 3298 | Your vessel is equipped with totally enclosed lifeboats. Which statement is TRUE when the boat is enveloped in flames? | The motor takes its air supply from outside the lifeboat to prevent asphyxiation of the crew. | The ventilators will automatically close by the action of fusible links. | A water spray system to cool the outside of the boat is operated by a high-volume manual pump. | An air tank will provide about ten minutes of air for the survivors and the engine. |
| 3299 | The number 2 lifeboat on a tanker would be _____. | abaft #1 lifeboat starboard side | abaft #1 lifeboat port side | forwardmost on the port side | forwardmost on the starboard side |
| 3300 | The number 2 lifeboat on a tanker would be found _____. | abaft #1 lifeboat on the port side | on the starboard side | on the port side | abaft #1 lifeboat on the starboard side |
| 3301 | Most lifeboats are equipped with _____. | balanced rudders | straight rudders | contraguide rudders | unbalanced rudders |

| | | | | | |
|---|---|---|---|---|---|
| 3302 | The steering oar in a lifeboat is _____. | used by the forward man in the boat to direct the bow | longer than the others and should be lashed to the stern | shorter than the others | used for the stroke oar |
| 3303 | The steering oar in a lifeboat is _____. | used for the stroke oar | longer than the others and should be lashed to the stern | used by the forward man in the boat to direct the bow | shorter than the others |
| 3304 | The Emergency Position Indicating Radio beacon on a cargo vessel must be stowed _____. | in an approved bracket | so that it is accessible from the bridge of the vessel | in an inside passageway | so that it will float free if the vessel sinks |
| 3305 | You are tending the lifeline of a person who has entered a compartment wearing a breathing apparatus. How many tugs of the lifeline mean "Are you all right"? | . Four | Two | One | Three |
| 3306 | Most enclosed lifeboats will right themselves after capsizing IF the _____. | passengers are strapped to their seats | lower ballast tanks are filled with water | sea anchor is deployed to windward | fuel tanks are not less than half full |
| 3307 | Which type of EPIRB must each ocean-going ship carry? | Category 1 | Class B | Class A | Class C |
| 3308 | The vessel's Emergency Position Indicating Radio beacon (EPIRB) must be tested _____. | weekly | monthly | every 3 months | every 2 months |
| 3309 | The Master shall insure that the Emergency Position Indicating Radio beacon (EPIRB) is _____. | tested monthly | secured inside the wheelhouse | secured in the emergency locker | tested annually |
| 3310 | When a sea anchor is used in landing stern first in a heavy surf, sternway is checked by _____. | slacking the tripping line and towing the sea anchor by the holding line | towing the apex end forward with the tripping line | slacking the tripping line and towing the sea anchor from the stern | towing with the tripping line and leaving the holding line slack |
| 3311 | The center of flotation of a vessel is the point in the waterplane _____. | about which the vessel lists and trims | which, in the absence of external forces, is always vertically aligned with the center of gravity | which is shown in the hydrostatic tables as VCB | which coincides with the center of buoyancy |
| 3312 | The greatest effect on stability occurs from loose liquids flowing _____. | from side to side in the tanks of the vessel | in and out of a vessel that is holed in a wing tank | from fore to aft in the tanks of a vessel | in and out of a vessel that is holed in a peak tank |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 3313 | The purpose of the tripping line on a sea anchor is to _____. | aid in its recovery | direct the drift of the vessel | maintain maximum resistance to broaching | aid in casting off |
| 3314 | Liferafts carried on passenger ships shall be fitted with radar transponder in a ratio of one transponder for every how many liferafts? | 12 | 7 | 5 | 4 |
| 3315 | What is the minimum number of lifebuoys shall a cargo ship of 150 meters or more in length carry? | 15 | 6 | 12 | 9 |
| 3316 | The engines for lifeboats and rescue boats must be run for a total period of NOT less than: | 10 minutes | 5 minutes | 3 minutes | 2 minutes |
| 3317 | Liferafts carried on passenger ships shall be fitted with radar transponder in a ratio of one transponder for every how many liferafts? | 7 | 12 | 5 | 4 |
| 3318 | What is the minimum number of lifebuoys shall a cargo ship of 150 meters or more in length carry? | 9 | 12 | 15 | 6 |
| 3319 | The engines for lifeboats and rescue boats must be run for a total period of NOT less than: | 10 minutes | 3 minutes | 5 minutes | 2 minutes |
| 3320 | Recovery time of rescue boats shall NOT be more than how many minutes in moderate sea conditions when loaded with its full complement and equipment? | 30 minutes | 25 minutes | 5 minutes | 10 minutes |
| 3321 | Emergency towing arrangement should be pre-rigged and be capable of being deployed in a controlled manner in harbor conditions in not more than _____, | 30 minutes | 15 Minutes | 20 minutes | 25 minutes |
| 3322 | What is the period of validity of a cargo ship safety equipment certificate? | 24 months | 12 months | 60 months | 36 months |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 3323 | Liferafts are sent for re-packing and checking every: | 6 months | 4 months | year | 36 months |
| 3324 | SOLAS requires that the boarding arrangement of every cargo ship davit-launched liferaft shall be that it can be boarded in how many minutes from the time the instruction to board is given? | 5 minutes | 6 minutes | 3 minutes | 4 minutes |
| 3325 | A distress alert from an Inmarsat-EPIRB, is received in the coverage area of a satellite by ground station within: | 30 to 60 minutes | two minutes | Don't know | 60 to 90 minutes |
| 3326 | To enable periodic maintenance of the survival craft launching and recovery arrangement, lifeboats must be provided with: | food, clothings, emergency kit and a radio | off-load release system | hanging-off to free the release gear | a gong, a whistle and a flare |
| 3327 | What is the range of SART - at sea level and to Aircraft? | About 3 nm at sea level, about 30 nm to Aircraft "line of sight" | About 1 nm at sea level, about 30 nm to Aircraft "line of sight" | About 5 nm at sea level, about 60 nm to Aircraft "line of sight" | About 2 nm at sea level, about 30 nm to Aircraft "line of sight" |
| 3328 | Mechanical gearing of deck machinery such as the windlass or boat hoists should _____. | be painted a contrasting color from the base color in order to call attention to the gearing | not be operated if there is any crew within 10 feet of the machinery | have a guard over the gearing | be open to view so, if a foreign object gets in the gearing, the operator can immediately stop the machinery |
| 3329 | One of your crew members falls overboard from the starboard side. You should IMMEDIATELY: | apply left rudder | begin backing your engines | throw the crew member a life preserver | position your vessel to windward and begin recovery |
| 3330 | In a rescue operation in heavy sea, you decide to hove to, the lifeboat should be: | brought quarter into the sea | brought bow into the sea | brought to the sea | brought to a position with stern into the sea |
| 3331 | What is the EPIRB coverage? | Sea Area 4 | Inmarsat - A1, A2 and A3 | COSPAS-SARSAT - A1, A2, A3 and A4 | COSPAS-SARSAT - A1, A2, A3 and A4 / Inmarsat - A1, A2 and A3 |
| 3332 | When a sea anchor is used in landing in heavy surf, headway is checked by: | Slacking the tripping line and towing the apex end forward | Slacking the tripping line and towing the mouth forward by the holding line | Drag the sea anchor | Open the watertight door |

OIC NAVIGATIONAL WATCH

| | | | | | |
|---|---|---|---|---|---|
| 3333 | Bring survivors in a lifeboat and your position has not been transmitted to rescue services. What is the first action you should do? | ration the water and food in case rescue is delayed | fire smoke signals to show your position | start rowing in a fixed direction to look for help | light a fire at night to show your position |
| 3334 | As per LSA Code, buoyant lifelines as required shall _____. | have a diameter of not less than 8 mm | have a breaking strength of less than 5 kN | be kinking | have a diameter of less than 8 mm |
| 3335 | Self-contained breathing apparatus is used to: | enter areas that may contain dangerous fumes or lack oxygen | have a safe air when abandoning a ship | determine if the air in a tank is safe for men | fight a dangerous fire onboard |
| 3336 | With regards to Lifebuoy specification as per LSA Code, every lifebuoy shall _____. | have an outer diameter of 800 mm and an inner diameter of 600 mm | have an outer diameter of not more than 800 mm and an inner diameter of not less than 200 mm | have an outer diameter of more than 800 mm and an inner diameter of not less than 600 mm | have an outer diameter of not more than 800 mm and an inner diameter of not less than 400 mm |
| 3337 | The immersion suits and thermal protective aids are required on all passenger ship EXCEPT if the: | ship is constantly engaged on voyages on warm climates | if it is not required to use the immersion suit and thermal protective aid | persons are accommodated in open lifeboats only | if the Captain says it is not needed onboard |
| 3338 | Each lifeboat fitted with a certificate of approval, endorsed by the Administration, shall be containing the following items; I. manufacturer's name and address; II. month and year of manufacture; III. number of persons the lifeboat is approved to carry | I, II and III | I and III | I and II | II and III |
| 3339 | The certifying organization shall provide the lifeboat with a certificate of approval which specifies among others the____. I. number of the certificate of approval II. material of hull construction III. total mass fully equipped and fully manned | II and III | I and III | I and II | I, II and III |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 3340 | In addition to the equipment required to the normal equipment of every rescue boat, every rigid rescue boat shall include: I. a boat-hook II. a bucket III. a knife or hatchet | II and III | I and III | I and II | I, II and III |
| 3341 | The markings on inflatable liferafts shall be marked with _____. I. maker's name or trade mark II. date of manufacture (month and year) III. name of approving authority | II and III | I and II | I, II and III | I and III |
| 3342 | A Float-free arrangement for life rafts should have____. I. Painter system II. Weak link III. Hydrostatic release units | II and III | I and III | I and II | I, II and III |
| 3343 | Your course of action if you have to abandon ship and enter a liferaft should be: | get underway as far as you can | remain in the vicinity of the sinking ship | remain just a few meters from the vessel | immediately get underway to avoid suction |
| 3344 | What shall you do if you see a person falling into the sea? | Run aft | Put on a lifejacket | Launch a lifeboat | Throw a lifebuoy over board and report to the bridge immediately |
| 3345 | If a vessel is to be abandoned and the vessel is listed, passengers should be instructed to leap from the ends. If it is made from the high side, the passenger: | will have a better chance of survival | is likely to strike underwater projections or the hull plating | may be struck by masts, funnel, ventilators or Samson post | any of these |
| 3346 | If a "man overboard" is heard over the radio, what precedes the message? | PAN PAN | MAYDAY | SECURITE | CQ CQ |
| 3347 | which of the following do you do to let-go the boat from the ship In launching an enclosed lifeboat? | Release the sea anchor | Drag the sea anchor. | Look for a good sign before releasing the sea anchor | Release the painter when ready. |
| 3348 | In an enclosed lifeboat, which of the following do you do to let-go the boat from the ship? | If in dangerous water, release the sea anchor. | Release the sea anchor and drag and confirm your position | If in a dangerous atmosphere, open the air supply and water spray valves. | Open the watertight door |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 3349 | During a helicopter operation, while lifting a personnel from a survival craft, what should the other individuals in the craft do? | Stand on the outside of the craft to assist the person being lifted | All of the choices | Remove their lifejackets to prepare for their transfer to the helicopter | Remain seated inside the craft to provide body weight for stability |
| 3350 | Anyone seeing a person in the water should immediately throw a lifebuoy and give alarm by: | go to the bridge quickly and report the incident and point to where the person is in the water | reporting to any officer that you can see and point to the person in the water | inform the first crew member that you met and point out the person in the water | look for ship telephone and report what you saw to the Captain |
| 3351 | What is the recommended method if you must land on a beach with an oar-propelled lifeboat through a heavy surf? | ride in on the back of a large breaker | head directly into the beach by staying, between the crests of the waves | keep the bow into the seas with the sea anchor out over the bow, and row to meet the breaking waves | keep the bow directly in toward the beach, and tow the sea anchor off the stern |
| 3352 | In a distress situation and immediately after the distress signal has been sounded, what is the next action to be taken by the Chief Officer on duty? | Send distress signals to call for help | Use the VHF-radio telephone to ask ships in the vicinity to stand by | Use the intercom to inform crew and passengers of the reason for the alarm | Call the nearest coastal radio station |
| 3353 | In an enclosed lifeboat, which of the following do you do to let-go the boat from the ship? | Steer away from the ship. | If in dangerous water, release the sea anchor | Drag the sea anchor. | Slacking the tripping lineand towing the appex end forward |
| 3354 | What should be done by the first person to notice a man overboard incident? | throw a life ring to the victim, notify the crew | sound fire alarm, throw life buoy | pass the word man overboard over the P.A system | inform the watch, throw life buoy |
| 3355 | In all probability, the LAST persons to abandon the vessel will be _____. When they leave their post, all machinery should be stopped and watertight doors and hatches tightly closed. | The Master, Chief Cook and the Chief Officer | those engaged in last-minute damage control | those who brought their luggage | those person more than 75 kgs. |
| 3356 | You are proceeding to the area of reported distress. When you arrive at the reported position, the vessel in distress is not sighted. What type of search should be conducted? | Expanding square | Parallel track search | Track crawl | Sector search |

| | | | | | |
|---|---|---|---|---|---|
| 3357 | During monthly inspection of survival crafts, to ensure operational readiness, all lifeboats without any persons on board shall be: | at any time not be inspected for it is already certified and tested | turned end-for-end so that the wire falls can be thoroughly greased | turned out in any weather and sea condition | turned out from their stowed position if weather and sea conditions allow |
| 3358 | When the GMDSS Radio Operator on watch hears "SECURITE" spoken three times he can expect to receive a message concerning: | the safety of a vessel or a person is in jeopardy | the safety of navigation or important meteorological warnings | urgent message | distress message |
| 3359 | Maintenance of lifeboat davits consist of? | Testing, painting and greasing | Weekly painting can be necessary | No maitenance is needed as long as it working | Greasing all over its surface |
| 3360 | Liferafts carried on passenger ships shall be fitted with radar transponder in a ratio of one transponder for every how many liferafts? | 12 | 7 | 4 | 5 |
| 3361 | What is the minimum number of lifebuoys shall a cargo ship of 150 meters or more in length carry? | 15 | 6 | 12 | 9 |
| 3362 | The engines for lifeboats and rescue boats must be run for a total period of NOT less than: | 5 minutes | 10 minutes | 2 minutes | 3 minutes |
| 3363 | Recovery time of rescue boats shall NOT be more than how many minutes in moderate sea conditions when loaded with its full complement and equipment? | 10 minutes | 25 minutes | 5 minutes | 30 minutes |
| 3364 | Emergency towing arrangement should be pre-rigged and be capable of being deployed in a controlled manner in harbor conditions in not more than _____, | 25 minutes | 15 Minutes | 30 minutes | 20 minutes |
| 3365 | What is the period of validity of a cargo ship safety equipment certificate? | 36 months | 12 months | 60 months | 24 months |
| 3366 | Liferafts are sent for re-packing and checking every: | 4 months | 36 months | 6 months | year |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 3367 | SOLAS requires that the boarding arrangement of every cargo ship davit-launched liferaft shall be that it can be boarded in how many minutes from the time the instruction to board is given? | 3 minutes | 5 minutes | 6 minutes | 4 minutes |
| 3368 | A distress alert from an Inmarsat-EPIRB, is received in the coverage area of a satellite by ground station within: | two minutes | 60 to 90 minutes | 30 to 60 minutes | Don't know |
| 3369 | To enable periodic maintenance of the survival craft launching and recovery arrangement, lifeboats must be provided with: | a gong, a whistle and a flare | food, clothings, emergency kit and a radio | hanging-off to free the release gear | off-load release system |
| 3370 | What is the range of SART - at sea level and to Aircraft? | About 3 nm at sea level, about 30 nm to Aircraft "line of sight" | About 5 nm at sea level, about 60 nm to Aircraft "line of sight" | About 1 nm at sea level, about 30 nm to Aircraft "line of sight" | About 2 nm at sea level, about 30 nm to Aircraft "line of sight" |
| 3371 | Mechanical gearing of deck machinery such as the windlass or boat hoists should _____. | not be operated if there is any crew within 10 feet of the machinery | have a guard over the gearing | be open to view so, if a foreign object gets in the gearing, the operator can immediately stop the machinery | be painted a contrasting color from the base color in order to call attention to the gearing |
| 3372 | One of your crew members falls overboard from the starboard side. You should IMMEDIATELY: | apply left rudder | begin backing your engines | throw the crew member a life preserver | position your vessel to windward and begin recovery |
| 3373 | In a rescue operation in heavy sea, you decide to hove to, the lifeboat should be: | brought quarter into the sea | brought bow into the sea | brought to the sea | brought to a position with stern into the sea |
| 3374 | What is the EPIRB coverage? | COSPAS-SARSAT - A1, A2, A3 and A4 | Sea Area 4 | COSPAS-SARSAT - A1, A2, A3 and A4 / Inmarsat - A1, A2 and A3 | Inmarsat - A1, A2 and A3 |
| 3375 | When a sea anchor is used in landing in heavy surf, headway is checked by: | Drag the sea anchor | Slacking the tripping line and towing the apex end forward | Open the watertight door | Slacking the tripping line and towing the mouth forward by the holding line |
| 3376 | Bring survivors in a lifeboat and your position has not been transmitted to rescue services. What is the first action you should do? | start rowing in a fixed direction to look for help | ration the water and food in case rescue is delayed | fire smoke signals to show your position | light a fire at night to show your position |

OIC NAVIGATIONAL WATCH

| | | | | | |
|---|---|---|---|---|---|
| 3377 | As per LSA Code, buoyant lifelines as required shall _____. | have a breaking strength of less than 5 kN | be kinking | have a diameter of not less than 8 mm | have a diameter of less than 8 mm |
| 3378 | Self-contained breathing apparatus is used to: | determine if the air in a tank is safe for men | have a safe air when abandoning a ship | fight a dangerous fire onboard | enter areas that may contain dangerous fumes or lack oxygen |
| 3379 | With regards to Lifebuoy specification as per LSA Code, every lifebuoy shall _____. | have an outer diameter of not more than 800 mm and an inner diameter of not less than 400 mm | have an outer diameter of more than 800 mm and an inner diameter of not less than 600 mm | have an outer diameter of 800 mm and an inner diameter of 600 mm | have an outer diameter of not more than 800 mm and an inner diameter of not less than 200 mm |
| 3380 | The immersion suits and thermal protective aids are required on all passenger ship EXCEPT if the: | if the Captain says it is not needed onboard | ship is constantly engaged on voyages on warm climates | if it is not required to use the immersion suit and thermal protective aid | persons are accommodated in open lifeboats only |
| 3381 | Each lifeboat fitted with a certificate of approval, endorsed by the Administration, shall be containing the following items;<br>I. manufacturer's name and address; II. month and year of manufacture; III. number of persons the lifeboat is approved to carry | I and III | I and II | I, II and III | II and III |
| 3382 | The certifying organization shall provide the lifeboat with a certificate of approval which specifies among others the____.<br>I. number of the certificate of approval II. material of hull construction III. total mass fully equipped and fully manned | I and II | II and III | I, II and III | I and III |
| 3383 | In addition to the equipment required to the normal equipment of every rescue boat, every rigid rescue boat shall include:<br>I. a boat-hook II. a bucket III. a knife or hatchet | I, II and III | I and III | II and III | I and II |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 3384 | The markings on inflatable liferafts shall be marked with _____.<br>I. maker's name or trade mark II. date of manufacture (month and year) III. name of approving authority | I, II and III | II and III | I and III | I and II |
| 3385 | A Float-free arrangement for life rafts should have____.<br>I. Painter system II. Weak link III. Hydrostatic release units | I and II | I and III | I, II and III | II and III |
| 3386 | Your course of action if you have to abandon ship and enter a liferaft should be: | immediately get underway to avoid suction | remain in the vicinity of the sinking ship | remain just a few meters from the vessel | get underway as far as you can |
| 3387 | What shall you do if you see a person falling into the sea? | Run aft | Put on a lifejacket | Launch a lifeboat | Throw a lifebuoy over board and report to the bridge immediately |
| 3388 | If a vessel is to be abandoned and the vessel is listed, passengers should be instructed to leap from the ends. If it is made from the high side, the passenger: | may be struck by masts, funnel, ventilators or Samson post | will have a better chance of survival | is likely to strike underwater projections or the hull plating | any of these |
| 3389 | If a "man overboard" is heard over the radio, what precedes the message? | SECURITE | CQ CQ | MAYDAY | PAN PAN |
| 3390 | which of the following do you do to let-go the boat from the ship In launching an enclosed lifeboat? | Release the sea anchor | Release the painter when ready. | Look for a good sign before releasing the sea anchor | Drag the sea anchor. |
| 3391 | In an enclosed lifeboat, which of the following do you do to let-go the boat from the ship? | Release the sea anchor and drag and confirm your position | Open the watertight door | If in a dangerous atmosphere, open the air supply and water spray valves. | If in dangerous water, release the sea anchor. |
| 3392 | During a helicopter operation, while lifting a personnel from a survival craft, what should the other individuals in the craft do? | Stand on the outside of the craft to assist the person being lifted | Remove their lifejackets to prepare for their transfer to the helicopter | All of the choices | Remain seated inside the craft to provide body weight for stability |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 3393 | Anyone seeing a person in the water should immediately throw a lifebuoy and give alarm by: | go to the bridge quickly and report the incident and point to where the person is in the water | look for ship telephone and report what you saw to the Captain | inform the first crew member that you met and point out the person in the water | reporting to any officer that you can see and point to the person in the water |
| 3394 | What is the recommended method if you must land on a beach with an oar-propelled lifeboat through a heavy surf? | head directly into the beach by staying, between the crests of the waves | ride in on the back of a large breaker | keep the bow directly in toward the beach, and tow the sea anchor off the stern | keep the bow into the seas with the sea anchor out over the bow, and row to meet the breaking waves |
| 3395 | In a distress situation and immediately after the distress signal has been sounded, what is the next action to be taken by the Chief Officer on duty? | Call the nearest coastal radio station | Use the intercom to inform crew and passengers of the reason for the alarm | Use the VHF-radio telephone to ask ships in the vicinity to stand by | Send distress signals to call for help |
| 3396 | In an enclosed lifeboat, which of the following do you do to let-go the boat from the ship? | Steer away from the ship. | Drag the sea anchor. | If in dangerous water, release the sea anchor | Slacking the tripping lineand towing the appex end forward |
| 3397 | What should be done by the first person to notice a man overboard incident? | sound fire alarm, throw life buoy | throw a life ring to the victim, notify the crew | pass the word man overboard over the P.A system | inform the watch, throw life buoy |
| 3398 | In all probability, the LAST persons to abandon the vessel will be _____. When they leave their post, all machinery should be stopped and watertight doors and hatches tightly closed. | The Master, Chief Cook and the Chief Officer | those engaged in last-minute damage control | those person more than 75 kgs. | those who brought their luggage |
| 3399 | You are proceeding to the area of reported distress. When you arrive at the reported position, the vessel in distress is not sighted. What type of search should be conducted? | Parallel track search | Track crawl | Expanding square | Sector search |
| 3400 | During monthly inspection of survival crafts, to ensure operational readiness, all lifeboats without any persons on board shall be: | turned out in any weather and sea condition | turned end-for-end so that the wire falls can be thoroughly greased | turned out from their stowed position if weather and sea conditions allow | at any time not be inspected for it is already certified and tested |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 3401 | When the GMDSS Radio Operator on watch hears "SECURITE" spoken three times he can expect to receive a message concerning: | the safety of a vessel or a person is in jeopardy | urgent message | distress message | the safety of navigation or important meteorological warnings |
| 3402 | Maintenance of lifeboat davits consist of? | Testing, painting and greasing | No maitenance is needed as long as it working | Greasing all over its surface | Weekly painting can be necessary |
| 3403 | According to the SOLAS regulations lifeboat falls must be renewed at intervals of how many years? | 2.5 | 5 | 4 | 3 |
| 3404 | All vessels not limited to daylight service shall be fitted with a ring life buoy _____. (small passenger vessel regulations) | with a twenty fathom line attached | with no line attached | with a water light to be attached during nighttime operation | on the stern of the vessel |
| 3405 | By regulation life preservers aboard an uninspected towing vessel must be which of the following? | stowed with the emergency provisions | readily accessible | stored in sealed containers | securely stowed |
| 3406 | How should signal flares be used after you have abandoned ship and are adrift in a liferaft? | Use all the signals during the first night. | Use them only when you are aware of a ship or plane in the area. | Immediately use all the signals at once. | Employ a signal every hour after abandoning ship until they are gone. |
| 3407 | If a man falls overboard from a rig under tow you should FIRST _____. | sound the general alarm | deploy life buoys | notify the tug | launch a boat |
| 3408 | Ring life buoys used aboard a small passenger vessels on oceans or coastwise routes are required to be what color? | Orange | Any highly visible color easily seen from the air | White or international orange | White |
| 3409 | Steering a motor lifeboat broadside to the sea could cause it to _____. | sink | capsize | run smoother | run faster |
| 3410 | The lights on the outside of the canopy on an inflatable liferaft operate _____. | by a switch at each light | automatically when the raft is inflated | by a light sensor | by turning the globe clockwise |
| 3411 | The number 2 lifeboat on a tanker would be _____. | forwardmost on the port side | forwardmost on the starboard side | abaft no.1 lifeboat starboard side | abaft no.1 lifeboat port side |
| 3412 | Vessels in ocean service shall carry sufficient life floats for _____. | 50% of all persons on board | 25% of all persons on board | 75% of all persons on board | 100% of all persons on board |

| | | | | | |
|---|---|---|---|---|---|
| 3413 | When lowering a boat with gravity davits it will be pulled into the embarkation deck by the _____. | boat hooks | falls | frapping lines | tricing pendants |
| 3414 | Which of the following steps should normally be taken first by those who have boarded a liferaft in an emergency situation? | Ration food and water supplies | Determine position and closest point of land | Check pyrotechnic supplies | Search for survivors |
| 3415 | Which statement is TRUE concerning a motor lifeboat? | It is propelled by engine or hand-propelling gear. | All of the above | It has a sufficient fuel capacity if motorized for 48 hours of operation. | It must be able to maintain a loaded speed of 6 knots. |
| 3416 | You are proceeding to a distress site and expect large numbers of people in the water. Which statement is TRUE? | You should stop to windward of the survivors in the water and only use the ship s boats to recover the survivors. | Survivors in the water should never be permitted alongside due to the possibility of injury from the vessel. | An inflatable liferaft secured alongside can be an effective boarding station for transfer of survivors from the boats. | If the survivors are in inflatable rafts you should approach from windward to create a lee for the survivors. |
| 3417 | Free pratique means that _____. | clearance requirements for all regulatory bodies have been met | health requirements have been met and no further quarantine formalities are required | shipment will be made at no cost | tonnage taxes are not required to be paid |
| 3418 | A right-handed propeller will cause the survival craft to _____. | run faster than a left-handed propeller | walk the stern to starboard in reverse | right itself if capsized | walk the stern to port in reverse |
| 3419 | A safety feature provided on all inflatable liferafts is _____. | water stabilizing pockets | overhead safety straps | built in seats | internal releasing hooks |
| 3420 | All personnel should be familiar with the lifeboats _____. | fuel consumption rates | navigational systems | boarding and operating procedures | maintenance schedule |
| 3421 | Aluminum lifeboats are subject to damage by electrolytic corrosion (the aluminum being eaten away). In working around boats of aluminum you must be very careful _____. | not to leave steel or iron tools lying in or near these boats | to rinse these boats regularly with salt water | to keep an electric charge on the hull at all times | to keep the boats covered at all times |
| 3422 | By regulation orange smoke distress signals will expire not more than how many months from the date of manufacture? | 24 months | 54 months | 36 months | 42 months |

| | | | | | |
|---|---|---|---|---|---|
| 3423 | Category 1 EPIRBs are required to be carried on board _____. | small passenger vessels on the Great Lakes | fishing industry vessels | small passenger vessels | all deep draft vessels |
| 3424 | Frapping lines are fitted to lifeboat davits to _____. | secure the lifeboat in the davits when in the stowed position | be used as a safety line in an emergency | hold the lifeboat to the ship s side until the tricing lines are passed | reduce the swinging of the lifeboat as it is being lowered from the embarkation level |
| 3425 | Generally when lifting an inflatable liferaft back aboard ship you would use the _____. | main weather cover | external lifelines | righting strap | towing bridle |
| 3426 | If an inflatable liferaft is to be released manually where should the operating cord be attached before throwing the raft overboard? | You should stand on the cord. | Attach the cord to the special pad eye on the raft davit launcher . | Do not attach the cord to anything but throw it overboard with the raft container. | Attach the cord to a fixed object on the ship. |
| 3427 | If more than one raft is manned after the vessel has sunk you should _____. | reduce the number of rafts by getting as many people as possible into as few rafts as possible | spread out to increase the possibility of a search aircraft finding you | tie the rafts together and try to stay in a single group | go in a different direction in search of land |
| 3428 | If water is rising in the bilge of a survival craft you should first _____. | shift all personnel to the stern | abandon the survival craft | check the bilge drain plug | check for cracks in the hull |
| 3429 | If you find an inflatable liferaft container with the steel bands still in place around its case you should _____. | remove the bands yourself | tell the Mate | tell the Master | leave the bands in place |
| 3430 | A documented vessel operating over 50 miles offshore must carry an inflatable liferaft with a _____. | SOLAS B pack | SOLAS A pack | coastal pack | small vessel pack |
| 3431 | A feature of an inflatable raft which helps keep people stationary in rough weather is _____. | straps from the overhead | lashings on the floor of the raft for the passenger s feet | ridges in the floor of the raft | lifelines on the inside of the raft |
| 3432 | A fully loaded motor-propelled lifeboat must be capable of attaining a speed of at least _____. | 3 knots in rough water | 3 knots in smooth water | 6 knots in smooth water | 6 knots in rough water |
| 3433 | A hydrostatic release mechanism for a liferaft _____. | must be submerged to a certain depth to release automatically | will inflate the raft in its cradle if operated manually | should be kept in a watertight cover except in an emergency | must be wet before it will release |

| | | | | | |
|---|---|---|---|---|---|
| 3434 | A life line must be connected to the liferaft _____. | in the middle | at the stern | at the bow | all around |
| 3435 | A lifeline must be connected to the liferaft _____. | at the bow | all around | in the middle | at the stern |
| 3436 | A mechanical davit is designed to automatically _____. | position the boat at the embarkation station | set the brake on the winch | energize the winch for the falls | lift the boat off the inboard chocks |
| 3437 | A motor lifeboat shall carry sufficient fuel to operate continuously for a period of _____. | 36 hours | 12 hours | 18 hours | 24 hours |
| 3438 | A new liferaft has been installed on your vessel. The operating cord should be _____. | checked to see that it s unattached | coiled neatly on the raft container | faked on deck and lead through a chock | attached to the raft stowage cradle or to a secure object nearby with a weak link |
| 3439 | A person referring to the stern sheets of a lifeboat is speaking of _____. | the emergency rudder | the line attached to the tack of the lugsail | the aftermost seating | a canvas awning |
| 3440 | A rigid lifesaving device designed to support survivors in the water is a _____. | rigid liferaft | survival capsule | inflatable liferaft | life float |
| 3441 | A sea anchor is _____. | a pad eye to which the sea painter is made fast | a cone shaped bag used to slow down the wind drift effect | a heavy anchor with an extra long line used to anchor in deep water | made of wood if it is of an approved type |
| 3442 | A self-righting survival craft will return to an upright position provided that all personnel _____. | escape from the craft | are seated with seat belts on and doors open | are to shift to one side to right it | are seated with seat belts on and doors shut |
| 3443 | A sweep oar is an oar that is _____. | is longer than the others and is used as the stroke oar | longer than the others used for steering | generally shorter than the others and is used to steer with | is raised in the bow of the boat for the steersman to steer by |
| 3444 | A vessel carrying passengers for hire shall have on board an approved life jacket _____. (small passenger vessel regulations) | or buoyant cushion for every person on board plus 10% for children | for every passenger on board | for every person on board plus 10% childrens life jackets | for every person on board plus 10% additional on upper deck in box |
| 3445 | Aboard a survival craft ether can be used to _____. | prime the sprinkler system | aid in helping personnel breathe | prime the air supply | start the engine in cold weather |

| | | | | | |
|---|---|---|---|---|---|
| 3446 | According to the Lifesaving regulations in Subchapter W fire and abandon ship drills must be held within 24 hours of leaving port if the percentage of the crew that has not participated in drills aboard that particular vessel in the prior month exceeds _____. | 0.05 | 0.4 | 0.25 | 0.1 |
| 3447 | According to the regulations for lifeboat falls which action must be taken at 30-month intervals? | End-for-ended | Renewed | Inspected | Weight tested |
| 3448 | After a liferaft is launched the operating cord _____. | detaches automatically | serves as a sea painter | is cut immediately as it is of no further use | is used to rig the boarding ladder |
| 3449 | After abandoning a vessel water that is consumed within the first 24 hours will _____. | help to prevent seasickness | help to prevent fatigue | quench thirst for only 2 hours | pass through the body with little absorbed by the system |
| 3450 | After you have thrown the liferaft and stowage container into the water you inflate the liferaft by _____. | using the hand pump provided | A. forcing open the container which operates the CO2 | hitting the hydrostatic release | pulling on the painter line |
| 3451 | All self-propelled vessels on an international voyage must be equipped with how many Emergency Position Indicating Radio beacons (EPIRB)? | One approved Class B EPIRB | Two approved Class B EPIRBs | Three approved Category 1 EPIRBs | One approved Category 1 EPIRB |
| 3452 | An on-load release system on a survival craft means the cable can be released _____. | at any time | only when there is a load on the cable | only when the load is taken off the cable | only when activated by the controls at the lowering station |
| 3453 | An inflatable liferaft equipped with a SOLAS B pack must be stowed _____. | near the wheelhouse | as far forward as possible | with the vessel s emergency equipment | so as to float free |
| 3454 | An inflatable liferaft is hand-launched by _____. | removing the rubber packing strip | throwing the entire container overboard | pulling a cord | cutting the wire restraining bands |
| 3455 | After the boat is at the top of the davit heads, the davit arms begin moving up the tracks and are stopped by the _____. | brake handle | limit switch | preventer bar | hoist man |

| | | | | | |
|---|---|---|---|---|---|
| 3456 | When picking up a lifeboat at sea with way on the ship, the sea painter should be secured _____. | only after the falls have been attached | well aft in the lifeboat | about amidships in the lifeboat | well forward in the lifeboat |
| 3457 | When in command of a lifeboat under oars, the command Backwater means to _____. | complete the stroke, come to Oars, raise oars smartly to vertical, rest handles on footing, trim blades fore and aft | row in astern motion | lift oars to vertical position, trim blades fore and aft with handles resting on footings | complete stroke, stop rowing, dip blade about halfway into water, hold water to stop the way on the boat |
| 3458 | Which operation should be done when launching an inflatable liferaft by hand? | After inflation, detach operating cord from liferaft. | Turn the valve on the CO2 cylinder to start inflation. | Open the liferaft casing. | Make sure the operating cord is secured to the vessel before throwing it over the side. |
| 3459 | Generally, when lifting an inflatable liferaft back aboard ship you would use the _____. | external lifelines | righting strap | towing bridle | main weather cover |
| 3460 | After launching, an inflatable raft should be kept dry inside by _____. | opening the automatic drain plugs | draining the water pockets | using the electric bilge pump | using the bailers and cellulose sponge |
| 3461 | Lines passed around the falls to hold the boat while passengers are boarding are _____. | tricing lines | life lines | tripping lines | frapping lines |
| 3462 | In order to retrieve an inflatable liferaft and place it on deck, you should heave on the _____. | righting strap | towing bridle | sea anchor | lifelines |
| 3463 | If the coxswain of your lifeboat gives the command Hold water you should _____. | dip the blade of your oar into the water vertically and hold it perpendicular to the keel line | lift the oar in a vertical position | complete the stroke and hold the oar out of the water | complete the stroke, raise your oar slightly, swinging the oar slightly forward, and place it in the boat |
| 3464 | The purpose of the tricing pendants is to _____. | provide suspensions for the manropes | hold a lifeboat next to the embarkation deck while loading | control the fore and aft motion of a lifeboat during lowering | control the outboard swing of a lifeboat during lowering |
| 3465 | You have abandoned ship and after two days in a raft, you can see an aircraft near the horizon apparently carrying out a search pattern. You should: | Use visual distress signals in conjunction with the EPIRB | Turn on the strobe light on the top of the EPIRB | Switch the EPIRB to the homing signal mode | Use the voice transmission capability of the EPIRB to guide the aircraft to your raft |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 3466 | What should you do with your EPIRB if you are in a life raft during storm conditions? | bring it inside the life raft and turn it off until the storm passes | bring it inside the life raft and leave it on | bring it inside the life raft and turn it off until the storm passes | bring it inside the life raft and turn it off until the storm passes |
| 3467 | The battery of an EPIRB_____ | must be replaced before the expiry date is exceeded | must be renewed every year | load must be checked weekly | Dont know |
| 3468 | The Emergency Position Indicating Radio beacon on a cargo vessel must be stowed _____. | so that it is accessible from the bridge of the vessel | in an inside passageway | in an approved bracket | so that it will float free if the vessel sinks |
| 3469 | One can check the functioning of the SART by_____ | activating it by extracting the antenna | Dont know | activating the SART and checking the effect on the radar screen | removing it from the holder and turning the SART upside down |
| 3470 | Preventer bars are fitted on lifeboat releasing gear to prevent _____. | the falls from rehooking after they have been released | accidental unhooking when the falls become slack | the falls from unhooking if the releasing gear is operated accidentally | operation of the release lever until the boat is waterborne |
| 3471 | The purpose of the tripping line on a sea anchor is to _____. | aid in its recovery | maintain maximum resistance to broaching | aid in casting off | direct the drift of the vessel |
| 3472 | Your vessel is equipped with totally enclosed lifeboats. Which statement is TRUE when the boat is enveloped in flames? | The ventilators will automatically close by the action of fusible links. | The motor takes its air supply from outside the lifeboat to prevent asphyxiation of the crew. | A water spray system to cool the outside of the boat is operated by a high-volume manual pump. | An air tank will provide about ten minutes of air for the survivors and the engine. |
| 3473 | The davit launched liferaft can be boarded _____. | at the deck | by jumping down onto it | through the escape tube | from the water only |
| 3474 | Your liferaft is to leeward of a fire on the water and riding to its sea anchor. You should FIRST _____. | splash water over the liferaft to cool it | paddle away from the fire | get out of the raft and swim to safety | boat the sea anchor |
| 3475 | Which of following items shall be included in an abandon ship drill? | Checking the lifeboat provisions and supplies. | Checking the distress signal rockets and other distress signals. | Checking that lifejackets are correctly donned. | Checking passengers immersion suits. |
| 3476 | The Muster List shall show the duties assigned to members of the crew. Which of the following duties shall be included in the muster list according to present regulations? | Preparation of survival crafts Emergency Positions Indicating Radio Beacons. | Closing of watertight doors, fire doors, valves, scuppers, side scuttles, skylights. | Operation of the vessels propulsion system. | Preparation of immersion suits and thermo protective aids for the ships passengers. |

OIC NAVIGATIONAL WATCH

| | | | | | |
|---|---|---|---|---|---|
| 3477 | While adrift in an inflatable liferaft in hot, tropical weather _____. | the pressure valve may be periodically opened to prevent excessive air pressure | deflating the floor panels may help to cool personnel | the canopy should be deflated so that it will not block cooling breezes | the entrance curtains should never be opened |
| 3478 | If you reach shore in a liferaft, the first thing to do is _____. | drag the raft ashore and lash it down for a shelter | get the provisions out of the raft | set the raft back out to sea so someone may spot it | find some wood for a fire |
| 3479 | Which of the following is considered primary life-saving equipment? | Life Preserver | Lifering | Personal flotation device | Lifeboat |
| 3480 | The steering oar in an open lifeboat is _____. | used for the stroke oar | longer than the others and should be lashed to the stern | shorter than the others | used by the forward man in the boat to direct the bow |
| 3481 | The vessels Emergency Position Indicating Radio beacon (EPIRB) must be tested _____. | weekly | monthly | every 2 months | every 3 months |
| 3482 | A hydrostatic release mechanism for a liferaft: | Must be submerged to a certain depth to release automatically | WIl inflate the liferaft | Must be wet before it will release | Should be kept watertight before release |
| 3483 | Which one of the given requirements regarding survival craft muster and embarkation arrangements corresponds to the present SOLAS regulations? | Muster and embarkation stations shall be readily accessible from accommodation and work areas. | Davit-launched survival craft muster and embarkation stations shall not be arranged to enable stretchers to be placed in survival craft. | Muster and embarkation stations are to be arranged separately to improve working conditions. | Searchlights to be provided at the launching station. |
| 3484 | You hear air escaping from the liferaft just after it has inflated. You should _____. | check the painter line attachment for a tear caused by the initial opening | not panic since the safety valves allow excess pressure to escape | quickly hunt for the hole before the raft deflates | check the sea anchor line attachment for a tear if the seas are rough |
| 3485 | The number 2 lifeboat on a tanker would be found _____. | on the starboard side | abaft #1 lifeboat on the starboard side | on the port side | abaft #1 lifeboat on the port side |
| 3486 | Most enclosed lifeboats will right themselves after capsizing IF the _____. | lower ballast tanks are filled with water | fuel tanks are not less than half full | passengers are strapped to their seats | sea anchor is deployed to windward |
| 3487 | A life float on a fishing vessel must be equipped with _____. | red hand flares | pendants | a righting line | drinking water |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 3488 | To disengage a survival craft suspended from the cable above the water, you must pull the safety pin and _____. | pull the hook release handle | pull the hook release handle and depress the retainer | pull the hook release handle and use the ratchet bar | use the ratchet bar and depress the retainer |
| 3489 | Your small vessel is broken down and rolling in heavy seas. You can reduce the possibility of capsizing by _____. | constantly shifting the rudder | moving all personnel forward and low | rigging a sea anchor | moving all personnel aft |
| 3490 | To turn over an inflatable liferaft that is upside down, you should pull on the _____. | righting strap | sea painter | manropes | canopy |
| 3491 | How are lifelines attached to a life float? | Securely attached around the outside in bights no longer than three feet | With an approved safety hook or shackle | By serving | By splicing one end of the line around the apparatus |
| 3492 | A liferaft which has inflated bottom-up on the water _____. | should be righted by standing on the carbon dioxide cylinder, holding the righting straps, and leaning backwards | must be cleared of the buoyant equipment before it will right itself | will right itself when the canopy tubes inflate | should be righted by standing on the life line, holding the righting straps, and leaning backwards |
| 3493 | When a sea anchor is used in landing stern first in a heavy surf, sternway is checked by _____. | towing with the tripping line and leaving the holding line slack | slacking the tripping line and towing the sea anchor from the stern | towing the apex end forward with the tripping line | slacking the tripping line and towing the sea anchor by the holding line |
| 3494 | The purpose of storm oil is to: | Weight down the sea anchor | Lubricate sea anchor | Repel dangerous fish | Smooth the sea |
| 3495 | If an inflatable liferaft inflates upside down, you can right it by _____. | standing on the CO2 bottle, holding the bottom straps, and throwing your weight backwards | getting at least three or four men to push down on the side containing the CO2 cylinder | doing nothing; it will right itself after the canopy supports inflate | pushing up on one side |
| 3496 | After abandoning ship, you should deploy the sea anchor from a liferaft to _____. | Navigate against the current | Keep personnel from getting seasick | keep the liferaft from capsizing | Stay in the general location |
| 3497 | The Master shall insure that the Emergency Position Indicating Radio beacon (EPIRB) is _____. | tested monthly | tested annually | secured inside the wheelhouse | secured in the emergency locker |
| 3498 | The following information must be given on the SART | date of replacement of the battery | Dont know | the MMSI number | date of replacement of the hydrostatic release unit |

| | | | | | |
|---|---|---|---|---|---|
| 3499 | Which is TRUE concerning immersion suits and their use? | Only a light layer of clothing may be worn underneath. | They provide sufficient flotation to do away with the necessity of wearing a life jacket. | They should be tight fitting. | A puncture in the suit will not appreciably reduce its value. |
| 3500 | If more than one raft is manned after the vessel has sunk, you should _____. | go in a different direction in search of land | spread out to increase the possibility of a search aircraft finding you | reduce the number of rafts by getting as many people as possible into as few rafts as possible | tie the rafts together and try to stay in a single group |
| 3501 | Most lifeboats are equipped with _____. | unbalanced rudders | balanced rudders | contraguide rudders | straight rudders |
| 3502 | An orage colored smoke signal or detonating luminous signals fired at interval of one minute means: | To embark here is dangerous | Man in the buoy | We see you, we will provide help as soon as possible | This is the most suitable place to embark |
| 3503 | While retrieving the survival craft, the engine should be stopped _____. | at the embarkation deck | when the cable has been attached | when the craft clears the water | on approach to the platform |
| 3504 | On board an accident happened. Urgent radio-medical advice is needed. We choose the category_____ | Don't know | Urgency | Routine | Safety |
| 3505 | While operating off Panama, a seaman is injured. What indicator should be included in the preamble of a telegram requesting a medical advice from a Panamanian station? | Radio medical | Med rad | DH medico | XXX |
| 3506 | If one requires medical advice by means of an Inmarsat-C terminal one should use the following address_____ | Radiomedical | Don't know | 32 | MED + |
| 3507 | There has been an accident on board. Urgent medical advice is needed. The call is preceded by_____ | emergency signal | Don't know | urgency signal | safety signal |
| 3508 | There has been an accident on board. Urgent medical advice is needed. The call is preceded by_____ | Don't know | SECURITE (3x) | MAYDAY (3x) | PAN PAN (3x) |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 3509 | What is the purpose of a Medico Message? | Medico is the certificate which permit the Master to be doctor onboard. | Giving a regular statement of the health of the vessel's crew. | Calling the health department in the next port of call and ask for free radio practice. | Call a hospital for professional medical assistance by radio when needed. |
| 3510 | One of the sailors needs urgent medical assistance. The VHF-call starts with_____ | SOS (3x) | MAYDAY (3x) | Don't know | PAN PAN (3x) |
| 3511 | An oiler was badly burned and you are communicating with a passenger ship that has a doctor and hospital on board. You want to rendezvous in a certain position so the oiler can be evacuated for medical treatment. Which code should your message contain? | MAF | MAE | MAB | MAA |
| 3512 | You receive a medical message that contains the code MSJ. This means "_____." | The wound should not be stitched | Place patient in hot bath | You should pass a stomach tube | The wound should be stitched |
| 3513 | What is considered a Serious Marine Incident? | an injury to a crewmember, passenger, or other person which requires professional medical treatment beyond first aid | a collision that results in $500 damage to a boat dock | None of the stated options | grounding of a vessel on a sandbar that does not result in injuries and/or any damage to the vessel |
| 3514 | If a person is in a state of shock, what of the following is the correct thing of you to do? | Apply hot-water bottles to keep the patient warm. | Be kind to the casualty and give anything to eat or drink at first opportunity. | Move the casualty as much as possible. | Treat and reassure the casualty and stay with the person at all times. |
| 3515 | Appendicitis symptoms include cramps or pain in the abdomen located in the _____. | lower left side | upper left side | lower right side | upper right side |
| 3516 | When a person is suspected of having appendicitis, the pain should be relieved by: | Giving the patient laxative. | Keeping an ice bag over the location of the appendix. | Giving the patient morphine sulfate. | Giving the patient aspirin with a glass of water. |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 3517 | Which of the following should NOT be a treatment for a person who has received a head injury and is groggy or unconscious? | Give a stimulant. | Treat for shock. | Elevate his head. | Stop severe bleeding. |
| 3518 | ____ is the proper stimulant for an unconscious person? | Ammonia | dextran | water | tiger balm |
| 3519 | Narcotics is given to a patient when: | In great pain | Intoxicated | Unconscious | He is groggy |
| 3520 | Universal antidote is used to neutralize a sick person with: | Poison | Diarrhea | Hemorrhage | Clean wounds |
| 3521 | Stimulant is given to a peson who is _____ . | poisoned | intoxicated | none of these | fainting |
| 3522 | Another name for pain reliever is _____ . | analgesic | hypnotic | depressant | tranquilizer |
| 3523 | What is not a treatment for traumatic shock? | Have the injured person lie down. | Keep the patient warm but not hot. | Massage the arms and legs to restore circulation. | Relieve the pain of the injury. |
| 3524 | A person suffering from possible broken bones and internal injuries should _____. | be assisted in walking around | not be moved but made comfortable until medical assistance arrives | not be allowed to lie down where injured but moved to a chair or bunk | be examined then walked to a bunk |
| 3525 | You are treating a shipmate with a compound fracture of the lower arm. Which action should you take? | Apply traction to the hand to keep the bones in line, splint, and apply a pressure dressing. | Force the ends of the bones back into line, treat the bleeding, and splint. | Apply a tourniquet to control bleeding then align the bones and splint. | Apply a bulky, sterile, pressure dressing to control bleeding, then apply a temporary splint, and obtain medical advice. |
| 3526 | A man has suffered a burn on the arm. There is extensive damage to the skin with charring present. How is this injury classified using standard medical terminology? | Third-degree burn | Major burn | Dermal burn | Lethal burn |
| 3527 | In case a patient has to be moved after basic life support has been started, interruption time should not exceed: | 5 seconds | 10 seconds | 20 seconds | 15 seconds |
| 3528 | When administering artificial respiration to an adult, the breathing cycle should be repeated about: | as fast as possible | 12 to 15 times per minute | 20 to 25 times per minute | 18 to 20 times per minute |

| | | | | | |
|---|---|---|---|---|---|
| 3529 | Morphine is given either by subcutaneous injection or by Intramuscular Injection for quick pain relief and will act in approximately: | 10-15 minutes | 3-5 minutes | 5-8 minutes | 2-4 minutes |
| 3530 | How open is the medicine chest and its contents including the medical equipment carried on board be inspected? | 24 months | 18 months | 12 months | 36 months |
| 3531 | A patient has to be moved after basic life support has been started, interruption time should NOT exceed: | 15 seconds | 20 seconds | 5 seconds | 10 seconds |
| 3532 | If hydrogen sulfide is burned (flared) on a vessel, which of the following conditions can be expected to happen? | Only 80% of the hydrogen sulfide will be converted to sulfur dioxide | All of the hydrogen sulfide will be converted to hydrogen and free sulphur | none of the above | All of the hydrogen sulfide will be converted to sulfur dioxide |
| 3533 | First-, second-, and third-degree burns are classified according to the: | source of heat causing the burn | layers of skin affected | size of the burned area | area of the body burned |
| 3534 | A seafarer suffering from possible broken bones and internal injuries should: | be assisted in waling around | not be allowed to lie down onto the injured part but moved to a chair or bunk | not be moved, but made comfortable until medical assistance arrives, provided he is in a safe environment | be examined then walked to a bunk |
| 3535 | A fracture of the skull or head injury should receive immediate attention to prevent damage to the brain. Bleeding can be controlled by direct pressure on the: | temporal or carotid arteries | wrist on the left arm which is nearer to the heart | veins near the neck | capillaries on the left shoulder |
| 3536 | What substance neutralizes the effects of poison or prevents its absorption? | cathartic | emetic | antidote | stimulant |
| 3537 | A substance which neutralizes the effects of a poison or prevents its absorption. | Emetic | antidote | stimulant | cathartic |
| 3538 | High concentrations of H2S gas are most dangerous to personnel because they can: | paralyze your breathing system | cause involuntary muscle contractions | cause eye inflammation | cause dizziness |
| 3539 | If possible, get Radio Medical Advice before administering medicines to an age of: | children under 20 years old | children under 17 years old | children under 16 years old | children under 18 years old |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 3540 | What do you call a fracture if the bone may be visible? | Serious fracture | Compound fracture | Complex fracture | Simple fracture |
| 3541 | An open wound that is caused by rubbing or scrapping the skin. | abrasion | laceration | contusion | puncture |
| 3542 | Which should NOT be a treatment for a person who has received a head injury and is groggy or unconscious? | Elevate his head | Stop severe bleeding | Give a stimulant | Treat for shock |
| 3543 | A crew member has suffered frostbite to the toes of the right foot. Which is NOT an acceptable first aid measure? | Rub the toes briskly | immerse the feet in warm water | Give aspirin or other medication for pain if necessary | Elevate the foot slightly |
| 3544 | In the ship's medicine chest, medicaments are indicated using which language so that a correct translation can be found in each language? | Latin | English | Spanish | French |
| 3545 | Which type of injury should be the first to receive emergency treatment? | Severe shock | Eye injuries | Burns | Major multiple fractures |
| 3546 | In case a patient has to be moved after basic life support has been started, interruption time should not exceed: | 15 seconds | 5 seconds | 20 seconds | 10 seconds |
| 3547 | When administering artificial respiration to an adult, the breathing cycle should be repeated about: | 20 to 25 times per minute | 18 to 20 times per minute | as fast as possible | 12 to 15 times per minute |
| 3548 | Morphine is given either by subcutaneous injection or by Intramuscular Injection for quick pain relief and will act in approximately: | 10-15 minutes | 5-8 minutes | 2-4 minutes | 3-5 minutes |
| 3549 | How open is the medicine chest and its contents including the medical equipment carried on board be inspected? | 36 months | 18 months | 12 months | 24 months |
| 3550 | A patient has to be moved after basic life support has been started, interruption time should NOT exceed: | 20 seconds | 15 seconds | 10 seconds | 5 seconds |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 3551 | If hydrogen sulfide is burned (flared) on a vessel, which of the following conditions can be expected to happen? | All of the hydrogen sulfide will be converted to hydrogen and free sulphur | All of the hydrogen sulfide will be converted to sulfur dioxide | none of the above | Only 80% of the hydrogen sulfide will be converted to sulfur dioxide |
| 3552 | First-, second-, and third-degree burns are classified according to the: | layers of skin affected | area of the body burned | source of heat causing the burn | size of the burned area |
| 3553 | A seafarer suffering from possible broken bones and internal injuries should: | not be moved, but made comfortable until medical assistance arrives, provided he is in a safe environment | not be allowed to lie down onto the injured part but moved to a chair or bunk | be examined then walked to a bunk | be assisted in waling around |
| 3554 | A fracture of the skull or head injury should receive immediate attention to prevent damage to the brain. Bleeding can be controlled by direct pressure on the: | veins near the neck | wrist on the left arm which is nearer to the heart | temporal or carotid arteries | capillaries on the left shoulder |
| 3555 | What substance neutralizes the effects of poison or prevents its absorption? | cathartic | stimulant | antidote | emetic |
| 3556 | A substance which neutralizes the effects of a poison or prevents its absorption. | stimulant | cathartic | Emetic | antidote |
| 3557 | High concentrations of H2S gas are most dangerous to personnel because they can: | paralyze your breathing system | cause dizziness | cause involuntary muscle contractions | cause eye inflammation |
| 3558 | If possible, get Radio Medical Advice before administering medicines to an age of: | children under 20 years old | children under 17 years old | children under 16 years old | children under 18 years old |
| 3559 | What do you call a fracture if the bone may be visible? | Serious fracture | Compound fracture | Complex fracture | Simple fracture |
| 3560 | An open wound that is caused by rubbing or scrapping the skin. | contusion | laceration | abrasion | puncture |
| 3561 | Which should NOT be a treatment for a person who has received a head injury and is groggy or unconscious? | Treat for shock | Stop severe bleeding | Give a stimulant | Elevate his head |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 3562 | A crew member has suffered frostbite to the toes of the right foot. Which is NOT an acceptable first aid measure? | Rub the toes briskly | immerse the feet in warm water | Give aspirin or other medication for pain if necessary | Elevate the foot slightly |
| 3563 | In the ship's medicine chest, medicaments are indicated using which language so that a correct translation can be found in each language? | French | English | Spanish | Latin |
| 3564 | Which type of injury should be the first to receive emergency treatment? | Eye injuries | Burns | Major multiple fractures | Severe shock |
| 3565 | An unconscious person should NOT be : | treated for injuries until conscious | placed in a position with the head lower than the body | given an inhalation stimulant | given something to drink |
| 3566 | Which is the most serious type of fracture? | Compound | Crack | Closed | Greenstick |
| 3567 | An oxygen indicator can be used to determine if there is: | sufficient oxygen in a compartment to support life | hydrogen gas present | all of the above | combustible gases present |
| 3568 | A victim is coughing and wheezing from a partial obstruction of the airway. An observer should: | allow the person to continue coughing and dislodge the obstruction on his own | immediately administer CPR | give back blows and something to drink | perform the Heimlich maneuver |
| 3569 | A shipmate chokes suddenly, cannot speak, and starts to turn blue. What action should you take? | do nothing until the victim become unconscious | administer the Heimlich maneuver | make the victim lie down with the feet elevated to get blood to the brain | immediately administer CPR |
| 3570 | Before administering any penicillin, preparations should include determining whether the patient is _____ to such medicine. | addicted | allergic | accustomed | immuned |
| 3571 | What is a treatment for traumatic shock? | Keep the victim in a sitting position | Administer fluids | Open clothing to allow cooling of the body | Administer CPR |
| 3572 | A man has suffered a burn on the arm. There is extensive damage to the skin with charring present. This is an example of what kind of burn? | Third-degree burn | Major burn | Lethal burn | Dermal burn |

| | | | | | |
|---|---|---|---|---|---|
| 3573 | In the absence of arachis oil, earwax hardening causing deafness can be removed using: | clove oil | fish oil | nitroglycerine | olive oil |
| 3574 | If anti-seasickness pill is ineffective, what is an alternative medication? | Paracetamol | Antihistamine | Antipyretic | Eucalyptus oil |
| 3575 | Survivors in the water should be lifted in a horizontal or near-horizontal position if possible to minimize _____ induced by sudden transfer from the water and possible hypothermia. | wound | possible fracture | the pain | the risk of shock |
| 3576 | Unless there is danger of further injury, a person with a compound fracture should not be moved until bleeding is controlled and: | the fracture is immobilized | radio advice has been obtained | the bone has been set | the wound has been washed |
| 3577 | What is NOT a treatment for traumatic shock? | Have the injured person lie down | Keep the patient warm but not hot | Relieve the pain of the injury | Massage the arms and legs to restore circulation |
| 3578 | Appendicitis has become common to seafarers. It is a condition characterized by _____ of the appendix. | enlargement | inflammation | rupture | swelling |
| 3579 | A man has suffered a burn on the arm. There is reddening of the skin blistering and swelling. How would this injury be classified using standard medical terminology? | secondary burn | major burn | blister burn | second-degree burn |
| 3580 | A rapid, emergency evaluation of the patient should be made immediately at the scene of the injury to determine the: | cause of the accident | source of injury | type and extent of trauma | necessary antidote and the prevention of further injury |
| 3581 | How do you determine the first symptoms of a stroke? | All of the choices | Stomach pains | High blood pressure | Low blood pressure |
| 3582 | An oxygen indicator will detect: | all of the above | an oxygen deficiency in a space | concentrations of explosive gas | the presence of harmful amounts of carbon monoxide |

NOT FOR SALE

# OIC NAVIGATIONAL WATCH

| | | | | | |
|---|---|---|---|---|---|
| 3583 | You are using an automatic tension winch by yourself. If you get caught in the turns of the line as they lead into the gypsyhead: | the line will part and snap back | None of the choices are correct | you may be pulled into the winch and injured or killed | the safety cutout will stop the winch before you're injured |
| 3584 | Compound fracture is a fracture in which: | there is never any internal bleeding | more than one bone is broken | the bone may be visible | the same bone is broken in more than one place |
| 3585 | How can a victim with an airway completely obstructed be recognized? | Totally unconscious | Clutches neck with both hands | Collapse and lying at his back | Unable to speak, breath or cough |
| 3586 | An alternative method of Artificial respiration where in some instances, mouth-to-mouth respiration cannot be used due to certain toxic and caustic materials constitute a hazard for the rescuer is known as: | Silvester method | Xyphoid process | Heimlich maneuver | Heat compression |
| 3587 | During a bomb search, which of the following is an important principle to follow? | Throw any suspicious package overboard | Know exactly what a bomb looks like | Do not touch any suspicious package | Try to reach behind bulkhead to reach a bomb |
| 3588 | In case a patient has to be moved after basic life support has been started, interruption time should not exceed: | 10 seconds | 15 seconds | 20 seconds | 5 seconds |
| 3589 | When administering artificial respiration to an adult, the breathing cycle should be repeated about: | 18 to 20 times per minute | 20 to 25 times per minute | as fast as possible | 12 to 15 times per minute |
| 3590 | Morphine is given either by subcutaneous injection or by Intramuscular Injection for quick pain relief and will act in approximately: | 2-4 minutes | 5-8 minutes | 3-5 minutes | 10-15 minutes |
| 3591 | How open is the medicine chest and its contents including the medical equipment carried on board be inspected? | 12 months | 24 months | 18 months | 36 months |
| 3592 | A patient has to be moved after basic life support has been started, interruption time should NOT exceed: | 20 seconds | 10 seconds | 15 seconds | 5 seconds |
| 3593 | If hydrogen sulfide is burned (flared) on a vessel, which of the following conditions can be expected to happen? | All of the hydrogen sulfide will be converted to hydrogen and free sulphur | Only 80% of the hydrogen sulfide will be converted to sulfur dioxide | All of the hydrogen sulfide will be converted to sulfur dioxide | none of the above |

NOT FOR SALE

# OIC NAVIGATIONAL WATCH

| | | | | | |
|---|---|---|---|---|---|
| 3594 | First-, second-, and third-degree burns are classified according to the: | source of heat causing the burn | layers of skin affected | size of the burned area | area of the body burned |
| 3595 | A seafarer suffering from possible broken bones and internal injuries should: | be assisted in waling around | be examined then walked to a bunk | not be allowed to lie down onto the injured part but moved to a chair or bunk | not be moved, but made comfortable until medical assistance arrives, provided he is in a safe environment |
| 3596 | A fracture of the skull or head injury should receive immediate attention to prevent damage to the brain. Bleeding can be controlled by direct pressure on the: | veins near the neck | temporal or carotid arteries | capillaries on the left shoulder | wrist on the left arm which is nearer to the heart |
| 3597 | What substance neutralizes the effects of poison or prevents its absorption? | stimulant | cathartic | antidote | emetic |
| 3598 | A substance which neutralizes the effects of a poison or prevents its absorption. | Emetic | antidote | cathartic | stimulant |
| 3599 | High concentrations of H2S gas are most dangerous to personnel because they can: | paralyze your breathing system | cause eye inflammation | cause involuntary muscle contractions | cause dizziness |
| 3600 | If possible, get Radio Medical Advice before administering medicines to an age of: | children under 20 years old | children under 17 years old | children under 16 years old | children under 18 years old |
| 3601 | What do you call a fracture if the bone may be visible? | Compound fracture | Simple fracture | Complex fracture | Serious fracture |
| 3602 | An open wound that is caused by rubbing or scrapping the skin. | laceration | abrasion | puncture | contusion |
| 3603 | Which should NOT be a treatment for a person who has received a head injury and is groggy or unconscious? | Give a stimulant | Elevate his head | Stop severe bleeding | Treat for shock |
| 3604 | A crew member has suffered frostbite to the toes of the right foot. Which is NOT an acceptable first aid measure? | Rub the toes briskly | immerse the feet in warm water | Give aspirin or other medication for pain if necessary | Elevate the foot slightly |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 3605 | In the ship's medicine chest, medicaments are indicated using which language so that a correct translation can be found in each language? | Latin | Spanish | English | French |
| 3606 | Which type of injury should be the first to receive emergency treatment? | Burns | Major multiple fractures | Eye injuries | Severe shock |
| 3607 | An unconscious person should NOT be : | given an inhalation stimulant | given something to drink | treated for injuries until conscious | placed in a position with the head lower than the body |
| 3608 | Which is the most serious type of fracture? | Closed | Crack | Greenstick | Compound |
| 3609 | An oxygen indicator can be used to determine if there is: | hydrogen gas present | sufficient oxygen in a compartment to support life | all of the above | combustible gases present |
| 3610 | A victim is coughing and wheezing from a partial obstruction of the airway. An observer should: | perform the Heimlich maneuver | immediately administer CPR | allow the person to continue coughing and dislodge the obstruction on his own | give back blows and something to drink |
| 3611 | A shipmate chokes suddenly, cannot speak, and starts to turn blue. What action should you take? | do nothing until the victim become unconscious | administer the Heimlich maneuver | immediately administer CPR | make the victim lie down with the feet elevated to get blood to the brain |
| 3612 | Before administering any penicillin, preparations should include determining whether the patient is _____ to such medicine. | addicted | immuned | allergic | accustomed |
| 3613 | What is a treatment for traumatic shock? | Keep the victim in a sitting position | Administer CPR | Open clothing to allow cooling of the body | Administer fluids |
| 3614 | A man has suffered a burn on the arm. There is extensive damage to the skin with charring present. This is an example of what kind of burn? | Dermal burn | Third-degree burn | Lethal burn | Major burn |
| 3615 | In the absence of arachis oil, earwax hardening causing deafness can be removed using: | fish oil | nitroglycerine | clove oil | olive oil |
| 3616 | If anti-seasickness pill is ineffective, what is an alternative medication? | Eucalyptus oil | Antipyretic | Paracetamol | Antihistamine |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 3617 | Survivors in the water should be lifted in a horizontal or near-horizontal position if possible to minimize _____ induced by sudden transfer from the water and possible hypothermia. | wound | the risk of shock | possible fracture | the pain |
| 3618 | Unless there is danger of further injury, a person with a compound fracture should not be moved until bleeding is controlled and: | the wound has been washed | radio advice has been obtained | the bone has been set | the fracture is immobilized |
| 3619 | What is NOT a treatment for traumatic shock? | Have the injured person lie down | Massage the arms and legs to restore circulation | Keep the patient warm but not hot | Relieve the pain of the injury |
| 3620 | Appendicitis has become common to seafarers. It is a condition characterized by _____ of the appendix. | enlargement | inflammation | rupture | swelling |
| 3621 | A man has suffered a burn on the arm. There is reddening of the skin blistering and swelling. How would this injury be classified using standard medical terminology? | major burn | blister burn | second-degree burn | secondary burn |
| 3622 | A rapid, emergency evaluation of the patient should be made immediately at the scene of the injury to determine the: | source of injury | type and extent of trauma | necessary antidote and the prevention of further injury | cause of the accident |
| 3623 | How do you determine the first symptoms of a stroke? | Low blood pressure | High blood pressure | Stomach pains | All of the choices |
| 3624 | An oxygen indicator will detect: | concentrations of explosive gas | the presence of harmful amounts of carbon monoxide | an oxygen deficiency in a space | all of the above |
| 3625 | You are using an automatic tension winch by yourself. If you get caught in the turns of the line as they lead into the gypsyhead: | the safety cutout will stop the winch before you're injured | you may be pulled into the winch and injured or killed | the line will part and snap back | None of the choices are correct |
| 3626 | Compound fracture is a fracture in which: | more than one bone is broken | there is never any internal bleeding | the bone may be visible | the same bone is broken in more than one place |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 3627 | How can a victim with an airway completely obstructed be recognized? | Clutches neck with both hands | Unable to speak, breath or cough | Collapse and lying at his back | Totally unconscious |
| 3628 | An alternative method of Artificial respiration where in some instances, mouth-to-mouth respiration cannot be used due to certain toxic and caustic materials constitute a hazard for the rescuer is known as: | Heimlich maneuver | Silvester method | Xyphoid process | Heat compression |
| 3629 | During a bomb search, which of the following is an important principle to follow? | Know exactly what a bomb looks like | Throw any suspicious package overboard | Try to reach behind bulkhead to reach a bomb | Do not touch any suspicious package |
| 3630 | A man has a burn on his arm. There is reddening of the skin blistering and swelling. Using standard medical terminology what type of burn is this? | major burn | secondary burn | second-degree burn | third-degree burn |
| 3631 | A survivor has been pulled from the water off the coast of Greenland. The patient is in a state of confusion and has ceased shivering. Which of the following best describes the patient s condition? | the patient is suffering from mild hypothermia | the patient is suffering from frostbite | the patient is suffering from severe hypothermia | the patient is suffering from moderate hypothermia |
| 3632 | Following a serious marine incident who can administer use of the device that tests an individuals breath? | any USCG credentialed deck officer | the marine employer | qualified medical personnel only | any individual trained to conduct such tests |
| 3633 | If a rescuer finds an electrical burn victim in the vicinity of live electrical equipment or wiring what would be the first action to take? | remove the patient from the vicinity of the live electrical equipment or wiring | apply ointment to the burned areas on the patient | get assistance to shut down electrical power in the area | flush water over any burned area of the patient |
| 3634 | What are symptom(s) of a ruptured appendix? | Dilated pupils and shallow breathing | Muscle tenseness in almost the entire abdomen | Extreme sweating and reddening skin | Diarrhea and frequent urination |
| 3635 | What is MOST important when administering artificial respiration? | clear airways | know all approved methods | monitor blood pressure | clear head and body |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 3636 | WHat is the most importanat consideration while providing assistance to a victim of an epileptic seizure? | prevent patient from hurting himself | keep the patient awake and make him/her walk if necessary to keep him/her awake | give artificial respiration | remove any soiled clothing and put the patient in a clean bed |
| 3637 | What should you do before CPR is started? | establish an open airway | treat any bleeding wounds | insure the victim is conscious | establish comfort |
| 3638 | When treating a chemical burn what is the minimum amount of time you should flood the burned area? | five minutes | ten minutes | twenty minutes | six minutes |
| 3639 | While carrying out artificial respiration how should rescuers be changed out? | at ten-minute intervals | without losing the rhythm of respiration | only with the help of two other people | by not stopping the respiration for more than 5 minutes |
| 3640 | A crew member has suffered frostbite to the toes of the right foot. Which is NOT an acceptable first aid measure? | Give aspirin or other medication for pain if necessary | Rewarm rapidly | Elevate the foot slightly | Rub the toes briskly |
| 3641 | A man has a burn on his arm. There is reddening of the skin blistering and swelling. Using standard medical terminology this is a _____. | major burn | second-degree burn | secondary burn | blister burn |
| 3642 | A patient in shock should NOT be placed in which position? | Flat on their back with head and feet at the same level | Head down and feet up no injuries to face or head | Arms above their head | On their side if unconscious |
| 3643 | A person reports to you with a fishhook in his thumb. To remove it you should _____. | have a surgeon remove it | pull it out with pliers | cut the skin from around the hook | push the barb through cut it off then remove the hook |
| 3644 | A seaman has a small gaping laceration of the arm that is not bleeding excessively. What can be done as an alternative to suturing to close the wound? | Wrap a tight bandage around the wound | Apply a compression bandage | Use temporary stitches of sail twine | Apply butterfly strips then a sterile dressing |
| 3645 | A shipmate suffers a heart attack and stops breathing. You must _____. | administer oxygen immediately | make the victim comfortable in a bunk | immediately give a stimulant by force if necessary | check his pulse and start CPR |
| 3646 | An unconscious person should not be _____. | placed in a position with the head lower than the body | given an inhalation stimulant | given something to drink | treated for injuries until conscious |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 3647 | If a crew member faints you should: | check for pulse and breathing | lay him down with his head lower down his feet | let the patient rest in unconscious position | immediately execute Heimlich Maneuver |
| 3648 | If a crew member is exposed to phenol by way of skin or eye contact you should IMMEDIATELY _____. | treat victim for shock | administer oxygen | flush skin and eyes with water | give victim stimulant |
| 3649 | What are the symptoms of heat exhaustion? | reddish and clammy skin | slow and deep breathing | pale and clammy skin | slow and strong pulse |
| 3650 | What are the symptoms of heat stroke? | hot and moist skin high body temperature | cold and dry skin low body temperature | hot and dry skin high body temperature | cold and moist skin high body temperature |
| 3651 | What is it called when you sort accident victims according to the severity of their injuries? | surveying | evaluation | triage | ignore |
| 3652 | What is the most effective treatment for warming a crew member suffering from hypothermia? | running or jumping to increase circulation | bundling the body in blankets to rewarm gradually | raising body temperature rapidly by placing hands and feet in hot water | laying prone under heat lamps to rewarm rapidly |
| 3653 | What must the rescuer be able to do in managing a situation involving multiple injuries? | provide the necessary medication | prescribe treatment for the victim | accurately diagnose the ailment or injury | rapidly evaluate the seriousness of obvious injuries |
| 3654 | What should a observer do if a victim is coughing and wheezing from a partial obstruction of the airway? | perform the Heimlich maneuver | immediately start CPR | give back blows and something to drink | allow the person to continue coughing and dislodge the obstruction on his own |
| 3655 | What should you look for evidence of if a victim is unconscious? | broken limbs | head injury | high fever | irregular breathing |
| 3656 | A crew member is unconscious and the face is flushed. You should: | administer a liquid stimulant | lay the crew member down with the head lower than the feet | lay the crew member down with the head and shoulders slightly raised | attempt to stand the crew member upright to restore consciousness |
| 3657 | A crew member suddenly becomes blind in both eyes. Which code should your message contain? | MNO | MNJ | MNI | MNM |
| 3658 | A crew member suffering from hypothermia should be given _____. | a small dose of alcohol | a large meal | a brisk rub down | treatment for shock |
| 3659 | A dislocation: | Occurs when a bone is forced out of or twisted in its joint | Is not usually painful | Occurs only in the joints of the fingers. | Usually involves the spine |

| | | | | | |
|---|---|---|---|---|---|
| 3660 | A drug or medicine given to reduce pain without resulting in loss of consciousness. It is sometimes referred to as painkiller medications. | Antipyretic | antibiotics | antibacterial | Analgesic |
| 3661 | A faint is a brief loss of consciousness of no more than momentary duration caused by a temporary reduction in the flow of blood to the brain. How to prevent anyone from fainting? | given something to drink | Try to keep the person in an upstanding position. | Tell the person to sit down and lean forward with the head between the knees taking deep breaths. | treated for injuries until conscious |
| 3662 | A man has suffered a burn on the arm. There is a reddening of the skin but no other apparent damage. Using standard MEDICAL terminology this is a _____. | Superficial burn | Extremity burn | Minor burn | First-degree burn |
| 3663 | A man has suffered a burn on the arm. There is extensive damage to the skin with charring present. How is this injury classified using standard medical terminology? | second degree burn | Third-degree burn | Dermal burn | first degree burn |
| 3664 | A man has suffered a burn on the arm. There is a reddening of the skin but no other apparent damage. Using standard MEDICAL terminology what type of burn is this? | Minor burn | Superficial burn | First-degree burn | Extremity burn |
| 3665 | A Master may find it difficult to provide the necessary care for a gravely ill or injured crew on board. These are measures to be taken for the protection of the crew EXCEPT: | Inject adrenaline immediately | a message should be transmitted to Radio Medical Center | medical advise should be signed by the Master | to request instructions on the proper treatment |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 3666 | A Master may find it difficult to provide the necessary care for a gravely ill or injured crew on board. These are measures to be taken for the protection of the crew EXCEPT: I. Inject adrenaline immediately II. to request instructions on the proper treatment | I only | II only | Neither I nor II | I and II are correct |
| 3667 | A minor heat burn of the eye should be treated by _____. | gently flooding with water | laying the person flat on his back | mineral oil drops directly on the eye | warming the eye with moist warm packs |
| 3668 | A patient suffering from heat exhaustion should be _____. | kept standing and encouraged to walk slowly and continuously | None of the above is correct. | moved to a cool room and told to lie down | given a glass of water and told to return to work after 15 minutes of rest |
| 3669 | A patient with a severe head injury should be: | Given morphine at once to prevent pain | Watched carefully but his state of consciousness may be ignored because it may be misleading | Returned to work as soon as possible to determine if any brain damage has occurred | Put to bed. Relieve his pain with an ice bag and radio for advice |
| 3670 | A person being treated for shock should be wrapped in warm coverings to _____. | avoid self-inflicted wounds caused by spastic movement | protect the person from injury during transportation | increase body heat | preserve body heat |
| 3671 | A person has suffered a laceration of the arm. Severe bleeding has been controlled by using a sterile dressing and direct pressure. What should you do next? | Apply a pressure bandage over the dressing. | Apply a tourniquet to prevent the bleeding from restarting. | Remove any small foreign matter and apply antiseptic. | Administer fluids to assist the body in replacing the lost blood. |
| 3672 | A person is exhibiting signs of hypothermia and starts to shiver what does this indicate? | the body requires a rapid increase in core temperature | the body is trying to generate more heat | the body is dilating blood vessels to conserve heat | the body is in the final stages of severe hypothermia |
| 3673 | A person slowly feel more sleepy and thirsty. The skin become very dry and there is a sweet taste of the breath. The glucose reaction shows positive. What kind of medicine will the person need as soon as possible? | A glass of cold softdrinks | decstrose | A glass of cold milk. | Insulin. |

| | | | | | |
|---|---|---|---|---|---|
| 3674 | A person suffering from possible broken bones and internal injuries should _____. | be examined then walked to a bunk | be assisted in walking around | not be allowed to lie down where injured but moved to a chair or bunk | not be moved but made comfortable until medical assistance arrives |
| 3675 | A person who gets battery acid in an eye should IMMEDIATELY wash the eye with _____. | baking soda solution | boric acid solution | ammonia | water |
| 3676 | A person who gets battery acid in an eye should IMMEDIATELY wash the eye with what liquid? | water | water | boric acid solution | baking soda solution |
| 3677 | A person with diabetes has received a minor leg injury. What symptoms would indicate the onset of a diabetic coma? | slurred speech and loss of coordination | reduced appetite and thirst | only a low grade fever | sneezing and coughing |
| 3678 | Which statement is CORRECT with respect to inserting an airway tube? | Inserting the airway tube will prevent vomiting. | The airway tube will not damage the victims throat. | Only a trained person should attempt to insert an airway tube. | A size 2 airway tube is the correct size for an adult. |
| 3679 | First-, second-, and third-degree burns are classified according to the _____. | area of the body burned | layers of skin affected | source of heat causing the burn | size of the burned area |
| 3680 | A minor heat burn of the eye should be treated by _____. | mineral oil drops directly on the eye | warming the eye with moist warm packs | laying the person flat on his back | gently flooding with water |
| 3681 | Symptoms of heat stroke are _____. | hot and moist skin, high body temperature | cold and moist skin, high body temperature | cold and dry skin, low body temperature | hot and dry skin, high body temperature |
| 3682 | What are the symptoms of sun stroke? | Temperature is high, pulse is strong and rapid, skin is hot and dry. | Temperature falls below normal, pulse is rapid and feeble, skin is cold and clammy. | Temperature is high, pulse is slow and feeble, skin is clammy. | Temperature falls below normal, pulse is rapid, skin is clammy. |
| 3683 | A crew member has suffered frostbite to the toes of the right foot. Which is NOT an acceptable first aid measure? | Give aspirin or other medication for pain if necessary. | Elevate the foot slightly. | Rewarm rapidly. | Rub the toes briskly. |
| 3684 | Treatment of sunstroke consists principally of _____. | All of the options | drinking ice water | bathing with rubbing alcohol | cooling, removing to shaded area, and lying down |
| 3685 | Which procedure should NOT be done for a person who has fainted? | Revive the person with smelling salts. | Give pain reliever. | Loosen the clothing. | Lay the person horizontally. |

| | | | | | |
|---|---|---|---|---|---|
| 3686 | The proper stimulant for an unconscious person is _____. | coffee | whiskey and water | tea | ammonia inhalant |
| 3687 | In reviving a person who has been overcome by gas fumes, what would you AVOID doing? | Giving stimulants | Applying artificial respiration and massage | Keeping the patient warm and comfortable | Prompt removal of the patient from the suffocating atmosphere |
| 3688 | Persons who have swallowed a non-petroleum based poison are given large quantities of warm soapy water or warm salt water to _____. | neutralize the poison in the blood | increase the digestive process and eliminate the poison | absorb the poison from the blood | induce vomiting |
| 3689 | To reduce mild fever the MOST useful drug is _____. | aromatic spirits of ammonia | bicarbonate of soda | paregoric | aspirin |
| 3690 | First aid means _____. | setting of broken bones | medical treatment of accident | emergency treatment at the scene of the injury | dosage of medications |
| 3691 | The most important reason for taking anti-seasickness pills as soon as possible after entering a liferaft is to _____. | reduce appetite by decreasing nausea | assist in sleeping | prevent impaired judgment due to motion-induced deliriousness | prevent loss of body moisture by vomiting |
| 3692 | You may have to give artificial respiration after a/an _____. | All of the choices | electrocution | poisoning | drowning |
| 3693 | When administering artificial respiration, it is MOST important to _____. | know all approved methods | monitor blood pressure | clear airways | use the rhythmic pressure method |
| 3694 | A conscious victim who has suffered a blow to the head has symptoms that indicate the possibility of concussion. If the patient feels no indication of neck or spine injury, recommended treatment would include _____. | elevating the head and shoulders slightly with a pillow | turning the victims head to the side to keep his airway open | giving the victim water if he is thirsty, but no food | positioning the victim so the head is lower than the body |
| 3695 | A shipmate suffers a heart attack and stops breathing. You must _____. | immediately give a stimulant, by force if necessary | make the victim comfortable in a bunk | administer oxygen | immediately start CPR |
| 3696 | The most effective treatment for warming a crew member suffering from hypothermia is _____. | running or jumping to increase circulation | bundling the body in blankets to rewarm gradually | raising body temperature rapidly by placing hands and feet in hot water | laying prone under heat lamps to rewarm rapidly |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 3697 | Which procedure should be followed when individuals are rescued in cold climates and suffer from hypothermia? | Keep them moving to stimulate circulation to raise their body temperature. | Move them to a warm room to gradually raise their body temperature. | Warm them under an electric blanket to rapidly regain normal body temperature. | Give them brandy or other alcoholic stimulation to promote a return to an acceptable body temperature. |
| 3698 | When a person is in shock, their skin will be _____. | cold and dry | cold and damp | warm and dry | warm and damp |
| 3699 | A major health hazard of the product tert-butylamine is that it_____. | all of the options | is a very unstable product | can be absorbed through the skin | causes irreversible damage to eye tissue |
| 3700 | The first treatment given to a person overcome by benzene vapor should be to _____. | remove their clothing and wrap them in blankets | stand them up and walk them around | remove them to fresh air | flush their face with water for about 5 minutes |
| 3701 | What is NOT generally a characteristic of inhaling light naphtha? | Vomiting | Coughing | Dizziness | Headache |
| 3702 | If a crew member is exposed to phenol by way of skin or eye contact, you should IMMEDIATELY _____. | treat victim for shock | give victim stimulant | administer oxygen | flush skin and eyes with water |
| 3703 | Medical treatment aboard a ship should not go beyond examination and emergency care without first consulting _____. | the designated medic aboard | the shore based superintendent | the approved company medical manual | a medical doctor |
| 3704 | What is the proper first aid for LPG in the eye? | Keep the eyelid closed. | Flush the eye with plenty of water. | Rub the eye area clean. | Apply an ice pack to the eye. |
| 3705 | When providing first aid to a victim of gas poisoning, the MOST important symptom to check for is _____. | slow and weak pulse | suspension of breathing | cold and moist skin | unconsciousness |
| 3706 | While operating off Panama, a seaman is injured. What indicator should be included in the preamble of a telegram requesting a medical advice from a Panamanian station? | DH medico | Radio medical | XXX | Med rad |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 3707 | If one requires medical advice by means of an Inmarsat-C terminal one should use the following address_____ | MED + | Radiomedical | Dont know | 32 |
| 3708 | While operating off the coast of Greece, a seaman is injured. What indicator should be in the preamble of a radio telegram asking for medical advice from a Greek station? | Medico ellas | Radio medical | DH medico | Mayday |
| 3709 | What is the purpose of a Medico Message? | Giving a regular statement of the health of the vessels crew. | Calling the health department in the next port of call and ask for free radio practice. | Call a hospital for professional medical assistance by radio when needed. | Medico is the certificate which permit the Master to be doctor onboard. |
| 3710 | If a person is in a state of shock, what of the following is the correct thing of you to do? | Apply hot-water bottles to keep the patient warm. | Treat and reassure the casualty and stay with the person at all times. | Move the casualty as much as possible. | Be kind to the casualty and give anything to eat or drink at first opportunity. |
| 3711 | Appendicitis symptoms include cramps or pain in the abdomen located in the _____. | lower right side | lower left side | upper left side | upper right side |
| 3712 | When a person is suspected of having appendicitis, the pain should be relieved by: | Keeping an ice bag over the location of the appendix. | Giving the patient aspirin with a glass of water. | Giving the patient morphine sulfate. | Giving the patient laxative. |
| 3713 | ____ is the proper stimulant for an unconscious person? | dextran | water | Ammonia | tiger balm |
| 3714 | Narcotics is given to a patient when: | In great pain | He is groggy | Unconscious | Intoxicated |
| 3715 | Universal antidote is used to neutralize a sick person with: | Clean wounds | Poison | Diarrhea | Hemorrhage |
| 3716 | What is not a treatment for traumatic shock? | Have the injured person lie down. | Keep the patient warm but not hot. | Massage the arms and legs to restore circulation. | Relieve the pain of the injury. |
| 3717 | A person suffering from possible broken bones and internal injuries should _____. | not be allowed to lie down where injured but moved to a chair or bunk | be assisted in walking around | not be moved but made comfortable until medical assistance arrives | be examined then walked to a bunk |

| | | | | | |
|---|---|---|---|---|---|
| 3718 | You are treating a shipmate with a compound fracture of the lower arm. Which action should you take? | Apply a bulky, sterile, pressure dressing to control bleeding, then apply a temporary splint, and obtain medical advice. | Force the ends of the bones back into line, treat the bleeding, and splint. | Apply traction to the hand to keep the bones in line, splint, and apply a pressure dressing. | Apply a tourniquet to control bleeding then align the bones and splint. |
| 3719 | A man has suffered a burn on the arm. There is extensive damage to the skin with charring present. How is this injury classified using standard medical terminology? | Major burn | Lethal burn | Dermal burn | Third-degree burn |
| 3720 | Before CPR is started, you should _____. | treat any bleeding wounds | establish an open airway | make the victim comfortable | insure the victim is conscious |
| 3721 | The ABC-rules are an important part of the First Aiders know how. What does the First Aid ABC-rules stands for? | Anything But Continuation | Adults Behind Children | A Better Control | Airway Breathing Circulation |
| 3722 | According to SOLAS requirement for lifeboat fall, what action must be taken with the fall at interval of not more than 5 years? | weight tested | Proof tested | reverse | Renewed |
| 3723 | Due to the nature of a vessel's construction for a particular trade, it does not fully comply with the provisions of SOLAS. Where will this be indicated? | On the reverse of the particular SOLAS certificate affected | On the Exemption Certificate | On the face of the Certificate of Inspection | Nowhere; the vessel must comply to engage in international trade. |
| 3724 | In accordance with SOLAS convention, how long shall the auxilliary steering gear be capable of turning 15 degrees on one side to 15 degrees on the other side? | not more than 30 seconds | not more than 40 seconds | not more than 60 seconds | not more than 20 seconds |
| 3725 | ISPS Code was formulated as a result of what incident | Grounding of Exxon Valdez | Agreed upon by IMO member countries to address safety issues | 9/11 bombing of World Trade Center | Sinking of RMS Titanic |
| 3726 | Sludge are to be disposed off at sea | disposal prohibited | 50 miles offshore | 25 miles offshore | during darkness only |
| 3727 | Oily mixtures according to Marpol means: | a mixture with any oil content | a mixture with oil content above 100 ppm | a mixture with oil content above 50 ppm | a mixture with oil content above 15 ppm |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 3728 | An IOPP Certificate on an inspected vessel is valid for what period of time? | 2 years | 5 years | 6 months | 1 year |
| 3729 | When oil is discharged overboard, an entry is required in the _____. | Official Logbook | Oil Record Book | engine rough log | deck rough log |
| 3730 | When oily ballast has been pumped overboard, an entry must be made in the _____. | deck rough log | Oil Record Book | engine rough log | Official Logbook |
| 3731 | The Oil Record Book on a vessel NOT engaged on a foreign voyage shall be maintained on board for not less than _____. | 48 months | 36 months | 12 months | 24 months |
| 3732 | _____ must counter sign any completed pages of the Oil Record Book. | Master | Chief Engineer | Designated Officer | Master and Chief Engineer |
| 3733 | Oil discharge in large quantities form _____ which will affect birds at sea and may strand on beaches if these do not disperse into the water as water droplets before reaching shore: | patches | slicks | spills | emulsions |
| 3734 | What is the minimum number of fire pumps required on a cargo vessel of 900 GT? | 2 | 1 | 4 | 3 |
| 3735 | What is the minimum number of fire pumps required on a cargo vessel of 2,000 GT? | 1 | 4 | 3 | 2 |
| 3736 | Which vessel greater than 100 GT is NOT required to have an EPIRB. | A fishing vessel | A non self-propelled vessel in tow | A sailing vessel | A towing vessel |
| 3737 | For carbon dioxide fire-fighting systems for machinery spaces the fixed piping system shall be such that: (SOLAS II-2/5.2.4) | 70% of the gas can be discharged into the space within one minute | 100% of the gas can be discharged into the space within three minutes | 85% of the gas can be discharged into the space within two minutes | 100% of the gas can be discharged into the space within two minutes |
| 3738 | Lifeboats for ocean-going vessels shall carry in excess of the required regulation by: | 100% of persons on board | 25% of persons on board | 50% of persons on board | 75% of persons on board |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 3739 | Which one of the listed requirements regarding abandon ship drills corresponds to present SOLAS regulation? | All lifeboats shall be lowered during drills. | Each lifeboat shall be launched with its assigned crew, and maneuvered in the water at least once every three months during an abandon ship drill. | Drills shall be conducted when the ship is in a harbour. | On ships on short international voyages, each lifeboat shall be launched and maneuvered in the water at least every six months. |
| 3740 | As per SOLAS Regulation, the minimum Fuel supply for fast Rescue Boat shall last for__. | 16 hours | 8 hours | 4 hours | 12 hours |
| 3741 | SOLAS stipulates that if more than 25% of crew have not participated in abandonship and fire drills in the previous month, the drills of the crew shall take place_____. | 48 hours after embarkation | 24 hours after embarkation | within 24 hours after ship leaves port | within 48 hours after ship leaves port |
| 3742 | As per SOLAS Regulation, the capacity rate of ships emergency fire pumps shall be ____. | 30 cu.m./hour | 75 cu.m./hour | 50 cu.m./hour | 25 cu.m./hour |
| 3743 | In case each hydrant is not fitted with hose and nozzles, what is the requirement? (SOLAS II-2/4.6.1) | At each fire station, sufficient number of hoses with nozzles for the hydrants in the area shall be available | Hoses with fixed nozzles to be kept ready for use in conspicuous positions near the hydrants | Complete interchangeability of hose couplings and nozzles | Hoses and nozzles for each hydrant to be available at the fire stations |
| 3744 | SOLAS stipulates that ships of 500 GRT or more shall have at least one international shore connection with an outside diameter of____ | 174 mm | 172 mm | 176 mm | 178 mm |
| 3745 | Under SOLAS passenger ships and ships other than passenger ships of _____ and upwards constructed on or after 2002 must carry Voyage Data Recorders (VDR) to assist in accident investigation. | 2,000 GRT | 10,000 GRT | 3,000 GRT | 4,000 GRT |
| 3746 | The ISM Code requires ship owners or shipping companies to assign a _____ onboard their ship: | Overseeing Committee | Safety Committee | Welfare Committee | Logistics Committee |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 3747 | ISPS Code was formulated as a result of what incident | Agreed upon by IMO member countries to address safety issues | Grounding of Exxon Valdez | 9/11 bombing of World Trade Center | Sinking of RMS Titanic |
| 3748 | CSO is responsible for : | enhancing security awareness of port facility personnel | conducting audit of vessel regarding safety | Development, implementation and maintenance of SSP | undertaking regular security inspection of the vessel |
| 3749 | The ISPS Code was Adopted by Contracting Government with Part A & B. The mandatory requirements & guidance is under the provisions of _____ of the SOLAS as amended. | Chapter X-1 | Chapter XX-1 | Chapter IX-2 | Chapter XI-2 |
| 3750 | The ISPS Code applies to: I. Passenger ships II. Mobile offshore drilling units (MODU) | I only | Neither I or II | II only | Both I and II |
| 3751 | One of the many objectives of the _____ is to ensure the early and efficient collection and exchange of security-related information. | ISPS Code | STCW Code | FTP Code | Code of Safe Practice for the Handling of Cargo |
| 3752 | Who is given the authority to carry out assessment for a certification as required by Chapter XI-2 of SOLAS as amended of the ISPS Code? | Security Administration | Contracting Gov't Coast Guards | Recognize Security Organization | Port State Control |
| 3753 | At what security level is further specific protective security measures to be maintained for a limited period of time when a security incident is probable or imminent, although it may not be possible to identify the specific target? | Security level 3 | Security level 2 | Security level 1 | Security level 4 |
| 3754 | Under the New Regulations, what does SOLAS Chapter XI-1 deals with? | Additional provisions to combat Terrorism | Special provisions for Ship Security and Port Facilities | Security planning and Ship and Port Facility | Special measures to enhance Maritime Safety |
| 3755 | A CSO is designated by the_____. | Captain of the Port | Contracting Governments | Company operating the ship | Administration |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 3756 | Sludge are to be disposed off at sea | disposal prohibited | 50 miles offshore | during darkness only | 25 miles offshore |
| 3757 | Oily mixtures according to Marpol means: | a mixture with oil content above 15 ppm | a mixture with oil content above 50 ppm | a mixture with oil content above 100 ppm | a mixture with any oil content |
| 3758 | An IOPP Certificate on an inspected vessel is valid for what period of time? | 1 year | 5 years | 2 years | 6 months |
| 3759 | When oil is discharged overboard, an entry is required in the _____. | Official Logbook | Oil Record Book | engine rough log | deck rough log |
| 3760 | When oily ballast has been pumped overboard, an entry must be made in the _____. | deck rough log | engine rough log | Official Logbook | Oil Record Book |
| 3761 | The Oil Record Book on a vessel NOT engaged on a foreign voyage shall be maintained on board for not less than _____. | 36 months | 24 months | 12 months | 48 months |
| 3762 | _____ must counter sign any completed pages of the Oil Record Book. | Master and Chief Engineer | Master | Designated Officer | Chief Engineer |
| 3763 | Oil discharge in large quantities form _____ which will affect birds at sea and may strand on beaches if these do not disperse into the water as water droplets before reaching shore: | slicks | emulsions | spills | patches |
| 3764 | MEPC as referred to in the MARPOL Convention stands for: | Marine Environment Protocol Committee | Marine Environment Pollution Control | Marine Environment Protection Control | Marine Environment Protection Committee |
| 3765 | ____ is contained in Annex II of MARPOL 73/78? | Regulations for the Prevention of Pollution by Harmful Substances in a Packaged Form | Regulations for the Control of Pollution by Noxious Liquid Substances | Regulations for the Prevention of Pollution by Oil | Regulations for the Prevention of Pollution by Sewage |
| 3766 | Where in accommodation spaces shall smoke detectors be located? (SOLAS II-2/13.2.2) | In all crew and passenger cabins | Near ventilation ducts throughout the accommodation spaces | In stairways, corridors and escape routes | In messrooms, public lounges and other public rooms |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 3767 | Annex V of MARPOL 73/78 contains requirements pertaining to the discharge into the marine environment of: | Noxious liquid substances | Sewage | Garbage | Oil |
| 3768 | Regulation concerning the stowage, lashing and securing of timber deck cargoes aboard general cargo vessels may be found in the: | Rules and Regulations for Cargo and Miscellaneous Vessel | Vessels Classification Society Rules and Regulations | International Cargo Bureau Regulations | Load Lines Regulations |
| 3769 | Part C, Chapter VI of SOLAS deals with: | radioactive materials | General Provision | carriage of grain | bulk cargoes other than grain |
| 3770 | What is the outside diameter for standard discharged connection? | 215mm | 170mm | 185mm | 210mm |
| 3771 | What is the validity of an International Air Pollution Prevention Certificate as specified by the Administration? | 5 YEARS | 3 YEARS | 4 YEARS | 2 YEARS |
| 3772 | M/V Macario is on voyage charter and she is to load at a rate of 12,000 tons per day as stipulated in the C/P. Determine how many tons of cargo has she loaded without earning any dispatch or demurrage if the loading of the booked cargo was completed in 2 days and 20 hours? | 34,000.00 tons | 35,000.00 tons | 53,000.00 tons | 43,000.00 tons |
| 3773 | What is the meaning of "Slop Tank" as per Marpol? | A tank used for tank cleaning provided with heat coils | The two most aftward fitted wing tanks or the most aftward fitted center tank | A tank specifically designed for the collection of tank drainings, washings or other oily mixtures | Any tank where slops sludge's are collected |
| 3774 | Which term denotes the money is paid by the charterer for cargo which otherwise could have been loaded but was not? | allowance | deadfreight | bill of lading | demurrage |
| 3775 | What product is considered a noxious liquid substance for regulatory purposes? | Amylene | Sulfur | Hog grease | Nonane |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 3776 | When the original Bill of Lading is signed by the Master, it is NOT: | the company is will be held reliable to any proof that goods are received onboard | an intended penalty will be suitable if not signed by Master | surrendered to the customs agency of the country where cargo is discharged | a receipt and proof that goods have been received onboard |
| 3777 | An amendment procedure under MLC 2006? | Article XIII for amendments only to the Code | Article IX for amendments only to the Code | Article XV for amendments only to the Code | Article XI for amendments only to the Code |
| 3778 | What is the unit used in Instantaneous Rate of Discharge of Oil? | Barrel per unit area per knot | Tons per square mile per knot | Liters per nautical mile | Gallons per square meter per knot |
| 3779 | part of MLC 2006 will Port State Control inspectors inspect? | Both Parts A and B | Either A or B | Part B - Guidelines | Part A - Standards |
| 3780 | The National Cargo Bureau represents the: | Charterer | Broker | Shipper | Port Authority |
| 3781 | This is a cargo ship constructed or adapted and used for the carriage in bulk of any liquid product: | crude carrier | chemical tanker | product tanker | LPG tanker |
| 3782 | ILO Conventions are consolidated in the MLC, 2006? | Consolidated Convention of 2006 | 36 Conventions and one Protocol | International Conventions of Maritime Industry | ILO Conventions 68, 69 and 70 only |
| 3783 | When ballasting cargo tanks, _____ should be recorded in the Cargo Record Book for ships carrying noxious liquid substances. | Number of ballast tanks | Weight of ballast | Density of the ballast | Identity of tank(s) |
| 3784 | The computation of the charter party payments as per voyage charter is : | $145,200 | depends on the charterers choice in the memorandum of agreement | $142,500 | fixed in proportion to the cargo size or in the form of a lump sum for the voyage |
| 3785 | The Administration may waive the requirements for Garbage Record Book due to the following reason: | voyages of one (1) hour or less in duration /certified to carry 15 persons or more | discharge of clean ballast | destination of the cargoes | weather condition |
| 3786 | What is the penalty levied for ships delay after laydays have expired due to fault of the charterer? | demurrage | despatch money | distorted payment | extorted money |
| 3787 | Vessels that carry cargo exclusively and operates over a definite routes on a fixed schedule: | Liner shipping | Domestic shipping | Tramp shipping | Local shipping |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 3788 | Garbage is to be grouped into 9 categories for the purposes of the Garbage Record Book. Group "E" shall include? | Dunnages | Incinerator Ashes | Plastics | Food Wastes |
| 3789 | The markings defining the maximum allowable draft to which the vessel maybe submerged, also as the Plimsoll mark is _____? | loadline | Simpson mark | deckline | freeboard |
| 3790 | The shipping papers for the products being carried in your tankship are NOT required to contain the: | location of the delivery point(s) | exact quantity of the cargoes | name of the consignee(s) | grades of the cargoes |
| 3791 | What is the meaning IOPP Certificates issued by any government? | International Oil Pollution Prevention Certificate | International Oil Prevention and Pollution Cartel | International Oil Providers Provisionary certificate | International Oil Payment Provisional Certificate |
| 3792 | Which of the following gives the best form of assessment of training? | demonstrating competence in the workplace | acting as assistant in an unusual mooring operations | practice makes perfect | keeping a good eye on the Ship Captain |
| 3793 | Which of the following items has to be included in an abandon ship drill according to SOLAS regulations? | Maneuvering the lifeboat in the water. | Starting and operating radio life-saving appliances. | Checking that life-jackets are correctly donned. | Launching and recovery of a survival craft. |
| 3794 | The requirement for the rest periods as required by STCW convention need not be maintained in certain cases such as: | maneuvers to dock and undock | emergency or overriding operational conditions | stoppages of the main engines | cleaning holds |
| 3795 | The most accurate account of cargo on board will be found in the: | Portage Bill | Manifest | Bill of Lading | charter party |
| 3796 | Which office recommends and implements policies under the administration of MARINA? | MARINA Policy | Administrative Policy | Domestic Shipping Office | Domestic Policy Making Office |
| 3797 | (UNCLOS) required that all flag states take account or give effect to;or implement the relevant rules and standards developed by the _____? | International Maritime Organization (IMO) | Marintime Inquiry | International Shipping Company | Baltic International Maritime Corporation (BIMCO) |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 3798 | All wire ropes used in shipboard cargo gears must be identified and described in a certificate. The certificate shall certify all of the following except the: | number of strands and wires in each strand | name of the testing agency | date of the test | load at which the test sample broke |
| 3799 | A Philippine registered cargo vessel below 500 grt engaged in international voyage requires which license for the rank of Master? | Master Mariner | Recommending Officer | Chief Mate | Officer in charge |
| 3800 | What is the meaning of "Harmful Substances" under Marpol? | Petroleum products and petrochemicals | Oils and Fuels | Hydrocarbons in any form | Any substances creating harm to health and life or able to damage amenities |
| 3801 | When ships are on short voyages, how often is the quantity residue recorded in the Machinery Space Oil Record Book? | Twice a week | Once a week | Once a month | Once every two weeks |
| 3802 | A vessel not having on board a document of authorization issued in accordance with part A3 of the International Grain Code may be permitted to load bulk grain provided that the total weight of the bulk grain shall not exceed: | One-third of the deadweight of the ship | One-fourth of the deadweight of the ship | One-fifth of the deadweight of the ship | One-half of the deadweight of the ship |
| 3803 | An article of transport equipment that is of a permanent character and accordingly strong enough to be suitable for repeated use without immediate reloading. | Unit load | Container | Freight container | Overpack |
| 3804 | Part of MLC 2006 will NOT be inspected by PSC inspectors? | Both Parts A and B | Part B - Guidelines | Either A or C | Part A - Standards |
| 3805 | Ships under Class C includes all: | Cargo ships | Fishing vessel | Tankers | Passenger ships |
| 3806 | Provisions is made for special rules made by the Government of any State with respect to the use of additional whistle signals between which of the listed? | None of the choices is correct | tugs and their tows | pilot vessels and vessels requiring pilots | ships sailing under convoy and ships of war |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 3807 | MARINA was geared towards the following objectives EXCEPT: | plays an important role to protect and enhance the environment for future genearations | to increase production and productivity in the various islands and regions of the archipelago through the provision of linkage | to participate in marine pollution and promote the preservation of a good environment marine conservation | to create sub-agencies for the safe transport of goods and passengers |
| 3808 | What is issued before port authorities and agents can board if you are arriving from a foreign port on international voyage? | police clearance | entry clearance | voyage clearance | free pratique |
| 3809 | According to the Code of Safe Practices for Ship's Carrying Timber Deck Cargoes, which of the following is not included in the term "Timber"? | pulp wood | sawn wood | wood pulp | cant |
| 3810 | Which is true to claims in respect of expenses reasonably incurred or sacrifices reasonably made by the owner voluntarily to prevent/minimize pollution damage? | shall rank equally with other claims against the fund | shall rank at least two thirds of other claims against the fund | shall rank one third of the total amount claims | shall rank more than half of other claims against the fund |
| 3811 | The periodic weight testing of a vessel's cargo booms may be performed by the: | National Cargo Bureau | Society of Naval Architects and Engineers | U.S. Coast Guard | Classification society |
| 3812 | The Garbage Record Book entries for each incineration or discharge shall include the date, time, position of the ship, description of garbage and the estimated _____. | plastic included | time of arrival in port | speed of the ship | amount incinerated |
| 3813 | Your vessel is boarded by the Quarantine Officer. After examination, your vessel was found to have a specific deficiency, therefore you may be issued with which of the following? | Free Pratique | Alternative Pratique | Stress out Pratique | Controlled Free Pratique |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 3814 | Under the Manila Amendments, the performance of a prospective officer in each of the tasks and duties itemized in the training record book should be initialed by: | a qualified officer | company | the Master | the port surveyor |
| 3815 | Under the International Convention for the Prevention of Pollution from Ships,1973, it means the government of the state whose authority the ship is operating. | State | Administration | U.S. Coast Guard | Treaty |
| 3816 | Which among these vessels are classified as category I in the inter-island trade? | vessels whose travel time between ports exceed 6 hours | vessels traveling with a maximium of 17 knots | vessels traveling with a maximum of 20 knots | vessels whose travel time between ports exceed 4 hours |
| 3817 | What is the outside diameter for standard discharged connection? | 185mm | 210mm | 215mm | 170mm |
| 3818 | What is the validity of an International Air Pollution Prevention Certificate as specified by the Administration? | 2 YEARS | 5 YEARS | 3 YEARS | 4 YEARS |
| 3819 | M/V Macario is on voyage charter and she is to load at a rate of 12,000 tons per day as stipulated in the C/P. Determine how many tons of cargo has she loaded without earning any dispatch or demurrage if the loading of the booked cargo was completed in 2 days and 20 hours? | 35,000.00 tons | 43,000.00 tons | 34,000.00 tons | 53,000.00 tons |
| 3820 | What is the meaning of "Slop Tank" as per Marpol? | A tank specifically designed for the collection of tank drainings, washings or other oily mixtures | A tank used for tank cleaning provided with heat coils | The two most aftward fitted wing tanks or the most aftward fitted center tank | Any tank where slops sludge's are collected |
| 3821 | Which term denotes the money is paid by the charterer for cargo which otherwise could have been loaded but was not? | bill of lading | allowance | deadfreight | demurrage |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 3822 | What product is considered a noxious liquid substance for regulatory purposes? | Hog grease | Sulfur | Amylene | Nonane |
| 3823 | When the original Bill of Lading is signed by the Master, it is NOT: | a receipt and proof that goods have been received onboard | the company is will be held reliable to any proof that goods are received onboard | an intended penalty will be suitable if not signed by Master | surrendered to the customs agency of the country where cargo is discharged |
| 3824 | An amendment procedure under MLC 2006? | Article XV for amendments only to the Code | Article IX for amendments only to the Code | Article XI for amendments only to the Code | Article XIII for amendments only to the Code |
| 3825 | What is the unit used in Instantaneous Rate of Discharge of Oil? | Tons per square mile per knot | Barrel per unit area per knot | Gallons per square meter per knot | Liters per nautical mile |
| 3826 | part of MLC 2006 will Port State Control inspectors inspect? | Part B - Guidelines | Both Parts A and B | Either A or B | Part A - Standards |
| 3827 | The National Cargo Bureau represents the: | Broker | Charterer | Shipper | Port Authority |
| 3828 | This is a cargo ship constructed or adapted and used for the carriage in bulk of any liquid product: | LPG tanker | chemical tanker | product tanker | crude carrier |
| 3829 | ILO Conventions are consolidated in the MLC, 2006? | 36 Conventions and one Protocol | ILO Conventions 68, 69 and 70 only | International Conventions of Maritime Industry | Consolidated Convention of 2006 |
| 3830 | When ballasting cargo tanks, _____ should be recorded in the Cargo Record Book for ships carrying noxious liquid substances. | Identity of tank(s) | Density of the ballast | Number of ballast tanks | Weight of ballast |
| 3831 | The computation of the charter party payments as per voyage charter is : | fixed in proportion to the cargo size or in the form of a lump sum for the voyage | $142,500 | depends on the charterers choice in the memorandum of agreement | $145,200 |
| 3832 | The Administration may waive the requirements for Garbage Record Book due to the following reason: | weather condition | destination of the cargoes | discharge of clean ballast | voyages of one (1) hour or less in duration /certified to carry 15 persons or more |
| 3833 | What is the penalty levied for ships delay after laydays have expired due to fault of the charterer? | extorted money | demurrage | despatch money | distorted payment |

| | | | | | |
|---|---|---|---|---|---|
| 3834 | Vessels that carry cargo exclusively and operates over a definite routes on a fixed schedule: | Domestic shipping | Tramp shipping | Local shipping | Liner shipping |
| 3835 | Garbage is to be grouped into 9 categories for the purposes of the Garbage Record Book. Group "E" shall include? | Incinerator Ashes | Dunnages | Food Wastes | Plastics |
| 3836 | The markings defining the maximum allowable draft to which the vessel maybe submerged, also as the Plimsoll mark is _____? | deckline | freeboard | loadline | Simpson mark |
| 3837 | The shipping papers for the products being carried in your tankship are NOT required to contain the: | location of the delivery point(s) | name of the consignee(s) | exact quantity of the cargoes | grades of the cargoes |
| 3838 | What is the meaning IOPP Certificates issued by any government? | International Oil Payment Provisional Certificate | International Oil Providers Provisionary certificate | International Oil Pollution Prevention Certificate | International Oil Prevention and Pollution Cartel |
| 3839 | Which of the following gives the best form of assessment of training? | practice makes perfect | acting as assistant in an unusual mooring operations | keeping a good eye on the Ship Captain | demonstrating competence in the workplace |
| 3840 | Which of the following items has to be included in an abandon ship drill according to SOLAS regulations? | Starting and operating radio life-saving appliances. | Launching and recovery of a survival craft. | Maneuvering the lifeboat in the water. | Checking that life-jackets are correctly donned. |
| 3841 | The requirement for the rest periods as required by STCW convention need not be maintained in certain cases such as: | cleaning holds | emergency or overriding operational conditions | stoppages of the main engines | maneuvers to dock and undock |
| 3842 | The most accurate account of cargo on board will be found in the: | Bill of Lading | charter party | Portage Bill | Manifest |
| 3843 | Which office recommends and implements policies under the administration of MARINA? | Domestic Policy Making Office | Administrative Policy | MARINA Policy | Domestic Shipping Office |
| 3844 | (UNCLOS) required that all flag states take account or give effect to;or implement the relevant rules and standards developed by the _____? | Baltic International Maritime Corporation (BIMCO) | International Maritime Organization (IMO) | International Shipping Company | Marintime Inquiry |

| | | | | | |
|---|---|---|---|---|---|
| 3845 | All wire ropes used in shipboard cargo gears must be identified and described in a certificate. The certificate shall certify all of the following except the: | number of strands and wires in each strand | date of the test | load at which the test sample broke | name of the testing agency |
| 3846 | A Philippine registered cargo vessel below 500 grt engaged in international voyage requires which license for the rank of Master? | Recommending Officer | Chief Mate | Officer in charge | Master Mariner |
| 3847 | What is the meaning of "Harmful Substances" under Marpol? | Oils and Fuels | Hydrocarbons in any form | Petroleum products and petrochemicals | Any substances creating harm to health and life or able to damage amenities |
| 3848 | When ships are on short voyages, how often is the quantity residue recorded in the Machinery Space Oil Record Book? | Once a month | Twice a week | Once a week | Once every two weeks |
| 3849 | A vessel not having on board a document of authorization issued in accordance with part A3 of the International Grain Code may be permitted to load bulk grain provided that the total weight of the bulk grain shall not exceed: | One-third of the deadweight of the ship | One-half of the deadweight of the ship | One-fourth of the deadweight of the ship | One-fifth of the deadweight of the ship |
| 3850 | An article of transport equipment that is of a permanent character and accordingly strong enough to be suitable for repeated use without immediate reloading. | Container | Overpack | Freight container | Unit load |
| 3851 | Part of MLC 2006 will NOT be inspected by PSC inspectors? | Part A - Standards | Both Parts A and B | Part B - Guidelines | Either A or C |
| 3852 | Ships under Class C includes all: | Fishing vessel | Passenger ships | Cargo ships | Tankers |
| 3853 | Provisions is made for special rules made by the Government of any State with respect to the use of additional whistle signals between which of the listed? | ships sailing under convoy and ships of war | pilot vessels and vessels requiring pilots | None of the choices is correct | tugs and their tows |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 3854 | MARINA was geared towards the following objectives EXCEPT: | plays an important role to protect and enhance the environment for future genearations | to participate in marine pollution and promote the preservation of a good environment marine conservation | to create sub-agencies for the safe transport of goods and passengers | to increase production and productivity in the various islands and regions of the archipelago through the provision of linkage |
| 3855 | What is issued before port authorities and agents can board if you are arriving from a foreign port on international voyage? | police clearance | entry clearance | voyage clearance | free pratique |
| 3856 | According to the Code of Safe Practices for Ship's Carrying Timber Deck Cargoes, which of the following is not included in the term "Timber"? | wood pulp | cant | sawn wood | pulp wood |
| 3857 | Which is true to claims in respect of expenses reasonably incurred or sacrifices reasonably made by the owner voluntarily to prevent/minimize pollution damage? | shall rank equally with other claims against the fund | shall rank one third of the total amount claims | shall rank more than half of other claims against the fund | shall rank at least two thirds of other claims against the fund |
| 3858 | The periodic weight testing of a vessel's cargo booms may be performed by the: | National Cargo Bureau | Society of Naval Architects and Engineers | Classification society | U.S. Coast Guard |
| 3859 | The Garbage Record Book entries for each incineration or discharge shall include the date, time, position of the ship, description of garbage and the estimated _____. | amount incinerated | plastic included | time of arrival in port | speed of the ship |
| 3860 | Your vessel is boarded by the Quarantine Officer. After examination, your vessel was found to have a specific deficiency, therefore you may be issued with which of the following? | Stress out Pratique | Free Pratique | Controlled Free Pratique | Alternative Pratique |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 3861 | Under the Manila Amendments, the performance of a prospective officer in each of the tasks and duties itemized in the training record book should be initialed by: | the port surveyor | a qualified officer | the Master | company |
| 3862 | Under the International Convention for the Prevention of Pollution from Ships,1973, it means the government of the state whose authority the ship is operating. | Treaty | State | Administration | U.S. Coast Guard |
| 3863 | Which among these vessels are classified as category I in the inter-island trade? | vessels traveling with a maximum of 20 knots | vessels whose travel time between ports exceed 6 hours | vessels traveling with a maximium of 17 knots | vessels whose travel time between ports exceed 4 hours |
| 3864 | Thermal protective aids are required for what percentage of the persons a survival craft is equipped to carry? | 0.5 | 1 | 0.1 | 0.75 |
| 3865 | According to the Chemical Data Guide which extinguishing agent should be used on a petrolatum fire in an open area? | Monoxide powders | CO2 | Dry chemical | Foam |
| 3866 | At each initial and subsequent inspection for certification all carbon dioxide fire extinguishers aboard a vessel are _____. | sent ashore to an approved service facility | discharged and recharged | checked for pressure loss | weighed |
| 3867 | Fire protection and manning regulations for towing vessels state that the Master or person in charge must ensure that all crew members who have not participated in the drills or received the safety orientation _____. | receive a safety orientation or view a videotape before the vessel gets underway | receive a safety orientation within 24 hours of reporting for duty | none of the above | view a videotape on safety procedures within 48 hours of reporting for duty |
| 3868 | If you carry packaged hazardous cargoes on a break bulk vessel bound foreign you must _____. | have the shipping papers indicate the proper shipping name and the technical name of n.o.s. cargoes | remove the hazardous cargo labels from a portable tank after the tank is emptied | stow the hazardous cargoes on deck available for jettisoning if necessary | log the receipt of hazardous cargoes in the Official Logbook |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 3869 | On a vessel making a voyage more than 48 hours long regulations require that _____. | the entire steering gear be tested within 12 hours prior to departure | a lifeboat drill be held within 12 hours prior to departure | fire pumps be tested by starting within 12 hours prior to departure | the emergency generator and lighting system be tested by starting and operating within 12 hours prior to departure |
| 3870 | Records of tests and inspections of a cargo vessel s fire extinguishing systems shall be kept on board _____. | until the next Coast Guard inspection | for 1 year | until the vessel s Certificate of Inspection expires | for 2 years |
| 3871 | SOLAS requires a lifesaving training manual be provided in each crew cabin or in the _____. | bridge | engineering control station | fire control room | recreation and messrooms |
| 3872 | The Master of a vessel must conduct sufficient drills and give sufficient instruction as necessary _____. | To ensure that all crew members are familiar with their duties during emergencies | Every month | At each crew change | Every week |
| 3873 | Under normal weather and sea conditions when securing a stack of containers with non-locking fittings lashings are required when the tier exceeds what height? | Three containers | Lashings are always required | One container | Two containers |
| 3874 | Under the federal regulations what minimum level of Blood Alcohol Content (BAC) constitutes a violation of the laws prohibiting Boating Under the Influence of Alcohol (BUI) on commercial vessels? | .18% BAC | .06% BAC | .10% BAC | .04% BAC |
| 3875 | What is a requirement for remote manual shutdown stations for internal combustion engine driven cargo pumps on tank barges? | The valve rods shall be fitted with stuffing boxes. | There must be at least two such shutdown devices. | They must be conspicuously marked. | They must be located at least 10 feet from the engine. |
| 3876 | What is the minimum diameter allowed for bilge piping on small passenger vessels which are more than 65 feet in length? | 2-1/2 | 2 | 1 | 1/1/2002 |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 3877 | Which cargoes require strips of common building lathe as dunnage in order to carry away heat generated by the cargo? | Cardboard cartons of shoes | Canned soups packaged in crates | Paper products packaged in rolls | Refrigerated fruit that is ripening |
| 3878 | Which of the signals listed is required to be displayed during the day while bunkering? | A red and yellow flag | A red light | A red flag | A yellow flag |
| 3879 | You are requisitioning stores for your tank vessel. What type of matches are permitted aboard? | Phosphorous | Safety | Self-extinguishing | Wooden |
| 3880 | You have been carrying a liquid with flammable limits of 1% to 7% mixture with air. If your instructions say that no one shall enter the tank if the vapor concentration is over 15% of the LEL what is the maximum allowable percentage of vapors for men to enter? | 0.0015 | 0.0085 | 0.07 | 0.0105 |
| 3881 | A reinspection of the vessel shall be made between which of the following months while the Certificate of Inspection is valid? | 8 - 12 months | 10 - 12 months | 10 - 14 months | 12 - 14 months |
| 3882 | All lifeboats rescue boats and rigid-type liferafts shall be stripped cleaned and thoroughly overhauled at least once every _____. | year | 6 months | 18 months | two years |
| 3883 | For well control the American Petroleum Institute recommends that hydraulic units have sufficient horsepower to close the annular preventer in _____. | 15 seconds | 45 seconds | 60 seconds | 30 seconds |
| 3884 | Inflatable liferafts on vessels on an international voyage must be able to carry at least _____. | 4 persons | 8 persons | 2 persons | 6 persons |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 3885 | Regulations require that cargo pumps in tank vessels carrying grade D liquid cargo shall be isolated from sources of vapor ignition by _____. | cofferdams | gastight bulkheads | general cargo spaces | passageways or living quarters |
| 3886 | The document which shows a vessel s nationality ownership and tonnage is the _____. | Manifest Certificate | Certificate of Documentation | Bill of Lading Certificate | Official Logbook |
| 3887 | The supplement to the IOPP Certificate contains what type of data? | A list of the underwriters who will assume financial responsibility in the event of an oil spill. | A checklist of the equipment installed for controlling the discharge of oil. | The trade routes upon which the vessel may operate. | The grades of cargo that an oil tanker is permitted to carry. |
| 3888 | UNCLOS required that all flag states take account or give effect to;or implement the relevant rules and standards developed by the _____? | Baltic International Maritime Corporation (BIMCO) | Marintime Inquiry | International Shipping Company | International Maritime Organization (IMO) |
| 3889 | What is the period of validity of a Safety Management Certificate? | 36 months | 42 months | 60 months | 48 months |
| 3890 | A cargo information card does NOT contain _____. | appearance and odor characteristics of the cargo | duties of the person in charge during the transfer of cargo | precautions to be observed in case of a spill or leak | instructions for the safe handling of the cargo |
| 3891 | A drill must be conducted in the use of the line throwing appliance at least once in every _____. | 2 months | 4 months | 3 months | 5 months |
| 3892 | A gas-free certificate would usually be issued by a(n) _____. | ABS marine surveyor | certified marine chemist | Coast Guard marine inspector | port engineer |
| 3893 | A periodic thorough examination of the cargo gear proves satisfactory. What percentage of the total gear must be dismantled to determine actual internal condition? | 0.5 | 0.1 | 1 | 0.25 |
| 3894 | According to the Chemical Data Guide which material is not compatible with vinylidene chloride (inhibited)? | Copper or copper alloys | Nickel | Stainless steel | Aluminum |

| | | | | | |
|---|---|---|---|---|---|
| 3895 | According to the regulations the capacity of a liferaft is required to be marked _____. | on the Muster List ( Station Bill ) | on the Certificate of Inspection | in the Operations Manual | at the liferaft stowage location |
| 3896 | According to the regulations what fire safety control feature is required in quick-closing shut off valves? | Manual cut off switch | A fusible link | Electrical cut off switch | A water spray actuator |
| 3897 | After 1 September 1992 in the North Pacific area a documented 75-foot fishing vessel operating in cold waters 25 miles off the coast must have at least a(n) _____. | buoyant cushion for each person on board | inflatable buoyant apparatus with EPIRB attached | inflatable liferaft with a SOLAS pack | approved rescue boat |
| 3898 | All life jackets carried on board small passenger vessels are required to be marked _____. | with the maximum serviceable life of the life preserver | with the maximum weight to be held by the life preserver | with the vessel s official number | with the vessel s name |
| 3899 | All vessels not required to have a power driven fire pump shall carry _____. | not less than three hand fire pumps | an emergency hand fire and bilge pump | at least three 2-1/2 gallon fire buckets | a suitable detachable pump usable for fire fighting purposes |
| 3900 | All wire rope used in shipboard cargo gear must be identified and described in a certificate. The certificate shall certify all of the following EXCEPT the _____. | load at which a test sample broke | number of strands and of wires in each strand | date of the test | name of the vessel |
| 3901 | An accommodation ladder or other equally safe and convenient means must be provided for a pilot whenever the distance from the sea level is more than _____. | 20 feet | 50 feet | 40 feet | 30 feet |
| 3902 | An on-board monitoring system using level sensors permanently installed in each vessel compartment will have a high level alarm set at not more than _____. | 95% of compartment capacity | 90% of compartment capacity | 99% of compartment capacity | 97% of compartment capacity |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 3903 | At least one reinspection shall be made on each vessel holding a Certificate of Inspection valid for two years. This inspection shall be held between the tenth and fourteenth months of the duration period of the certificate and shall be _____. | at the discretion of the inspector but in no greater detail than required for original certification | generally similar in scope to the inspection required for certification but in less detail | equivalent to the inspection required for certification | at the discretion of the inspector but in no lesser detail than required for original certification |
| 3904 | Cargo hose carried on tank vessels must be designed to withstand the pressure of the shutoff head of the cargo pump or pump relief valve setting but in no case should it be less than _____. | 150 psi | 200 psi | 250 psi | 100 psi |
| 3905 | Cargo vessels being navigated and fitted with emergency lighting and power systems shall have their emergency systems tested at least once _____. | in each week | in every 6 months | in every 12 months | a month |
| 3906 | Each fire pump on a tankship must have a pressure gauge located at _____. | the manifold connection | the pump discharge | the pump station | each fire station discharge |
| 3907 | Fire hose stations shall be marked in red letters and figures such as Fire Station No. 1 2 3 etc. The height of the letters and figures must be at least _____. | 1/2 inch | 2 inches | 1-1/2 inches | 1 inch |
| 3908 | Fire protection regulations for towing vessels require any fuel line subject to internal head pressure from fuel in the tank to _____. | be fitted with a positive fuel shut-off valve located at the tank | have a shut-off valve at the top of the tank | have a gate valve easily accessible in the space where the tank is located | have a drain cock at the lowest point in the fuel line |
| 3909 | For each person it is certified to carry a lifeboat on an oceangoing passenger vessel must be provided with all of the following EXCEPT _____. | 1 life preserver | 1 seasickness kit | 1 unit of provisions | 3 liters of water |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 3910 | Gasoline tank vent lines on board small passenger vessels must be fitted with removable flame screens _____. | three inches in diameter with a check valve to prevent water from entering in heavy weather | three inches in circumference inside the fill pipe | and 30 square inches of louvers | consisting of a single screen of at least 30 X 30 mesh corrosion resistant wire |
| 3911 | How many low-velocity spray applicators are required on the weather decks of a tankship? | | Two | Four | Three |
| 3912 | If it is impractical to use the fill line to sound the fuel tank then the tank should be fitted with _____. | | a separate sounding tube or an installed marine type fuel gauge | A glass tube to visually observe the fuel | A good air vent of sufficient diameter |
| 3913 | Under the federal regulations, what minimum level of Blood Alcohol Content (BAC) constitutes a violation of the laws prohibiting Boating Under the Influence of Alcohol (BUI) on commercial vessels? | .04% BAC | | .10% BAC | .06% BAC |
| 3914 | A vessel arrives in a foreign port and the Master is informed that the vessel is being sold to foreign interests. The new owners request that the crew remain on board to complete the voyage. Under these circumstances, the crew _____. | must remain aboard until the vessel is delivered to the new owners at a mutually agreed upon port | must remain on board | must comply with the decision made by the Master | has the right to an immediate discharge and transportation to original port of engagement |
| 3915 | If there are any changes in the crew in a foreign port, the changes will be made by _____. | U.S. Consul on the Certified Crew List | | the Master on the Shipping Articles | U.S. Consul on the Shipping Articles |
| 3916 | The Shipping Articles shall be signed by each seaman and the _____. | | Master of the vessel | U.S. Customs Service | Shipping Commissioner |
| 3917 | Shipping articles are a contract of agreement between the members of the crew and the _____. | Coast Guard | Vessels owner | Master | Charterers |
| 3918 | The strictest load line regulations apply to _____. | passenger ships | gas carriers | | tankers |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 3919 | A tonnage tax is levied according to the _____. | net tonnage of vessel | | deadweight cargo tonnage aboard | displacement tonnage of vessel |
| 3920 | You are on a containership carrying a tank container that had been filled with sodium hydroxide solution. The container is empty but has not been cleaned. Which, if any, placard is required? | No placard is required; the tank openings must be sealed | Black and white corrosive placard | Empty placard with corrosive placard | Residue label with the UN number |
| 3921 | An International Tonnage Certificate will be issued to a vessel when it meets several requirements, one of which is that the vessel must _____. | admeasure over 100 GT | be issued a Certificate of Inspection | be 79 or more feet in length | engage in intercoastal or international trade |
| 3922 | Which agency is authorized to assist the Coast Guard in the inspection of vessels for the suitability of loading hazardous materials? | National Cargo Bureau, Inc. | U.S. Navy explosive loading details | Environmental Protection Agency | American Bureau of Shipping |
| 3923 | According to SOLAS requirement for lifeboat fall, what action must be taken with the fall at interval of not more than 5 years? | Renewed | Proof tested | weight tested | reverse |
| 3924 | Due to the nature of a vessels construction for a particular trade, it does not fully comply with the provisions of SOLAS. Where will this be indicated? | On the Exemption Certificate | On the face of the Certificate of Inspection | Nowhere; the vessel must comply to engage in international trade. | On the reverse of the particular SOLAS certificate affected |
| 3925 | Which one of the listed requirements regarding abandon ship drills corresponds to present SOLAS regulation? | Each lifeboat shall be launched with its assigned crew, and maneuvered in the water at least once every three months during an abandon ship drill. | Drills shall be conducted when the ship is in a harbour. | On ships on short international voyages, each lifeboat shall be launched and maneuvered in the water at least every six months. | All lifeboats shall be lowered during drills. |
| 3926 | As per SOLAS Regulation, the minimum Fuel supply for fast Rescue Boat shall last for__. | 12 hours | 4 hours | 8 hours | 16 hours |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 3927 | As per SOLAS Regulation, the capacity rate of ships emergency fire pumps shall be ____. | 75 cu.m./hour | 25 cu.m./hour | 50 cu.m./hour | 30 cu.m./hour |
| 3928 | In case each hydrant is not fitted with hose and nozzles, what is the requirement? (SOLAS II-2/4.6.1) | At each fire station, sufficient number of hoses with nozzles for the hydrants in the area shall be available | Complete interchangeability of hose couplings and nozzles | Hoses with fixed nozzles to be kept ready for use in conspicuous positions near the hydrants | Hoses and nozzles for each hydrant to be available at the fire stations |
| 3929 | SOLAS stipulates that ships of 500 GRT or more shall have at least one international shore connection with an outside diameter of____ | 174 mm | 172 mm | 178 mm | 176 mm |
| 3930 | What percentage of crew change would require a lifeboat drill to be held within 24 hours of sailing? | 40% | 50% | 25% | 75% |
| 3931 | As per SOLAS, fire pumps shall have a capacity to deliver at least_____. | 25 m3/hour | 50 m3/hour | 75 m3/hour | 100 m3/hour |
| 3932 | All lifeboats, rescue boats, and rigid-type liferafts shall be stripped, cleaned, and thoroughly overhauled at least once every _____. | two years | 18 months | year | 30 months |
| 3933 | The ISM Code requires ship owners or shipping companies to assign a _____ onboard their ship: | Welfare Committee | Safety Committee | Overseeing Committee | Logistics Committee |
| 3934 | ISPS Code was formulated as a result of what incident | 9/11 bombing of World Trade Center | Agreed upon by IMO member countries to address safety issues | Sinking of RMS Titanic | Grounding of Exxon Valdez |
| 3935 | A CSO is designated by the _____. | Company Operating the ship | ISPS Code | ISM Code | Ship Security Officer |
| 3936 | The ISPS Code applies to: I. Passenger ships II. Mobile offshore drilling units (MODU) | Neither I or II | Both I and II | I only | II only |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 3937 | One of the many objectives of the _____ is to ensure the early and efficient collection and exchange of security-related information. | Code of Safe Practice for the Handling of Cargo | STCW Code | FTP Code | ISPS Code |
| 3938 | At what security level is further specific protective security measures to be maintained for a limited period of time when a security incident is probable or imminent, although it may not be possible to identify the specific target? | Security level 3 | Security level 4 | Security level 2 | Security level 1 |
| 3939 | Under the New Regulations, what does SOLAS Chapter XI-1 deals with? | Additional provisions to combat Terrorism | Special measures to enhance Maritime Safety | Special provisions for Ship Security and Port Facilities | Security planning and Ship and Port Facility |
| 3940 | An SSO is designated by the_____. | Port Manager | Company operating the ship | Master of the Ship | Contracting Government |
| 3941 | Which ships does the ISM code apply to | All craft above 300GRT | Only tankers and Ro-ros | Only passenger vessels | All passenger ships, all cargo ships of 500GRT or above |
| 3942 | To ensure the early and efficient collection and exchange of security-related information is one of the many objectives of the? | STCW Code | FTP Code | ISPS Code | Code of Safe for the Handling of Cargo |
| 3943 | Under the New Regulations, what does SOLAS Chapter XI-2 deals with? | Additional provisions to combat Terrorism | Special provisions for the safety of the passengers | Special measures to enhance Maritime Security | Safety measures regarding Ship routing to avoid pirates |
| 3944 | The Oil Record Book on a vessel NOT engaged on a foreign voyage shall be maintained on board for not less than _____. | 24 months | 48 months | 12 months | 36 months |
| 3945 | An IOPP Certificate on an inspected vessel is valid for what period of time? | 2 years | 5 years | 6 months | 1 year |
| 3946 | Oily mixtures according to Marpol means: | a mixture with oil content above 50 ppm | a mixture with oil content above 15 ppm | a mixture with any oil content | a mixture with oil content above 100 ppm |
| 3947 | Sludge are to be disposed off at sea | 50 miles offshore | disposal prohibited | 25 miles offshore | during darkness only |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 3948 | Annex V of MARPOL 73/78 contains requirements pertaining to the discharge into the marine environment of: | Sewage | Garbage | Noxious liquid substances | Oil |
| 3949 | MEPC as referred to in the MARPOL Convention stands for: | Marine Environment Protection Control | Marine Environment Pollution Control | Marine Environment Protocol Committee | Marine Environment Protection Committee |
| 3950 | _____ must counter sign any completed pages of the Oil Record Book. | Designated Officer | Master | Chief Engineer | Master and Chief Engineer |
| 3951 | When oil is discharged overboard, an entry is required in the _____. | Oil Record Book | engine rough log | Official Logbook | deck rough log |
| 3952 | When oily ballast has been pumped overboard, an entry must be made in the _____. | Oil Record Book | Official Logbook | engine rough log | deck rough log |
| 3953 | ____ is contained in Annex II of MARPOL 73/78? | Regulations for the Prevention of Pollution by Sewage | Regulations for the Prevention of Pollution by Harmful Substances in a Packaged Form | Regulations for the Control of Pollution by Noxious Liquid Substances | Regulations for the Prevention of Pollution by Oil |
| 3954 | Oil discharge in large quantities form _____ which will affect birds at sea and may strand on beaches if these do not disperse into the water as water droplets before reaching shore: | spills | emulsions | patches | slicks |
| 3955 | Which vessel greater than 100 GT is NOT required to have an EPIRB. | A non self-propelled vessel in tow | A towing vessel | A fishing vessel | A sailing vessel |
| 3956 | Recruitment, training and development of organization members is _____ | staffing | organizational development | human resource management | organizing |
| 3957 | Which of the following would fit MOST on motivation? | factor that cause, channel and sustain people's behavior | that special inner desire to excel | efforts at keeping employees "cheered up" at all times | managerial strategies to inspire the working force |
| 3958 | This is the most effective management development technique. | Coaching | Training | Modeling | Irritation |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 3959 | The routes, zones or areas of operations of domestic ship operators are prescribed by which government agency? | MARINA | Office of the President of the Philippines | PCG | DOTC |
| 3960 | MARINA was created and geared towards the following objectives EXCEPT: | To provide for economical, safe, adequate and efficient shipment of raw materials, products, commodities and people | To create sub-agencies for the safe transport of goods and passengers | To increase production and productivity in the various islands and regions of the archipelago through the provision of linkage | To create more job opportunities |
| 3961 | Watchkeepers should have a mandatory rest periods of _____ in any one week. | 70 hours | 56 hours | 48 hours | 72 hours |
| 3962 | Managerial performance is based upon accomplishment of _____. | responsibilities | choices | duties | objectives |
| 3963 | In bridge resource management, which of the following statements are example of "hazardous thoughts" I.) I can do it II.) It won't happen to me III.) Why takes chances IV.) it's not my job V.) Don't tell me what to do VI.) We're all in the same ship | I, II, IV, V | IV, V, VI | I,II,III | I, II, III, IV, V |
| 3964 | Welding and burning are among the factors which give the highest risk of fire on board ships. Precaution has to be taken to avoid this risk. Which of the following safety rules may be regarded as the most important? | Only holders of welding certificates shall be allowed to carry out welding on board ships. | Only use electrodes from a well-known manufacturer. | Electric welding plants shall be controlled by a responsible engineer before use. | The welder shall have been instructed in the use of the ship's welding plant. |
| 3965 | VDR must be carried to assist in accident investigation on board passenger ships and ships other than passenger ships of how many gross tons? | 1,500 GT | 3,000 GT | 1,000 GT | 2,000 GT |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 3966 | Drills ought to be conducted in a realistic manner against imaginary and realistic situation every: | 15 days | three months | month | two weeks |
| 3967 | When officers from the Emergency Organization of a ship are changed the Emergency Organization should be mustered as soon as possible and definitely: | before the ship leaves port | a week after leaving port | a day after the ship leaves port | when the pilot disembark the ship |
| 3968 | Response by the ship's complement to an emergency situation is entirely dependent on the _____ of officers and crew. | knowledge | capability | level of training | ability |
| 3969 | It is defined as an undesired event that causes or has the potential to cause harm to people, damage to property and loss to an operation. | Accident | Near miss | Dangerous occurrence | Incident |
| 3970 | An incident that could have caused the death, serious injury or incapacity of a person, but which did not have that outcome. | Accident | Incident | Near miss | Dangerous occurrence |
| 3971 | An aircraft requests a vessels to change course and proceed towards a vessel in distress. The actions of the aircraft to convey this message will NOT include: | flashing the navigation lights on and off | none of the choices | advise the vessel to give a smoke signal | heading in the direction of the distress location |
| 3972 | Which of the following must be exhibited throughout the ship including the navigation bridge, engine room and crew accommodation spaces? | Muster lists | Posters of signs for the operating instructions of the survival craft | Individual Watch List | Bridge Watch List |
| 3973 | Rescue vessel approaches a lifeboat in heavy seas, the person in charge of the lifeboat should: | brought bow into the sea | brought to a position with stern into the sea | transfer only those personnel who are not seasick | transfer all personnel immediately |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 3974 | Administration shall ensure that qualified seafarers are issued with this certificate upon completion specialized trainings. | Certificate of competency | Certificate of compliance | Certificate of documentation | Certificate of proficiency |
| 3975 | Seafarers shall receive safety familiarization and basic training or instruction, where basic training is not included in the qualification for the certificate to be issued, this certificate will be issued instead _____. | Certificate of competency | Certificate of documentation | Certificate of compliance | Certificate of proficiency |
| 3976 | Orange colored smoke signal or this luminous signal fired at interval of one minute means _____. | we see you, we will provide help as soon as possible | come over and let us have a quick conversation | there are many sharks surrounding the vessel | to embark here is dangerous |
| 3977 | An accurate perception of the operational and environmental conditions affecting the vessel during a specific period of time is called _____. | communication | situational awareness | teamwork | workload management |
| 3978 | Masters, chief engineer officers, chief mates, second engineer officers and every person assigned immediate responsibility for embarking and disembarking passengers, loading, discharging or securing cargo, or closing hull openings on board ro-ro passenger ships shall have _____. | completed training in basic safety | completed approved training in passenger safety, cargo safety and hull integrity | completed in crisis management and human behavior | completed training in crowd management |
| 3979 | Masters, chief engineer officers, chief mates, second engineer officers and any person designated on muster lists of having responsibility for the safety of passengers in emergency situations shall have _____. | completed in crisis management and human behavior | completed training in basic safety | completed training in crowd management | advanced training in fast rescue boat |
| 3980 | Drill required by regulations is not completed, the Master or person in charge must: | accomplish the drill at any reason to complete the drill | conduct another drill the next day | conduct two of the required drills at the next opportunity | log the reason for not completing the drill |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 3981 | What is the most effective management development technique? | Coordination | Talking with Subordinates | Coaching | Communications |
| 3982 | Emergency Organization of a ship selected from the suitable officers and ratings. | Deck Squad | emergency squad | first aid squad | engine squad |
| 3983 | VDR must be carried to assist in accident investigation on board passenger ships and ships other than passenger ships of how many gross tons? | 2,000 GT | 1,000 GT | 3,000 GT | 1,500 GT |
| 3984 | Drills ought to be conducted in a realistic manner against imaginary and realistic situation every: | 15 days | two weeks | month | three months |
| 3985 | When officers from the Emergency Organization of a ship are changed the Emergency Organization should be mustered as soon as possible and definitely: | a day after the ship leaves port | a week after leaving port | when the pilot disembark the ship | before the ship leaves port |
| 3986 | Response by the ship's complement to an emergency situation is entirely dependent on the _____ of officers and crew. | capability | level of training | ability | knowledge |
| 3987 | It is defined as an undesired event that causes or has the potential to cause harm to people, damage to property and loss to an operation. | Dangerous occurrence | Accident | Incident | Near miss |
| 3988 | An incident that could have caused the death, serious injury or incapacity of a person, but which did not have that outcome. | Near miss | Dangerous occurrence | Incident | Accident |
| 3989 | An aircraft requests a vessels to change course and proceed towards a vessel in distress. The actions of the aircraft to convey this message will NOT include: | none of the choices | advise the vessel to give a smoke signal | heading in the direction of the distress location | flashing the navigation lights on and off |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 3990 | Which of the following must be exhibited throughout the ship including the navigation bridge, engine room and crew accommodation spaces? | Muster lists | Individual Watch List | Posters of signs for the operating instructions of the survival craft | Bridge Watch List |
| 3991 | Rescue vessel approaches a lifeboat in heavy seas, the person in charge of the lifeboat should: | brought to a position with stern into the sea | transfer all personnel immediately | brought bow into the sea | transfer only those personnel who are not seasick |
| 3992 | Administration shall ensure that qualified seafarers are issued with this certificate upon completion specialized trainings. | Certificate of competency | Certificate of compliance | Certificate of proficiency | Certificate of documentation |
| 3993 | Seafarers shall receive safety familiarization and basic training or instruction, where basic training is not included in the qualification for the certificate to be issued, this certificate will be issued instead _____. | Certificate of compliance | Certificate of proficiency | Certificate of competency | Certificate of documentation |
| 3994 | Orange colored smoke signal or this luminous signal fired at interval of one minute means _____. | come over and let us have a quick conversation | there are many sharks surrounding the vessel | to embark here is dangerous | we see you, we will provide help as soon as possible |
| 3995 | An accurate perception of the operational and environmental conditions affecting the vessel during a specific period of time is called _____. | situational awareness | teamwork | communication | workload management |
| 3996 | Masters, chief engineer officers, chief mates, second engineer officers and every person assigned immediate responsibility for embarking and disembarking passengers, loading, discharging or securing cargo, or closing hull openings on board ro-ro passenger ships shall have _____. | completed approved training in passenger safety, cargo safety and hull integrity | completed in crisis management and human behavior | completed training in crowd management | completed training in basic safety |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 3997 | Masters, chief engineer officers, chief mates, second engineer officers and any person designated on muster lists of having responsibility for the safety of passengers in emergency situations shall have _____. | completed training in crowd management | advanced training in fast rescue boat | completed in crisis management and human behavior | completed training in basic safety |
| 3998 | Drill required by regulations is not completed, the Master or person in charge must: | log the reason for not completing the drill | accomplish the drill at any reason to complete the drill | conduct another drill the next day | conduct two of the required drills at the next opportunity |
| 3999 | What is the most effective management development technique? | Communications | Coordination | Coaching | Talking with Subordinates |
| 4000 | Emergency Organization of a ship selected from the suitable officers and ratings. | Deck Squad | first aid squad | engine squad | emergency squad |
| 4001 | Picking up a person that has fallen onboard. A small craft should approach the victim: | to windward | with a net | to leeward | directly |
| 4002 | Line throwing equipment be demonstrated to the crew of a well run ships? | every three months | Every week | Every fridays | last week of the month |
| 4003 | Condition which are considered general emergencies are many and varied and may include the following except: | man overboard | helicopter ditching in the harbor | fire emergency | oil spill |
| 4004 | A detailed plan designed to implement the ideals and intentions expressed in the safety policy. | Fire plan | Safety policy | Safety plan | Safety program |
| 4005 | How many two-way VHF radiotelephone are required on passenger ships and every cargo ship of 500GT and over? | three | two | five | four |
| 4006 | When transferring survivors from survival craft to rescue vessel, personnel on board the craft should: | climb on top of the survival craft while waiting for their turn to transfer to the rescue vessels | remain seated inside the survival craft and make the transfer one person at a time | rush inside the craft as soon as possible to have an immidiate preparedness to any sea danger | gather at the center of the craft to store the warmth of every person and make a good compactness |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 4007 | Who are covered by the enforcement of rest periods under fitness for duty regulation of STCW? I. those whose duties involve designated safety II. those whose duties involve designated security III. those whose duties involve designated pollution prevention | II and III | I and II | I, II and III | I and III |
| 4008 | The abilities specified in the standards of competence are grouped, as appropriate, under the following seven functions which are composed of the following _____. I. Marine engineering II. Electrical, electronic and control engineering III. Maintenance and repair | I and II | II and III | I and III | I, II and III |
| 4009 | The objective of "code of safe working practices" is to provide practical guidance on health and safety in shipboard work with a view to: I. preventing accidents, diseases and other harmful effects II. ensuring that the responsibility for health and safety is understood and remains a priority III. promoting consultation and cooperation among government agencies, shipowner organisations and maritime unions | I, II, III | II, III | I, II | I, III |
| 4010 | An incident is defined as an undesired event that causes or has the potential to cause: I. harm to people II. damage to property III. loss to an operation; | II, III | I, II | I, III | I, II, III |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 4011 | Every candidate for a certificate in advanced training for liquefied gas tanker cargo operations shall _____. I. meet the requirements for certification in basic training for liquefied gas tanker cargo operations II. at least six months of approved seagoing service on liquefied gas tankers III. at least one month of approved onboard training on liquefied gas tankers, in a supernumerary capacity | I and III | I, II and III | II and III | I and II |
| 4012 | Rest periods is strictly implemented to avoid fatigue and be fit for duty, this regulation covers those who are _____. I. watchkeeping personnel II. designated in safety duties III. assigned in heavy strenuous jobs | I and III | I, II and III | I and II | II and III |
| 4013 | The abilities specified in the standards of competence are grouped, as appropriate, under the following seven functions which are composed of the following _____. I. Navigation II. Radio communications III. Emergency operations | I and II | I and III | II and III | I, II and III |
| 4014 | You are on watch and the Pilot has the conn. The Master has temporarily gone below. The Pilot orders a course change which you are certain will put the vessel into imminent danger. Your first action should be to: | make an appropriate entry in the deck log concerning the Pilot's order | countermand the order and immediately notify the Master | immediately call the Master and await further orders from him | immediately sound a short ring on the general alarm |
| 4015 | An incident that causes the death, serious injury or incapacity of a person. | Incident | Accident | Near miss | Dangerous occurrence |
| 4016 | The most important element in Bridge Resource Management is _____. | Strong Leadership | Teamwork | Plenty of Communication | Instrument manipulation |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 4017 | Operating managers would suffer anxiety from which of the following whenever an organization implements MIS? | barring to operate the system | loss of control of information | knowledge of the innformation system | misinterpretatio n of information |
| 4018 | The cranes on a LASH type vessel are a part of the light ship. Therefore, when securing for sea, they must be _____? | jacked off their bearings and stowed in a specific location | lashed and chocked in any convenient location | chocked in place ready for use at next port | secured over the cargo to be handled at the next port |
| 4019 | The shipboard organization consists of different levels. Which of these is NOT included? | Engineering level | Level of inconvinience | Support Level | Deck Department Level |
| 4020 | To bring together in one department all those engaged in one related activities, the basic principle of organization by _____ is used. | planning | function | market | management |
| 4021 | It is called the arrangement or responsibilities, authorities and relationship between people? | Management Chart | Task management | Management Organization | Organization structure |
| 4022 | Who shall establish and enforce rules of rest periods for watchkeeping personnel to avoid fatigue? | Coast Guard | Company | Administration | Master |
| 4023 | Chapter VI of the STCW code is concerned with _____. | Emergency, occupational safety, security, medical care and survival functions | Master and deck department | Radio communication and radio operators | Special training requirements for personnel on certain types of ships |
| 4024 | The Night Order Book consist of the following EXCEPT: | Colreg adherence | Maximum speed allowed | Calling the master | Correction to publications |
| 4025 | Emergency station bill indicating the names of the individuals and their assignments during emergencies should be posted in the Navigation Bridge and the following areas. which should not be included: | mess room | engine room control | off the gangway | individual cabin |
| 4026 | Which one is not in the list standards of competence which has seven functions? | Cargo handling and stowage | Emergency operations | Navigation | Radio communications |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 4027 | Where the emergency source of power is a generator, it shall have independent supply of fuel having a flashpoint of: | not more than 35 deg. Celcius | not less than 43 deg. Celsius | not more than 43 deg. Celsius | not less than 35 deg. Celcius |
| 4028 | What performance would a trainee exhibit when assessment takes place at end of the training program? | Enabling Objective | Ultimate Performing Objective | Performance Objective | Training Performance Objective |
| 4029 | What strategy or methods to be used in the conduct of training on board, is one of the items to be considered when_____ a formal training session. | Delivering the course outline | Preparing for | Planning | Informing the trainees for |
| 4030 | A written document produced by a shipowner indicating in broad terms its commitment, aims and objectives in relation to shipboard safety. | Safety policy | Safety Quality syatem | Safety program | Quality System |
| 4031 | The Night Order Book issued by the Master should be _____ by the officer in-charge of navigation watch the time he report to the bridge to undertake the watch. | Comply | Acknowledge and comply | Signed | Read |
| 4032 | In writing up the logbook at the end of your watch, you make an error in writing an entry. What is the proper means of correcting this error? | Blot out the error completely and rewrite the entry correctly. | Remove this page of the log book, and rewrite all entries on a clean page. | Cross out the error with a single line, and write the correct entry, then initial it. | Carefully and neatly erase the entry and rewrite it correctly. |
| 4033 | Emergency team is in charge of the engine room and is responsible for maintaining normal and emergency services. | one man team | reserve team | back-up team | support control team |
| 4034 | You hear the message "Seelonce Feenee" over the radiotelephone. What action should you take? | Do not transmit over the radiotelephone | Resume voyage as the distress situation is already over | transmit over the radiotelephone until distress situation is over | Resume base course and speed because the distress situation is over |
| 4035 | Emergency Training and Drills, which of the following is required whenever new passengers embark? | safety briefing immediately before sailing | safety briefing before the vessel arriving to the next port | safety briefing before or immediately after sailing | safety briefing after the vessel departs from the next port |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 4036 | The use of alternative certificates is not intended to _____. | justify the assignment of the combined duties of the engine and deck watchkeeping officers to a single certificate holder | save time for seafarers on training | lower the cost of training | upgrade the skill of seafarers |
| 4037 | What is the first step in planning? | Select goals for the ships organization | Set rules and procedures | Set up guidelines for ships organization | Set time limit |
| 4038 | Masters, officers and other personnel designated on muster lists to assist passengers in emergency situations on board passenger ships shall have _____. | specialized training in lifeboat operation | completed training in basic safety | advanced training in fast rescue boat | completed training in crowd management |
| 4039 | The level of proficiency to be achieved for the proper performance of functions on board ship incorporating prescribed standards or levels of knowledge, understanding and demonstrated skill. | Standard of competence | Standard of proficiency | Competency | Evaluation criteria |
| 4040 | An evaluation by qualified persons, independent of, or external to, the unit or activity being evaluated, to verify that the administrative and operational procedures at all levels are managed, organized, undertaken and monitored. | Evaluation criteria | Standard of proficiency | Standard of competence | Independent evaluation |
| 4041 | One of the most important innovations in the 1972 Regulations (COLREG) was the recognition given to traffic separation schemes. Under Rule 10 of this Regulation states that in so far as practicable, a vessel must avoid: | maneuvering while inside traffic lanes | crossing traffic lanes | stopping in the traffic lanes | none of these choices |
| 4042 | A person having the relevant training and skills and, if appropriate, qualifications, to perform particular tasks. | Competent person | Designated Person | Superintendent | Master |

NOT FOR SALE

# OIC NAVIGATIONAL WATCH

| | | | | | |
|---|---|---|---|---|---|
| 4043 | Emergency team may be needed to provide support by carrying additional equipment to the fist team. | reserve team | back-up team | support team | emergency team |
| 4044 | The CSS in a SAR situation should display by day: | The code flags FR | Three black balls in a vertical position | A black ball over a black diamond shape | The code flag T |
| 4045 | On-scene communication in the vicinity of distress should be under the control of whom? | On-scene Commander | the U.S. Coast Guard | the Master of the ship in distress | the Company of the vessel in distress |
| 4046 | Passenger vessel must have an emergency squad when: | the size of the crew permits | leas than 50 passenger are onboard | there is a doctor onboard | more than 50 passengers are on board |
| 4047 | In an employer-employee relationship. It often deals with consideration of the: | time and effort to progressive work | efficiency and effectiveness of work | managers interacting with employees | emotion between employer and employee |
| 4048 | Rescue operation in heavy sea, you decide to hove to, the lifeboat should be: | brought to a position with stern into the sea | brought bow into the sea | transfer only those personnel who are not seasick | transfer all personnel immediately |
| 4049 | Which of the following is in the list standards of competence which has seven functions? | Watch keeping for Engine room | Emergency operations | Watch keeping for Navigation | Cargo handling and stowage |
| 4050 | "hot work" means: | Works done even without any outfit requiered | Welding or cutting with a torch | When a tank temperature goes above 45 degrees C or 113 degrees F | Work done on a very hot temperature and hot weather |
| 4051 | "cold work" is defined as: | Works on a very cold temperature and cold weather | When the temperature drops below freezing | Work done with winter outfit for frost bite tendency | Work that can cause sparks when using a hammer/scrapper or other such tools |
| 4052 | Permit to work is? | Preffered working place before starting a job order | Working time given by the Chief Officer | Work orders from the senior officers | A complete check on preparedness prior to start of work |
| 4053 | You are in the confined waters. What is the danger in this situation if you should loose engine power? | You will drift to port but rather quickly with possible consequence of grounding | You will drift to port but rather slowly | You will sheer to port | You will loose headway, but there should be no immediate danger |
| 4054 | Every entry required to be made in the Official Logbook shall be signed by the _____. | Master and Chief Mate or other member of the crew | Mate on watch | Purser one of the Mates and some other member of the crew | Master only |

# OIC NAVIGATIONAL WATCH

| | | | | | |
|---|---|---|---|---|---|
| 4055 | Which party must ensure that legal work hour limitations (for both officers and crew members) rest periods and regulations governing work on Sundays and holidays are followed when the vessel is in a safe harbor? | The Master of the vessel | The owner of the vessel | The company chartering the vessel | The company operating the vessel |
| 4056 | A management system designed with the intent of ensuring fulfillment of customers requirement? | Bridge Resource Management | Chart Management System | Management system | Quality System |
| 4057 | A seaman assaults the Second Mate and injures him with a beer bottle while the ship is at sea. The incident is logged in the Official Logbook. In subsequent suspension and revocation proceedings against the seaman according to the regulations _____. | the logbook entry is prima facie evidence of the facts if it complies with the law | the case will be dismissed if the logbook entries are improperly made | the Second Mate and the Master must testify as to the facts of the assault | the logbook is inadmissible if the logbook entries do not conform to the law |
| 4058 | A structured and documented system enabling Company personnel to implement effectively the Company safety and environmental protection policy. | Safety Management System | International Safety Management | Safety of life at Sea | Internal Safety Management |
| 4059 | Factors that contribute to the occurrence of mistakes due to relationships among individuals. | environmental factor | individual factors | organizational factors | group factor |
| 4060 | Human characteristics and behaviors are _____ with the functioning of technology people design build maintain and operate. | distinct | discrete | intrinsically linked | extraneous |
| 4061 | In risk assessment what do you call this type of risks that risk based decisions are normally taken by the Company and are usually dynamic in nature? | Pure Risk | Speculative Risk | Major Risk | Limited Risk |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 4062 | In terms of vessel manning a watch is the _____. | direct performance of cargo loading and discharge operations only | performance of maintenance work necessary for the vessel s safe operation on a daily basis | direct performance of deck or engine operations in a scheduled and fixed rotation | performance of lookout duties |
| 4063 | One disadvantage of using regular dry chemical ( sodium bicarbonate ) in fire fighting is that. | controlling | planning | leading | coordinating |
| 4064 | Organizations depend upon the environment for _____. | survival | selling inputs | resources | inputs |
| 4065 | The terminology able to understand any order spoken by the officers refers to all of the following situations except _____. | for deck department crew members to understand the terminology used in the engine room | in response to a man overboard | directing the use of lifesaving equipment | in response to a fire |
| 4066 | There are three conflict methods most frequently used in managing conflicts; supervision integrative problem solving and _____. | comprehence | forcing | compromise | forging |
| 4067 | There are three learning scope for instructional objectives. Which objective is not part of these learning scope? | Subject Objectives | Cognitive Objectives | Disabling Objectives | Enabling Objectives |
| 4068 | What are SMS (continuous improvement process) Dynamic Elements? | The main shipboard manual Safety and health manual and contingency manual | Safety Management Assessments | Reviews and Audits | Risk Assessment |
| 4069 | What do you call the Master s special skill in order to deliver the best possible operation of his vessel within the budget constraints? | Leadership skills | Managerial skills | any of these options | Charismatic Approach |
| 4070 | What is a particular learning scope for instructional objective which is concerned with how a trainee controls or moves his body? | Instructional objective | Psychomotor Objective | Affective Objective | Cognitive Objective |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 4071 | What is a particular learning scope for instructional objectives dealing with what a trainee should know understand or comprehend? | Cognitive Objective | Affective Objective | Psychomotor Objective | Instructional objective |
| 4072 | What is the study of human capabilities in relationship to work? | Psychometric | Psychology | Physical Therapy | Ergonomics |
| 4073 | What kind of leadership style that demands respect from the people the serve? | Traditional leadership | Bureaucratic leadership | Leadership by example | Participative leadership |
| 4074 | When managers respond to pressure for change and deny that they exist they respond in a _____ way. | Managerial way | Good way | Destructive | Irrational |
| 4075 | When subordinates are given responsibility for dealing with a problem their _____ increases. | Pride | Body structure | Self-esteem | Patience |
| 4076 | Which of the following is not an indication of error chain development? I.) ambiguity II.) distraction III.) inadequacy and confusion VI.) communication V.) proper conning or lookout VI.) procedural violation | II | V | III | I |
| 4077 | You are signing on a crew. You can determine the minimum number and qualifications of the crew that you are required to carry by consulting which document? | fo c sle card | Articles of Agreement | Crew list | Certificate of Inspection |
| 4078 | You are signing on the Purser. He should present a Merchant Mariner s document with which endorsement? | Purser | Steward s Department | See Certificate of Registry | Staff Officer |
| 4079 | A DISADVANTAGE of a matrix organization is _____. | Members require some expertise in interpersonal relations | Control over resources | Facilitates specialization | It reduces efficiency |
| 4080 | A journal kept by the officer of the watch in which day to day happenings are recorded regarding the deck department is the _____. | bell book | Official Logbook | cargo record book | deck rough log |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 4081 | A kind of teaching- learning principle where the trainee must proceed step by step and each step must be in some way more difficult than the previous step. | Affective Objective | graduated sequence | perceived purpose | Cognitive Objective |
| 4082 | A kind of teaching- learning principle where the trainee must see why he should study something. | perceived purpose | Affective Objective | graduated sequence | Cognitive Objective |
| 4083 | A Master should do the following when faced with difficult problem situation EXCEPT: I. solving the problem ASAP in order to reduce negative consequences II. appeal to higher authority | I and II are correct | Neither I nor II | I only | II only |
| 4084 | A merchant ship with a crew of over 20 is required by shipping regulation to have on board one of the following: | Neil Robertson Stretcher | Emergency medical outfit | Escalating pathwalk | All of the options |
| 4085 | A new crew member aboard your fishing vessel who has not received any safety instructions or participated in any drills reports on board. The Master must provide a safety orientation _____. | before sailing | within one week | within 24 hours | on reporting day if it occurs within normal work hours |
| 4086 | A new crewman reports on board. He must be trained in the use of the ship s lifesaving appliances within what time period? | Before sailing | 2 weeks | 2 months | 1 month |
| 4087 | A particular learning scope for instructional objective which deals with how a trainee should about something in relation to the training program. | Affective Objective | Effective Objective | Cognitive Objective | Progressive Objective |
| 4088 | A person approved by the company to assess a seafarer s competence at the appropriate level and for the functions specified. | In-service assessor | The Administration | The Chief Officer | The Master |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 4089 | A personal call means that: | the applicant on board wishes to have a conversation with a person whose name is known | any of these options | done using the PA system | the applicant on board request the coastal station to bring about a conversation with a shore subscriber by means of a scrambler |
| 4090 | A seaman is entitled by law to a release from Foreign Articles when _____. | intoxicated | deductions are made from wages | the vessel is overloaded | injured |
| 4091 | A seaman may have all or part of his wages deposited by allotment to a bank or savings institution. Which of the following is NOT a requirement for this type of allotment? | All of the above are requirements. | The account must be either a checking or savings account. | The institution must be insured by the FSLIC or FDIC. | The account must be opened by the seaman and maintained in the seaman s name. |
| 4092 | A seaman may have all or part of his wages deposited by allotment to a bank or savings institution. Which of the following is not a requirement for this type of allotment? | The account must be opened by the seaman and maintained in the seaman s name. | All of the above are requirements. | The institution must be insured by the FSLIC or FDIC. | The account must be either a checking or savings account. |
| 4093 | A seaman may not make an allotment to his _____. | minor children | mother-in-law | grandparents | brother |
| 4094 | A seaman signed on articles on 16 January 1987 and signed off on 2 March 1987. How should you enter this under the Time of Service column in the articles? | 2 Months | 1 Month 16 Days | 46 Days | 1 Month 18 Days |
| 4095 | A seaman you have just discharged has a Continuous Discharge Book. Which statement is TRUE? | If the vessel was on coastwise articles the record of discharge will be made in the Official Logbook. | An entry should be made in the book and a Certificate of Discharge issued to the seaman. | A Certificate of Discharge form should be attached to the book. | The record of entry in the continuous discharge book shall agree with the entry made in the Ship s Articles. |
| 4096 | A significant development in the environment of a number of organization is ____. | Conference Assembly | globalization | Unification | infrastructure |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 4097 | A systematic application of management system policies procedures and practices to the task of analyzing evaluating and controlling environmental risk is called _____. | Environmental Risk Management | Environmental Rules and Regulations | Environmental Aspect | Environmental Safety Procedures |
| 4098 | A type of management where shipping business concept having many ships moving at seas and port of the world mainly to avoid losses and maximize earning profits? | Liability Management | Personnel Management | Self Management | Asset Management |
| 4099 | After a seaman is discharged at the end of the voyage the final payment of wages due must be made whichever is earliest either within 24 hours after the cargo has been discharged or _____. | prior to the vessel s departure on the next voyage | prior to any change of Master | prior to loading any out-bound cargo | within 4 days after the seaman s discharge |
| 4100 | All entries in the Official Logbook must be signed by the Master and _____. | No other signature is required. | the Chief Engineer | one other crew member | the person about whom the entry concerns |
| 4101 | An employment contract is a written agreement entered between an employer or local agency and the overseas contract worker containing which of the following? | Terms and condition of employment | All prohibitions of what not to do onboard ship | Either A or B | Neither A nor B |
| 4102 | Which rights does a seafarer who is unfit for work normally have? | Care, wages, free repatriation | A compensation equal to wages for six months. | Free passage home. | Care. |
| 4103 | In authority and assertiveness, which of the following thoughts is correct if a master or pilot is considered to be of too high authority? I. Total command expected II. Lack of communication III. Cannot delegate IV. Performance orientation | I, II | I, II, III, IV | III, IV | IV |
| 4104 | Once a problem has been defined by the management, the next move is: | Diagnose the causes | Develop alternatives | Identify the decisions objectives | Make remedial measures |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 4105 | All of the following are true about decision-making EXCEPT | it is needed in stable environments | it is a process of developing and selecting a course of action | it occurs at many points in the planning process | it involves allocations of resources |
| 4106 | The involvement of _____ is the more difficult part of ethical decision-making. | support level | making moral judgments | social responsibility | making better decisions |
| 4107 | Managerial performance is based upon accomplishment of _____. | choices | objectives | responsibilities | duties |
| 4108 | Management is defined as a/an _____. | process | resource | objective | goal |
| 4109 | The four basic steps in planning are: | Set goals, define present situation, define environmental constraint and develop a course of action | Set goals, examine resources, identify aids and barriers and develop course of action | Set goals, define present situation, identify aids and barriers and implement plans | Set goals, define present situation, identify aids and develop course of action |
| 4110 | Overcoming fear of failure and lack of confidence is accomplished by all of the following EXCEPT: | set only easily achievable goals and objectives | have constructive and supportive response when goals are missed | provide training and guidance | give recognition and rewards when goals are achieved |
| 4111 | The trainees must exhibit a performance when assessment takes place at the end of the training program called: | Performance Objective | Training Performance Objective | Ultimate Performance Objective | Enabling Objective |
| 4112 | In order to maintain safe working conditions on board the vessel, every crewmember should do the following, EXCEPT_____. | Be attentive to all what is happening in the surroundings. | Know the Station Bill and general instructions in force. | Familiarize himself with the emergency plan. | Special assignments assigned in case of emergency. |
| 4113 | This is called the assignment to other authority and responsibility for carrying out specific tasks. | Decentralization | Communication | Specialization | Delegation |
| 4114 | In bridge resource management, which of the following statements are example of hazardous thoughts I.) I can do it II.) It wont happen to me III.) Why takes chances IV.) its not my job V.) Dont tell me what to do VI.) Were all in the same ship | IV, V, VI | I, II, III, IV, V | I,II,III | I, II, IV, V |

| | | | | | |
|---|---|---|---|---|---|
| 4115 | An officer in charge of a watch or forming a part shall be provided a minimum of how many hours rest period in any 24 hour period pursuant to STCW regulations: | 8 hours | 6 hours | 10 hours | 4 hours |
| 4116 | Efficiency is the ability to: | Work orderly with good output | Get results to the maximum | Work without regard to outside forces | Get things done right |
| 4117 | Human resource management does NOT deal with: | Training | Recruitment | Production | Placement |
| 4118 | What is the most effective example of management development technique? | Coaching | Talking with subordinates | Communication | Coordination |
| 4119 | Management experts believed that efficient and effective organizations had a hierarchical structure called: | The chain of command | The span of control | Bureaucracy | Departmentalization |
| 4120 | The function which is more important in the accomplishment of objectives is _____. | planning | coordination | leading | controlling |
| 4121 | The Master remarks that is too slow. Which of the following implies this? | Assessment | Judgment | Measurement | Evaluation |
| 4122 | The more difficult part of ethical decision making involves: | Who has the right to do what and when. | Technical, human, conceptual. | Making better decisions. | Social responsibility. |
| 4123 | The most common OJT training methods are job rotation, apprenticeship and _____ . | internship | management situation | job specialization | job |
| 4124 | The number of subordinates who report directly to a manager is known as? | Departmentalization | Division of work | The span of management | The degree of coordination |
| 4125 | The planning process: | Ends when the control process begins. | Ends when plans are agreed upon. | Ends when plans are implemented. | Does not end but may involve replanning. |
| 4126 | The process of management includes? | Planning | Leading | All of the options | Organizing |
| 4127 | What would you call the psychological mechanism of blaming difficulties on someone or something else? | Aggression | Avoidance | Projection | Anxiety |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 4128 | The question of human relations considers? | Managers accompanying the employees. | Managers interacting with employees. | Managers directing with employees. | Managers summoning the employees. |
| 4129 | The word organization has two meaning, the first implies a/an _____, the second refers to _____: | continuous, a process | coordination, a process | institution, a process | coaching, a process |
| 4130 | There are four basic steps in human resource planning: Planning for future needs, Planning for future balance, Planning for recruiting and Planning for? | Advancement | Productivity | Development | Retirement |
| 4131 | There are three learning scope for instructional objectives. Which of the following is NOT part of these learning scope? | Psychomotor objectives | Affective objectives | Enabling objectives | Cognitive objectives |
| 4132 | This involves the recruitment, training and development of organizational members. | Staffing | Human Resource Management | Organizing | Organizational development |
| 4133 | This is a kind of learning principle where the trainee must see why he should study something. | Individual differentiation | Knowledge of results | Perceived purpose | Graduated sequence |
| 4134 | This is a kind of terminal Performance Objectives which specify what the trainee should be able to apply in their workplace when the training is completed. | Ultimate values objectives | Job behavior objectives | Cost benefit objectives | Skill objectives |
| 4135 | This is a particular learning scope for instructional objective which is concerned with how a trainee controls or moves his body. | Cognitive objective | Enabling objective | Affective objective | Psychomotor objective |
| 4136 | The scope of instructional objective which deals with how a trainee should know about something in relation to the training program is? | Affective objective | Enabling objective | Psychomotor objective | Cognitive objective |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 4137 | This term states a goal and what behavioral performance or activity the trainee will be doing when he has achieved the goal of a particular educational objective. | Educational aim | General education aim | Specific educational aim | Instructional objective |
| 4138 | What is the means by which data are transmitted across the levels of the organization? | Vertical information systems | Liaison individual | Lateral relationship | Chain of command |
| 4139 | This is the ability to get things done right. | Skill | Effective resource | Competency | Efficiency |
| 4140 | What is the basis of a manager making a choice of objectives. | Familiarization | Effectiveness | Efficiency | Ability |
| 4141 | This is the most basic resource of any organization. | People | Information | Equipment | Money |
| 4142 | To deal with the change constructively, manager can take two major approaches, they can react to the signs that changes are needed, and they can? | Deal with the forces for change when they appear. | Deal with the particular problems as they arise. | Maximize the effect of change. | Develop a program of planned change. |
| 4143 | Training programs are directed toward maintaining and improving _____ job performance. | future | potential | current | technical |
| 4144 | What is the necessary part of delegation of accountability and authority? | Goals | Achievements | Objectives | Responsibility |
| 4145 | When a Master takes the leadership in approaching a problem, Must his first action be a decision that will directly solve the problem? | Yes, with his experience, it is most likely that he has the best solution. | Not necessary, he shall use all available resources. He should resist the temptation to step in and do it all by himself. | Yes, take full control. Do not delegate to other officers, to avoid mistake. | No, he should observe the situation, and let the other senior officers solve the situation. |
| 4146 | When detailed plans are drawn to meet the training objectives the method of training becomes a /an: I. formal training II. Informal training | neither I nor II | I only | I & II | II only |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 4147 | When subordinates are given responsibility for dealing with a problem, their _____ increases. | self-actualization | sense of belongingness | all of these choices | self-esteem |
| 4148 | Which of the following is NOT a specific step in short term startegy during bridge team management? I.) leave the problem and do the alternatives II.) Identify the problem III.) build plans to deal with the problem IV.) check the plans with the BTM member | I,II,III | III, IV | II | V, VI |
| 4149 | Which of the following is not an indication of error chain development? I. ambiguity II. Distraction III. inadequacy and confusion IV. Communication V. proper conning or lookout VI. Procedural violation | III, VI | I | V | II,IV |
| 4150 | When should training in personal survival techniques be given? | After joining the ship. | Before being employed. | During the first week on board. | After one period at sea. |
| 4151 | If water is rising in the bilge of a survival craft, your should first: | Check the cracks in the hull | Check the bilge drain plug | Shift all personnel to the stern | Abandon the survival craft |
| 4152 | Which one of the listed routine test and inspections of life-saving appliances is not required by the regulations? | Inspection of life-saving appliances, including lifeboat equipment shall be carried out monthly to ensure they are complete and in good order | Survival crafts and rescue boats with launching appliances shall be visually inspected weekly to ensure they are ready for use | lifeboat engines to be run for at least 3 minutes every week | general emergency alarm to be tested daily |
| 4153 | A lifejacket should be provided with_____ . | a whistle and a light | a light | a whistle | On ships built after February 1992 all lifejackets should be fitted with a light |
| 4154 | Every inflatable life raft , inflatable lifejacket and hydrostatic release units shall be serviced_____ | every 18 months. | every 36 months. | every 12 months. | every 24 months. |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 4155 | While underway, fire break out in the forward part of the vessel. Whenever practicable, what will be the first thing you will do if your are on watch? | Abandonship to windward | Call for assistance | Put the vessel's stern into the wind | Keep going on half spead |
| 4156 | In the event of fire in the crew's quarter, one of your first act is to: | Close all ventillation to the quarters | Attempt to put out the fire by portable fire-extinguisher | Ventilate the quarters | Prepare to abandonship |
| 4157 | A drip tray containing oil is on fire. The only fire fighting equipment available is water hose with spray jet/spray nozzle. How, if at all, should you attempt to put out this fire using water? | Water should be applied to the oil in a single jet only. | The water can be applied in a fine spray starting from the front in a sweeping motion. | Water should be applied in a jet to the back of the fire. | Water should not be used on any type of oil fire. |
| 4158 | A high-velocity fog stream can be used in fire fighting situations to drive heat and smoke ahead of the fire fighters in a passageway. This technique should only be used when: | The fire is totally contained by the ship's structure | At least two fog streams can be used | Using a 2 ½ inch hose | There is an outlet for the smoke and heat |
| 4159 | The primary objective of First Aid is: | To alleviate pain | To prevent further injury | To give life | To help a patient |
| 4160 | In reviving a person who has been overcomed by gas fumes, which of the following would you AVOID doing? | Applying artificial respiration and massage | Keeping him warm and comfortable | Prompt removal of the patient from the suffocating atmosphere | Giving stimulants |
| 4161 | As with heat burns the damage of frostbite /hypothermia may be either superficial or deep, and the affected tissues may be destroyed. What kind of first aid should be given a person with frostbite ? | Heat the affected area with hot-water bottles. | Hand or body heat the affected parts skin-to-skin (e.g. frozen hand in persons opposite armpit...) | Rub the affected area. | Give the casualty a cigarette. |
| 4162 | When giving first aid you should avoid _____. | Instruction by standers | Touching the patient before washing your hands | Unnecessary haste and appearance of uncertainty | Any conversation with the patient |
| 4163 | The ABC-rules are an important part of the First Aiders know how. What does the First Aid ABC-rules stands for? | A Better Control | Adults Behind Children | Anything But Continuation | Airway Breathing Circulation |

| | | | | | |
|---|---|---|---|---|---|
| 4164 | First aid treatment for small cuts and open wounds is to _____. | stop the bleeding, clean, medicate, and cover the wound | apply an ice pack to the wound and cover it when the bleeding stops | apply a hot towel to purge the wound, then medicate and cover it | lay the patient down and cover the wound when the bleeding stops |
| 4165 | The MOST important element in administering CPR is: | Administering of oxygen | Treating for traumatic shock | Having the proper equipment for the process | Starting the treatment quickly |
| 4166 | A person slowly feel more sleepy and thirsty. The skin become very dry and there is a sweet taste of the breath. The glucose reaction shows positive. What kind of medicine will the person need as soon as possible? | Insulin | Sugar lump, sugar drink or something sweet | Nothing at all | A glass of cold milk |
| 4167 | A device used to immobilize fractures and help prevent bone displacement is: | Bandage | Stretcher | Tourniquet | Splint |
| 4168 | A tourniquet should be used to control bleeding ONLY _____. | with puncture wounds | when all other means have failed | to prevent bleeding from minor wounds | when the victim is unconscious |
| 4169 | First, second, and third degree burns are classified according to the: | Area of the body burned | Size of the burned area | Source of heat causing the burn | Layers of skin affected |
| 4170 | Treatment of burns and scalds depends on the severity of the injury. What is the correct thing to do for minor burns and scalds? | Place the injured part under slowly running cold water for at least 10 minutes, but preferably until the pain is gone. If no water is available, use any cold, harmless liquid. | Apply lotions, ointments or fat to the injury. | Remove all sticky clothing from the casualty. | Break blisters, remove any loose skin or foreign objects from the injured area. |
| 4171 | A shipmate suffers a heart attack and stops breathing. You must: | Make the victim as comfortable as he could be | Check his pulse and start CPR | Administer oxygen immediately | Let him lie on his side |
| 4172 | Which position is the best to stop bleeding from the nose? | Holding the nose above steamed water. | Laying on the back, leaning the head as much back as possible. | Laying on the back, holding a wet, cold towel on the top of the nose. | Sitting on a chair, leaning forward, with two fingers pressing the nose together. |
| 4173 | A seaman has a small, gaping laceration of the arm that is not bleeding excessively. What can be done as an alternative to suturing to close the wound? | Apply a compression bandage. | Apply butterfly strips, then a sterile dressing. | Wrap a tight bandage around the wound. | Use temporary stitches of sail twine. |

| | | | | | |
|---|---|---|---|---|---|
| 4174 | Before CPR is started, you should _____. | treat any bleeding wounds | Insure the victim is conscious | make the victim comfortable | establish an open airway |
| 4175 | Fire and abandon ship stations and duties may be found on the _____. | crewman's duty list | shipping articles | Certificate of Inspection | muster List |
| 4176 | What is a contingency plan for ships? | Loading plan for general cargo | Plan for next voyage | Plan for safety preparedness | Plan for maintenance and repair |
| 4177 | Which of the following is FALSE why there may not be enough oxygen in an enclosed space or tank? | tank may have been coated with preservatives | cargo inside may have absorb the oxygen | oxygen is depleted as oxidation may have taken place | enclosed as it is, no proper circulation of air |
| 4178 | Injuries resulting from slips and falls constitute the largest percentage of accidents that occur in the catering department. What shall be done to reduce this high accident rate? | Keep the floors and decks free from fat and grease. | Do not wash off all rubbish to prevent persons slipping. | Install thermostat to avoid water from freezing to ice. | Ensure that slippery substances are not left where several persons are expected to be around. |
| 4179 | The primary concern in aiding a back injury patient is _____. | d. providing enough fluids to prevent dehydration | Avoiding possible injury to the spinal cord by incorrect handling | c. preventing convulsions and muscle spasms caused by the pain | a. relieving the patient's pain by giving aspirin or stronger medication |
| 4180 | The most effective first aid treatment for chemical burns is to immediately _____. | Wrap the burn with sterile dressing | Flood the affected area with water | Apply an ice pack to the burned area | Apply ointment to the burned area |
| 4181 | To treat a person suffering from heat exhaustion, you should _____. | Give him sips of cool water | Cover him with a light cloth | Put him in a tub of ice water | Administer artificial respiration |
| 4182 | When administering first aid you should avoid _____. | Unnecessary haste and appearance of uncertainty | Any conversation with the patient | Instructing bystanders | Touching the patient before washing your hands |
| 4183 | Since electrical burn victims may be in shock, the FIRST medical response is to check for _____. | Indication of broken bones | Bleeding injuries | Breathing and heartbeat | Symptoms of concussion |
| 4184 | When administering first aid you should avoid _____. | Touching the patient before washing your hands | Any conversation with the patient | Unnecessary haste and appearance of uncertainty | Instructing bystanders |
| 4185 | The most effective first aid treatment for chemical burns is to immediately _____. | Wrap the burn with sterile dressing | Apply ointment to the burned area | Flood the affected area with water | Apply an ice pack to the burned area |
| 4186 | Carbon dioxide fire extinguisher have a capacity of at least how many kilograms? | 10 | 3 | 7 | 5 |

| | | | | | |
|---|---|---|---|---|---|
| 4187 | Each powder or carbon dioxide fire extinguisher shall have a capacity of at least how many kilograms. | 5 | 3 | 7 | 9 |
| 4188 | Each foam extinguisher shall have a capacity of at least how many liters? | 5 | 9 | 11 | 7 |
| 4189 | Dangerous goods are divided into _____ classification? | 9 | 7 | 8 | 6 |
| 4190 | A tanker vessel is loading a hazardous cargo. The allowance for expansion is based on ambient temperatures of what maximum range? | 0deg.C to 100deg.C | -10deg.C to 90deg.C | -18deg.C to 46deg.C | -40deg.C to 50deg.C |
| 4191 | For CO2 fire-fighting systems for machinery spaces, the fixed piping system shall be such that: | 85% of the gas can be discharged into the space within two minutes | 70% of the gas can be discharged into the space within one minute | 100% of the gas can be discharged into the space within three minutes | 100% of the gas can be discharged into the space within two minutes |
| 4192 | A petroleum liquid is said to be grade D combustible liquid flash point is: | A flammable liquid | 100deg. F but below 150deg. F | D | above 80deg. F |
| 4193 | Grade D combustible liquids have a maximum flash point of: | 109deg. F | 100deg. F | 110deg. F | 149deg. F |
| 4194 | Which activity will have the greatest fire-fighting effect in case of a fire? | Call the Chief Officer | Extinguishing attempt is started immediately | All possible fire-fighting equipment is brought to the scene | All fire-fighting teams are organized as soon as possible |
| 4195 | Which type of fire extinguisher has a disadvantage and danger of malfunction that may result to dangerous overpressure? | powder | mechanical foam | carbon dioxide | water |
| 4196 | After extinguishing a fire in a paint locker using the fixed CO2 system, the next immediate action is for the space to be: | opened and doused with water to prevent reflash | left closed with vents off until all boundaries are cool | checked for the proper oxygen level | opened and burned material removed |
| 4197 | Which type of fire extinguisher is best to use in the presence of electrical hazards? | water | powder | carbon dioxide | chemical foam |

| | | | | | |
|---|---|---|---|---|---|
| 4198 | Which of the listed modes of heat transfer does NOT require any physical contact between a warmer and a cooler substance? | Radiation | convection | conduction | any of the choices |
| 4199 | These can be dissolved in the fuel and not removed by the purifier. | Sulphur and Vanadium | Aluminum and Copper | Copper and Sulphur | Vanadium and Aluminum |
| 4200 | A pan on the galley stove containing oil catches fire, which of the following should NOT be used on this type of fire? | Raise the alarm, close galley door and wait for the fire teams to arrive | Cover pan with fire blanket and switch of heat source | Use water extinguisher to put out the fire | Cover pan with lid and switch of heat source |
| 4201 | Which is not a functional requirement embodied in the regulations in order to achieve the fire safety objectives set out in SOLAS. | division of the ship into main vertical and horizontal zones by thermal boundaries | detection of any fire in the zone of origin | prohibits the use of combustible materials | containment and extinction of any fire in the space of origin |
| 4202 | Which of the Code provides international specific engineering standards for fire fighting equipments. | FSA | FAS | FFS | FSS |
| 4203 | Which is not a functional requirement to detect a fire from a space of and to provide for alarm for safe escape and fire-fighting activity? | fire patrols | fixed fire detection and fire alarm system installations | manually operated call points | fire teams |
| 4204 | A term of maximum temperature at which a given gas can be liquified by pressure i.e. Tank vessel cargo of ammonia 256 degrees fahrenheit. | Critical temperature | Critical pressure | Flammable temperature | Flammable pressure |
| 4205 | The combustion elements in a fuel are carbon ( C ), hydrogen (H2) and which other element? | Nitrogen (N) | Sulphur (S) | None of the above. | Halon |
| 4206 | Cooling of compartment boundaries where fire has occurred should be continued until: | flash point is approached | ambient temperature is approached | Reid vapor pressure is attained | ignition temperature is approached |
| 4207 | In which event should the Master take actions to protect and safeguard all persons on board his ship? | during drydocking | during emergencies | when docking or undocking | in an extreme weather conditions |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 4208 | According to basic principles regarding fire protection the ship is to be divided in zones by structural and thermal boundaries which is: | Main Fire zones in accordance with the ship's fire-fighting system | In main zones according to utilization (Accommodation , Machinery, Cargo) | In main horizontal zones | in main vertical zones |
| 4209 | As a firefighting medium, CO2 can be dangerous under certain conditions as it can cause which of the following? | indigestion | carbon monoxide poison | burns and blistering | hallucinations |
| 4210 | A term called when a temperature at which a liquid starts to and completely becomes a solid. | Latent Heat | Melting Point | Boiling Point | Solidifying Point |
| 4211 | There are currently two standards of classifying fires as A, B, C, and D, according to the nature of the burning material. One standard is ISO 3941, the other is: | NFPA 12 | NFPA 10 | IFPA 10 | IFPA 12 |
| 4212 | It is impossible to extinguish a shipboard fire, except in rare cases, by: | removing the heat | removing the fuel | interrupting the chain reaction | removing the oxygen |
| 4213 | If portable fire extinguisher has been partially discharged, it should be: | labeled empty and recharged as soon as possible | replaced In Its proper location If weight loss Is no more than 15% | replaced in its proper location if weight loss is no more than 25% | replaced in its proper location regardless of weight |
| 4214 | Carbon dioxide fire extinguisher have a capacity of at least how many kilograms? | 3 | 7 | 10 | 5 |
| 4215 | Each powder or carbon dioxide fire extinguisher shall have a capacity of at least how many kilograms. | 5 | 9 | 3 | 7 |
| 4216 | Each foam extinguisher shall have a capacity of at least how many liters? | 5 | 11 | 9 | 7 |
| 4217 | Dangerous goods are divided into _____ classification? | 6 | 9 | 7 | 8 |
| 4218 | A tanker vessel is loading a hazardous cargo. The allowance for expansion is based on ambient temperatures of what maximum range? | -18deg.C to 46deg.C | -40deg.C to 50deg.C | 0deg.C to 100deg.C | -10deg.C to 90deg.C |

| | | | | | |
|---|---|---|---|---|---|
| 4219 | For CO2 fire-fighting systems for machinery spaces, the fixed piping system shall be such that: | 100% of the gas can be discharged into the space within two minutes | 70% of the gas can be discharged into the space within one minute | 100% of the gas can be discharged into the space within three minutes | 85% of the gas can be discharged into the space within two minutes |
| 4220 | A petroleum liquid is said to be grade D combustible liquid flash point is: | D | 100deg. F but below 150deg. F | above 80deg. F | A flammable liquid |
| 4221 | Grade D combustible liquids have a maximum flash point of: | 149deg. F | 100deg. F | 109deg. F | 110deg. F |
| 4222 | Which activity will have the greatest fire-fighting effect in case of a fire? | Call the Chief Officer | All possible fire-fighting equipment is brought to the scene | Extinguishing attempt is started immediately | All fire-fighting teams are organized as soon as possible |
| 4223 | Which type of fire extinguisher has a disadvantage and danger of malfunction that may result to dangerous overpressure? | powder | mechanical foam | carbon dioxide | water |
| 4224 | After extinguishing a fire in a paint locker using the fixed CO2 system, the next immediate action is for the space to be: | opened and burned material removed | left closed with vents off until all boundaries are cool | checked for the proper oxygen level | opened and doused with water to prevent reflash |
| 4225 | Which type of fire extinguisher is best to use in the presence of electrical hazards? | powder | water | chemical foam | carbon dioxide |
| 4226 | Which of the listed modes of heat transfer does NOT require any physical contact between a warmer and a cooler substance? | Radiation | convection | any of the choices | conduction |
| 4227 | These can be dissolved in the fuel and not removed by the purifier. | Sulphur and Vanadium | Copper and Sulphur | Vanadium and Aluminum | Aluminum and Copper |
| 4228 | A pan on the galley stove containing oil catches fire, which of the following should NOT be used on this type of fire? | Cover pan with fire blanket and switch of heat source | Cover pan with lid and switch of heat source | Raise the alarm, close galley door and wait for the fire teams to arrive | Use water extinguisher to put out the fire |
| 4229 | Which is not a functional requirement embodied in the regulations in order to achieve the fire safety objectives set out in SOLAS. | division of the ship into main vertical and horizontal zones by thermal boundaries | prohibits the use of combustible materials | containment and extinction of any fire in the space of origin | detection of any fire in the zone of origin |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 4230 | Which of the Code provides international specific engineering standards for fire fighting equipments. | FSA | FFS | FSS | FAS |
| 4231 | Which is not a functional requirement to detect a fire from a space of and to provide for alarm for safe escape and fire-fighting activity? | manually operated call points | fire teams | fixed fire detection and fire alarm system installations | fire patrols |
| 4232 | A term of maximum temperature at which a given gas can be liquified by pressure i.e. Tank vessel cargo of ammonia 256 degrees fahrenheit. | Critical temperature | Critical pressure | Flammable pressure | Flammable temperature |
| 4233 | The combustion elements in a fuel are carbon ( C ), hydrogen (H2) and which other element? | Nitrogen (N) | Sulphur (S) | Halon | None of the above. |
| 4234 | Cooling of compartment boundaries where fire has occurred should be continued until: | ignition temperature is approached | flash point is approached | Reid vapor pressure is attained | ambient temperature is approached |
| 4235 | In which event should the Master take actions to protect and safeguard all persons on board his ship? | during drydocking | in an extreme weather conditions | during emergencies | when docking or undocking |
| 4236 | According to basic principles regarding fire protection the ship is to be divided in zones by structural and thermal boundaries which is: | In main horizontal zones | In main zones according to utilization (Accommodation , Machinery, Cargo) | Main Fire zones in accordance with the ship's fire-fighting system | in main vertical zones |
| 4237 | As a firefighting medium, CO2 can be dangerous under certain conditions as it can cause which of the following? | indigestion | carbon monoxide poison | burns and blistering | hallucinations |
| 4238 | A term called when a temperature at which a liquid starts to and completely becomes a solid. | Boiling Point | Solidifying Point | Latent Heat | Melting Point |
| 4239 | There are currently two standards of classifying fires as A, B, C, and D, according to the nature of the burning material. One standard is ISO 3941, the other is: | NFPA 10 | IFPA 10 | NFPA 12 | IFPA 12 |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 4240 | It is impossible to extinguish a shipboard fire, except in rare cases, by: | removing the fuel | interrupting the chain reaction | removing the heat | removing the oxygen |
| 4241 | If portable fire extinguisher has been partially discharged, it should be: | replaced in its proper location if weight loss is no more than 25% | labeled empty and recharged as soon as possible | replaced in its proper location regardless of weight | replaced In Its proper location If weight loss Is no more than 15% |
| 4242 | When attempting to enter a compartment containing fire, which method of applying water a most appropriate? | Solid stream directed toward the overhead | Straight stream directed into the center of the fire | High-velocity fog stream directed toward the overhead | Sweeping the compartment with a fog stream |
| 4243 | What does the FTP code relate to? | fire safety requirements | security requirements | Testing and evaluating products that are flammable | temperature in the cargo hold |
| 4244 | Prior to the release the CO2 system to the compartment in order to extinguish the fire, rest assure that all personnel has vacated the area. | The Chief Engineer immediately at his discretion release the CO2 system | The EOW shall release the CO2 system immediately | The master shall order the release of CO2 system | The 2nd Engineer shall release the CO2 system |
| 4245 | Combustible liquids are divided into how many classes? | one | three | four | two |
| 4246 | It is necessary to extend ventilators to the bilges in order: | to keep them dry, and thus easier to clean | to remove fuel vapors which are heavier than air | to cool the machinery areas | to provide adequate air to the engine |
| 4247 | In addition to weighing the cartridge, what other routine maintenance is required for a cartridge-operated dry chemical extinguisher? | Check the hose and nozzle for clogs | Discharge small amount to see if it works | Check the external pressure gauge | Weigh the powder in the canister |
| 4248 | Carbon Monoxide is considered as one of the most toxic gases onboard. One of its characteristics is: | highly corrosive | whitish in color | odorless | lighter than air |
| 4249 | Carbon dioxide fire extinguisher have a capacity of at least how many kilograms? | 10 | 7 | 3 | 5 |
| 4250 | Each powder or carbon dioxide fire extinguisher shall have a capacity of at least how many kilograms. | 3 | 5 | 9 | 7 |
| 4251 | Each foam extinguisher shall have a capacity of at least how many liters? | 5 | 11 | 9 | 7 |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 4252 | Dangerous goods are divided into _____ classification? | 8 | 7 | 9 | 6 |
| 4253 | A tanker vessel is loading a hazardous cargo. The allowance for expansion is based on ambient temperatures of what maximum range? | -10deg.C to 90deg.C | 0deg.C to 100deg.C | -40deg.C to 50deg.C | -18deg.C to 46deg.C |
| 4254 | For CO2 fire-fighting systems for machinery spaces, the fixed piping system shall be such that: | 70% of the gas can be discharged into the space within one minute | 100% of the gas can be discharged into the space within three minutes | 100% of the gas can be discharged into the space within two minutes | 85% of the gas can be discharged into the space within two minutes |
| 4255 | A petroleum liquid is said to be grade D combustible liquid flash point is: | 100deg. F but below 150deg. F | D | A flammable liquid | above 80deg. F |
| 4256 | Grade D combustible liquids have a maximum flash point of: | 149deg. F | 110deg. F | 109deg. F | 100deg. F |
| 4257 | Which activity will have the greatest fire-fighting effect in case of a fire? | All fire-fighting teams are organized as soon as possible | Extinguishing attempt is started immediately | Call the Chief Officer | All possible fire-fighting equipment is brought to the scene |
| 4258 | Which type of fire extinguisher has a disadvantage and danger of malfunction that may result to dangerous overpressure? | powder | water | carbon dioxide | mechanical foam |
| 4259 | After extinguishing a fire in a paint locker using the fixed CO2 system, the next immediate action is for the space to be: | opened and burned material removed | left closed with vents off until all boundaries are cool | opened and doused with water to prevent reflash | checked for the proper oxygen level |
| 4260 | Which type of fire extinguisher is best to use in the presence of electrical hazards? | chemical foam | powder | water | carbon dioxide |
| 4261 | Which of the listed modes of heat transfer does NOT require any physical contact between a warmer and a cooler substance? | any of the choices | conduction | convection | Radiation |
| 4262 | These can be dissolved in the fuel and not removed by the purifier. | Vanadium and Aluminum | Copper and Sulphur | Sulphur and Vanadium | Aluminum and Copper |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 4263 | A pan on the galley stove containing oil catches fire, which of the following should NOT be used on this type of fire? | Cover pan with fire blanket and switch of heat source | Use water extinguisher to put out the fire | Cover pan with lid and switch of heat source | Raise the alarm, close galley door and wait for the fire teams to arrive |
| 4264 | Which is not a functional requirement embodied in the regulations in order to achieve the fire safety objectives set out in SOLAS. | detection of any fire in the zone of origin | prohibits the use of combustible materials | containment and extinction of any fire in the space of origin | division of the ship into main vertical and horizontal zones by thermal boundaries |
| 4265 | Which of the Code provides international specific engineering standards for fire fighting equipments. | FSS | FSA | FFS | FAS |
| 4266 | Which is not a functional requirement to detect a fire from a space of and to provide for alarm for safe escape and fire-fighting activity? | manually operated call points | fire teams | fixed fire detection and fire alarm system installations | fire patrols |
| 4267 | A term of maximum temperature at which a given gas can be liquified by pressure i.e. Tank vessel cargo of ammonia 256 degrees fahrenheit. | Flammable pressure | Critical pressure | Flammable temperature | Critical temperature |
| 4268 | The combustion elements in a fuel are carbon ( C ), hydrogen (H2) and which other element? | Nitrogen (N) | Sulphur (S) | None of the above. | Halon |
| 4269 | Cooling of compartment boundaries where fire has occurred should be continued until: | ignition temperature is approached | flash point is approached | ambient temperature is approached | Reid vapor pressure is attained |
| 4270 | In which event should the Master take actions to protect and safeguard all persons on board his ship? | in an extreme weather conditions | during drydocking | during emergencies | when docking or undocking |
| 4271 | According to basic principles regarding fire protection the ship is to be divided in zones by structural and thermal boundaries which is: | In main horizontal zones | Main Fire zones in accordance with the ship's fire-fighting system | In main zones according to utilization (Accommodation , Machinery, Cargo) | in main vertical zones |
| 4272 | As a firefighting medium, CO2 can be dangerous under certain conditions as it can cause which of the following? | hallucinations | carbon monoxide poison | indigestion | burns and blistering |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 4273 | A term called when a temperature at which a liquid starts to and completely becomes a solid. | Solidifying Point | Melting Point | Boiling Point | Latent Heat |
| 4274 | There are currently two standards of classifying fires as A, B, C, and D, according to the nature of the burning material. One standard is ISO 3941, the other is: | IFPA 10 | NFPA 10 | NFPA 12 | IFPA 12 |
| 4275 | It is impossible to extinguish a shipboard fire, except in rare cases, by: | removing the fuel | removing the oxygen | removing the heat | interrupting the chain reaction |
| 4276 | If portable fire extinguisher has been partially discharged, it should be: | replaced in its proper location if weight loss is no more than 25% | replaced In Its proper location If weight loss Is no more than 15% | replaced in its proper location regardless of weight | labeled empty and recharged as soon as possible |
| 4277 | When attempting to enter a compartment containing fire, which method of applying water a most appropriate? | Sweeping the compartment with a fog stream | High-velocity fog stream directed toward the overhead | Solid stream directed toward the overhead | Straight stream directed into the center of the fire |
| 4278 | What does the FTP code relate to? | Testing and evaluating products that are flammable | fire safety requirements | temperature in the cargo hold | security requirements |
| 4279 | Prior to the release the CO2 system to the compartment in order to extinguish the fire, rest assure that all personnel has vacated the area. | The Chief Engineer immediately at his discretion release the CO2 system | The EOW shall release the CO2 system immediately | The 2nd Engineer shall release the CO2 system | The master shall order the release of CO2 system |
| 4280 | Combustible liquids are divided into how many classes? | three | one | two | four |
| 4281 | It is necessary to extend ventilators to the bilges in order: | to provide adequate air to the engine | to keep them dry, and thus easier to clean | to remove fuel vapors which are heavier than air | to cool the machinery areas |
| 4282 | In addition to weighing the cartridge, what other routine maintenance is required for a cartridge-operated dry chemical extinguisher? | Weigh the powder in the canister | Check the hose and nozzle for clogs | Check the external pressure gauge | Discharge small amount to see if it works |
| 4283 | Carbon Monoxide is considered as one of the most toxic gases onboard. One of its characteristics is: | highly corrosive | whitish in color | lighter than air | odorless |

| | | | | | |
|---|---|---|---|---|---|
| 4284 | A system where spread of disease on board can be controlled is also known as _____. | isolation | recovery | contagious | quarantine |
| 4285 | A tank vessel transferring non-flammable hazardous cargo in bulk must display warning signs. These signs must _____. | be visible from both sides and from forward and aft | use black lettering on a white background | indicate NO SMOKING | be displayed only while transferring cargo and fast to a dock |
| 4286 | Ambient air which you normally breathe contains what percent of oxygen? | 0.06 | 0.1 | 0.21 | 0.15 |
| 4287 | An emergency life-saving procedure that consist of recognizing and correcting failure of the respiratory or cardiovascular systems is called: | medical first Aid | medical Care | basic life support | advanced life support |
| 4288 | Combustion can occur inside a piping system such as a vapor collection header in a marine emission control system. Which of the following will not aid in this combustion process? | fuel | oxygen | ignition | nitrogen |
| 4289 | Compared to air the weight of liquefied petroleum gas vapors are which of the following? | heavier | variable | lighter | the same |
| 4290 | How often shall each member of the crew participate in an abandon ship -drill? | once a year | Once every month | once every 3 months | Once every week |
| 4291 | How often shall it be conducted an abandon ship drill and fire drill onboard a passenger ship? | tri-weekly (trice a month) | monthly | weekly | bi-weekly (twice a month) |
| 4292 | If some of the passengers are disabled i.e. using wheelchair cane blind etc. What precaution should the crew take? | none of the above | passengerswith disability will hire somecrew to accompany them | All passengers that will require some form for assistance in case of evacuation etc. must be registered so there can be sent crew to assist them if needed. | Passenger with some form for disability must travel with accompany and live in same cabin or next door. |

NOT FOR SALE

# OIC NAVIGATIONAL WATCH

| | | | | | |
|---|---|---|---|---|---|
| 4293 | If the meter needle of the oxygen indicator cannot be set to zero what should be done? | Check the sampling tube for blockage. | Replace the platinum filament. | Adjust the final reading by the amount the needle is displaced from zero. | Replace the batteries. |
| 4294 | If you hear air escaping from the lifer- aft just after it has inflated you should: | not panic since the safety valves allow excess pressure to escape | quickly hunt for the hole before the raft deflates | check the painter line attachment for a tear caused by the initial opening | check the sea anchor line for a tear if the seas are rough |
| 4295 | If you launch a lifeboat in heavy seas how should you lead the frapping lines to provide better control? | Around both falls from the embarkation deck | Around both falls at the main deck level | Around both falls at the mid deck level | Around both falls at the poop deck level |
| 4296 | In this view of the bridge deck on the fire control plan what is represented by the symbol on the aft bulkhead port side of the wheelhouse? | Emergency Lighting Board | Fire Alarm Panel | Copy of Fire Control Plan | Water Tight Door(s) Switch |
| 4297 | In what location MUST a duplicate fire control plan be located? | Engine Room | Gangway | Chief Mate s Office | Crew Mess |
| 4298 | Lines or gear not in use should be _____. | stowed anywhere | left on deck | secured or stowed out of the way | conspicuously marked |
| 4299 | Normally It is desirable to have screens on the vents of potable water tanks to _____. | stop insects from entering | prevent backups | filter the incoming air | prevent explosions |
| 4300 | Safety goggles or glasses are NOT normally worn when _____. | handling wire rope or natural fiber line | painting with a spray gun | using a rotary grinder with an installed shield | letting go the anchor |
| 4301 | Severe exposure to chlorine gas can be fatal. Chlorine gas is primarily a _____. | nerve paralyzing irritant | respiratory irritant | blood poisoning agent | skin burning agent |
| 4302 | What characteristic does a chemical additive to LPG give it? | Odor | Color | Density | Pressure |
| 4303 | What is the effect of high concentrations of H2S gas on personnel? | cause involuntary muscle contractions | cause eye inflammation | cause dizziness | paralyze your breathing system |
| 4304 | When a passenger vessel s plans must be permanently exhibited they are NOT required to show information on the _____. | fire detection system | lifeboats liferafts and life preservers | ventilation systems | portable fire extinguishers |

NOT FOR SALE

# OIC NAVIGATIONAL WATCH

| | | | | | |
|---|---|---|---|---|---|
| 4305 | When can a work vest be substituted for a lifejacket in the total count of the required lifesaving gear? | When working near or over the water | A work vest may never be counted as a lifejacket. | When it is approved by the Coast Guard | When stowed away from the ring buoys |
| 4306 | When working on a tow a good safety precaution is to _____. | walk on the top of covered barges when possible to avoid narrow gunwales | tighten ratchets outboard | carry loads on your inside shoulder when walking along the outside of a barge | always remove the toothpick after tightening the ratchet |
| 4307 | Which statement about the use of portable electric lights in petroleum product tanks is TRUE? | They must be explosion-proof self-contained battery-fed lamps. | The fixture must be explosion-proof and the line must have a ground wire. | They can be used only when the compartment is gas free. | No portable electric equipment of any type is allowed. |
| 4308 | With an increase in temperature the volume of flammable and combustible liquids _____. | remains constant if pressure remains constant | expands | remains constant | contracts |
| 4309 | You are on an inerted tankship. A low pressure alarm must be set to cause an audible and visual alarm if the pressure in the tanks cannot be maintained at more than _____. | 4 water gauge | 90% of the vacuum assist fan | 90% of the vacuum relief setting | 90% of the pressure drop through the scrubber |
| 4310 | A vessels steering systems should be checked: | immediately afte r departure | within 12 hours after departure | upon arrival on the next port | within 12 hours before departure |
| 4311 | Due to exposure to heat fatigue, heat stroke and dehydration, what is the maximum recommended effective temperature (ET) for full work load in enclosed spaces? | 27.5 deg C ET | 37.5 deg C ET | 30.5 deg C ET | 32.5 deg C ET |
| 4312 | A chemical additive to LPG gives it a characteristic _____. | odor | color | density | pressure |
| 4313 | A combustible gas indicator meter is calibrated to read the percentage of _____. | vapor to oxygen | the lower explosive limit concentration | the flammable limit concentration | the autoignition concentration |
| 4314 | A device fitted over the discharge opening on a relief valve consisting of one or two woven wire fabrics is called a flame _____. | screen | filter | restrictor | stopper |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 4315 | A faint is a brief loss of consciousness of no more than momentary duration caused by a temporary reduction in the flow of blood to the brain. How to prevent anyone from fainting? | given something to drink | treated for injuries until conscious | Tell the person to sit down and lean forward with the head between the knees taking deep breaths. | Try to keep the person in an upstanding position. |
| 4316 | A large metallic device mounted directly in the piping (usually located at the dock near the point where the vapor hose is attached) designed to prevent the passage of a rapidly moving flame through the piping is called a _____. | lame arrestor | detonation blocker | flame screen | detonation arrestor |
| 4317 | A piece of small stuff (small line) secured to an object to prevent it from going adrift is a _____. | keeper | lanyard | noose | stopper |
| 4318 | A pumproom is suspected of accumulating gases after a ventilation machinery breakdown. Where should the combustible gas indicator case be placed when testing the pumproom atmosphere for combustible gases? | In the upper level of the pumproom | In the middle level of the pumproom | In the lower level of the pumproom | On the deck outside the pumproom |
| 4319 | A vessel is underway with a work stage rigged over the side. A seaman may work on the stage but only when _____. | wearing a safety harness secured to the stage | the vessel is not making way | wearing a life jacket | wearing both a life jacket and a safety harness secured to the stage |
| 4320 | Abdominal Thrust is the name on a technique which involves applying a series of thrusts to the upper abdomen in an attempt to force air out of a choking casualty s lungs. How to perform this technique? | Neither A nor B | Remove the obstruction and restore normal breathing. | Stand behind the casualty. Clench your fist with the thumb inwards in the center of upper abdomen. Grasp your fist with your other hand and pull quickly inwards. | Either A or B |
| 4321 | According to SOLAS regulations which of the following is a requirement of the ventilation system of a pump room on a tanker? | the regulation makes exception for the ventilation requirements if a SCBA is mounted at the entrance | the regulation only applies to vessels built prior to Jan 1 1963 | the regulation only requires the installation of an exhaust fan | the regulation requires that the ventilation be non-spark producing |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 4322 | After checked for open airway given the first two inflations and checked the pulse to make sure that the heart is beating what is the rate of inflations given until natural breathing is restored? | 15 - 18 times per minute | 13 - 15 times per minute | 12 - 16 times per minute | 10 - 12 times per minute |
| 4323 | After each reading of an oxygen indicator the instrument should be purged with _____. | fresh air | CO2 | the tested compartment s air | water |
| 4324 | An oxygen indicator can be used to determine if there is _____. | combustible gases present | All of the above | sufficient oxygen in a compartment to support life | hydrogen gas present |
| 4325 | Any suspicious act or circumstances threatening the security of the ship or of a port facility or any ship/port interface or ship to ship activity. | Hijacked | terrorism | sabotage | security incident |
| 4326 | Anyone of the crew who is assigned to watch duties in ports has a number of important tasks to carry out. Which one of the listed tasks has to be included in the watchman s duties? | Checking the trim of the vessel. | Checking the moorings for tightness/slack. | Checking the mean draft of the vessel | checking the difference between forward and aft |
| 4327 | Aside from terrorist attacks on the ship which seldom happens the main threat is from people trying to: | assist stowaways | none of these choices | carry drugs on board | smuggle weapons and explosives |
| 4328 | Asphyxia is generally limited to enclosed spaces and the deficiency of breathable air in an enclosed space can occur with any of the following conditions. Indicate the condition that will NOT cause asphyxia. | Where rusting of internal tank surfaces has taken place. | When 21% of oxygen is present. | Where large quantities of inert gas is present. | When large quantities of cargo vapor is present |
| 4329 | At night while the ship is tied up to the dock a fire breaks out in a cargo hatch. After sounding the alarm what should the person on watch do? | Send a person to summon the shore authorities | fight the fire alone | sound the alarmand closethe hatch | Begin fighting the fire immediately |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 4330 | At what latest time shall doors side scuttles gangway doors cargo- and coaling ports and other openings which are to be kept closed watertight at sea be closed at the start of the voyage? | after entering open waters | after leaving the port | before leaving the port | before entering open waters |
| 4331 | Does the Master have an obligation to assist in towing of a vessel when unqualified obligation to assist persons in distress exist? | Master has no obligations to assist in towing of a vessel in distress but may do so when taken necessary precautions in coordination with Chief Engineer and Company Claim Manager. | master is the over incharge and has the obligations in the towing party | any of these options | Master has no obligations to assist in towing of a vessel. |
| 4332 | For how long should a tank be ventilated when people are working inside? | for at least 30 minutes. | For as long as people are working in the tank. | for at least 120 minutes. | for at least 60 minutes. |
| 4333 | When should training in personal survival techniques be given? | Before being employed. | After one period at sea. | After joining the ship. | During the first week on board. |
| 4334 | If water is rising in the bilge of a survival craft, your should first: | Abandon the survival craft | Check the cracks in the hull | Check the bilge drain plug | Shift all personnel to the stern |
| 4335 | Which one of the listed routine test and inspections of life-saving appliances is not required by the regulations? | Inspection of life-saving appliances, including lifeboat equipment shall be carried out monthly to ensure they are complete and in good order | Survival crafts and rescue boats with launching appliances shall be visually inspected weekly to ensure they are ready for use | general emergency alarm to be tested daily | lifeboat engines to be run for at least 3 minutes every week |
| 4336 | A lifejacket should be provided with_____ . | a light | a whistle and a light | On ships built after February 1992 all lifejackets should be fitted with a light | a whistle |
| 4337 | Every inflatable life raft , inflatable lifejacket and hydrostatic release units shall be serviced_____ | every 36 months. | every 18 months. | every 12 months. | every 24 months. |

| | | | | | |
|---|---|---|---|---|---|
| 4338 | If there are a number of survivors in the water after abandoning ship, they should _____. | form a raft by lashing their life preservers together | send the strongest swimmer to shore for assistance | form a small circular group to create a warmer pocket of water in the center of the circle | tie themselves to the unit so they wont drift with the current |
| 4339 | To keep injured survivors warm in the water after abandoning ship, they should _____. | be placed in the middle of a small circle formed by the other survivors in the water | sip water at intervals of fifteen minutes | float on their backs with their arms extended for maximum exposure to the air | remove their life preservers and hold on to the uninjured survivors |
| 4340 | You have abandoned ship and are in charge of a liferaft. How much water per day should you permit each occupant to drink after the first 24 hours? | 1 pint | 1 gallon | 1 can | 1 quart |
| 4341 | On an oceangoing vessel, for each person a lifeboat (without desalting kits) is certified to carry, the boat must be supplied with _____. | a life preserver | 2 pounds of condensed milk | a signaling whistle | 3 liters of water |
| 4342 | You are at sea in an inflatable liferaft. In high latitudes, the greatest danger is _____. | hypothermia caused by cold temperature | asphyxiation due to keeping the canopy closed | collapse of the raft due to cold temperatures | starvation |
| 4343 | You have just abandoned ship and boarded a raft. After the raft is completely inflated you hear a whistling noise coming from a safety valve. You should _____. | plug the safety valve | remove the safety valve and replace it with a soft patch | not become alarmed unless it continues for a long period of time | unscrew the deflation plugs |
| 4344 | You have abandoned ship in a life raft. Which of the following actions should you take? | organize a lookout system | Join up with any other survival craft and stream the sea anchor | Organize a watch system, post as a lookout, tie up with other survival craft if possible, and stream the sea anchor | start paddling in the direction of the nearest land |
| 4345 | Spreading oil on the open sea has the effect of _____. | diminishing the height of the seas | preventing the wave crests from breaking | increasing the height of the seas | lengthening the distance between successive crests |
| 4346 | If you are forced to abandon ship in a lifeboat, you should _____. | head for the nearest land | remain in the immediate vicinity | head for the closest sea-lanes | vote on what to do, so all hands will have a part in the decision |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 4347 | If, for any reason, it is necessary to abandon ship while far out at sea, it is important that the crew members should _____. | get away from the area because sharks will be attracted to the vessel | separate from each other as this will increase the chances of being rescued | immediately head for the nearest land | remain together in the area because rescuers will start searching at the vessels last known position |
| 4348 | What is the percentage of oxygen in a typical sample of uncontaminated air? | 18% | 12% | 15% | 21% |
| 4349 | What is meant by the term overhaul in firefighting? | Smother the fire with a blanket or similar object | Break up solid objects to ensure that any deep seated fires are extinguished | Cover the fire with foam | Slow down the spread of fire by cooling adjacent structures |
| 4350 | In the event of fire in the crews quarter, one of your first act is to: | Close all ventillation to the quarters | Ventilate the quarters | Attempt to put out the fire by portable fire-extinguisher | Prepare to abandonship |
| 4351 | An instrument used to detect explosive gas/air mixtures, usually measures the concentration in terms of the lower explosive limit, and is known as a _____. | combustible gas indicator | gas absorption detector | flame safety lamp | toxic vapor meter |
| 4352 | The best method of extinguishing a class A fire is to _____. | smother the fire with foam | smother the fire with CO2 | cool the substance below its ignition temperature | remove oxygen from the area |
| 4353 | The most likely place for a fire to start through the process of spontaneous combustion is in _____. | radio room | an electrical room | Galley | battery room |
| 4354 | Combustible material which is stored adjacent to a compartment where there is a fire, may also be ignited. This ignition can occur by _____. | heat conduction of combustion gases | heat convection through the bulkheads | direct radiation emitted by the adjacent fire | heat radiated from the bulkhead by the adjacent fire |
| 4355 | Where in accommodation spaces shall smoke detectors be located? (SOLAS II-2/13.2.2) | In all crew and passenger cabins | In messrooms, public lounges and other public rooms | In stairways, corridors and escape routes | Near ventilation ducts throughout the accommodation spaces |
| 4356 | Why is it necessary to cool the bulkheads, decks, and overheads surrounding an involved compartment fire? | Prevent oxygen from reaching the flames. | Prevent the fire from spreading by heat conduction. | Cool the metal below its ignition temperature. | Form a dense coating of smothering steam. |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 4357 | While underway, fire break out in the forward part of the vessel. Whenever practicable, what will be the first thing you will do if your are on watch? | Abandonship to windward | Put the vessels stern into the wind | Call for assistance | Keep going on half spead |
| 4358 | When taking samples of a tank atmosphere with an explosimeter, you should _____. | avoid sampling in the vicinity of deep webs to prevent false readings | only sample around the deck longitudinals as gases are lighter than air | sample as much of the tank as possible, especially at the bottom | sample only near the ullage openings as all vapors accumulate there |
| 4359 | Which of the following methods should be used to prevent a class A fire in a topside compartment, with steel bulkheads, from spreading to the adjacent compartments? | Sweep the exterior bulkheads with water fog until steam is no longer produced, secure the nozzle, and repeat as necessary. | Sweep the exterior bulkheads with a solid stream of water until the fire is reportedly extinguished. | Sweep the exterior bulkheads with water fog until the fire is reportedly extinguished. | Sweep the exterior bulkheads with a solid stream of water until steam is no longer produced, secure the nozzle, and repeat as necessary. |
| 4360 | A vapor sample is drawn into the combustible gas indicator. The needle deflects to the explosive range of the scale and then returns to rest at 20%. What does this indicate? | The concentration of combustible vapor in the sample is above the upper explosive limit. | The indicator is improperly calibrated. | The concentration of combustible vapor in the sample is twenty percent. | The concentration of combustible vapor in the sample is twenty percent of its lower explosive limit. |
| 4361 | A fire is considered under control when _____. | all hands are at their fire stations | the fire is contained and no longer spreading | the fixed systems are activated | all firefighting equipment is at the scene |
| 4362 | When entering a burning compartment equipped with a fire hose and an all-purpose nozzle, you should first direct _____. | the high velocity fog at the deck to cool it for entry | a straight stream aimed at the flames of the fire | the high velocity fog into the center of the fire | the high velocity fog at the overhead to absorb heat |
| 4363 | The most likely place for a fire to start through the process of spontaneous combustion is in _____. | the pressure tanks | the fuel oil tanks | the oily rag bin | an electrical switchboard |
| 4364 | A combustible gas indicator is used to determine _____. | the amount of CO2 present in flue gas | if there is sufficient oxygen to support life | the toxicity of flammable gases or vapors | the presence of flammable gases or vapors in the air |
| 4365 | Radiation can cause a fire to spread by _____. | heated gases flowing through ventilation systems | transmitting the heat of a fire through the ships metal | the transfer of heat across an unobstructed space | burning liquids flowing into another space |

| | | | | | |
|---|---|---|---|---|---|
| 4366 | A drip tray containing oil is on fire. The only fire fighting equipment available is water hose with spray jet/spray nozzle. How, if at all, should you attempt to put out this fire using water? | The water can be applied in a fine spray starting from the front in a sweeping motion. | Water should not be used on any type of oil fire. | Water should be applied to the oil in a single jet only. | Water should be applied in a jet to the back of the fire. |
| 4367 | A definite advantage in the use of water as a fire extinguishing agent is its ability to _____. | vaporize and rapidly expand as water absorbs heat | absorb smoke and gases as water is converted from liquid to vapor | rapidly contract as water is converted from liquid to vapor | alternate expansion and contraction as water in liquid state becomes vapor |
| 4368 | The most practical method of extinguishing a class A fire, involving burning dunnage, is to use _____. | chemical foam | a hand portable CO2 extinguishers | Purple K powder and light water | water |
| 4369 | First, second, and third degree burns are classified according to the: | Size of the burned area | Area of the body burned | Source of heat causing the burn | Layers of skin affected |
| 4370 | The ABC-rules are an important part of the First Aiders know how. What does the First Aid ABC-rules stands for? | Adults Behind Children | Anything But Continuation | A Better Control | Airway Breathing Circulation |
| 4371 | A seaman has a small, gaping laceration of the arm that is not bleeding excessively. What can be done as an alternative to suturing to close the wound? | Use temporary stitches of sail twine. | Wrap a tight bandage around the wound. | Apply butterfly strips, then a sterile dressing. | Apply a compression bandage. |
| 4372 | A shipmate suffers a heart attack and stops breathing. You must: | Make the victim as comfortable as he could be | Let him lie on his side | Administer oxygen immediately | Check his pulse and start CPR |
| 4373 | Before CPR is started, you should _____. | establish an open airway | Insure the victim is conscious | treat any bleeding wounds | make the victim comfortable |
| 4374 | In reviving a person who has been overcomed by gas fumes, which of the following would you AVOID doing? | Keeping him warm and comfortable | Applying artificial respiration and massage | Giving stimulants | Prompt removal of the patient from the suffocating atmosphere |
| 4375 | As with heat burns the damage of frostbite /hypothermia may be either superficial or deep, and the affected tissues may be destroyed. What kind of first aid should be given a person with frostbite ? | Hand or body heat the affected parts skin-to-skin (e.g. frozen hand in persons opposite armpit...) | Rub the affected area. | Heat the affected area with hot-water bottles. | Give the casualty a cigarette. |

NOT FOR SALE

| | | | | | |
|---|---|---|---|---|---|
| 4376 | A person slowly feel more sleepy and thirsty. The skin become very dry and there is a sweet taste of the breath. The glucose reaction shows positive. What kind of medicine will the person need as soon as possible? | A glass of cold milk | Nothing at all | Insulin | Sugar lump, sugar drink or something sweet |
| 4377 | Treatment of burns and scalds depends on the severity of the injury. What is the correct thing to do for minor burns and scalds? | Break blisters, remove any loose skin or foreign objects from the injured area. | Remove all sticky clothing from the casualty. | Apply lotions, ointments or fat to the injury. | Place the injured part under slowly running cold water for at least 10 minutes, but preferably until the pain is gone. If no water is available, use any cold, harmless liquid. |
| 4378 | A device used to immobilize fractures and help prevent bone displacement is: | Tourniquet | Splint | Stretcher | Bandage |
| 4379 | The MOST important element in administering CPR is: | Starting the treatment quickly | Having the proper equipment for the process | Treating for traumatic shock | Administering of oxygen |
| 4380 | First aid treatment for small cuts and open wounds is to _____. | lay the patient down and cover the wound when the bleeding stops | apply a hot towel to purge the wound, then medicate and cover it | apply an ice pack to the wound and cover it when the bleeding stops | stop the bleeding, clean, medicate, and cover the wound |
| 4381 | The primary objective of First Aid is: | To give life | To help a patient | To prevent further injury | To alleviate pain |
| 4382 | When giving first aid you should avoid _____. | Unnecessary haste and appearance of uncertainty | Touching the patient before washing your hands | Any conversation with the patient | Instruction by standers |
| 4383 | A tourniquet should be used to control bleeding ONLY _____. | when all other means have failed | to prevent bleeding from minor wounds | when the victim is unconscious | with puncture wounds |
| 4384 | Fire and abandon ship stations and duties may be found on the _____. | shipping articles | muster List | crewmans duty list | Certificate of Inspection |
| 4385 | What is a contingency plan for ships? | Plan for next voyage | Plan for safety preparedness | Plan for maintenance and repair | Loading plan for general cargo |
| 4386 | Which of the following is FALSE why there may not be enough oxygen in an enclosed space or tank? | tank may have been coated with preservatives | oxygen is depleted as oxidation may have taken place | enclosed as it is, no proper circulation of air | cargo inside may have absorb the oxygen |

| | | | | | |
|---|---|---|---|---|---|
| 4387 | Injuries resulting from slips and falls constitute the largest percentage of accidents that occur in the catering department. What shall be done to reduce this high accident rate? | Ensure that slippery substances are not left where several persons are expected to be around. | Keep the floors and decks free from fat and grease. | Do not wash off all rubbish to prevent persons slipping. | Install thermostat to avoid water from freezing to ice. |

NOT FOR SALE