

# broker-worker

The read-only proxy between BullionEdge Pro and your MetaTrader account.

Free tier is plenty: Cloudflare gives 100,000 Worker requests a day, and this caches for 30 seconds, so a desk open all day is a few hundred.

---

## Why it exists at all

MetaTrader has no browser-reachable API. Reading an account means a service that holds a terminal open for you — **MetaApi** — and that service authenticates with a token.

**The token cannot go in the app.** Anything shipped to a browser is public, and "obfuscated" is not a category. It lives here as a Worker secret instead, and the browser only ever knows a URL and an account id.

---

## Before you start

1. A MetaApi account with your MT4/MT5 account provisioned. Copy the **\*\*account id and note the region\*\*** it deployed to.
2. **Give MetaApi the investor password, not the master one.** MetaTrader issues a read-only investor password alongside your real one — it shows balance, equity and history and it cannot trade. Anything holding the master password can move your money.
3. Node installed.

---

## Deploy

```
cd tools/broker-worker
npx wrangler login
npx wrangler secret put METAAPI_TOKEN
npx wrangler deploy
```

Then edit **wrangler.jsonc** and set **ALLOWED\_ACCOUNTS** to your account id, and **METAAPI\_REGION** to the region MetaApi shows. Deploy again.

**ALLOWED\_ACCOUNTS** is not optional and the Worker refuses to serve without it. The account id arrives from the browser, and your token can read every account under it — so an empty list means anyone who finds the URL can enumerate ids and read your other accounts through your own proxy.

Wrangler prints a URL like **https://bullionedge-broker.<subdomain>.workers.dev**. Put that in **Settings** → **Broker sync** → **proxy endpoint**, add your account id, and press Test connection.

# Check it yourself

```
curl "https://bullionedge-broker.<subdomain>.workers.dev/account?account=<id>"
```

Expect balance and equity. Then check it refuses what it should:

```
curl -X POST "https://.../account?account=<id>"      # 405, read-only
curl "https://.../trade?account=<id>"                # 404, no such route
curl "https://.../account?account=not-yours"         # 404, not on the list
```

The last one returns the same "Unknown account" as a genuinely missing route, so the endpoint cannot be used to work out which ids are real.

## What it will not do

There is no order method, no path passthrough, and no POST handler. The obvious version of this proxy forwards `/*` to MetaApi and adds the auth header — that version is a remote control for your trading account published on the open internet, because MetaApi's trade endpoint is one POST away.

Here, two GET routes are hard-coded and everything else is refused before anything is read. You cannot place an order through this Worker because there is no code in it that could.

## The endpoints

**GET** `/account?account=<id>`

```
{ "balance": 1000, "equity": 984.2, "margin": 50, "freeMargin": 934.2,
  "marginLevel": 1968.4, "currency": "USD", "leverage": 500 }
```

Only the fields the app reads. Account names, server names and broker identifiers are dropped rather than republished through an anonymous endpoint.

**GET** `/history?account=<id>&days=30`

```
{ "deals": [{ "id": "P1", "positionId": "P1", "side": "long", "symbol": "XAUUSD",
  "volume": 0.2, "openPrice": 2640, "closePrice": 2670, "profit": 600,
  "commission": -7, "swap": -1.2, "closeTime": "2026-08-20T14:00:00.000Z" }] }
```

`days` is clamped to 1–180.

## The part that is easy to get wrong

MetaApi returns **deals**, not **trades**. One position produces an entry deal and an exit deal, and only the exit carries the realised profit. Importing them one-for-one doubles every trade — an entry booked as a break-even and an exit booked as the whole result — which halves the win rate while leaving both numbers looking entirely plausible.

The exit deal also carries the **opposite type** to the position: you close a buy by selling. Reading direction off it files every winning long as a winning short.

`pairDeals()` groups by `positionId`, takes the direction from the entry, the close price and time from the last exit, and sums profit, commission and swap across every leg so partial closes and both-sided commission are counted.

It is covered by `test/worker-pairing.test.mjs`, including a round-trip test asserting that what this Worker emits is what `domain/broker.js` accepts — the contract between the two, checked rather than assumed.

---

## Costs

Cloudflare Workers free tier: 100k requests/day. MetaApi is the paid part — check their current pricing; the cheapest tier is enough for one account, and the caching here keeps calls to roughly two a minute per open desk.