

Computation & optimization for Lasso - part 2

Luyang Han & Janosch Ott

ETH Zürich

22 October 2018

2018-10-02

Computation & optimization

Overview

1. Coordinate Descent
2. A Simulation Study
3. Least Angle Regression
4. ADMM
5. Minor-Max Algorithms
6. Alternating Minimizations
7. Screening Rules

2018-10-02

Computation & optimization

└ Overview

1. Coordinate Descent
2. A Simulation Study
3. Least Angle Regression
4. ADMM
5. Minor-Max Algorithms
6. Alternating Minimizations
7. Screening Rules

Alternating Direction Method of Multipliers (ADMM)

Problem

$$\underset{\beta \in \mathbb{R}^m, \theta \in \mathbb{R}^n}{\text{minimize}} \quad f(\beta) + g(\theta) \quad \text{subject to} \quad \mathbf{A}\beta + \mathbf{B}\theta = c$$

Lagrangian

$$f(\beta) + g(\theta) + \rho \|\mathbf{A}\beta + \mathbf{B}\theta - c\|_2^2$$

Augmented Lagrangian

$$L_\rho(\beta, \theta, \mu) := f(\beta) + g(\theta) + \langle \mu, \mathbf{A}\beta + \mathbf{B}\theta - c \rangle + \frac{\rho}{2} \|\mathbf{A}\beta + \mathbf{B}\theta - c\|_2^2$$

2018-10-02

Computation & optimization

└ ADMM

└ Alternating Direction Method of Multipliers
(ADMM)Augmented: scalar product with μ gets added

Problem

$$\underset{\beta \in \mathbb{R}^m, \theta \in \mathbb{R}^n}{\text{minimize}} \quad f(\beta) + g(\theta) \quad \text{subject to} \quad \mathbf{A}\beta + \mathbf{B}\theta = c$$

Lagrangian

$$f(\beta) + g(\theta) + \rho \|\mathbf{A}\beta + \mathbf{B}\theta - c\|_2^2$$

Augmented Lagrangian

$$L_\rho(\beta, \theta, \mu) := f(\beta) + g(\theta) + \langle \mu, \mathbf{A}\beta + \mathbf{B}\theta - c \rangle + \frac{\rho}{2} \|\mathbf{A}\beta + \mathbf{B}\theta - c\|_2^2$$

Dual variable update

$$\beta^{t+1} = \arg \min_{\beta \in \mathbb{R}^m} L_{\rho}(\beta, \theta^t, \mu^t)$$

$$\theta^{t+1} = \arg \min_{\theta \in \mathbb{R}^m} L_{\rho}(\beta^{t+1}, \theta, \mu^t)$$

$$\mu^{t+1} = \mu^t + \rho(\mathbf{A}\beta^{t+1} + \mathbf{B}\theta^{t+1} - c)$$

2018-10-02

Computation & optimization

└ ADMM

└ Dual variable update

Dual variable update

$$\begin{aligned}\beta^{t+1} &= \arg \min_{\beta \in \mathbb{R}^m} L_{\rho}(\beta, \theta^t, \mu^t) \\ \theta^{t+1} &= \arg \min_{\theta \in \mathbb{R}^m} L_{\rho}(\beta^{t+1}, \theta, \mu^t) \\ \mu^{t+1} &= \mu^t + \rho(\mathbf{A}\beta^{t+1} + \mathbf{B}\theta^{t+1} - c)\end{aligned}$$

ADMM - Why?

- convex problems with nondifferentiable constraints
- blockwise computation
 - sample blocks
 - feature blocks

2018-10-02

Computation & optimization

└ ADMM

└ ADMM - Why?

Details for blockwise computation in Exercise 5.12.

- convex problems with nondifferentiable constraints
- blockwise computation
 - sample blocks
 - feature blocks

ADMM for the Lasso

Problem in Lagrangian form

$$\underset{\beta \in \mathbb{R}^p, \theta \in \mathbb{R}^p}{\text{minimize}} \left\{ \frac{1}{2} \|\mathbf{y} - \mathbf{X}\beta\|_2^2 + \lambda \|\theta\|_1 \right\} \quad \text{such that } \beta - \theta = 0$$

Update

$$\beta^{t+1} = (\mathbf{X}^T \mathbf{X} + \rho \mathbf{I})^{-1} (\mathbf{X}^T \mathbf{y} + \rho \theta^t - \mu^t)$$

$$\theta^{t+1} = \mathcal{S}_{\lambda/\rho}(\beta^{t+1} + \mu^t/\rho)$$

$$\mu^{t+1} = \mu^t + \rho(\beta^{t+1} - \theta^{t+1})$$

where $\mathcal{S}_{\lambda/\rho}(z) = \text{sign}(z)(|z| - \frac{\lambda}{\rho})_+$.

Problem in Lagrangian form

$$\underset{\beta \in \mathbb{R}^p, \theta \in \mathbb{R}^p}{\text{minimize}} \left\{ \frac{1}{2} \|\mathbf{y} - \mathbf{X}\beta\|_2^2 + \lambda \|\theta\|_1 \right\} \quad \text{such that } \beta - \theta = 0$$

Update

$$\beta^{t+1} = (\mathbf{X}^T \mathbf{X} + \rho \mathbf{I})^{-1} (\mathbf{X}^T \mathbf{y} + \rho \theta^t - \mu^t)$$

$$\theta^{t+1} = \mathcal{S}_{\lambda/\rho}(\beta^{t+1} + \mu^t/\rho)$$

$$\mu^{t+1} = \mu^t + \rho(\beta^{t+1} - \theta^{t+1})$$

where $\mathcal{S}_{\lambda/\rho}(z) = \text{sign}(z)(|z| - \frac{\lambda}{\rho})_+$.

Computational cost: Initially $\mathcal{O}(p^3)$, which is a lot, for the SVD(singular value decomposition of \mathbf{X}), after that comparable to coordinate descent or composite gradient from earlier

Minorization-Maximization Algorithms (MMA)

- Problem: minimize $f(\beta)$ over $\beta \in \mathbb{R}^p$
for f possibly non-convex
- Introduce additional variable θ
- Use θ to majorize (bound from above) the objective
function to be minimized

Majorization-Minimization Algorithms work analogously.

2018-10-02

Computation & optimization

└ Minor-Max Algorithms

└ Minorization-Maximization Algorithms (MMA)

Minorization-Maximization
Algorithms (MMA)

- Problem: minimize $f(\beta)$ over $\beta \in \mathbb{R}^p$
for f possibly non-convex
- Introduce additional variable θ
- Use θ to majorize (bound from above) the objective
function to be minimized

Majorization-Minimization Algorithms work analogously.

MMA visually




Figure: Figure from [de Leeuw, 2015]

2018-10-02

Computation & optimization

└ Minor-Max Algorithms

└ MMA visually

MMA visually




Figure: Figure from [de Leeuw, 2015]

MMA analytically I

Def. $\Psi : \mathbb{R}^p \times \mathbb{R}^p \rightarrow \mathbb{R}$ **majorizes** f at $\beta \in \mathbb{R}^p$ if

$$\forall \theta \in \mathbb{R}^p \quad \Psi(\beta, \theta) \geq f(\beta)$$

with equality for $\theta = \beta$.

Minor-Max algorithm

- initialize β^0
- update with $\beta^{t+1} = \arg \min_{\beta \in \mathbb{R}^p} \Psi(\beta, \beta^t)$

2018-10-02

Computation & optimization

└ Minor-Max Algorithms

└ MMA analytically I

MMA analytically I

Def. $\Psi : \mathbb{R}^p \times \mathbb{R}^p \rightarrow \mathbb{R}$ **majorizes** f at $\beta \in \mathbb{R}^p$ if
 $\forall \theta \in \mathbb{R}^p \quad \Psi(\beta, \theta) \geq f(\beta)$

with equality for $\theta = \beta$.

Minor-Max algorithm

- initialize β^0
- update with $\beta^{t+1} = \arg \min_{\beta \in \mathbb{R}^p} \Psi(\beta, \beta^t)$

MMA analytically II

This scheme generates a sequence of β 's for which the cost $f(\beta^t)$ is nonincreasing, because

$$f(\beta^t) \stackrel{(i)}{=} \Psi(\beta^t, \beta^t) \stackrel{(ii)}{\geq} \Psi(\beta^{t+1}, \beta^t) \stackrel{(iii)}{\geq} f(\beta^{t+1})$$

where

(i) & (iii) Definiton of majorize

(ii) β^{t+1} is a minimizer of $\beta \mapsto \Psi(\beta, \beta^t)$

2018-10-02

Computation & optimization

└ Minor-Max Algorithms

└ MMA analytically II

for inequalities: show previous slide

This scheme generates a sequence of β 's for which the cost $f(\beta^t)$ is nonincreasing, because

$$f(\beta^t) \stackrel{(i)}{=} \Psi(\beta^t, \beta^t) \stackrel{(ii)}{\geq} \Psi(\beta^{t+1}, \beta^t) \stackrel{(iii)}{\geq} f(\beta^{t+1})$$

where

(i) & (iii) Definiton of majorize
(ii) β^{t+1} is a minimizer of $\beta \mapsto \Psi(\beta, \beta^t)$

Biconvexity

Let's consider an example ...

$$f(\alpha, \beta) = (1 - \alpha \beta)^2$$

2018-10-02

Computation & optimization
└ Alternating Minimizations
└ Biconvexity

Mathematica: 3D plot $(1-xy)^2$, x in $[-2,2]$, y in $[-2,2]$
The formula is a link.

Let's consider an example ...

$$f(\alpha, \beta) = (1 - \alpha \beta)^2$$

Biconvexity

Let's consider an example . . .

$$f(\alpha, \beta) = (1 - \alpha \beta)^2$$

Def. A function $f(\alpha, \beta) : \mathbb{R}^m \times \mathbb{R}^n \rightarrow \mathbb{R}$ is **biconvex**, if for each $\alpha \in \mathbb{R}^m$ the function $\alpha \mapsto f(\alpha, \beta)$ is convex and for each $\beta \in \mathbb{R}^n$ the function $\beta \mapsto f(\alpha, \beta)$ is convex. Analogously, a set $\mathcal{C} \subseteq \mathcal{A} \times \mathcal{B}$, for \mathcal{A}, \mathcal{B} convex sets, is called biconvex, if it is convex

2018-10-02

Computation & optimization

- Alternating Minimizations
 - Biconvexity

Mathematica: 3D plot $(1-xy)^2$, x in $[-2,2]$, y in $[-2,2]$
The formula is a link.

Let's consider an example . . .

$$f(\alpha, \beta) = (1 - \alpha \beta)^2$$

Def. A function $f(\alpha, \beta) : \mathbb{R}^m \times \mathbb{R}^n \rightarrow \mathbb{R}$ is biconvex, if for each $\alpha \in \mathbb{R}^m$ the function $\alpha \mapsto f(\alpha, \beta)$ is convex and for each $\beta \in \mathbb{R}^n$ the function $\beta \mapsto f(\alpha, \beta)$ is convex. Analogously, a set $\mathcal{C} \subseteq \mathcal{A} \times \mathcal{B}$, for \mathcal{A}, \mathcal{B} convex sets, is called biconvex, if it is convex

Alternate Convex Search

Block coordinate descent applied to α and β blocks

1. Initialize (α^0, β^0) at some point in the biconvex set to minimize over
2. For $t = 0, 1, 2, \dots$
 - (i) Fix $\beta = \beta^t$ and update $\alpha^{t+1} \in \arg \min_{\alpha \in \mathcal{C}_{\beta^t}} f(\alpha, \beta^t)$
 - (ii) Fix $\alpha = \alpha^{t+1}$ and update $\beta^{t+1} \in \arg \min_{\beta \in \mathcal{C}_{\alpha^{t+1}}} f(\alpha^{t+1}, \beta)$

For a function bounded from below, the algorithm converges to a partial optimum (i.e. as biconvexity, only optimal in one coordinate if the other coordinate is fixed).

Block coordinate descent applied to α and β blocks

1. Initialize (α^0, β^0) at some point in the biconvex set to minimize over
2. For $t = 0, 1, 2, \dots$
 - (i) Fix $\beta = \beta^t$ and update $\alpha^{t+1} \in \arg \min_{\alpha \in \mathcal{C}_{\beta^t}} f(\alpha, \beta^t)$
 - (ii) Fix $\alpha = \alpha^{t+1}$ and update $\beta^{t+1} \in \arg \min_{\beta \in \mathcal{C}_{\alpha^{t+1}}} f(\alpha^{t+1}, \beta)$

For a function bounded from below, the algorithm converges to a partial optimum (i.e. as biconvexity, only optimal in one coordinate if the other coordinate is fixed).

Dual Polytope Projection (DPP)

Suppose we want to calculate a lasso solution at $\lambda < \lambda_{\max}$.
The DPP rule discards the j^{th} variable if

$$\left| \mathbf{x}_j^T \mathbf{y} \right| < \lambda_{\max} - \|\mathbf{x}_j\|_2 \|\mathbf{y}\|_2 \frac{\lambda_{\max} - \lambda}{\lambda}$$

Sequential DPP rule

Suppose we have the lasso solution $\hat{\beta}(\lambda')$ at λ' and want to
screen variables for solutions at $\lambda < \lambda'$. We discard the j^{th}
variable if

$$\left| \mathbf{x}_j^T (\mathbf{y} - \mathbf{X} \hat{\beta}(\lambda')) \right| < \lambda' - \|\mathbf{x}_j\|_2 \|\mathbf{y}\|_2 \frac{\lambda_{\max} - \lambda}{\lambda}$$

$$\left| \mathbf{x}_j^T \mathbf{y} \right| < \lambda_{\max} - \|\mathbf{x}_j\|_2 \|\mathbf{y}\|_2 \frac{\lambda_{\max} - \lambda}{\lambda}$$

$$\left| \mathbf{x}_j^T (\mathbf{y} - \mathbf{X} \hat{\beta}(\lambda')) \right| < \lambda' - \|\mathbf{x}_j\|_2 \|\mathbf{y}\|_2 \frac{\lambda_{\max} - \lambda}{\lambda}$$

Global Strong Rule

Suppose we want to calculate a lasso solution at $\lambda < \lambda_{\max}$.

The global strong rule discards the j^{th} variable if

$$\left| \mathbf{x}_j^T \mathbf{y} \right| < \lambda - (\lambda_{\max} - \lambda) = 2\lambda - \lambda_{\max}$$

Sequential Strong Rule

Suppose we have the lasso solution $\hat{\beta}(\lambda')$ at λ' and want to screen variables for solutions at $\lambda < \lambda'$. We discard the j^{th} variable if

$$\left| \mathbf{x}_j^T (\mathbf{y} - \mathbf{X} \hat{\beta}(\lambda')) \right| < 2\lambda - \lambda'$$

2018-10-02

Computation & optimization

└ Screening Rules

└ Global Strong Rule

Global Strong Rule

Suppose we want to calculate a lasso solution at $\lambda < \lambda_{\max}$.
The global strong rule discards the j^{th} variable if

$$\left| \mathbf{x}_j^T \mathbf{y} \right| < \lambda - (\lambda_{\max} - \lambda) = 2\lambda - \lambda_{\max}$$

Sequential Strong Rule

Suppose we have the lasso solution $\hat{\beta}(\lambda')$ at λ' and want to screen variables for solutions at $\lambda < \lambda'$. We discard the j^{th} variable if

$$\left| \mathbf{x}_j^T (\mathbf{y} - \mathbf{X} \hat{\beta}(\lambda')) \right| < 2\lambda - \lambda'$$

References



Trevor Hastie, Robert Tibshirani, and Martin Wainwright (2015)
Statistical learning with sparsity: the Lasso and generalizations
CRC Press; Boca Raton, FL



Jan De Leeuw (2015)
Block Relaxation Methods in Statistics
doi.org/10.13140/RG.2.1.3101.9607 (last accessed: 02.10.18)

2018-10-02

Computation & optimization

└ Screening Rules

└ References

Comments . . .
Questions . . .
Suggestions . . .

2018-10-02

Computation & optimization
└ Screening Rules

Comments . . .
Questions . . .
Suggestions . . .

That's it.
Thanks for listening.

Fill out your feedback sheets!

2018-10-02

Computation & optimization
└ Screening Rules

That's it.
Thanks for listening.

Fill out your feedback sheets!