


# Optional Lab: Feature Engineering and Polynomial Regression ¶



## Goals

In this lab you will:

- explore feature engineering and polynomial regression which allows you to use the machinery of linear regression to fit very complicated, even very non-linear functions.

## Tools

You will utilize the function developed in previous labs as well as matplotlib and NumPy.

```
In [1]: import numpy as np
import matplotlib.pyplot as plt
from lab_utils_multi import zscore_normalize_features, run_gradient_descent
np.set_printoptions(precision=2) # reduced display precision on num
```

## Feature Engineering and Polynomial Regression Overview

Out of the box, linear regression provides a means of building models of the form:

$$f_{w,b} = w_0x_0 + w_1x_1 + \dots + w_{n-1}x_{n-1} + b \quad (1)$$

What if your features/data are non-linear or are combinations of features? For example, Housing prices do not tend to be linear with living area but penalize very small or very large houses resulting in the curves shown in the graphic above. How can we use the machinery of linear regression to fit this curve? Recall, the 'machinery' we have is the ability to modify the parameters  $\mathbf{w}$ ,  $\mathbf{b}$  in (1) to 'fit' the equation to the training data. However, no amount of adjusting of  $\mathbf{w}$ ,  $\mathbf{b}$  in (1) will achieve a fit to a non-linear curve.

## Polynomial Features

Above we were considering a scenario where the data was non-linear. Let's try using what we know so far to fit a non-linear curve. We'll start with a simple quadratic:  $y = 1 + x^2$

You're familiar with all the routines we're using. They are available in the lab\_utils.py file for review. We'll use np.c\_[ ]

## Numpy Column Stack


```
>>> np.c_[np.array([1,2,3]), np.array([4,5,6])]
array([[1, 4],
       [2, 5],
       [3, 6]])
>>> np.c_[np.array([[1,2,3]]), 0, 0, np.array([[4,5,6]])]
array([[1, 2, 3, ..., 4, 5, 6]])
```

```
In [2]: # create target data
x = np.arange(0, 20, 1)
y = 1 + x**2
X = x.reshape(-1, 1)

model_w,model_b = run_gradient_descent_feng(X,y,iterations=1000, alp

plt.scatter(x, y, marker='x', c='r', label="Actual Value"); plt.titl
plt.plot(x,X@model_w + model_b, label="Predicted Value"); plt.xlabe
```

```
Iteration      0, Cost: 1.65756e+03
Iteration    100, Cost: 6.94549e+02
Iteration    200, Cost: 5.88475e+02
Iteration    300, Cost: 5.26414e+02
Iteration    400, Cost: 4.90103e+02
Iteration    500, Cost: 4.68858e+02
Iteration    600, Cost: 4.56428e+02
Iteration    700, Cost: 4.49155e+02
Iteration    800, Cost: 4.44900e+02
Iteration    900, Cost: 4.42411e+02
w,b found by gradient descent: w: [18.7], b: -52.0834
```



Well, as expected, not a great fit. What is needed is something like  $y = w_0x_0^2 + b$ , or a **polynomial feature**. To accomplish this, you can modify the *input data* to *engineer* the needed features. If you swap the original data with a version that squares the  $x$  value, then you can achieve  $y = w_0x_0^2 + b$ . Let's try it. Swap  $X$  for  $X**2$  below:


```
In [3]: # create target data
x = np.arange(0, 20, 1)
y = 1 + x**2

# Engineer features
X = x**2      #<-- added engineered feature
```

```
In [4]: X = X.reshape(-1, 1) #X should be a 2-D Matrix
model_w, model_b = run_gradient_descent_feng(X, y, iterations=10000,

plt.scatter(x, y, marker='x', c='r', label="Actual Value"); plt.titl
plt.plot(x, np.dot(X, model_w) + model_b, label="Predicted Value"); p
```

```
Iteration      0, Cost: 7.32922e+03
Iteration    1000, Cost: 2.24844e-01
Iteration    2000, Cost: 2.22795e-01
Iteration    3000, Cost: 2.20764e-01
Iteration    4000, Cost: 2.18752e-01
Iteration    5000, Cost: 2.16758e-01
Iteration    6000, Cost: 2.14782e-01
Iteration    7000, Cost: 2.12824e-01
Iteration    8000, Cost: 2.10884e-01
Iteration    9000, Cost: 2.08962e-01
w,b found by gradient descent: w: [1.], b: 0.0490
```



Great! near perfect fit. Notice the values of  $w$  and  $b$  printed right above the graph:  $w$ ,  $b$  found by gradient descent:  $w$ : [1.],  $b$ : 0.0490. Gradient descent modified our initial values of  $w$ ,  $b$  to be (1.0, 0.049) or a model of  $y = 1 * x_0^2 + 0.049$ , very close to our target of  $y = 1 * x_0^2 + 1$ . If you ran it longer, it could be a better match.

## Selecting Features

Above, we knew that an  $x^2$  term was required. It may not always be obvious which features are required. One could add a variety of potential features to try and find the most useful. For example, what if we had instead tried:  $y = w_0x_0 + w_1x_1^2 + w_2x_2^3 + b$ ?


Run the next cells.

```
In [5]: # create target data
x = np.arange(0, 20, 1)
y = x**2

# engineer features .
X = np.c_[x, x**2, x**3] #<-- added engineered feature
```

```
In [6]: model_w,model_b = run_gradient_descent_feng(X, y, iterations=10000,
plt.scatter(x, y, marker='x', c='r', label="Actual Value"); plt.titl
plt.plot(x, X@model_w + model_b, label="Predicted Value"); plt.xlabel
```

```
Iteration      0, Cost: 1.14029e+03
Iteration    1000, Cost: 3.28539e+02
Iteration    2000, Cost: 2.80443e+02
Iteration    3000, Cost: 2.39389e+02
Iteration    4000, Cost: 2.04344e+02
Iteration    5000, Cost: 1.74430e+02
Iteration    6000, Cost: 1.48896e+02
Iteration    7000, Cost: 1.27100e+02
Iteration    8000, Cost: 1.08495e+02
Iteration    9000, Cost: 9.26132e+01
w,b found by gradient descent: w: [0.08 0.54 0.03], b: 0.0106
```



Note the value of  $w$ ,  $[0.08 \ 0.54 \ 0.03]$  and  $b$  is  $0.0106$ . This implies the model after fitting/training is:

$$0.08x + 0.54x^2 + 0.03x^3 + 0.0106$$

Gradient descent has emphasized the data that is the best fit to the  $x^2$  data by increasing the  $w_1$  term relative to the others. If you were to run for a very long time, it would continue to reduce the impact of the other terms.

Gradient descent is picking the 'correct' features for us by emphasizing its associated parameter

Let's review this idea:

- less weight value implies less important/correct feature, and in extreme, when the weight becomes zero or very close to zero, the associated feature is not useful in fitting the model to the data.

- above, after fitting, the weight associated with the  $x^2$  feature is much larger than the weights for  $x$  or  $x^3$  as it is the most useful in fitting the data.


## An Alternate View

Above, polynomial features were chosen based on how well they matched the target data. Another way to think about this is to note that we are still using linear regression once we have created new features. Given that, the best features will be linear relative to the target. This is best understood with an example.

```
In [7]: # create target data
x = np.arange(0, 20, 1)
y = x**2

# engineer features .
X = np.c_[x, x**2, x**3] #<-- added engineered feature
X_features = ['x', 'x^2', 'x^3']
```

```
In [8]: fig,ax=plt.subplots(1, 3, figsize=(12, 3), sharey=True)
for i in range(len(ax)):
    ax[i].scatter(X[:,i],y)
    ax[i].set_xlabel(X_features[i])
ax[0].set_ylabel("y")
plt.show()
```



Above, it is clear that the  $x^2$  feature mapped against the target value  $y$  is linear. Linear regression can then easily generate a model using that feature.

## Scaling features

As described in the last lab, if the data set has features with significantly different scales, one should apply feature scaling to speed gradient descent. In the example above, there is  $x$ ,  $x^2$  and  $x^3$  which will naturally have very different scales. Let's apply Z-score normalization to our example.

```
In [9]: # create target data
x = np.arange(0,20,1)
X = np.c_[x, x**2, x**3]
print(f"Peak to Peak range by column in Raw X:{np.ptp(X,axis=

# add mean_normalization
X = zscore_normalize_features(X)
print(f"Peak to Peak range by column in Normalized X:{np.ptp(X,axis=

Peak to Peak range by column in Raw X:[ 19 361 6859]
Peak to Peak range by column in Normalized X:[3.3 3.18 3.28]
```

Now we can try again with a more aggressive value of alpha:


```
In [10]: x = np.arange(0,20,1)
y = x**2

X = np.c_[x, x**2, x**3]
X = zscore_normalize_features(X)

model_w, model_b = run_gradient_descent_feng(X, y, iterations=100000

plt.scatter(x, y, marker='x', c='r', label="Actual Value"); plt.titl
plt.plot(x,X@model_w + model_b, label="Predicted Value"); plt.xlabel

Iteration      0, Cost: 9.42147e+03
Iteration    10000, Cost: 3.90938e-01
Iteration    20000, Cost: 2.78389e-02
Iteration    30000, Cost: 1.98242e-03
Iteration    40000, Cost: 1.41169e-04
Iteration    50000, Cost: 1.00527e-05
Iteration    60000, Cost: 7.15855e-07
Iteration    70000, Cost: 5.09763e-08
Iteration    80000, Cost: 3.63004e-09
Iteration    90000, Cost: 2.58497e-10
w,b found by gradient descent: w: [5.27e-05 1.13e+02 8.43e-05], b:
123.5000
```



Feature scaling allows this to converge much faster.

Note again the values of  $\mathbf{w}$ . The  $w_1$  term, which is the  $x^2$  term is the most emphasized. Gradient descent has all but eliminated the  $x^3$  term.

## Complex Functions

With feature engineering, even quite complex functions can be modeled:


```
In [11]: x = np.arange(0,20,1)
y = np.cos(x/2)

X = np.c_[x, x**2, x**3, x**4, x**5, x**6, x**7, x**8, x**9, x**10, x**11, x**12, x**13, x**14, x**15, x**16, x**17, x**18, x**19]
X = zscore_normalize_features(X)

model_w, model_b = run_gradient_descent_feng(X, y, iterations=1000000)

plt.scatter(x, y, marker='x', c='r', label="Actual Value"); plt.title("Actual Value vs Predicted Value")
plt.plot(x, X@model_w + model_b, label="Predicted Value"); plt.xlabel("x")
```

```
Iteration      0, Cost: 2.20188e-01
Iteration 100000, Cost: 1.70074e-02
Iteration 200000, Cost: 1.27603e-02
Iteration 300000, Cost: 9.73032e-03
Iteration 400000, Cost: 7.56440e-03
Iteration 500000, Cost: 6.01412e-03
Iteration 600000, Cost: 4.90251e-03
Iteration 700000, Cost: 4.10351e-03
Iteration 800000, Cost: 3.52730e-03
Iteration 900000, Cost: 3.10989e-03
w,b found by gradient descent: w: [ -1.34 -10.      24.78   5.96 -12.
49 -16.26  -9.51   0.59   8.7   11.94
 9.27   0.79 -12.82], b: -0.0073
```



## Congratulations!

In this lab you:

- learned how linear regression can model complex, even highly non-linear functions using feature engineering
- recognized that it is important to apply feature scaling when doing feature engineering

In [ ]: