

Bold amber marks (.hl-ops) on the ATIS body, METAR, TAF, and every extra card on the TAF tab (SIGMET, G-AIRMET, PIREPs, NAS delay, SNOWTAM). They are a scan aid only. They do not change official minima, and they are not a substitute for the chart or the ATIS itself.

Wind

- **Tailwind $\geq$ 9 kt (rounded), using the greater of mean and gust. Fully variable wind with no direction is treated as a pure tail.**
Example LANDING RWY 06 · WIND 240 DEG, 9 KT
Not marked WIND 240 DEG, 8 KT on RWY 06
- **Crosswind $>$ 20 kt (rounded), same speed (mean or gust).**
Example LANDING RWY 06 · WIND 150 DEG, 21 KT
Not marked WIND 150 DEG, 20 KT
- **Strong wind on any heading, including on the nose: mean $\geq$ 30 kt or gust $\geq$ 35 kt. Whole group. Spoken GUSTS / MAX as well.**
Example 24032G45KT WIND 240 DEG, 32 KT GUSTS 40 MAX 40
Not marked 24029KT on RWY 24 (headwind) GUSTS 18 MAX 18
- **TAF-tab SIGMET, G-AIRMET, PIREPs, NAS delay, and SNOWTAM use the same scanner. Unit-only strong wind (no direction) counts. Isolated TS, EMBD, SFC WND, MT OBSC, named TC, PIREP TB, MOD TO SEV.**
Example SFC WIND 50KT SFC WND TS TC BIPARJOY /TB SEV MOD TO SEV
Not marked MOV NE 25KT a bare taxiway TC
- **Gusty coded group when gust minus mean $>$ 10 kt (gust digits only, unless the whole group already qualifies above).**
Example 24012G24KT (the G24)
Not marked spread of 10 kt or less, unless mean/gust already strong
- **VRB sector bound more than 90° from the paired runway heading.**
Example variable sector that includes a tail or strong cross on that runway
Not marked a bound still within 90° of the runway

Altimeter / QNH

- **QNH below 990 hPa, or altimeter below 29.23 inHg.**
Example Q0987 QNH 987 HPA A2912 ALTIMETER 29.12
Not marked Q0990 Q1013 QNH 1003HPA A2992

Runway braking

- **Braking action POOR, NIL, UNRELIABLE, MEDIUM TO POOR, or LESS THAN POOR.**
Example BRAKING ACTION POOR BA NIL POOR BRAKING ACTION
Not marked BRAKING ACTION GOOD BA GOOD FAIR / MEDIUM alone

Blowing sand and dust

- **Blowing (and drifting) sand or dust. Duststorm / sandstorm already counted.**
Example BLSA BLDU BLOWING SAND BLOWING DUST DS SS
Not marked plain SA or DU without BL/DR moderate rain RA

Arrival minima (DA, MDA, OCH)

- **Decision / descent / obstacle-clearance heights on the arrival ATIS: DA, DH, MDA, MDH, OCA, OCH plus a height. Spoken Decision Altitude/Height, Minimum Descent Altitude/Height, Obstacle Clearance Altitude/Height.**
Example DA 250 FT MDA 450 FT OCH 186 DECISION HEIGHT 200 FT
Not marked density altitude DA1,800 runway type LDA
- **Minima changed or withdrawn: RAISED, INCREASED, AMENDED, REDUCED, NOT AUTHORIZED / NA. CAT II/III not authorized.**
Example DA 250 FT RAISED TO 350 APPROACH MINIMUMS RAISED TO 400 FEET ILS MINIMA NOT AUTHORIZED
Not marked an unchanged published DA with no height and no change phrase

Weather, vis, ceiling, temperature

- **Present-weather group if it is heavy (+), contains TS, or contains hail GR / small hail GS. Whole token.**
Example +TSRAGR TSRA SHGR +RA
Not marked RA -RA BR
- **Ceiling BKN / OVC / VV below 400 ft. VV/// counts. Spoken CEILING / CIG / CLOUD BASE. SCT/FEW are not ceiling.**
Example BKN003 OVC002CB VV/// CEILING 300 FT
Not marked BKN004 SCT003 CEILING 400 FT
- **Prevailing vis and RVR below 550 m (CAT I RVR floor). M0550 (less than 550) counts.**
Example 0400 R27L/0500 R27L/M0550 VIS 500 M 1/4SM
Not marked 0550 R27L/0550 0800 1/2SM
- **Temperature $\leq 10^{\circ}\text{C}$, or heat $> 35^{\circ}\text{C}$. METAR TT/Td and TAF TX/TN are always Celsius. US D-ATIS (K*, PANC, PHNL, TJSJ) speaks Fahrenheit: mark only above 95°F .**
Example 36/18 TX36/2706Z TN08/2622Z TEMPERATURE 38 TEMPERATURE 96 at KMIA
Not marked 35/18 TX31 TEMPERATURE 32 TEMPERATURE 88 at KMIA
- **Fog-risk dewpoint: $|T - T_d| \leq 2^{\circ}\text{C}$ and the lightest wind in the copy is below 5 kt.**
Example dewpoint digits next to a near-calm wind
Not marked the same spread with 5 kt or more
- **Other hazards already in the scanner: TS, CB, TCU, WS / LLWS, FZRA/FZDZ, SN/BLSN/DRSN, icing, turbulence, VA, hail, SNOWTAM / ice / slush wording, LIFR/IFR, birds, CLOSED / CLSD / INOP / OTS.**
Example WS CB FZRA BLSN BIRDS RWY 24L CLOSED
Not marked ordinary FEW/SCT clouds NSW
- **Runway condition code digits 0-5 in a 6/6/6 group (6 is dry and stays unmarked).**
Example 3/3/2
Not marked 6/6/6
- **ATIS ident letter; in-use runway numbers from the arrival/departure extract.**
Example ATIS K RWY 06
Not marked a runway number that is not in use in that copy

Rebuild the same way in js/hl.js. Do not invent a second set of thresholds. A sitting on GearUp is not a chart amendment.