# 1 Problem Setup

As input, we are given a graph  $G = (V_G, E_G)$ , where each vertex is a geographic position  $s_i \in S^2$ , and each edge (i, j) has an associated (Olivier-Ricci) curvature  $R_{i,j} \in (-2,1)$  and an associated latency  $t_{i,j} \in \mathbb{R}_{\geq 0}$ .

Intuitively, we want to return a surface in  $\mathbb{R}^3$  that is the graph of a function  $\rho: \overline{S^2} \to \mathbb{R}_{>0}$  whose geodesics  $g_{i,j}$  between  $s_i$  and  $s_j$  (and their missing  $\rho$ -coordinates) have length  $\phi_{i,j}$  that is in a linear relationship with the latency.

The strategy to realize this intuition is to create a mesh  $M = (V_M, E_M)$  supported on a subset of  $S^2$  that contains our input positions. We use a standard half-edge setup, so that  $E_M$  is a set of ordered pairs (edges are directed). Let P be the support. Then for each  $s_i \in P$ , we want to assign a  $\rho_i \in \mathbb{R}_{>0}$ , which in turn gives a point  $v_i = (s_i, \rho_i) \in V$ . This setup is made explicit in mesh/sphere.py.

A similar setup is found in mesh/rectangle.py, where we use  $[0,1]^2$  instead of  $S^2$ . In general, this setup just requires that the position of any mesh vertex is controlled by a single scalar parameter.

# 2 Objective/Loss Functions

To enforce that the mesh approximates our desired surface, we define the objective functions

$$\mathcal{L}_{\text{geodesic}}(M) \triangleq \sum_{e \in E_G} (\text{least squares residual of edge } e)^2,$$

$$\mathcal{L}_{\text{smooth}}(M) \triangleq -\rho^{\mathsf{T}} L_C \rho,$$

$$\mathcal{L}_{\text{curvature}}(M) \triangleq \sum_{\substack{v \in V_M \\ v \text{ close to } (i,j)}} (\kappa(v) - R_{i,j})^2,$$

$$\mathcal{L}(M) \triangleq \lambda_{\text{geodesic}} \mathcal{L}_{\text{geodesic}}(M) + \lambda_{\text{curvature}} \mathcal{L}_{\text{curvature}}(M) + \lambda_{\text{smooth}} \mathcal{L}_{\text{smooth}}(M),$$

where the  $\lambda$ 's are tunable hyperparameters. The other variables will be defined in the upcoming subsections. Our goal is then to minimize  $\mathcal{L}(M)$ .

Note that the loss functions (particularly the geodesic and total ones) also have a dependence on the measured latencies. We omit that as a written parameter because they are treated as fixed (we are really optimizing over the manifold, not over the measured latencies).

## 2.1 Laplacian

Some mesh notation first. If i and j are two indices vertices for which  $(v_i, v_j) \in E_M$ , let c(i, j) be the index such that  $v_i \to v_j \to v_{c(i,j)}$  traces a triangle counterclockwise. Note that this index exists and is unique assuming we have a mesh without boundary. On a mesh with boundary, if no c(i, j) exists, then the half-edge  $(v_i, v_j)$  lies on the boundary.

We also write  $\partial M$  to represent the boundary of our mesh. Abusing notation, we can write things like  $v_i \in \partial M$  or  $(v_i, v_j) \in \partial M$ .

We define the following variables:

$N_{i,j}$	Outward normal of triangle $v_i \to v_j \to v_{c(i,j)}$
$A_{i,j}$	Area of triangle $v_i \to v_j \to v_{c(i,j)}$
$D_{i,j}$	Vertex triangle areas; diagonal
$\theta_{i,j}$	Measure of $\angle v_i v_{c(i,j)} v_j$
$L_C^{ m N}$	Cotangent operator with zero-Neumann boundary condition
$L_C^{\mathrm{D}}$	Cotangent operator with zero-Dirichlet boundary condition
$L_C$	Cotangent operator in the no-boundary case; sparse

## 2.1.1 Forward Computation

We have the following (standard) definition of the Laplace-Beltrami operator on a mesh:

$$N_{i,j} = \left(v_i - v_{c(i,j)}\right) \times \left(v_j - v_{c(i,j)}\right),$$
  
$$A_{i,j} = \frac{1}{2} \|N_{i,j}\|_2,$$

$$D_{i,j} = \begin{cases} \frac{1}{3} \sum_{k} A_{i,k} & \text{if } i = j, \\ (v_i, v_k) \in E_M \\ 0 & \text{otherwise,} \end{cases}$$
 
$$\cot\left(\theta_{i,j}\right) = \frac{\left(v_i - v_{c\left(i,j\right)}\right) \cdot \left(v_j - v_{c\left(i,j\right)}\right)}{2A_{i,j}},$$
 
$$if \left(v_i, v_j\right) \in \partial M,$$
 
$$\frac{1}{2} \cot\left(\theta_{i,j}\right) & \text{if } \left(v_i, v_j\right) \in \partial M,$$
 
$$\frac{1}{2} \left(\cot\left(\theta_{i,j}\right) + \cot\left(\theta_{j,i}\right)\right) & \text{if } \left(v_i, v_j\right) \in E_M \text{ and } \left(v_j, v_i\right) \in E_M,$$
 
$$\left(L_C^N\right)_{i,j} = \begin{cases} \frac{1}{2} \left(\cot\left(\theta_{i,j}\right) + \cot\left(\theta_{j,i}\right)\right) & \text{if } \left(v_i, v_j\right) \in E_M \text{ and } \left(v_j, v_i\right) \in E_M, \end{cases}$$
 
$$\left(L_C^D\right)_{i,j} = \begin{cases} \frac{1}{2} \left(\cot\left(\theta_{i,j}\right) + \cot\left(\theta_{j,i}\right)\right) & \text{if } \left(v_i, v_j\right) \in E_M, v_i \notin \partial M, \text{ and } v_j \notin \partial M, \\ \left(v_i, v_i\right) \in E_M \end{cases}$$
 otherwise.

Flipping our attention back to meshes without boundary, the two definitions above coincide, so we can write

$$L_C = L_C^{\text{Neumann}} = L_C^{\text{Dirichlet}}$$

### 2.1.2 Reverse Computation

For the ease of notation, assume that we are using the spherical setup, so  $v_{\ell} = \rho_{\ell} s_{\ell}$ . We compute

$$\begin{split} \frac{\partial v_i}{\partial \rho_\ell} &= \begin{cases} s_i & \text{if } \ell = i, \\ 0 & \text{otherwise,} \end{cases} \\ \frac{\partial N_{i,j}}{\partial \rho_\ell} &= \begin{cases} \left(v_{c(i,j)} - v_j\right) \times \frac{\partial v_\ell}{\partial \rho_\ell} & \text{if } \ell = i, \\ \left(v_i - v_{c(i,j)}\right) \times \frac{\partial v_\ell}{\partial \rho_\ell} & \text{if } \ell = j, \\ \left(v_j - v_i\right) \times \frac{\partial v_\ell}{\partial \rho_\ell} & \text{if } \ell = c(i,j), \\ 0 & \text{otherwise,} \end{cases} \\ \frac{\partial A_{i,j}}{\partial \rho_\ell} &= \frac{1}{4A_{i,j}} N_{i,j} \cdot \frac{\partial N_{i,j}}{\partial \rho_\ell}, \\ \left(\frac{\partial D}{\partial \rho_\ell}\right)_{i,j} &= \begin{cases} \frac{1}{3} \sum_{\substack{k \\ (v_i, v_k) \in E_M \\ 0}} \frac{\partial A_{i,k}}{\partial \rho_\ell} & \text{if } i = j, \\ \end{cases} \end{split}$$

$$\frac{\partial}{\partial \rho_{\ell}}\cot(\theta_{i,j}) = \begin{cases} \frac{\left(v_{j} - v_{c(i,j)}\right) \cdot \frac{\partial v_{\ell}}{\partial \rho_{\ell}} - 2\cot(\theta_{i,j}) \frac{\partial A_{i,j}}{\partial \rho_{\ell}}}{2A_{i,j}} & \text{if } \ell = i, \\ \frac{\left(v_{i} - v_{c(i,j)}\right) \cdot \frac{\partial v_{\ell}}{\partial \rho_{\ell}} - 2\cot(\theta_{i,j}) \frac{\partial A_{i,j}}{\partial \rho_{\ell}}}{2A_{i,j}} & \text{if } \ell = j, \\ \frac{\left(2v_{c(i,j)} - v_{i} - v_{j}\right) \cdot \frac{\partial v_{\ell}}{\partial \rho_{\ell}} - 2\cot(\theta_{i,j}) \frac{\partial A_{i,j}}{\partial \rho_{\ell}}}{2A_{i,j}} & \text{if } \ell = c(i,j), \\ 0 & \text{otherwise,} \end{cases} \\ \left(\frac{\partial L_{C}^{N}}{\partial \rho_{\ell}}\right)_{i,j} = \begin{cases} \frac{1}{2} \frac{\partial}{\partial \rho_{\ell}} \cot(\theta_{i,j}) + \frac{\partial}{\partial \rho_{\ell}} \cot(\theta_{j,i}) \\ \frac{1}{2} \frac{\partial}{\partial \rho_{\ell}} \cot(\theta_{i,j}) + \frac{\partial}{\partial \rho_{\ell}} \cot(\theta_{j,i}) \\ 0 & \text{otherwise,} \end{cases} & \text{if } (v_{i}, v_{j}) \in \partial M, \\ \left(v_{i}, v_{k}) \in E_{M} + \frac{\partial}{\partial \rho_{\ell}} \cot(\theta_{j,k}) + \sum_{k} \frac{\partial}{\partial \rho_{\ell}} \cot(\theta_{k,i}) \\ 0 & \text{otherwise,} \end{cases} \\ \left(\frac{\partial L_{C}^{D}}{\partial \rho_{\ell}}\right)_{i,j} = \begin{cases} \frac{1}{2} \left(\frac{\partial}{\partial \rho_{\ell}} \cot(\theta_{i,j}) + \frac{\partial}{\partial \rho_{\ell}} \cot(\theta_{j,i}) \right) & \text{if } (v_{i}, v_{j}) \in E_{M} \\ \left(v_{i}, v_{k} \in E_{M}\right) \\ 0 & \text{otherwise,} \end{cases} \end{cases} \\ \left(\frac{\partial L_{C}^{D}}{\partial \rho_{\ell}}\right)_{i,j} = \begin{cases} \frac{1}{2} \left(\frac{\partial}{\partial \rho_{\ell}} \cot(\theta_{i,j}) + \frac{\partial}{\partial \rho_{\ell}} \cot(\theta_{j,i}) \right) & \text{if } (v_{i}, v_{j}) \in E_{M}, v_{i} \notin \partial M, \text{and } v_{j} \notin \partial M, \\ \left(v_{i}, v_{k} \in E_{M}\right) \end{cases} & \text{otherwise.} \end{cases}$$

#### 2.2Geodesic Distance via the Heat Method

Here are the variables used for this part of the computation:

$\gamma$	Set of points in $V_M$
$\overline{h}$	Mean half-edge length
$\delta^{\gamma}$	Heat source (indicator on $\gamma$ )
$u^{\gamma,N}$	Heat flow with zero-Neumann boundary condition
$u^{\gamma,\mathrm{D}}$	Heat flow with zero-Dirichlet boundary condition
$u^{\gamma}$	Heat flow
$q_{i,j}^{\gamma}$	Intermediate value for computation
$\frac{q_{i,j}^{\gamma}}{m_{i,j}^{\gamma}}$	Intermediate value for computation
$X_{i,j}^{\gamma}$	Unit vector in same direction as $\nabla u_{i,j}^{\gamma}$
$\frac{\overline{X_{i,j}^{\gamma}}}{p_{i,j}^{\gamma}}$	Intermediate value for computation
$\phi^{\gamma}$	Vector of geodesic distances

#### 2.2.1 Forward Computation

Say we want to find the geodesic distances to a set of points  $\gamma \subseteq V_M$ . Following the Crane et al's Heat Method, we use the (approximate) heat flow  $u^{\gamma}$ , where

$$h = \text{TODO},$$

$$\delta^{\gamma} = \begin{cases} 1 & \text{if } v_i \in \gamma, \\ 0 & \text{if } v_i \notin \gamma, \end{cases}$$

$$u^{\gamma,N} = \left(D - h^2 L_C^N\right)^{-1} \delta^{\gamma},$$

$$u^{\gamma,D} = \left(D - h^2 L_C^D\right)^{-1} \delta^{\gamma},$$

$$u^{\gamma} = \frac{1}{2} \left( u^{\gamma,N} + u^{\gamma,D} \right),$$

$$q_{i,j}^{\gamma} = u_i^{\gamma} \left( v_{c(i,j)} - v_j \right),$$

$$m_{i,j}^{\gamma} = q_{i,j}^{\gamma} + q_{j,c(i,j)}^{\gamma} + q_{c(i,j),i}^{\gamma},$$

$$(\nabla u^{\gamma})_{i,j} = N_{i,j} \times m_{i,j}^{\gamma},$$

$$X_{i,j}^{\gamma} = -\frac{(\nabla u^{\gamma})_{i,j}}{\left\| (\nabla u^{\gamma})_{i,j} \right\|_2},$$

$$p_{i,j} = \cot(\theta_{i,j}) \left( v_j - v_i \right),$$

$$(\nabla \cdot X^{\gamma})_i = \frac{1}{2} \sum_{k} \left( p_{i,k} - p_{c(i,k),i} \right) \cdot X_{i,k}^{\gamma},$$

$$\phi^{\gamma} = \left( L_C^{N} \right)^+ \cdot (\nabla \cdot X^{\gamma}).$$

Here,  $(L_C^{\rm N})^+$  is the pseudoinverse of  $L_C^{\rm N}$  (this is necessary as it is singular).

Note that we're being careful about which pieces have a dependence on  $\gamma$ , as we can reuse certain computations if we want to compute distances from multiple sources. We can get the pairwise distance matrix (that is, get rid of the  $\gamma$  dependence) from

$$\phi_{i,j} = \left(\phi^{\left\{v_j\right\}}\right)_i.$$

### 2.2.2 Reverse Computation

Note that c(i, c(j, i)) = j. This is helpful for reindexing some sums (in particular, the one for  $\nabla \cdot X$ ). We then have the following partial derivatives:

$$\begin{split} \frac{\partial h}{\partial \rho_{\ell}} &= \text{TODO}, \\ \frac{\partial u^{\gamma, N}}{\partial \rho_{\ell}} &= - \left(D - h^{2} L_{C}^{N}\right)^{-1} \left(\frac{\partial D}{\partial \rho_{\ell}} - 2h \frac{\partial h}{\partial \rho_{\ell}} L_{C}^{N} - h^{2} \frac{\partial L_{C}}{\partial \rho_{\ell}}\right) u^{\gamma, N}, \\ \frac{\partial u^{\gamma, D}}{\partial \rho_{\ell}} &= - \left(D - h^{2} L_{C}^{D}\right)^{-1} \left(\frac{\partial D}{\partial \rho_{\ell}} - 2h \frac{\partial h}{\partial \rho_{\ell}} L_{C}^{D} - h^{2} \frac{\partial L_{C}}{\partial \rho_{\ell}}\right) u^{\gamma, D}, \\ \frac{\partial u^{\gamma}}{\partial \rho_{\ell}} &= \frac{1}{2} \left(\frac{\partial u^{\gamma, N}}{\partial \rho_{\ell}} + \frac{\partial u^{\gamma, D}}{\partial \rho_{\ell}}\right), \\ \frac{\partial q_{i, j}^{\gamma}}{\partial \rho_{\ell}} &= \begin{cases} \frac{\partial u_{i}^{\gamma}}{\rho_{\ell}} \left(v_{c(i, j)} - v_{j}\right) - u_{i}^{\gamma} \frac{\partial v_{\ell}}{\partial \rho_{\ell}} & \text{if } \ell = j, \\ \frac{\partial u_{i}^{\gamma}}{\rho_{\ell}} \left(v_{c(i, j)} - v_{j}\right) + u_{i}^{\gamma} \frac{\partial v_{\ell}}{\partial \rho_{\ell}} & \text{if } \ell = c(i, j), \\ \frac{\partial u_{i}^{\gamma}}{\rho_{\ell}} \left(v_{c(i, j)} - v_{j}\right) & \text{otherwise}, \end{cases} \\ \frac{\partial m_{i, j}^{\gamma}}{\partial \rho_{\ell}} &= \frac{\partial q_{i, j}^{\gamma}}{\partial \rho_{\ell}} + \frac{\partial q_{j, c(i, j)}^{\gamma}}{\partial \rho_{\ell}} + \frac{\partial q_{c(i, j), i}^{\gamma}}{\partial \rho_{\ell}}, \\ \frac{\partial (\nabla u^{\gamma})_{i, j}}{\partial \rho_{\ell}} &= \frac{\partial N_{i, j}}{\partial \rho_{\ell}} \times m_{i, j}^{\gamma} + N_{i, j} \times \frac{\partial m_{i, j}^{\gamma}}{\partial \rho_{\ell}}, \\ \frac{\partial X_{i, j}^{\gamma}}{\partial \rho_{\ell}} &= -\frac{1}{\left\| (\nabla u^{\gamma})_{i, j} \right\|_{2}} \left(I - X_{i, j}^{\gamma} \left(X_{i, j}^{\gamma}\right)^{\mathsf{T}}\right) \frac{\partial (\nabla u^{\gamma})_{i, j}}{\partial \rho_{\ell}}, \end{cases} \end{cases}$$

$$\begin{split} \frac{\partial p_{i,j}}{\partial \rho} &= \begin{cases} \left(\frac{\partial}{\partial \rho_{\ell}} \cot\left(\theta_{i,j}\right)\right) \left(v_{j} - v_{i}\right) - \cot\left(\theta_{i,j}\right) \frac{\partial v_{\ell}}{\rho_{\ell}} & \text{if } \ell = i, \\ \left(\frac{\partial}{\partial \rho_{\ell}} \cot\left(\theta_{i,j}\right)\right) \left(v_{j} - v_{i}\right) + \cot\left(\theta_{i,j}\right) \frac{\partial v_{\ell}}{\rho_{\ell}} & \text{if } \ell = j, \\ \left(\frac{\partial}{\partial \rho_{\ell}} \cot\left(\theta_{i,j}\right)\right) \left(v_{j} - v_{i}\right) & \text{if } \ell = c(i,j), \\ 0 & \text{otherwise,} \end{cases} \\ \frac{\partial (\nabla \cdot X^{\gamma})_{i}}{\partial \rho_{\ell}} &= \frac{1}{2} \sum_{k} \left(\left(\frac{\partial p_{i,k}}{\partial \rho_{\ell}} - \frac{\partial p_{c(i,k),i}}{\partial \rho_{\ell}}\right) \cdot X_{i,k}^{\gamma} + \left(p_{i,k} - p_{c(i,k),i}\right) \cdot \frac{\partial X_{i,k}^{\gamma}}{\partial \rho_{\ell}}\right), \\ \frac{\partial \phi^{\gamma}}{\partial \rho_{\ell}} &= \left(L_{C}^{N}\right)^{+} \left(\frac{\partial (\nabla \cdot X^{\gamma})}{\partial \rho_{\ell}} - \frac{\partial L_{C}^{N}}{\partial \rho_{\ell}}\phi^{\gamma}\right). \end{split}$$