Neurons of a Looped Language Model: Neuron-Level Interpretability and Pre-Registered Causal Steering of Ouro-1.4B

Libor Burian

Code: https://github.com/BurnyCoder/looped-transformers-llms-neuron-mechanistic-interpretability

Abstract. Looped language models apply the same layers several times per token, so every MLP neuron fires once per loop. We study the 135,168 SwiGLU neurons of Ouro-1.4B, which loops its 24 layers four times, at the level of single neurons, following Goodfire's raw-neuron methodology.

Atlas. From 8M tokens we build per-loop top-context tables.
- Strongest activations concentrate in early loops (41% at loop 1, 13% at loop 4).
- Same-token activations of a neuron at loops 1 and 4 correlate with median $r = 0.54$, and consecutive loops converge (r: 0.65, 0.84, 0.94).

Pre-registered test. We selected candidates on discovery prompts only and committed a pre-registration before using held-out prompts. Clamping a single neuron at all loops was compared against unsteered generation and against 100 random neurons from the same layer, with Holm correction and fluency and degeneracy guards.
- **All five** pre-registered neurons (phonetics, non-duality, pedagogy, forum answers, electron orbitals) steer 48-token continuations toward their concept: mean Δconcept-score 0.13–0.18, d_z 0.99–1.61, Holm-adjusted Wilcoxon $p \leq 1.1 \times 10^{-15}$, beating 99–100 of 100 random neurons, perplexity ratio ≤ 1.83.
- The effects are concept-specific, confirmed by a blind LLM judge, and replicate at identical indices in the reasoning-tuned Ouro-1.4B-Thinking.

Follow-ups (post hoc).
- Clamping at any single loop barely steers ($\Delta C \leq 0.043$ versus 0.13–0.17 for all loops), so steering is strongly super-additive across loops, consistent with self-repair.
- Dose-response saturates, as predicted by the post-MLP RMSNorm.

Negative results.
- Perplexity-based fluency guards accept degenerate repetitions ("Fib Fib Fib…").
- Explanations from a local 9B model transfer across loops as well as within them, so this audit could not detect loop-specific function.

1 Introduction

Looped (recurrent-depth) language models apply one block of layers several times in sequence, which lets them spend more computation per token without adding parameters [1], [2], [3]. Ouro-1.4B [2] loops its entire 24-layer stack four times. Its model card reports performance matching 3–4B-parameter standard transformers. Mechanistic work on looped models has so far studied the residual stream:
- recurrent blocks converge to cyclic fixed points and repeat the "stages of inference" of feedforward models [4];
- residual-direction steering of Ouro-1.4B-Thinking works best at the last loop, and earlier injections are "rotated away" [5];
- per-execution-step refusal directions in Ouro-2.6B align from the second pass onward [6].

No published study we are aware of works at the level of **individual neurons** in a looped model.

Neurons are a natural unit for looped models for two reasons. First, a recent essay from Goodfire argues that most MLP neurons of modern models are already interpretable without a learned decomposition [7]. Second, weight sharing creates a test that has no analogue in a feedforward network: the same

neuron, with the same weights, is evaluated at every loop. It may do the same job each time, or it may be reused for different jobs at different depths.

We ask three questions:
1. What do Ouro's neurons respond to, and at which loop?
2. Does a neuron keep its function across loops?
3. Can clamping a **single** neuron change what the model writes, with statistical significance against pre-registered controls, including random neurons from the same layer clamped the same way?

Contributions.
- A neuron atlas covering all 135,168 Ouro-1.4B neurons, with per-loop top contexts and statistics.
- A pre-registered, paired steering test with permutation nulls built from random same-layer neurons, a multiplicity correction, a fluency guard, and power analysis on selection-free validation data.
- Measurements of loop structure: where neurons peak, and how similar their activations are across loops.
- Loop-resolved causal experiments: single-loop steering, test-time loop sweeps, and the saturation predicted by the sandwich norm.
- An interpretability audit of explanation transfer across loops.

Positive and negative results are both reported.

2 Related work

Looped and recurrent-depth language models. The models differ mainly in what they loop and how they inject the input:
- Huginn loops a middle block, with input injection and a randomly initialized latent state [1].
- Ouro loops the whole stack and learns an early-exit gate [2].
- Parcae stabilizes looping by constraining the spectral norm of the injection [3].

On the mechanistic side, [4] analyze fixed points and attention-mixing stages. Blog-length studies steer Ouro with residual-stream directions and find a last-loop advantage, along with apparent self-repair [5], [6]. Self-repair after ablations is also known in feedforward models [8].

Neuron-level interpretability. There are three strands relevant here:
- Explaining neurons from max-activating examples, possibly with an LLM: [9] and Delphi [10], which also introduced the detection scorer we use.
- Studies of specific neuron families: universal [11], confidence-regulation [12], dead/n-gram/positional [13], sparse-probing [14], and vocabulary-promoting value vectors [15].
- Goodfire's essay [7], which argues that most neuron poles of modern models have one main job. It reads, steers and ablates raw neurons, and compares ablations to random neurons from the same layers. We adopt that design and make it quantitative with pre-registered tests.

Steering evaluation. Activation addition [16] is the basic residual-stream steering method. AxBench [17] rates steered text for concept presence and fluency with an LLM judge; we use its prompts as a secondary metric. Our primary metric is LLM-free, so explanations cannot leak into their own evaluation.

Methodology. We follow common guidance on avoiding ML pitfalls [18]: disjoint selection and test data, pre-registration, multiplicity control, and reporting of negative results.

3 Method

3.1 Model and neuron definition

We study Ouro-1.4B [2] at revision `574fa66`. It has 24 decoder layers (d = 2048, 16-head MHA, SwiGLU MLP of width 5632, vocabulary 49,152). The whole stack is applied $T = 4$ times with shared weights. Each layer uses sandwich RMSNorm, and the residual stream is RMS-normalized after every loop.

We always read the output of the last loop (`exit_at_step = T-1`). The default early-exit path, which thresholds a cumulative exit distribution, disagreed with fixed last-loop exit on 0 of 2,048 held-out positions (8 chunks × 256), but fixing the exit makes every computation identical by construction. A **neuron** (ℓ, i) is element i of the SwiGLU activation entering `down_proj` in layer ℓ:

$$a_{\ell,i,t} = \text{silu}(g_i^\top x) \cdot (u_i^\top x)$$

Here x is the post-attention-normalized residual at loop t. There are $24 \times 5632 = 135{,}168$ neurons, and each fires once per loop. Activations are signed, so following [7] we treat the positive and negative **poles** of every neuron as separate units. Reading and editing use one forward pre-hook per `down_proj`; the loop index is the per-layer call count modulo T. Unit tests check the hook against a manual SwiGLU recomputation at every loop, confirm that identity edits leave the logits bit-identical, and confirm that cached decoding matches full forward passes.

3.2 Neuron atlas

We stream 8M tokens: FineWeb-Edu [19] (90%) plus OpenWebMath [20] (10%), packed into 256-token chunks. For every neuron and pole we keep the top-40 contexts, taking the maximum over positions and loops and recording the loop at which it occurs. We also keep the top-20 contexts at each loop, and per-loop moments and exceedance counts (computed on every 8th batch). The first 4 positions of each chunk are excluded.

3.3 Candidate selection on discovery data

Prompts are 12-token stems of WikiText-103 **test** paragraphs [21], a corpus disjoint from the atlas text. They are split once, with a fixed seed, into discovery (150), confirmatory (300) and reserve (300) sets.

Selection. From a random pool of 4,000 alive neurons (8,000 units), we embed each unit's top-20 contexts with bge-small-en-v1.5 [22] and rank units by coherence (mean pairwise cosine). Units whose top contexts share a single peak token at least 50% of the time are excluded as token detectors [13]. The 200 most coherent units are clamped at $\alpha \in \{1, 2, 4\}$ times their maximum activation, on 25 discovery prompts, to obtain a quick estimate of the effect. The ten best units that pass a perplexity guard are then **validated** on 100 different discovery prompts, so that the effect sizes entering the power analysis are not inflated by selection. A unit is eligible if its validation mean $\Delta C > 0$, its median perplexity ratio is at most 2, and its median steered distinct-2 is at least 0.6 (a degeneracy guard; see Section 4.2). The five eligible units with the largest validation d_z are pre-registered.

3.4 Steering intervention and primary metric

Steering clamps $a_{\ell,i,t} := c = \pm\alpha \cdot \max|a|$ (sign of the pole) at every position and, unless stated otherwise, every loop. Because the MLP write is RMS-normalized after `down_proj`, a single clamped neuron's contribution per layer and loop is bounded. As $|c| \to \infty$ the write tends to $\gamma \odot \text{sign}(c) \frac{w_i}{\text{rms}(w_i)}$, so the dose-response must saturate (scale $c^* \approx \|W_{\text{down}} a\| \,/\, \|w_i\|$).

For each prompt we sample $k = 3$ continuations of 48 tokens (temperature 0.7, top-p 0.9). Steered and unsteered runs share seeds and batch layout, so each steered sample is paired with an unsteered sample.

The **concept score** of a continuation is the cosine between its bge-small embedding and the unit's **contrastive concept direction** $u = \text{normalize}\big(\bar{e}_{\text{top}} - \bar{e}_{\text{random}}\big)$. Here $\bar{e}_{\text{top}}$ is the mean embedding of the unit's top-20 atlas contexts and $\bar{e}_{\text{random}}$ the mean over 2,000 random atlas contexts. The primary per-prompt statistic is ΔC, the steered minus unsteered score averaged over the k samples. It involves no LLM, so a label cannot leak into its own evaluation.

3.5 Pre-registered confirmatory test

Candidates, α, n, the tests and the decision rule were written to `reports/preregistration.md` and committed before any confirmatory prompt was used. The pipeline refuses to run the test otherwise.

- **Test 1:** one-sided Wilcoxon signed-rank on per-prompt ΔC.

- **Test 2:** random-neuron null [7]. $R = 100$ alive neurons from the candidate's layer are clamped at the same α times their own maximum on the same pole. Each is scored with the **candidate's** concept direction on the first 50 prompts, giving the empirical $p = (1 + \#\{\text{null} \geq \text{obs}\})/(R + 1)$ [23].
- **Multiplicity:** Holm [24] across the K candidates, separately for each test. $K \leq 5$ is forced because the smallest attainable permutation p, $1/101$, must be at most $0.05/K$.
- **Decision rule:** a neuron is a significant steering neuron iff both Holm-adjusted $p < 0.05$, the median perplexity ratio of steered to unsteered continuations (both scored by the unsteered model) is at most 2, and the median distinct-2 of steered continuations is at least 0.6.
- **Effect sizes:** d_z and matched-pairs rank-biserial r [25], with bootstrap 95% CIs.
- **Power:** n is chosen from the validation d_z by power analysis (one-sided paired t at $0.05/K$, power 0.9, divided by the Wilcoxon ARE of 0.955), clipped to [100, 300].

3.6 Secondary analyses (post hoc unless stated)

These analyses are not part of the decision rule:

- an all-MiniLM-L6-v2 concept score;
- distinct-2 [26];
- AxBench-style blind LLM ratings [17] from a local Qwen3.5-9B [27] served by llama.cpp [28];
- dose-response over α;
- zero-ablation of the neuron on its held-out top contexts versus 100 random same-layer ablations;
- **loop locus** (clamping at a single loop);
- **test-time loops** ($T = 1..8$).

The loop structure of all neurons is summarized by:

- the loop holding each neuron's strongest context;
- the Jaccard overlap of top-20 contexts between loops;
- per-neuron Pearson correlation of activations between loops on the same held-out tokens.

The interpretability audit asks the local LLM, using the Delphi explainer and detection scorer [10], to describe 150 neurons separately at loop 1 and loop 4, and scores each explanation on held-out contexts from the same and from the other loop.

4 Results

4.1 Model sanity and the neuron atlas

Held-out loss falls from 4.03 nats at $T = 1$ to 2.51 at the trained $T = 4$ (perplexity 12.3), and rises slightly when extrapolating to $T = 5..8$ (2.55–2.56). This matches the behavior described for Ouro [2].

- **Atlas.** 8M tokens, 72.5 min. No neuron is dead. Median $\max|a|$ is 0.64.
- **Peak location.** Strongest activations concentrate in early loops: the share of neurons whose top context occurs at loop 1, 2, 3, 4 is 41.0%, 29.7%, 16.7%, 12.7%.
- **Cross-loop similarity.** On 32,256 held-out tokens, the median per-neuron Pearson correlation between loop-1 and loop-4 activations is 0.54 (IQR 0.43–0.63). It rises with depth from ≈ 0 in layer 0 to 0.59–0.65 in layers 14–23.
- **Convergence.** Adjacent loops converge: median $r(1, 2) = 0.65$, $r(2, 3) = 0.84$, $r(3, 4) = 0.94$, consistent with fixed-point dynamics [4].
- **Top-context overlap** between loop 1 and loop 4 is much lower (Jaccard 0.01–0.19 by layer). This mostly reflects how sensitive top-k sets are to near-ties (Figure 1).




Figure 1: Loop structure of all 135,168 neurons. Left: share of neurons whose strongest atlas context occurs at each loop. Middle: Jaccard overlap of top-20 contexts between loops. Right: median same-token activation correlation between loops (held-out text).

4.2 Selection, and a failure mode of the fluency guard

Of 8,000 neuron poles, 21.2% are token detectors. The 200 most coherent of the remaining units were quick-steered.

The two units with the largest validated concept effects, an if-statement neuron (L19 N3901−, $d_z = 2.52$) and a Fibonacci neuron (L0 N2848+, $d_z = 2.33$), turned out to reach them by degenerating into "ififif…" and "Fib Fib Fib…". This degenerate text has **lower** perplexity under the unsteered model than normal continuations, so a perplexity guard alone accepts it. We added a distinct-2 guard (steered median $\geq$ 0.6; unsteered ≈ 0.95) before any confirmatory prompt was used, and recorded the amendment in the pre-registration.

4.3 Confirmatory test (H1, pre-registered)

Table 1 reports the pre-registered test.

All five candidates meet the decision rule, so H1 is supported.

- Wilcoxon $p \leq 1.1 \times 10^{-15}$ before correction for every neuron.
- Every bootstrap 95% CI of mean ΔC excludes zero.
- Each neuron's 50-prompt statistic exceeds all 100 (four neurons) or 99 of 100 (L4 N2104) random same-layer neurons clamped the same way. The candidates sit 7.3–12.1 null standard deviations above the null mean.
- The Holm-adjusted permutation $p = 0.0495$ is the smallest value attainable with $K = 5$ and $R = 100$. It reflects the resolution of the null, not a marginal effect.
- Effects are large: $d_z = 0.99$–1.61 and matched-pairs rank-biserial $r = 0.91$–0.99.
- The secondary MiniLM embedder agrees ($\Delta C = 0.108$–0.248).
- Steering costs fluency but stays within the guard: median perplexity ratio 1.58–1.83, and steered distinct-2 is 0.80–0.91 against ≈ 0.95 unsteered.

Neuron	α	Concept (top contexts)	mean ΔC [95% CI]	d_z	Holm p_{Wil}	p_{null} (Holm)	z vs null	PPL ratio
L18 N3066 −	1	phonetics, letters	0.179 [0.155, 0.204]	1.42	2.4e-17	0.0099 (0.0495)	12.1	1.58
L13 N1680 +	1	non-duality, dependent origination	0.141 [0.119, 0.163]	1.26	1.7e-16	0.0099 (0.0495)	11.3	1.62
L4 N2104 +	2	pedagogy	0.130 [0.112, 0.148]	1.43	2.5e-17	0.0198 (0.0495)	7.6	1.65
L6 N3344 −	4	forum "mark as accepted answer"	0.167 [0.147, 0.188]	1.61	2.4e-17	0.0099 (0.0495)	7.3	1.83
L18 N1735 −	2	electron orbitals, bonding	0.127 [0.103, 0.153]	0.99	1.1e-15	0.0099 (0.0495)	11.2	1.72

Table 1: Pre-registered confirmatory test on 100 held-out prompts × 3 paired samples. ΔC: change in concept score (bge-small). p_{null}: empirical p against 100 random same-layer neurons. z vs null is descriptive (post hoc). All five rows meet the decision rule. Source: `results/Ouro-1.4B/confirm.json`.




Figure 2: Mean ΔC with 95% bootstrap CIs (blue) and the 95th percentile of the random same-layer neuron null (orange tick) for each candidate.

Steered text visibly carries the concepts. The examples below are the first confirmatory prompt, sample 0:

- L18 N3066− (phonetics) continues "In the Philippines, Nepartak produced strong winds, heavy" with "rains, and severe flooding. The sounds of the letters /p/ and /t/ are softened. In the International Phonetic Alphabet (IPA) …".
- The unsteered model continues the same prompt with casualty and damage figures.
- L4 N2104+ (pedagogy) instead writes "The Role of an Educator: An educator, a dedicated instructor, plays a pivotal …".

4.4 Follow-up experiments (post hoc)

These analyses use 60 held-out prompts, 1 sample each.

Specificity. Steering neuron i and scoring concept j gives a matrix whose diagonal is the largest entry of each row, 1.4–3.8× the largest off-diagonal entry (Figure 3). The smallest margin pairs the forum "accepted answer" neuron with the programming concept, an overlap that is plausible for Q&A text.

Dose-response. ΔC rises monotonically with α and then plateaus, as the sandwich-norm bound predicts. Neurons with larger $c^*/\max|a|$ (2.2–2.6) keep rising up to $\alpha = 8$–16; those near 1 plateau from $\alpha \approx 2$–4. Clamping to the opposite sign has no effect ($|\Delta C| \leq 0.04$), so each concept lives on one pole. Perplexity ratio exceeds 2 for most neurons at $\alpha \geq 4$.

Loop locus (H2). Clamping a single loop barely steers: $\Delta C \leq 0.043$, against 0.13–0.17 for all four loops, for the five confirmed neurons. The four single-loop effects sum to 0–30% of the all-loop effect for four of them.

- Steering in a looped model is therefore strongly super-additive across loops. One injection is largely undone by the following loops, consistent with self-repair [5], [8].
- The exploratory if-statement neuron is the exception. Its last loop alone gives 56% of the full effect ($\Delta C = 0.176$, $p = 1.7 \times 10^{-10}$), while loops 1–3 give nothing, matching the last-loop advantage reported for residual-direction steering of Ouro [5].
- Clamping at loop 4 moves the final hidden state most (relative displacement 0.20–0.47, against 0.12–0.23 at loops 1–3).

Test-time loops (H3). Clamping at every loop while running $T = 1..8$:

- the concept effect is already present at $T = 1$ (ΔC 0.10–0.35);
- it stays roughly flat in T;
- next-token KL grows monotonically with T.

More loops add more injections and more distribution shift, but not proportionally more concept.

Necessity. Zero-ablating a neuron on its held-out top contexts increases the next-token loss beyond all 100 random same-layer ablations for 4 of 6 neurons (unadjusted $p = 0.0099$; $z = 3.1$–53.6). This is exploratory; correcting with Holm across six would give 0.059. Two confirmed neurons are sufficient for steering but not necessary for prediction, and ablating L6 N3344 even **improves** prediction ($z = -8.9$).




Figure 3: Steering specificity: mean ΔC on each concept (columns) when steering each neuron (rows). Diagonal entries dominate their rows.

4.5 Interpretability audit (H4)

Delphi explanations written by the local Qwen3.5-9B from 12 examples per loop detect held-out activating contexts above chance (balanced accuracy 0.60 vs 0.50 for shuffled explanations, $p = 1.4 \times 10^{-7}$). However, they transfer across loops as well as within a loop (same 0.60, cross 0.59; paired difference +0.012, $p = 0.20$, $n = 240$).

H4 (loop-specific explanations) is therefore not supported. Only about 20% of neurons reach balanced accuracy ≥ 0.75, so the weak explainer limits how sensitive this test can be, and the activation correlations above are the more sensitive evidence.

4.6 Replication on Ouro-1.4B-Thinking

The five neuron indices were tested unchanged in Ouro-1.4B-Thinking, which is Ouro-1.4B after supervised fine-tuning on about 8.3M reasoning examples. There was no re-selection.

Reasoning SFT barely moves the MLP neurons:

- the per-neuron cosine between base and Thinking weights is ≥ 0.993 for 99% of neurons in the relevant layers;
- the candidates' maximum activations change by at most 5.1%.

All five neurons steer the post-trained model with similar or larger effects:

- $\Delta C = 0.161$–0.180, against 0.127–0.179 in the base model (larger for four neurons; for L18 N3066 it is 0.171 against 0.179, within the confidence intervals);
- Holm-adjusted Wilcoxon $p \leq 2.1 \times 10^{-16}$;
- each neuron exceeds all 20 random same-layer neurons;
- the PPL ratio is at most 1.98.

4.7 LLM judge (secondary, pre-registered)

A local Qwen3.5-9B rated continuations of 50 confirm prompts using the AxBench concept and fluency templates [17]. Each continuation was rated by itself, in a shuffled order, so the judge was blind to condition.

Concept presence (0–2). The neuron's Qwen label served as the concept, and ratings rose from ≈ 0 unsteered to:

- 0.26 for L18 N3066−;
- 0.24 for L13 N1680+;
- 0.26 for L4 N2104+;
- 0.36 for L18 N1735−;
- 0.06 for L6 N3344−.

Paired one-sided Wilcoxon $p = 0.003$, 0.0007, 0.0007, 0.0001 and 0.042 respectively. All remain below 0.05 after Holm.

Fluency (0–2). Fluency fell from 1.50 to 0.90–1.17 (95% CIs of the paired differences exclude 0), which agrees with the perplexity cost.

The judge is strict: absolute concept ratings are low, and the forum-answer neuron (L6 N3344), whose concept is the most abstract, is the weakest by this measure. The ranking of neurons only partly matches the embedding metric.

5 Discussion

Single neurons are effective steering handles in a looped LM. Goodfire's essay argues that raw neurons are often clean, single-purpose units [7]. Our results support a narrower causal version of that claim for a looped model. Neurons chosen for coherent top contexts include units that steer generation toward their concept, and they do so far beyond random neurons from the same layer clamped the same way. The effect survives a change of embedding model and reasoning post-training, and it is specific to each neuron's own concept.

Looping makes steering cumulative. A clamp applied at one loop is largely undone by the remaining loops. Only repeated injection, at every pass through the shared weights, changes behavior. Steering a neuron at all four loops works well, while for four of the five confirmed neurons any single loop is nearly inert (for L13 N1680, single-loop effects are small but non-zero). This resembles the "rotated away" behavior reported for residual directions in Ouro [5] and is consistent with the convergence of the residual stream across loops (median same-token activation correlation between consecutive loops rises from 0.65 to 0.94).

The exception, the if-statement neuron, acts mainly at the last loop. That suggests the location of the effect depends on the neuron: some concepts are written late, close to the output, while others are maintained throughout.

The neuron's function is mostly, but not entirely, shared across loops. Same-token activations at loop 1 and loop 4 correlate at a median of 0.54. Neurons are therefore partly reused for different inputs at different depths, as the input distribution of every layer shifts from loop to loop. Explanations written by a local 9B model do not detect this difference (same-loop 0.60 vs cross-loop 0.59). With explainers this weak, activation statistics are the more sensitive instrument.

Fluency guards must catch repetition. Concept scores can be maximized by degenerate repetition, which a language model finds **easy** to predict. Perplexity-based fluency guards therefore pass exactly the worst outputs. A lexical-diversity guard, or an LLM fluency judge as in AxBench [17], is necessary.

6 Limitations

- **Scope.** One looped model family (Ouro-1.4B and its Thinking variant) and 5 confirmed neurons, chosen for steerability from a pool of 200 coherent units. These are existence claims and say nothing about how common steerable neurons are.
- **Metric.** The primary metric is an embedding-based concept score built from each neuron's own top contexts. It measures movement toward that contrastive direction, not human-judged concept presence. The LLM judge is a secondary check from a small local model.

- **Intervention.** We clamp the neuron at every position, including the prompt, and far beyond its natural activation pattern (α up to 4 for confirmation). Steering costs fluency (perplexity ratio 1.6–1.8).
- **Null resolution.** With $R = 100$ random neurons and $K = 5$, the permutation test's Holm-adjusted p cannot go below 0.0495. We report z-margins (7–12 SD) as descriptive support.
- **Post hoc analyses.** Follow-ups use 60 prompts and 1 sample. Ablation p-values are unadjusted. The T sweep beyond $T = 4$ is extrapolation.
- **Atlas size.** 8M tokens is far smaller than the 100M tokens used by Goodfire, so rare features are under-sampled.
- **Compute.** Everything ran on one 8 GB laptop GPU. The labeler is a 4-bit 9B model.

7 Conclusion

In Ouro-1.4B, a looped transformer that applies its 24 layers four times, we built a 135k-neuron atlas and ran a pre-registered, paired steering test with random same-layer neuron nulls. All five pre-registered neurons (phonetics, non-duality, pedagogy, forum answers, electron orbitals) steer generation toward their concept with large, statistically significant effects. They are specific to their own concepts, saturate with clamp strength as the sandwich norm predicts, and replicate in the reasoning-tuned Ouro-1.4B-Thinking.

Steering a neuron in a looped model requires clamping it at every loop. Single-loop interventions are mostly undone by the following loops. Neurons are largely reused across loops, but not identically: their same-token activation correlation between the first and last loop has a median of 0.54.

Bibliography

[1] J. Geiping *et al.*, "Scaling up Test-Time Compute with Latent Reasoning: A Recurrent Depth Approach," *arXiv preprint arXiv:2502.05171*, 2025, [Online]. Available: https://arxiv.org/abs/2502.05171

[2] R.-J. Zhu *et al.*, "Scaling Latent Reasoning via Looped Language Models," *arXiv preprint arXiv:2510.25741*, 2025, [Online]. Available: https://arxiv.org/abs/2510.25741

[3] H. Prairie, Z. Novack, T. Berg-Kirkpatrick, and D. Y. Fu, "Parcae: Scaling Laws For Stable Looped Language Models," *arXiv preprint arXiv:2604.12946*, 2026, [Online]. Available: https://arxiv.org/abs/2604.12946

[4] Á. Arroyo, J. Obando-Ceron, P. S. Castro, A. Courville, M. Bronstein, and X. Dong, "A Mechanistic Analysis of Looped Reasoning Language Models," *arXiv preprint arXiv:2604.11791*, 2026, [Online]. Available: https://arxiv.org/abs/2604.11791

[5] nesiacel, "A recurrent LLM is quite easy to interpret but complex to steer." [Online]. Available: https://www.lesswrong.com/posts/rzcJMpnehFBD686gj/a-recurrent-llm-is-quite-easy-to-interpret-but-complex-to

[6] M. Suiche, "Abliterating a Loop: Control Vectors Meet the Looped Transformer." [Online]. Available: https://msuiche.com/posts/abliterating-a-loop-control-vectors-meet-the-looped-transformer/

[7] N. Cammarata, C. Tigges, and T. Gogineni, "Neural Networks Are Already Clean." [Online]. Available: https://already-clean.goodfire.com/

[8] T. McGrath, M. Rahtz, J. Kramár, V. Mikulik, and S. Legg, "The Hydra Effect: Emergent Self-repair in Language Model Computations," *arXiv preprint arXiv:2307.15771*, 2023, [Online]. Available: https://arxiv.org/abs/2307.15771

[9] S. Bills *et al.*, "Language models can explain neurons in language models." [Online]. Available: https://openaipublic.blob.core.windows.net/neuron-explainer/paper/index.html

[10] G. Paulo, A. Mallen, C. Juang, and N. Belrose, "Automatically Interpreting Millions of Features in Large Language Models," *arXiv preprint arXiv:2410.13928*, 2024, [Online]. Available: https://arxiv.org/abs/2410.13928

[11] W. Gurnee *et al.*, "Universal Neurons in GPT2 Language Models," *arXiv preprint arXiv:2401.12181*, 2024, [Online]. Available: https://arxiv.org/abs/2401.12181

[12] A. Stolfo *et al.*, "Confidence Regulation Neurons in Language Models," *arXiv preprint arXiv:2406.16254*, 2024, [Online]. Available: https://arxiv.org/abs/2406.16254

[13] E. Voita, J. Ferrando, and C. Nalmpantis, "Neurons in Large Language Models: Dead, N-gram, Positional," *arXiv preprint arXiv:2309.04827*, 2023, [Online]. Available: https://arxiv.org/abs/2309.04827

[14] W. Gurnee, N. Nanda, M. Pauly, K. Harvey, D. Troitskii, and D. Bertsimas, "Finding Neurons in a Haystack: Case Studies with Sparse Probing," *arXiv preprint arXiv:2305.01610*, 2023, [Online]. Available: https://arxiv.org/abs/2305.01610

[15] M. Geva, A. Caciularu, K. R. Wang, and Y. Goldberg, "Transformer Feed-Forward Layers Build Predictions by Promoting Concepts in the Vocabulary Space," *arXiv preprint arXiv:2203.14680*, 2022, [Online]. Available: https://arxiv.org/abs/2203.14680

[16] A. M. Turner *et al.*, "Steering Language Models With Activation Engineering," *arXiv preprint arXiv:2308.10248*, 2023, [Online]. Available: https://arxiv.org/abs/2308.10248

[17] Z. Wu *et al.*, "AxBench: Steering LLMs? Even Simple Baselines Outperform Sparse Autoencoders," *arXiv preprint arXiv:2501.17148*, 2025, [Online]. Available: https://arxiv.org/abs/2501.17148

[18] M. A. Lones, "How to avoid machine learning pitfalls: a guide for academic researchers," *arXiv preprint arXiv:2108.02497*, 2021, [Online]. Available: https://arxiv.org/abs/2108.02497

[19] G. Penedo *et al.*, "The FineWeb Datasets: Decanting the Web for the Finest Text Data at Scale," *arXiv preprint arXiv:2406.17557*, 2024, [Online]. Available: https://arxiv.org/abs/2406.17557

[20] K. Paster, M. Dos Santos, Z. Azerbayev, and J. Ba, "OpenWebMath: An Open Dataset of High-Quality Mathematical Web Text," *arXiv preprint arXiv:2310.06786*, 2023, [Online]. Available: https://arxiv.org/abs/2310.06786

[21] S. Merity, C. Xiong, J. Bradbury, and R. Socher, "Pointer Sentinel Mixture Models," *arXiv preprint arXiv:1609.07843*, 2016, [Online]. Available: https://arxiv.org/abs/1609.07843

[22] S. Xiao, Z. Liu, P. Zhang, and N. Muennighoff, "C-Pack: Packaged Resources To Advance General Chinese Embedding," *arXiv preprint arXiv:2309.07597*, 2023, [Online]. Available: https://arxiv.org/abs/2309.07597

[23] B. Phipson and G. K. Smyth, "Permutation P-values Should Never Be Zero: Calculating Exact P-values When Permutations Are Randomly Drawn," *Statistical Applications in Genetics and Molecular Biology*, vol. 9, no. 1, 2010, [Online]. Available: https://arxiv.org/abs/1603.05766

[24] S. Holm, "A Simple Sequentially Rejective Multiple Test Procedure," *Scandinavian Journal of Statistics*, vol. 6, no. 2, pp. 65–70, 1979, [Online]. Available: https://www.jstor.org/stable/4615733

[25] D. S. Kerby, "The Simple Difference Formula: An Approach to Teaching Nonparametric Correlation," *Comprehensive Psychology*, vol. 3, 2014, [Online]. Available: https://doi.org/10.2466/11.IT.3.1

[26] J. Li, M. Galley, C. Brockett, J. Gao, and B. Dolan, "A Diversity-Promoting Objective Function for Neural Conversation Models," *arXiv preprint arXiv:1510.03055*, 2016, [Online]. Available: https://arxiv.org/abs/1510.03055

[27] Qwen Team, "Qwen3.5." [Online]. Available: https://huggingface.co/Qwen/Qwen3.5-9B

[28] G. Gerganov and contributors, "llama.cpp." [Online]. Available: https://github.com/ggml-org/llama.cpp

---

AI statement. The codebase, experiments and this paper were written by Claude Code (Anthropic), an AI coding agent, which executed the exact research idea provided by a human (Libor Burian): Goodfire-style neuron-level analysis of a looped transformer language model, aiming to find at least one neuron whose steering changes behavior with statistical significance. Human cleanup and rewriting of the code and text are in progress.