

Parameter Category	Specific Parameters	KINGLONG	KINGLONG
MODEL	Model	XMQ6127G	KING LONG XMQ6940G
Picture	picture		
Basic Information	Overall Dimensions (L×W×H mm)	11980×2550×3200	9430*2500*3300
	Seating Capacity	41+2 (Folding seat) +1	27+2 (Folding Seats) +1
	Wheelbase (mm)	6000	4510
	Gross Vehicle Weight (kg)	18000-19000	14500
	Warranty Policy	1 year or 100,000 km (whichever comes first)	1 year or 100,000 km (whichever comes first)
Chassis	Engine Model	Yuchai YC6L280N -52 (Euro V)	YC6J225N -52, Euro V
	Gearbox	VOITH Automatic Transmission with Retarder 854.6	VOITH Automatic Transmission with Retarder 854.6
	Suspension	Domestic air suspension (2 front/4 rear airbags)	Domestic air suspension , front 2 airbags and rear 4 airbags
	Braking System	Front/rear disc brakes + WABCO ABS + Retarder	Front disc and rear disc brakes
	CNG Cylinder Capacity	7×120L	6*120L CNG
	Tires	Triangle 295/80R22.5 tubeless	Triangle 275/70R22.5 Tubeless Tire

Body	Doors	Dual inward swinging front/middle doors	Single inward swinging front passenger door, double inward swinging middle passenger door
	Side Windows	Aluminum frame sliding	Aluminum frame sliding
	Seat Type	Kaiping Chunshan CS001 (smooth surface, no cushion)	Kaiping Chunshan Seat (CS001) CS001, Smooth Surface without Cushion
	Air Conditioning	Roof-mounted King Long single cooling A/C	Roof-mounted King Long Single Cooling Air Conditioner
Electrical System	Monitoring System	Middle door and rearview monitor	Middle Door and Rearview Monitor / Color Rearview Monitor
	CAN Bus	Domestic simplified version	Domestic Simplified Version CAN Bus
	Audio-visual System	MP3	MP3
Safety Features	Fire Extinguisher	2×4kg inside + automatic in engine compartment	4 kg *2 fire extinguishers inside bus, automatic fire extinguisher in engine cabin
	Safety Hammer	Safety emergency hammers	Safety Emergency Hammers
	Others	Disabled access ramp	Alighting Bell, Disabled Access Ramp, Top-Mounted Air Intake, Aluminum Foil + PU + PE Composite Noise-Reducing Cotton