

```
-- phpMyAdmin SQL Dump
-- version 4.5.4.1deb2ubuntu2
```

-- <http://www.phpmyadmin.net>

```
-- Host: localhost
-- Generation Time: Jun 24, 2018 at 11:21 PM
-- Server version: 5.7.22-0ubuntu0.16.04.1
-- PHP Version: 7.0.30-0ubuntu0.16.04.1
```

```
SET SQL_MODE = "NO_AUTO_VALUE_ON_ZERO";
SET time_zone = "+00:00";
```

```
/*!40101 SET @OLD_CHARACTER_SET_CLIENT=@@CHARACTER_SET_CLIENT */;
/*!40101 SET @OLD_CHARACTER_SET_RESULTS=@@CHARACTER_SET_RESULTS */;
/*!40101 SET @OLD_COLLATION_CONNECTION=@@COLLATION_CONNECTION */;
/*!40101 SET NAMES utf8mb4 */;
```

```
--
```

-- Database: **emispheres**

```
--
```

-- Table structure for table **client**

```
CREATE TABLE client (
  ID_c int(8) NOT NULL,
  Nom varchar(100) DEFAULT NULL,
  Prenom varchar(100) DEFAULT NULL
) ENGINE=InnoDB DEFAULT CHARSET=latin1;
```

```
--
```

-- Dumping data for table **client**

```
INSERT INTO client (ID_c, Nom, Prenom) VALUES
(1, 'BUYUK', 'cem');
```

--

-- Table structure for table MESSAGE

```
CREATE TABLE MESSAGE (  
  ID_message int(8) NOT NULL,  
  Message varchar(255) DEFAULT NULL,  
  ID_c int(8) DEFAULT NULL  
) ENGINE=InnoDB DEFAULT CHARSET=latin1;
```

--

-- Dumping data for table MESSAGE

```
INSERT INTO MESSAGE ( ID_message , Message , ID_c ) VALUES  
(1, 'Super vos programme.super!!!!', 1);
```

--

-- Table structure for table question

```
CREATE TABLE question (  
  ID_q int(8) NOT NULL,  
  question varchar(255) DEFAULT NULL  
) ENGINE=InnoDB DEFAULT CHARSET=latin1;
```

--

-- Dumping data for table question

```
INSERT INTO question ( ID_q , question ) VALUES  
(1, 'Nos programme répondent-ils à vos besoins ?'),  
(2, 'La compréhension de vos besoins par notre société est-elle'),  
(3, 'Le rapport qualité-prix de notre programme vous semble?'),  
(4, 'Notre programme vous a-t-il été bénéfique ? ');
```

--

-- Table structure for table `reponse`

```
CREATE TABLE reponse (  
  ID_c int(8) DEFAULT NULL,  
  ID_q int(8) DEFAULT NULL,  
  reponse varchar(255) DEFAULT NULL  
) ENGINE=InnoDB DEFAULT CHARSET=latin1;
```

--

-- Dumping data for table `reponse`

```
INSERT INTO reponse ( ID_c , ID_q , reponse ) VALUES  
(1, 1, 'Bien'),  
(1, 2, 'Exellent'),  
(1, 3, 'Insuffisant'),  
(1, 4, 'Moyen');
```

--

-- Table structure for table `users`

```
CREATE TABLE users (  
  id int(11) NOT NULL,  
  username varchar(50) NOT NULL,  
  password varchar(255) NOT NULL,  
  created_at datetime DEFAULT CURRENT_TIMESTAMP  
) ENGINE=InnoDB DEFAULT CHARSET=latin1;
```

--

-- Dumping data for table `users`

```
INSERT INTO users ( id , username , password , created_at ) VALUES  
(1, 'qsdf', '$2y$10$pzZhuuKnsNB/W1vn06F9LeM475a3enHE1jalqif22zYyM7yxL.Jye', '2018-  
06-24 23:13:13');
```

--

-- Indexes for dumped tables

--

-- Indexes for table client

```
ALTER TABLE client
ADD PRIMARY KEY ( ID_c );
```

--

-- Indexes for table MESSAGE

```
ALTER TABLE MESSAGE
ADD PRIMARY KEY ( ID_message ),
ADD KEY ID_c ( ID_c );
```

--

-- Indexes for table question

```
ALTER TABLE question
ADD PRIMARY KEY ( ID_q );
```

--

-- Indexes for table reponse

```
ALTER TABLE reponse
ADD KEY ID_c ( ID_c ),
ADD KEY ID_q ( ID_q );
```

--

-- Indexes for table users

```
ALTER TABLE users
ADD PRIMARY KEY ( id ),
ADD UNIQUE KEY username ( username );
```

```
--
```

-- AUTO_INCREMENT for dumped tables

```
--
```

-- AUTO_INCREMENT for table client

```
ALTER TABLE client
```

```
MODIFY ID_c int(8) NOT NULL
AUTO_INCREMENT, AUTO_INCREMENT=2;
```

-- AUTO_INCREMENT for table MESSAGE

```
ALTER TABLE MESSAGE
```

```
MODIFY ID_message int(8) NOT NULL
AUTO_INCREMENT, AUTO_INCREMENT=2;
```

-- AUTO_INCREMENT for table question

```
ALTER TABLE question
```

```
MODIFY ID_q int(8) NOT NULL
AUTO_INCREMENT, AUTO_INCREMENT=5;
```

-- AUTO_INCREMENT for table users

```
ALTER TABLE users
```

**MODIFY `id` int(11) NOT NULL AUTO_INCREMENT,
AUTO_INCREMENT=2;**

-- Constraints for dumped tables

--

-- Constraints for table `MESSAGE`

```
ALTER TABLE MESSAGE  
ADD CONSTRAINT MESSAGE_ibfk_1 FOREIGN KEY ( ID_c ) REFERENCES client ( ID_c );
```

--

-- Constraints for table `reponse`

```
ALTER TABLE reponse  
ADD CONSTRAINT reponse_ibfk_1 FOREIGN KEY ( ID_c ) REFERENCES client ( ID_c ),  
ADD CONSTRAINT reponse_ibfk_2 FOREIGN KEY ( ID_q ) REFERENCES question ( ID_q );
```

```
/*!40101 SET CHARACTER_SET_CLIENT=@OLD_CHARACTER_SET_CLIENT */;  
/*!40101 SET CHARACTER_SET_RESULTS=@OLD_CHARACTER_SET_RESULTS */;  
/*!40101 SET COLLATION_CONNECTION=@OLD_COLLATION_CONNECTION */;
```