Join Route Request Module
Matthew Wang

Class:
ap(Already passenger): Boolean (Database check)
# pass: Numbers > 0 only
scr(Self Created Route): Boolean (Database check)

Test Cases:
ap: True, False
pass: 0, 1, 2, 8, 9, 10
scr: True, False

Values Inputted:
ap: True
pass: 1
scr: False
Overall: False

ap: True
pass: 0
scr: False
Overall: False

ap: True
pass: 2
scr: False
Overall: False

ap: True
pass: 8
scr: False
Overall: False

ap: True
pass: 9
scr: False
Overall: False

ap: True
pass: 10
scr: False
Overall: False

ap: False
pass: 1
scr: False
Overall: True

ap: False
pass: 0
scr: False
Overall: False

ap: False
pass: 2
scr: False
Overall: True

ap: False
pass: 8
scr: False
Overall: True

ap: False
pass: 9
scr: False
Overall: True

ap: False
pass: 10
scr: False
Overall: True

ap: False
pass: 1
scr: True
Overall: false

ap: False
pass: 0
scr: True
Overall: false

ap: False
pass: 2
scr: True

Overall: false

ap: False
pass: 8
scr: True
Overall: false

ap: False
pass: 9
scr: True
Overall: false

ap: False
pass: 10
scr: True
Overall: false