Computer Architecture and Operating Systems
Lecture 10: Processor. Multiple Issue. Exceptions.

Andrei Tatarnikov

atatarnikov@hse.ru

@andrewt0301

Exceptions and Interrupts

- "Unexpected" events requiring change in flow of control
  - Different ISAs use the terms differently
- Exception
  - Arises within the CPU
    - e.g., undefined opcode, syscall, …
- Interrupt
  - From an external I/O controller
- Dealing with them without sacrificing performance is hard

Handling Exceptions

- Save PC of offending (or interrupted) instruction
  - In RISC-V: Supervisor Exception Program Counter (SEPC)
- Save indication of the problem
  - In RISC-V: Supervisor Exception Cause Register (SCAUSE)
  - 64 bits, but most bits unused
    - Exception code field: 2 for undefined opcode, 12 for hardware malfunction, …
- Jump to handler
  - Assume at $0000\ 0000\ 1C09\ 0000_{hex}$

An Alternate Mechanism

- Vectored Interrupts
  - Handler address determined by the cause
- Exception vector address to be added to a vector table base register:
  - Undefined opcode 00 0100 0000_{two}
  - Hardware malfunction: 01 1000 0000_{two}
  - …: …
- Instructions either
  - Deal with the interrupt, or
  - Jump to real handler

Handler Actions

- Read cause, and transfer to relevant handler
- Determine action required
- If restartable
  - Take corrective action
  - Use SEPC to return to program
- Otherwise
  - Terminate program
  - Report error using SEPC, SCAUSE, …

Exceptions in a Pipeline

- Another form of control hazard
- Consider malfunction on add in EX stage

  `add x1, x2, x1`
  - Prevent x1 from being clobbered
  - Complete previous instructions
  - Flush `add` and subsequent instructions
  - Set SEPC and SCAUSE register values
  - Transfer control to handler
- Similar to mispredicted branch
  - Use much of the same hardware

Pipeline with Exceptions



Exception Properties

- Restartable exceptions
  - Pipeline can flush the instruction
  - Handler executes, then returns to the instruction
    - Refetched and executed from scratch
- PC saved in SEPC register
  - Identifies causing instruction

Exception Example

- Exception on add in

```
40    sub   x11, x2, x4
44    and   x12, x2, x5
48    orr   x13, x2, x6
4c    add   x1,  x2, x1
50    sub   x15, x6, x7
54    ld    x16, 100(x7)
…
```

- Handler

```
1c090000 sd x26, 1000(x10)
1c090004 sd x27, 1008(x10)
…
```

Multiple Exceptions

- Pipelining overlaps multiple instructions
  - Could have multiple exceptions at once
- Simple approach: deal with exception from earliest instruction
  - Flush subsequent instructions
  - "Precise" exceptions
- In complex pipelines
  - Multiple instructions issued per cycle
  - Out-of-order completion
  - Maintaining precise exceptions is difficult!

Imprecise Exceptions

- Just stop pipeline and save state
  - Including exception cause(s)
- Let the handler work out
  - Which instruction(s) had exceptions
  - Which to complete or flush
    - May require "manual" completion
- Simplifies hardware, but more complex handler software
- Not feasible for complex multiple-issue out-of-order pipelines

Instruction-Level Parallelism (ILP)

- Pipelining: executing multiple instructions in parallel
- To increase ILP
  - Deeper pipeline
    - Less work per stage $\Rightarrow$ shorter clock cycle
  - Multiple issue
    - Replicate pipeline stages $\Rightarrow$ multiple pipelines
    - Start multiple instructions per clock cycle
    - CPI < 1, so use Instructions Per Cycle (IPC)
    - E.g., 4GHz 4-way multiple-issue
      - 16 BIPS, peak CPI = 0.25, peak IPC = 4
    - But dependencies reduce this in practice

Multiple Issue

- Static multiple issue
  - Compiler groups instructions to be issued together
  - Packages them into “issue slots”
  - Compiler detects and avoids hazards
- Dynamic multiple issue
  - CPU examines instruction stream and chooses instructions to issue each cycle
  - Compiler can help by reordering instructions
  - CPU resolves hazards using advanced techniques at runtime

Speculation

- "Guess" what to do with an instruction
  - Start operation as soon as possible
  - Check whether guess was right
    - If so, complete the operation
    - If not, roll-back and do the right thing
- Common to static and dynamic multiple issue
- Examples
  - Speculate on branch outcome
    - Roll back if path taken is different
  - Speculate on load
    - Roll back if location is updated

Compiler/Hardware Speculation

- Compiler can reorder instructions
  - e.g., move load before branch
  - Can include “fix-up” instructions to recover from incorrect guess
- Hardware can look ahead for instructions to execute
  - Buffer results until it determines they are actually needed
  - Flush buffers on incorrect speculation

Static Multiple Issue

- Compiler groups instructions into “issue packets”
  - Group of instructions that can be issued on a single cycle
  - Determined by pipeline resources required
- Think of an issue packet as a very long instruction
  - Specifies multiple concurrent operations
  - $\Rightarrow$ Very Long Instruction Word (VLIW)

Scheduling Static Multiple Issue

- Compiler must remove some/all hazards
  - Reorder instructions into issue packets
  - No dependencies with a packet
  - Possibly some dependencies between packets
    - Varies between ISAs; compiler must know!
  - Pad with nop if necessary

RISC-V with Static Dual Issue

- Two-issue packets
  - One ALU/branch instruction
  - One load/store instruction
  - 64-bit aligned
    - ALU/branch, then load/store
    - Pad an unused instruction with nop

Address	Instruction type	Pipeline Stages						
n	ALU/branch	IF	ID	EX	MEM	WB		
n + 4	Load/store	IF	ID	EX	MEM	WB		
n + 8	ALU/branch		IF	ID	EX	MEM	WB	
n + 12	Load/store		IF	ID	EX	MEM	WB	
n + 16	ALU/branch			IF	ID	EX	MEM	WB
n + 20	Load/store			IF	ID	EX	MEM	WB

Dynamic Multiple Issue

- "Superscalar" processors
- CPU decides whether to issue 0, 1, 2, … each cycle
  - Avoiding structural and data hazards
- Avoids the need for compiler scheduling
  - Though it may still help
  - Code semantics ensured by the CPU

Dynamic Pipeline Scheduling

- Allow the CPU to execute instructions out of order to avoid stalls
  - But commit result to registers in order
- Example

```
ld    x31,20(x21)
add   x1,x31,x2
sub   x23,x23,x3
andi  x5,x23,20
```

  - Can start sub while add is waiting for ld

Why Do Dynamic Scheduling?

- Why not just let the compiler schedule code?
- Not all stalls are predicable
  - e.g., cache misses
- Can't always schedule around branches
  - Branch outcome is dynamically determined
- Different implementations of an ISA have different latencies and hazards

Dynamically Scheduled CPU



Preserves dependencies

Hold pending operands

Results also sent to any waiting reservation stations

Reorders buffer for register writes

Can supply operands for issued instructions

Does Multiple Issue Work?

- Yes, but not as much as we'd like
- Programs have real dependencies that limit ILP
- Some dependencies are hard to eliminate
  - e.g., pointer aliasing
- Some parallelism is hard to expose
  - Limited window size during instruction issue
- Memory delays and limited bandwidth
  - Hard to keep pipelines full
- Speculation can help if done well

Conclusion

- ISA influences design of datapath and control
- Datapath and control influence design of ISA
- Pipelining improves instruction throughput using parallelism
  - More instructions completed per second
  - Latency for each instruction not reduced
- Hazards: structural, data, control
- Multiple issue and dynamic scheduling (ILP)
  - Dependencies limit achievable parallelism
  - Complexity leads to the power wall

Any Questions?

```
            .text
__start:    addi t1, zero, 0x18
            addi t2, zero, 0x21
cycle:      beq t1, t2, done
            slt t0, t1, t2
            bne t0, zero, if_less
            nop
            sub t1, t1, t2
            j cycle
            nop
if_less:    sub t2, t2, t1
            j cycle
done:       add t3, t1, zero
```