

知识分析与处理

陈豪

51205901129

ACL 2020

**Improving Multi-hop Question Answering over Knowledge Graphs using
Knowledge Base Embeddings**

Apoorv Saxena*

Aditay Tripathi*

Partha Talukdar


Indian Institute of Science, Bangalore

`{apoorvsaxena, aditayt, ppt}@iisc.ac.in`

✧ Outline

- ▶ Background
- ▶ Related Work
- ▶ Model
- ▶ Experiments
- ▶ Conclusion


► Background: KG



► Background: KGQA

Question: *What are the genres of movies written by Louis Mellis?*


Answer : *Crime*



► Background: KGQA

Question: *What are the genres of movies written by Louis Mellis?*


Answer : *Crime*



► Related Work

- ✓ **TransE: Translating embeddings for modeling multi-relational data**
- ✓ **Memory Networks: ...**
- ✓ **Neural Networks: ...**


► Model: EmbedKGQA




► Link Prediction

Question: *What are the genres of movies written by Louis Mellis?*

Answer : *Crime*




► Model



$$\phi(e_h, e_q, e_a) > 0 \quad \forall a \in \mathcal{A}$$

$$\phi(e_h, e_q, e_{\bar{a}}) < 0 \quad \forall \bar{a} \notin \mathcal{A}$$

► Model: Answer Selection



$$h_q = \text{RoBERTa}(q')$$

$$S(r, q) = \text{sigmoid}(h_q^T h_r)$$

$$\text{RelScore}_{a'} = |\mathcal{R}_a \cap \mathcal{R}_{a'}|$$

$$e_{ans} = \underset{a' \in \mathcal{N}_h}{\text{argmax}} \phi(e_h, e_q, e_{a'}) + \gamma * \text{RelScore}_{a'}$$

► Experiments

Model	WebQSP KG-Full	WebQSP KG-50
KV-Mem	46.7	32.7 (31.6)
GraftNet	66.4	48.2 (49.7)
PullNet	68.1	50.1 (51.9)
EmbedKGQA	66.6	53.2

► Conclusion

- EmbedKGQA 构建方法简单且有效，充分利用了现有嵌入方法在应对知识图谱稀疏性与实现链接预测方面的良好表现，实现了多跳 QA。
- 候选答案实体选择的方法细节并未在文中被阐述清楚，在大型知识图谱上的多跳 QA 效果可能值得深究。

THANKS

—2020.11.05