

# CS 5350/6350: Machine Learning Fall 2016

## Homework 6

Handed out: November 17, 2016

Due date: December 6, 2016

## General Instructions

- You are welcome to talk to other members of the class about the homework. I am more concerned that you understand the underlying concepts. However, you should write down your own solution. Please keep the class collaboration policy in mind.
- Feel free discuss the homework with the instructor or the TAs.
- Your written solutions should be brief and clear. You need to show your work, not just the final answer, but you do *not* need to write it in gory detail. Your assignment should be **no more than 10 pages**. Every extra page will cost a point.
- Handwritten solutions will not be accepted.
- The homework is due by midnight of the due date. Please submit the homework on Canvas.
- Some questions are marked **For 6350 students**. Students who are registered for CS 6350 should do these questions. Of course, if you are registered for CS 5350, you are welcome to do the question too, but you will not get any credit for it.

## 1 Warmup: Probabilities

For the following questions, suppose  $A_1, A_2, A_3, A_4$  are events.

*(Remember that no points will be awarded without explanations.)*

1. [2 points] If  $P(A_1) = P(A_2) = P(A_1 \mid A_2) = \frac{1}{2}$ , then are the events  $A_1$  and  $A_2$  independent? Why?
2. [3 points] Suppose  $A_1, A_2$  and  $A_3$  are mutually exclusive. If, for  $i \in \{1, 2, 3\}$ , we have  $P(A_i) = \frac{1}{3}$  and  $P(A_4 \mid A_i) = \frac{i}{6}$ , then what is  $P(A_4)$ ?
3. [3 points] Let  $n$  be the number at the top when a fair six-sided die is tossed. If a fair coin is tossed  $n$  times, then what is the probability of exactly two heads?
4. [4 points] Prove or disprove: If  $P(A_1) = a_1$  and  $P(A_2) = a_2$ , then  $P(A_1 \mid A_2) \geq \frac{a_1 + a_2 - 1}{a_2}$ .
5. [8 points] If  $A_1$  and  $A_2$  are independent events, then show that

(a)  $E[A_1 + A_2] = E[A_1] + E[A_2]$

(b)  $var[A_1 + A_2] = var[A_1] + var[A_2]$

Here  $E[\cdot]$  and  $var[\cdot]$  denote the mean and variance respectively.

## 2 Naive Bayes

In this question, we will examine the influence of the conditional independence assumption that the naive Bayes model makes. For this question, we will use the notation  $P$  to denote the true probabilities that generates the data and  $\hat{P}$  to denote probabilities that are learned from data. Assume no smoothing is done.

1. [Part 1] Suppose we have a binary classification problem where the label  $y$  can either be  $-1$  or  $1$ . In the first case, consider the case where we have only one feature  $x_1$  that can also be either  $-1$  or  $1$ . The generative distribution of the data is  $P(x_1, y) = P(y)P(x_1 | y)$ . Note that this satisfies the independence assumption of the naive Bayes model. All features are conditionally independent of each other given the label – of course, there is only one feature so this statement is trivially true.

Suppose we know the true distribution that generated the data as follows:

- $P(y = -1) = 0.1$  and  $P(y = 1) = 0.9$
- $P(x_1 = -1 | y = -1) = 0.8$ ,  $P(x_1 = 1 | y = -1) = 0.2$ ,  $P(x_1 = -1 | y = 1) = 0.1$  and  $P(x_1 = 1 | y = 1) = 0.9$ .

- (a) [2 points] If we have infinite data drawn from this distribution and we train a naive Bayes classifier, what would the values of  $\hat{P}(x_1 | y)$  and  $\hat{P}(y)$  be?

- (b) [6 points] Use these learned values probabilities from the previous question to fill up the following table:

Input $x_1$	$\hat{P}(x_1, y = -1)$	$\hat{P}(x_1, y = 1)$	Prediction: $y' = \arg \max_y \hat{P}(x_1, y)$
-1			
1			

- (c) [3 points] If the probabilities learned above were used to make predictions, what would the error of that classifier be? In other words, what is  $P(y' \neq y)$ ?

Hint: To answer this, you should use the fact that  $P(y' \neq y) = P(y' \neq y, x_1 = -1) + P(y' \neq y, x_1 = 1)$ .

2. [Part 2] Now, suppose we have a binary classification problem with two features  $x_1, x_2$  both of which can be  $-1$  or  $1$ . However, the second feature  $x_2$  is actually identical to the first feature  $x_1$ . And we have the same true probabilities  $P(x_1 | y)$  and  $P(y)$  as in Part 1 above.
  - (a) [1 point] Are  $x_1$  and  $x_2$  conditionally independent given  $y$ ? Prove your answer formally using the definition of conditional independence.

- (b) [8 points] Let  $\hat{P}(x_1 | y)$ ,  $\hat{P}(x_2 | y)$  and  $\hat{P}(y)$  represent the learned parameters of a naive Bayes classifier that is learned on infinite data generated according to the above distribution. Using these parameters, fill up the following table:

$x_1$	$x_2$	$\hat{P}(x_1, x_2, y = -1)$	$\hat{P}(x_1, x_2, y = 1)$	<b>Prediction:</b> $y' = \arg \max_y \hat{P}(x_1, x_2, y)$
-1	-1			
-1	1			
1	-1			
1	1			

- (c) [3 points] If the probabilities learned above were used to make predictions, what would the error of that classifier be? In other words, what is  $P(y' \neq y)$ ?
- (d) [2 points] Do you expect a logistic regression classifier to have the same performance as the naive Bayes classifier when the variable is duplicated? Give an intuitive explanation (no more than 2 sentences) for your answer.

### 3 [25 points, Extra Credit for the holidays] Naïve Bayes and Linear Classifiers

In this problem you will show that a Gaussian naïve Bayes classifier is a linear classifier. We will denote inputs by  $d$  dimensional vectors,  $\mathbf{x} = (x_1, x_2, \dots, x_d)^T$ . We will assume that each feature  $x_j$  is a real number. Our classifier will predict the label 1 if  $\Pr(y = 1 | \mathbf{x}) \geq \Pr(y = 0 | \mathbf{x})$ . Or equivalently,

$$\frac{\Pr(\mathbf{x} | y = 1) \Pr(y = 1)}{\Pr(\mathbf{x} | y = 0) \Pr(y = 0)} \geq 1$$

Remember the naïve Bayes assumption we saw in class:

$$\Pr(\mathbf{x} | y) = \prod_{j=0}^d \Pr(x_j | y)$$

Suppose each  $P(x_j | y)$  is defined using a Gaussian/Normal probability density function, one for each value of  $y$  and  $j$ . Each Gaussian distribution has mean  $\mu_{j,y}$  and variance  $\sigma^2$  (Note that they will all have same variance). As a reminder, the Gaussian distribution is represented by the following probability density function:

$$f(x_j | \mu_{j,y}, \sigma) = \frac{1}{\sqrt{2\sigma^2}} e^{-\frac{(x_j - \mu_{j,y})^2}{2\sigma^2}}$$

Show that this naïve Bayes classifier has a linear decision boundary.

[Hint: Refer to the notes on the naive Bayes classifier and Linear models in the class website to see how to do this with binary features]

## 4 Experiment

We looked maximum a posteriori learning of the logistic regression classifier in class. In particular, we showed that learning the classifier is equivalent to the following optimization

problem:

$$\min_{\mathbf{w}} \left\{ \sum_{i=1}^m \log(1 + \exp(-y_i \mathbf{w}^T \mathbf{x}_i)) + \frac{1}{\sigma^2} \mathbf{w}^T \mathbf{w} \right\}$$

In this question, you will derive the stochastic gradient descent algorithm for the logistic regression classifier, and also implement it with cross-validation.

1. [5 points] What is the derivative of the function  $g(\mathbf{w}) = \log(1 + \exp(-y_i \mathbf{w}^T \mathbf{x}_i))$  with respect to the weight vector?
2. [5 points] The inner most step in the SGD algorithm is the gradient update where we use a single example instead of the entire dataset to compute the gradient. Write down the objective where the entire dataset is composed of a single example, say  $(\mathbf{x}_i, y_i)$ . Derive the gradient of this objective with respect to the weight vector.
3. [10 points] Write down the pseudo code for the stochastic gradient algorithm using the gradient from previous part.
4. [20 points] Implement your pseudo code as a training algorithm with cross-validation on the  $\sigma$  parameter. This parameter basically helps trade off between generalizability and model fit.

Use the Adult data set from the UCI Machine Learning repository which you used in homework 2 to train and evaluate the learner. (For a description of the data, see homework 2.) In your writeup, please report on the accuracy of your system, what value of sigma you chose based on cross validation, how many epochs you chose to run SGD, and a plot of the NEGATIVE log likelihood after each epoch of SGD.

## Experiment Submission Guidelines

1. The report should detail your experiments. For each step, explain in no more than a paragraph or so how your implementation works. You may provide the results for the final step as a table or a graph.
2. *Your code should run on the CADE machines.* You should include a shell script, **run.sh**, that will execute your code in the CADE environment. Your code should produce similar output to what you include in your report.

You are responsible for ensuring that the grader can execute the code using only the included script. If you are using an esoteric programming language, you should make sure that its runtime is available on CADE.

3. Please do not hand in binary files! We will *not* grade binary submissions.