

# Working with Data Sources, Gateways and DirectQuery

**Lab Time:** 60 minutes

**Lab Folder:** C:\Student\Modules\09\_Gateways\Lab

**Lab Overview:** In this lab you will get hands-on experience configuring datasets in the Power BI service for the manual and scheduled refreshing of data from underlying data sources. You will also get experience installing and configuring a Power BI gateway to refresh data from an on-premises data source. In the final experience, you will create a Power BI Desktop project based on a live connection. This will give you a chance to see how different things are when you are creating queries and data modeling in DirectQuery mode.


**Lab Dependency 1:** This lab assumes you completed lab 6 titled **Designing Interactive Reports in Power BI Desktop** in which you created and published a Power BI Desktop project named **Wingtip Sales Analysis.pbix**. If you would like to begin work on this lab without completing lab 6, copy the lab solution file named **Wingtip Sales Analysis.pbix** which is located in the student folder at **C:\Student\Modules\06\_Reports\Lab\Solution** into the folder at **C:\Student\Projects**.

**Lab Dependency 2:** Exercise 3 in this lab assumes you completed the lab 8 titled **Designing Dashboards for Mobile Devices** in which you created and published a Power BI Desktop project named **R&D Expenses** which used an underlying data source based on a local Excel workbook file located at **C:\Data\R&D Expenses.xlsx**.

## Exercise 1: Configure Data Source Credentials in the Power BI Service

In this exercise you will create a new dashboard using the dataset and report you created in early labs using Power BI Desktop.


1. Using the browser log into the Power BI service and access your personal workspace. While your personal workspace might contain many different dashboards, reports and datasets by this point, you should see two datasets named **R&D Expenses** and **Wingtip Sales Analysis** as shown in the following screenshot.




2. Launch Power BI Desktop and open the PBIX project file in the **C:\Student\Projects** folder named **Wingtip Sales Analysis.pbix**.

Currently, the Power BI Desktop project named **Wingtip Sales Analysis.pbix** contains a data source based on a local Excel workbook file located at **C:\Student\Data\WingtipSalesRegions.xlsx**. In the next step you will remove this local file dependency by updating the data source to use copy of the same Excel workbook that can be access from across the Internet using anonymous access.

3. Update the data source for the query named **SalesRegions**.
  - a) Once the project has opened, click the **Edit Queries** button to display the Query Editor window.




- b) In the **Queries** list on the left, select the query named **SalesRegion**.




	State	StateFullName	SalesRegion	SalesRegionsSortOrder
1	AK	Alaska	Western Region	1
2	AZ	Arizona	Western Region	1
3	AL	Alabama	Central Region	2
4	AR	Arkansas	Central Region	2
5	CA	California	Western Region	1
6	CO	Colorado	Western Region	1
7	CT	Connecticut	Eastern Region	3

- c) Inside the **APPLIED STEPS** list on the right, locate the **Source** step and click its gear icon button to modify its value.




- d) You should be prompted with the **Excel** dialog which displays the current file path.




- e) Update the **File path** value for **WingtipSalesRegions.xlsx** by copying and pasting the following URL.

<https://github.com/CriticalPathTraining/PBI365/raw/master/Student/Data/WingtipSalesRegions.xlsx>


- f) Once the **Excel** dialog matches the screenshot below, click **OK** to save your changes.




- g) In the **Queries** list on the left, right-click on the query named **SalesRegions** and then click the **Include In Report Refresh** option once to put this property into a disabled state. Once you have disabled **Include in Report Refresh** property, you should be able to verify that this property has no checkmark next to it as shown in the following screenshot.




- h) Click the **Close & Apply** button to close the Query Editor window.




- i) Click the **Refresh** button on the **Home** ribbon tab of the main Power BI desktop application window to refresh the project's data sources.



- j) You should see all the tables from the Azure SQL databases being refreshed. However, the SalesRegions query was not refreshed because you set its **Include in Report Refresh** property to a disabled state.




- k) Click the **Save** button to save your changes to the project named **Wingtip Sales Analysis.pbix**.




4. Publish your project to push the changes you made to **Wingtip Sales Analysis.pbix** into the Power BI service.


- a) Click the **Publish** button in the **Home** tab of the ribbon.




- b) When prompted to **Select a destination**, choose **My Workspace** then click the **Select** button.




- c) If you are prompted with the **Replacing dataset** dialog, click the **Replace** button to continue.



- d) Wait while Power BI Desktop publishes your project updates to the Power BI service.




- e) When Power BI Desktop is done, it should display a message indicating success and a link to navigate to your personal workspace in the browser. Click the link with the caption **Open 'Wingtip Sales Analysis' in Power BI**.




5. Try and perform a manual refresh on the **Wingtip Sales Analysis** dataset.


- a) At this point, you should see the dashboards, reports and datasets in your personal workspace including the datasets named **Wingtip Sales Analysis**.




- b) Click the ellipse button (...) to the right of the **Wingtip Sales Analysis** dataset to see the available dataset commands.




- c) Click the **REFRESH NOW** command on **Wingtip Sales Analysis** dataset.



- d) You will see a spinning animation to the left of the dataset indicating that the Power BI service is attempting to refresh its data.




- e) The manual update should fail because you have not yet updated the credentials for the dataset's underlying data sources. When you attempt a refresh and it fails, the Power BI service should automatically redirect you to the dataset properties page for the **Wingtip Sales Analysis** dataset and display an error message in the **Data source credentials** section.




Note that this lab exercise makes the assumption that you have not already configured the credentials for the underlying data sources. If you have already configured credentials for the SQL Azure database, you might find that the manual refresh attempt succeeds instead of failing as indicated in the previous step.


6. Configure the credentials for the data source associated with the SQL Azure database.
- a) In the **Data source credentials** section for the **Wingtip Sales Analysis** dataset, click the **Edit credentials** link for the data source named **WingtipSalesDB-cpt.database.windows.net**.




- b) You are prompted with a dialog to configure the credentials for this data source.
- c) Change the **Authentication method** to **Basic**.
- d) Enter a **User name** of **CptStudent**.
- e) Enter a **Password** of **pass@word1**.
- f) Click the **Sign In** button to save the credentials and cache them inside the Power BI service.




7. Configure the data source credentials for the Excel workbook with sales regions located in a public GitHub repository.
- a) Click the **Edit credentials** link for the data source named **Web**.




- b) You are prompted with a dialog to configure the credentials for this data source.
- c) Change the **Authentication method** to **Anonymous**.
- d) Click the **Sign In** button to save the credentials (or lack thereof) for this data source.




- e) At this point, the error message should no longer be displayed in the **Data source credentials** section.



8. Attempt to perform a manual refresh a second time now that you have updated the dataset's underlying data source credentials.
- a) Click the **REFRESH NOW** command on **Wingtip Sales Analysis** dataset.




- b) You will see a spinning animation to the left of the dataset which indicates the Power BI service is attempting to refresh the underlying data. When the spinning animation stops, expand the dataset's flyout menu and verify that the refresh operation was successful.




## Exercise 2: Create a Schedule to Automatically Refresh a Dataset

In the previous exercise you configured the data source credentials for the **Wingtip Sales Analysis** dataset and then you executed the command to perform a manual refresh. In this exercise you will configure the **Wingtip Sales Analysis** dataset to automatically refresh on a periodic schedule


1. Click the ellipse flyout menu for the **Wingtip Sales Analysis** dataset and click the **SCHEDULE REFRESH** command. When you do this, you should be redirected to a page that displays the **Schedule Refresh** section for that dataset.




2. When you examine the **Schedule Refresh** section, you should be able to see that the **Keep your data up to date** property is set to **No** as its default setting.



3. Configure the **Schedule Refresh** settings for the **Wingtip Sales Analysis** dataset.
  - a) Update the **Keep your data up to date** property to **Yes**.
  - b) Update the **Refresh frequency** property to **Daily**.
  - c) Set the time to 6:00 AM.
  - d) Click the **Add another time link** and configure the second time for **11:00 AM**.
  - e) Click the **Add another time link** and configure the third time for **3:00 PM**.
  - f) Make sure the **Send refresh failure notification email to me** checkbox is in a checked state.
  - g) When your **Schedule Refresh** settings match the following screenshot, click the **Apply** button to save your changes.



- h) Once you have configured the scheduled refresh settings, you should be able to verify when the next refresh is scheduled.






### Exercise 3: Install a Power BI Gateway as a Personal Gateway


You will begin this exercise by attempting to refresh the data that has been imported into the **R&D Expenses** dataset. However, the first refresh attempt on the **R&D Expenses** dataset will fail because this dataset has an underlying data source based on an Excel workbook file named **R&D Expenses.xlsx** which resides on a local hard drive with a file path the **C:\Data\R&D Expenses.xlsx**. In order for you to refresh the data directly from the Power BI service, you will be required to install and configure a personal gateway.

1. Attempt to refresh the **R&D Expenses** dataset.

- a) Click on the ellipse flyout menu for the **R&D Expenses** dataset and click **REFRESH NOW**.




- b) The **REFRESH NOW** command should fail because the Power BI service cannot refresh a dataset based on a local Excel workbook file unless you have configured a Power BI gateway.
- c) Examine the **Dataset Settings** for the **R&D Expenses** dataset. You should see a message informing you that a data gateway will be required in order to refresh the data for this dataset.




2. Download and install a Power BI Gateway.


- a) Drop down the Download menu from the main window of the Power BI service and click **Data Gateway**.



- b) You will be redirected to a page with a **Download gateway** button.
- c) Click the **Download gateway** button to download the installation file for a Power BI gateway.



- d) If prompted, click **Save** to download the installation file named **PowerBIGatewayInstall.exe**.




- e) Once the installed file named **PowerBIGatewayInstall.exe** has been downloaded, click **Run** to begin the installation.




The On-premises data gateway installer should now begin to run. You will be prompted by several different screens during installation.


- f) When prompted by the **Start your on-premises data gateway installation** screen, click **Next** to continue.




- g) On the **Choose the type of gateway you need** screen, select the option button for **Personal gateway (Power BI Only)** and then click **Next** to begin the installation.




- h) On the **Welcome to the Power BI Gateway – Personal Installation Wizard** screen, click Next to **continue**.




- i) On the **There are some important things you should know** screen, read the information message about making sure your computer is kept running and then click **Next**.




- j) On the **Please read the following license agreement carefully** screen, click the **I accept the terms of the Licensing Agreement** checkbox and click **Next**.



- k) On the **Destination Folder** screen, accept the default location and click **Next**.




- l) Wait until you see the **Completed the installation wizard** screen indicating the installation was successful.  
m) Click the **Launch** button to start up the personal gateway.




When you click the Launch button, it might take a minute or two for the Personal Gateway to start up. If it hasn't started up after a minute or two you can find and launch it from the Windows Start menu by searching for **Power BI gateway – Personal**.


3. Configure the personal gateway by logging in with your primary Office 365 account.
- a) If the Power BI Gateway isn't running, launch it from the Windows Start menu by searching for **Power BI gateway – Personal**.
  - b) On the **Sign in to Power BI** screen, click **Next** to begin the login sequence.



- c) Sign in using your primary Office 365 account.




- d) Once you have logged in, you will see a **Success** message.  
e) Click **Finish** to dismiss the **Power BI Gateway - Personal** dialog.




At this point, the personal gateway is running behind the scenes and is connected to the Power BI service using Azure Service Bus. Your next step is to navigate to the Power BI service in a browser so you can configure one or more data sources to use this gateway.


4. Configure the data source based on the local Excel workbook file to use the Gateway.
- a) Navigate to the Power BI service in the browser.
  - b) Drop down the **Settings** menu with the gear icon and then click the **Settings** menu command.




- c) On the **Settings** page, select the **Datasets** tab and then select the **R&D Expenses** dataset.




- d) Expand the **Gateway connection** section. You should see that the personal gateway you just installed is connected.



- e) Expand the **Data source credentials** section. You should see an error message indicating that the data source for the Excel workbook files named **R&D Expenses.xlsx** has invalid credentials. Click the **Edit credentials** link.




- f) On the **Configure R&D Expenses** dialog, click the **Sign In** button to configure credentials for the data source.




You will find that when you click the **Sign In** button that you are not prompted for credentials such as a user name and password. This is due to the fact that you are using a personal gateway which cannot use credentials cached in the cloud. The personal gateway is running under the same Windows identity that you used to log in when you installed the gateway.


- g) Once the credentials have been configured, you will no longer see the error message in the **Data source credentials** section.



5. Refresh the R&D Expenses dataset by executing the **Refresh Now** command. It will take a few seconds for the command to complete. However, you should be able to verify that the Power BI service has successfully refresh the dataset.




6. Inspect the **R&D Expenses** dashboard. Take note of the amount in the **Total Expenses** tile.




7. Update the Excel workbook named **R&D Expenses.xlsx** to add another expense.
- Launch Microsoft Excel 2016
  - Open the Excel workbook file at the path **C:\Data\R&D Expenses.xlsx**.
  - Add a new expense to the bottom of the expenses table as shown in the following screenshot.

21	Dell M4600	8/12/2016	\$3,223.34	Hardware	Ted
22	ToyCon, Las Vegas	8/15/2016	\$1,800.00	Conferences	Fred
23	ToyCon, Las Vegas	8/15/2016	\$1,800.00	Conferences	Jed
24	ToyCon, Las Vegas	8/15/2016	\$1,800.00	Conferences	Ted
25	Microsoft Azure	8/28/2016	\$87.34	Online Services	Ted
26	Linux Server	8/24/2016	\$2,412.45	Hardware	Jed
27	iToy Testing Service	9/15/2016	\$1,895.00	Online Services	Fred
28					

- Save and close the Excel workbook file **R&D Expenses.xlsx**.
8. Refresh the **R&D Expenses** dataset once again by executing the **Refresh Now** command.



9. Inspect the **R&D Expenses** dashboard. The amount in the **Total Expenses** tile should update to reflect the new expense amount.




## Exercise 4: Connect to a Data Source using DirectQuery Mode

In this exercise you will create a new Power BI Desktop project that uses DirectQuery mode to retrieve data from the SQL Azure database named **WingtipSalesDB**. Note that this is the same SQL Azure database that you have worked with in earlier lab exercises. As you will see, working in DirectQuery mode usually requires writing SQL statements for queries to compensate for the data modeling limitation which prevents you from creating calculated columns.


1. Launch Power BI Desktop to start a new project.
2. Save the new project as **DirectQuery Lab.pbix** using the following path.

**C:\Student\Projects\DirectQuery Lab.pbix**

3. Create a new query in DirectQuery mode to retrieve customer data from an Azure SQL database.
  - a) Drop down the **Get Data** menu button on the ribbon and click **More...**



- b) In the **Get Data** dialog...
  - i) Select **Azure** from the list on the left.
  - ii) Select **Microsoft Azure SQL Database** from the list on the right.
  - iii) Click the **Connect** button.



- c) When you are prompted with the **SQL Server Database** dialog, complete the following tasks.
  - i) Enter a **Server** value of **cpt.database.windows.net**
  - ii) Enter a **Database** value of **WingtipSalesDB**
  - iii) Select the option button for **DirectQuery**.
  - iv) Expand the **Advanced options** section.



- d) In the **SQL statement** textbox inside the **Advanced option** section, copy and paste the following SQL statement.

```
SELECT
  CustomerId,
  FirstName + N' ' + LastName AS Customer,
  CASE Gender
    WHEN 'F' THEN 'Female'
    WHEN 'M' THEN 'Male'
  END AS Gender,
  State,
  City + N' ' + State AS City,
  Zipcode
FROM Customers
```

You can copy and paste this SQL statement from the text-based SQL file named **Customers.sql** located in the folder for this lab.

- e) Make sure the checkboxes for **Include Relationship Columns** and **Navigate using full hierarchy** are both checked.
- f) When the **SQL Server Database** dialog matches the following screenshot, click **OK**.

SQL Server Database

Import data from a SQL Server database.

Server  
cpt.database.windows.net

Database (optional)  
WingtipSalesDB

☐ Import  
☒ DirectQuery

Advanced options  
Command timeout in minutes (optional)

SQL statement (optional)

```
SELECT
  CustomerId,
  FirstName + N' ' + LastName AS Customer,
  CASE Gender
    WHEN 'F' THEN 'Female'
    WHEN 'M' THEN 'Male'
  END AS Gender,
  State,
  City + N' ' + State AS City,
  Zipcode
FROM Customers
```

☒ Include relationship columns  
☒ Navigate using full hierarchy

OK Cancel

- g) You should now be prompted with the **Access a SQL Server Database** dialog asking for data source credentials. Select the option for **Database** on the left side of the dialog.

Access a SQL Server Database

Windows  
Database

cpt.database.windows.net;WingtipSalesDB


Use your Windows credentials to access this database.

☒ Use my current credentials  
☐ Use alternate credentials


Username

Password


- h) Enter a Username of **CptStudent**.
- i) Enter a password of **pass@word1**.
- j) Click the **Connect** button to submit the credentials for the Azure SQL database.




- k) When you see the dialog which displays rows of data, click the **Edit** button to open the new query in the Query Editor window.



- l) You should see that the new query has been created with the name **Query1**.
- m) In the **Query Settings** pane in the right-side of the Query Editor window, change the query name from **Query1** to **Customers**.



- n) Click the **Close & Apply** button to close the Query Editor window.
- o) Navigate to Relationship View and inspect the **Customers** table.



You will notice that the left navigation has buttons to navigate to Report View and Relationship View. However, there is no navigation button for Data View because it is not supported when working in DirectQuery mode.

- 4. Save your work by clicking the **Save** button at the top left of the main Power BI Desktop window.
- 5. Create a new query in DirectQuery mode to retrieve product data from the same Azure SQL database.
  - a) Drop down the **Get Data** menu button on the ribbon and click **More...**
  - b) On the **Get Data** dialog, select **Azure** in the list on the left. Next, select **Microsoft SQL Azure Database** on the right and then click the **Connect** button.
  - c) When you are prompted with the **SQL Server Database** dialog, complete the following tasks.
    - i) Enter a **Server** value of **cpt.database.windows.net**
    - ii) Enter a **Database** value of **WingtipSalesDB**
    - iii) Select the option button for **DirectQuery**.
    - iv) Expand the **Advanced options** section.
  - d) In the **SQL statement** textbox of the **Advanced options** section, copy and paste the following SQL statement.

```
SELECT
ProductId,
LEFT(ProductCategory, CHARINDEX(' >', ProductCategory) - 1) AS Category,
RIGHT(ProductCategory, LEN(ProductCategory) - CHARINDEX(' >', ProductCategory)) AS Subcategory,
Title AS Product,
ProductImageUri As [Product Image]
FROM
Products
```

You can copy and paste this SQL statement from the text-based SQL file named **Products.sql** located in the folder for this lab.

- e) Make sure the checkboxes for **Include Relationship Columns** and **Navigate using full hierarchy** are both checked.
- f) When the **SQL Server Database** dialog matches the following screenshot, click **OK**.

SQL Server Database

Import data from a SQL Server database.

Server  
cpt.database.windows.net

Database  
WingtipSalesDB

☐ Import  
☒ DirectQuery

Advanced options  
Command timeout in minutes (optional)

SQL statement (optional)  

```

SELECT
    ProductId,
    LEFT(ProductCategory, CHARINDEX(' >', ProductCategory) - 1) AS Category,
    RIGHT(ProductCategory, LEN(ProductCategory) - CHARINDEX(' >', ProductCategory)) AS Subcategory,
    Title AS Product,
    ProductImageUri AS [Product Image]
FROM
    Products
        
```

☒ Include relationship columns  
☒ Navigate using full hierarchy

OK Cancel

- g) When you see the dialog which displays rows of data, click the **Edit** button to open the new query in the Query Editor window.
- h) In the **Query settings** pane in the right-side of the Query Editor window, change the query name to **Products**.

Queries [3]  
Customers  
Products

ProductId	Category	Subcategory	Product	Product Image
1	Action Figures	Tough Guys	Batman Action Figure	http://classresourc
2	Action Figures	Tough Guys	Captain America Action Figure	http://classresourc
3	Action Figures	Tough Guys	GI Joe Action Figure	http://classresourc
4	Action Figures	Tough Guys	Green Hulk Action Figure	http://cl
5	Action Figures	Tough Guys	Red Hulk Alter Ego Action Figure	http://classresourc
6	Action Figures	Tough Guys	Spider-Man Action Figure	http://classresourc

Query Settings  
 PROPERTIES  
 Name  
 Products  
 All Properties

- i) Click the **Close & Apply** button to close the Query Editor window.
- j) Navigate to Relationship View and inspect the **Products** table which should be displayed next to the **Customers** table.

File Home Modeling

Clipboard: Cut, Copy, Paste, Format Painter  
 Data Sources: Get Data, Recent, Enter Data, Edit Queries, Refresh  
 External Data: New Page, New Visual, Text Box, Image, Shapes  
 Insert: Page View, Manage Relationships, Relationships, Calculations, Share  
 View: Publish

Customers  
 CustomerId  
 Customer  
 Gender  
 State  
 City  
 Zipcode

Products  
 ProductId  
 Category  
 Subcategory  
 Product  
 Product Image

- k) Save your work by clicking the **Save** button at the top left of the main Power BI Desktop window.

6. Create a new query in DirectQuery mode to execute a SQL statement which joins the **Invoice** table to the **InvoiceDetails** table.
  - a) Drop down the **Get Data** menu button on the ribbon and click **More....**
  - b) On the **Get Data** dialog, select **Azure** in the list on the left. Next, select **Microsoft SQL Azure Database** on the right and then click the **Connect** button.
  - c) When you are prompted with the **SQL Server Database** dialog, complete the following tasks.
    - i) Enter a Server value of **cpt.database.windows.net**
    - ii) Enter a Database value of **WingtipSalesDB**.
    - iii) Select the option button for **DirectQuery**.
    - iv) Expand the **Advanced options** section.
  - d) In the **SQL statement** textbox of the **Advanced options** section, copy and paste the following SQL statement.

```
SELECT
  CustomerId,
  ProductId,
  Cast(InvoiceDate As date) AS [Purchase Date],
  Year(InvoiceDate) As [Purchase Year],
  Quantity,
  SalesAmount,
  CASE InvoiceType
    WHEN 'InPerson' THEN 'Store Transaction'
    WHEN 'MailOrder' THEN 'Mail Order Transaction'
    WHEN 'Online' THEN 'Online Transaction'
  END AS [Purchase Type]
FROM InvoiceDetails INNER JOIN Invoices
  ON InvoiceDetails.InvoiceId = Invoices.InvoiceId
```

You can copy and paste this SQL statement from the text-based SQL file named **Sales.sql** located in the folder for this lab.

- e) Make sure the checkboxes for **Include Relationship Columns** and **Navigate using full hierarchy** are both checked.
- f) When the **SQL Server Database** dialog matches the following screenshot, click **OK**.

SQL Server Database

Import data from a SQL Server database.

Server  
cpt.database.windows.net

Database  
WingtipSalesDB

☐ Import  
☒ DirectQuery

Advanced options


Command timeout in minutes (optional)

SQL statement (optional)  
SELECT  
 CustomerId,  
 ProductId,  
 Cast(InvoiceDate As date) AS [Purchase Date],  
 Year(InvoiceDate) As [Purchase Year],  
 Quantity,  
 SalesAmount,  
 CASE InvoiceType  
 WHEN 'InPerson' THEN 'Store Transaction'  
 WHEN 'MailOrder' THEN 'Mail Order Transaction'  
 WHEN 'Online' THEN 'Online Transaction'  
 END AS [Purchase Type]  
FROM InvoiceDetails INNER JOIN Invoices  
 ON InvoiceDetails.InvoiceId = Invoices.InvoiceId


☒ Include relationship columns  
☒ Navigate using full hierarchy

OK Cancel


- g) When you see the dialog which displays rows of data, click the **Edit** button to open the new query in the Query Editor window.
- h) In the **Query settings** pane in the right-side of the Query Editor window, change the query name to **Sales**.



- i) Click the **Close & Apply** button to close the Query Editor window.
- j) Navigate to Relationship View and inspect the set of tables which should now include **Customers**, **Products** and **Sales**.
- k) Use the mouse to rearrange the layout of the three tables to match the following screenshot.



- l) Save your work by clicking the **Save** button at the top left of the main Power BI Desktop window.
7. Create a relationship between the **Customers** table and the **Sales** table.
- a) In Relationship View, use the mouse to drag and drop the **CustomerId** field from **Customers** table onto the **CustomerId** field from **Sales** table. When you do this, Power BI desktop will prompt you with the **Create Relationship** dialog.
  - b) In the **Create Relationship** dialog, make sure that the **Make this relationship active** checkbox and the **Assume Referential Integrity** checkbox are both in a checked state.
  - c) Click the **OK** button to create the new relationship and to dismiss the **Create Relationship** dialog.



8. Create a relationship between the **Products** table and the **Sales** table.
  - a) In Relationship View, use the mouse to drag and drop the **ProductId** field from **Products** table onto the **ProductId** field from **Sales** table. When you do this, Power BI desktop will prompt you with the **Create Relationship** dialog.
  - b) In the **Create Relationship** dialog, make sure that the **Make this relationship active** checkbox and the **Assume Referential Integrity** checkbox are both in a checked state.
  - c) Click the **OK** button to create the new relationship and to dismiss the **Create Relationship** dialog.

Create Relationship

Select tables and columns that relate to one another.

Products

ProductId	Category	Subcategory	Product	Product Image
1	Action Figures	Tough Guys	Batman Action Figure	http://classresources.blob.core.windows.net/ima
2	Action Figures	Tough Guys	Captain America Action Figure	http://classresources.blob.core.windows.net/ima
3	Action Figures	Tough Guys	GI Joe Action Figure	http://classresources.blob.core.windows.net/ima

Sales

CustomerId	ProductId	Purchase Date	Purchase Year	Quantity	SalesAmount	Purchase Type
1	16	1/28/2012 12:00:00 AM	2012	1	2.95	Store Transaction
2	15	1/28/2012 12:00:00 AM	2012	6	14.94	Store Transaction
3	6	1/28/2012 12:00:00 AM	2012	1	19.95	Store Transaction

Cardinality: One to Many (1:\*)


Cross filter direction: Single

☒ Make this relationship active


☒ Assume Referential Integrity [Learn More](#)

OK Cancel


- d) There should now be two tables relationships that relate all three tables together into a single data model.




- e) Save your work by clicking the **Save** button at the top left of the main Power BI Desktop window.
9. Hide the fields in the data model from Report View that will not be used when designing report pages.
    - a) In Relationship View, right-click the **CustomerId** field in the Customers table and click the **Hide in Report View** command.




- b) Use the same technique to hide the **CustomerId** field in the **Sales** table.
  - c) Use the same technique to hide the **ProductId** field in the **Sales** table.
  - d) Use the same technique to hide the **Quantity** field in the **Sales** table.
  - e) Use the same technique to hide the **SalesAmount** field in the **Sales** table.
  - f) Use the same technique to hide the **ProductId** field in the **Products** table.
10. Configure Geolocation Metadata for the **State** field in the **Customers** table.
- a) Make sure you are still in Report View.
  - b) From the **Fields** list on the right, select the **State** field from the **Customers** table.
  - c) Drop down the **Data Category** menu from the ribbon and select **State or Province**.



11. Configure geolocation metadata for the **City** field in the **Customers** table.
- a) Make sure you are still in Report View.
  - b) From the **Fields** list on the right, select the **City** field from the **Customers** table.
  - c) Drop down the **Data Category** menu from the ribbon and select **City**.



12. Configure geolocation metadata for the **Zipcode** field in the **Customers** table.
- a) Make sure you are still in Report View.
  - b) From the **Fields** list on the right, select the **Zipcode** field from the **Customers** table.
  - c) Drop down the **Data Category** menu from the ribbon and select **Postal Code**.






d) Save your work by clicking the **Save** button at the top left of the main Power BI Desktop window.

13. Add a new dimensional hierarchy to the **Products** table.

a) Inspect the **Products** table in the **Fields** list. This table should display the fields shown in the following screenshot.



b) Right-click on the **Category** field and then select the **New Hierarchy** menu command.

c) You should now see a new dimensional hierarchy in the fields list named **Category Hierarchy**.


d) Right-click **Category Hierarchy** and select the **Rename** menu command.

e) Rename the new hierarchy **Product Category**.

f) Right-click on the **Subcategory** field and select the **Add to Product Category** menu command.

g) Right-click on the **Product** field and select the **Add to Product Category** menu command.

h) The **Product Category** hierarchy should now contain three fields as shown in the following screenshot.




14. Configure image URL metadata for the **Product Image** field in the **Products** table.

a) Make sure you are still in Report View.


b) From the **Fields** list on the right, select the **Product Image** field from the **Products** table.

c) Drop down the **Data Category** menu from the ribbon and select **Image URL**.




15. Configure the formatting for the **Purchase Date** field in the **Sales** table.

- Make sure you are still in Report View.
- In the **Fields** list in the right, select the **Purchase Date** field from the **Sales** table.
- Set the **Format** property to **3/14/2001 (M/d/yyyy)**.




16. Configure the default summarization for the **Purchase Year** field in the **Sales** table.

- Make sure you are still in Report View.
- In the **Fields** list in the right, select the **Purchase Year** field from the **Sales** table.
- Set the **Default Summarization** property to **Do Not Summarize**.



17. Create a measure named **Units Sold** to perform a sum aggregation on the **Quantity** column of the **Sales** table.


- Make sure you are in Report View.
- Select the **Sales** table from the **Fields** list.
- Create a new measure by clicking the **New Measure** button in the **Modeling** tab of the ribbon.



- d) Enter to following DAX expression into the formula bar to create the measure named **Units Sold**.

```
Units Sold = SUM(Sales[Quantity])
```

- e) Press the **ENTER** key to add the measure to data model.  
f) Modify the formatting by clicking and selecting the Comma button on the ribbon to add a comma separator.




18. Create a measure named **Sales Revenue** to perform a sum aggregation on the **SalesAmount** column of the **Sales** table.

- a) Create a new measure by clicking the **New Measure** button in the ribbon.  
b) Enter to following DAX expression into the formula bar to create the measure named **Sales Revenue**.

```
Sales Revenue = Sum(Sales[SalesAmount])
```

- c) Press the **ENTER** key to add the measure to data model.  
d) Modify the formatting by dropping down the **Format** menu on the ribbon and selecting **Currency > \$ English (United States)**. Also use the spinner control below the **Format** menu to set the number of decimal places shown to zero.




19. Create a measure named **Customer Count** to perform an aggregation to count the number of rows in the **Customers** table.


- a) Make sure the **Customers** table is selected.  
b) Create a new measure by clicking the **New Measure** button in the ribbon.  
c) Enter the following DAX expression into the formula bar to create the measure named **Customer Count**.

```
Customer Count = COUNTROWS(Customers)
```


- d) Press the **ENTER** key to add the measure to data model.  
e) Modify the formatting by clicking and selecting the Comma button on the ribbon to add a comma separator.




- f) At this point, the fields in the Sales table should match the following screenshot.




20. Save your work by clicking the **Save** button at the top left of the main Power BI Desktop window.
21. Currently, the report for the current project has a single page. Rename this report page from **Page1** to **Sales Analysis**.




22. Create a rectangle shape on the report page to provide background formatting for a slicer visual.
- a) Drop down the **Shapes** menu and select the **Rectangle** command to add a new shape to the report.
  - b) Using the mouse, resize the rectangle shape to take up the full height of the report page and about 20% of the width.




23. Add a new slicer visual to the page to filter by **Purchase Year**.
- a) Click the **New Visual** button on the ribbon to add a new visual to the page.
  - b) Change the visual to a slicer by clicking the **Slicer** button in the **Visualizations** list.



- c) Position the slicer on top of the rectangle.
- d) Drag and drop the **Purchase Year** column from the **Sales** table into the **Values** well.




- e) You should now have a slicer visual that matches the following screenshot.



24. Create a new matrix visual to display sales revenue broken out by product category, subcategory and product.

- a) Click the **New Visual** button on the ribbon to add a new visual to the page.
- b) Change the visual to a matrix by clicking the **Matrix** button in the **Visualizations** list.
- c) In the **Fields** list, click the checkbox for the **Product Category**.
- d) Drag and drop the **Sales Revenue** field from the **Sales** table into the **Values** well.




- e) The Matrix visual should now display sales revenue for each product along with totals for each subcategory and category.

The screenshot shows a matrix visual with a slicer for 'Purchase Year' on the left. The matrix has three columns: Category, Subcategory, and Product. The data is organized into a hierarchy, with 'Action Figures' as the main category, 'Cute and Huggable' and 'Tough Guys' as subcategories, and various action figures as products. A 'Total' row is also present for each subcategory.


Category	Subcategory	Product
Action Figures	Cute and Huggable	Black Power Ranger Action Figure
		Green Angry Bird Action Figure
		Perry the Platypus Action Figure
		Phineas and Ferb Action Figure Set
		Red Angry Bird Action Figure
		Twitter Follower Action Figure
		Woody Action Figure
		<b>Total</b>
	Tough Guys	Batman Action Figure
		Captain America Action Figure
		GI Joe Action Figure




- c) Configure the fields for the **Line Chart** visual by adding the **Purchase Date** field from the **Sale** table into the **Axis** well and the **Sales Revenue** field from the **Sales** table into the **Values** well.



- d) Configure the **Title** property of the matrix visual to **Off**.  
e) Configure the **Border** property of the matrix visual to **On**.




- f) Position the line chart visual in the upper right-hand corner of the report page.




27. Save your work by clicking the **Save** button at the top left of the main Power BI Desktop window.

28. Add a new Map visual to display sales revenue by state.


- a) Click the **New Visual** button on the ribbon to create a new visual.  
b) Click the **Map** button in the **Visualizations** list to change the visual into a Map visual.




- c) Configure the fields for the **Map** visual by adding the **State** field from the **Customers** table into the **Location** well.
- d) Add the **Gender** field from the **Customers** table into the **Legend** well.
- e) Add the **Sales Revenue** field from the **Sales** table into the **Size** well.



- f) Add the **Units Sold** field and the **Customer Count** field from the **Sales** table into the **Tooltips** well.




- g) With the Map visual still selected, switch over the Format properties pane.
- h) In the **Data colors** section, change the **Female** color to pink and the **Male** color to blue.




Alternatively, you might prefer to select two colors other than pink and blue that don't perpetuate age-old, gender-based stereotypes.

- i) Configure the **Title** property of the matrix visual to **Off**.
- j) Configure the **Border** property of the matrix visual to **On**.







- k) Reposition the map visual so it appears in the bottom left corner of the report page.




29. Save your work by clicking the **Save** button at the top left of the main Power BI Desktop window.
30. Publish the project to the Power BI service.
- Navigate to **Home** tab in ribbon
  - Click the **Publish** button on the far right-hand side of the ribbon.




- c) When prompted to **Select a destination**, choose **My Workspace** then click the **Select** button.




- After a project which uses DirectQuery mode has been published, Power BI Desktop will prompt you with a dialog which informs you that you must configure the data source credentials before the report can be used.
- Click the link with the caption **Open 'DirectQuery Lab.pbix' in Power BI** to navigate to the Power BI service in the browser.




- f) When you navigate to the report for the **DirectQuery Lab** project, you will notice that the visuals cannot render their data and there is a message bar with the error message **"We need your credentials to access the data source"**.
- g) Click the **Enter credentials** link to the right of the error message to redirect to the data source settings page.




- h) When you inspect the **Data source credentials** section for the **DirectQuery Lab** dataset, you should see another error message indicating the data source cannot be queried because no credentials have been provided.
- i) Click the **Edit credentials** link.




- j) On the **Configure DirectQuery Lab** dialog, set the **Authentication method** property to **Basic**
- k) Enter a **User name** of **CptStudent**.
- l) Enter a **Password** of **pass@word1**.
- m) Click the **Sign In** button to save the credentials and cache them inside the Power BI service.



- n) The Power BI service should display a notification that the data source has been updated.



- o) At this point, you should now be able to access the **DirectQuery Lab** report. Each time you select a different year in the slicer, the Power BI service will execute a query against the Azure SQL Server database to update the report.



Congratulations. You have now completed this lab exercise.