

Supplementary Material 1 for: Continuous curation of an *Alteromonas macleodii* metabolic model

Helen Scott, Devlin Moyer, Osnat Weissberg, Franziska Kratzl, Waseem Bashir
Valiya Kalladi, Rogier Braakman, Mary Ann Moran, Daniel Sher, Daniel Segrè

Contents

1	Motivation	2
1.1	Why do we need this?	2
1.2	What have people been doing before this?	2
1.2.1	MEMOTE	2
1.2.2	standard-GEM	2
1.2.3	human-GEM and yeast-GEM	2
1.3	What's new here	2
2	Set-Up	3
2.1	What is GitHub?	3
2.1.1	Diffs	3
2.2	What's in a Name?: Choosing your Model and Repository Name	5
2.3	Branches	6
2.4	Repository Structure	6
2.4.1	Model	6
2.4.2	Data	6
2.5	GitHub Actions	6
2.5.1	Defining an Action with a YML file	6
3	The Continuous Curation Loop	6
3.1	Step 1) Curate	7
3.1.1	Removing Reactions/Metabolites	7
3.1.2	Commits	7
3.1.3	Pull Requests	8
3.2	Step 2) Test	8
3.2.1	What is a Unit Test?	8
3.2.2	What makes a Good Unit Test?	9
3.2.3	Examples of Unit Tests on the Model	10
3.2.4	Examples of Unit Tests on the Data Files	11
3.2.5	Examples of Unit Tests on Tools	13
3.2.6	Examples of Unit Tests on Consistency Between Two Objects	13
3.3	Step 3) Report	13
3.3.1	Scripts vs Tests	13
3.4	Step 4) Release	14
3.5	Step 5) Run	14
3.6	Step 6) Monitor	14
4	Why can't you just make it for me?	15
5	What's the cost?	15

6	How to think like a Programmer	15
6.1	Questions to Ask Yourself:	15
7	Glossary	16
	References	17

GEMs are, at their heart, a software product, and we took lessons from software development and applied them to the model curation process. We term this constant testing and iterative model improvement strategy “continuous curation”, inspired by continuous integration (CI) for traditional software. This included tracking all changes using version control, having multiple curators collaborate and propose changes by working on branches and opening pull requests, testing the model with defined pass/fail tests, and automatically generating artifacts for curator inspection.

- None of this is really new
 - we borrowed all of this from software engineering
 - other groups do or are developing similar things
 - we took some things directly from human-GEM and standard-GEM
 - the field is crystallizing
 - but the field lacks a single reference point for guidelines

1 Motivation

1.1 Why do we need this?

- GEMs are important tools
 - But their quality is often questioned
- Manual curation is hard/messy
 - Manual curation can be an overwhelming task- the typical advice of just go “pathway by pathway” can be paralyzingly large
- Manual curation can last for a long time (including decades, spanning many people and projects)
 - Often one group publishes a model, then another may find it, modify it, and publish a new paper, resulting in branching sets of models

1.2 What have people been doing before this?

1.2.1 MEMOTE

- MEMOTE exists (1)
 - but it’s more of a benchmarking tool- a lot of things is just about the file
 - test what the custom tests ever did

1.2.2 standard-GEM

- standard-GEM is... (2)
- no tests

1.2.3 human-GEM and yeast-GEM

- some tests
- A lot of things were not enforced, just reminders and check boxes

1.3 What’s new here

- Our specific unit tests- not really clear who go to running it as CI first...
- Biomass component producibility heatmaps

- Improved tracking removed reactions/metabolites

2 Set-Up

2.1 What is GitHub?

Version control is critical for model curation because it tracks the “who”, “what”, and “when” of all changes made to the model. Who edited the model file, when did they make the edits, and what exactly was changed. It also maintains the historical versions of the model file, so at any time you can revert changes and return to an older version of the model.

Version control keeps a historical record of changes made to tracked files in a specialized database called a repository (or “repo”). Git is the software tool that enables version control, and GitHub is one popular cloud-based platform to host Git repositories, that also offers other functionalities such as issue tracking and wiki hosting. While we used GitHub, and will use GitHub-focused terminology (e.g., pull requests, actions) it is not the only option for hosting Git repositories, other popular options include GitLab, Bitbucket and Azure DevOps, each of which have analogous tools to those we describe here and could similarly be used for a continuous curation pipeline.

- A Git repository lives in two places. . .
- Local vs Remote, basic terminology (commit, push, pull, etc.)




Figure 1: An introduction to basic Git terminology: Local and remote repositories, commit, push, and pull

2.1.1 Diffs

- How to read a diff

Commit e8c0690 Preview Give feedback Browse files

hgscott committed 6 hours ago

Remove more nan formulae

main 1 parent ff92fbf commit e8c0690

Filter files... 1 file changed +2 -2 lines changed Search within code

@@ -7399,7 +7399,7 @@			
7399			</html>
7400			</notes>
7401			</species>
7402	-		<species id="M_cpd27484_c0" name="MPT-Synthases [c0]" compartment="c0" hasOnlySubstanceUnits="false" boundaryCondition="false" constant="false" fbc:charge="0" fbc:chemicalFormula="nan">
7403			<notes>
7404			<html
7405			xmlns="http://www.w3.org/1999/xhtml">
			<p>modelseed_template_id:
			cpd27484_c</p>

- Not all diffs are equally helpful
 - File types to avoid
 - Microsoft office files: e.g., .xlsx

Excel

Commit 5fd631e

[Preview](#)
[Give feedback](#)
[Browse files](#)

hgscott committed on Jan 24 · ✖ 0 / 1

Expand the annotation cols

main

1 parent [ce4f625](#) commit 5fd631e

2 files changed
+16 -0 lines changed

> export_model.py

+16 ■■■■■ ...

▼ model.xlsx

40.2 KB ...

Binary file not shown.

CSV

[illegible]

For a more in depth coverage, see...

2.2 What's in a Name?: Choosing your Model and Repository Name


- BiGG names models following a pattern, of i{Author's Initials}{Number of genes in the model} (3)
 - the i in the name refers to an in silico model (that is, a computer model)
 - e.g., iJR904 is an in silico model (i), built by Jennifer Reed (JR), containing 904 genes (904)
 - The 'i' in the name refers to an in silico model (that is, a computer model). This 'i' is followed by the initials (XX) of the person who developed the model and then the number of genes (xxx) included in the model. (3)
 - i.e. the current E. coli model is iML1515
 - M stands from Jonathan Monk, L stands for Colton Lloyd
 - iJO1366 is by Jeffrey Orth
- But this naming is inherently a snapshot, and would have to be continuously updated as the model evolved
 - Every time you add or remove a gene you would need to change the number
 - As new curators contribute to the model or take over, the author list may expand or change, or people may be annoyed to leave an old authors name at the prime spot
- It would be better instead to have a single name that is not dependent on the author or gene list, that

is specific to the organism

- It would be nice to instead have on model with different versions
- e.g. e.coli model v1, e.coli model v2, to make it clear the lineage of the model
- The recommendation from standard-GEM is to name the repository and model {something}-GEM, a common name, KEGG organism, or taxonomy-derived short name
 - e.g. Human-GEM and yeast-GEM
 - We followed that advice, and named the model MIT1002-GEM

2.3 Branches

Branching is a key feature of Git- it allows developers to isolate their changes so that the main version of the repository is not affected. This allows multiple developers to work simultaneously, and allows developers to test out changes where they will not affect anyone else. We chose to use a branching strategy based on the popular GitFlow strategy. We had two long-lived branches, “main”, the main branch, which had the official releases of the model, and “dev”, the development branch, where all accepted changes to the model were integrate before an official release. All changes made the model were made on feature branches that branched off of and were merged back into the dev branch. This ensured that any new feature development did not disturb the main model. Early on in development, branching is critical to XXX, and later branching became increasingly important to differentiate the version of model from users vs from developers.



2.4 Repository Structure

2.4.1 Model

2.4.1.1 What file type to use?

- XML
- SBML

2.4.2 Data

2.5 GitHub Actions

We used automation through GitHub actions to run tests and scripts upon the opening of a pull request.

2.5.1 Defining an Action with a YAML file

3 The Continuous Curation Loop

The Continuous Curation loop consists of 6 steps: 1. Curate 2. Test 3. Report 4. Release 5. Run 6. Monitor




Figure 2: Continuous Curation is an iterative process with the following steps: Curate, Test, Report, Release, Run, and Monitor.

3.1 Step 1) Curate

NOTE: We do not discuss here how to make curation decisions, but rather how to implement them

- How big is one curation task?

3.1.1 Removing Reactions/Metabolites

- Palsson said to do it (4)
- What we took from human-GEM: the table
- What is new
 - The standard vocabulary of reason
 - The list of removed things in the model file itself
 - And the test to make sure it does not drift
 - The test that no old reactions are still in the model file

3.1.2 Commits

- Commit often- don't just wait until the end of all your changes
- Use concise descriptive commit messages
- Use semantic commits
 - [optional scope]:
 - We got this from standard-GEM
 - type
 - chore: updating toolbox, data files, etc.
 - doc: updating documentation or explanatory comments in functions.
 - feat: new feature added, e.g. new reaction / metabolite / function / etc.
 - fix: something that was incorrect in the model and now has been corrected.
 - refactor: see code refactoring.
 - style: minor format changes of model, functions or data (spaces, semi-colons, etc., no code change)
 - scope
 - optional
 - refers to the receiver of the action, i.e. what part of the model/data are you modifying
 - description
 - concise description of what you did
 - some examples (direct copy from yeast-GEM contributing guidelines) |commit|commit message| |:—:|—:| |Add new rxns|feat-rxn: methanol pathway| |Remove a metabo-

```

lite|fix-met: duplicated citrate| |Add metabolite formula|feat-met.prop: carbohydrate
formulas| |Fix rxn stoichiometry|fix-rxn.prop: complex V stoich coeffs| |Update
gene IDs|fix-gene.annot: update IDs from SWISSPROT| |Format name of compart-
ment|style-comp.annot: remove uppercases| |Split a rxn in 2|refactor-rxn: split
isomerase in 2 steps| |Add some data|feat-data: metabolomics data| |Update documenta-
tion of function|doc: addDBnewRxn.m| |Update toolbox|chore: update RAVEN version|

```

3.1.3 Pull Requests

One critical component of the history of changes to the model is the “why”- why was a change to the model made (e.g., was a reaction found to have genomic evidence, was there a mistake in the biochemistry database, etc.). There are text fields in the model file itself where this information can be stored, and there have been cases in the past of defined “codes” used to represent different types of evidence that support each reaction (CITE EXAMPLES) however we have found that these are not well used, lack standardization across the community, and are often not comprehensive enough to fully explain the reasoning behind each change. We instead elected to document these in issues and pull requests on the repository. Issues can be used as a sort of electronic lab notebook. To ensure that all curators (present and future) are reminded to document their reasoning, a pull request template was used.

- Open a pull request, that starts the cycle

3.2 Step 2) Test

- Testing code is important, testing the model is just as important
- Typical software tools can be used, but some concepts need to be generalized
- Unit tests are considered critical to the success of any project

3.2.1 What is a Unit Test?

- Unit tests are a common software development practice in which the smallest individual parts of the code (called units) are individually tested, to ensure each gives the expected outcome

3.2.1.1 Software example

- Imagine you have a python module called `hello` with a single function, also called `hello`, that says “Hello” to a person, given their name:

```

def hello(name: str):
    message = 'Hello, ' + name + '!'

    return message

```

- To write the unit test, you would make a new file, by convention in a directory named “test” or “tests”, and name the file “test_[module name]”, for that individual python module, so in our case “test_hello”
- While there are other testing frameworks, we show the python standard-library testing framework, `unittest`
- In your test, you first import `unittest`, and your function that you are testing

```
import unittest
```

```
from hello import hello
```

- All tests are put within a class

```
class TestHello(unittest.TestCase):
```

- Within that class you can write multiple tests
- For example, first test an expected input, e.g., “Helen”

- `def test_helen(self):`
 - # Define a name*
 - `name = 'Helen'`
 - # Call the function*
 - `message = hello(name)`
 -
 - # Assert that the function returns the correct string*
 - `self.assertEqual(message, 'Hello, Helen!')`
- You define if the output is correct or not with an assert statement
- There are other options for assert statements that make sense for different kinds of tests
 - Table/list of assert statements
- Then test an edge case, something that could return a bad output if your function is not properly written, e.g. a number

Add a test checking that the function fails when an integer is passed

```
def test_integer(self):
    # Define a name
    name = 123
    # Call the function
    with self.assertRaises(TypeError):
        message = hello.hello(name)
```

- At the end of the file- set it to run all of the classes

```
if __name__ == '__main__':
    unittest.main()
```

- Unit tests can be run manually- e.g., a developer runs them on their own computer and verifies that they all pass before pushing code
- Or they can be run automatically (e.g., as part of a GitHub action)
- In GEM-MIT1002 we run them all automatically in the CI-workflow, finding and executing tests with pytest

3.2.2 What makes a Good Unit Test?

- Needs to pass/fail, have an expected outcome, not generate an artifact
 - Boolean result- pass or fail
 - Self-validating — it returns pass or fail, not output a human must inspect
- One reason to fail — a test asserting five things tells you “something broke,” not what
- Fast — slow tests don’t get run, and a suite people skip provides no safety
- Independent — no test depends on another’s state or on run order
- Repeatable — same result on any machine, any time; no network, no clock, no randomness
- Deterministic — the intermittent test is worse than no test, because it trains people to re-run until green
- No logic in the test — conditionals and loops inside a test can themselves be buggy, and then you’re debugging your test
- Tests behavior, not implementation — a test that breaks when you refactor without changing behavior is a liability
- A name that says what broke without opening the file
- Table with columns:
 - Example of good unit tests

- Test that a script generate the correct data and saves a plot with the correct path
- Example of bad unit tests
 - Generate a figure, that you need to look at
 - A test you know will fail, and you will just ignore it (skip the test or mark it a known failure instead)
- We can differentiate the tests used in GEM-MIT1002 by what they tested, the model, the data files, the helper tools, or consistency between two things. A single test file can contain multiple different kinds of tests, so some file names may repeat across the list.

3.2.3 Examples of Unit Tests on the Model

- In traditional software engineering, the unit being tested is often a function, however for the case of model curation, we are testing the model as a whole, but can write tests to focus on individual aspects of the model
- The ones we present here are by no means an exhaustive list of everything that could or should be tested.
- Many of these tests use previously published tools (e.g., MEMOTE), but we found that by implementing them with unit tests on a GitHub action it was easier to track model performance over time and recognize errors introduced into the model quickly.
- `test_biomass.py`
 - `TestBiomass`
 - `test_biomass_weight`:
 - Tests that the biomass reactions component metabolites add up to 1 g
 - this ensures that one mole of the biomass pseudometabolite is equal to 1 g of dry weight
 - this is important to ensure that the flux through the biomass reaction is indeed equivalent to growth rate
 - this test uses `gem_utils.biomass.calculate_biomass_weight()`
- `test_cycles.py`:
 - `TestCycles`
 - `test_atp_generating_cycles`
 - Tests that there are no erroneous energy generating cycles capable of regenerating ATP without an input carbon source, using the MEMOTE function `memote.support.consistency.detect_energy_generating_cycles()` (1)
- `test_exchanges.py`:
 - `TestExchanges`
 - `test_dead_end_extrac_mets`
 - Tests that there are no dead-end transporters (i.e., external metabolites without an exchange reaction).
- `test_growth.py`:
 - `TestGrowthWithoutCarbon`
 - `test_no_growth_without_carbon`
 - Tests that the model is not capable of growth without a carbon source in the medium.
 - `TestExpectedGrowthPhenotypes`
 - `test_no_new_mismatches`
 - Tests that the model never gets worse (i.e., that there is never a new mismatch)
 - Compares against a committed baseline of accepted mismatches
 - This keeps you from having a test you will fail for the majority of time of curation
 - It's a ratchet, once the model is better (i.e., you've gap-filled for a new reaction), the baseline is updated, so that you now compare against it
 - `test_no_stale_baseline_entries`
 - Tests that baseline mismatches that now match are removed from the baseline mismatch file
 - `test_mismatch_categories_are_unchanged`
 - Tests that the category of mismatch (i.e., false positive or false negative) is correct and

- current- these can become wrong if the file is edited by hand
 - `test_excluded_rows_are_not_scored`
 - Tests that growth phenotypes that are marked to be excluded (e.g., because we were unsure about the data, or a control was missing) were not included in the matching score
 - `test_every_phenotype_was_evaluated`
 - Tests that all growth phenotypes were evaluated- none were silently dropped
- `test_sbml.py`:
 - `TestValidSBML`
 - `test_valid_sbml`
 - Tests that the SBML file is valid
 - Important as COBRApy may fail to load a model with a malformed file
 - KBase created such files- they had “null” in `fbcc:chemicalFormula`
 - `test_isolated_genes_and_mets`
 - Tests for genes and metabolites in the model not associated with any reaction
 - Taken from the Human-GEM repo
 - `test_mass_balance`
 - Tests that all reactions were mass and charge balanced
 - Using the built-in COBRApy function, `cobra.manipulation.check_mass_balance()`

3.2.4 Examples of Unit Tests on the Data Files

- `test_deprecated.py`
 - `TestDeprecatedSchema`
 - `test_headers_exact`
 - Tests that the header row are the same column names, in the same order, and with no extra, defined in `COLUMNS` in `tools.deprecate`: “id”, “name”, “reason”, “replaced_by”, “pr”, “date”, “notes”
 - `test_no_duplicate_ids`
 - Tests that there are no duplicate ids in the deprecated tables- i.e. that each ID only has one row
 - `test_reasons_in_vocabulary`
 - Tests that all values in the `reason` column of the deprecated tables are from the list `REASONS` defined in `tools.deprecate`: “duplicate”, “id_changed”, “no_genomic_evidence”, “no_experimental_evidence”, “mass_imbalance”, “infeasible_cycle”, “dead_end”, “orphaned”, “erroneous_annotation”, “out_of_scope”, “unknown”,
 - `test_ids_have_no_sbml_prefix`
 - Tests that the IDs listed in the deprecated tables do NOT have the SBML prefixes (“R_”, “M_”, “G_”) on them, e.g., a reaction ID should be `rxn00196_c0`, not `R_rxn00196_c0`
 - `test_dates_are_iso`
 - Tests that all dates are given in YYYY-MM-DD format
 - `test_pr_format`
 - Tests that all PRs are given as a number sign followed by a number, e.g., `#123`
 - `test_notes_are_under_200_char`
 - Check that all notes are under 200 characters
 - Notes in the deprecated table should really just be a short summary, you can go into more detail in the PR
 - `TestReplacedBy`
 - `test_separator_is_semicolon`
 - Test that there are no `, + [] {} () ' "` in the replaced by column
 - If you need a list of ids, they should be separated by semi-colons (`;`)
 - `test_no_sbml_prefix_on_targets`
 - See `TestDeprecatedSchema > test_ids_have_no_sbml_prefix`, now just on the IDs in the `replaced_by` column, instead of the ID column
 - `test_no_duplicate_targets`

- Tests that for each row in the deprecated tables, the `replaced_by` column doesn't include any repeats, e.g., your `replaced_by` column cannot be "cpd9999;cpd9999"
- `test_required_when_reason_is_relative`
 - Tests that if a row in the deprecated table was removed due to any of the reasons defined in `REASONS_REQUIRING_REPLACEMENT` ("duplicate", "id_changed"), that there is also an entry in that row's `replaced_by` column
- `test_not_self_referential`
 - Tests that an ID is not replaced by itself, i.e., that the ID in the ID column and the ID in the `replaced_by` column are not the same
- `test_targets_resolve`
 - Tests that all IDs in the `replaced_by` column are either in the model or are in the deprecated list as well
- o `TestVocabularyDocumented`
 - `test_every_reason_in_readme`
 - Tests that a README file exists at `data/deprecated_identifiers/README.md`
 - Tests that every reason defined in `tools.deprecate.REASONS` ("duplicate", "id_changed", "no_genomic_evidence", "no_experimental_evidence", "mass_imbalance", "infeasible_cycle", "dead_end", "orphaned", "erroneous_annotation", "out_of_scope", "unknown") is defined in a table in the README under the heading "### Controlled vocabulary for reason"
- `test_phenotype_data.py`
 - o `TestPhenotypeSchema`
 - `test_growth_column_vocabulary`
 - Test that every value in the column `growth` is either "Yes", "No", or "Unsure"
 - `test_exclude_reason_vocabulary`
 - Test that every value used in the "exclude_reason" column, is from the dictionary `EXCLUSION_REASONS` defined in `tools.phenotypes`: "control_failed", "id_uncertain", "conflicting_reports", "not_representable"
 - `test_every_reason_is_documented`
 - Test that every reason for exclusion defined in the `EXCLUSION_REASONS` dictionary is included in the table in the ### `exclude_reason` section of `data/README.md`
 - `test_every_documented_exclusion_reason_has_a_description`
 - Tests that the definition table in the README doesn't include any blank cells
 - `test_condition_keys_are_unique`
 - Test that `minimal_media + c_source` identifies a row, there are no duplicates of that value pair
 - `test_met_ids_are_present_and_well_formed`
 - Test that all values in the `met_id` column are non-empty lists, and each value in the list begins with "cpd"
 - Note, this only works if the model is in the ModelSEED ID namespace, and that all metabolites tested were present in the ModelSEED database (e.g., nothing had to be custom defined)
 - o `TestExpectedMisMatches`
 - `test_baseline_has_the_expected_columns`
 - Tests that the baseline mismatch file contains the columns defined in `tools.phenotypes.MISMATCH_COLUMNS`: "minimal_media", "c_source", "category", "notes"
 - `test_baseline_rows_refer_to_real_conditions`
 - Tests that the mismatches listed in the baseline mismatch file exist in the phenotype data file
 - `test_baseline_does_not_list_excluded_conditions`
 - Tests that excluded rows of the phenotype data are not listed in the baseline file
 - Excluded rows are not scored, so they cannot be mismatches, so they should not be in the baseline

3.2.5 Examples of Unit Tests on Tools

Part of the GEM-MIT1002 repo is helper functions (i.e. for XXX), these functions, just like any other functions in a python module should be tested. For example: `* test_growth.py *` `TestSummaryArithmetic` `* test_every_row_gets_a_known_category *` Tests that every row in the expected growth phenotype table gets one of the categories defined in `tools.phenotypes.CATEGORIES`: “true_positive”, “true_negative”, “false_positive”, “false_negative”, “unsure”, “invalid_solve”, “excluded” `* test_categories_partition_the_table *` Tests that `tools.phenotypes.summarise()` does not count any row twice: the total number of rows in the phenotype table matches the sum of scored rows and unscored rows `* test_no_uptake_route_is_a_subset_of_the_negative_predictions *` Tests that the number of phenotypes with “no_uptake_route” is less than the total number of phenotypes marked as false negative and true negative, since a metabolite with no uptake route can never have positive growth `* test_a_missing_exchange_does_not_by_itself_decide_the_verdict *` Test that no growth phenotypes where the model is missing an exchange, but still grows, is not marked as “no_uptake_route” `* test_confusion_matrix_sums_to_the_scored_rows *` `test_matches_are_the_concordant_cells *` `test_matches_never_exceed_the_interpretable_denominator` `* test_excluded_rows_keep_their_underlying_verdict *` `test_deprecated.py` `* TestStampPrNumber *` `test_fills_blanks_and_preserves_existing *` `test_is_idempotent` `* test_rejects_non_numeric *` `TestIdentifierListParsing` `* test_accepts_common_separators *` `test_strips_sbml_prefixes *` `test_empty_is_empty *` `test_normalizes_to_semicolons *` `test_record_normalizes_on_construction` `* test_preserves_gene_style_identifiers *` `test_phenotype_data.py` `* TestCountInterpretable *` `test_counts_only_definite_unexcluded_rows *` Tests that the `tools.phenotypes.count_interpretable()` function works on small 6 row data frame, covering every combination of Yes, No, Unsure and excluded, not `* test_one_row_at_a_time *` Tests each row in the dummy table one at a time, so that the exact row that caused the failure in the previous is identified `* test_empty_table_is_zero *` If you give `count_interpretable()` an empty table, it should return 0

3.2.6 Examples of Unit Tests on Consistency Between Two Objects

- `test_deprecated.py`
 - `TestDeprecatedNotInModel`
 - `test_deprecated_reactions_absent`
 - Tests that no reactions in the deprecated reactions table are present in the model
 - Could occur if someone adds back a reaction without realizing it was removed before
 - `test_deprecated_metabolites_absent`
 - Tests that no metabolite in the deprecated metabolites table are present in the model
 - Could occur if someone adds back a reaction without realizing it was removed before
 - `TestNotesMirror`
 - `test_mirror_matches_tsv`
 - `test_pointer_present`
 - `test_mirror_survives_cobrapy_round_trip`

3.3 Step 3) Report

3.3.1 Scripts vs Tests

- Scripts differ from tests because they cannot “pass” or “fail”, and instead generate artifacts (e.g., plots) for a human curator to look at
- If you can state in advance what is right or wrong- make a test
- If you can use the information, but you’re not sure what is right- make a scripts
- Tests can block a merge- you need to pass all tests before you can merge a PR
- Scripts don’t block anything
- Automated- also ran through GitHub actions
 - Doesn’t include any arguments or hand editing
- Should be something you need continually- not just a one off for a specific question
 - If no one is looking at the artifact- you don’t need the script

- They might share code with tests
 - E.g. the growth phenotype plot uses the same code as the growth phenotype ratchet test
 - Make sure shared code lives in tools, not recreated in both files ##### Examples of Scripts Used for Model Curation
- Using the same underlying code as the growth test, we generated a plot of which experimentally known growth phenotypes the model matched or not. The heatmap visualization was useful for sharing results.
- While this graph is useful to grasp model performance at a glance, it was not the most instructive when gap-filling the model (just knowing that the model does not grow does not help you find a gap). Instead we checked the model's ability to produce each individual biomass component (i.e., we added a demand/sink reaction for each biomass component that take the metabolite and removes it from the system (similar to an exchange reaction), and looped through the list of biomass components and set each as the objective, maximizing the flux through that sink reaction. A positive value indicated that the model was capable of producing that biomass component. This helped narrow down searches for gaps (e.g., could say that a subset of amino acids was not producible, therefore there must be a gap in that pathway). When using an objective other than the biomass, we considered if there should be free transport/exchange/sinks for all biomass components simultaneously or if only the one being maximized should have a sink. Theoretically, there could be components whose production is tied and without flux through the biomass reaction, dead ends could appear that block flux.

3.4 Step 4) Release

- What counts as a new version
- Chores upon release
 - different file types
 - MEMOTE (1)
 - MACAW (5)
- GitHub release
- Zenodo release

3.5 Step 5) Run

- This is the fun part, where you, or others, actually try to use the model
- Who might be using the model
 - Yourself- as the person making the model- you probably have questions you are interested in and simulations you would like to run
 - Your collaborators
 - Strangers- people who read your paper and want to use your model- potentially years after initial publication
- Making the model available to run throughout the curation process is what makes our curation “continuous”, we aren't trying to finish the model before every using it, but will update the model as issues are found in use
- This means that you can curate the model in order of scientific questions- curating the pathways relevant to specific questions first, rather than in an arbitrary order
 - This means that the model will be better in regions of the metabolic network of previous interest
- This helps discover unexpected problems in the model- tests can only catch expected problems
- For tutorials on how to use a GEM to run FBA, see COBRA tutorials
 - MATLAB: <https://opencobra.github.io/cobratoolbox/stable/tutorials/>
 - COBRApy: <https://cobrapy.readthedocs.io/en/latest/>

3.6 Step 6) Monitor

- Typically there is limited feedback after publication- someone might try to recreate your results or use your model, but if it fails, they have no where to turn
- GitHub issues can be used to plan, discuss, and track work

- anyone can open an issue
- Use issues to keep track of bugs, enhancements, or other requests
- When to open an issue
 - You find something wrong
 - Bug/weird simulation results
 - New data to add
 - Missing feature you would like the model to have
 - Documentation confusing or unclear
 - Any type of feedback
- Open an issue
 - How to open an issue
 1. Go to the main page of the repository
 2. Click Issues
 3. Click New Issue
 - GitHub issues are written in [GitHub Flavored Markdown](#)
- What belongs in an issue
 - A concise and descriptive title
 - e.g. model does not grow on glucose, not model wrong, or “I tried to simulate growth on glucose, and got 0.00”
 - In the description
 - Detailed description
 - Provide context- including what you expected to happen versus what actually occurred
 - Step-by-step instructions for replicating the bug
 - include code, logs, or screenshots
 - Environment details
 - What OS are you using, what version of tools (e.g., COBRApy) are you using, what version of the model are you using, did you start from a release, from the main branch, from the dev branch
 - Note your issue is public, so don’t include anything you don’t want shared
 - Other repos (Human-GEM) have templates for reporting bugs, which can be helpful to ensure that someone gives all of the information needed to recreate and investigate the bug
- Anyone can comment on issues
- Unlike in traditional software this is a more human-dependent step- we aren’t just getting crash reports, we require people to really run the model and manually open issues
- While this might seem trivial, this is a critical step, because without opening issues curation becomes a straight line, not a loop, and can’t be continuous any more- so all issues are welcome!

4 Why can’t you just make it for me?

- Can’t you just make an installable tool that makes all of this for me?
- Everyone will have different data
- It is very possible to make a template- i.e. Standard-GEM

5 What’s the cost?

6 How to think like a Programmer

6.1 Questions to Ask Yourself:

- 1.

7 Glossary

- **Artifact:**
 - *In software engineering:*
 - *In continuous curation:*
- **Branch:** A branch is a parallel version of a repository. It is contained within the repository, but does not affect the primary or main branch allowing you to work freely without disrupting the “live” version.¹
- **Commit:** A commit, or “revision”, is an individual change to a file (or set of files). When you make a commit to save your work, Git creates a unique ID (a.k.a. the “SHA” or “hash”) that allows you to keep record of the specific changes committed along with who made them and when. Commits usually contain a commit message which is a brief description of what changes were made.²
- **Commit Message:** Short, descriptive text that accompanies a commit and communicates the change the commit is introducing³.
- **Conflict:** A situation where two branches have changes in a file that Git cannot automatically merge, requiring manual resolution⁴.
- **Continuous Integration (CI):** A development practice where team members frequently integrate their code into a shared repository, often multiple times a day. Each integration is verified by automated builds and tests to detect errors early⁵.
- **Continuous Delivery:** A software development practice where teams keep their product in a deployable state at all times, but deployment still requires a manual decision⁶.
- **Continuous Deployment:** A software development practice where every change that passes all automated tests is released to production automatically⁷.
- **Curation:**
 - *In continuous curation:*
- **Diff:** A diff is the difference in changes between two commits, or saved changes. The diff will visually describe what was added or removed from a file since its last commit⁸.
- **Feature Branch:** A branch used to experiment with a new feature or fix an issue that is not in production. Also called a topic branch⁹.
- **Git:** Git is an open source program for tracking changes in text files¹⁰.
- **GitFlow:**
- **GitHub:** A web-based platform that facilitates Git’s use for collaboration between individuals. Other web-based platforms include GitLab and BitBucket¹¹.
- **GitHub Actions:**
- **Issue:** Issues are suggested improvements, tasks or questions related to the repository. Issues can be created by anyone (for public repositories), and are moderated by repository collaborators. Each issue contains its own discussion thread. You can also categorize an issue with labels and assign it to someone¹².
- **JSON:**
- **Local:**
- **Merge:** Merging takes the changes from one branch (in the same repository or from a fork), and applies them into another. This often happens as a “pull request” (which can be thought of as a request to merge), or via the command line¹³.

¹<https://docs.github.com/en/get-started/learning-about-github/github-glossary>

²<https://docs.github.com/en/get-started/learning-about-github/github-glossary>

³<https://docs.github.com/en/get-started/learning-about-github/github-glossary>

⁴<https://informatics.fas.harvard.edu/resources/glossary/#git-terms>

⁵<https://www.agile-academy.com/en/agile-dictionary/>

⁶<https://www.agile-academy.com/en/agile-dictionary/>

⁷<https://www.agile-academy.com/en/agile-dictionary/>

⁸<https://docs.github.com/en/get-started/learning-about-github/github-glossary>

⁹<https://docs.github.com/en/get-started/learning-about-github/github-glossary>

¹⁰<https://docs.github.com/en/get-started/learning-about-github/github-glossary>

¹¹<https://informatics.fas.harvard.edu/resources/glossary/#git-terms>

¹²<https://docs.github.com/en/get-started/learning-about-github/github-glossary>

¹³<https://informatics.fas.harvard.edu/resources/glossary/#git-terms>

- **Monitor:**
 - *In software engineering:*
 - *In continuous curation:*
- **Pull:** The process of integrating changes from one version of a repository to another (e.g. from a fork back to the original repo, or from a branch back to the main branch). There are two general use cases: 1) When the owner of a repository makes changes to it, you pull those changes into your local copy. 2) When you make changes to a forked repository or a branch of a repository and want to incorporate the changes back to the original repo or branch, you initiate a pull request, and then whoever is in charge of the original repository can pull those changes in ¹⁴.
- **Pull Request:** Pull requests are proposed changes to a repository submitted by a user and accepted or rejected by a repository's collaborators ¹⁵.
- **Push:** To push means to send your committed changes to a remote repository on GitHub.com. For instance, if you change something locally, you can push those changes so that others may access them ¹⁶.
- **Release:**
 - *In software engineering:*
 - *In continuous curation:*
- **Remote Repository:** This is the version of a repository or branch that is hosted on a server, most likely GitHub.com ¹⁷.
- **Report:**
 - *In software engineering:*
 - *In continuous curation:*
- **Repository/Repo:** A repository is the most basic element of GitHub. They're easiest to imagine as a project's folder. A repository contains all of the project files (including documentation), and stores each file's revision history. Repositories can have multiple collaborators and can be either public or private ¹⁸.
- **Run:**
 - *In software engineering:*
 - *In continuous curation:*
- **SBML:**
- **Script:**
 - *In software engineering:*
 - *In continuous curation:*
- **Semantic Versioning:**
- **Test:**
 - *In software engineering:*
 - *In continuous curation:*
- **Trunk-Based Development:**
- **Version Control:** The process of tracking changes to files over time, allowing you to recall specific versions later ¹⁹.
- **XML:**

References

1. Lieven C, others. 2020. [MEMOTE for standardized genome-scale metabolic model testing](#). Nature Biotechnology 38:272–276.

¹⁴<https://informatics.fas.harvard.edu/resources/glossary/#git-terms>

¹⁵<https://docs.github.com/en/get-started/learning-about-github/github-glossary>

¹⁶<https://docs.github.com/en/get-started/learning-about-github/github-glossary>

¹⁷<https://docs.github.com/en/get-started/learning-about-github/github-glossary>

¹⁸<https://docs.github.com/en/get-started/learning-about-github/github-glossary>

¹⁹<https://informatics.fas.harvard.edu/resources/glossary/#git-terms>

2. Anton M, others. 2023. standard-GEM: Standardization of open-source genome-scale metabolic models. bioRxiv <https://doi.org/10.1101/2023.03.21.512712>.
3. Reed JL, Vo TD, Schilling CH, Palsson BO. 2003. [An expanded genome-scale model of Escherichia coli K-12 \(iJR904 GSM/GPR\)](#). Genome Biology 4:R54.
4. Thiele I, Palsson BØ. 2010. [A protocol for generating a high-quality genome-scale metabolic reconstruction](#). Nature Protocols 5:93–121.
5. Moyer D, others. 2025. MACAW: A method for semi-automatic detection of errors in genome-scale metabolic models. Genome Biology <https://doi.org/10.1186/s13059-025-03533-6>.