

Ch23-Trees

August 7, 2020

1 Trees

<http://openbookproject.net/thinkcs/python/english3e/trees.html> - like linked lists, trees are made up of nodes

1.1 Binary Tree

- is a commonly used tree in which each node contains a reference to atmost two other nodes (possibly None)
- these references are referred to as the left and right subtrees
- like the node of linked list, each node also contains data/cargo
- like linked lists, trees are recursive data structures that are defined recursively:
 1. the empty tree, represented by None, or
 2. a node that contains a data and two tree references (left and right subtree)

1.2 Building trees

- similar to building linked-list

```
[1]: class Tree:
      def __init__(self, data, left=None, right=None):
          self.cargo = data
          self.left = left
          self.right = right

      def __str__(self):
          return "{}".format(self.cargo)
```

1.2.1 bottom-up way to build-trees

- first create children and link them to the parent

```
[4]: left = Tree(2)
      right = Tree(3)
      tree = Tree(1, left, right)
```

```
[5]: tree1 = Tree(10, Tree(20), Tree(30))
```

```
[6]: print(tree)
```

1

```
[7]: print(tree1)
```

10

1.3 traversing tree

- natural way to traverse a tree is recursively!

```
[8]: def findSum(tree):  
    if not tree:  
        return 0  
    return tree.cargo + findSum(tree.left) + findSum(tree.right)
```

```
[9]: findSum(tree)
```

[9]: 6

```
[10]: findSum(tree1)
```

[10]: 60

1.4 Expression trees

- trees are natural way to represent the structure of an expression unambiguously.
- infix expression $1 + 2 * 3$ is ambiguous unless we know the order of operation that $*$ happens before $+$
- we can use tree to represent the same expression
 - operands are leaf nodes
 - operator nodes contain references to their operands; operators are binary (two operands)
- applications:
 - translate expressions to postfix, prefix, and infix
 - compilers use expression trees to parse, optimize, and translate programs
- three ways to traverse trees: pre-order, in-order and post-order

```
[18]: expression = Tree('+', Tree(1), Tree('*', Tree(2), Tree(3)))
```

1.4.1 pre-order tree traversal

- contents of the root appear before the contents of the children
- recursive algorithm:
 - visit the node
 - visit left subtree
 - visit right subtree

```
[19]: def preorder(tree):
        if not tree:
            return
        print(tree.cargo, end=' ')
        preorder(tree.left)
        preorder(tree.right)
```

```
[20]: preorder(expression)
```

```
+ 1 * 2 3
```

1.4.2 in-order tree traversal

- contents of the tree appear in order
- recursive algorithm:
 - visit left subtree
 - visit node
 - visit right subtree

```
[21]: def inorder(tree):
        if not tree:
            return
        inorder(tree.left)
        print(tree.cargo, end=' ')
        inorder(tree.right)
```

```
[22]: inorder(expression)
```

```
1 + 2 * 3
```

```
[29]: def inorderIndented(tree, level=0):
        if not tree:
            return
        inorderIndented(tree.right, level+1)
        print(' '*level + str(tree.cargo))
        inorderIndented(tree.left, level+1)
```

```
[30]: inorderIndented(expression)
```

```
      3
    *
    2
+
  1
```

1.4.3 post-order traversal

- recursive algorithm:

1. visit left subtree
2. visit right subtree
3. visit node

```
[33]: def postorder(tree):
      if not tree:
          return
      postorder(tree.left)
      postorder(tree.right)
      print(tree.cargo, end=' ')
```

```
[34]: postorder(expression)
```

```
1 2 3 * +
```

1.5 building an expression tree

- parse an infix expression and build the corresponding expression tree
 - e.g., $(3 + 7) * 9$ yields the following tree:
1. tokenize expression into python list? How (left as an exercise)
 - $(3 + 7) * 9 = [“(”, 3, “+”, 7, “)”, “*”, 9, “end”]$
 2. “end” token is useful for preventing the parser from reading past the end of the list

```
[31]: def get_token(token_list, expected):
      if token_list[0] == expected:
          del token_list[0]
          return True
      return False
```

```
[36]: # handles operands
      def get_number(token_list):
          x = token_list[0]
          if not isinstance(x, int):
              return None
          del token_list[0]
          return Tree(x, None, None) # leaf node
```

```
[37]: token_list = [9, 11, 'end']
      x = get_number(token_list)
      postorder(x)
```

```
9
```

```
[38]: print(token_list)
```

```
[11, 'end']
```

```
[39]: def get_product(token_list):
        a = get_number(token_list)
        if get_token(token_list, '*'):
            b = get_number(token_list)
            return Tree('*', a, b)
        return a
```

```
[40]: token_list = [9, '*', 11, 'end']
        tree = get_product(token_list)
```

```
[42]: postorder(tree)
```

9 11 *

```
[44]: token_list = [9, '+', 11, 'end']
        tree = get_product(token_list)
        postorder(tree)
```

9

```
[45]: # adapt the function for compound product such as 3 * (5 * (7 * 9))
def get_product(token_list):
    a = get_number(token_list)
    if get_token(token_list, '*'):
        b = get_product(token_list)
        return Tree('*', a, b)
    return a
```

```
[46]: token_list = [2, "*", 3, "*", 5, "*", 7, "end"]
        tree = get_product(token_list)
        postorder(tree)
```

2 3 5 7 * * *

```
[47]: # a sum can be a tree with + at the root, a product on the left, and a sum on
        → the right.
        # Or, a sum can be just a product.
def get_sum(token_list):
    a = get_product(token_list)
    if get_token(token_list, "+"):
        b = get_sum(token_list)
        return Tree("+", a, b)
    return a
```

```
[48]: token_list = [9, "*", 11, "+", 5, "*", 7, "end"]
        tree = get_sum(token_list)
```

```
[49]: postorder(tree)
```

```
9 11 * 5 7 * +
```

```
[52]: # handle parenthesis
def get_number(token_list):
    if get_token(token_list, "("):
        x = get_sum(token_list)          # Get the subexpression
        get_token(token_list, ")")      # Remove the closing parenthesis
        return x
    else:
        x = token_list[0]
        if not isinstance(x, int):
            return None
        del token_list[0]
        return Tree(x, None, None)
```

```
[53]: # 9 * (11 + 5) * 7
token_list = [9, "*", "(", 11, "+", 5, ")", "*", 7, "end"]
tree = get_sum(token_list)
postorder(tree)
```

```
9 11 5 + 7 * *
```

1.6 handling errors on malformed expressions

```
[54]: # handle parenthesis
def get_number(token_list):
    if get_token(token_list, "("):
        x = get_sum(token_list)          # Get the subexpression
        if not get_token(token_list, ")"): # Remove the closing parenthesis
            raise ValueError('Missing close parenthesis!')
        return x
    else:
        x = token_list[0]
        if not isinstance(x, int):
            return None
        del token_list[0]
        return Tree(x, None, None)
```

```
[55]: token_list = [9, "*", "(", 11, "+", 5, "*", 7, "end"]
tree = get_sum(token_list)
postorder(tree)
```

↳ -----

ValueError
Traceback (most recent call_
↪last)

```
<ipython-input-55-4140410c22b2> in <module>()
    1 token_list = [9, "*", "(", 11, "+", 5, "*", 7, "end"]
----> 2 tree = get_sum(token_list)
    3 postorder(tree)
```

```
<ipython-input-47-840e89a9fc06> in get_sum(token_list)
    2 # Or, a sum can be just a product.
    3 def get_sum(token_list):
----> 4     a = get_product(token_list)
    5     if get_token(token_list, "+"):
    6         b = get_sum(token_list)
```

```
<ipython-input-45-dc9c6c17cd73> in get_product(token_list)
    2     a = get_number(token_list)
    3     if get_token(token_list, '*'):
----> 4         b = get_product(token_list)
    5         return Tree('*', a, b)
    6     return a
```

```
<ipython-input-45-dc9c6c17cd73> in get_product(token_list)
    1 def get_product(token_list):
----> 2     a = get_number(token_list)
    3     if get_token(token_list, '*'):
    4         b = get_product(token_list)
    5         return Tree('*', a, b)
```

```
<ipython-input-54-e5973ec52d85> in get_number(token_list)
    4         x = get_sum(token_list)          # Get the subexpression
    5         if not get_token(token_list, ")"): # Remove the closing_
↪parenthesis
----> 6             raise ValueError('Missing close parenthesis!')
    7         return x
    8     else:
```

ValueError: Missing close parenthesis!

1.7 exercises:

1. Modify inorder function so that it puts parentheses around every operator and pair of operands. Is the output correct and unambiguous? Are the parentheses always necessary?
2. Write a function that takes an expression string and returns a token list.
3. Find other places in the expression tree functions where errors can occur and add appropriate raise statements. Test your code with improperly formed expressions.

[]: