## **Sprint 4**

Team ID	PNT2022TMID48824
Project Name	Personal Assistance for Seniors Who Are
	SelfReliant

## **Code for Simulation:**

```
#include <WiFi.h>//library for wifi
#include <PubSubClient.h>//library for MQtt
#include <LiquidCrystal_I2C.h>
#include "DHT.h"// Library for dht11
#define DHTPIN 15 // what pin we're connected to
#define DHTTYPE DHT11 // define type of sensor DHT 11
#define LED 2
DHT dht (DHTPIN, DHTTYPE);// creating the instance by passing pin and typr of
dht connected
void callback(char* subscribetopic, byte* payload, unsigned int
payloadLength);
//----credentials of IBM Accounts-----
#define ORG "64yf7x"//IBM ORGANITION ID
#define DEVICE_TYPE "b11m3edevicetype"//Device type mentioned in ibm watson
IOT Platform
#define DEVICE_ID "b11m3edeviceid"//Device ID mentioned in ibm watson IOT
Platform
#define TOKEN "-&EMtr71-v-Gz2G))e" //Token
String data3="";
int buzz= 13;
//----- Customise the above values ------
char server[] = ORG ".messaging.internetofthings.ibmcloud.com";// Server Name
char publishTopic[] = "iot-2/evt/Data/fmt/json";// topic name and type of
event perform and format in which data to be send
char subscribetopic[] = "iot-2/cmd/command/fmt/String";// cmd REPRESENT
command type AND COMMAND IS TEST OF FORMAT STRING
char authMethod[] = "use-token-auth";// authentication method
char token[] = TOKEN;
char clientId[] = "d:" ORG ":" DEVICE TYPE ":" DEVICE ID;//client id
LiquidCrystal_I2C lcd(0x27,16,2);
WiFiClient wifiClient; // creating the instance for wificlient
```

```
PubSubClient client(server, 1883, callback ,wifiClient); //calling the
predefined client id by passing parameter like server id, portand
wificredential
void setup()// configureing the ESP32
 Serial.begin(115200);
 dht.begin();
 pinMode(buzz, OUTPUT);
 pinMode(LED,OUTPUT);
 delay(10);
 Serial.println();
 wificonnect();
 mqttconnect();
}
void loop()// Recursive Function
 if (!client.loop()) {
   mqttconnect();
 }
}
/*.....retrieving to
Cloud....*/
void PublishData(float temp, float humid) {
 mqttconnect();//function call for connecting to ibm
void mqttconnect() {
 if (!client.connected()) {
   Serial.print("Reconnecting client to ");
   Serial.println(server);
   while (!!!client.connect(clientId, authMethod, token)) {
     Serial.print(".");
     delay(500);
   }
    initManagedDevice();
    Serial.println();
 }
void wificonnect() //function defination for wificonnect
{
```

```
Serial.println();
  Serial.print("Connecting to ");
  WiFi.begin("Wokwi-GUEST", "", 6);//passing the wifi credentials to establish
the connection
  while (WiFi.status() != WL_CONNECTED) {
    delay(500);
    Serial.print(".");
  }
  Serial.println("");
  Serial.println("WiFi connected");
  Serial.println("IP address: ");
  Serial.println(WiFi.localIP());
}
void initManagedDevice() {
  if (client.subscribe(subscribetopic)) {
    Serial.println((subscribetopic));
    Serial.println("subscribe to cmd OK");
  } else {
    Serial.println("subscribe to cmd FAILED");
  }
}
void callback(char* subscribetopic, byte* payload, unsigned int payloadLength)
  Serial.print("callback invoked for topic: ");
  Serial.println(subscribetopic);
  for (int i = 0; i < payloadLength; i++) {</pre>
    //Serial.print((char)payload[i]);
   data3 += (char)payload[i];
  }
  Serial.println("Medicine Name: "+ data3);
  if(data3 != "")
  {
    lcd.init();
    lcd.print(data3);
    digitalWrite(LED,HIGH);
    tone(buzz, 100, 1000);
    delay(2000);
    digitalWrite(LED,LOW);
   noTone(buzz);
   delay(1000);
  }
```

```
else
{
digitalWrite(LED,LOW);
}
data3="";
}
```

## **Output:**

