Data Integrity & 250+ Tournament Playbook

Winston-Salem readiness sprint, then the US Open production standard.
Version 2.0 — amended against the repository, the live site, and the calendar.

Eight defects observed in production are one problem: provider data enters MatchRead without enough normalization, validation, reconciliation or product-scope enforcement. This sprint makes the ingestion layer self-checking and self-repairing, and narrows the public product to the tournaments MatchRead has chosen to support.

VERSION	2.0 · supersedes v1.0 of 20 August 2026
OWNER	Launch engineer. One owner, one sprint, no parallel feature work.
EVIDENCE	Live-site audit of Cincinnati (`t-atp-21347`) and Tianjin (`t-atp-21964`); Tennis API Integration Brief; `FINAL-ENGINEERING-READINESS.md`; `ENGINEER-MAPPING.md`; migrations `0001–0028`.
REHEARSAL	Winston-Salem, ATP 250, draw pending for 24 August.
PRODUCTION	US Open, 31 August. Four working days between the two.

Green by 24 August. Winston-Salem cannot be run as a rehearsal without it.

Green by 31 August. Required for the US Open, not for the rehearsal.

After launch. Real work, wrong month.

> WHAT CHANGED IN V2.0
>
> Scope moved from seventh to first; a preflight section was added, because three of the four blockers in `FINAL-ENGINEERING-READINESS.md` are load-bearing for §7; the code map, the level enum and the identity migration were rewritten against the actual schema; the repository's rules on RLS, the service-role key and lock authority were restated; and a dated cut line was added. **§20 lists every change and its reason.**

01 · PREFLIGHT · GREEN BY 24 AUG

Four questions to answer before writing any code

`FINAL-ENGINEERING-READINESS.md` records four absent pieces of infrastructure. Everything in §7 assumes at least two of them exist. The live site shows draws advancing, so at least part of the ingest path is running — which means that document is now partly stale and nobody knows which part. Resolve that first. Half a day here saves a week of building on a path nothing invokes.

BLOCKER	EVIDENCE REQUIRED TO CLOSE IT	STATUS
`Settlement scheduling`	Every `pg_cron` call in the repository is a comment. Run `select jobid, jobname, schedule, active from cron.job;` against the production project and paste the output into the sprint log. If the four jobs in `runbooks/SETTLEMENT-SCHEDULING.md` are not armed, §7 has no settlement path to call.	UNKNOWN
`Edge function deployability`	`settle-slate` imports `npm:@matchread/core` and `settle-tournament` imports `npm:@matchread/settlement`; neither is published, and `core` depends on `i18n` through `workspace:*`. Deploy succeeds, first invocation 500s. Invoke each function once and record the response body.	UNKNOWN
`Socket listener`	ADR-0018 puts the socket in an always-on container. No `Dockerfile`, no `apps/listener`. Deferrable for the rehearsal at a stated cost: results arrive by REST sweep and lag by the sweep interval. Not deferrable for a public US Open.	UNKNOWN
`Auth round trip`	The magic-link flow has never been exercised against a deployed project. A rehearsal in which nobody can sign in is not a rehearsal. Run the nine-step manual check in the runbook once.	UNKNOWN

> **STOP CONDITION**
>
> If settlement is not scheduled, **arming it is the first commit of this sprint**, ahead of everything in §5. It has been described as the highest-value twenty lines in the repository for three consecutive phases. A reconciliation job that repairs fixture rows and then calls a settlement engine nothing invokes produces correct data and a dead product.

> **ALSO RESOLVE**
>
> The US Open start date disagrees between sources. The live calendar shows 31 August; the prototype fixture in `matchread-spec.html` assumes a 30 August start with a lock at `2026-08-30T15:00:00Z` — 11:00 ET. Both cannot be right, and the lock instant is the one moment in this product where being wrong is unrecoverable. Confirm against the provider before the rehearsal, not during it.

02 · DIRECTION

One trust boundary, not eight bugs

A wrong-tour player, a stalled quarter, a truncated surname, a universal Hard default and a tournament still marked Open ten days after play began are not five defects. They are five places where provider data crossed into MatchRead without being checked, and where the system chose a plausible value over an honest failure.

The fix is not more careful ingestion. It is an ingestion layer that **refuses to publish what it cannot verify**, repairs itself on a schedule, and reports its own failures before a consumer finds them. Every section below is an instance of that.

Priority order, revised

#	PRIORITY	WHY IT SITS HERE
1	Product scope: ATP/WTA 250+	**Moved from 7th.** One predicate takes the public calendar from ~250 events to ~10. It removes the ITF draws where the duplicate-label defect is worst, removes the M15 Tianjin draw where the cross-tour signal appeared, and reduces the number of tournaments the reconciliation job must keep fresh by an order of magnitude. It is the cheapest risk reduction available and it makes every subsequent item smaller.
2	Tournament / tour identity	Still required after narrowing: Cincinnati, Monterrey and the US Open each exist as an ATP and a WTA event with the same city string. Wrong-tour contamination corrupts a bracket before any downstream logic can be trusted.
3	Result reconciliation	One missed result stalled a quarter of the Cincinnati draw and is still stalled. Live feeds are incomplete by nature; the authoritative sweep is what makes them survivable.
4	Player identity and display	Ambiguous seats make a bracket unfillable even when the identities beneath them are correct. This is the defect a user meets first.
5	Provider verification matrix	Converts the integration brief from documentation into executable evidence. Every assumption gets a probe, an expected result and a failure behaviour.
6	Surface and environment	One function. Removes a silent default that is publishing obviously wrong metadata on every page and breaking three of four calendar filters.
7	Tournament-state repair	Largely falls out of §7. Stale Open states are a symptom of missing reconciliation, not an independent bug.
8	Timezone presentation	Cheap, visible, and easy to regress in the wrong direction. See the constraint in §14.
9	Merchandising	The product consequence of §5. Cannot be built before the eligibility flag exists.

#	PRIORITY	WHY IT SITS HERE
10	SEO and template cleanup	Launch polish. Only after data trust is green.

FREEZE RULE

No new consumer feature work until priorities 1–4 are green in production-like tests. A polished page carrying the wrong participant is worse than a plain page carrying a trustworthy one.

03 · THE CUT LINE

What must be true by the 24th, and what may slip

Today is 20 August. Winston-Salem's draw is pending for the 24th and will publish a day or two before. That is four working days for one engineer. The list in §2 is not four days of work, so the choice of what to drop will be made either here, deliberately, or at 2am on the 23rd, silently. Cincinnati on 13 August was described as the last free rehearsal; it has passed, and the disruption pipeline still has never met a retirement, a walkover or a suspension in real data. Winston-Salem is the last chance before the US Open.

GATE	MUST BE GREEN	CONSEQUENCE OF MISSING IT
BY 24 AUG Winston-Salem rehearsal	§1 Preflight §5 Scope §6 Identity §7 Reconciliation §8 Names	There is no rehearsal. An ATP 250 that imports, opens, locks, reconciles, settles and completes without manual database intervention is the entire point of the exercise, and each of these five is on that path. Missing any one means the US Open is the first real test.
BY 31 AUG US Open draw	§9 Verification §10 Surface §11 State §12 Load §13 Merchandising §16 Integrity gate	The product ships with wrong metadata and a homepage that promotes what it cannot support. Recoverable, embarrassing, and visible to every new user arriving from a Slam.
AFTER Post-launch	§14 Timezone §15 SEO Socket listener	Live scores lag by the sweep interval and times read as UTC. Both are real costs and neither breaks a bracket.

IF ONLY THREE THINGS GET DONE

Scope, reconciliation, names. Scope because it makes everything else smaller. Reconciliation because a stalled quarter is the one defect that destroys a league's reason to open the app. Names because a bracket with two identical seats cannot be filled at all. Tour identity is fourth only because narrowing to 250+ removes most of its exposure — but Cincinnati and the US Open both have same-city ATP and WTA events, so it cannot be dropped entirely; at minimum add the assertion in §6 and let it fail loudly.

NOT NEGOTIABLE AT ANY DEADLINE

Lock time is enforced by a Postgres trigger (migration `0013`). Nothing in this sprint may introduce a second lock authority in TypeScript, and no shortcut may route a server component through the service-role key. Both fail open, silently, and both are worse than shipping late.

04 · CODE MAP

Where this work lands in the monorepo

v1.0 described a single-app `src/lib/…` layout. This is a pnpm workspace with six packages, a Postgres schema that owns most of the enforcement, and a settlement engine that already exists. Building beside those rather than inside them is how a second normalization layer gets created. Paths below are the real ones.

RESPONSIBILITY	MODULE	OWNS
Provider client	`supabase/functions/ingest-events/`	REST calls, retries, rate limiting, raw payload logging. Already the idempotent front door for match events; extend it rather than adding a second caller.
Normalization	`packages/core/src/ingest/`	New. Pure functions: tour, tier, surface, environment, outcome, display name. No I/O, no Supabase client. Imported by the edge function, the reconciliation job and the tests alike, so client and server cannot disagree.
Eligibility policy	`packages/core/src/tournament/eligibility.ts`	New. `PUBLIC_TIERS` and `isBracketProduct()`. Mirrored by a SQL function; the two are asserted equal in pgTAP (§5).
Draw import	`supabase/functions/ingest-events/draw.ts`	Draw seats, seeds, byes, qualifier placeholders. Writes `draws` and `draw_seats` (migrations `0006`–`0008`).
Reconciliation	`packages/settlement/src/reconcile.ts`	New. The authoritative repair sweep. Lives beside settlement because it calls it, and because the monorepo resolves `workspace:*` natively — which is the cheapest answer to the edge-function packaging blocker in §1.
Settlement	`packages/settlement/`	Unchanged. Advance winners, score picks, write `bracket_snapshots`. Do not modify without a failing test that proves the engine itself is wrong.
Tournament state	`packages/core/src/tournament/state.ts`	Derivation only. Lock authority stays in the database.

RESPONSIBILITY	MODULE	OWNS
Scheduling	`supabase/migrations/ · pg_cron`	Per `runbooks/SETTLEMENT-SCHEDULING.md`. Cadence is measured, not inherited — see §7.
Public reads	`apps/web/src/data/`	The only place Supabase is called from the web tier. Anon key plus the user's JWT. Never the service role.
Integrity report	`apps/web/app/(app)/admin/integrity/`	Extends the existing Founder Dashboard pattern and reads `settlement_runs` and `draw_settlement_health`. RLS-gated to an operator role — see §4.1.
Verification CLI	`packages/settlement/src/verify/cli.ts`	New. `pnpm tennis:verify`. §9.
Schema	`supabase/migrations/0029+ · supabase/tests/`	Constraints, enums, policies. Baseline to beat: 631 pgTAP assertions across 22 files.

4.1 Cross-cutting rules that override anything below

These are house rules this repository already enforces. They are restated here because a playbook that omits them invites a well-meaning engineer to break one under time pressure.

RULE	DETAIL
`Service role`	The service-role key exists only in edge functions and the settlement worker. Server components authenticate as the user via `@supabase/ssr`. Using it in a server component silently discards every RLS policy in `0001` and `0004` and **fails open** — nothing breaks and nobody notices until someone reads another user's unlocked bracket. Enforced by lint and a CI grep; the admin integrity page in §4 is the single most likely place for this to be broken this sprint.
`RLS`	Every table a user can read is covered, no exceptions. New tables and new columns on existing tables inherit that obligation. An integrity or audit table is not exempt because it is internal.
`pgTAP`	Every acceptance test in this document names a file under `supabase/tests/`. A test described in prose and not written is a defect that will recur. Never apply anything in `supabase/tests/` to a real project — one file recreates `auth.users`.
`Lock authority`	A Postgres trigger, migration `0013`. If you find yourself adding a lock rule to a component, it belongs in the database or in `packages/core`.
`No silent defaults`	Unknown provider enum values are logged and alerted, never coerced. This rule applies to the migrations in this document as much as to the provider — v1.0 broke it in its own identity migration, which is why §6 is rewritten.
`Idempotency`	Provider payloads must be replayable without double-settling. Out-of-order and duplicate delivery are normal, not exceptional.

RULE	DETAIL
Copy is i18n	Three locales ship: `en`, `es`, `ja`. Every new user-visible string in this sprint — empty states, integrity warnings, the "no draw open" message in §13 — needs all three or it renders as a key.
One definition	UI components never encode tier eligibility, tour mapping or tournament-state rules. If a rule appears in a component, it has already been duplicated.

05 · P0-1 · GREEN BY 24 AUG

Product scope: ATP and WTA 250+

A tournament is publicly bracket-eligible only when it is ATP or WTA and its level is 250 or above. Grand Slams and Tour Finals are in. Challenger, ITF and WTA 125 events may continue to be ingested for coverage; they are not public bracket products unless explicitly flagged on.

The live calendar currently lists roughly 250 events, of which the great majority are M15, M25, W15 and W35. The homepage promises "Fill a bracket" and lands on a list whose first thirty-six rows are on-court events nobody can enter. Narrowing is a product improvement in its own right — but it is first on this list because of what it does to risk: it removes most of the rows the reconciliation job must keep fresh, and it removes the exact draws where the worst defects live.

5.1 Reconcile with the existing enum. Do not create a second one.

Migration `0001` already defines `tournament_tier` as `('grand_slam','tour_finals','masters_1000','tour_500','tour_250','other')`, and it is wired into the rating K-factor per ADR-0003. v1.0 proposed a parallel `TournamentLevel` vocabulary. Two level vocabularies is precisely the duplication §4.1 forbids, and the proposed one silently dropped `tour_finals`.

Extend the enum instead. The three numeric tiers are level names, not tour names — `tour` is a separate column and already disambiguates a WTA 1000 from an ATP Masters 1000. What is missing is the ability to say what an event is when it is *below* 250, because `other` is currently a dumping ground that cannot be filtered on.

```
-- 0029_tournament_levels.sql
-- Postgres will not let a new enum value be used in the same transaction that
-- adds it, and Supabase wraps each migration in one. This migration adds the
-- values and nothing else; 0030 backfills. Do not merge them.

alter type tournament_tier add value if not exists 'challenger';
alter type tournament_tier add value if not exists 'wta_125';
alter type tournament_tier add value if not exists 'itf';

-- comment on the three numeric tiers so the next reader does not repeat
-- v1.0's mistake and assume masters_1000 is ATP-only.
comment on type tournament_tier is
  'Level, not tour. masters_1000 covers ATP Masters 1000 and WTA 1000; '
  'tour_500 and tour_250 cover both tours at those levels. Disambiguate '
  'with tournaments.tour. Levels below 250 are named explicitly so they '
  'can be excluded from the public bracket product rather than hidden '
  'inside ''other''.';
```

```
-- 0030_bracket_eligibility.sql

create type product_override as enum ('force_on','force_off');

alter table tournaments
  add column product_override product_override,          -- null = policy decides
  add column ingestion_enabled boolean not null default true,
  add column featured boolean not null default false;

-- One authoritative definition, in SQL, so the public query can use it.
-- packages/core mirrors it for the TypeScript side and 23_eligibility.test.sql
-- asserts the two agree.
create or replace function is_bracket_product(
  p_tour tour,
  p_tier tournament_tier,
  p_override product_override default null
) returns boolean
language sql immutable as $$
  select case
    when p_override = 'force_on'  then true
    when p_override = 'force_off' then false
    else p_tier in ('grand_slam','tour_finals','masters_1000','tour_500','tour_250')
  end
$$;

-- Stored, so the calendar query is an index scan rather than a function call
-- per row. Generated, so it cannot drift from the policy.
alter table tournaments
  add column bracket_eligible boolean
  generated always as (is_bracket_product(tour, tier, product_override)) stored;

create index tournaments_public_calendar
  on tournaments (starts_on)
  where bracket_eligible;
```

RULE

Call `is_bracket_product()` — or read `bracket_eligible` — at ingestion activation, public calendar queries, bracket creation, tournament landing CTAs and admin QA. **Level rules never appear in a React component.** Keep `ingestion_enabled` and `featured` independent of eligibility: MatchRead can ingest what it does not merchandise, and can support every 250+ event while the homepage leads with ten.

5.2 Backfill, and the question v1.0 did not answer

Roughly 250 tournament rows are already ingested with `tier` almost certainly set to `other`, and some number of brackets may already exist against them. Narrowing the product must not destroy user data.

— **Backfill `tier` from the provider category field**, not from the name string. Where the provider gives no category, leave the row and alert; do not guess from `M15` in the title. Guessing from names is the defect in §8 wearing a different hat.

- **Ineligible does not mean deleted.** An existing bracket on a now-ineligible tournament stays readable, stays in its league, and settles normally. Eligibility governs *discovery and new entry*, nothing else. Assert this: it is the rule most likely to be broken by a well-meaning cascade.
- **Nothing new may be created** on an ineligible tournament. Enforce in the database, not the route — a check constraint or a policy on `brackets`, so a stale client cannot get around it.
- `force_off` **is the incident kill switch.** A tournament whose data has gone wrong mid-event is pulled from the public product with one update, without a deploy and without touching bracket rows. Document it as the on-call action.

5.3 Acceptance — `supabase/tests/23_eligibility.test.sql`

- Seed one ATP 250, one ATP Challenger, one WTA 250, one WTA 125, one ATP 1000, one Grand Slam and one ITF M15. Public bracket discovery returns exactly the four 250+ rows; all seven remain present for internal ingestion.
- `force_on` promotes the Challenger; `force_off` demotes the Grand Slam. Both are reversible and neither touches bracket rows.
- A bracket created before demotion survives it, remains readable by its owner and its league, and still settles.
- Inserting a new bracket against an ineligible tournament is rejected by the database.
- The tier list inside `is_bracket_product()` equals `PUBLIC_TIERS` exported from `packages/core`, fed in as a fixture. This assertion is the thing that stops the two definitions drifting.

06 · P0-2 · GREEN BY 24 AUG

Tournament and tour identity

The ATP M15 Tianjin draw contains several feminine surname forms, and a W15 Tianjin exists in the same week. That is a cross-tour contamination signal. Do not delete the row. Trace the provider tournament ID, season ID, draw ID, tour discriminator and player IDs through the whole ingest path, and make the wrong result impossible rather than absent.

6.1 Hypotheses to falsify, in order of likelihood

- Provider tournament IDs are unique only within a tour namespace, and MatchRead treats them as globally unique.
- A season-to-tournament join uses the provider ID without also checking tour.
- ATP and WTA events with matching city or name strings are being merged by a slug fallback. Cincinnati, Monterrey and the US Open all have this shape, so this hypothesis is testable against events that matter.
- Draw import selects the wrong `season_id`, or reuses a cached response from the previous tournament in the loop.
- Normalization permits an existing tournament row to be updated from a payload belonging to another tour.

> **CORRECTIONS TO V1.0**
>
> v1.0's migration added `provider text not null default 'matchstat'` — a silent default, in a NOT NULL column, naming a provider the integration brief does not mention. That is the same defect class as the universal Hard surface, shipped inside the migration meant to fix it. It also added `tour text`, which shadows the existing `tour` enum from migration `0001`. Both are removed below.

```
-- 0031_provider_identity.sql
-- No default. Backfill explicitly, then constrain. An unbackfillable row is a
-- row nobody understands, and it should stop the migration, not inherit a guess.

create type data_provider as enum ('tennis_api_rapidapi');

alter table tournaments
  add column provider data_provider,
  add column provider_tournament_id text,
  add column provider_season_id text;

-- external_ref already carries the provider key. Split it, do not re-fetch.
update tournaments set
  provider = 'tennis_api_rapidapi',
  provider_tournament_id = split_part(external_ref, '-', 2),
  provider_season_id     = split_part(external_ref, '-', 3)
where external_ref is not null;

do $$
begin
  if exists (select 1 from tournaments where provider_season_id is null) then
    raise exception 'unbackfillable tournament rows: resolve before constraining';
  end if;
end $$;

alter table tournaments
  alter column provider set not null,
  alter column provider_tournament_id set not null,
  alter column provider_season_id set not null;

-- Identity is composite. tour is the existing enum column, not a new one.
create unique index tournaments_provider_identity
  on tournaments (provider, provider_tournament_id, provider_season_id, tour);

-- A draw points at exactly one tournament row, by id. Never by name or city.
alter table draws
  add constraint draws_tournament_fk
  foreign key (tournament_id) references tournaments(id);
```

6.2 Runtime invariant

Placed in `packages/core/src/ingest/` so the edge function, the reconciliation job and the verification CLI all use the same one.

```
export function assertDrawBelongsToTournament(
  draw: NormalizedDraw,
  tournament: TournamentRow,
): void {
  invariant(draw.providerTournamentId === tournament.providerTournamentId,
    `provider tournament mismatch: ${draw.providerTournamentId}`);
  invariant(draw.providerSeasonId === tournament.providerSeasonId,
    `provider season mismatch: ${draw.providerSeasonId}`);
  invariant(normalizeTour(draw.tour) === tournament.tour,
    `tour mismatch: draw ${draw.tour} into ${tournament.tour} tournament`);
}
```

Failure is loud and the payload is not persisted. A rejected import is an alert and a `DRAW_PENDING` tournament; a silently accepted one is a bracket with the wrong people in it, which nobody notices until a user does.

6.3 Acceptance — `supabase/tests/24_provider_identity.test.sql`

- ATP and WTA events with identical city and name strings create two distinct rows. Run it against Cincinnati and the US Open specifically, since both are in this sprint's path.
- A WTA draw payload cannot be persisted into an ATP tournament row; the write fails.
- No `draw_seats` row references a player whose source payload carries a tour conflicting with the tournament, where the provider supplies tour context.
- Re-running the same import twice produces no second tournament row and no seat churn.

07 · P0-3 · GREEN BY 24 AUG

Result reconciliation and exceptional outcomes

A single unrecorded Cincinnati R32 result — Fonseca against O'Connell on 18 August — left the R16 reading "Not played" and a quarter-final with an empty seat, while every other quarter advanced to the last eight. Matches played later the same day settled correctly, so this is not lag. It is one fixture that never came back, and nothing swept up behind it. It is still wrong today.

Live feeds drop events. That is not a provider defect to be complained about, it is a property of the medium. The design answer is an authoritative periodic sweep whose job is to assume the stream lied and prove it — the reconciliation layer the integration brief already names as the backstop behind both pipelines.

7.1 The loop

1. Select tournaments that are `bracket_eligible` and not `COMPLETE`, plus any explicitly monitored.
2. Fetch the provider's authoritative completed and current fixture set for each.
3. Compare provider status and winner against stored fixture state.
4. Upsert changed fixture facts idempotently, keyed on the provider fixture ID.
5. For each newly resolved winner, invoke the existing settlement path. Do not reimplement advancement.
6. Recompute downstream participants only from stable upstream winner IDs, never from a seat's current label.
7. Log every repair: tournament ID, fixture ID, before, after, source timestamp, job run ID.
8. Alert when a provider fixture is terminal but cannot produce exactly one valid bracket winner.

```
export async function reconcileTournament(tournamentId: TournamentId) {
  const run = await audit.startRun('reconcile', tournamentId);
  const tournament = await repo.getTournament(tournamentId);
  const providerFixtures = await provider.getTournamentFixtures(tournament);

  for (const raw of providerFixtures) {
    const normalized = normalizeFixture(raw);           // packages/core/src/ingest
    const current = await repo.getFixtureByProviderId(normalized.providerId);
    if (!needsRepair(current, normalized)) continue;

    const repaired = await repo.upsertFixture(normalized);
    if (canAdvanceWinner(repaired.outcome, repaired.winnerPlayerId)) {
      await settleDraw({ tournamentId, fixtureId: repaired.id, runId: run.id });
    }
    await audit.logRepair({ runId: run.id, before: current, after: repaired });
  }

  await repo.setTournamentState(tournamentId, deriveTournamentState(tournament)); // §11
  await audit.finishRun(run.id);
}
```

7.2 Terminal outcomes are explicit

```
type MatchOutcome =
  | 'COMPLETED' | 'WALKOVER' | 'RETIREMENT'
  | 'DEFAULT'   | 'CANCELLED' | 'SUSPENDED';

const ADVANCING: ReadonlySet<MatchOutcome> =
  new Set(['COMPLETED', 'WALKOVER', 'RETIREMENT', 'DEFAULT']);

export function canAdvanceWinner(outcome: MatchOutcome, winnerId?: string) {
  return ADVANCING.has(outcome) && Boolean(winnerId);
}
```

> **NEVER INFER A WINNER FROM SCORE TEXT**
>
> The provider's winner or player ID is authoritative. Scores are presentation data and are routinely incomplete for walkovers, retirements and defaults — which are exactly the cases where inference is most tempting and most wrong.

7.3 The gap this exposes, which v1.0 normalized but did not solve

`SUSPENDED` and `CANCELLED` normalize cleanly and then have nowhere to go. Per `ENGINEER-MAPPING.md`, postponed, suspended and cancelled have **no first-class representation in the tournament UI at all**. Geneva 2025 is the only tournament ever replayed against this system and it contained no retirements, walkovers, withdrawals or suspensions, so the entire disruption pipeline has never met real data.

Two consequences for this sprint. First, normalizing an outcome the product cannot display is half a fix: budget UI for the three states, even if it is one honest sentence per state. Second, withdrawal and replacement already have

semantics — migration `0028` defines voided picks, which are neither correct nor incorrect and get neither green nor red. **Use them.** Do not invent a second representation of the same idea.

7.4 Cadence, measured rather than inherited

v1.0 proposed "every 2–5 minutes if quota permits." That is the same number `runbooks/SETTLEMENT-SCHEDULING.md` describes, in its own words, as a guess informed by nothing — and ADR-0018 asks for it to be set from provider quota instead. The Geneva capture has the data to do that.

CLASS	STARTING CADENCE	SET IT BY
Eligible tournament in play	**2–5 min**	Measure calls per sweep against the RapidAPI plan's quota, then set the interval so a full match day stays inside it with headroom for a retry storm. Record the arithmetic in the runbook.
Draw published, not started	**10–15 min**	Withdrawals and replacements, which move seats before anyone is watching.
Recently complete	**once, then daily ×2**	One post-event repair sweep, then a daily check for 48 hours.
Ineligible but ingested	**daily**	Coverage, not product. Must never compete for quota with a live 250+ event.

Retries must be safe. `cron.job_run_details` records that cron *fired*; it says nothing about whether the work succeeded. `settlement_runs` and the repair audit are what answer that, and they are what the integrity page in §16 reads.

7.5 Acceptance — `supabase/tests/25_reconciliation.test.sql` and `packages/settlement/src/reconcile.test.ts`

- Replay the Cincinnati draw with the Fonseca–O'Connell result withheld, then supply it. The R16 and QF seats resolve without manual intervention and without double-settling anything downstream.
- The same payload delivered twice produces one settlement. Out-of-order delivery produces the same final state as in-order.
- A terminal fixture with no winner raises an alert and advances nothing.
- A walkover with no score text advances the winner.
- A retirement mid-match advances the winner and preserves the partial score for display.

08 · P0-4 · GREEN BY 24 AUG

Player identity and display names

Cincinnati renders Aliassime, Minaur, Zandschulp, Assche and Jong — particles stripped from Auger-Aliassime, de Minaur, van de Zandschulp, van Assche and de Jong. Tianjin renders Mingzhou and Hongyu, which are given names, so for Chinese players the parser is taking the wrong end of the string entirely. And Tianjin's R64 puts Gao next to Gao, Han next to Han, and three players labelled Chen in the same draw.

This is the defect a user meets first, and it is the one that makes the product look scraped. It is also worse than cosmetic: **a bracket with two identical seats cannot be filled.** There is no pick to make when both options read the same.

8.1 Separate identity from display

```
type Player = {
  id: PlayerId;                  // MatchRead internal UUID
  provider: DataProvider;
  providerPlayerId: string;      // the identity key. the only join key.
  displayName: string;           // provider canonical, user-facing
  firstName?: string | null;     // auxiliary. never a join key.
  lastName?: string | null;      // auxiliary. never a join key.
  countryCode?: string | null;
};
```

- **Never create or join a player by name.** Section 07 of the integration brief says this in as many words; the display layer has the same problem the matching logic was warned about.
- **Never derive a display name by taking the last token.** Preserve particles, hyphens, accents, multiword surnames and cultural name order.
- If the provider gives no clean display name, use an explicit formatter with country and language awareness — and treat it as a fallback that is logged, not a normal path.
- Existing `players.last_name` stays as an auxiliary column. It is not deleted and it is not trusted.

8.2 Backfill

1. Add `display_name` and `provider_player_id` if absent.
2. Backfill from the provider canonical name for every player referenced by an active `bracket_eligible` draw. That set is small once §5 lands — this is the second time narrowing scope pays for itself.
3. Flag unresolved or suspicious names rather than guessing. A flagged seat blocks publication (§16); it does not get a plausible label.
4. Rebuild any search index that depends on name parts — `players_name_trgm` in migration `0001` indexes `full_name` and must follow the new canonical value.

8.3 Duplicate-label detection

```
-- Run per draw, not globally. Duplicate labels across the season are fine;
-- duplicate labels inside one bracket are the defect.
select d.tournament_id, p.display_name, count(*) as seats
from draw_seats s
join draws   d on d.id = s.draw_id
join players p on p.id = s.player_id
group by d.tournament_id, p.display_name
having count(*) > 1;
```

> **THE QA RULE**
>
> Duplicate display names are legitimate — two Cerundolos really are in the Cincinnati draw. The rule is not "duplicates forbidden," it is **"duplicates must remain distinguishable"** through seed, country, full canonical name or another stable visible discriminator. In a seeded draw, seed and country usually do it. In an unseeded ITF draw with two Chinese players named Gao and the same flag, they do not — which is one more reason those draws are not a public bracket product.

8.4 Land the fix once

Per `ENGINEER-MAPPING.md`, the seed / name / country triple is hand-rolled in four places: the bracket editor, the rankings table, the operator seat list and the draw list. Extracting `PlayerChip` is already recorded in KNOWN_WEAKNESSES and the spec prototype implements it once. **Do that extraction as part of this fix**, so the disambiguation rule exists in one component rather than being reimplemented four times and drifting three ways.

8.5 Acceptance — `supabase/tests/26_player_display.test.sql` and `packages/core/src/ingest/name.test.ts`

- Fixtures covering, at minimum: a particle surname (de Minaur), a compound particle (van de Zandschulp), a hyphenated surname (Auger-Aliassime), a family-name-first order (Chinese and Japanese entrants), an accented surname, and a two-word surname without a particle (Carreño Busta). Each round-trips to the provider canonical form.
- No player in an eligible draw has a `display_name` produced by the fallback formatter without a corresponding log line.
- The duplicate-label query returns no row for any eligible draw where the duplicates lack a visible discriminator.
- Renaming a player upstream does not create a second player row.

09 · P1-5 · GREEN BY 31 AUG

Provider verification matrix

Section 08 of the integration brief is a pre-production verification checklist. On the evidence of the live site it has not been run against live data — three of its questions (surface normalization, UTC handling, tour isolation) would have failed. Make it executable and make it a gate.

CHECK	PROBE	PASS CONDITION AND FAILURE BEHAVIOUR
Tournament identity	Fetch draw plus tournament metadata	Provider IDs, tour and season map to exactly one MatchRead row. BLOCK
Tour isolation	Probe same-city ATP and WTA events	No cross-tour join is possible. Run against Cincinnati and the US Open. BLOCK
Draw structure	Count positions, byes, placeholders	Seat count matches declared draw size; no fixture reconstruction inferred from results. BLOCK
Draw order	Compare top-to-bottom order with the official draw sheet	Order is exact. The brief calls this the largest unresolved risk in the whole integration; it is answered by eye, once, per tournament shape. BLOCK
Player identity	Compare player IDs across draw, core and live payloads	Stable mapping, or an explicit persisted crosswalk. BLOCK
Player display	Render every seat label	No fallback-formatted name, no indistinguishable pair. BLOCK SEAT
Results	Fetch completed fixtures	Every terminal match carries an explicit winner and outcome. ALERT
Live mapping	Compare fixture ID against socket event ID	Known equality, or a persisted mapping. ALERT
Surface	Inspect several hard, clay and grass events	Provider values normalize; no silent Hard default. WARN
Times	Inspect raw timestamps and offsets	Storage semantics documented; rendered time verified against a published order of play. WARN

CHECK	PROBE	PASS CONDITION AND FAILURE BEHAVIOUR
Replacement	Withdrawal, lucky loser, qualifier resolution	Seat updates preserve identity and bracket history; voids behave per **0028**. BLOCK

Test against one completed Grand Slam, one active event and one whose draw has just published. For this sprint that is Wimbledon or Roland-Garros, Cincinnati, and Winston-Salem.

```
$ pnpm tennis:verify --tournament <providerSeasonId>

[PASS] tournament identity          atp / 21348 / winston-salem
[PASS] tour isolation               ATP; 0 cross-tour seats
[PASS] draw structure               48 seats, 16 byes, size 48
[PASS] draw order                   matches official sheet
[PASS] player identity              44 provider IDs, 0 unresolved
[PASS] player display               0 fallback-formatted, 0 ambiguous pairs
[PASS] surface                      hard / outdoor
[PASS] times                        UTC stored, America/New_York rendered
[WARN] live mapping                 socket listener absent; REST sweep only
[WARN] 1 replacement observed       seat history preserved

RESULT: SAFE_TO_PUBLISH=true
```

10 · P1-6 · GREEN BY 31 AUG

Surface and environment

Every one of the roughly 250 tournaments on the live calendar is labelled Hard, including events at Todi, Lesa, Santa Margherita di Pula and Campos do Jordão. The calendar offers four surface filters and three of them return nothing. Every page in the product shares one Open Graph image, `court-hard.webp`.

`surface` is `not null` in migration `0001`, and the provider exposes the value as `court` on the calendar endpoint. Something is filling the column rather than mapping it. Remove the fallback.

```
export function normalizeSurface(raw: string | null): Surface | null {
  const v = raw?.trim().toLowerCase();
  if (!v) return null;                          // unknown is a value, not an error
  if (v.includes('clay'))   return 'clay';
  if (v.includes('grass'))  return 'grass';
  if (v.includes('carpet')) return 'carpet';
  if (v.includes('hard'))   return 'hard';
  throw new UnknownProviderValue('surface', raw);  // logged, alerted, never coerced
}

export function normalizeEnvironment(raw: string | null): Environment | null {
  // Separate axis. "Indoor Hard" is two facts, not one.
}
```

THREE CONSEQUENCES THE SCHEMA FORCES

Indoor is not a surface. The enum is `hard | clay | grass | carpet`; the calendar's fourth filter chip says Indoor, which is an environment. Either the filter is rebuilt on two axes or the chip is removed — it cannot stay as it is. **Unknown must be representable.** That means dropping the `not null` on `surface` so an unmapped value is visible to admin QA rather than silently rewritten to Hard. **Only expose filters the data supports.** A filter that returns nothing teaches a user the product is empty.

The court hairline is the one place these values become visible. Four colours, three pixels, on a tournament row and nowhere else — enough to make the shape of a tennis year legible without a word of explanation. Getting the mapping right is what earns that.

Clay	#C2633C
Grass	#5F8F3A
Hard	#2F6FA8
Indoor / carpet	#293D5E

These communicate tournament context and nothing else. They never carry state, emphasis or identity, and `tokens.test.ts` asserts none has leaked into a semantic role. This is the only page of this document on which they appear.

---

11 · P1-7 · GREEN BY 31 AUG

Tournament-state reconciliation

W75 Kursumlijska Banja, starting 10 August, is still listed as open for entry today, ten days later — while the 17 August edition of the same event shows On court. Events whose results never ingested never transitioned. This is a symptom of §7 rather than an independent bug, and it mostly disappears when reconciliation runs.

```
type TournamentState =
  | 'DRAW_PENDING' | 'OPEN' | 'LOCKED' | 'ON_COURT' | 'COMPLETE';

export function deriveTournamentState(ctx: StateContext): TournamentState {
  if (ctx.allMatchesTerminal) return 'COMPLETE';
  if (ctx.anyMatchStarted)    return 'ON_COURT';
  if (ctx.now >= ctx.locksAt) return 'LOCKED';
  if (ctx.drawPublished)      return 'OPEN';
  return 'DRAW_PENDING';
}
```

> **THIS FUNCTION IS PRESENTATIONAL**
>
> It decides what badge to draw. **It is not a lock.** Lock is enforced by a Postgres trigger in migration `0013`, and bracket submission must be refused by that authoritative clock even when a stale badge still says Open. Two clocks is worse than one wrong badge: a badge is a cosmetic defect, a second clock is a bracket edited after the first ball.

- Persist the derived state if it helps queries, but treat it as repairable cache, never as truth.
- Recompute after every provider update and on the reconciliation schedule.
- A tournament that has been `OPEN` past its own start date for more than one sweep is an alert, not a display quirk. That single assertion would have caught this defect ten days ago.

---

12 · P1-8 · GREEN BY 31 AUG

Peak load and incident response

Absent from v1.0 and specific to this launch. The US Open traffic profile is not a ramp, it is a cliff: the last three hours before lock, when everyone who procrastinated fills 127 slots each, simultaneously.

- **Load-test that shape**, not an average day. The relevant metric is concurrent whole-bracket submissions in the final hour, not requests per second across a week.
- **Entry is already incremental and resumable**, which is what stops a dropped connection at 10:47 costing twenty minutes of work. Do not regress it while touching the seat components in §8.
- **The bracket editor renders every round in full.** Fine at 32 seats; a 128 draw is a very tall column. Mobile solved this with a quarter-and-half `DrawNavigator` — that component is the model to port, and the US Open is the first 128 draw the web tier will ever serve.
- **Incident response is** `product_override = 'force_off'` (§5). One update pulls a tournament whose data has gone wrong out of the public product, with no deploy and no data loss. Write it into the on-call notes with the exact statement to run.
- **Every repair is logged** with a run ID, so the question "why is this bracket wrong?" is answered from the audit trail rather than by reading random rows at 3am.

13 · P1-9 · GREEN BY 31 AUG

Public merchandising

Coverage, eligibility and emphasis are three different concerns. MatchRead can support every ATP and WTA 250+ bracket without giving all of them the same visual weight, and it can ingest below that line without showing any of it.

LAYER	GOVERNED BY	PURPOSE
`Ingested`	`ingestion_enabled`	Internal data coverage. May include Challenger and ITF for future use and for rankings.
`Bracket eligible`	`bracket_eligible`	The public product contract. ATP and WTA 250+ only.
`Featured`	`featured`	Homepage and primary CTA. The next six to ten marquee events.
`Open now`	`derived`	Eligible, draw published, before lock. The action-oriented browse.
`Live / locked`	`derived`	Follow results, standings, the Daily Check. Still discoverable; never the primary "Fill a bracket" destination.

```
select t.*
from tournaments t
where t.bracket_eligible
  and t.starts_on >= (select starts_on from seasons where is_current)
order by t.featured desc, t.starts_on asc;
```

13.1 The funnel defect this fixes

The homepage's primary call to action is "Fill a bracket." It lands on a calendar whose first thirty-six rows are On-court events that cannot be entered; the sixteen that can be are below them. Separately, "See what it looks like" points at Cincinnati — a locked tournament, which is the one state where the product's core action is unavailable. Two changes:

- **Open-now first.** The primary CTA lands on eligible, open, unlocked tournaments. Locked and live events stay reachable, lower.
- **Point the demo at something enterable.** If nothing eligible is open, say so plainly and name the next event that opens — never fall back to promoting an unsupported lower-tier bracket.

> COPY, IN THE PRODUCT'S OWN VOICE
>
> The Phase 4 writing rule is that a string names what is true *and then what happens next*. "No tournaments open" fails it. **"Nothing is open right now. The Winston-Salem draw comes out on Saturday — your league can be ready before it does."** passes. Three locales, per §4.1.

14 · P2-10 · AFTER LAUNCH

Timezone presentation

Cincinnati fixtures display at 01:45, 02:10 and 05:35 in the morning. They read correctly as UTC and nonsensically as anything else. Store UTC; convert only at the presentation boundary; decide once whether MatchRead shows viewer-local time, tournament-local time, or both.

> **CONSTRAINT V1.0 OMITTED, AND THE REASON THIS IS NOT A FIVE-MINUTE FIX**
>
> Format on the **server**, against an explicit zone. The `BetweenTournaments` work already does this deliberately: rendering a time on the client flashes on first paint and produces a hydration mismatch that React resolves by trusting the server — *so the correction sometimes never happens*. A client-side `Intl.DateTimeFormat` reintroduces a bug this codebase has already solved.

- Persist `starts_at` as `timestamptz`.
- Persist the tournament's IANA zone — `America/New_York` for Winston-Salem and the US Open — as a column, not a lookup.
- Prefer `preferences.time_zone` where the viewer has one; otherwise tournament-local, which is always safer than raw UTC.
- Label it when ambiguity matters. The lock deadline in particular already has a `LocalDeadline` primitive; every other displayed time should match its behaviour.

15 · P2-11 · AFTER LAUNCH

Canonical hosts and template hygiene

- **One canonical hostname, 301 the other.** Today `www` serves 200s with a canonical tag pointing at the apex. Pick one and redirect.
- **Remove the leaked template marker.** `{MatchRead` appears in rendered markup on every page fetched. Add a smoke test that fetches representative pages and asserts no unresolved marker is present — an assertion, not a one-time deletion.
- **Surface-aware or neutral Open Graph images.** One hard-court photograph on every page of a product about the whole season is a small dishonesty, and it becomes a visible one the moment §10 lands and Roland-Garros is orange everywhere except when shared.
- **Templated descriptions carry no information.** "Official draw, dates, and entry" is true of every page. Once eligibility narrows the set to ten, per-tournament descriptions are affordable.

16 · DRAW INTEGRITY GATE

A bracket becomes playable by passing, not by existing

This is the mechanism that makes everything above durable. Rows existing is not the condition for publication. Passing is.

GATE	FAILS WHEN	ACTION
Tour identity	Draw and tournament tour disagree	BLOCK PUBLICATION
Tournament identity	Provider season or tournament IDs are ambiguous	BLOCK PUBLICATION
Player identity	A real participant has no provider player ID	BLOCK SEAT
Player display	A seat label is ambiguous or fallback-formatted	BLOCK UNTIL DISAMBIGUATED
Draw structure	Seat count, byes or positions are inconsistent	BLOCK PUBLICATION
Results	A terminal match has no valid winner where one is required	ALERT AND RECONCILE
Propagation	A downstream participant conflicts with an upstream winner	BLOCK SETTLEMENT
State	Open after lock, or after play began	REPAIR AND ALERT
Surface	An unknown value was silently defaulted	WARN; BLOCK METADATA PUBLISH
Freshness	Reconciliation is stale for an active tournament	WARN, THEN BLOCK AT THRESHOLD
Eligibility	A tournament is publicly listed without `bracket_eligible`	BLOCK LISTING

```
type IntegrityReport = {
  safeToPublish: boolean;
  blockingErrors: IntegrityIssue[];
  warnings: IntegrityIssue[];
  checkedAt: Instant;
  sourceSnapshotId: string;
};
```

Surface it on the admin page described in §4, beside `settlement_runs` and `draw_settlement_health`. Follow the Founder Dashboard pattern: one sentence at the top, then the evidence, with every threshold asserted in one file so the page holds no opinions of its own. And read it through the user's JWT with an operator role — **not** the service-role key, which is the shortcut this particular page exists to tempt you into.

17 · REHEARSAL

The Winston-Salem readiness gate

Success is not "the page loads." Success is **an ATP 250 that imports, opens, locks, reconciles, settles and completes without a single manual database intervention.** Every hand-run SQL statement during the rehearsal is a defect that will recur at the US Open with a hundred times the audience.

STAGE	PROOF REQUIRED BEFORE ADVANCING
`Before draw publish`	Normalized as ATP, tier `tour_250`, `bracket_eligible` true. Provider and season IDs composite-unique. Surface and IANA zone mapped from provider values, not defaults. Verification CLI returns `SAFE_TO_PUBLISH=true`.
`At draw publish`	Draw imports in exact bracket order. Byes, qualifier placeholders and seeds correct. Every seat label distinguishable. Integrity gate green. If the gate blocks, the tournament stays `DRAW_PENDING` and someone is paged — it does not publish anyway.
`Open period`	A real user, signed in through the real magic-link flow, submits a complete bracket from a phone. No ambiguous seats. Lock time verified against the published order of play, in the right zone.
`Lock`	Submission stops on the authoritative clock, proven by attempting a write one second after lock and being refused by the database — not by observing a greyed-out button.
`During play`	Fixture updates land. Reconciliation runs on schedule and its runs are visible. At least one walkover, retirement or suspension is exercised — if Winston-Salem does not supply one, inject it from a fixture, because the disruption pipeline has still never met real data.
`Round transitions`	Every resolved winner advances exactly once. No quarter stalls from a missed event. Deliberately drop one result from the feed and confirm the sweep repairs it unaided.
`Completion`	Champion and standings settle. State becomes `COMPLETE`. Final repair sweep passes. `previous_score` is non-null and the Daily Check has something to say.

17.1 Minimum fixture set

Each of these gets a test, whether or not Winston-Salem produces it naturally.

Normal completed match	Walkover before first ball
Retirement after a partial score	Suspended and resumed match
Withdrawal and replacement before R1	Qualifier placeholder becoming a real player
Lucky loser entering after the draw	Bye advancement
Two visually similar surnames in one draw	Particle, hyphen and non-Western name order

Provider update delivered twice	Provider updates delivered out of order

18 · EXECUTION

Sequence, with dates

	DELIVERABLE	GREEN CONDITION	BY
0	Preflight	Four blockers answered with evidence. Settlement armed if it is not.	20 AUG
A	Scope	Public bracket discovery returns only ATP/WTA 250+. Existing brackets on demoted tournaments survive and still settle.	21 AUG
B	Identity	No cross-tour payload can persist. Cincinnati ATP and WTA are two rows.	22 AUG
C	Reconciliation	A withheld Cincinnati result self-heals within one sweep, without double-settling.	22 AUG
D	Names	Every seat in an eligible draw is distinguishable. No token truncation in the fixture set. `PlayerChip` exists once.	23 AUG
E	Rehearsal	Winston-Salem runs the §17 gate end to end.	24-30 AUG
F	Verification	CLI returns `SAFE_TO_PUBLISH=true` for three tournament shapes.	27 AUG
G	Metadata & state	No Hard default. Filters match real data. No tournament can sit Open past its start.	28 AUG
H	Merchandising & load	CTA lands on open 250+ events. The 128-draw editor survives a simulated lock-hour cliff.	30 AUG
I	Time & template	Server-rendered local times. One canonical host. Smoke tests green.	AFTER

Blocks B and C are shown in parallel on the 22nd because they touch different layers and because the schedule has no slack. If that proves optimistic, C outranks B — a stalled bracket is visible to every member of a league; a cross-tour seat, once §5 has removed the ITF draws, is latent.

19 · HANDOFF

Definition of done, and the posture that gets you there

- No manual SQL correction is required to complete a normal 250-level tournament lifecycle.
- Every ingestion assumption that matters to bracket correctness has an automated assertion or a verification probe.
- Provider payloads can be replayed without double-settling or corrupting downstream state.
- Public bracket discovery is intentionally limited to ATP and WTA 250+ products, and the limit is enforced in one place.
- An engineer can answer "why is this bracket wrong?" from logs and audit data, without inspecting random database rows.
- Winston-Salem has been run end to end as a rehearsal, and every intervention it required has become a test.

19.1 Posture

Prefer invariants, idempotent repair and explicit failure over silent fallback. The live site has already demonstrated the failure mode this sprint exists to end: ingestion that is *mostly* correct looks convincing, ships, and breaks the experience anyway.

DO NOT	BECAUSE
Rewrite the bracket engine	Unless a failing test proves the engine itself is wrong. Every piece of evidence here points at source normalization and missing reconciliation.
Fix a production example by hand and close the defect	Convert every production failure into a regression test or an integrity rule. The Cincinnati quarter-final can be repaired with one UPDATE; doing that and stopping is how it happens again at the US Open.
Match tournaments or players by name	Provider IDs exist. Name matching is the root of both the tour-contamination signal and the duplicate-seat defect.
Let a component encode a rule	Tier eligibility, tour mapping and state rules live in one place each. A rule in a component has already been duplicated.
Swallow an unknown provider value	Log and alert. An unknown surface is information; a defaulted one is a lie the product tells on 250 pages.
Reach for the service-role key	It fails open, so nothing breaks and nobody notices. Of everything in this document, this is the mistake with the longest gap between committing it and discovering it.
Add a second lock	The trigger in `0013` is the clock. Anything else is a UI hint.
Ship a new string in one language	Three locales, or it renders as a key.

NEXT CHECKPOINT

Winston-Salem dry run → integrity gate green → invited beta → US Open draw rehearsal.

20 · APPENDIX

What changed from v1.0, and why

Recorded because the engineer may already have read v1.0, and because two of these are corrections rather than preferences.

CHANGE	KIND	REASON
Preflight added (§1)	CORRECTION	v1.0's reconciliation loop calls a settlement engine that, per `FINAL-ENGINEERING-READINESS.md`, nothing invokes: every `pg_cron` call in the repository is a comment, and the two edge functions import unpublished workspace packages. Building §7 on that is building on air.
Scope moved 7th → 1st (§5)	JUDGEMENT	One predicate reduces the public surface from ~250 tournaments to ~10, removes the draws where the worst defects live, and cuts the reconciliation job's working set by an order of magnitude. Cheapest risk reduction on the list; it should not have been seventh.
`TournamentLevel` enum dropped (§5.1)	CORRECTION	Collided with the existing `tournament_tier` from migration `0001`, which is wired into the rating K-factor, and silently dropped `tour_finals`. Extending the existing enum keeps one vocabulary. The transaction-boundary note on `alter type … add value` is added because Supabase wraps migrations and this will otherwise fail on first run.
`default 'matchstat'` removed (§6)	CORRECTION	A silent default in a NOT NULL column, naming a provider the integration brief does not mention — the same defect class as the universal Hard surface, inside the migration meant to fix it. Also removed `tour text`, which shadowed the existing enum column.
Cross-cutting rules added (§4.1)	CORRECTION	v1.0 was silent on RLS, the service-role rule, pgTAP, lock authority and i18n. Each is already enforced in this repository, and the admin integrity page v1.0 proposes is the most likely place for the service-role rule to be broken.
Code map rewritten (§4)	CORRECTION	v1.0 described a single-app `src/lib/…` layout. Following it literally creates a second normalization layer beside `packages/core`.
Dated cut line added (§3)	JUDGEMENT	v1.0 listed eight blocks with no estimates and no triage, four days before the rehearsal. Without a stated cut line the choice still gets made — just later, alone, and undocumented.

CHANGE	KIND	REASON
`Client-side Intl replaced (§14)`	CORRECTION	Formatting time on the client produces a hydration mismatch React resolves by trusting the server, so the correction sometimes never lands. This codebase already solved it server-side in `BetweenTournaments`.
`Disruption UI gap named (§7.3)`	ADDITION	v1.0 normalizes `SUSPENDED` and `CANCELLED`. The product has nowhere to display them, and migration `0028` already defines void semantics that should be reused rather than reinvented.
`Cadence de-guessed (§7.4)`	ADDITION	The 2–5 minute figure is the number the runbook itself calls a guess informed by nothing. The Geneva capture has the data to set it.
`Load and rollback added (§12)`	ADDITION	The lock-hour cliff and the 128-draw editor are both first-time-at-the-US-Open risks. `force_off` is the kill switch and needed naming as such.
`Demotion semantics defined (§5.2)`	ADDITION	v1.0 did not say what happens to a bracket already filled on a tournament that stops being eligible. The answer is: nothing. It is the rule most likely to be broken by a well-meaning cascade.
`Duplicate query corrected (§8.3)`	CORRECTION	v1.0 queried `draw_entries`. The table is `draw_seats` (`0006–0008`), and the grouping must be per draw rather than global.
`US Open date conflict flagged (§1)`	CORRECTION	The live calendar says 31 August; the prototype fixture assumes a 30 August start with an 11:00 ET lock. The lock instant is the one moment where being wrong is unrecoverable.

> STANDING INSTRUCTION
>
> If a section of this document is wrong, the document is wrong. Amend it and say what changed. A playbook the engineer quietly stops following on day two is worse than no playbook, because everyone else still believes it is being followed.