

# Effective types: examples (extracts from P1796R0, plus more)

Peter Sewell, Kayvan Memarian, Victor B. F. Gomes,  
Jens Gustedt, Hubert Tong

18 July 2019

with thanks to other C memory object model people

WG21, Cologne, 2019-07-18

## Provenance and subobjects

Yesterday: only considered provenance at per-allocation granularity.

## Provenance and subobjects: container-of casts

Can one cast from a pointer to the first member of a struct to the struct as a whole, and then use that to access other members.

Yes?

## Provenance and subobjects: multidimensional arrays

ISO C: multidimensional arrays are recursively structured arrays-of-arrays.

For access via explicit indexing: yes.

For access via pointer arithmetic: should (e.g.) a linear traversal of a multidimensional array be allowed?

## Provenance and subobjects: representation-byte arithmetic and access

N2222 2.5.4 Q34 Can one move among the members of a struct using representation-pointer arithmetic and casts?

Yes

Can one move among the members of a struct with other pointer arithmetic?

```
// provenance_intra_object_1.c
1 #include <stdio.h>
2 #include <string.h>
3 typedef struct { int x; int y; } st;
4 int main() {
5     st s = { .x=1, .y=2 };
6     int *p = &s.x + 1;
7     int *q = &s.y;
8     printf("Addresses: p=%p q=%p\n", (void*)p, (void*)q);
9     if (memcmp(&p, &q, sizeof(p)) == 0) {
10         *p = 11; // is this free of undefined behaviour?
11         printf("s.x=%d s.y=%d *p=%d *q=%d\n", s.x, s.y, *p, *q);
12     }
13 }
```

No

## Plan?

Have a per-subobject provenance restriction by default, but relax this (to per-allocation provenance) for pointers that have been formed by an explicit cast.

Perhaps only for casts to **void \***, **unsigned char \***, `intptr_t`, or `uintptr_t`, or perhaps (for simplicity) for all casts.

## Effective types

Q73. Can one do type punning between arbitrary types? No

Q91. Can a pointer to a structure alias with a pointer to one of its members? Yes

Q76. After writing a structure to a malloc'd region, can its members can be accessed via pointers of the individual member types? Yes

Q93. After writing all members of structure in a malloc'd region, can the structure be accessed as a whole? Yes



Q92. Can one do whole-struct type punning between distinct but isomorphic structure types in an allocated region?

A: Basic. This example writes a value of one struct type into a malloc'ed region then reads it via a pointer to a distinct but isomorphic struct type.

```
// effective_type_2b.c
1  #include <stdio.h>
2  #include <stdlib.h>
3  typedef struct { int  i1; } st1;
4  typedef struct { int  i2; } st2;
5  int main() {
6      void *p = malloc(sizeof(st1));
7      st1 *p1 = (st1 *)p;
8      *p1 = (st1){.i1 = 1};
9      st2 *p2 = (st2 *)p;
10     st2 s2 = *p2;      // undefined behaviour?
11     printf("s2.i2=%i\n",s2.i2);
12 }
```

no

**Q92. Can one do whole-struct type punning between distinct but isomorphic structure types in an allocated region?**

B: read via lvalue merely at type **int**, but constructed via a pointer of type **st2 \***

```
// effective_type_2d.c
1  #include <stdio.h>
2  #include <stdlib.h>
3  typedef struct { int  i1; } st1;
4  typedef struct { int  i2; } st2;
5  int main() {
6      void *p = malloc(sizeof(st1));
7      st1 *p1 = (st1 *)p;
8      *p1 = (st1){.i1 = 1};
9      st2 *p2 = (st2 *)p;
10     int *pi = &(p2->i2); // defined behaviour?
11     int i = *pi;          // defined behaviour?
12     printf("i=%i\n",i);
13 }
```

no?

Q92. Can one do whole-struct type punning between distinct but isomorphic structure types in an allocated region?

C: read via an lvalue merely at type `int`, constructed by `offsetof` pointer arithmetic.

```
// effective_type_2e.c
1 #include <stdio.h>
2 #include <stdlib.h>
3 typedef struct { int i1; } st1;
4 typedef struct { int i2; } st2;
5 int main() {
6     void *p = malloc(sizeof(st1));
7     st1 *p1 = (st1 *)p;
8     *p1 = (st1){.i1 = 1};
9     st2 *p2 = (st2 *)p;
10    int *pi = (int *)((char *)p + offsetof(st2,i1));
11    int i = *pi;           // defined behaviour?
12    printf("i=%i\n",i);
13 }
```

yes

## Q92. Can one do whole-struct type punning between distinct but isomorphic structure types in an allocated region?

D: Here `f` is given aliased pointers to two distinct but isomorphic struct types, and uses them both to access an `int` member of a struct. We presume this is intended to be forbidden.

But the lvalue expressions, `s1p->i1` and `s2p->i2`, have identical type. this case. To forbid it, we have to take the construction of the lvalues into account, to see the types of `s1p` and `s2p`, not just the types of `s1p->i1` and `s2p->i2`.

```
// effective_type_2.c
1  #include <stdio.h>
2  typedef struct { int i1; } st1;
3  typedef struct { int i2; } st2;
4  void f(st1* s1p, st2* s2p) {
5      s1p->i1 = 2;
6      s2p->i2 = 3;
7      printf("f: s1p->i1 = %i\n", s1p->i1);
8  }
9  int main() {
10     st1 s = {.i1 = 1};
11     st1 * s1p = &s;
12     st2 * s2p;
13     s2p = (st2*)s1p;
14     f(s1p, s2p); // defined behaviour?
```

## Effective types and representation-byte writes

ISO C says: copying an object “*as an array of character type*” carries the effective type. But should representation byte writes with other integers affect the effective type?

A: take the result of a `memcpy`'d `int` and then overwrite all of its bytes with zeros before trying to read it as an `int`.  
allowed

B: similar, but tries to read the resulting memory as a `float` (presuming the implementation-defined fact that these have the same size and alignment, and that pointers to them can be meaningfully interconverted).  
?

**Q75. Can an unsigned character array with static or automatic storage duration be used (in the same way as a 'malloc'd region) to hold values of other types?**

**ISO C: no. Real-world: yes ?**

## Hubert's examples

These show that current compiler behaviour is not consistent with the ISO C notion of effective types that allows type-changing updates within allocated regions simply by memory writes.

```
typedef struct A { int x, y; } A;
typedef struct B { int x, y; } B;

__attribute__((__noinline__, __weak__))
void f(long unk, void *pa, void *pa2, void *pb, long *x) {
    for (long i = 0; i < unk; ++i) {
        int oldy = ((A *)pa)->y;
        ((B *)pb)->y = 42;
        ((A *)pa2)->y = oldy ^ x[i];
    }
}

int main(void) {
    void *p = malloc(sizeof(A));
    ((A *)p)->y = 13;
    f(1, p, p, p, (long []){ 0 });
    printf("pa->y(%d)\n", ((A *)p)->y);
}
```

## P0593R4 Implicit creation of objects for low-level object manipulation

*The abstract machine creates objects of implicit lifetime types within those regions of storage as needed to give the program defined behavior.*

(a) whole-program definedness is neither co- nor contra-variant: finding more executions may also find data races or unsequenced races

(b) style!

Accumulate constraints?