

## history log for data analysis

### 1. converting DICOMS to BIDS data-structure

- get the scanner-generated and time-ordered DICOM-files relating to a measured subject (“time-folder”) from the server (USB-stick)
- create data folder (“raw\_data\_tnac”) and within folder subdirectory (sub...)
- use the heudiconf docker-image and follow the instructions on <http://nipy.org/heudiconv/> to transfer data into BIDS-structure (define a “unique heudiconf.py-file”; watch out, that subject folders are just named 01, 02,...; adjust paths to py-file, DICOM-images and output folder)
- use the online BIDS-validator to check, if your data is correctly formatted into BIDS-structure (<http://incf.github.io/bids-validator/>); use mozilla and not opera as browser

### 2. defacing

- change read-write-execute rights of your BIDS-data (chmod...)
- use the pydeface.py module to deface your T1 and T2 images (set up a python2 environment in bash; “source activate...deactivate”)
- control via freeview or fsl
- rename the defaced images so that they still fit into BIDS and remove the non-defaced images

### 3. quality control

- use the mriqc docker-image and follow the instructions on <http://mriqc.readthedocs.io/en/stable/docker.html> to perform quality control on your BIDS
- visually inspect your images (html-output in reports), more explanations on <https://mriqc.readthedocs.io/en/latest/reports/smri.html> and <https://mriqc.readthedocs.io/en/latest/reports/bold.html>

### 4. anatomical “preprocessing” via FreeSurfer, ANTS, mindboggle

- use the mindboggle docker-image and follow the instructions on <http://mindboggle.readthedocs.io/en/latest/> to process your anatomical data
- inspect output via fsl or freeview

### 5. “functional” preprocessing

- write preprocessing workflow in own jupyter notebook, not within docker images!
- (use as much SPM-interface-based nodes as possible for later DCM!!!)
- (segment to dissect grey matter from white matter, brainstem, cerebrospinal fluid (use templates from the freesurfer “anatomical processing”))
- unzip the functional images and use the selectfiles-node for input-control

- (no slice time correction with short TR=1; no despiking or TSNR, because we don't know influences on time series needed for DCM; no scan drop, because scanner already performed shim-correction)
- motion-correct the functional images to a mean func image and use the parameters-file to visually inspect for motion-outliers via ArtifactDetect
- skullstrip the mean func image
- coregister the skullstripped mean func image to the skullstripped anatomical image (from the freesurfer-derived anatomical processing); use bbregister from freesurfer
- coregister the skullstripped anat file to the ANTs-template
- put the 2 coregistered func-/anat-files into a list and perform ApplyTransforms via ANTs for normalisation (before 1<sup>st</sup> level, because DCM!)
- smoothing with FWHM=6mm