

Doom Configuration file

Casper Weiss Bang

December 10, 2020

Contents

1	Config	3
1.1	Personal Information	3
1.1.1	Set full name	3
1.1.2	Set email address	3
1.2	tabsize	3
1.3	Strech cursor	3
1.4	Color themes	3
1.5	Projectile	4
1.6	Languages	4
1.6.1	Python	4
1.7	ORG-mode	4
1.7.1	Directory	4
1.7.2	Auto fill	4
1.7.3	Org agenda	4
1.7.4	Org agenda Prefixes	5
1.7.5	Syntax highlight PDF	5
1.7.6	Refile targets	5
1.7.7	Capture templates	6
1.7.8	Always show images	6
1.7.9	export to keybase	6
1.7.10	Exporting	7
1.7.11	Org-ref / bibtex	7
1.7.12	Dot / graphviz	8
1.7.13	IEEEtran export	8
1.7.14	Change the character that displays on collapsed head- ings	12
1.8	Ranger-mode	12

1.9	Movements	12
1.10	RSS	12
1.11	Hacks	12
2	Sources	13
2.1	https://github.com/Brettm12345/doom-emacs-literate-config/ blob/master/config.org#emacseshell	13
2.2	https://github.com/hlissner/doom-emacs-private/blob/ master/config.el	13

1 Config

1.1 Personal Information

1.1.1 Set full name

```
1 (setq user-full-name "Casper Weiss Bang")
```

1.1.2 Set email address

```
1 (setq user-mail-address "cawb@itu.dk")
```

1.2 tabsize

Set width for tabs

```
1 (setq-default tab-width 4)
```

1.3 Stretch cursor

Stretch cursor to the glyph width

```
1 (setq-default x-stretch-cursor t)
```

1.4 Color themes

```
1 (setq doom-font (font-spec :family "SauceCodePro Nerd Font" :size 12))
2 (setq doom-theme 'doom-nord)
3 ;; Edit org coloring levels, so it follows the official palette.
4 (custom-set-faces
5   '(org-level-1 ((t (:foreground "#8fbcbb" :weight extra-bold))))
6   '(org-level-2 ((t (:foreground "#88C0D0" :weight bold))))
7   '(org-level-3 ((t (:foreground "#81a1c1" :weight semi-bold))))
8   '(org-level-4 ((t (:foreground "#5e81ac" :weight normal))))
9   '(org-level-5 ((t (:inherit org-level-4))))
10  '(org-level-6 ((t (:inherit org-level-4))))
11  '(org-level-7 ((t (:inherit org-level-4))))
12  '(org-level-8 ((t (:inherit org-level-4)))))
```

1.5 Projectile

```
1 (setq projectile-indexing-method 'alien
2     projectile-sort-order 'recently-active
3     projectile-globally-ignored-files '(".DS_Store" "Icon" "TAGS")
4     projectile-globally-ignored-file-suffixes '(".elc" ".pyc" ".o")
5     projectile-globally-ignored-directories '("node_modules")
6     projectile-enable-caching t)
```

1.6 Languages

1.6.1 Python

```
1 (setq-hook! python-mode python-indent-offset 2)
2
3 (add-hook! 'python-mode-hook (modify-syntax-entry ?_ "w"))
```

1.7 ORG-mode

1.7.1 Directory

```
1 (after! org
2     (setq org-directory "~/Documents/org/"))
3 )
```

1.7.2 Auto fill

```
1 (after! org
2     (auto-fill-mode 1)
3     )
4 (add-hook 'text-mode-hook 'turn-on-auto-fill)
```

1.7.3 Org agenda

```
1 (setq org-agenda-files '("~/Documents/org/inbox.org"
2     "~/Documents/org/gtd.org"
3     "~/Documents/org/wishlist.org"))
```

```

4         "~/Documents/org/gcal.org"
5         "~/Documents/org/tickler.org"))

```

1.7.4 Org agenda Prefixes

```

1 (setq org-agenda-prefix-format
2     (quote
3       ((agenda . " %i %-12:c%?-12t% s")
4        (todo . "%l %i %-6:c")
5        (tags . " %i %-12:c")
6        (search . " %i %-12:c"))))

```

1.7.5 Syntax highlight PDF

```

1 (eval-after-load 'org
2   '(add-to-list 'org-latex-packages-alist '("" "minted")))
3 (setq org-latex-listings 'minted)
4 (setq org-latex-minted-options
5     '(("frame" "lines") ("linenos=true") ))
6 (eval-after-load 'tex-mode
7   '(setcar (cdr (cddaar tex-compile-commands)) " -shell-escape "))
8 (eval-after-load 'ox-latex
9   '(setq org-latex-pdf-process
10        '("latexmk -pdflatex='pdflatex -shell-escape -interaction nonstopmode' -pdf

```

1.7.6 Refile targets

```

1 (setq org-refile-targets '("~/Documents/org/gtd.org" :maxlevel . 3)
2                           ("~/Documents/org/someday.org" :level . 1)
3                           ("~/Documents/org/archive.org" :level . 1)
4                           ("~/Documents/org/wishlist.org" :level . 1)
5                           ("~/Documents/org/tickler.org" :maxlevel . 2)))

```

1.7.7 Capture templates

```
1 (after! org
2   (setq org-capture-templates '(("t" "Todo [inbox]" entry
3     (file+headline "~/Documents/org/gtd.org" "Backlog")
4     "* TODO %i%?")
5     ("n" "Note" entry
6       (file+headline "~/Documents/org/notes.org" "Notes")
7       "* %U \n%i%?")
8     ("f" "Frida Journal" entry
9       (file+headline "~/Documents/org/frida.org" "Fridas d
10      "* %U \n%i%?")
11     ("w" "Wish" entry
12       (file+headline "~/Documents/org/wishlist.org" "Wishl
13       "* %i%?")
14     ))
15 )
```

1.7.8 Always show images

```
1 (after! org-ref
2   (setq org-startup-with-inline-images "inlineimages")
3 )
```

1.7.9 export to keybase

```
1 (after! org
2   (setq org-publish-project-alist
3     `(("KBP"
4       :base-directory "~/Documents/org/kbp"
5       :publishing-directory "/keybase/public/cabang/"
6       :publishing-function org-twbs-publish-to-html
7       ;;:section-numbers nil
8       :with-headline-numbers nil
9       ;;:table-of-contents nil
10      :html-head-extra ,(format "<style type=\"text/css\">%s</style>"
11                                (with-temp-buffer
12                                  (insert-file-contents "~/.config/doom/nord.css
```

```

13                                     (buffer-string))
14                                     )
15             )))
16 )

```

1.7.10 Exporting

```

1  ;; newline on toc
2  (org-babel-do-load-languages
3    'org-babel-load-languages
4    '((plantuml . t)))
5  (setq org-latex-toc-command "\\tableofcontents \\clearpage")

```

1.7.11 Org-ref / bibtex

1. set paths

```

1  ;;(after! org
2  ;;      (setq bibtex-completion-bibliography "~/Documents/bibliography/references
3  ;;          bibtex-completion-library-path "~/Documents/bibliography/bibtex-pdfs"
4  ;;          bibtex-completion-notes-path "~/Documents/bibliography/helm-bibtex-no
5  ;; )

```

2. Pre/Post text support

```

1  (after! org-ref
2    (setf (cdr (assoc 'org-mode bibtex-completion-format-citation-functions)) 'o
3    )

```

3. How to open files

```

1  (after! org
2    (setq bibtex-completion-pdf-open-function 'org-open-file)
3    )

```

4. Export to PDF/L^AT_EX

```

1 (after! org
2   (setq org-latex-pdf-process
3     '("pdflatex -interaction nonstopmode -output-directory %o %f"
4       "bibtex %b"
5       "pdflatex -interaction nonstopmode -output-directory %o %f"
6       "pdflatex -interaction nonstopmode -output-directory %o %f"))
7   )
8 (after! org
9   (setq bibtex-dialect 'bibtex)
10  )

```

1.7.12 Dot / graphviz

```

1 (org-babel-do-load-languages
2   'org-babel-load-languages
3   '((dot . t))) ; this line activates dot

```

1.7.13 IEEEtran export

```

1 (after! org
2   (setq org-latex-default-packages-alist
3     '((" "graphicx" t)
4       (" "grffile" t)
5       (" "longtable" nil)
6       (" "wrapfig" nil)
7       (" "rotating" nil)
8       ("normalem" "ulem" t)
9       (" "amsmath" t)
10      (" "textcomp" t)
11      (" "amssymb" t)
12      (" "capt-of" nil)
13      (" "hyperref" nil)
14    ))
15
16   (add-to-list 'org-latex-classes
17     ' (
18       ("IEEEtran"

```



```

19         "\\documentclass{IEEEtran}
20         \\usepackage{cite}
21         \\usepackage{amsmath,amssymb,amsfonts}
22         \\usepackage{algorithmic}
23         \\usepackage{graphicx}
24         \\usepackage{textcomp}
25         \\usepackage{xcolor}
26         \\usepackage{hyperref}
27         [DEFAULT-PACKAGES]
28         [PACKAGES]
29         [EXTRA] "
30         ("\\section{%s}" . "\\section*{%s}")
31         ("\\subsection{%s}" . "\\subsection*{%s}")
32         ("\\subsubsection{%s}" . "\\subsubsection*{%s}")
33         ("\\paragraph{%s}" . "\\paragraph*{%s}")
34         ("\\subparagraph{%s}" . "\\subparagraph*{%s}")
35     )
36     ("article"
37         "\\RequirePackage{fix-cm}
38         \\PassOptionsToPackage{svgnames}{xcolor}
39         \\documentclass[11pt]{article}
40         \\usepackage{fontspec}
41         \\setmainfont{ETBembo RomanOSF}
42         \\setsansfont[Scale=MatchLowercase]{Raleway}
43         \\setmonofont[Scale=MatchLowercase]{Operator Mono SSm}
44         \\usepackage{sectsty}
45         \\allsectionsfont{\\sffamily}
46         \\usepackage{enumitem}
47         \\setlist[description]{style=unboxed,font=\\sffamily\\bfseries}
48         \\usepackage{listings}
49         \\lstset{frame=single,aboveskip=1em,
50             framesep=.5em,backgroundcolor=\\color{AliceBlue},
51             rulecolor=\\color{LightSteelBlue},framerule=1pt}
52         \\usepackage{xcolor}
53         \\newcommand\\basicdefault[1]{\\scriptsize\\color{Black}\\ttfamily#1}
54         \\lstset{basicstyle=\\basicdefault{\\spaceskip1em}}
55         \\lstset{literate=
56             {§}{\\S}}1
57             {@}{\\raisebox{.125ex}{\\copyright}\\enspace}}1
58             {{\\guillemotleft}}1

```

```

59      {}{{\guillemotright}}1
60      {Á}{{\ 'A}}1
61      {Ä}{{\ \"A}}1
62      {É}{{\ 'E}}1
63      {Í}{{\ 'I}}1
64      {Ó}{{\ 'O}}1
65      {Ö}{{\ \"O}}1
66      {Ú}{{\ 'U}}1
67      {Ü}{{\ \"U}}1
68      {ß}{{\ss}}2
69      {à}{{\`a}}1
70      {á}{{\ 'a}}1
71      {ä}{{\ \"a}}1
72      {é}{{\ 'e}}1
73      {í}{{\ 'i}}1
74      {ó}{{\ 'o}}1
75      {ö}{{\ \"o}}1
76      {ú}{{\ 'u}}1
77      {ü}{{\ \"u}}1
78      {¹}{{\textsuperscript1}}1
79          {²}{{\textsuperscript2}}1
80          {³}{{\textsuperscript3}}1
81      {₁}{{\i}}1
82      { | }{{\---}}1
83      { ' }{{\ ' }}1
84      { ... }{{\dots}}1
85          { }{{\hookleftarrow$}}1
86      { _ }{{\textvisiblespace}}1,
87      keywordstyle=\color{DarkGreen}\bfseries,
88      identifierstyle=\color{DarkRed},
89      commentstyle=\color{Gray}\upshape,
90      stringstyle=\color{DarkBlue}\upshape,
91      emphstyle=\color{Chocolate}\upshape,
92      showstringspaces=false,
93      columns=fullflexible,
94      keepspaces=true}
95      \usepackage[a4paper,margin=1in,left=1.5in]{geometry}
96      \usepackage{parskip}
97      \makeatletter
98      \renewcommand{\maketitle}{%

```

```

99         \\\begingroup\\parindent0pt
100         \\\sffamily
101         \\\Huge{\\bfseries\\@title}\\par\\bigskip
102         \\\LARGE{\\bfseries\\@author}\\par\\medskip
103         \\\normalsize\\@date\\par\\bigskip
104         \\\endgroup\\@afterindentfalse\\@afterheading}
105         \\\makeatother
106         [DEFAULT-PACKAGES]
107         \\\hypersetup{linkcolor=Blue,urlcolor=DarkBlue,
108         citecolor=DarkRed,colorlinks=true}
109         \\\AtBeginDocument{\\renewcommand{\\UrlFont}{\\ttfamily}}
110         [PACKAGES]
111         [EXTRA] "
112         ("\\section{%s}" . "\\section*{%s}")
113         ("\\subsection{%s}" . "\\subsection*{%s}")
114         ("\\subsubsection{%s}" . "\\subsubsection*{%s}")
115         ("\\paragraph{%s}" . "\\paragraph*{%s}")
116         ("\\subparagraph{%s}" . "\\subparagraph*{%s}")
117     )
118
119     ("report" "\\documentclass[11pt]{report}"
120     ("\\part{%s}" . "\\part*{%s}")
121     ("\\chapter{%s}" . "\\chapter*{%s}")
122     ("\\section{%s}" . "\\section*{%s}")
123     ("\\subsection{%s}" . "\\subsection*{%s}")
124     ("\\subsubsection{%s}" . "\\subsubsection*{%s}")
125 )
126
127     ("book" "\\documentclass[11pt]{book}"
128     ("\\part{%s}" . "\\part*{%s}")
129     ("\\chapter{%s}" . "\\chapter*{%s}")
130     ("\\section{%s}" . "\\section*{%s}")
131     ("\\subsection{%s}" . "\\subsection*{%s}")
132     ("\\subsubsection{%s}" . "\\subsubsection*{%s}")
133 )
134 )
135 )
136 )

```

1. **TODO** automatically handle *abstract*

1.7.14 Change the character that displays on collapsed headings

```
1 (setq org-ellipsis " ")
```

1.8 Ranger-mode

```
1 (map! (:leader (:prefix "o" :desc "Ranger" :nv "F" 'ranger)))
2 (after! ranger
3   (setq ranger-ignored-extensions '("mkv" "iso" "mp4"))
4   (setq ranger-show-hidden t)
5   (setq ranger-cleanup-on-disable t)
6   (setq ranger-cleanup-eagerly t)
7 )
```

1.9 Movements

```
1 (map!
2   (:after evil
3     :en "C-h" #'evil-window-left
4     :en "C-j" #'evil-window-down
5     :en "C-k" #'evil-window-up
6     :en "C-l" #'evil-window-right))
```

1.10 RSS

```
1 ;; el feed
2 (global-set-key (kbd "C-x w") 'elfeed)
3 (setq elfeed-feeds
4   '("http://nullprogram.com/feed/"
5     "https://node2.feed43.com/2538022243138888.xml"
6     "https://www.dr.dk/nyheder/service/feeds/allenyheder"
7     ))
```

1.11 Hacks

So i got an error, and based on this the following should fix it

¹ `(setq max-specpdl-size 13000)`

2 Sources

- 2.1 <https://github.com/Brettm12345/doom-emacs-literate-config/blob/master/config.org#emacseshell>
- 2.2 <https://github.com/hlissner/doom-emacs-private/blob/master/config.el>