



Select a spec

default

# Api Documentation <sup>1.0</sup>

[ Base URL: localhost:8080/ ]  
<http://localhost:8080/v2/api-docs>

Api Documentation  
[Terms of service](#)  
[Apache 2.0](#)

basic-error-controller Basic Error Controller

>

ticket-resource Ticket Resource

✓

POST

/tickets

An endpoint to book a ticket using a user's name, phone number, and timings.

Parameters

Try it out

Name	Description
<b>ticket</b> * required	ticket
(body)	<div><div>Example Value</div><div>Model</div><div><pre>{   "bookedDate": "yyyy-MM-dd",   "id": 0,   "mobNumber": "string",   "movieTime": "HH:mm:ss",   "status": 0,   "userName": "string" }</pre></div></div>

Parameter content type

application/json

Responses

Response content type

\*/\*

Code	Description
201	<i>Created</i>
<div><div>Example Value</div><div>Model</div><pre>{  "bookedDate": "yyyy-MM-dd",  "id": 0,  "mobNumber": "string",  "movieTime": "HH:mm:ss",  "status": 0,  "userName": "string"}</pre></div>	
401	<i>Unauthorized</i>
403	<i>Forbidden</i>
404	<i>Not Found</i>

GET

/tickets/{id}

An endpoint to view the user's details based on the ticket id.

Parameters

Try it out

Name	Description
<div><div>id * required</div><div>integer(\$int32)</div><div>(path)</div></div>	id

Responses

Response content type

\*/\*

Code	Description
------	-------------

Code	Description
200	<i>OK</i>
<div><div>Example Value</div><div>Model</div><pre>{  "emailId": "string",  "id": 0,  "mobNumber": "string",  "name": "string"}</pre></div>	
401	<i>Unauthorized</i>
403	<i>Forbidden</i>
404	<i>Not Found</i>

DELETE

/tickets/{id}

An endpoint to delete a particular ticket based on ticket id.

Parameters

Try it out

Name	Description
<div><div>id * required</div><div>integer(\$int32)</div><div>(path)</div></div>	id

Responses

Response content type

\*/\*

Code	Description
200	<i>OK</i>
204	<i>No Content</i>

Code	Description
401	<i>Unauthorized</i>
403	<i>Forbidden</i>

PATCH

/tickets/{id}

An endpoint to update a ticket timing based on ticket id.

Parameters

Try it out

Name	Description
<b>id</b> * required integer(\$int32) (path)	id
<b>ticketUpdate</b> * required (body)	ticketUpdate

Example Value

Model

```
{  "bookedDate": "yyyy-MM-dd",  "movieTime": "HH:mm:ss"}
```

Parameter content type

application/json

Responses

Response content type

\*/\*

Code	Description
------	-------------

Code	Description
200	<i>OK</i>
<div><div>Example Value</div><div>Model</div><pre>{  "bookedDate": "yyyy-MM-dd",  "id": 0,  "mobNumber": "string",  "movieTime": "HH:mm:ss",  "status": 0,  "userName": "string"}</pre></div>	
204	<i>No Content</i>
401	<i>Unauthorized</i>
403	<i>Forbidden</i>

GET

/tickets/mt/{bookedDate}/{movieTime}

An endpoint to view all the tickets for a particular time.

Parameters

Try it out

Name	Description
<b>bookedDate</b> * required string (path)	bookedDate
<b>movieTime</b> * required string (path)	movieTime

Responses

Response content type

\*/\*

Code	Description
------	-------------

Code	Description
200	<i>OK</i>
<div><div>Example Value</div><div>Model</div><pre>[   {     "bookedDate": "yyyy-MM-dd",     "id": 0,     "mobNumber": "string",     "movieTime": "HH:mm:ss",     "status": 0,     "userName": "string"   } ]</pre></div>	
401	<i>Unauthorized</i>
403	<i>Forbidden</i>
404	<i>Not Found</i>

user-resource

User Resource



POST

/users

Add a user to the User database

Parameters

Try it out

Name	Description

Name

Description

newUser \* required

(body)

Example Value

Model

```
{
  "emailId": "string",
  "id": 0,
  "mobNumber": "string",
  "name": "string"
}
```

Parameter content type

application/json

Responses

Response content type \*/\*

Code

Description

201

Created

Example Value

Model

```
{
  "emailId": "string",
  "id": 0,
  "mobNumber": "string",
  "name": "string"
}
```

401

Unauthorized

Models

403

Forbidden

ModelAndView

404

Not Found

7/8

```
Ticket  {  
    bookedDate      string  
                    example: yyyy-MM-dd  
    id              integer($int32)  
    mobNumber       string  
    movieTime       string  
                    example: HH:mm:ss  
    status          integer($int32)  
    userName        string  
}
```

```
TicketUpdate  {  
    bookedDate      string  
                    example: yyyy-MM-dd  
    movieTime       string  
                    example: HH:mm:ss  
}
```

```
User  {  
    emailId         string  
    id              integer($int32)  
    mobNumber       string  
    name            string  
}
```

**View**