Design & Implementierung eines Echtzeit-Q&A-Systems als Erweiterung des IAmA-Subreddits

(Python) – Dokumentation von Crawler / Analyzer - Scripts

Benedikt Hierl
Version 1.0
Sonntag, den 25.09.2016

Table of Contents

Namespace Index

Packages

Here are the packages with brief descriptions (if available):

Class Index

Class List

Here are the classes, structs, unions and interfaces with brief descriptions:

File Index

File List

Here is a list of all files with brief descriptions:

Namespace Documentation

a__everything_Big_CSV_analyzer Namespace Reference

Functions

- def relation_question_upvotes_with_amount_of_questions_answered_by_iama_host ()
- def average_means_of_values_f_threads ()
- def relation_thread_upvotes_with_amount_of_comments ()
- def relation_thread_upvotes_with_amount_of_questions ()
- def relation_thread_downvotes_with_amount_of_comments ()
- def relation_thread_downvotes_with_amount_of_questions ()
- def relation_thread_upvotes_and_iama_host_response_time_comments ()
- def relation_thread_upvotes_and_iama_host_response_time_questions ()
- def relation_thread_downvotes_and_iama_host_response_time_comments ()
- def relation_thread_downvotes_and_iama_host_response_time_questions ()
- def relation_thread_lifespan_to_last_comment_and_amount_of_comments ()
- def relation_thread_lifespan_to_last_comment_and_amount_of_questions ()
- def relation_thread_lifespan_to_last_question_and_amount_of_comments ()
- def relation_thread_lifespan_to_last_question_and_amount_of_question ()
- def relation_thread_lifespan_to_last_comment_and_iama_host_response_time_to_comments ()
- def relation_thread_lifespan_to_last_comment_and_iama_host_response_time_to_questions ()
- def relation_thread_lifespan_to_last_question_and_iama_host_response_time_to_comments ()
- def relation_thread_lifespan_to_last_question_and_iama_host_response_time_to_questions ()
- def relation_thread_reaction_time_comments_and_iama_host_response_time_to_comments ()
- def relation_thread_reaction_time_comments_and_iama_host_response_time_to_questions ()
- def relation_thread_reaction_time_questions_and_iama_host_response_time_to_comments ()
- def relation_thread_reaction_time_questions_and_iama_host_response_time_to_questions ()
- def relation_thread_reaction_time_comments_and_amount_of_comments_the_iama_host_answered_to ()
- def relation_thread_reaction_time_comments_and_amount_of_questions_the_iama_host_answered_to ()
- def relation_thread_reaction_time_questions_and_amount_of_comments_the_iama_host_answered_to ()
- def relation_thread_reaction_time_questions_and_amount_of_questions_the_iama_host_answered_to ()
- def relation_thread_amount_of_questioners_total_and_num_questions_answered_by_iama_host ()
- def realation_thread_amount_of_commentators_total_and_num_comments_answered_by_iama_host ()
- def relation_thread_amount_of_questions_and_amount_questions_answered_by_iama_host ()
- def thread_overall_correlation ()
- def question_overall_correlation ()
- def average_means_of_values_f_authors ()
- def median_of_values_f_authors_randomized ()
- def median_of_values_f_authors ()
- def arr_of_values_f_authors ()
- def calculate_t_tests_of_author_values ()

Variables

- author_information_iama
- author_information_iama_sampleset_randomized
- author_information_random
- author_information_random_sampleset_randomized
- thread_information
- question_information
- inplace
- author_amount_creation_iama_threads = author_information_iama['amount_creation_iama_threads']

- author_amount_creation_other_threads = author_information_iama['amount_creation_other_threads']
- author_amount_of_comments_except_iama = author_information_iama['amount_of_comments_except_iama']
- author_amount_of_comments_iama = author_information_iama['amount_of_comments_iama']
- author_author_birth_date = author_information_iama['author_birth_date']
- author_author_comment_karma_amount = author_information_iama['author_comment_karma_amount']
- author_author_link_karma_amount = author_information_iama['author_link_karma_amount']
- author_author_name = author_information_iama['author_name']
- author_comment_creation_every_x_sec = author_information_iama['comment_creation_every_x_sec']
- author_thread_creation_every_x_sec = author_information_iama['thread_creation_every_x_sec']
- author_time_acc_birth_first_iama_thread = author_information_iama['time_acc_birth_first_iama_thread']
- author_time_diff_acc_creation_n_first_comment = author_information_iama['time_diff_acc_creation_n_first_comment']
- author_time_diff_acc_creation_n_first_thread = author_information_iama['time_diff_acc_creation_n_first_thread']
- author_amount_creation_iama_threads_randomized = author_information_iama_sampleset_randomized['amount_creation_iama_threads']
- author_amount_creation_other_threads_randomized = author_information_iama_sampleset_randomized['amount_creation_other_threads']
- author_amount_of_comments_except_iama_randomized = author_information_iama_sampleset_randomized['amount_of_comments_except_iama']
- author_amount_of_comments_iama_randomized = author_information_iama_sampleset_randomized['amount_of_comments_iama']
- author_author_birth_date_randomized = author_information_iama_sampleset_randomized['author_birth_date']
- author_author_comment_karma_amount_randomized = author_information_iama_sampleset_randomized['author_comment_karma_amount']
- author_author_link_karma_amount_randomized = author_information_iama_sampleset_randomized['author_link_karma_amount']
- author_author_name_randomized = author_information_iama_sampleset_randomized['author_name']
- author_comment_creation_every_x_sec_randomized = author_information_iama_sampleset_randomized['comment_creation_every_x_sec']
- author_thread_creation_every_x_sec_randomized = author_information_iama_sampleset_randomized['thread_creation_every_x_sec']
- author_time_acc_birth_first_iama_thread_randomized = author_information_iama_sampleset_randomized['time_acc_birth_first_iama_thread']
- author_time_diff_acc_creation_n_first_comment_randomized = author_information_iama_sampleset_randomized['time_diff_acc_creation_n_first_comment']
- author_time_diff_acc_creation_n_first_thread_randomized = author_information_iama_sampleset_randomized['time_diff_acc_creation_n_first_thread']
- random_author_amount_creation_iama_threads = author_information_random['amount_creation_iama_threads']
- random_author_amount_creation_other_threads = author_information_random['amount_creation_other_threads']
- random_author_amount_of_comments_except_iama = author_information_random['amount_of_comments_except_iama']
- random_author_amount_of_comments_iama = author_information_random['amount_of_comments_iama']
- random_author_author_birth_date = author_information_random['author_birth_date']
- random_author_author_comment_karma_amount = author_information_random['author_comment_karma_amount']
- random_author_author_link_karma_amount = author_information_random['author_link_karma_amount']
- random_author_author_name = author_information_random['author_name']
- random_author_comment_creation_every_x_sec = author_information_random['comment_creation_every_x_sec']
- random_author_thread_creation_every_x_sec = author_information_random['thread_creation_every_x_sec']
- random_author_time_acc_birth_first_iama_thread = author_information_random['time_acc_birth_first_iama_thread']
- random_author_time_diff_acc_creation_n_first_comment = \

- random_author_time_diff_acc_creation_n_first_thread
- random_author_amount_creation_iama_threads_randomized = author_information_random_sampleset_randomized['amount_creation_iama_threads']
- random_author_amount_creation_other_threads_randomized = author_information_random_sampleset_randomized['amount_creation_other_threads']
- random_author_amount_of_comments_except_iama_randomized = author_information_random_sampleset_randomized['amount_of_comments_except_iama']
- random_author_amount_of_comments_iama_randomized = author_information_random_sampleset_randomized['amount_of_comments_iama']
- random_author_author_birth_date_randomized = author_information_random_sampleset_randomized['author_birth_date']
- random_author_author_comment_karma_amount_randomized = author_information_random_sampleset_randomized['author_comment_karma_amount']
- random_author_author_link_karma_amount_randomized = author_information_random_sampleset_randomized['author_link_karma_amount']
- random_author_author_name_randomized = author_information_random_sampleset_randomized['author_name']
- random_author_comment_creation_every_x_sec_randomized = author_information_random_sampleset_randomized['comment_creation_every_x_sec']
- random_author_thread_creation_every_x_sec_randomized = author_information_random_sampleset_randomized['thread_creation_every_x_sec']
- random_author_time_acc_birth_first_iama_thread_randomized = author_information_random_sampleset_randomized['time_acc_birth_first_iama_thread']
- random_author_time_diff_acc_creation_n_first_comment_randomized = \
- random_author_time_diff_acc_creation_n_first_thread_randomized
- question_ups = question_information['Question ups']
- question_answered_by_iAMA_host = question_information['Question answered by iAMA host']
- thread_year = thread_information['Year']
- thread_id = thread_information['Thread id']
- thread_author = thread_information['Thread author']
- thread_ups = thread_information['Thread ups']
- thread_downs = thread_information['Thread downs']
- thread_creation_time_stamp = thread_information['Thread creation time stamp']
- thread_average_comment_vote_score_total
- thread_average_comment_vote_score_tier_1
- thread_average_comment_vote_score_tier_x
- thread_average_question_vote_score_total
- thread_average_question_vote_score_tier_1
- thread_average_question_vote_score_tier_x
- thread_num_comments_total_skewed
- thread_num_comments_total = thread_information['Thread num comments total']
- thread_num_comments_tier_1 = thread_information['Thread num comments tier 1']
- thread_num_comments_tier_x = thread_information['Thread num comments tier x']
- thread_num_questions_total = thread_information['Thread num questions total']
- thread_num_questions_tier_1 = thread_information['Thread num questions tier 1']
- thread_num_questions_tier_x = thread_information['Thread num questions tier x']
- thread_num_questions_answered_by_iama_host_total
- thread_num_questions_answered_by_iama_host_tier_1
- thread_num_questions_answered_by_iama_host_tier_x
- thread_num_comments_answered_by_iama_host_total
- thread_num_comments_answered_by_iama_host_tier_1
- thread_num_comments_answered_by_iama_host_tier_x
- thread_average_reaction_time_between_comments_total
- thread_average_reaction_time_between_comments_tier_1
- thread_average_reaction_time_between_comments_tier_x

- thread_average_reaction_time_between_questions_total
- thread_average_reaction_time_between_questions_tier_1
- thread_average_reaction_time_between_questions_tier_x
- thread_average_response_to_comment_time_iama_host_total
- thread_average_response_to_comment_time_iama_host_tier_1
- thread_average_response_to_comment_time_iama_host_tier_x
- thread_average_response_to_question_time_iama_host_total
- thread_average_response_to_question_time_iama_host_tier_1
- thread_average_response_to_question_time_iama_host_tier_x
- thread_amount_of_questioners_total
- thread_amount_of_questioners_tier_1
- thread_amount_of_questioners_tier_x
- thread_amount_of_commentators_total
- thread_amount_of_commentators_tier_1
- thread_amount_of_commentators_tier_x
- thread_life_span_until_last_comment
- thread_life_span_until_last_question

Function Documentation

def a__everything_Big_CSV_analyzer.arr_of_values_f_authors ()

Definition at line 3671 of file a__everything_Big_CSV_analyzer.py.

def a__everything_Big_CSV_analyzer.average_means_of_values_f_authors ()

```
Calculation of the average means of different values for author data

Args:
    -
Returns:
    -
```

Definition at line 3252 of file a__everything_Big_CSV_analyzer.py.

def a__everything_Big_CSV_analyzer.average_means_of_values_f_threads ()

```
Calculation of the average means of different values

Args:
    -
Returns:
    -
```

Definition at line 339 of file a__everything_Big_CSV_analyzer.py.

def a__everything_Big_CSV_analyzer.calculate_t_tests_of_author_values ()

Definition at line 3812 of file a__everything_Big_CSV_analyzer.py.

def a__everything_Big_CSV_analyzer.median_of_values_f_authors ()

Definition at line 3529 of file a__everything_Big_CSV_analyzer.py.

def a__everything_Big_CSV_analyzer.median_of_values_f_authors_randomized ()

Definition at line 3402 of file a__everything_Big_CSV_analyzer.py.

def a__everything_Big_CSV_analyzer.question_overall_correlation ()

```
Calculation of the correlation of every column with every column for the questions

Args:
    -
Returns:
    -
```

Definition at line 3240 of file a__everything_Big_CSV_analyzer.py.

def a__everything_Big_CSV_analyzer.realation_thread_amount_of_commentators_total_and_num_comments_answered_by_iama_host ()

```
Calculation of the correlation amount of commentators per thread <-> amount of questions answered
by iama host

Args:
    -
Returns:
    -
```

Definition at line 3003 of file a__everything_Big_CSV_analyzer.py.

def a__everything_Big_CSV_analyzer.relation_question_upvotes_with_amount_of_questions_answered_by_iama_host ()

```
Calculation of the correlation question upvotes <-> amount of questions answered by the iama host

Args:
    -
Returns:
    -
```

Definition at line 305 of file a__everything_Big_CSV_analyzer.py.

def a__everything_Big_CSV_analyzer.relation_thread_amount_of_questioners_total_and_num_questions_answered_by_iama_host ()

```
Calculation of the correlation amount of questioners per thread <-> amount of questions answered
by iama host

Args:
```

```
    -
Returns:
    -
```

Definition at line 2875 of file a__everything_Big_CSV_analyzer.py.

def a__everything_Big_CSV_analyzer.relation_thread_amount_of_questions_and_amount_questions_answered_by_iama_host ()

```
Calculation of the amount of questions ansked <-> amount of questions answered by iama host

Args:
    -
Returns:
    -
```

Definition at line 3131 of file a__everything_Big_CSV_analyzer.py.

def a__everything_Big_CSV_analyzer.relation_thread_downvotes_and_iama_host_response_time_comments ()

```
Calculation of the correlation thread downvotes <-> iama host repsonse time to comments

Args:
    -
Returns:
    -
```

Definition at line 886 of file a__everything_Big_CSV_analyzer.py.

def a__everything_Big_CSV_analyzer.relation_thread_downvotes_and_iama_host_response_time_questions ()

```
Calculation of the correlation thread downvotes <-> iama host repsonse time to questions

Args:
    -
Returns:
    -
```

Definition at line 972 of file a__everything_Big_CSV_analyzer.py.

def a__everything_Big_CSV_analyzer.relation_thread_downvotes_with_amount_of_comments ()

```
Calculation of the correlation thread downvotes <-> amount of comments

Args:
    -
Returns:
    -
```

Definition at line 584 of file a__everything_Big_CSV_analyzer.py.

def a__everything_Big_CSV_analyzer.relation_thread_downvotes_with_amount_of_questions ()

```
Calculation of the correlation thread downvotes <-> amount of questions

Args:
    -
Returns:
    -
```

Definition at line 651 of file a__everything_Big_CSV_analyzer.py.

def a__everything_Big_CSV_analyzer.relation_thread_lifespan_to_last_comment_and_amount_of_comments ()

```
Calculation of the correlation thread life span (until last comment) <-> amount of comments

Args:
    -
Returns:
    -
```

Definition at line 1060 of file a__everything_Big_CSV_analyzer.py.

def a__everything_Big_CSV_analyzer.relation_thread_lifespan_to_last_comment_and_amount_of_questions ()

```
Calculation of the correlation thread life span (until last comment) <-> amount of questions

Args:
    -
Returns:
    -
```

Definition at line 1127 of file a__everything_Big_CSV_analyzer.py.

def a__everything_Big_CSV_analyzer.relation_thread_lifespan_to_last_comment_and_iama_host_response_time_to_comments ()

```
Calculation of the correlation thread life span (until last comment) <-> iama host repsonse time
to comments

Args:
    -
Returns:
    -
```

Definition at line 1335 of file a__everything_Big_CSV_analyzer.py.

def a__everything_Big_CSV_analyzer.relation_thread_lifespan_to_last_comment_and_iama_host_response_time_to_questions ()

```
Calculation of the correlation thread life span (until last comment) <-> iama host repsonse time
to questions

Args:
    -
Returns:
    -
```

Definition at line 1463 of file a__everything_Big_CSV_analyzer.py.

def a__everything_Big_CSV_analyzer.relation_thread_lifespan_to_last_question_and_amount_of_comments ()

```
Calculation of the correlation thread life span (until last question) <-> amount of comments

Args:
    -
Returns:
    -
```

Definition at line 1194 of file a__everything_Big_CSV_analyzer.py.

def a__everything_Big_CSV_analyzer.relation_thread_lifespan_to_last_question_and_amount_of_question ()

```
Calculation of the correlation thread life span (until last question) <-> amount of question

Args:
    -
Returns:
    -
```

Definition at line 1261 of file a__everything_Big_CSV_analyzer.py.

def a__everything_Big_CSV_analyzer.relation_thread_lifespan_to_last_question_and_iama_host_response_time_to_comments ()

```
Calculation of the correlation thread life span (until last question) <-> and iama host repsonse
time to comments

Args:
    -
Returns:
    -
```

Definition at line 1591 of file a__everything_Big_CSV_analyzer.py.

def a__everything_Big_CSV_analyzer.relation_thread_lifespan_to_last_question_and_iama_host_response_time_to_questions ()

```
Calculation of the correlation thread life span (until last question) <-> iama host repsonse time
to questions
```

```
Args:
    -
Returns:
    -
```

Definition at line 1719 of file a__everything_Big_CSV_analyzer.py.

def a__everything_Big_CSV_analyzer.relation_thread_reaction_time_comments_and_amount_of_comments_the_iama_host_answered_to ()

```
Calculation of the correlation thread reaction time between comments <-> amount of comments the
iama host
    reacted to

Args:
    -
Returns:
    -
```

Definition at line 2359 of file a__everything_Big_CSV_analyzer.py.

def a__everything_Big_CSV_analyzer.relation_thread_reaction_time_comments_and_amount_of_questions_the_iama_host_answered_to ()

```
Calculation of the correlation thread reaction time between comments <-> amount of questions the
    iama host reacted to

Args:
    -
Returns:
    -
```

Definition at line 2488 of file a__everything_Big_CSV_analyzer.py.

def a__everything_Big_CSV_analyzer.relation_thread_reaction_time_comments_and_iama_host_response_time_to_comments ()

```
Calculation of the correlation thread reaction time between comments <-> iama host repsonse time
to comments

Args:
    -
Returns:
    -
```

Definition at line 1847 of file a__everything_Big_CSV_analyzer.py.

def a__everything_Big_CSV_analyzer.relation_thread_reaction_time_comments_and_iama_host_response_time_to_questions ()

```
Calculation of the correlation thread reaction time between comments <-> iama host repsonse time
to questions
```

```
Args:
    -
Returns:
    -
```

Definition at line 1975 of file a__everything_Big_CSV_analyzer.py.

def a__everything_Big_CSV_analyzer.relation_thread_reaction_time_questions_and_amount_of_comments_the_iama_host_answered_to ()

```
Calculation of the correlation thread reaction time between questions <-> amount of comments the
    iama host reacted to

Args:
    -
Returns:
    -
```

Definition at line 2617 of file a__everything_Big_CSV_analyzer.py.

def a__everything_Big_CSV_analyzer.relation_thread_reaction_time_questions_and_amount_of_questions_the_iama_host_answered_to ()

```
Calculation of the correlation thread reaction time between questions <-> amount of questions the
iama
    host reacted to

Args:
    -
Returns:
    -
```

Definition at line 2746 of file a__everything_Big_CSV_analyzer.py.

def a__everything_Big_CSV_analyzer.relation_thread_reaction_time_questions_and_iama_host_response_time_to_comments ()

```
Calculation of the correlation thread reaction time between questions <-> iama host repsonse time
to comments

Args:
    -
Returns:
    -
```

Definition at line 2103 of file a__everything_Big_CSV_analyzer.py.

def a__everything_Big_CSV_analyzer.relation_thread_reaction_time_questions_and_iama_host_response_time_to_questions ()

```
Calculation of the correlation thread reaction time between questions <-> iama host repsonse time
to questions
```

```
Args:
    -
Returns:
    -
```

Definition at line 2231 of file a__everything_Big_CSV_analyzer.py.

def a__everything_Big_CSV_analyzer.relation_thread_upvotes_and_iama_host_response_time_comments ()

```
Calculation of the correlation thread upvotes <-> iama host repsonse time to comments

Args:
    -
Returns:
    -
```

Definition at line 718 of file a__everything_Big_CSV_analyzer.py.

def a__everything_Big_CSV_analyzer.relation_thread_upvotes_and_iama_host_response_time_questions ()

```
Calculation of the correlation thread upvotes <-> iama host repsonse time to questions

Args:
    -
Returns:
    -
```

Definition at line 800 of file a__everything_Big_CSV_analyzer.py.

def a__everything_Big_CSV_analyzer.relation_thread_upvotes_with_amount_of_comments ()

```
Calculation of the correlation thread upvotes <-> amount of comments

Args:
    -
Returns:
    -
```

Definition at line 449 of file a__everything_Big_CSV_analyzer.py.

def a__everything_Big_CSV_analyzer.relation_thread_upvotes_with_amount_of_questions ()

```
Calculation of the correlation thread upvotes <-> amount of questions

Args:
    -
Returns:
    -
```

Definition at line 517 of file a__everything_Big_CSV_analyzer.py.

def a__everything_Big_CSV_analyzer.thread_overall_correlation ()

```
Calculation of the correlation of every column with every column for the threads

Args:
    -
Returns:
    -
```

Definition at line 3228 of file a__everything_Big_CSV_analyzer.py.

Variable Documentation

a__everything_Big_CSV_analyzer.author_amount_creation_iama_threads =
author_information_iama['amount_creation_iama_threads']

Definition at line 134 of file a__everything_Big_CSV_analyzer.py.

a__everything_Big_CSV_analyzer.author_amount_creation_iama_threads_randomized =
author_information_iama_sampleset_randomized['amount_creation_iama_threads']

Definition at line 149 of file a__everything_Big_CSV_analyzer.py.

a__everything_Big_CSV_analyzer.author_amount_creation_other_threads =
author_information_iama['amount_creation_other_threads']

Definition at line 135 of file a__everything_Big_CSV_analyzer.py.

a__everything_Big_CSV_analyzer.author_amount_creation_other_threads_randomized =
author_information_iama_sampleset_randomized['amount_creation_other_threads']

Definition at line 150 of file a__everything_Big_CSV_analyzer.py.

a__everything_Big_CSV_analyzer.author_amount_of_comments_except_iama =
author_information_iama['amount_of_comments_except_iama']

Definition at line 136 of file a__everything_Big_CSV_analyzer.py.

a__everything_Big_CSV_analyzer.author_amount_of_comments_except_iama_randomized =
author_information_iama_sampleset_randomized['amount_of_comments_except_iama']

Definition at line 151 of file a__everything_Big_CSV_analyzer.py.

a__everything_Big_CSV_analyzer.author_amount_of_comments_iama =
author_information_iama['amount_of_comments_iama']

Definition at line 137 of file a__everything_Big_CSV_analyzer.py.

a__everything_Big_CSV_analyzer.author_amount_of_comments_iama_randomized = author_information_iama_sampleset_randomized['amount_of_comments_iama']

Definition at line 152 of file a__everything_Big_CSV_analyzer.py.

a__everything_Big_CSV_analyzer.author_author_birth_date = author_information_iama['author_birth_date']

Definition at line 138 of file a__everything_Big_CSV_analyzer.py.

a__everything_Big_CSV_analyzer.author_author_birth_date_randomized = author_information_iama_sampleset_randomized['author_birth_date']

Definition at line 153 of file a__everything_Big_CSV_analyzer.py.

a__everything_Big_CSV_analyzer.author_author_comment_karma_amount = author_information_iama['author_comment_karma_amount']

Definition at line 139 of file a__everything_Big_CSV_analyzer.py.

a__everything_Big_CSV_analyzer.author_author_comment_karma_amount_randomized = author_information_iama_sampleset_randomized['author_comment_karma_amount']

Definition at line 154 of file a__everything_Big_CSV_analyzer.py.

a__everything_Big_CSV_analyzer.author_author_link_karma_amount = author_information_iama['author_link_karma_amount']

Definition at line 140 of file a__everything_Big_CSV_analyzer.py.

a__everything_Big_CSV_analyzer.author_author_link_karma_amount_randomized = author_information_iama_sampleset_randomized['author_link_karma_amount']

Definition at line 155 of file a__everything_Big_CSV_analyzer.py.

a__everything_Big_CSV_analyzer.author_author_name = author_information_iama['author_name']

Definition at line 141 of file a__everything_Big_CSV_analyzer.py.

a__everything_Big_CSV_analyzer.author_author_name_randomized = author_information_iama_sampleset_randomized['author_name']

Definition at line 156 of file a__everything_Big_CSV_analyzer.py.

a__everything_Big_CSV_analyzer.author_comment_creation_every_x_sec = author_information_iama['comment_creation_every_x_sec']

Definition at line 142 of file a__everything_Big_CSV_analyzer.py.

a__everything_Big_CSV_analyzer.author_comment_creation_every_x_sec_randomized = author_information_iama_sampleset_randomized['comment_creation_every_x_sec']

Definition at line 157 of file a__everything_Big_CSV_analyzer.py.

a__everything_Big_CSV_analyzer.author_information_iama

```
Initial value:    1 = pandas.read_csv(
    2     'a_author_information_iama.csv',
    3     sep=',',
    4     na_values="None")
```

Definition at line 78 of file a__everything_Big_CSV_analyzer.py.

a__everything_Big_CSV_analyzer.author_information_iama_sampleset_randomized

```
Initial value:    1 = author_information_iama.ix[np.random.choice
    2 (author_information_iama.index.values, 10000)]
```

Definition at line 84 of file a__everything_Big_CSV_analyzer.py.

a__everything_Big_CSV_analyzer.author_information_random

```
Initial value:    1 = pandas.read_csv(
    2     'a_author_Information_random.csv',
    3     sep=',',
    4     na_values="None")
```

Definition at line 90 of file a__everything_Big_CSV_analyzer.py.

a__everything_Big_CSV_analyzer.author_information_random_sampleset_randomized

```
Initial value:    1 = author_information_random.ix[np.random.choice
    2 (author_information_random.index.values, 10000)]
```

Definition at line 96 of file a__everything_Big_CSV_analyzer.py.

a__everything_Big_CSV_analyzer.author_thread_creation_every_x_sec = author_information_iama['thread_creation_every_x_sec']

Definition at line 143 of file a__everything_Big_CSV_analyzer.py.

a__everything_Big_CSV_analyzer.author_thread_creation_every_x_sec_randomized = author_information_iama_sampleset_randomized['thread_creation_every_x_sec']

Definition at line 158 of file a__everything_Big_CSV_analyzer.py.

a__everything_Big_CSV_analyzer.author_time_acc_birth_first_iama_thread = author_information_iama['time_acc_birth_first_iama_thread']

Definition at line 144 of file a__everything_Big_CSV_analyzer.py.

a__everything_Big_CSV_analyzer.author_time_acc_birth_first_iama_thread_randomized = author_information_iama_sampleset_randomized['time_acc_birth_first_iama_thread']

Definition at line 159 of file a__everything_Big_CSV_analyzer.py.

a__everything_Big_CSV_analyzer.author_time_diff_acc_creation_n_first_comment = author_information_iama['time_diff_acc_creation_n_first_comment']

Definition at line 145 of file a__everything_Big_CSV_analyzer.py.

a__everything_Big_CSV_analyzer.author_time_diff_acc_creation_n_first_comment_randomized = author_information_iama_sampleset_randomized['time_diff_acc_creation_n_first_comment']

Definition at line 160 of file a__everything_Big_CSV_analyzer.py.

a__everything_Big_CSV_analyzer.author_time_diff_acc_creation_n_first_thread = author_information_iama['time_diff_acc_creation_n_first_thread']

Definition at line 146 of file a__everything_Big_CSV_analyzer.py.

a__everything_Big_CSV_analyzer.author_time_diff_acc_creation_n_first_thread_randomized = author_information_iama_sampleset_randomized['time_diff_acc_creation_n_first_thread']

Definition at line 161 of file a__everything_Big_CSV_analyzer.py.

a__everything_Big_CSV_analyzer.inplace

Definition at line 117 of file a__everything_Big_CSV_analyzer.py.

a__everything_Big_CSV_analyzer.question_answered_by_iAMA_host = question_information['Question answered by iAMA host']

Definition at line 199 of file a__everything_Big_CSV_analyzer.py.

a__everything_Big_CSV_analyzer.question_information

```
Initial value:    1 = pandas.read_csv(
    2     'a question Answered Yes No Tier Percentage 2009 until 2016 ALL tier any.csv',
    3     sep=',',
    4     na values="None",
    5     low_memory=False)
```

Definition at line 110 of file a__everything_Big_CSV_analyzer.py.

a__everything_Big_CSV_analyzer.question_ups = question_information['Question ups']

Definition at line 198 of file a__everything_Big_CSV_analyzer.py.

a__everything_Big_CSV_analyzer.random_author_amount_creation_iama_threads = author_information_random['amount_creation_iama_threads']

Definition at line 164 of file a__everything_Big_CSV_analyzer.py.

a__everything_Big_CSV_analyzer.random_author_amount_creation_iama_threads_randomized = author_information_random_sampleset_randomized['amount_creation_iama_threads']

Definition at line 182 of file a__everything_Big_CSV_analyzer.py.

a__everything_Big_CSV_analyzer.random_author_amount_creation_other_threads = author_information_random['amount_creation_other_threads']

Definition at line 165 of file a__everything_Big_CSV_analyzer.py.

a__everything_Big_CSV_analyzer.random_author_amount_creation_other_threads_randomized = author_information_random_sampleset_randomized['amount_creation_other_threads']

Definition at line 183 of file a__everything_Big_CSV_analyzer.py.

a__everything_Big_CSV_analyzer.random_author_amount_of_comments_except_iama = author_information_random['amount_of_comments_except_iama']

Definition at line 166 of file a__everything_Big_CSV_analyzer.py.

a__everything_Big_CSV_analyzer.random_author_amount_of_comments_except_iama_randomized = author_information_random_sampleset_randomized['amount_of_comments_except_iama']

Definition at line 184 of file a__everything_Big_CSV_analyzer.py.

a__everything_Big_CSV_analyzer.random_author_amount_of_comments_iama = author_information_random['amount_of_comments_iama']

Definition at line 167 of file a__everything_Big_CSV_analyzer.py.

a__everything_Big_CSV_analyzer.random_author_amount_of_comments_iama_randomized = author_information_random_sampleset_randomized['amount_of_comments_iama']

Definition at line 185 of file a__everything_Big_CSV_analyzer.py.

a__everything_Big_CSV_analyzer.random_author_author_birth_date = author_information_random['author_birth_date']

Definition at line 168 of file a__everything_Big_CSV_analyzer.py.

a__everything_Big_CSV_analyzer.random_author_author_birth_date_randomized = author_information_random_sampleset_randomized['author_birth_date']

Definition at line 186 of file a__everything_Big_CSV_analyzer.py.

a__everything_Big_CSV_analyzer.random_author_author_comment_karma_amount = author_information_random['author_comment_karma_amount']

Definition at line 169 of file a__everything_Big_CSV_analyzer.py.

a__everything_Big_CSV_analyzer.random_author_author_comment_karma_amount_randomized = author_information_random_sampleset_randomized['author_comment_karma_amount']

Definition at line 187 of file a__everything_Big_CSV_analyzer.py.

a__everything_Big_CSV_analyzer.random_author_author_link_karma_amount = author_information_random['author_link_karma_amount']

Definition at line 170 of file a__everything_Big_CSV_analyzer.py.

a__everything_Big_CSV_analyzer.random_author_author_link_karma_amount_randomized = author_information_random_sampleset_randomized['author_link_karma_amount']

Definition at line 188 of file a__everything_Big_CSV_analyzer.py.

a__everything_Big_CSV_analyzer.random_author_author_name = author_information_random['author_name']

Definition at line 171 of file a__everything_Big_CSV_analyzer.py.

a__everything_Big_CSV_analyzer.random_author_author_name_randomized = author_information_random_sampleset_randomized['author_name']

Definition at line 189 of file a__everything_Big_CSV_analyzer.py.

a__everything_Big_CSV_analyzer.random_author_comment_creation_every_x_sec = author_information_random['comment_creation_every_x_sec']

Definition at line 172 of file a__everything_Big_CSV_analyzer.py.

a__everything_Big_CSV_analyzer.random_author_comment_creation_every_x_sec_randomized = author_information_random_sampleset_randomized['comment_creation_every_x_sec']

Definition at line 190 of file a__everything_Big_CSV_analyzer.py.

a__everything_Big_CSV_analyzer.random_author_thread_creation_every_x_sec = author_information_random['thread_creation_every_x_sec']

Definition at line 173 of file a__everything_Big_CSV_analyzer.py.

a__everything_Big_CSV_analyzer.random_author_thread_creation_every_x_sec_randomized = author_information_random_sampleset_randomized['thread_creation_every_x_sec']

Definition at line 191 of file a__everything_Big_CSV_analyzer.py.

a__everything_Big_CSV_analyzer.random_author_time_acc_birth_first_iama_thread = author_information_random['time_acc_birth_first_iama_thread']

Definition at line 174 of file a__everything_Big_CSV_analyzer.py.

a__everything_Big_CSV_analyzer.random_author_time_acc_birth_first_iama_thread_randomized = author_information_random_sampleset_randomized['time_acc_birth_first_iama_thread']

Definition at line 192 of file a__everything_Big_CSV_analyzer.py.

**a__everything_Big_CSV_analyzer.random_author_time_diff_acc_creation_n_first_comment = **

Definition at line 175 of file a__everything_Big_CSV_analyzer.py.

**a__everything_Big_CSV_analyzer.random_author_time_diff_acc_creation_n_first_comment_randomized = **

Definition at line 193 of file a__everything_Big_CSV_analyzer.py.

a__everything_Big_CSV_analyzer.random_author_time_diff_acc_creation_n_first_thread

```
Initial value:    1 = author_information_random[
    2     'time_diff_acc_creation_n_first_thread']
```

Definition at line 177 of file a__everything_Big_CSV_analyzer.py.

a__everything_Big_CSV_analyzer.random_author_time_diff_acc_creation_n_first_thread_randomized

```
Initial value:    1 = author_information_random_sampleset_randomized[
    2     'time_diff_acc_creation_n_first_thread']
```

Definition at line 195 of file a__everything_Big_CSV_analyzer.py.

a__everything_Big_CSV_analyzer.thread_amount_of_commentators_tier_1

```
Initial value:    1 = thread_information[
    2     'Thread amount of commentators tier 1']
```

Definition at line 286 of file a__everything_Big_CSV_analyzer.py.

a__everything_Big_CSV_analyzer.thread_amount_of_commentators_tier_x

```
Initial value:    1 = thread_information[
    2     'Thread amount of commentators tier x']
```

Definition at line 288 of file a__everything_Big_CSV_analyzer.py.

a__everything_Big_CSV_analyzer.thread_amount_of_commentators_total

```
Initial value:    1 = thread_information[
    2     'Thread amount of commentators total']
```

Definition at line 284 of file a__everything_Big_CSV_analyzer.py.

a__everything_Big_CSV_analyzer.thread_amount_of_questioners_tier_1

```
Initial value:    1 = thread_information[
    2     'Thread amount of questioners tier 1']
```

Definition at line 279 of file a__everything_Big_CSV_analyzer.py.

a__everything_Big_CSV_analyzer.thread_amount_of_questioners_tier_x

```
Initial value:    1 = thread_information[
    2     'Thread amount of questioners tier x']
```

Definition at line 281 of file a__everything_Big_CSV_analyzer.py.

a__everything_Big_CSV_analyzer.thread_amount_of_questioners_total

```
Initial value:    1 = thread_information[
    2     'Thread amount of questioners total']
```

Definition at line 277 of file a__everything_Big_CSV_analyzer.py.

a__everything_Big_CSV_analyzer.thread_author = thread_information['Thread author']

Definition at line 205 of file a__everything_Big_CSV_analyzer.py.

a__everything_Big_CSV_analyzer.thread_average_comment_vote_score_tier_1

```
Initial value:    1 = thread_information[
    2     'Thread average comment vote score tier 1']
```

Definition at line 213 of file a__everything_Big_CSV_analyzer.py.

a__everything_Big_CSV_analyzer.thread_average_comment_vote_score_tier_x

```
Initial value:    1 = thread_information[
    2     'Thread average comment vote score tier x']
```

Definition at line 215 of file a__everything_Big_CSV_analyzer.py.

a__everything_Big_CSV_analyzer.thread_average_comment_vote_score_total

```
Initial value:    1 = thread_information[
    2     'Thread average comment vote score total']
```

Definition at line 210 of file a__everything_Big_CSV_analyzer.py.

a__everything_Big_CSV_analyzer.thread_average_question_vote_score_tier_1

```
Initial value:    1 = thread_information[
    2     'Thread average question vote score tier 1']
```

Definition at line 220 of file a__everything_Big_CSV_analyzer.py.

a__everything_Big_CSV_analyzer.thread_average_question_vote_score_tier_x

```
Initial value:    1 = thread_information[
    2     'Thread average question vote score tier x']
```

Definition at line 222 of file a__everything_Big_CSV_analyzer.py.

a__everything_Big_CSV_analyzer.thread_average_question_vote_score_total

```
Initial value:    1 = thread_information[
    2     'Thread average question vote score total']
```

Definition at line 218 of file a__everything_Big_CSV_analyzer.py.

a__everything_Big_CSV_analyzer.thread_average_reaction_time_between_comments_tier_1

```
Initial value:    1 = thread_information[
    2     'Thread average reaction time between comments tier 1']
```

Definition at line 251 of file a__everything_Big_CSV_analyzer.py.

a__everything_Big_CSV_analyzer.thread_average_reaction_time_between_comments_tier_x

```
Initial value:    1 = thread_information[
    2     'Thread average reaction time between comments tier x']
```

Definition at line 253 of file a__everything_Big_CSV_analyzer.py.

a__everything_Big_CSV_analyzer.thread_average_reaction_time_between_comments_total

```
Initial value:    1 = thread_information[
    2     'Thread average reaction time between comments total']
```

Definition at line 249 of file a__everything_Big_CSV_analyzer.py.

a__everything_Big_CSV_analyzer.thread_average_reaction_time_between_questions_tier_1

```
Initial value:    1 = thread_information[
    2     'Thread average reaction time between questions tier 1']
```

Definition at line 258 of file a__everything_Big_CSV_analyzer.py.

a__everything_Big_CSV_analyzer.thread_average_reaction_time_between_questions_tier_x

```
Initial value:    1 = thread_information[
    2     'Thread average reaction time between questions tier x']
```

Definition at line 260 of file a__everything_Big_CSV_analyzer.py.

a__everything_Big_CSV_analyzer.thread_average_reaction_time_between_questions_total

```
Initial value:    1 = thread_information[
    2     'Thread average reaction time between questions total']
```

Definition at line 256 of file a__everything_Big_CSV_analyzer.py.

a__everything_Big_CSV_analyzer.thread_average_response_to_comment_time_iama_host_tier_1

```
Initial value:    1 = thread_information[
    2     'Thread average response to comment time iama host tier 1']
```

Definition at line 265 of file a__everything_Big_CSV_analyzer.py.

a__everything_Big_CSV_analyzer.thread_average_response_to_comment_time_iama_host_tier_x

```
Initial value:    1 = thread_information[
    2     'Thread average response to comment time iama host tier x']
```

Definition at line 267 of file a__everything_Big_CSV_analyzer.py.

a__everything_Big_CSV_analyzer.thread_average_response_to_comment_time_iama_host_total

```
Initial value:    1 = thread_information[
    2     'Thread average response to comment time iama host total']
```

Definition at line 263 of file a__everything_Big_CSV_analyzer.py.

a__everything_Big_CSV_analyzer.thread_average_response_to_question_time_iama_host_tier_1

```
Initial value:    1 = thread_information[
    2     'Thread average response to question time iama host tier 1']
```

Definition at line 272 of file a__everything_Big_CSV_analyzer.py.

a__everything_Big_CSV_analyzer.thread_average_response_to_question_time_iama_host_tier_x

```
Initial value:    1 = thread_information[
    2     'Thread average response to question time iama host tier x']
```

Definition at line 274 of file a__everything_Big_CSV_analyzer.py.

a__everything_Big_CSV_analyzer.thread_average_response_to_question_time_iama_host_total

```
Initial value:    1 = thread_information[
    2     'Thread average response to question time iama host total']
```

Definition at line 270 of file a__everything_Big_CSV_analyzer.py.

a__everything_Big_CSV_analyzer.thread_creation_time_stamp = thread_information['Thread creation time stamp']

Definition at line 208 of file a__everything_Big_CSV_analyzer.py.

a__everything_Big_CSV_analyzer.thread_downs = thread_information['Thread downs']

Definition at line 207 of file a__everything_Big_CSV_analyzer.py.

a__everything_Big_CSV_analyzer.thread_id = thread_information['Thread id']

Definition at line 204 of file a__everything_Big_CSV_analyzer.py.

a__everything_Big_CSV_analyzer.thread_information

```
Initial value:    1 = pandas.read_csv(
    2     'all.csv',
    3     sep=',',
    4     na_values="None")
```

Definition at line 104 of file a__everything_Big_CSV_analyzer.py.

a__everything_Big_CSV_analyzer.thread_life_span_until_last_comment

```
Initial value:    1 = thread_information[
    2     'Thread life span until last comment']
```

Definition at line 292 of file a__everything_Big_CSV_analyzer.py.

a__everything_Big_CSV_analyzer.thread_life_span_until_last_question

```
Initial value:    1 = thread_information[
    2     'Thread life span until last question']
```

Definition at line 294 of file a__everything_Big_CSV_analyzer.py.

a__everything_Big_CSV_analyzer.thread_num_comments_answered_by_iama_host_tier_1

```
Initial value:    1 = thread_information[
    2     'Thread num comments answered by iama host tier 1']
```

Definition at line 244 of file a__everything_Big_CSV_analyzer.py.

a__everything_Big_CSV_analyzer.thread_num_comments_answered_by_iama_host_tier_x

```
Initial value:    1 = thread_information[
    2     'Thread num comments answered by iama host tier x']
```

Definition at line 246 of file a__everything_Big_CSV_analyzer.py.

a__everything_Big_CSV_analyzer.thread_num_comments_answered_by_iama_host_total

```
Initial value:    1 = thread_information[
    2     'Thread num comments answered by iama host total']
```

Definition at line 242 of file a__everything_Big_CSV_analyzer.py.

a__everything_Big_CSV_analyzer.thread_num_comments_tier_1 = thread_information['Thread num comments tier 1']

Definition at line 228 of file a__everything_Big_CSV_analyzer.py.

a__everything_Big_CSV_analyzer.thread_num_comments_tier_x = thread_information['Thread num comments tier x']

Definition at line 229 of file a__everything_Big_CSV_analyzer.py.

a__everything_Big_CSV_analyzer.thread_num_comments_total = thread_information['Thread num comments total']

Definition at line 227 of file a__everything_Big_CSV_analyzer.py.

a__everything_Big_CSV_analyzer.thread_num_comments_total_skewed

```
Initial value:    1 = thread_information[
    2     'Thread num comments total skewed']
```

Definition at line 225 of file a__everything_Big_CSV_analyzer.py.

a__everything_Big_CSV_analyzer.thread_num_questions_answered_by_iama_host_tier_1

```
Initial value:    1 = thread_information[
    2     'Thread num questions answered by iama host tier 1']
```

Definition at line 237 of file a__everything_Big_CSV_analyzer.py.

a__everything_Big_CSV_analyzer.thread_num_questions_answered_by_iama_host_tier_x

```
Initial value:    1 = thread_information[
    2     'Thread num questions answered by iama host tier x']
```

Definition at line 239 of file a__everything_Big_CSV_analyzer.py.

a__everything_Big_CSV_analyzer.thread_num_questions_answered_by_iama_host_total

```
Initial value:    1 = thread_information[
    2     'Thread num questions answered by iama host total']
```

Definition at line 235 of file a__everything_Big_CSV_analyzer.py.

a__everything_Big_CSV_analyzer.thread_num_questions_tier_1 = thread_information['Thread num questions tier 1']

Definition at line 232 of file a__everything_Big_CSV_analyzer.py.

a__everything_Big_CSV_analyzer.thread_num_questions_tier_x = thread_information['Thread num questions tier x']

Definition at line 233 of file a__everything_Big_CSV_analyzer.py.

a__everything_Big_CSV_analyzer.thread_num_questions_total = thread_information['Thread num questions total']

Definition at line 231 of file a__everything_Big_CSV_analyzer.py.

a__everything_Big_CSV_analyzer.thread_ups = thread_information['Thread ups']

Definition at line 206 of file a__everything_Big_CSV_analyzer.py.

a__everything_Big_CSV_analyzer.thread_year = thread_information['Year']

Definition at line 203 of file a__everything_Big_CSV_analyzer.py.

a_author_Information Namespace Reference

Functions

- def check_script_arguments ()
- def initialize_mongo_db_parameters ()
- def write_csv_data ()

Variables

- mongo_db_client_instance = None
- mongo_db_author_instance = None
- mongo_db_author_collection = None
- int mongo_db_author_collection_original = 0
- string argument_db_to_choose = ""

Function Documentation

def a_author_Information.check_script_arguments ()

```
Checks if enough and correct arguments have been given to run this script adequate

1. It checks in the first instance if enough arguments have been given
2. Then necessary variables will be filled with appropriate values

Args:
    -
Returns:
    -
```

Definition at line 14 of file a_author_Information.py.

def a_author_Information.initialize_mongo_db_parameters ()

```
Instantiates all necessary variables for the correct usage of the mongoDB client

Args:
    -
Returns:
    -
```

Definition at line 48 of file a_author_Information.py.

def a_author_Information.write_csv_data ()

```
Gets all information from every collection within 'iAMA Reddit Authors*' database and writes it
into a csv file

Args:
    -
Returns:
    -
```

Definition at line 76 of file a_author_Information.py.

Variable Documentation

string a_author_Information.argument_db_to_choose = ""

Definition at line 177 of file a_author_Information.py.

a_author_Information.mongo_db_author_collection = None

Definition at line 169 of file a_author_Information.py.

int a_author_Information.mongo_db_author_collection_original = 0

Definition at line 173 of file a_author_Information.py.

a_author_Information.mongo_db_author_instance = None

Definition at line 166 of file a_author_Information.py.

a_author_Information.mongo_db_client_instance = None

Definition at line 163 of file a_author_Information.py.

a_iAMA_Commenttime_arr Namespace Reference

Functions

- def check_script_arguments ()
- def initialize_mongo_db_parameters (actually_processed_year)
- def start_data_generation_for_analysis ()
- def prepare_data_for_graph ()
- def add_thread_list_to_global_list (list_to_append)
- def generate_data_to_be_analyzed ()
- def calculate_ar_mean_answer_time_for_questions (id_of_thread, author_of_thread)
- def check_if_comment_is_a_question (given_string)
- def check_if_comment_is_on_tier_1 (comment_parent_id)
- def check_if_comment_is_not_from_thread_author (author_of_thread, comment_author)
- def check_if_comment_is_answer_from_thread_author (author_of_thread, comment_actual_id, comments_cursor)
- def calculate_time_difference (comment_time_stamp, answer_time_stamp_iama_host)
- def write_csv_data (list_with_information)
- def plot_generated_data ()

Variables

- int argument_year_beginning = 0
- int year_actually_in_progress = 0
- int argument_year_ending = 0
- string argument_tier_in_scope = ""
- string argument_plot_time_unit = ""
- mongo_DB_Client_Instance = None
- mongo_DB_Threads_Instance = None
- mongo_DB_Thread_Collection = None
- mongo_DB_Comments_Instance = None
- list list_To_Be_Plotted = []
- list global_thread_list = []
- list data_to_give_plotly = []

Function Documentation

def a_iAMA_Commenttime_arr.add_thread_list_to_global_list (*list_to_append*)

```
Adds all elements of for the current year into a global list. This global list will be written into
a csv file
later on

1. This method simply checks wether both strings match each other or not.
    I have built this extra method to have a better overview in the main code..

Args:
    list_to_append (list) : The list which will be iterated over and which elements will be added
to the global list
Returns:
    -
```

Definition at line 248 of file a_iAMA_Commenttime_arr.py.

def a_iAMA_Commenttime_arr.calculate_ar_mean_answer_time_for_questions (*id_of_thread*, *author_of_thread*)

```
Calculates the arithmetic mean of the answer time by the iama host in minutes

In dependence of the given tier argument (second argument) the processing of tiers will be filtered

Args:
    id_of_thread (str): The id of the thread which is actually processed. (Necessary for checking
if a question
        lies on tier 1 or any other tier)
    author_of_thread (str): The name of the thread author. (Necessary for checking if a given answer
is from the
        iama host or not)
Returns:
    Whenever there was a minimum of 1 question asked and 1 answer from the iama host:
        amount of answer times (int) : The amount of the arithmetic mean time of
    Whenever there no questions have been asked for that thread / or no answers were given /
        or all values in the database were null:
        None:   Returns an empty object of the type None
```

Definition at line 315 of file a_iAMA_Commenttime_arr.py.

def a_iAMA_Commenttime_arr.calculate_time_difference (*comment_time_stamp*, *answer_time_stamp_iama_host*)

```
Calculates the time difference in seconds between the a comment and its answer from the iama host

1. The time stamps will be converted from epoch
    into float and afterwards into str again
    (necessary for correct subtraction)
2. Then the time stamps will be subtracted from each other
3. The containing time difference will be converted into seconds (int)

Args:
    comment_time_stamp (str): The time stamp of the comment
    answer_time_stamp_iama_host (str): The time stamp of the iAMA hosts answer
Returns:
    time difference in seconds (int) : The time difference of the comment and its answer by the
iAMA host in seconds
```

Definition at line 593 of file a_iAMA_Commenttime_arr.py.

def a_iAMA_Commenttime_arr.check_if_comment_is_a_question (*given_string*)

```
Simply checks whether a given string is a question or not

1. This method simply checks wether a question mark exists within that string or not..
    This is just that simple because messing around with natural processing kits to determine the
semantic sense
    would blow up my bachelor work...

Args:
    given_string (int) : The string which will be checked for a question mark
Returns:
    True (bool): Whenever the given string is a question
```

False (bool): Whenever the given string is not a question

Definition at line 491 of file a_iAMA_Commenttime_arr.py.

def a_iAMA_Commenttime_arr.check_if_comment_is_answer_from_thread_author (*author_of_thread*, *comment_actual_id*, *comments_cursor*)

```
Checks whether both strings are equal or not

1. A dictionary containing flags whether that a question is answered by the host with the appropriate
timestamp will
    be created in the beginning.
2. Then the method iterates over every comment within that thread
    1.1. Whenever an answer is from the iAMA hosts and the processed comments 'parent_id' matches
the iAMA hosts
        comments (answers) id, the returned dict will contain appropriate values and will be
returned
    1.2. If this is not the case, it will be returned in its default condition

Args:
    author of thread (str) : The name of the thread author (iAMA-Host)
    comment actual id (str) : The id of the actually processed comment
    comments cursor (list) : The cursor which shows to the amount of comments which can be iterated
Returns:
    True (bool): Whenever the strings do not match
    False (bool): Whenever the strings do match
     answered that given question)
```

Definition at line 548 of file a_iAMA_Commenttime_arr.py.

def a_iAMA_Commenttime_arr.check_if_comment_is_not_from_thread_author (*author_of_thread*, *comment_author*)

```
Checks whether both strings are equal or not

1. This method simply checks wether both strings match each other or not.
    I have built this extra method to have a better overview in the main code..

Args:
    author_of_thread (str) : The name of the thread author (iAMA-Host)
    comment_author (str) : The name of the comments author
Returns:
    True (bool): Whenever the strings do not match
    False (bool): Whenever the strings do match
     answered that given question)
```

Definition at line 528 of file a_iAMA_Commenttime_arr.py.

def a_iAMA_Commenttime_arr.check_if_comment_is_on_tier_1 (*comment_parent_id*)

```
Checks whether a comment relies on the first tier or any other tier

Args:
    comment parent id (str) : The name id of the comments parent
Returns:
    True (bool): Whenever the comment lies on tier 1
    False (bool): Whenever the comment lies on any other tier
```

Definition at line 512 of file a_iAMA_Commenttime_arr.py.

def a_iAMA_Commenttime_arr.check_script_arguments ()

```
Checks if enough and correct arguments have been given to run this script adequate
```

```
1. It checks in the first instance if enough arguments have been given
2. Then necessary variables will be filled with appropriate values

Args:
    -
Returns:
    -
```

Definition at line 20 of file a_iAMA_Commenttime_arr.py.

def a_iAMA_Commenttime_arr.generate_data_to_be_analyzed ()

```
Generates the data which will be analyzed

1. This method iterates over every thread
    1.1. It filters if that iterated thread is an iAMA-request or not
        1.1.1. If yes: this thread gets skipped and the next one will be processed
        1.1.2. If no: this thread will be processed
2. If the thread gets processed it will receive the arithmetic mean of answer time
3. This value will be added to a global list and will be plotted later on

Args:
    -
Returns:
    -
```

Definition at line 267 of file a_iAMA_Commenttime_arr.py.

def a_iAMA_Commenttime_arr.initialize_mongo_db_parameters (*actually_processed_year*)

```
Instantiates all necessary variables for the correct usage of the mongoDB-Client

Args:
    actually_processed_year (int) : The year with which parameters the database should be accessed
Returns:
    -
```

Definition at line 47 of file a_iAMA_Commenttime_arr.py.

def a_iAMA_Commenttime_arr.plot_generated_data ()

```
Plots the data which is to be generated

1. This method plots the data which has been calculated before by using Pltoly-Framework within
a self written class

Args:
    -
Returns:
    -
```

Definition at line 691 of file a_iAMA_Commenttime_arr.py.

def a_iAMA_Commenttime_arr.prepare_data_for_graph ()

```
Sorts and prepares data for graph plotting

Args:
    -
```

```
Returns:
    -
```

Definition at line 147 of file a_iAMA_Commenttime_arr.py.

def a_iAMA_Commenttime_arr.start_data_generation_for_analysis ()

```
Starts the data processing by swichting through the years

1. Triggers the data generation process and moves forward within the years
    1.1. By moving through the years a csv file will be created for every year
    1.2. Additionally an interactive chart will be plotted

Args:
    -
Returns:
    -
```

Definition at line 67 of file a_iAMA_Commenttime_arr.py.

def a_iAMA_Commenttime_arr.write_csv_data (*list_with_information*)

```
Creates a csv file containing all necessary information about the average comment time of the iama
host

Args:
    list with information (list) : Contains various information about thread and comment time
Returns:
    -
```

Definition at line 632 of file a_iAMA_Commenttime_arr.py.

Variable Documentation

string a_iAMA_Commenttime_arr.argument_plot_time_unit = ""

Definition at line 720 of file a_iAMA_Commenttime_arr.py.

string a_iAMA_Commenttime_arr.argument_tier_in_scope = ""

Definition at line 717 of file a_iAMA_Commenttime_arr.py.

int a_iAMA_Commenttime_arr.argument_year_beginning = 0

Definition at line 708 of file a_iAMA_Commenttime_arr.py.

int a_iAMA_Commenttime_arr.argument_year_ending = 0

Definition at line 714 of file a_iAMA_Commenttime_arr.py.

list a_iAMA_Commenttime_arr.data_to_give_plotly = []

Definition at line 752 of file a_iAMA_Commenttime_arr.py.

list a_iAMA_Commenttime_arr.global_thread_list = []

Definition at line 738 of file a_iAMA_Commenttime_arr.py.

list a_iAMA_Commenttime_arr.list_To_Be_Plotted = []

Definition at line 735 of file a_iAMA_Commenttime_arr.py.

a_iAMA_Commenttime_arr.mongo_DB_Client_Instance = None

Definition at line 723 of file a_iAMA_Commenttime_arr.py.

a_iAMA_Commenttime_arr.mongo_DB_Comments_Instance = None

Definition at line 732 of file a_iAMA_Commenttime_arr.py.

a_iAMA_Commenttime_arr.mongo_DB_Thread_Collection = None

Definition at line 729 of file a_iAMA_Commenttime_arr.py.

a_iAMA_Commenttime_arr.mongo_DB_Threads_Instance = None

Definition at line 726 of file a_iAMA_Commenttime_arr.py.

int a_iAMA_Commenttime_arr.year_actually_in_progress = 0

Definition at line 711 of file a_iAMA_Commenttime_arr.py.

a_iAMA_Commenttime_med Namespace Reference

Functions

- def check_script_arguments ()
- def initialize_mongo_db_parameters (actually_processed_year)
- def start_data_generation_for_analysis ()
- def prepare_data_for_graph ()
- def add_thread_list_to_global_list (list_to_append)
- def generate_data_to_be_analyzed ()
- def calculate_ar_mean_answer_time_for_questions (id_of_thread, author_of_thread)
- def check_if_comment_is_a_question (given_string)
- def check_if_comment_is_on_tier_1 (comment_parent_id)
- def check_if_comment_is_not_from_thread_author (author_of_thread, comment_author)
- def check_if_comment_is_answer_from_thread_author (author_of_thread, comment_actual_id, comments_cursor)
- def calculate_time_difference (comment_time_stamp, answer_time_stamp_iama_host)
- def write_csv_data (list_with_information)
- def plot_generated_data ()

Variables

- int argument_year_beginning = 0
- int year_actually_in_progress = 0
- int argument_year_ending = 0
- string argument_tier_in_scope = ""
- string argument_plot_time_unit = ""
- mongo_DB_Client_Instance = None
- mongo_DB_Threads_Instance = None
- mongo_DB_Thread_Collection = None
- mongo_DB_Comments_Instance = None
- list list_To_Be_Plotted = []
- list global_thread_list = []
- list data_to_give_plotly = []

Function Documentation

def a_iAMA_Commenttime_med.add_thread_list_to_global_list (*list_to_append*)

```
Adds all elements of for the current year into a global list. This global list will be written into
a csv file
later on

1. This method simply checks wether both strings match each other or not.
    I have built this extra method to have a better overview in the main code..

Args:
    list_to_append (list) : The list which will be iterated over and which elements will be added
to the global list
Returns:
    -
```

Definition at line 248 of file a_iAMA_Commenttime_med.py.

def a_iAMA_Commenttime_med.calculate_ar_mean_answer_time_for_questions (*id_of_thread*, *author_of_thread*)

```
Calculates the arithmetic mean of the answer time by the iama host in minutes

In dependence of the given tier argument (second argument) the processing of tiers will be filtered

Args:
    id_of_thread (str): The id of the thread which is actually processed. (Necessary for checking
if a question
        lies on tier 1 or any other tier)
    author_of_thread (str): The name of the thread author. (Necessary for checking if a given answer
is from the
        iama host or not)
Returns:
    Whenever there was a minimum of 1 question asked and 1 answer from the iama host:
        amount of answer times (int) : The amount of the arithmetic mean time of
    Whenever there no questions have been asked for that thread / or no answers were given /
        or all values in the database were null:
        None:   Returns an empty object of the type None
```

Definition at line 315 of file a_iAMA_Commenttime_med.py.

def a_iAMA_Commenttime_med.calculate_time_difference (*comment_time_stamp*, *answer_time_stamp_iama_host*)

```
Calculates the time difference in seconds between the a comment and its answer from the iama host

1. The time stamps will be converted from epoch
    into float and afterwards into str again
    (necessary for correct subtraction)
2. Then the time stamps will be subtracted from each other
3. The containing time difference will be converted into seconds (int)

Args:
    comment_time_stamp (str): The time stamp of the comment
    answer_time_stamp_iama_host (str): The time stamp of the iAMA hosts answer
Returns:
    time difference in seconds (int) : The time difference of the comment and its answer by the
iAMA host in seconds
```

Definition at line 593 of file a_iAMA_Commenttime_med.py.

def a_iAMA_Commenttime_med.check_if_comment_is_a_question (*given_string*)

```
Simply checks whether a given string is a question or not

1. This method simply checks wether a question mark exists within that string or not..
    This is just that simple because messing around with natural processing kits to determine the
semantic sense
    would blow up my bachelor work...

Args:
    given_string (int) : The string which will be checked for a question mark
Returns:
    True (bool): Whenever the given string is a question
```

False (bool): Whenever the given string is not a question

Definition at line 491 of file a_iAMA_Commenttime_med.py.

def a_iAMA_Commenttime_med.check_if_comment_is_answer_from_thread_author (*author_of_thread*, *comment_actual_id*, *comments_cursor*)

```
Checks whether both strings are equal or not

1. A dictionary containing flags whether that a question is answered by the host with the appropriate
timestamp will
    be created in the beginning.
2. Then the method iterates over every comment within that thread
    1.1. Whenever an answer is from the iAMA hosts and the processed comments 'parent_id' matches
the iAMA hosts
        comments (answers) id, the returned dict will contain appropriate values and will be
returned
    1.2. If this is not the case, it will be returned in its default condition

Args:
    author of thread (str) : The name of the thread author (iAMA-Host)
    comment actual id (str) : The id of the actually processed comment
    comments cursor (list) : The cursor which shows to the amount of comments which can be iterated
Returns:
    True (bool): Whenever the strings do not match
    False (bool): Whenever the strings do match
     answered that given question)
```

Definition at line 548 of file a_iAMA_Commenttime_med.py.

def a_iAMA_Commenttime_med.check_if_comment_is_not_from_thread_author (*author_of_thread*, *comment_author*)

```
Checks whether both strings are equal or not

1. This method simply checks wether both strings match each other or not.
    I have built this extra method to have a better overview in the main code..

Args:
    author_of_thread (str) : The name of the thread author (iAMA-Host)
    comment_author (str) : The name of the comments author
Returns:
    True (bool): Whenever the strings do not match
    False (bool): Whenever the strings do match
     answered that given question)
```

Definition at line 528 of file a_iAMA_Commenttime_med.py.

def a_iAMA_Commenttime_med.check_if_comment_is_on_tier_1 (*comment_parent_id*)

```
Checks whether a comment relies on the first tier or any other tier

Args:
    comment parent id (str) : The name id of the comments parent
Returns:
    True (bool): Whenever the comment lies on tier 1
    False (bool): Whenever the comment lies on any other tier
```

Definition at line 512 of file a_iAMA_Commenttime_med.py.

def a_iAMA_Commenttime_med.check_script_arguments ()

```
Checks if enough and correct arguments have been given to run this script adequate
```

```
1. It checks in the first instance if enough arguments have been given
2. Then necessary variables will be filled with appropriate values

Args:
    -
Returns:
    -
```

Definition at line 20 of file a_iAMA_Commenttime_med.py.

def a_iAMA_Commenttime_med.generate_data_to_be_analyzed ()

```
Generates the data which will be analyzed

1. This method iterates over every thread
    1.1. It filters if that iterated thread is an iAMA-request or not
        1.1.1. If yes: this thread gets skipped and the next one will be processed
        1.1.2. If no: this thread will be processed
2. If the thread gets processed it will receive the arithmetic mean of answer time
3. This value will be added to a global list and will be plotted later on

Args:
    -
Returns:
    -
```

Definition at line 267 of file a_iAMA_Commenttime_med.py.

def a_iAMA_Commenttime_med.initialize_mongo_db_parameters (*actually_processed_year*)

```
Instantiates all necessary variables for the correct usage of the mongoDB-Client

Args:
    actually_processed_year (int) : The year with which parameters the database should be accessed
Returns:
    -
```

Definition at line 47 of file a_iAMA_Commenttime_med.py.

def a_iAMA_Commenttime_med.plot_generated_data ()

```
Plots the data which is to be generated

1. This method plots the data which has been calculated before by using Pltoly-Framework within
a self written class

Args:
    -
Returns:
    -
```

Definition at line 691 of file a_iAMA_Commenttime_med.py.

def a_iAMA_Commenttime_med.prepare_data_for_graph ()

```
Sorts and prepares data for graph plotting

Args:
    -
```

```
Returns:
    -
```

Definition at line 147 of file a_iAMA_Commenttime_med.py.

def a_iAMA_Commenttime_med.start_data_generation_for_analysis ()

```
Starts the data processing by swichting through the years

1. Triggers the data generation process and moves forward within the years
    1.1. By moving through the years a csv file will be created for every year
    1.2. Additionally an interactive chart will be plotted

Args:
    -
Returns:
    -
```

Definition at line 67 of file a_iAMA_Commenttime_med.py.

def a_iAMA_Commenttime_med.write_csv_data (*list_with_information*)

```
Creates a csv file containing all necessary information about the average comment time of the iama
host

Args:
    list with information (list) : Contains various information about thread and comment time
Returns:
    -
```

Definition at line 632 of file a_iAMA_Commenttime_med.py.

Variable Documentation

string a_iAMA_Commenttime_med.argument_plot_time_unit = ""

Definition at line 720 of file a_iAMA_Commenttime_med.py.

string a_iAMA_Commenttime_med.argument_tier_in_scope = ""

Definition at line 717 of file a_iAMA_Commenttime_med.py.

int a_iAMA_Commenttime_med.argument_year_beginning = 0

Definition at line 708 of file a_iAMA_Commenttime_med.py.

int a_iAMA_Commenttime_med.argument_year_ending = 0

Definition at line 714 of file a_iAMA_Commenttime_med.py.

list a_iAMA_Commenttime_med.data_to_give_plotly = []

Definition at line 752 of file a_iAMA_Commenttime_med.py.

list a_iAMA_Commenttime_med.global_thread_list = []

Definition at line 738 of file a_iAMA_Commenttime_med.py.

list a_iAMA_Commenttime_med.list_To_Be_Plotted = []

Definition at line 735 of file a_iAMA_Commenttime_med.py.

a_iAMA_Commenttime_med.mongo_DB_Client_Instance = None

Definition at line 723 of file a_iAMA_Commenttime_med.py.

a_iAMA_Commenttime_med.mongo_DB_Comments_Instance = None

Definition at line 732 of file a_iAMA_Commenttime_med.py.

a_iAMA_Commenttime_med.mongo_DB_Thread_Collection = None

Definition at line 729 of file a_iAMA_Commenttime_med.py.

a_iAMA_Commenttime_med.mongo_DB_Threads_Instance = None

Definition at line 726 of file a_iAMA_Commenttime_med.py.

int a_iAMA_Commenttime_med.year_actually_in_progress = 0

Definition at line 711 of file a_iAMA_Commenttime_med.py.

a_question_Answered_Yes_No_Extrema Namespace Reference

Functions

- def check_script_arguments ()
- def initialize_mongo_db_parameters (actually_processed_year)
- def start_data_generation_for_analysis ()
- def generate_data_now ()
- def process_answered_questions_within_thread (id_of_thread, author_of_thread, thread_creation_date)
- def check_if_comment_is_a_question (given_string)
- def check_if_comment_is_not_from_thread_author (author_of_thread, comment_author)
- def check_if_comment_has_been_answered_by_thread_author (author_of_thread, comment_acutal_id, comments_cursor)
- def calculate_time_difference (comment_time_stamp, answer_time_stamp_iama_host)
- def sort_questions (list_which_is_to_be_sorted)
- def create_question_list_containing_all_years (list_with_comments_per_years)
- def write_csv_and_count_unanswered (list_with_comments)
- def plot_generated_data ()

Variables

- int argument_year_beginning = 0
- int year_actually_in_progress = 0
- int argument_year_ending = 0
- argument_sorting = bool
- int argument_amount_of_top_quotes = 0
- mongo_DB_Client_Instance = None
- mongo_DB_Threads_Instance = None
- mongo_DB_Thread_Collection = None
- mongo_DB_Comments_Instance = None
- list question_information_list = []
- list data_to_give_plotly = []

Function Documentation

def a_question_Answered_Yes_No_Extrema.calculate_time_difference (*comment_time_stamp*, *answer_time_stamp_iama_host*)

```
Calculates the time difference in seconds between the a comment and its answer from the iama host

1. The time stamps will be converted from epoch
    into float and afterwards into str again
    (necessary for correct subtraction)
2. Then the time stamps will be subtracted from each other
3. The containing time difference will be converted into seconds (int)

Args:
    comment_time_stamp (str): The time stamp of the comment
    answer_time_stamp_iama_host (str): The time stamp of the iAMA hosts answer
Returns:
    time difference in seconds (int) : The time difference of the comment and its answer by the
iAMA host in seconds
```

Definition at line 425 of file a_question_Answered_Yes_No_Extrema.py.

def a_question_Answered_Yes_No_Extrema.check_if_comment_has_been_answered_by_thread_author (*author_of_thread*, *comment_acutal_id*, *comments_cursor*)

```
Checks whether both strings are equal or not

1. A dictionary containing flags whether that a question is answered by the host with the appropriate
timestamp will
    be created in the beginning.
2. Then the method iterates over every comment within that thread
    1.1. Whenever an answer is from the iAMA hosts and the processed comments 'parent id' matches
the iAMA hosts
        comments (answers) id, the returned dict will contain appropriate values and will be
returned
    1.2. If this is not the case, it will be returned in its default condition

Args:
    author_of_thread (str) : The name of the thread author (iAMA-Host)
    comment_acutal_id (str) : The id of the actually processed comment
    comments cursor (list) : The cursor which shows to the amount of comments which can be iterated
Returns:
    True (bool): Whenever the strings do not match
    False (bool): Whenever the strings do match
     answered that given question)
```

Definition at line 381 of file a_question_Answered_Yes_No_Extrema.py.

def a_question_Answered_Yes_No_Extrema.check_if_comment_is_a_question (*given_string*)

```
Simply checks whether a given string is a question or not

1. This method simply checks wether a question mark exists within that string or not..
    This is just that simple because messing around with natural processing kits to determine the
semantic sense
    would blow up my bachelor work...

Args:
    given_string (str) : The string which will be checked for a question mark
Returns:
    True (bool): Whenever the given string is a question
```

False (bool): Whenever the given string is not a question

Definition at line 340 of file a_question_Answered_Yes_No_Extrema.py.

def a_question_Answered_Yes_No_Extrema.check_if_comment_is_not_from_thread_author (*author_of_thread*, *comment_author*)

```
Checks whether both strings are equal or not

1. This method simply checks wether both strings match each other or not.
    I have built this extra method to have a better overview in the main code..

Args:
    author of thread (str) : The name of the thread author (iAMA-Host)
    comment_author (str) : The name of the comments author
Returns:
    True (bool): Whenever the strings do not match
    False (bool): Whenever the strings do match
     answered that given question)
```

Definition at line 361 of file a_question_Answered_Yes_No_Extrema.py.

def a_question_Answered_Yes_No_Extrema.check_script_arguments ()

```
Checks if enough and correct arguments have been given to run this script adequate

1. It checks in the first instance if enough arguments have been given
2. Then necessary variables will be filled with appropriate values

Args:
    -
Returns:
    -
```

Definition at line 22 of file a_question_Answered_Yes_No_Extrema.py.

def a_question_Answered_Yes_No_Extrema.create_question_list_containing_all_years (*list_with_comments_per_years*)

```
Creates a list, containing all questions from all years

Args:
    list_with_comments_per_years (list) : The list containing the current years questions
Returns:
    -
```

Definition at line 494 of file a_question_Answered_Yes_No_Extrema.py.

def a_question_Answered_Yes_No_Extrema.generate_data_now ()

```
Generates the data which will be written into csv and plotted later on

1. This method iterates over every thread
    1.1. It filters if that iterated thread is an iAMA-request or not
        1.1.1. If yes: this thread gets skipped and the next one will be processed
        1.1.2. If no: this thread will be processed
2. If the thread gets processed it will receive an ordered dictionary containing information about
every question
    whether it has been answered or not
3. This ordered dictionary will be appended to a global list, which will be processed afterwards
for the generation
    of plots and csv files

Args:
    -
Returns:
    -
```

Definition at line 165 of file a_question_Answered_Yes_No_Extrema.py.

def a_question_Answered_Yes_No_Extrema.initialize_mongo_db_parameters (*actually_processed_year*)

```
Instantiates all necessary variables for the correct usage of the mongoDB client

Args:
    actually_processed_year (int) : The year with which parameters the database should be accessed
Returns:
    -
```

Definition at line 59 of file a_question_Answered_Yes_No_Extrema.py.

def a_question_Answered_Yes_No_Extrema.plot_generated_data ()

```
Plots the data which is to be generated

1. This method plots the data which has been calculated before by using Pltoly-Framework within
a self written class

Args:
    -
Returns:
    -
```

Definition at line 583 of file a_question_Answered_Yes_No_Extrema.py.

def a_question_Answered_Yes_No_Extrema.process_answered_questions_within_thread (*id_of_thread*, *author_of_thread*, *thread_creation_date*)

```
Checks whether an iterated question has been answered by the iama host or not

1. This method checks at first whether an iterated comment contains values (e.g. is not none)
    1.1. If not: That comment will be skipped / if no comment is remaining None will be returned
    1.2. If yes: That comment will be processed
2. Now it will be checked whether that iterated comment is a question or not
3. Afterwards it will be checked wether that comment is a comment from the iAMA Host or not
    3.1. If this is not the case the next comment will be processed
4. Whenever that processed comment is a question and not (!!) from the thread author:
    amount_of_tier_any_questions (int) will be increased by one
5. Now it will be checked whether that comment has a comment ( answer ) below it which is from the
iAMA-host
    5.1. If yes: amount of tier any questions answered (int) will be increased by one and the
dictionary, which
        is to be returned will be filled with values
    5.2. If no: the dictionary, which is to be returned will be filled with values

Args:
    id_of_thread (str) : Contains the id of the thread which is to be iterated
    author of thread (str) : Contains the name of the thread author
    thread_creation_date (str): Contains the time
Returns:
    amount_of_questions_not_answered (int) : The amount of questions which have not been answered
```

Definition at line 217 of file a_question_Answered_Yes_No_Extrema.py.

def a_question_Answered_Yes_No_Extrema.sort_questions (*list_which_is_to_be_sorted*)

```
Sorts a list of questions for a year, depending on the upvotes

1. This method prepares the data, in kind of sorting and counting amount of questions not being
answered
2. It also returns the number of unanswered questions, necessary for chart plotting

Args:
    list_which_is_to_be_sorted (list) : The list you want to sort regarding the sorting arguments
give on execution
Returns:
    questions_sorted (list) : The amount of questions, sorted on upvotes
```

Definition at line 462 of file a_question_Answered_Yes_No_Extrema.py.

def a_question_Answered_Yes_No_Extrema.start_data_generation_for_analysis ()

```
Starts the data processing by swichting through the years

1. Triggers the data generation process and moves forward within the years
    1.1. By moving through the years a csv file will be created for every year
    1.2. At the end a csv file will be generated containing all questions of all years, sorted
    1.3. Additionally an interactive chart will be plotted

Args:
    -
Returns:
    -
```

Definition at line 79 of file a_question_Answered_Yes_No_Extrema.py.

def a_question_Answered_Yes_No_Extrema.write_csv_and_count_unanswered (*list_with_comments*)

```
Creates a csv file containing all necessary information and calculates the amount of unanswered
questions

1. This method iterates over the top / worst X comments
    1.1. By iterating: all necessary information will be written into the csv file
    1.2. By iterating: the amount of unanswered questions will be counted
2. After iterating the amount of unanswered questions will be returned, which is necessary for graph
plotting

Args:
    list_with_comments (list): Contains all comments from the year
Returns:
    amount_of_questions_not_answered (int) : The amount of questions which have not been answered
```

Definition at line 516 of file a_question_Answered_Yes_No_Extrema.py.

Variable Documentation

int a_question_Answered_Yes_No_Extrema.argument_amount_of_top_quotes = 0

Definition at line 613 of file a_question_Answered_Yes_No_Extrema.py.

a_question_Answered_Yes_No_Extrema.argument_sorting = bool

Definition at line 610 of file a_question_Answered_Yes_No_Extrema.py.

int a_question_Answered_Yes_No_Extrema.argument_year_beginning = 0

Definition at line 600 of file a_question_Answered_Yes_No_Extrema.py.

int a_question_Answered_Yes_No_Extrema.argument_year_ending = 0

Definition at line 606 of file a_question_Answered_Yes_No_Extrema.py.

list a_question_Answered_Yes_No_Extrema.data_to_give_plotly = []

Definition at line 642 of file a_question_Answered_Yes_No_Extrema.py.

a_question_Answered_Yes_No_Extrema.mongo_DB_Client_Instance = None

Definition at line 617 of file a_question_Answered_Yes_No_Extrema.py.

a_question_Answered_Yes_No_Extrema.mongo_DB_Comments_Instance = None

Definition at line 626 of file a_question_Answered_Yes_No_Extrema.py.

a_question_Answered_Yes_No_Extrema.mongo_DB_Thread_Collection = None

Definition at line 623 of file a_question_Answered_Yes_No_Extrema.py.

a_question_Answered_Yes_No_Extrema.mongo_DB_Threads_Instance = None

Definition at line 620 of file a_question_Answered_Yes_No_Extrema.py.

list a_question_Answered_Yes_No_Extrema.question_information_list = []

Definition at line 630 of file a_question_Answered_Yes_No_Extrema.py.

int a_question_Answered_Yes_No_Extrema.year_actually_in_progress = 0

Definition at line 603 of file a_question_Answered_Yes_No_Extrema.py.

a_question_Answered_Yes_No_Tier_Percentage Namespace Reference

Functions

- def check_script_arguments ()
- def initialize_mongo_db_parameters (actually_processed_year)
- def start_data_generation_for_analysis ()
- def generate_data_to_be_analyzed ()
- def question_answering_distribution_tier1_tierx_tierany (id_of_thread, author_of_thread)
- def check_if_comment_is_a_question (given_string)
- def check_if_comment_is_on_tier_1 (comment_parent_id)
- def check_if_comment_is_not_from_thread_author (author_of_thread, comment_author)
- def check_if_comment_is_answer_from_thread_author (author_of_thread, comment_actual_id, comments_cursor)
- def write_csv (list_with_information)
- def add_local_list_to_global_list (list_to_append)
- def prepare_data_for_graph ()
- def plot_generated_data ()

Variables

- int argument_year_beginning = 0
- int year_actually_in_progress = 0
- int argument_year_ending = 0
- string argument_tier_in_scope = ""
- mongo_DB_Client_Instance = None
- mongo_DB_Threads_Instance = None
- mongo_DB_Thread_Collection = None
- mongo_DB_Comments_Instance = None
- list global_question_list = []
- list year_question_list = []
- list data_to_give_plotly = []

Function Documentation

def a_question_Answered_Yes_No_Tier_Percentage.add_local_list_to_global_list (*list_to_append*)

```
Adds all elements of for the current year into a global list. This global list will be written into
a csv file
later on

1. This method simply checks wether both strings match each other or not.
    I have built this extra method to have a better overview in the main code..

Args:
    list_to_append (list) : The list which will be iterated over and which elements will be added
to the global list
Returns:
    -
```

Definition at line 483 of file a_question_Answered_Yes_No_Tier_Percentage.py.

def a_question_Answered_Yes_No_Tier_Percentage.check_if_comment_is_a_question (*given_string*)

```
Simply checks whether a given string is a question or not

1. This method simply checks whether a question mark exists within that string or not..
    This is just that simple because messing around with natural processing kits to determine the
semantic sense
    would blow up my bachelor work...

Args:
    given_string (str) : The string which will be checked for a question mark
Returns:
    True (bool): Whenever the given string is a question
```

False (bool): Whenever the given string is not a question

Definition at line 326 of file a_question_Answered_Yes_No_Tier_Percentage.py.

def a_question_Answered_Yes_No_Tier_Percentage.check_if_comment_is_answer_from_thread_author (*author_of_thread*, *comment_actual_id*, *comments_cursor*)

```
Iterates over ewery comment, while compraing the ids and the comments creation author

1. the method iterates over every comment within that thread
    1.1. Whenever an answer is from the iAMA hosts and the processed comments 'parent id' matches
the iAMA hosts
        comments (answers) id, the returned dict will contain appropriate values and will be
returned
    1.2. If this is not the case, it will be returned in its default condition

Args:
    author_of_thread (str) : The name of the thread author (iAMA-Host)
    comment_actual_id:  (str) : The id of the actually processed comment
    comments_cursor (Cursor) : The cursor which shows to the amount of comments which can be iterated
Returns:
    True (bool): Whenever the strings do not match
    False (bool): Whenever the strings do match
```

Definition at line 386 of file a_question_Answered_Yes_No_Tier_Percentage.py.

def a_question_Answered_Yes_No_Tier_Percentage.check_if_comment_is_not_from_thread_author (*author_of_thread*, *comment_author*)

```
Checks whether both strings are equal or not

1. This method simply checks wether both strings match each other or not.
    I have built this extra method to have a better overview in the main code..

Args:
    author_of_thread (str) : The name of the thread author (iAMA-Host)
    comment_author (str) : The name of the comments author
Returns:
    True (bool): Whenever the strings do not match
    False (bool): Whenever the strings do match
     answered that given question)
```

Definition at line 365 of file a_question_Answered_Yes_No_Tier_Percentage.py.

def a_question_Answered_Yes_No_Tier_Percentage.check_if_comment_is_on_tier_1 (*comment_parent_id*)

```
Simply checks whether a given string is a question posted on tier 1 or not

1. This method simply checks whether a question has been posted on tier 1 by looking whether the
given
    string contains the substring "t3_" or not

Args:
    comment parent id (str): The string which will be checked for "t3 " appearance in it
Returns:
    -
```

Definition at line 347 of file a_question_Answered_Yes_No_Tier_Percentage.py.

def a_question_Answered_Yes_No_Tier_Percentage.check_script_arguments ()

```
Checks if enough and correct arguments have been given to run this script adequate

1. It checks in the first instance if enough arguments have been given
2. Then necessary variables will be filled with appropriate values

Args:
    -
Returns:
    -
```

Definition at line 20 of file a_question_Answered_Yes_No_Tier_Percentage.py.

def a_question_Answered_Yes_No_Tier_Percentage.generate_data_to_be_analyzed ()

```
Generates the data which will be analyzed

1. This method iterates over every thread
    1.1. It filters if that iterated thread is an iAMA-request or not
        1.1.1. If yes: this thread gets skipped and the next one will be processed
        1.1.2. If no: this thread will be processed
2. If the thread gets processed it will receive the distribution of questions on the tiers
3. This value will be added to a global list and will be plotted later on

Args:
    -
Returns:
    -
```

Definition at line 141 of file a_question_Answered_Yes_No_Tier_Percentage.py.

def a_question_Answered_Yes_No_Tier_Percentage.initialize_mongo_db_parameters (*actually_processed_year*)

```
Instantiates all necessary variables for the correct usage of the mongoDB-Client

Args:
    actually_processed_year (int) : The year with which parameters the database should be accessed
Returns:
    -
```

Definition at line 45 of file a_question_Answered_Yes_No_Tier_Percentage.py.

def a_question_Answered_Yes_No_Tier_Percentage.plot_generated_data ()

```
Plots the data which is to be generated

1. This method plots the data which has been calculated before by using Pltoly-Framework within
a self written class

Args:
    -
Returns:
    -
```

Definition at line 528 of file a_question_Answered_Yes_No_Tier_Percentage.py.

def a_question_Answered_Yes_No_Tier_Percentage.prepare_data_for_graph ()

```
Sorts and prepares data for graph plotting

Args:
    -
Returns:
    -
```

Definition at line 502 of file a_question_Answered_Yes_No_Tier_Percentage.py.

def a_question_Answered_Yes_No_Tier_Percentage.question_answering_distribution_tier1_tierx_tier any (*id_of_thread*, *author_of_thread*)

```
Generates the data which will be analyzed

1. It iterates over every comment and
     1.1. checks if the iterated comment is a question
     1.2. checks if the iterated comment has been posted on tier 1 level
     1.3. checks if that comment is from the iAMA-Host himself or not

2. Now the posted question will be added to a global list, which will be used for csv writing and
chart generation
    later on

Args:
    id_of_thread (str) : Contains the id of the processed thread
    author_of_thread (str) : Contains the iAMA-Hosts name
Returns:
```

    -

Definition at line 184 of file a_question_Answered_Yes_No_Tier_Percentage.py.

def a_question_Answered_Yes_No_Tier_Percentage.start_data_generation_for_analysis ()

```
Starts the data processing by swichting through the years

1. Triggers the data generation process and moves forward within the years
    1.1. By moving through the years a csv file will be created for every year
    1.2. Additionally an interactive chart will be plotted

Args:
    -
Returns:
    -
```

Definition at line 65 of file a_question_Answered_Yes_No_Tier_Percentage.py.

def a_question_Answered_Yes_No_Tier_Percentage.write_csv (*list_with_information*)

```
Creates a csv file containing all necessary information about the distribution of questions on the
tiers

This method iterates over the the given list, which contains every single questions of that year
(or all years)
and writes a csv file containing misc information about those questions.

Args:
    list_with_information (list) : Contains various information about thread and comment time
Returns:
    -
```

Definition at line 417 of file a_question_Answered_Yes_No_Tier_Percentage.py.

Variable Documentation

string a_question_Answered_Yes_No_Tier_Percentage.argument_tier_in_scope = ""

Definition at line 556 of file a_question_Answered_Yes_No_Tier_Percentage.py.

int a_question_Answered_Yes_No_Tier_Percentage.argument_year_beginning = 0

Definition at line 547 of file a_question_Answered_Yes_No_Tier_Percentage.py.

int a_question_Answered_Yes_No_Tier_Percentage.argument_year_ending = 0

Definition at line 553 of file a_question_Answered_Yes_No_Tier_Percentage.py.

list a_question_Answered_Yes_No_Tier_Percentage.data_to_give_plotly = []

Definition at line 587 of file a_question_Answered_Yes_No_Tier_Percentage.py.

list a_question_Answered_Yes_No_Tier_Percentage.global_question_list = []

Definition at line 572 of file a_question_Answered_Yes_No_Tier_Percentage.py.

a_question_Answered_Yes_No_Tier_Percentage.mongo_DB_Client_Instance = None

Definition at line 560 of file a_question_Answered_Yes_No_Tier_Percentage.py.

a_question_Answered_Yes_No_Tier_Percentage.mongo_DB_Comments_Instance = None

Definition at line 569 of file a_question_Answered_Yes_No_Tier_Percentage.py.

a_question_Answered_Yes_No_Tier_Percentage.mongo_DB_Thread_Collection = None

Definition at line 566 of file a_question_Answered_Yes_No_Tier_Percentage.py.

a_question_Answered_Yes_No_Tier_Percentage.mongo_DB_Threads_Instance = None

Definition at line 563 of file a_question_Answered_Yes_No_Tier_Percentage.py.

int a_question_Answered_Yes_No_Tier_Percentage.year_actually_in_progress = 0

Definition at line 550 of file a_question_Answered_Yes_No_Tier_Percentage.py.

list a_question_Answered_Yes_No_Tier_Percentage.year_question_list = []

Definition at line 575 of file a_question_Answered_Yes_No_Tier_Percentage.py.

a_question_Tier_Distribution Namespace Reference

Functions

- def initialize_mongo_db_parameters (actually_processed_year)
- def check_script_arguments ()
- def start_data_generation_for_analysis ()
- def generate_data_to_be_analyzed ()
- def question_distribution_tier1_tierx (id_of_thread, author_of_thread)
- def check_if_comment_is_a_question (given_string)
- def check_if_comment_is_on_tier_1 (comment_parent_id)
- def check_if_comment_is_not_from_thread_author (author_of_thread, comment_author)
- def add_actual_year_list_to_global_list (list_to_append)
- def write_csv (list_with_information)
- def prepare_data_for_graph ()
- def plot_generated_data ()

Variables

- int argument_year_beginning = 0
- int year_actually_in_progress = 0
- int argument_year_ending = 0
- mongo_DB_Client_Instance = None
- mongo_DB_Threads_Instance = None
- mongo_DB_Thread_Collection = None
- mongo_DB_Comments_Instance = None
- list current_year_question_list = []
- list global_year_question_list = []
- list data_to_give_plotly = []

Function Documentation

def a_question_Tier_Distribution.add_actual_year_list_to_global_list (*list_to_append*)

```
Iterates over a given list with thread information and adds every single element to a global list
    The global list will be printed to csv in the end

Args:
    list to append (list) : List with thread information which will be appended to a global list
Returns:
    -
```

Definition at line 329 of file a_question_Tier_Distribution.py.

def a_question_Tier_Distribution.check_if_comment_is_a_question (*given_string*)

```
Simply checks whether a given string is a question or not

1. This method simply checks whether a question mark exists within that string or not..
    This is just that simple because messing around with natural processing kits to determine the
semantic sense
    would blow up my bachelor work...

Args:
```

```
    given_string (str) : The string which will be checked for a question mark
Returns:
    True (bool): Whenever the given string is a question
```

False (bool): Whenever the given string is not a question

Definition at line 269 of file a_question_Tier_Distribution.py.

def a_question_Tier_Distribution.check_if_comment_is_not_from_thread_author (*author_of_thread*, *comment_author*)

```
Checks whether both strings are equal or not

1. This method simply checks wether both strings match each other or not.
    I have built this extra method to have a better overview in the main code..

Args:
    author_of_thread (str) : The name of the thread author (iAMA-Host)
    comment_author (str) : The name of the comments author
Returns:
    True (bool): Whenever the strings do not match
    False (bool): Whenever the strings do match
     answered that given question)
```

Definition at line 308 of file a_question_Tier_Distribution.py.

def a_question_Tier_Distribution.check_if_comment_is_on_tier_1 (*comment_parent_id*)

```
Simply checks whether a given string is a question posted on tier 1 or not

1. This method simply checks whether a question has been posted on tier 1 by looking whether the
given
    string contains the substring "t3_" or not

Args:
    comment_parent_id (str): The string which will be checked for "t3_" appearance in it
Returns:
    -
```

Definition at line 290 of file a_question_Tier_Distribution.py.

def a_question_Tier_Distribution.check_script_arguments ()

```
Checks if enough and correct arguments have been given to run this script adequate

1. It checks in the first instance if enough arguments have been given
2. Then necessary variables will be filled with appropriate values

Args:
    -
Returns:
    -
```

Definition at line 40 of file a_question_Tier_Distribution.py.

def a_question_Tier_Distribution.generate_data_to_be_analyzed ()

```
Generates the data which will be analyzed

1. This method iterates over every thread
    1.1. It filters if that iterated thread is an iAMA-request or not
```

```
        1.1.1. If yes: this thread gets skipped and the next one will be processed
        1.1.2. If no: this thread will be processed
2. If the thread gets processed it will receive the distribution of questions on the tiers
3. This value will be added to a global list and will be plotted later on

Args:
    -
Returns:
    -
```

Definition at line 143 of file a_question_Tier_Distribution.py.

def a_question_Tier_Distribution.initialize_mongo_db_parameters (*actually_processed_year*)

```
Instantiates all necessary variables for the correct usage of the mongoDB-Client

Args:
    actually_processed_year (int) : The year with which parameters the database should be accessed
Returns:
    -
```

Definition at line 20 of file a_question_Tier_Distribution.py.

def a_question_Tier_Distribution.plot_generated_data ()

```
Plots the data which is to be generated

1. This method plots the data which has been calculated before by using Pltoly-Framework within
a self written class

Args:
    -
Returns:
    -
```

Definition at line 437 of file a_question_Tier_Distribution.py.

def a_question_Tier_Distribution.prepare_data_for_graph ()

```
Sorts and prepares data for graph plotting

Args:
    -
Returns:
    -
```

Definition at line 412 of file a_question_Tier_Distribution.py.

def a_question_Tier_Distribution.question_distribution_tier1_tierx (*id_of_thread*, *author_of_thread*)

```
Generates the data which will be analyzed

1. It iterates over every comment and
     1.1. checks if the iterated comment is a question
     1.2. checks if the iterated comment has been posted on tier 1 level
     1.3. checks if that comment is from the iAMA-Host himself or not
```

```
2. Now the posted question will be added to a global list, which will be used for csv writing and
chart generation
    later on

Args:
    id_of_thread (str) : Contains the id of the processed thread
    author_of_thread (str) : Contains the iAMA-Hosts name
Returns:
    -
```

Definition at line 186 of file a_question_Tier_Distribution.py.

def a_question_Tier_Distribution.start_data_generation_for_analysis ()

```
Starts the data processing by swichting through the years

1. Triggers the data generation process and moves forward within the years
    1.1. By moving through the years a csv file will be created for every year
    1.2. Additionally an interactive chart will be plotted

Args:
    -
Returns:
    -
```

Definition at line 67 of file a_question_Tier_Distribution.py.

def a_question_Tier_Distribution.write_csv (*list_with_information*)

```
Creates a csv file containing all necessary information about the distribution of questions on the
tiers

This method iterates over the "current_year_question_list", which contains every single questions
of that year
and writes a csv file containing misc information about those questions.

One thing is to be said: The .csv file will be written in binary mode, therefore looking at them
in a plain text
editor could be a problem - please use excel for that.
I had to use "binary" mode, otherwise the questions-text could not be written into the csv file,
because windows
has some problem by converting some special chars to utf.

Args:
    list with information (list) : Contains information about questions for the current year
Returns:
    -
```

Definition at line 345 of file a_question_Tier_Distribution.py.

Variable Documentation

int a_question_Tier_Distribution.argument_year_beginning = 0

Definition at line 454 of file a_question_Tier_Distribution.py.

int a_question_Tier_Distribution.argument_year_ending = 0

Definition at line 460 of file a_question_Tier_Distribution.py.

list a_question_Tier_Distribution.current_year_question_list = []

Definition at line 476 of file a_question_Tier_Distribution.py.

list a_question_Tier_Distribution.data_to_give_plotly = []

Definition at line 491 of file a_question_Tier_Distribution.py.

list a_question_Tier_Distribution.global_year_question_list = []

Definition at line 479 of file a_question_Tier_Distribution.py.

a_question_Tier_Distribution.mongo_DB_Client_Instance = None

Definition at line 464 of file a_question_Tier_Distribution.py.

a_question_Tier_Distribution.mongo_DB_Comments_Instance = None

Definition at line 473 of file a_question_Tier_Distribution.py.

a_question_Tier_Distribution.mongo_DB_Thread_Collection = None

Definition at line 470 of file a_question_Tier_Distribution.py.

a_question_Tier_Distribution.mongo_DB_Threads_Instance = None

Definition at line 467 of file a_question_Tier_Distribution.py.

int a_question_Tier_Distribution.year_actually_in_progress = 0

Definition at line 457 of file a_question_Tier_Distribution.py.

a_thread_Lifespan_N_Average_Commenttime Namespace Reference

Functions

- def check_script_arguments ()
- def initialize_mongo_db_parameters (actually_processed_year)
- def start_data_generation_for_analysis ()
- def prepare_data_for_graph_life_span ()
- def prepare_data_for_comment_time ()
- def generate_data_to_be_analyzed ()
- def calculate_time_difference (id_of_thread, creation_date_of_thread)
- def write_csv (list_with_information)
- def add_thread_list_to_global_list (list_to_append)
- def prepare_dict_by_time_separation_for_comment_time ()
- def plot_generated_data ()

Variables

- int argument_year_beginning = 0
- string argument_calculation = ""
- int argument_year_ending = 0
- int year_actually_in_progress = 0
- string argument_plot_time_unit = ""
- mongo_DB_Client_Instance = None
- mongo_DB_Threads_Instance = None
- mongo_DB_Thread_Collection = None
- mongo_DB_Comments_Instance = None
- list global_thread_list = []
- list temp_time_difference_list = []
- list list_with_currents_year_infos = []
- list data_to_give_plotly = []

Function Documentation

def a_thread_Lifespan_N_Average_Commenttime.add_thread_list_to_global_list (*list_to_append*)

```
Adds all elements of for the current year into a global list. This global list will be written into
a csv file
later on

1. This method simply checks wether both strings match each other or not.
    I have built this extra method to have a better overview in the main code..

Args:
    list_to_append (list) : The list which will be iterated over and which elements will be added
to the global list
Returns:
    -
```

Definition at line 742 of file a_thread_Lifespan_N_Average_Commenttime.py.

def a_thread_Lifespan_N_Average_Commenttime.calculate_time_difference (*id_of_thread*, *creation_date_of_thread*)

```
Calculates the difference between thread creation date and the last comment found in that thread

1. The creation date of a thread gets determined
2. Then the comments will be iterated over, creating a dictionary which is structured as follows:
  {
      ('first_Comment_After_Thread_Started', int),
      ('thread_life_span', int),
      ('arithmetic Mean Response Time', int),
      ('median_Response_Time', int),
      ('id')
  }
3. That returned dictionary will be appended to a global list
4. That List will be iterated later on and the appropriate graph will be plotted

Args:
    id of thread (str) : The string which contains the id of the actually processed thread
    creation_date_of_thread (str) : The string which contains the creation date of the thread (in
epoch formatation)
Returns:
```

dict_to_be_returned (dict) : Containing information about the time difference

Definition at line 480 of file a_thread_Lifespan_N_Average_Commenttime.py.

def a_thread_Lifespan_N_Average_Commenttime.check_script_arguments ()

```
Checks if enough and correct arguments have been given to run this script adequate

1. It checks in the first instance if enough arguments have been given
2. Then necessary variables will be filled with appropriate values

Args:
    -
Returns:
    -
```

Definition at line 21 of file a_thread_Lifespan_N_Average_Commenttime.py.

def a_thread_Lifespan_N_Average_Commenttime.generate_data_to_be_analyzed ()

```
Generates the data which will be analyzed

1. This method iterates over every thread
    1.1. It filters if that iterated thread is an iAMA-request or not
        1.1.1. If yes: this thread gets skipped and the next one will be processed
        1.1.2. If no: this thread will be processed
2. If the thread gets processed it will receive the life span and other information about the thread
as dictionary
3. This dictionary will be added to a global list and will be plotted later on

Args:
    -
Returns:
    -
```

Definition at line 422 of file a_thread_Lifespan_N_Average_Commenttime.py.

def a_thread_Lifespan_N_Average_Commenttime.initialize_mongo_db_parameters (*actually_processed_year*)

```
Instantiates all necessary variables for the correct usage of the mongoDB-Client

Args:
    actually_processed_year (int) : The year with which parameters the database should be accessed
Returns:
    -
```

Definition at line 48 of file a_thread_Lifespan_N_Average_Commenttime.py.

def a_thread_Lifespan_N_Average_Commenttime.plot_generated_data ()

```
Plots the data which is to be generated

1. This method plots the data which has been calculated before by using Pltoly-Framework within
a self written class

Args:
    -
Returns:
    -
```

Definition at line 881 of file a_thread_Lifespan_N_Average_Commenttime.py.

def a_thread_Lifespan_N_Average_Commenttime.prepare_data_for_comment_time ()

```
Prepares the average mean comment time per thread

Args:
    -
Returns:
    -
```

Definition at line 316 of file a_thread_Lifespan_N_Average_Commenttime.py.

def a_thread_Lifespan_N_Average_Commenttime.prepare_data_for_graph_life_span ()

```
Calculates the distribution of single values regarding the chosen time argument

Args:
    -
Returns:
    -
```

Definition at line 215 of file a_thread_Lifespan_N_Average_Commenttime.py.

def a_thread_Lifespan_N_Average_Commenttime.prepare_dict_by_time_separation_for_comment_time ()

```
Restructures the dictionary which is to be plotted for the display of the average mean comment time

1. This method processes the data in dependence of the commited time

Args:
    -
Returns:
    -
```

Definition at line 761 of file a_thread_Lifespan_N_Average_Commenttime.py.

def a_thread_Lifespan_N_Average_Commenttime.start_data_generation_for_analysis ()

```
Starts the data processing by swichting through the years

1. Triggers the data generation process and moves forward within the years
    1.1. By moving through the years a csv file will be created for every year
    1.2. Additionally an interactive chart will be plotted

Args:
    -
Returns:
    -
```

Definition at line 68 of file a_thread_Lifespan_N_Average_Commenttime.py.

def a_thread_Lifespan_N_Average_Commenttime.write_csv (***list_with_information*** **)**

```
Creates a csv file containing all necessary information about the life span of a thread and various
information
    about comments

Args:
    list with information (list) : Contains various information about thread and comment time
Returns:
    -
```

Definition at line 685 of file a_thread_Lifespan_N_Average_Commenttime.py.

Variable Documentation

string a_thread_Lifespan_N_Average_Commenttime.argument_calculation = ""

Definition at line 900 of file a_thread_Lifespan_N_Average_Commenttime.py.

string a_thread_Lifespan_N_Average_Commenttime.argument_plot_time_unit = ""

Definition at line 909 of file a_thread_Lifespan_N_Average_Commenttime.py.

int a_thread_Lifespan_N_Average_Commenttime.argument_year_beginning = 0

Definition at line 897 of file a_thread_Lifespan_N_Average_Commenttime.py.

int a_thread_Lifespan_N_Average_Commenttime.argument_year_ending = 0

Definition at line 903 of file a_thread_Lifespan_N_Average_Commenttime.py.

list a_thread_Lifespan_N_Average_Commenttime.data_to_give_plotly = []

Definition at line 945 of file a_thread_Lifespan_N_Average_Commenttime.py.

list a_thread_Lifespan_N_Average_Commenttime.global_thread_list = []

Definition at line 924 of file a_thread_Lifespan_N_Average_Commenttime.py.

list a_thread_Lifespan_N_Average_Commenttime.list_with_currents_year_infos = []

Definition at line 930 of file a_thread_Lifespan_N_Average_Commenttime.py.

a_thread_Lifespan_N_Average_Commenttime.mongo_DB_Client_Instance = None

Definition at line 912 of file a_thread_Lifespan_N_Average_Commenttime.py.

a_thread_Lifespan_N_Average_Commenttime.mongo_DB_Comments_Instance = None

Definition at line 921 of file a_thread_Lifespan_N_Average_Commenttime.py.

a_thread_Lifespan_N_Average_Commenttime.mongo_DB_Thread_Collection = None

Definition at line 918 of file a_thread_Lifespan_N_Average_Commenttime.py.

a_thread_Lifespan_N_Average_Commenttime.mongo_DB_Threads_Instance = None

Definition at line 915 of file a_thread_Lifespan_N_Average_Commenttime.py.

list a_thread_Lifespan_N_Average_Commenttime.temp_time_difference_list = []

Definition at line 927 of file a_thread_Lifespan_N_Average_Commenttime.py.

int a_thread_Lifespan_N_Average_Commenttime.year_actually_in_progress = 0

Definition at line 906 of file a_thread_Lifespan_N_Average_Commenttime.py.

a_thread_Lifespan_N_Average_Questiontime Namespace Reference

Functions

- def check_script_arguments ()
- def initialize_mongo_db_parameters (actually_processed_year)
- def start_data_generation_for_analysis ()
- def prepare_data_for_graph_life_span ()
- def prepare_data_for_comment_time ()
- def generate_data_to_be_analyzed ()
- def calculate_time_difference (id_of_thread, creation_date_of_thread)
- def write_csv (list_with_information)
- def add_thread_list_to_global_list (list_to_append)
- def prepare_dict_by_time_separation_for_comment_time ()
- def plot_generated_data ()

Variables

- int argument_year_beginning = 0
- string argument_calculation = ""
- int argument_year_ending = 0
- int year_actually_in_progress = 0
- string argument_plot_time_unit = ""
- mongo_DB_Client_Instance = None
- mongo_DB_Threads_Instance = None
- mongo_DB_Thread_Collection = None
- mongo_DB_Comments_Instance = None
- list global_thread_list = []
- list temp_time_difference_list = []
- list list_with_currents_year_infos = []
- list data_to_give_plotly = []

Function Documentation

def a_thread_Lifespan_N_Average_Questiontime.add_thread_list_to_global_list (*list_to_append*)

```
Adds all elements of for the current year into a global list. This global list will be written into
a csv file
later on

1. This method simply checks wether both strings match each other or not.
    I have built this extra method to have a better overview in the main code..

Args:
    list_to_append (list) : The list which will be iterated over and which elements will be added
to the global list
Returns:
    -
```

Definition at line 751 of file a_thread_Lifespan_N_Average_Questiontime.py.

def a_thread_Lifespan_N_Average_Questiontime.calculate_time_difference (*id_of_thread*, *creation_date_of_thread*)

```
Calculates the difference between thread creation date and the last comment found in that thread

1. The creation date of a thread gets determined
2. Then the comments will be iterated over, creating a dictionary which is structured as follows:
  {
      ('first_Comment_After_Thread_Started', int),
      ('thread_life_span', int),
      ('arithmetic_Mean_Response_Time', int),
      ('median Response Time', int),
      ('id')
  }
3. That returned dictionary will be appended to a global list
4. That List will be iterated later on and the appropriate graph will be plotted

Args:
    id_of_thread (str) : The string which contains the id of the actually processed thread
    creation date of thread (str) : The string which contains the creation date of the thread (in
epoch formatation)
Returns:
```

dict_to_be_returned (dict) : Containing information about the time difference

Definition at line 480 of file a_thread_Lifespan_N_Average_Questiontime.py.

def a_thread_Lifespan_N_Average_Questiontime.check_script_arguments ()

```
Checks if enough and correct arguments have been given to run this script adequate

1. It checks in the first instance if enough arguments have been given
2. Then necessary variables will be filled with appropriate values

Args:
    -
Returns:
    -
```

Definition at line 21 of file a_thread_Lifespan_N_Average_Questiontime.py.

def a_thread_Lifespan_N_Average_Questiontime.generate_data_to_be_analyzed ()

```
Generates the data which will be analyzed

1. This method iterates over every thread
    1.1. It filters if that iterated thread is an iAMA-request or not
        1.1.1. If yes: this thread gets skipped and the next one will be processed
        1.1.2. If no: this thread will be processed
2. If the thread gets processed it will receive the life span and other information about the thread
as dictionary
3. This dictionary will be added to a global list and will be plotted later on

Args:
    -
Returns:
    -
```

Definition at line 422 of file a_thread_Lifespan_N_Average_Questiontime.py.

def a_thread_Lifespan_N_Average_Questiontime.initialize_mongo_db_parameters (*actually_processed_year*)

```
Instantiates all necessary variables for the correct usage of the mongoDB-Client

Args:
    actually_processed_year (int) : The year with which parameters the database should be accessed
```

```
Returns:
    -
```

Definition at line 48 of file a_thread_Lifespan_N_Average_Questiontime.py.

def a_thread_Lifespan_N_Average_Questiontime.plot_generated_data ()

```
Plots the data which is to be generated

1. This method plots the data which has been calculated before by using Pltoly-Framework within
a self written class

Args:
    -
Returns:
    -
```

Definition at line 890 of file a_thread_Lifespan_N_Average_Questiontime.py.

def a_thread_Lifespan_N_Average_Questiontime.prepare_data_for_comment_time ()

```
Prepares the average mean comment time per thread

Args:
    -
Returns:
    -
```

Definition at line 316 of file a_thread_Lifespan_N_Average_Questiontime.py.

def a_thread_Lifespan_N_Average_Questiontime.prepare_data_for_graph_life_span ()

```
Calculates the distribution of single values regarding the chosen time argument

Args:
    -
Returns:
    -
```

Definition at line 215 of file a_thread_Lifespan_N_Average_Questiontime.py.

def a_thread_Lifespan_N_Average_Questiontime.prepare_dict_by_time_separation_for_comment_time ()

```
Restructures the dictionary which is to be plotted for the display of the average mean comment time

1. This method processes the data in dependence of the commited time

Args:
    -
Returns:
    -
```

Definition at line 770 of file a_thread_Lifespan_N_Average_Questiontime.py.

def a_thread_Lifespan_N_Average_Questiontime.start_data_generation_for_analysis ()

```
Starts the data processing by swichting through the years

1. Triggers the data generation process and moves forward within the years
    1.1. By moving through the years a csv file will be created for every year
    1.2. Additionally an interactive chart will be plotted

Args:
    -
Returns:
    -
```

Definition at line 68 of file a_thread_Lifespan_N_Average_Questiontime.py.

def a_thread_Lifespan_N_Average_Questiontime.write_csv (***list_with_information*** **)**

```
Creates a csv file containing all necessary information about the life span of a thread and various
information
    about comments

Args:
    list with information (list) : Contains various information about thread and comment time
Returns:
    -
```

Definition at line 694 of file a_thread_Lifespan_N_Average_Questiontime.py.

Variable Documentation

string a_thread_Lifespan_N_Average_Questiontime.argument_calculation = ""

Definition at line 909 of file a_thread_Lifespan_N_Average_Questiontime.py.

string a_thread_Lifespan_N_Average_Questiontime.argument_plot_time_unit = ""

Definition at line 918 of file a_thread_Lifespan_N_Average_Questiontime.py.

int a_thread_Lifespan_N_Average_Questiontime.argument_year_beginning = 0

Definition at line 906 of file a_thread_Lifespan_N_Average_Questiontime.py.

int a_thread_Lifespan_N_Average_Questiontime.argument_year_ending = 0

Definition at line 912 of file a_thread_Lifespan_N_Average_Questiontime.py.

list a_thread_Lifespan_N_Average_Questiontime.data_to_give_plotly = []

Definition at line 954 of file a_thread_Lifespan_N_Average_Questiontime.py.

list a_thread_Lifespan_N_Average_Questiontime.global_thread_list = []

Definition at line 933 of file a_thread_Lifespan_N_Average_Questiontime.py.

list a_thread_Lifespan_N_Average_Questiontime.list_with_currents_year_infos = []

Definition at line 939 of file a_thread_Lifespan_N_Average_Questiontime.py.

a_thread_Lifespan_N_Average_Questiontime.mongo_DB_Client_Instance = None

Definition at line 921 of file a_thread_Lifespan_N_Average_Questiontime.py.

a_thread_Lifespan_N_Average_Questiontime.mongo_DB_Comments_Instance = None

Definition at line 930 of file a_thread_Lifespan_N_Average_Questiontime.py.

a_thread_Lifespan_N_Average_Questiontime.mongo_DB_Thread_Collection = None

Definition at line 927 of file a_thread_Lifespan_N_Average_Questiontime.py.

a_thread_Lifespan_N_Average_Questiontime.mongo_DB_Threads_Instance = None

Definition at line 924 of file a_thread_Lifespan_N_Average_Questiontime.py.

list a_thread_Lifespan_N_Average_Questiontime.temp_time_difference_list = []

Definition at line 936 of file a_thread_Lifespan_N_Average_Questiontime.py.

int a_thread_Lifespan_N_Average_Questiontime.year_actually_in_progress = 0

Definition at line 915 of file a_thread_Lifespan_N_Average_Questiontime.py.

ar_analyzer Namespace Reference

Functions

- def average_means_of_values_f_threads ()
- def std_derivation ()

Variables

- thread_information
- thread_year = thread_information['Year']
- thread_id = thread_information['Thread id']
- thread_author = thread_information['Thread author']
- thread_ups = thread_information['Thread ups']
- thread_downs = thread_information['Thread downs']
- thread_creation_time_stamp = thread_information['Thread creation time stamp']
- thread_average_comment_vote_score_total
- thread_average_comment_vote_score_tier_1
- thread_average_comment_vote_score_tier_x
- thread_average_question_vote_score_total
- thread_average_question_vote_score_tier_1
- thread_average_question_vote_score_tier_x
- thread_num_comments_total_skewed
- thread_num_comments_total = thread_information['Thread num comments total']
- thread_num_comments_tier_1 = thread_information['Thread num comments tier 1']
- thread_num_comments_tier_x = thread_information['Thread num comments tier x']
- thread_num_questions_total = thread_information['Thread num questions total']
- thread_num_questions_tier_1 = thread_information['Thread num questions tier 1']
- thread_num_questions_tier_x = thread_information['Thread num questions tier x']
- thread_num_questions_answered_by_iama_host_total
- thread_num_questions_answered_by_iama_host_tier_1
- thread_num_questions_answered_by_iama_host_tier_x
- thread_num_comments_answered_by_iama_host_total
- thread_num_comments_answered_by_iama_host_tier_1
- thread_num_comments_answered_by_iama_host_tier_x
- thread_average_reaction_time_between_comments_total
- thread_average_reaction_time_between_comments_tier_1
- thread_average_reaction_time_between_comments_tier_x
- thread_average_reaction_time_between_questions_total
- thread_average_reaction_time_between_questions_tier_1
- thread_average_reaction_time_between_questions_tier_x
- thread_average_response_to_comment_time_iama_host_total
- thread_average_response_to_comment_time_iama_host_tier_1
- thread_average_response_to_comment_time_iama_host_tier_x
- thread_average_response_to_question_time_iama_host_total
- thread_average_response_to_question_time_iama_host_tier_1
- thread_average_response_to_question_time_iama_host_tier_x
- thread_amount_of_questioners_total
- thread_amount_of_questioners_tier_1
- thread_amount_of_questioners_tier_x
- thread_amount_of_commentators_total
- thread_amount_of_commentators_tier_1
- thread_amount_of_commentators_tier_x
- thread_life_span_until_last_comment

- thread_life_span_until_last_question

Function Documentation

def ar_analyzer.average_means_of_values_f_threads ()

```
Calculation of the average means of different values

Args:
    -
Returns:
    -
```

Definition at line 110 of file ar_analyzer.py.

def ar_analyzer.std_derivation ()

Definition at line 259 of file ar_analyzer.py.

Variable Documentation

ar_analyzer.thread_amount_of_commentators_tier_1

```
Initial value:    1 = thread_information[
    2     'Thread amount of commentators tier 1']
```

Definition at line 98 of file ar_analyzer.py.

ar_analyzer.thread_amount_of_commentators_tier_x

```
Initial value:    1 = thread_information[
    2     'Thread amount of commentators tier x']
```

Definition at line 100 of file ar_analyzer.py.

ar_analyzer.thread_amount_of_commentators_total

```
Initial value:    1 = thread_information[
    2     'Thread amount of commentators total']
```

Definition at line 96 of file ar_analyzer.py.

ar_analyzer.thread_amount_of_questioners_tier_1

```
Initial value:    1 = thread_information[
    2     'Thread amount of questioners tier 1']
```

Definition at line 91 of file ar_analyzer.py.

ar_analyzer.thread_amount_of_questioners_tier_x

```
Initial value:    1 = thread_information[
    2     'Thread amount of questioners tier x']
```

Definition at line 93 of file ar_analyzer.py.

ar_analyzer.thread_amount_of_questioners_total

```
Initial value:    1 = thread_information[
    2     'Thread amount of questioners total']
```

Definition at line 89 of file ar_analyzer.py.

ar_analyzer.thread_author = thread_information['Thread author']

Definition at line 17 of file ar_analyzer.py.

ar_analyzer.thread_average_comment_vote_score_tier_1

```
Initial value:    1 = thread_information[
    2     'Thread average comment vote score tier 1']
```

Definition at line 25 of file ar_analyzer.py.

ar_analyzer.thread_average_comment_vote_score_tier_x

```
Initial value:    1 = thread_information[
    2     'Thread average comment vote score tier x']
```

Definition at line 27 of file ar_analyzer.py.

ar_analyzer.thread_average_comment_vote_score_total

```
Initial value:    1 = thread_information[
    2     'Thread average comment vote score total']
```

Definition at line 22 of file ar_analyzer.py.

ar_analyzer.thread_average_question_vote_score_tier_1

```
Initial value:    1 = thread_information[
    2     'Thread average question vote score tier 1']
```

Definition at line 32 of file ar_analyzer.py.

ar_analyzer.thread_average_question_vote_score_tier_x

```
Initial value:    1 = thread_information[
    2     'Thread average question vote score tier x']
```

Definition at line 34 of file ar_analyzer.py.

ar_analyzer.thread_average_question_vote_score_total

```
Initial value:    1 = thread_information[
    2     'Thread average question vote score total']
```

Definition at line 30 of file ar_analyzer.py.

ar_analyzer.thread_average_reaction_time_between_comments_tier_1

```
Initial value:    1 = thread_information[
    2     'Thread average reaction time between comments tier 1']
```

Definition at line 63 of file ar_analyzer.py.

ar_analyzer.thread_average_reaction_time_between_comments_tier_x

```
Initial value:    1 = thread_information[
    2     'Thread average reaction time between comments tier x']
```

Definition at line 65 of file ar_analyzer.py.

ar_analyzer.thread_average_reaction_time_between_comments_total

```
Initial value:    1 = thread_information[
    2     'Thread average reaction time between comments total']
```

Definition at line 61 of file ar_analyzer.py.

ar_analyzer.thread_average_reaction_time_between_questions_tier_1

```
Initial value:    1 = thread_information[
    2     'Thread average reaction time between questions tier 1']
```

Definition at line 70 of file ar_analyzer.py.

ar_analyzer.thread_average_reaction_time_between_questions_tier_x

```
Initial value:    1 = thread_information[
    2     'Thread average reaction time between questions tier x']
```

Definition at line 72 of file ar_analyzer.py.

ar_analyzer.thread_average_reaction_time_between_questions_total

```
Initial value:    1 = thread_information[
    2     'Thread average reaction time between questions total']
```

Definition at line 68 of file ar_analyzer.py.

ar_analyzer.thread_average_response_to_comment_time_iama_host_tier_1

```
Initial value:    1 = thread_information[
    2     'Thread average response to comment time iama host tier 1']
```

Definition at line 77 of file ar_analyzer.py.

ar_analyzer.thread_average_response_to_comment_time_iama_host_tier_x

```
Initial value:    1 = thread_information[
    2     'Thread average response to comment time iama host tier x']
```

Definition at line 79 of file ar_analyzer.py.

ar_analyzer.thread_average_response_to_comment_time_iama_host_total

```
Initial value:    1 = thread_information[
    2     'Thread average response to comment time iama host total']
```

Definition at line 75 of file ar_analyzer.py.

ar_analyzer.thread_average_response_to_question_time_iama_host_tier_1

```
Initial value:    1 = thread_information[
    2     'Thread average response to question time iama host tier 1']
```

Definition at line 84 of file ar_analyzer.py.

ar_analyzer.thread_average_response_to_question_time_iama_host_tier_x

```
Initial value:    1 = thread_information[
    2     'Thread average response to question time iama host tier x']
```

Definition at line 86 of file ar_analyzer.py.

ar_analyzer.thread_average_response_to_question_time_iama_host_total

```
Initial value:    1 = thread_information[
    2     'Thread average response to question time iama host total']
```

Definition at line 82 of file ar_analyzer.py.

ar_analyzer.thread_creation_time_stamp = thread_information['Thread creation time stamp']

Definition at line 20 of file ar_analyzer.py.

ar_analyzer.thread_downs = thread_information['Thread downs']

Definition at line 19 of file ar_analyzer.py.

ar_analyzer.thread_id = thread_information['Thread id']

Definition at line 16 of file ar_analyzer.py.

ar_analyzer.thread_information

```
Initial value:    1 = pandas.read_csv(
    2     'd_create_Big_CSV_2009_until_2016_BIGDATA_ALL.csv',
    3     sep=',',
    4     na_values="None")
```

Definition at line 10 of file ar_analyzer.py.

ar_analyzer.thread_life_span_until_last_comment

```
Initial value:    1 = thread_information[
    2     'Thread life span until last comment']
```

Definition at line 104 of file ar_analyzer.py.

ar_analyzer.thread_life_span_until_last_question

```
Initial value:    1 = thread_information[
    2     'Thread life span until last question']
```

Definition at line 106 of file ar_analyzer.py.

ar_analyzer.thread_num_comments_answered_by_iama_host_tier_1

```
Initial value:    1 = thread_information[
    2     'Thread num comments answered by iama host tier 1']
```

Definition at line 56 of file ar_analyzer.py.

ar_analyzer.thread_num_comments_answered_by_iama_host_tier_x

```
Initial value:    1 = thread_information[
    2     'Thread num comments answered by iama host tier x']
```

Definition at line 58 of file ar_analyzer.py.

ar_analyzer.thread_num_comments_answered_by_iama_host_total

```
Initial value:    1 = thread_information[
    2     'Thread num comments answered by iama host total']
```

Definition at line 54 of file ar_analyzer.py.

ar_analyzer.thread_num_comments_tier_1 = thread_information['Thread num comments tier 1']

Definition at line 40 of file ar_analyzer.py.

ar_analyzer.thread_num_comments_tier_x = thread_information['Thread num comments tier x']

Definition at line 41 of file ar_analyzer.py.

ar_analyzer.thread_num_comments_total = thread_information['Thread num comments total']

Definition at line 39 of file ar_analyzer.py.

ar_analyzer.thread_num_comments_total_skewed

```
Initial value:    1 = thread_information[
    2     'Thread num comments total skewed']
```

Definition at line 37 of file ar_analyzer.py.

ar_analyzer.thread_num_questions_answered_by_iama_host_tier_1

```
Initial value:    1 = thread_information[
    2     'Thread num questions answered by iama host tier 1']
```

Definition at line 49 of file ar_analyzer.py.

ar_analyzer.thread_num_questions_answered_by_iama_host_tier_x

```
Initial value:    1 = thread_information[
    2     'Thread num questions answered by iama host tier x']
```

Definition at line 51 of file ar_analyzer.py.

ar_analyzer.thread_num_questions_answered_by_iama_host_total

```
Initial value:    1 = thread_information[
    2     'Thread num questions answered by iama host total']
```

Definition at line 47 of file ar_analyzer.py.

ar_analyzer.thread_num_questions_tier_1 = thread_information['Thread num questions tier 1']

Definition at line 44 of file ar_analyzer.py.

ar_analyzer.thread_num_questions_tier_x = thread_information['Thread num questions tier x']

Definition at line 45 of file ar_analyzer.py.

ar_analyzer.thread_num_questions_total = thread_information['Thread num questions total']

Definition at line 43 of file ar_analyzer.py.

ar_analyzer.thread_ups = thread_information['Thread ups']

Definition at line 18 of file ar_analyzer.py.

ar_analyzer.thread_year = thread_information['Year']

Definition at line 15 of file ar_analyzer.py.

c_crawl_Author_Information Namespace Reference

Functions

- def check_script_arguments ()
- def initialize_mongo_db_parameters (actually_processed_year)
- def start_data_generation_for_analysis ()
- def generate_data_now ()
- def calculate_time_difference (time_value_1, time_value_2)
- def get_author_information (name_of_author)

Variables

- int argument_year_beginning = 0
- int year_actually_in_progress = 0
- int argument_year_ending = 0
- string argument_inverse_crawling = ""
- mongo_db_client_instance = None
- mongo_db_threads_instance = None
- mongo_db_thread_collection = None
- mongo_db_author_instance = None
- reddit_instance = praw.Reddit(user_agent="University_Regensburg_iAMA_Crawler_0.001")

Function Documentation

def c_crawl_Author_Information.calculate_time_difference (*time_value_1*, *time_value_2*)

```
Calculates the time difference between two floats in epoch style and returns seconds

Args:
    time_value_1 (float): The first time value to be used for calculation
    time_value_2 (float): The second time value to be used for calculation
Returns:
    time_diff_seconds (int): The amount of time difference in seconds
```

Definition at line 233 of file c_crawl_Author_Information.py.

def c_crawl_Author_Information.check_script_arguments ()

```
Checks if enough and correct arguments have been given to run this script adequate

1. It checks in the first instance if enough arguments have been given
2. Then necessary variables will be filled with appropriate values

Args:
    -
Returns:
    -
```

Definition at line 18 of file c_crawl_Author_Information.py.

def c_crawl_Author_Information.generate_data_now ()

```
Crawls author information and writes them into the mongoDB database with the name
'iAMA_Reddit_Authors'

It does this by first checking the given crawling direction. The ability to crawl bidirectional
allows you to build
up you database in a much more faster way, because you can start one instance crawling forward while
the other
instance crawls backward.

This method works in the following way:

1. Checks for crawling direction
2. It checks whether an iterated collection is no "system.indexes".
3. By iterating over all collections it checks for iAMA-Requests and skips them. Because we do not
want requests
in our dataset, because we want data of actually created iama threads

4. Now it will be checked whether the author already exists within the database (collection name).
This will be
done by always re-initialising the collection.names() which is necessary to always have a
up2date-overview!

    4.1. Whenever the author does not exist yet get the necessary information and write it into
the database

    4.2. Whenever the author does already exist skip that calculation part

Args:
    -
Returns:
    -
```

Definition at line 103 of file c_crawl_Author_Information.py.

def c_crawl_Author_Information.get_author_information (*name_of_author*)

```
Calculates various information about the author
    Because I have created this script shortly before my evaluation everything listed here is not
outsourced by
    written in a very sequential / procedural way, therefore I ask for you understanding.

    The method does the following:

    1. Referencing a reddit author object, which is necessary to get all that necessary data
    2. Declaration of necessary variables for later assignment
    3. Trial of receiving the authors birthday
        We have to try this here, because, if the account has already been deleted a http error
will be thrown
        and we would have to recrawl all that data.
    4. Receival authors comment / link karma - amount
    5. Trial of receiving of all links / comments the author every made
        Because it could happen, that there is an internal error in reddit ongoing (Error 500) which
will reset
        the connection and therefore we would have to recrawl all of our data
    6. Iteration of all comments / links and therefore saving the time difference (in seconds)
between each created
        comment / link
    7. Calculation of time difference between acc birth & first iama in seconds
    8. Patching up a big dictionary which will be sorted (alphabetically correct)
    9. Return that dictionary

Args:
    name_of_author (str): The name of the author which information need to be calculated
Returns:
    dict_to_be_returned (dict): Dictionary containing various information about the author. It will
be written
```

Definition at line 269 of file c_crawl_Author_Information.py.

def c_crawl_Author_Information.initialize_mongo_db_parameters (*actually_processed_year*)

```
Instantiates all necessary variables for the correct usage of the mongoDB client

Args:
    actually_processed_year (int) : The year with which parameters the database should be accessed
Returns:
    -
```

Definition at line 48 of file c_crawl_Author_Information.py.

def c_crawl_Author_Information.start_data_generation_for_analysis ()

```
Starts the data processing by swichting through the years
    After every year cycle the mongo db parameters will be reinitialized

Args:
    -
Returns:
    -
```

Definition at line 68 of file c_crawl_Author_Information.py.

Variable Documentation

string c_crawl_Author_Information.argument_inverse_crawling = ""

Definition at line 499 of file c_crawl_Author_Information.py.

int c_crawl_Author_Information.argument_year_beginning = 0

Definition at line 490 of file c_crawl_Author_Information.py.

int c_crawl_Author_Information.argument_year_ending = 0

Definition at line 496 of file c_crawl_Author_Information.py.

c_crawl_Author_Information.mongo_db_author_instance = None

Definition at line 511 of file c_crawl_Author_Information.py.

c_crawl_Author_Information.mongo_db_client_instance = None

Definition at line 502 of file c_crawl_Author_Information.py.

c_crawl_Author_Information.mongo_db_thread_collection = None

Definition at line 508 of file c_crawl_Author_Information.py.

c_crawl_Author_Information.mongo_db_threads_instance = None

Definition at line 505 of file c_crawl_Author_Information.py.

c_crawl_Author_Information.reddit_instance = praw.Reddit(user_agent="University_Regensburg_iAMA_Crawler_0.001")

Definition at line 514 of file c_crawl_Author_Information.py.

int c_crawl_Author_Information.year_actually_in_progress = 0

Definition at line 493 of file c_crawl_Author_Information.py.

c_crawl_Differences Namespace Reference

Functions

- def check_script_arguments ()
- def initialize_mongo_db_parameters ()
- def crawl_missing_collection_into_comments_database (name_of_missing_collection)
- def check_if_collection_is_missing_in_comments_database ()
- def crawl_missing_collection_into_threads_database (name_of_missing_collection)
- def check_if_collection_is_missing_in_threads_database ()
- def start_crawling_for_diffs ()

Variables

- mongo_DB_Client_Instance = None
- mongo_DB_Threads_Instance = None
- mongo_DB_Thread_Collection = None
- mongo_DB_Comments_Instance = None
- mongo_DB_Comments_Collection = None
- string argument_year_beginning = ""
- string argument_year_ending = ""
- string argument_inverse_crawling = ""

Function Documentation

def c_crawl_Differences.check_if_collection_is_missing_in_comments_database ()

```
Checks if a specific collection (thread) is missing in the appropriate comments database

    The method starts the diff checking for all collections within the threads database.
    Whenever a thread exists in the comment database but not in the threads database it will be
crawled from the
    reddit servers and written into the database.

Args:
    -
Returns:
    -
```

Definition at line 213 of file c_crawl_Differences.py.

def c_crawl_Differences.check_if_collection_is_missing_in_threads_database ()

```
Checks if a specific collection (thread) is missing in the appropriate threads database

    The method starts the diff checking for all collections within the threads database.
    Whenever a thread exists in the comment database but not in the threads database it will be
crawled from the
    reddit servers and written into the database.

Args:
    -
Returns:
    -
```

Definition at line 353 of file c_crawl_Differences.py.

def c_crawl_Differences.check_script_arguments ()

```
Checks if enough and correct arguments have been given to run this script adequate

1. It checks in the first instance if enough arguments have been given
2. Then necessary variables will be filled with appropriate values

Args:
    -
Returns:
    -
```

Definition at line 14 of file c_crawl_Differences.py.

def c_crawl_Differences.crawl_missing_collection_into_comments_database (*name_of_missing_collection*)

```
Crawls a specific thread, which is missing in the comments database and writes the appropriate entry
in the db

    The method works as follows:
    1. It checks whether that thread / collection is really missing (even when that has been done
before, we check
        it again here, just to make sure that collection has not been created in the meanwhile by
another crawling
        process.
    2. Now the comments will be crawled from the reddit servers with flattened hierarchy
    3. Yet the comments will be written into the appropriate comments database. The correct database
will be
        deviated from the threads creation timestamp.


Args:
    name_of_missing_collection (str) : The id of the collection which is actually missing in the
comments database
Returns:
    -
```

Definition at line 76 of file c_crawl_Differences.py.

def c_crawl_Differences.crawl_missing_collection_into_threads_database (*name_of_missing_collection*)

```
Crawls a specific thread, which is missing in the thread database and writes the appropriate entry
in the db

    The method works as follows:
    1. It checks whether that thread / collection is really missing (even when that has been done
before, we check
        it again here, just to make sure that collection has not been created in the meanwhile by
another crawling
        process.
    2. Now the the thread will be crawled from the reddit servers
    3. Yet the thread will be written into the appropriate threads database. The correct database
will be
        deviated from the threads creation timestamp.

Args:
    name of missing collection (str) : The id of the collection which is actually missing in the
comments database
Returns:
```

```
    -
```

Definition at line 269 of file c_crawl_Differences.py.

def c_crawl_Differences.initialize_mongo_db_parameters ()

```
Instantiates all necessary variables for the correct usage of the mongoDB-Client

Args:
    -
Returns:
    -
```

Definition at line 49 of file c_crawl_Differences.py.

def c_crawl_Differences.start_crawling_for_diffs ()

```
This method starts the crawling, with the method you have defined in your arguments

Args:
    -
Returns:
    -
```

Definition at line 406 of file c_crawl_Differences.py.

Variable Documentation

string c_crawl_Differences.argument_inverse_crawling = ""

Definition at line 481 of file c_crawl_Differences.py.

string c_crawl_Differences.argument_year_beginning = ""

Definition at line 475 of file c_crawl_Differences.py.

string c_crawl_Differences.argument_year_ending = ""

Definition at line 478 of file c_crawl_Differences.py.

c_crawl_Differences.mongo_DB_Client_Instance = None

Definition at line 460 of file c_crawl_Differences.py.

c_crawl_Differences.mongo_DB_Comments_Collection = None

Definition at line 472 of file c_crawl_Differences.py.

c_crawl_Differences.mongo_DB_Comments_Instance = None

Definition at line 469 of file c_crawl_Differences.py.

c_crawl_Differences.mongo_DB_Thread_Collection = None

Definition at line 466 of file c_crawl_Differences.py.

c_crawl_Differences.mongo_DB_Threads_Instance = None

Definition at line 463 of file c_crawl_Differences.py.

c_crawl_Random_Author_Information Namespace Reference

Functions

- def check_script_arguments ()
- def initialize_mongo_db_parameters ()
- def start_data_generation_for_analysis ()
- def generate_data_now (randomized_author_name)
- def calculate_time_difference (time_value_1, time_value_2)
- def get_author_information (name_of_author)

Variables

- argument_limit_crawling_amount = None
- mongo_db_client_instance = None
- mongo_db_random_author_instance = None
- mongo_db_random_author_collection = None
- mongo_db_iama_author_instance = None
- mongo_db_iama_author_collection = None
- int mongo_db_iama_author_collection_amount = 0
- reddit_instance = praw.Reddit(user_agent="University_Regensburg_iAMA_Crawler_0.001")

Function Documentation

def c_crawl_Random_Author_Information.calculate_time_difference (*time_value_1*, *time_value_2*)

```
Calculates the time difference between two floats in epoch style and returns seconds

Args:
    time_value_1 (float): The first time value to be used for calculation
    time value 2 (float): The second time value to be used for calculation
Returns:
    time_diff_seconds (int): The amount of time difference in seconds
```

Definition at line 159 of file c_crawl_Random_Author_Information.py.

def c_crawl_Random_Author_Information.check_script_arguments ()

```
Checks if enough and correct arguments have been given to run this script adequate

1. It checks in the first instance if enough arguments have been given
2. Then necessary variables will be filled with appropriate values

Args:
    -
Returns:
    -
```

Definition at line 17 of file c_crawl_Random_Author_Information.py.

def c_crawl_Random_Author_Information.generate_data_now (*randomized_author_name*)

```
Crawls author information and writes them into the mongoDB database with the name
'iAMA_Reddit_Authors_Random'

It does this by first checking the given crawling direction. The ability to crawl bidirectional
allows you to build
up you database in a much more faster way, because you can start one instance crawling forward while
the other
instance crawls backward.

This method works in the following way:

1. Checks for crawling direction
2. It checks whether an iterated collection is no "system.indexes".
3. By iterating over all collections it checks for iAMA-Requests and skips them. Because we do not
want requests
in our dataset, because we want data of actually created iama threads

4. Now it will be checked whether the author already exists within the database (collection name).
This will be
done by always re-initialising the collection.names() which is necessary to always have a
up2date-overview!

    4.1. Whenever the author does not exist yet get the necessary information and write it into
the database

    4.2. Whenever the author does already exist skip that calculation part

Args:
    -
Returns:
    -
```

Definition at line 107 of file c_crawl_Random_Author_Information.py.

def c_crawl_Random_Author_Information.get_author_information (*name_of_author*)

```
Calculates various information about the author
    Because I have created this script shortly before my evaluation everything listed here is not
outsourced by
    written in a very sequential / procedural way, therefore I ask for you understanding.

    The method does the following:

    1. Referencing a reddit author object, which is necessary to get all that necessary data
    2. Declaration of necessary variables for later assignment
    3. Trial of receiving the authors birthday
        We have to try this here, because, if the account has already been deleted a http error
will be thrown
        and we would have to recrawl all that data.
    4. Receival authors comment / link karma - amount
    5. Trial of receiving of all links / comments the author every made
        Because it could happen, that there is an internal error in reddit ongoing (Error 500) which
will reset
        the connection and therefore we would have to recrawl all of our data
    6. Iteration of all comments / links and therefore saving the time difference (in seconds)
between each created
        comment / link
    7. Calculation of time difference between acc birth & first iama in seconds
    8. Patching up a big dictionary which will be sorted (alphabetically correct)
    9. Return that dictionary

Args:
    name_of_author (str): The name of the author which information need to be calculated
Returns:
    dict_to_be_returned (dict): Dictionary containing various information about the author. It will
be written
```

Definition at line 195 of file c_crawl_Random_Author_Information.py.

def c_crawl_Random_Author_Information.initialize_mongo_db_parameters ()

```
Instantiates all necessary variables for the correct usage of the mongoDB client

Args:
    -
Returns:
    -
```

Definition at line 43 of file c_crawl_Random_Author_Information.py.

def c_crawl_Random_Author_Information.start_data_generation_for_analysis ()

```
Starts the data processing by swichting through the years
    After every year cycle the mongo db parameters will be reinitialized

Args:
    -
Returns:
    -
```

Definition at line 68 of file c_crawl_Random_Author_Information.py.

Variable Documentation

c_crawl_Random_Author_Information.argument_limit_crawling_amount = None

Definition at line 422 of file c_crawl_Random_Author_Information.py.

c_crawl_Random_Author_Information.mongo_db_client_instance = None

Definition at line 425 of file c_crawl_Random_Author_Information.py.

c_crawl_Random_Author_Information.mongo_db_iama_author_collection = None

Definition at line 437 of file c_crawl_Random_Author_Information.py.

int c_crawl_Random_Author_Information.mongo_db_iama_author_collection_amount = 0

Definition at line 440 of file c_crawl_Random_Author_Information.py.

c_crawl_Random_Author_Information.mongo_db_iama_author_instance = None

Definition at line 434 of file c_crawl_Random_Author_Information.py.

c_crawl_Random_Author_Information.mongo_db_random_author_collection = None

Definition at line 431 of file c_crawl_Random_Author_Information.py.

c_crawl_Random_Author_Information.mongo_db_random_author_instance = None

Definition at line 428 of file c_crawl_Random_Author_Information.py.

c_crawl_Random_Author_Information.reddit_instance = praw.Reddit(user_agent="University_Regensburg_iAMA_Crawler_0.001")

Definition at line 443 of file c_crawl_Random_Author_Information.py.

c_crawl_Threads_N_Comments Namespace Reference

Functions

- def initialize_mongo_db_parameters ()
- def check_script_arguments ()
- def convert_argument_year_to_epoch (year)
- def crawl_data ()
- def crawl_threads ()
- def crawl_comments ()
- def check_if_coll_in_db_already_exists_up2date (submission)

Variables

- mongo_DB_Client_Instance = None
- reddit_Instance = None
- argument_crawl_type = None
- argument_year_beginning = None
- argument_year_end = None
- argument_hours_to_shift = None
- time_shift_difference

Function Documentation

def c_crawl_Threads_N_Comments.check_if_coll_in_db_already_exists_up2date (*submission*)

```
Checks if a collection already exists in the database or not

This is necessary, otherwise thread information would be written into the database twice.
It works the following way:

1. Define a tolerance factor (necessary because reddit skews information about the amount of
    "upvotes"). Without defining that tolerance factor every thread would be created anew.
    After messing around a few days I found this one to be the best value to work with

2. Create values for temporary values for checking

3. Check and recreate collection if necessary

4. Return appropriate boolean value if collection already existed within the database or not


Args:
    submission (Submission) : The thread which will be processed / iterated over at the moment
Returns:
    True / False (bool) : Whenever the collection already exists within the database (True) or not
(False)
```

Definition at line 373 of file c_crawl_Threads_N_Comments.py.

def c_crawl_Threads_N_Comments.check_script_arguments ()

```
Checks if enough and correct arguments have been given to run this script adequate

1. It checks in the first instance if enough arguments have been given
2. Then necessary variables will be filled with appropriate values
```

```
Args:
    -
Returns:
    -
```

Definition at line 36 of file c_crawl_Threads_N_Comments.py.

def c_crawl_Threads_N_Comments.convert_argument_year_to_epoch (*year*)

```
"Converts" a given string into the appropriate epoch string format (int)

Args:
    year (str) : The year which will be "converted" into epoch format (necessary for correct PRAW
API behaviour)
Returns:
    year (int) : The year "converted" into epoch format as integer
```

Definition at line 71 of file c_crawl_Threads_N_Comments.py.

def c_crawl_Threads_N_Comments.crawl_comments ()

```
Crawls thread information and writes them into the mongoDB storage
It works as follwoing:

1. At first an attempt to the amazon cloud search will be made, with necessary parameters which
returns an object,
    of the class "Generator" which contains all comments for the given / crawled time windows

2. After that the "Generator"s elements will be iterated over

    2.1. It will be checked if that iterated collection already exists within the database or not

        2.2.1. If it already exists, it will be checked whether if it is up to date or not
            2.2.1.1. If up2date: do nothing
            2.2.1.2. If not up2date: drop that collection within the database and crawl the
collection anew

        2.2.2. If it does not yet exist: create that collection in the database with the necessary
information

3. Whenever there are no elements left to iterate over the time crawling window will be shifted
into the future by
    using the given amount in hours (fourth argument), whenever the ending year (third argument)
is not reached yet

Args:
    -
Returns:
    -
```

Definition at line 258 of file c_crawl_Threads_N_Comments.py.

def c_crawl_Threads_N_Comments.crawl_data ()

```
Crawls data from reddit, depending on the first argument (threads / comments) you give the script

Args:
    -
Returns:
    -
```

Definition at line 121 of file c_crawl_Threads_N_Comments.py.

def c_crawl_Threads_N_Comments.crawl_threads ()

```
Crawls thread information and writes them into the mongoDB storage
It works as follwoing:

1. At first an attempt to the amazon cloud search will be made, with necessary parameters which
returns an object,
    of the class "Generator" which contains all threads for the given / crawled time windows

2. After that the "Generator"s elements will be iterated over

    2.1. It will be checked if that iterated collection already exists within the database or not

        2.2.1. If it already exists, it will be checked whether if it is up to date or not
            2.2.1.1. If up2date: do nothing
            2.2.1.2. If not up2date: drop that collection within the database and crawl the
collection anew

        2.2.2. If it does not yet exist: create that collection in the database with the necessary
information

3. Whenever there are no elements left to iterate over the time crawling window will be shifted
into the future by
    using the given amount in hours (third argument), whenever the ending year (second argument)
is not reached yet

Args:
    -
Returns:
    -
```

Definition at line 140 of file c_crawl_Threads_N_Comments.py.

def c_crawl_Threads_N_Comments.initialize_mongo_db_parameters ()

```
Instantiates all necessary variables for the correct usage of the mongoDB-Client

Args:
    -
Returns:
    -
```

Definition at line 21 of file c_crawl_Threads_N_Comments.py.

Variable Documentation

c_crawl_Threads_N_Comments.argument_crawl_type = None

Definition at line 480 of file c_crawl_Threads_N_Comments.py.

c_crawl_Threads_N_Comments.argument_hours_to_shift = None

Definition at line 496 of file c_crawl_Threads_N_Comments.py.

c_crawl_Threads_N_Comments.argument_year_beginning = None

Definition at line 483 of file c_crawl_Threads_N_Comments.py.

c_crawl_Threads_N_Comments.argument_year_end = None

Definition at line 486 of file c_crawl_Threads_N_Comments.py.

c_crawl_Threads_N_Comments.mongo_DB_Client_Instance = None

Definition at line 474 of file c_crawl_Threads_N_Comments.py.

c_crawl_Threads_N_Comments.reddit_Instance = None

Definition at line 477 of file c_crawl_Threads_N_Comments.py.

c_crawl_Threads_N_Comments.time_shift_difference

```
Initial value:    1 = int(
    2     round(time.mktime(
    3         (datetime.fromtimestamp(argument_year_beginning) +
    4          timedelta(
    5              hours=argument_hours_to_shift)
    6          ).timetuple()
    7     )
    8     )
    9 )
```

Definition at line 516 of file c_crawl_Threads_N_Comments.py.

d_create_Big_CSV_ar Namespace Reference

Functions

- def check_script_arguments ()
- def initialize_mongo_db_parameters (actually_processed_year)
- def start_data_generation_for_analysis ()
- def generate_data ()
- def process_specific_thread (thread_id, thread_creation_time_stamp, thread_author)
- def check_if_comment_is_a_question (given_string)
- def check_if_comment_is_on_tier_1 (comment_parent_id)
- def check_if_comment_is_not_from_thread_author (author_of_thread, comment_author)
- def check_if_comment_has_been_answered_by_thread_author (author_of_thread, comment_actual_id, comments_cursor)
- def calculate_time_difference (comment_time_stamp, answer_time_stamp_iama_host)
- def calculate_reaction_time_average (list_to_be_processed, thread_creation_time_stamp)
- def calculate_life_span (thread_creation_time_stamp, time_value_of_last_comment, time_value_of_last_question)
- def add_actual_year_list_to_global_list (list_to_append)
- def write_csv_data (list_with_information)

Variables

- int argument_year_beginning = 0
- int argument_year_ending = 0
- int year_actually_in_progress = 0
- list list_current_year = []
- list list_global_year = []

Function Documentation

def d_create_Big_CSV_ar.add_actual_year_list_to_global_list (*list_to_append*)

```
Iterates over a given list with thread information and adds every single element to a global list
    The global list will be printed to csv in the end

Args:
    list_to_append (list) : List with thread information which will be appended to a global list
Returns:
    -
```

Definition at line 1028 of file d_create_Big_CSV_ar.py.

def d_create_Big_CSV_ar.calculate_life_span (*thread_creation_time_stamp*, *time_value_of_last_comment*, *time_value_of_last_question*)

```
Calculates the life span between to time stamps

1. The creation date of a thread gets determined
2. Then the comments will be iterated over, creating a dictionary which is structured as follows:
  {
      ('first_Comment_After_Thread_Started', int),
      ('thread_life_span', int),
      ('arithmetic_Mean_Response_Time', int),
```

```
      ('median_Response_Time', int),
      ('id')
  }
3. That returned dictionary will be appended to a global list
4. That List will be iterated later on and the appropriate graph will be plotted

Args:
    thread_creation_time_stamp (float) : The time stamp (utc epoch) of the thread creation
    time value of last comment (float) : The time stamp (utc epoch) of the threads last comment
    time_value_of_last_question (float) : The time stamp (utc epoch) of the threads last question
Returns:
    dict_to_be_returned (dict) : Containing information about the time differences:
        Thread creation timestamp <-> Last question time stamp
```

Thread creation timestamp <-> Last comment time stamp

Definition at line 973 of file d_create_Big_CSV_ar.py.

def d_create_Big_CSV_ar.calculate_reaction_time_average (*list_to_be_processed*, *thread_creation_time_stamp*)

```
Calculates the reaction time of a list with time values in it

Args:
    list to be processed (list) : The list which contains time values (utc epoch)
    thread_creation_time_stamp (str) : The string which contains the creation date of the thread
(utc epoch)
Returns:
    None : Whenever there were no time values given
```

np.mean(time_difference) (float) : Time arithmetic mean of the reaction time in seconds

Definition at line 889 of file d_create_Big_CSV_ar.py.

def d_create_Big_CSV_ar.calculate_time_difference (*comment_time_stamp*, *answer_time_stamp_iama_host*)

```
Calculates the time difference in seconds between the a comment and its answer from the iama host

1. The time stamps will be converted from epoch
    into float and afterwards into str again
    (necessary for correct subtraction)
2. Then the time stamps will be subtracted from each other
3. The containing time difference will be converted into seconds (int)

Args:
    comment_time_stamp (str): The time stamp of the comment
    answer_time_stamp_iama_host (str): The time stamp of the iAMA hosts answer
Returns:
    time_difference_in_seconds (int) : The time difference of the comment and its answer by the
iAMA host in seconds
```

Definition at line 850 of file d_create_Big_CSV_ar.py.

def d_create_Big_CSV_ar.check_if_comment_has_been_answered_by_thread_author (*author_of_thread*, *comment_actual_id*, *comments_cursor*)

```
Checks whether both strings are equal or not

1. A dictionary containing flags whether that a question is answered by the host with the appropriate
timestamp will
    be created in the beginning.
2. Then the method iterates over every comment within that thread
    1.1. Whenever an answer is from the iAMA hosts and the processed comments 'parent_id' matches
the iAMA hosts
```

```
        comments (answers) id, the returned dict will contain appropriate values and will be
returned
    1.2. If this is not the case, it will be returned in its default condition

Note: We take a list as 'comments cursor' and not a real cursor, because real cursors can be
exhausted, which
        could lead to, that not all comments will be iterated.. This is especially critical when
you have to do
        many iterations with only one cursor... [took me 8 hours to figure this "bug" out...]

Args:
    author_of_thread (str) : The name of the thread author (iAMA-Host)
    comment_actual_id (str) : The id of the actually processed comment
    comments_cursor (list) : The list containing all comments
Returns:
    True (bool): Whenever the strings do not match
    False (bool): Whenever the strings do match
     answered that given question)
```

Definition at line 802 of file d_create_Big_CSV_ar.py.

def d_create_Big_CSV_ar.check_if_comment_is_a_question (*given_string*)

```
Simply checks whether a given string is a question or not

This method simply checks wether a question mark exists within that string or not..
    This is just that simple because messing around with natural processing kits to determine the
semantic sense
    would blow up my bachelor work...

Args:
    given_string (int) : The string which will be checked for a question mark
Returns:
    True (bool): Whenever the given string is a question
```

False (bool): Whenever the given string is not a question

Definition at line 745 of file d_create_Big_CSV_ar.py.

def d_create_Big_CSV_ar.check_if_comment_is_not_from_thread_author (*author_of_thread*, *comment_author*)

```
Checks whether both strings are equal or not

1. This method simply checks wether both strings match each other or not.
    I have built this extra method to have a better overview in the main code..

Args:
    author_of_thread (str) : The name of the thread author (iAMA-Host)
    comment author (str) : The name of the comments author
Returns:
    True (bool): Whenever the strings do not match
    False (bool): Whenever the strings do match
     answered that given question)
```

Definition at line 782 of file d_create_Big_CSV_ar.py.

def d_create_Big_CSV_ar.check_if_comment_is_on_tier_1 (*comment_parent_id*)

```
Checks whether a comment relies on the first tier or any other tier

Args:
    comment_parent_id (str) : The name id of the comments parent
Returns:
```

```
    True (bool): Whenever the comment lies on tier 1
    False (bool): Whenever the comment lies on any other tier
```

Definition at line 766 of file d_create_Big_CSV_ar.py.

def d_create_Big_CSV_ar.check_script_arguments ()

```
Checks if enough and correct arguments have been given to run this script adequate

1. It checks in the first instance if enough arguments have been given
2. Then necessary variables will be filled with appropriate values

Args:
    -
Returns:
    -
```

Definition at line 20 of file d_create_Big_CSV_ar.py.

def d_create_Big_CSV_ar.generate_data ()

```
Starts calculating various information about thread and iama behaviour related to the year which
is currently
    being processed

After the caluclations have every iteration the results will ber appended to a list, which will
contain all that
    information for the current year... That list will be writtend to csv and appended to a global
list in other
    methods

Args:
    -
Returns:
    -
```

Definition at line 105 of file d_create_Big_CSV_ar.py.

def d_create_Big_CSV_ar.initialize_mongo_db_parameters (*actually_processed_year*)

```
Instantiates all necessary variables for the correct usage of the mongoDB-Client

Args:
    actually_processed_year (int) : The year with which parameters the database should be accessed
Returns:
    -
```

Definition at line 45 of file d_create_Big_CSV_ar.py.

def d_create_Big_CSV_ar.process_specific_thread (*thread_id*, *thread_creation_time_stamp*, *thread_author*)

```
Does the needed operations, for gaining information / knowledge about threads on the given thread
id

After the caluclations have every iteration the results will ber appended to a list, which will
contain all that
    information for the current year... That list will be writtend to csv and appended to a global
list in other
```

```
    methods

Args:
    thread_id (str) : The id, needed for operating (i.E. comparison of parent - child relation)
    thread creation time stamp (int) : Creation time stamp of thread, needed for time difference
calculation
    thread_author (str): The name of the threads author, needed for answer checking of a post
Returns:
    -
```

Definition at line 260 of file d_create_Big_CSV_ar.py.

def d_create_Big_CSV_ar.start_data_generation_for_analysis ()

```
Starts the whole combination of generating data, checking data and writing them into csv files

1. Triggers the data generation process and moves forward within the years -
    by moving through the years a csv file will be created for every year

Args:
    -
Returns:
    -
```

Definition at line 65 of file d_create_Big_CSV_ar.py.

def d_create_Big_CSV_ar.write_csv_data (*list_with_information*)

```
Creates a csv file containing all necessary information about the thread and its mannerism to do
research on

Args:
    list with information (list) : Contains various information about threads mannerism
Returns:
    -
```

Definition at line 1044 of file d_create_Big_CSV_ar.py.

Variable Documentation

int d_create_Big_CSV_ar.argument_year_beginning = 0

Definition at line 1203 of file d_create_Big_CSV_ar.py.

int d_create_Big_CSV_ar.argument_year_ending = 0

Definition at line 1206 of file d_create_Big_CSV_ar.py.

list d_create_Big_CSV_ar.list_current_year = []

Definition at line 1212 of file d_create_Big_CSV_ar.py.

list d_create_Big_CSV_ar.list_global_year = []

Definition at line 1215 of file d_create_Big_CSV_ar.py.

int d_create_Big_CSV_ar.year_actually_in_progress = 0

Definition at line 1209 of file d_create_Big_CSV_ar.py.

d_create_Big_CSV_med Namespace Reference

Functions

- def check_script_arguments ()
- def initialize_mongo_db_parameters (actually_processed_year)
- def start_data_generation_for_analysis ()
- def generate_data ()
- def process_specific_thread (thread_id, thread_creation_time_stamp, thread_author)
- def check_if_comment_is_a_question (given_string)
- def check_if_comment_is_on_tier_1 (comment_parent_id)
- def check_if_comment_is_not_from_thread_author (author_of_thread, comment_author)
- def check_if_comment_has_been_answered_by_thread_author (author_of_thread, comment_actual_id, comments_cursor)
- def calculate_time_difference (comment_time_stamp, answer_time_stamp_iama_host)
- def calculate_reaction_time_average (list_to_be_processed, thread_creation_time_stamp)
- def calculate_life_span (thread_creation_time_stamp, time_value_of_last_comment, time_value_of_last_question)
- def add_actual_year_list_to_global_list (list_to_append)
- def write_csv_data (list_with_information)

Variables

- int argument_year_beginning = 0
- int argument_year_ending = 0
- int year_actually_in_progress = 0
- list list_current_year = []
- list list_global_year = []

Function Documentation

def d_create_Big_CSV_med.add_actual_year_list_to_global_list (*list_to_append*)

```
Iterates over a given list with thread information and adds every single element to a global list
    The global list will be printed to csv in the end

Args:
    list_to_append (list) : List with thread information which will be appended to a global list
Returns:
    -
```

Definition at line 1028 of file d_create_Big_CSV_med.py.

def d_create_Big_CSV_med.calculate_life_span (*thread_creation_time_stamp*, *time_value_of_last_comment*, *time_value_of_last_question*)

```
Calculates the life span between to time stamps

1. The creation date of a thread gets determined
2. Then the comments will be iterated over, creating a dictionary which is structured as follows:
  {
      ('first_Comment_After_Thread_Started', int),
      ('thread_life_span', int),
      ('arithmetic_Mean_Response_Time', int),
```

```
      ('median_Response_Time', int),
      ('id')
  }
3. That returned dictionary will be appended to a global list
4. That List will be iterated later on and the appropriate graph will be plotted

Args:
    thread_creation_time_stamp (float) : The time stamp (utc epoch) of the thread creation
    time value of last comment (float) : The time stamp (utc epoch) of the threads last comment
    time_value_of_last_question (float) : The time stamp (utc epoch) of the threads last question
Returns:
    dict_to_be_returned (dict) : Containing information about the time differences:
        Thread creation timestamp <-> Last question time stamp
```

Thread creation timestamp <-> Last comment time stamp

Definition at line 973 of file d_create_Big_CSV_med.py.

def d_create_Big_CSV_med.calculate_reaction_time_average (*list_to_be_processed*, *thread_creation_time_stamp*)

```
Calculates the reaction time of a list with time values in it

Args:
    list to be processed (list) : The list which contains time values (utc epoch)
    thread_creation_time_stamp (str) : The string which contains the creation date of the thread
(utc epoch)
Returns:
    None : Whenever there were no time values given
```

np.median(time_difference) (float) : Time arithmetic median of the reaction time in seconds

Definition at line 889 of file d_create_Big_CSV_med.py.

def d_create_Big_CSV_med.calculate_time_difference (*comment_time_stamp*, *answer_time_stamp_iama_host*)

```
Calculates the time difference in seconds between the a comment and its answer from the iama host

1. The time stamps will be converted from epoch
    into float and afterwards into str again
    (necessary for correct subtraction)
2. Then the time stamps will be subtracted from each other
3. The containing time difference will be converted into seconds (int)

Args:
    comment_time_stamp (str): The time stamp of the comment
    answer_time_stamp_iama_host (str): The time stamp of the iAMA hosts answer
Returns:
    time_difference_in_seconds (int) : The time difference of the comment and its answer by the
iAMA host in seconds
```

Definition at line 850 of file d_create_Big_CSV_med.py.

def d_create_Big_CSV_med.check_if_comment_has_been_answered_by_thread_author (*author_of_thread*, *comment_actual_id*, *comments_cursor*)

```
Checks whether both strings are equal or not

1. A dictionary containing flags whether that a question is answered by the host with the appropriate
timestamp will
    be created in the beginning.
2. Then the method iterates over every comment within that thread
    1.1. Whenever an answer is from the iAMA hosts and the processed comments 'parent_id' matches
the iAMA hosts
```

```
        comments (answers) id, the returned dict will contain appropriate values and will be
returned
    1.2. If this is not the case, it will be returned in its default condition

Note: We take a list as 'comments cursor' and not a real cursor, because real cursors can be
exhausted, which
        could lead to, that not all comments will be iterated.. This is especially critical when
you have to do
        many iterations with only one cursor... [took me 8 hours to figure this "bug" out...]

Args:
    author_of_thread (str) : The name of the thread author (iAMA-Host)
    comment_actual_id (str) : The id of the actually processed comment
    comments_cursor (list) : The list containing all comments
Returns:
    True (bool): Whenever the strings do not match
    False (bool): Whenever the strings do match
     answered that given question)
```

Definition at line 802 of file d_create_Big_CSV_med.py.

def d_create_Big_CSV_med.check_if_comment_is_a_question (*given_string*)

```
Simply checks whether a given string is a question or not

This method simply checks wether a question mark exists within that string or not..
    This is just that simple because messing around with natural processing kits to determine the
semantic sense
    would blow up my bachelor work...

Args:
    given_string (int) : The string which will be checked for a question mark
Returns:
    True (bool): Whenever the given string is a question
```

False (bool): Whenever the given string is not a question

Definition at line 745 of file d_create_Big_CSV_med.py.

def d_create_Big_CSV_med.check_if_comment_is_not_from_thread_author (*author_of_thread*, *comment_author*)

```
Checks whether both strings are equal or not

1. This method simply checks wether both strings match each other or not.
    I have built this extra method to have a better overview in the main code..

Args:
    author_of_thread (str) : The name of the thread author (iAMA-Host)
    comment author (str) : The name of the comments author
Returns:
    True (bool): Whenever the strings do not match
    False (bool): Whenever the strings do match
     answered that given question)
```

Definition at line 782 of file d_create_Big_CSV_med.py.

def d_create_Big_CSV_med.check_if_comment_is_on_tier_1 (*comment_parent_id*)

```
Checks whether a comment relies on the first tier or any other tier

Args:
    comment_parent_id (str) : The name id of the comments parent
Returns:
```

```
    True (bool): Whenever the comment lies on tier 1
    False (bool): Whenever the comment lies on any other tier
```

Definition at line 766 of file d_create_Big_CSV_med.py.

def d_create_Big_CSV_med.check_script_arguments ()

```
Checks if enough and correct arguments have been given to run this script adequate

1. It checks in the first instance if enough arguments have been given
2. Then necessary variables will be filled with appropriate values

Args:
    -
Returns:
    -
```

Definition at line 20 of file d_create_Big_CSV_med.py.

def d_create_Big_CSV_med.generate_data ()

```
Starts calculating various information about thread and iama behaviour related to the year which
is currently
    being processed

After the caluclations have every iteration the results will ber appended to a list, which will
contain all that
    information for the current year... That list will be writtend to csv and appended to a global
list in other
    methods

Args:
    -
Returns:
    -
```

Definition at line 105 of file d_create_Big_CSV_med.py.

def d_create_Big_CSV_med.initialize_mongo_db_parameters (*actually_processed_year*)

```
Instantiates all necessary variables for the correct usage of the mongoDB-Client

Args:
    actually_processed_year (int) : The year with which parameters the database should be accessed
Returns:
    -
```

Definition at line 45 of file d_create_Big_CSV_med.py.

def d_create_Big_CSV_med.process_specific_thread (*thread_id*, *thread_creation_time_stamp*, *thread_author*)

```
Does the needed operations, for gaining information / knowledge about threads on the given thread
id

After the caluclations have every iteration the results will ber appended to a list, which will
contain all that
    information for the current year... That list will be writtend to csv and appended to a global
list in other
```

```
    methods

Args:
    thread_id (str) : The id, needed for operating (i.E. comparison of parent - child relation)
    thread creation time stamp (int) : Creation time stamp of thread, needed for time difference
calculation
    thread_author (str): The name of the threads author, needed for answer checking of a post
Returns:
    -
```

Definition at line 260 of file d_create_Big_CSV_med.py.

def d_create_Big_CSV_med.start_data_generation_for_analysis ()

```
Starts the whole combination of generating data, checking data and writing them into csv files

1. Triggers the data generation process and moves forward within the years -
    by moving through the years a csv file will be created for every year

Args:
    -
Returns:
    -
```

Definition at line 65 of file d_create_Big_CSV_med.py.

def d_create_Big_CSV_med.write_csv_data (*list_with_information*)

```
Creates a csv file containing all necessary information about the thread and its mannerism to do
research on

Args:
    list with information (list) : Contains various information about threads mannerism
Returns:
    -
```

Definition at line 1044 of file d_create_Big_CSV_med.py.

Variable Documentation

int d_create_Big_CSV_med.argument_year_beginning = 0

Definition at line 1203 of file d_create_Big_CSV_med.py.

int d_create_Big_CSV_med.argument_year_ending = 0

Definition at line 1206 of file d_create_Big_CSV_med.py.

list d_create_Big_CSV_med.list_current_year = []

Definition at line 1212 of file d_create_Big_CSV_med.py.

list d_create_Big_CSV_med.list_global_year = []

Definition at line 1215 of file d_create_Big_CSV_med.py.

int d_create_Big_CSV_med.year_actually_in_progress = 0

Definition at line 1209 of file d_create_Big_CSV_med.py.

PlotlyBarChart Namespace Reference

Classes

- class PlotlyBarChart

PlotlyBarChart_5_Bars Namespace Reference

Classes

- class PlotlyBarChart5Bars

Class Documentation

PlotlyBarChart.PlotlyBarChart Class Reference

Public Member Functions

- def __init__ (self)
- def main_method (self, list_of_calculated_data)

Static Public Member Functions

- def fill_x_axis_list (list_of_calculated_data)
- def fill_y_axis_answered_list (list_of_calculated_data)
- def fill_y_axis_unanswered_list (list_of_calculated_data)
- def fill_bar_percentages_values (list_of_calculated_data)
- def fill_chart_title_description (list_of_calculated_data)
- def fill_bar_description (list_of_calculated_data)
- def generate_chart ()

Static Public Attributes

- time_now_date = time.strftime("%d.%m.%Y")
- time_now_time = time.strftime("%H:%M:%S")
- string bar_x_axis_text = 'Chart creation date: '
- string chart_title = ""
- list bar_value_description = []
- list bar_x_axis_values = []
- list bar_y_axis_first_values = []
- list bar_y_axis_second_values = []
- list bar_first_n_second_values_percentage = []

Detailed Description

```
The class to create a stacked bar chart.
    This class is heavily modified because it pyplot normally is not designed to run offline this way..

Args:
    -
Returns:
    -
```

Definition at line 13 of file PlotlyBarChart.py.

Constructor & Destructor Documentation

def PlotlyBarChart.PlotlyBarChart.__init__ (*self*)

```
Instanciates the class

Args:
    -
```

```
Returns:
    -
```

Definition at line 44 of file PlotlyBarChart.py.

Member Function Documentation

def PlotlyBarChart.PlotlyBarChart.fill_bar_description (*list_of_calculated_data*) [static]

```
Defines the bar description in dependence to given parameters list_of_calculated_data[0][0]

Args:
    list_of_calculated_data (list) : Will be accessed to gain necessary values
Returns:
    -
```

Definition at line 208 of file PlotlyBarChart.py.

def PlotlyBarChart.PlotlyBarChart.fill_bar_percentages_values (*list_of_calculated_data*) [static]

```
Calculates percentages to be shown within the graph..
    This is not supported within pyplot under normal circumstances.. so we're tricking the HTML
settings

Args:
    list_of_calculated_data (list) : Will be iterated to gain necessary values
Returns:
    -
```

Definition at line 129 of file PlotlyBarChart.py.

def PlotlyBarChart.PlotlyBarChart.fill_chart_title_description (*list_of_calculated_data*) [static]

```
Defines the chart title in dependence to sorting method and processed years

Args:
    list_of_calculated_data (list) : Will be accessed to gain necessary values
Returns:
    -
```

Definition at line 160 of file PlotlyBarChart.py.

def PlotlyBarChart.PlotlyBarChart.fill_x_axis_list (*list_of_calculated_data*) [static]

```
Fills the "x axis" with the values of the years

Args:
    list of calculated data (list) : Will be iterated to gain necessary values
Returns:
    -
```

Definition at line 81 of file PlotlyBarChart.py.

def PlotlyBarChart.PlotlyBarChart.fill_y_axis_answered_list (*list_of_calculated_data*) [static]

```
Fills an bar within the chart with values of the amount of unanswered questions

Args:
    list_of_calculated_data (list) : Will be iterated to gain necessary values
Returns:
    -
```

Definition at line 97 of file PlotlyBarChart.py.

def PlotlyBarChart.PlotlyBarChart.fill_y_axis_unanswered_list (*list_of_calculated_data*) [static]

```
Fills an bar within the chart with values of the amount of unanswered questions

Args:
    list_of_calculated_data (list) : Will be iterated to gain necessary values
Returns:
    -
```

Definition at line 113 of file PlotlyBarChart.py.

def PlotlyBarChart.PlotlyBarChart.generate_chart () [static]

```
Generates the chart "temp-plot.html" which will be automatically opened within the browser

Args:
    -
Returns:
    -
```

Definition at line 235 of file PlotlyBarChart.py.

def PlotlyBarChart.PlotlyBarChart.main_method (*self*, *list_of_calculated_data*)

```
Sequential fills the necessary varibales for the graph
Structure of list of calculated data:

[ "sorting", [year, answered, unanswered], [year, answered, unanswered], ... ]
i.e. ["top",
      [2009, 900, 1536],
      [2010, 500, 500],
      [2011, 300, 700]
      ]

Args:
    list_of_calculated_data (list): Contains sorting method, and the years data
Returns:
    -
```

Definition at line 55 of file PlotlyBarChart.py.

Member Data Documentation

list PlotlyBarChart.PlotlyBarChart.bar_first_n_second_values_percentage = [] `[static]`

Definition at line 42 of file PlotlyBarChart.py.

list PlotlyBarChart.PlotlyBarChart.bar_value_description = [] `[static]`

Definition at line 32 of file PlotlyBarChart.py.

string PlotlyBarChart.PlotlyBarChart.bar_x_axis_text = 'Chart creation date: ' `[static]`

Definition at line 26 of file PlotlyBarChart.py.

list PlotlyBarChart.PlotlyBarChart.bar_x_axis_values = [] `[static]`

Definition at line 33 of file PlotlyBarChart.py.

list PlotlyBarChart.PlotlyBarChart.bar_y_axis_first_values = [] `[static]`

Definition at line 36 of file PlotlyBarChart.py.

list PlotlyBarChart.PlotlyBarChart.bar_y_axis_second_values = [] `[static]`

Definition at line 39 of file PlotlyBarChart.py.

string PlotlyBarChart.PlotlyBarChart.chart_title = "" `[static]`

Definition at line 29 of file PlotlyBarChart.py.

PlotlyBarChart.PlotlyBarChart.time_now_date = time.strftime("%d.%m.%Y") `[static]`

Definition at line 23 of file PlotlyBarChart.py.

PlotlyBarChart.PlotlyBarChart.time_now_time = time.strftime("%H:%M:%S") `[static]`

Definition at line 24 of file PlotlyBarChart.py.

The documentation for this class was generated from the following file:

- PlotlyBarChart.py

PlotlyBarChart_5_Bars.PlotlyBarChart5Bars Class Reference

Public Member Functions

- def __init__ (self)
- def main_method (self, list_of_calculated_data)

Static Public Member Functions

- def fill_x_axis_list (list_of_calculated_data)
- def fill_y_axis_values (list_of_calculated_data)
- def fill_bar_percentages_values (list_of_calculated_data)
- def fill_chart_title_description (list_of_calculated_data)
- def fill_bar_description (list_of_calculated_data)
- def fill_bar_annotations ()
- def generate_chart ()

Static Public Attributes

- string color_1 = 'rgba(255, 114, 86, 1.0)'
- string color_1_border = 'rgba(238, 106, 80, 1.0)'
- string color_2 = 'rgba(238, 118, 0, 1.0)'
- string color_2_border = 'rgba(205, 102, 0, 1.0)'
- string color_3 = 'rgba(0, 201, 87, 1.0)'
- string color_3_border = 'rgba(0, 139, 0, 1.0)'
- string color_4 = 'rgba(0, 205, 205, 1.0)'
- string color_4_border = 'rgba(0, 139, 139, 1.0)'
- string color_5 = 'rgba(137, 104, 205, 1.0)'
- string color_5_border = 'rgba(39, 71, 139, 1.0)'
- time_now_date = time.strftime("%d.%m.%Y")
- time_now_time = time.strftime("%H:%M:%S")
- string bar_x_axis_text = 'Chart creation date: '
- string chart_title = ""
- list bar_value_description = []
- list bar_x_axis_values = []
- list bar_y_axis_first_values = []
- list bar_y_axis_second_values = []
- list bar_y_axis_third_values = []
- list bar_y_axis_fourth_values = []
- list bar_y_axis_fifth_values = []
- list bar_percentages_values_1 = []
- list bar_percentages_values_2 = []
- list bar_percentages_values_3 = []
- list bar_percentages_values_4 = []
- list bar_percentages_values_5 = []
- list annotations_1 = []
- list annotations_2 = []
- list annotations_3 = []
- list annotations_4 = []
- list annotations_5 = []
- list annotations_all = []

Detailed Description

```
The class to create a stacked bar chart.
    This class is heavily modified because it pyplot normally is not designed to run offline this way..

Args:
    -
Returns:
    -
```

Definition at line 13 of file PlotlyBarChart_5_Bars.py.

Constructor & Destructor Documentation

def PlotlyBarChart_5_Bars.PlotlyBarChart5Bars.__init__ (*self*)

```
Instanciates the class

Args:
    -
Returns:
    -
```

Definition at line 71 of file PlotlyBarChart_5_Bars.py.

Member Function Documentation

def PlotlyBarChart_5_Bars.PlotlyBarChart5Bars.fill_bar_annotations () `[static]`

Definition at line 291 of file PlotlyBarChart_5_Bars.py.

def PlotlyBarChart_5_Bars.PlotlyBarChart5Bars.fill_bar_description (*list_of_calculated_data*) `[static]`

```
Defines the bar description in dependence to given parameters list_of_calculated_data[0][0]

Args:
    list_of_calculated_data (list) : Will be accessed to gain necessary values
Returns:
    -
```

Definition at line 246 of file PlotlyBarChart_5_Bars.py.

def PlotlyBarChart_5_Bars.PlotlyBarChart5Bars.fill_bar_percentages_values (*list_of_calculated_data*) `[static]`

```
Calculates percentages to be shown within the graph..
    This is not supported within pyplot under normal circumstances.. so we're tricking the HTML
settings

Args:
    list_of_calculated_data (list) : Will be iterated to gain necessary values
```

```
Returns:
    -
```

Definition at line 144 of file PlotlyBarChart_5_Bars.py.

def PlotlyBarChart_5_Bars.PlotlyBarChart5Bars.fill_chart_title_description (*list_of_calculated_data*) `[static]`

```
Defines the chart title in dependence to sorting method and processed years

Args:
    list_of_calculated_data (list) : Will be accessed to gain necessary values
Returns:
    -
```

Definition at line 189 of file PlotlyBarChart_5_Bars.py.

def PlotlyBarChart_5_Bars.PlotlyBarChart5Bars.fill_x_axis_list (*list_of_calculated_data*) `[static]`

```
Fills the "x axis" with the values of the years

Args:
    list of calculated data (list) : Will be iterated to gain necessary values
Returns:
    -
```

Definition at line 108 of file PlotlyBarChart_5_Bars.py.

def PlotlyBarChart_5_Bars.PlotlyBarChart5Bars.fill_y_axis_values (*list_of_calculated_data*) `[static]`

```
Fills an bar within the chart with values of the amount of unanswered questions

Args:
    list of calculated data (list) : Will be iterated to gain necessary values
Returns:
    -
```

Definition at line 124 of file PlotlyBarChart_5_Bars.py.

def PlotlyBarChart_5_Bars.PlotlyBarChart5Bars.generate_chart () `[static]`

```
Generates the chart "temp-plot.html" which will be automatically opened within the browser

Args:
    -
Returns:
    -
```

Definition at line 393 of file PlotlyBarChart_5_Bars.py.

def PlotlyBarChart_5_Bars.PlotlyBarChart5Bars.main_method (*self*, *list_of_calculated_data*)

```
Sequential fills the necessary varibales for the graph
Structure of list_of_calculated_data:

[ "sorting", [year, answered, unanswered], [year, answered, unanswered], ... ]
i.e. ["top",
      [2009, 900, 1536],
      [2010, 500, 500],
      [2011, 300, 700]
      ]

Args:
    list_of_calculated_data (list): Contains sorting method, and the years data
Returns:
    -
```

Definition at line 82 of file PlotlyBarChart_5_Bars.py.

Member Data Documentation

list PlotlyBarChart_5_Bars.PlotlyBarChart5Bars.annotations_1 = [] [static]

Definition at line 64 of file PlotlyBarChart_5_Bars.py.

list PlotlyBarChart_5_Bars.PlotlyBarChart5Bars.annotations_2 = [] [static]

Definition at line 65 of file PlotlyBarChart_5_Bars.py.

list PlotlyBarChart_5_Bars.PlotlyBarChart5Bars.annotations_3 = [] [static]

Definition at line 66 of file PlotlyBarChart_5_Bars.py.

list PlotlyBarChart_5_Bars.PlotlyBarChart5Bars.annotations_4 = [] [static]

Definition at line 67 of file PlotlyBarChart_5_Bars.py.

list PlotlyBarChart_5_Bars.PlotlyBarChart5Bars.annotations_5 = [] [static]

Definition at line 68 of file PlotlyBarChart_5_Bars.py.

list PlotlyBarChart_5_Bars.PlotlyBarChart5Bars.annotations_all = [] [static]

Definition at line 69 of file PlotlyBarChart_5_Bars.py.

list PlotlyBarChart_5_Bars.PlotlyBarChart5Bars.bar_percentages_values_1 = [] [static]

Definition at line 58 of file PlotlyBarChart_5_Bars.py.

list PlotlyBarChart_5_Bars.PlotlyBarChart5Bars.bar_percentages_values_2 = [] [static]

Definition at line 59 of file PlotlyBarChart_5_Bars.py.

list PlotlyBarChart_5_Bars.PlotlyBarChart5Bars.bar_percentages_values_3 = [] `[static]`

Definition at line 60 of file PlotlyBarChart_5_Bars.py.

list PlotlyBarChart_5_Bars.PlotlyBarChart5Bars.bar_percentages_values_4 = [] `[static]`

Definition at line 61 of file PlotlyBarChart_5_Bars.py.

list PlotlyBarChart_5_Bars.PlotlyBarChart5Bars.bar_percentages_values_5 = [] `[static]`

Definition at line 62 of file PlotlyBarChart_5_Bars.py.

list PlotlyBarChart_5_Bars.PlotlyBarChart5Bars.bar_value_description = [] `[static]`

Definition at line 47 of file PlotlyBarChart_5_Bars.py.

string PlotlyBarChart_5_Bars.PlotlyBarChart5Bars.bar_x_axis_text = 'Chart creation date: ' `[static]`

Definition at line 41 of file PlotlyBarChart_5_Bars.py.

list PlotlyBarChart_5_Bars.PlotlyBarChart5Bars.bar_x_axis_values = [] `[static]`

Definition at line 49 of file PlotlyBarChart_5_Bars.py.

list PlotlyBarChart_5_Bars.PlotlyBarChart5Bars.bar_y_axis_fifth_values = [] `[static]`

Definition at line 55 of file PlotlyBarChart_5_Bars.py.

list PlotlyBarChart_5_Bars.PlotlyBarChart5Bars.bar_y_axis_first_values = [] `[static]`

Definition at line 51 of file PlotlyBarChart_5_Bars.py.

list PlotlyBarChart_5_Bars.PlotlyBarChart5Bars.bar_y_axis_fourth_values = [] `[static]`

Definition at line 54 of file PlotlyBarChart_5_Bars.py.

list PlotlyBarChart_5_Bars.PlotlyBarChart5Bars.bar_y_axis_second_values = [] `[static]`

Definition at line 52 of file PlotlyBarChart_5_Bars.py.

list PlotlyBarChart_5_Bars.PlotlyBarChart5Bars.bar_y_axis_third_values = [] `[static]`

Definition at line 53 of file PlotlyBarChart_5_Bars.py.

string PlotlyBarChart_5_Bars.PlotlyBarChart5Bars.chart_title = "" [static]

Definition at line 44 of file PlotlyBarChart_5_Bars.py.

string PlotlyBarChart_5_Bars.PlotlyBarChart5Bars.color_1 = 'rgba(255, 114, 86, 1.0)' [static]

Definition at line 23 of file PlotlyBarChart_5_Bars.py.

string PlotlyBarChart_5_Bars.PlotlyBarChart5Bars.color_1_border = 'rgba(238, 106, 80, 1.0)' [static]

Definition at line 24 of file PlotlyBarChart_5_Bars.py.

string PlotlyBarChart_5_Bars.PlotlyBarChart5Bars.color_2 = 'rgba(238, 118, 0, 1.0)' [static]

Definition at line 26 of file PlotlyBarChart_5_Bars.py.

string PlotlyBarChart_5_Bars.PlotlyBarChart5Bars.color_2_border = 'rgba(205, 102, 0, 1.0)' [static]

Definition at line 27 of file PlotlyBarChart_5_Bars.py.

string PlotlyBarChart_5_Bars.PlotlyBarChart5Bars.color_3 = 'rgba(0, 201, 87, 1.0)' [static]

Definition at line 29 of file PlotlyBarChart_5_Bars.py.

string PlotlyBarChart_5_Bars.PlotlyBarChart5Bars.color_3_border = 'rgba(0, 139, 0, 1.0)' [static]

Definition at line 30 of file PlotlyBarChart_5_Bars.py.

string PlotlyBarChart_5_Bars.PlotlyBarChart5Bars.color_4 = 'rgba(0, 205, 205, 1.0)' [static]

Definition at line 32 of file PlotlyBarChart_5_Bars.py.

string PlotlyBarChart_5_Bars.PlotlyBarChart5Bars.color_4_border = 'rgba(0, 139, 139, 1.0)' [static]

Definition at line 33 of file PlotlyBarChart_5_Bars.py.

string PlotlyBarChart_5_Bars.PlotlyBarChart5Bars.color_5 = 'rgba(137, 104, 205, 1.0)' [static]

Definition at line 35 of file PlotlyBarChart_5_Bars.py.

string PlotlyBarChart_5_Bars.PlotlyBarChart5Bars.color_5_border = 'rgba(39, 71, 139, 1.0)' `[static]`

Definition at line 36 of file PlotlyBarChart_5_Bars.py.

PlotlyBarChart_5_Bars.PlotlyBarChart5Bars.time_now_date = time.strftime("%d.%m.%Y") `[static]`

Definition at line 38 of file PlotlyBarChart_5_Bars.py.

PlotlyBarChart_5_Bars.PlotlyBarChart5Bars.time_now_time = time.strftime("%H:%M:%S") `[static]`

Definition at line 39 of file PlotlyBarChart_5_Bars.py.

The documentation for this class was generated from the following file:

- PlotlyBarChart_5_Bars.py

File Documentation

a__everything_Big_CSV_analyzer.py File Reference

Namespaces

- a__everything_Big_CSV_analyzer

Functions

- def a__everything_Big_CSV_analyzer.relation_question_upvotes_with_amount_of_questions_answered_by_iama_host ()
- def a__everything_Big_CSV_analyzer.average_means_of_values_f_threads ()
- def a__everything_Big_CSV_analyzer.relation_thread_upvotes_with_amount_of_comments ()
- def a__everything_Big_CSV_analyzer.relation_thread_upvotes_with_amount_of_questions ()
- def a__everything_Big_CSV_analyzer.relation_thread_downvotes_with_amount_of_comments ()
- def a__everything_Big_CSV_analyzer.relation_thread_downvotes_with_amount_of_questions ()
- def a__everything_Big_CSV_analyzer.relation_thread_upvotes_and_iama_host_response_time_comments ()
- def a__everything_Big_CSV_analyzer.relation_thread_upvotes_and_iama_host_response_time_questions ()
- def a__everything_Big_CSV_analyzer.relation_thread_downvotes_and_iama_host_response_time_comments ()
- def a__everything_Big_CSV_analyzer.relation_thread_downvotes_and_iama_host_response_time_questions ()
- def a__everything_Big_CSV_analyzer.relation_thread_lifespan_to_last_comment_and_amount_of_comments ()
- def a__everything_Big_CSV_analyzer.relation_thread_lifespan_to_last_comment_and_amount_of_questions ()
- def a__everything_Big_CSV_analyzer.relation_thread_lifespan_to_last_question_and_amount_of_comments ()
- def a__everything_Big_CSV_analyzer.relation_thread_lifespan_to_last_question_and_amount_of_question ()
- def a__everything_Big_CSV_analyzer.relation_thread_lifespan_to_last_comment_and_iama_host_response_time_to_comments ()
- def a__everything_Big_CSV_analyzer.relation_thread_lifespan_to_last_comment_and_iama_host_response_time_to_questions ()
- def a__everything_Big_CSV_analyzer.relation_thread_lifespan_to_last_question_and_iama_host_response_time_to_comments ()
- def a__everything_Big_CSV_analyzer.relation_thread_lifespan_to_last_question_and_iama_host_response_time_to_questions ()
- def a__everything_Big_CSV_analyzer.relation_thread_reaction_time_comments_and_iama_host_response_time_to_comments ()
- def a__everything_Big_CSV_analyzer.relation_thread_reaction_time_comments_and_iama_host_response_time_to_questions ()
- def a__everything_Big_CSV_analyzer.relation_thread_reaction_time_questions_and_iama_host_response_time_to_comments ()
- def a__everything_Big_CSV_analyzer.relation_thread_reaction_time_questions_and_iama_host_response_time_to_questions ()
- def a__everything_Big_CSV_analyzer.relation_thread_reaction_time_comments_and_amount_of_comments_the_iama_host_answered_to ()

- def a__everything_Big_CSV_analyzer.relation_thread_reaction_time_comments_and_amount_of_questions_the_iama_host_answered_to ()
- def a__everything_Big_CSV_analyzer.relation_thread_reaction_time_questions_and_amount_of_comments_the_iama_host_answered_to ()
- def a__everything_Big_CSV_analyzer.relation_thread_reaction_time_questions_and_amount_of_questions_the_iama_host_answered_to ()
- def a__everything_Big_CSV_analyzer.relation_thread_amount_of_questioners_total_and_num_questions_answered_by_iama_host ()
- def a__everything_Big_CSV_analyzer.realation_thread_amount_of_commentators_total_and_num_comments_answered_by_iama_host ()
- def a__everything_Big_CSV_analyzer.relation_thread_amount_of_questions_and_amount_questions_answered_by_iama_host ()
- def a__everything_Big_CSV_analyzer.thread_overall_correlation ()
- def a__everything_Big_CSV_analyzer.question_overall_correlation ()
- def a__everything_Big_CSV_analyzer.average_means_of_values_f_authors ()
- def a__everything_Big_CSV_analyzer.median_of_values_f_authors_randomized ()
- def a__everything_Big_CSV_analyzer.median_of_values_f_authors ()
- def a__everything_Big_CSV_analyzer.arr_of_values_f_authors ()
- def a__everything_Big_CSV_analyzer.calculate_t_tests_of_author_values ()

Variables

- a__everything_Big_CSV_analyzer.author_information_iama
- a__everything_Big_CSV_analyzer.author_information_iama_sampleset_randomized
- a__everything_Big_CSV_analyzer.author_information_random
- a__everything_Big_CSV_analyzer.author_information_random_sampleset_randomized
- a__everything_Big_CSV_analyzer.thread_information
- a__everything_Big_CSV_analyzer.question_information
- a__everything_Big_CSV_analyzer.inplace
- a__everything_Big_CSV_analyzer.author_amount_creation_iama_threads = author_information_iama['amount_creation_iama_threads']
- a__everything_Big_CSV_analyzer.author_amount_creation_other_threads = author_information_iama['amount_creation_other_threads']
- a__everything_Big_CSV_analyzer.author_amount_of_comments_except_iama = author_information_iama['amount_of_comments_except_iama']
- a__everything_Big_CSV_analyzer.author_amount_of_comments_iama = author_information_iama['amount_of_comments_iama']
- a__everything_Big_CSV_analyzer.author_author_birth_date = author_information_iama['author_birth_date']
- a__everything_Big_CSV_analyzer.author_author_comment_karma_amount = author_information_iama['author_comment_karma_amount']
- a__everything_Big_CSV_analyzer.author_author_link_karma_amount = author_information_iama['author_link_karma_amount']
- a__everything_Big_CSV_analyzer.author_author_name = author_information_iama['author_name']
- a__everything_Big_CSV_analyzer.author_comment_creation_every_x_sec = author_information_iama['comment_creation_every_x_sec']
- a__everything_Big_CSV_analyzer.author_thread_creation_every_x_sec = author_information_iama['thread_creation_every_x_sec']
- a__everything_Big_CSV_analyzer.author_time_acc_birth_first_iama_thread = author_information_iama['time_acc_birth_first_iama_thread']

- a__everything_Big_CSV_analyzer.author_time_diff_acc_creation_n_first_comment = author_information_iama['time_diff_acc_creation_n_first_comment']
- a__everything_Big_CSV_analyzer.author_time_diff_acc_creation_n_first_thread = author_information_iama['time_diff_acc_creation_n_first_thread']
- a__everything_Big_CSV_analyzer.author_amount_creation_iama_threads_randomized = author_information_iama_sampleset_randomized['amount_creation_iama_threads']
- a__everything_Big_CSV_analyzer.author_amount_creation_other_threads_randomized = author_information_iama_sampleset_randomized['amount_creation_other_threads']
- a__everything_Big_CSV_analyzer.author_amount_of_comments_except_iama_randomized = author_information_iama_sampleset_randomized['amount_of_comments_except_iama']
- a__everything_Big_CSV_analyzer.author_amount_of_comments_iama_randomized = author_information_iama_sampleset_randomized['amount_of_comments_iama']
- a__everything_Big_CSV_analyzer.author_author_birth_date_randomized = author_information_iama_sampleset_randomized['author_birth_date']
- a__everything_Big_CSV_analyzer.author_author_comment_karma_amount_randomized = author_information_iama_sampleset_randomized['author_comment_karma_amount']
- a__everything_Big_CSV_analyzer.author_author_link_karma_amount_randomized = author_information_iama_sampleset_randomized['author_link_karma_amount']
- a__everything_Big_CSV_analyzer.author_author_name_randomized = author_information_iama_sampleset_randomized['author_name']
- a__everything_Big_CSV_analyzer.author_comment_creation_every_x_sec_randomized = author_information_iama_sampleset_randomized['comment_creation_every_x_sec']
- a__everything_Big_CSV_analyzer.author_thread_creation_every_x_sec_randomized = author_information_iama_sampleset_randomized['thread_creation_every_x_sec']
- a__everything_Big_CSV_analyzer.author_time_acc_birth_first_iama_thread_randomized = author_information_iama_sampleset_randomized['time_acc_birth_first_iama_thread']
- a__everything_Big_CSV_analyzer.author_time_diff_acc_creation_n_first_comment_randomized = author_information_iama_sampleset_randomized['time_diff_acc_creation_n_first_comment']
- a__everything_Big_CSV_analyzer.author_time_diff_acc_creation_n_first_thread_randomized = author_information_iama_sampleset_randomized['time_diff_acc_creation_n_first_thread']
- a__everything_Big_CSV_analyzer.random_author_amount_creation_iama_threads = author_information_random['amount_creation_iama_threads']
- a__everything_Big_CSV_analyzer.random_author_amount_creation_other_threads = author_information_random['amount_creation_other_threads']
- a__everything_Big_CSV_analyzer.random_author_amount_of_comments_except_iama = author_information_random['amount_of_comments_except_iama']
- a__everything_Big_CSV_analyzer.random_author_amount_of_comments_iama = author_information_random['amount_of_comments_iama']
- a__everything_Big_CSV_analyzer.random_author_author_birth_date = author_information_random['author_birth_date']
- a__everything_Big_CSV_analyzer.random_author_author_comment_karma_amount = author_information_random['author_comment_karma_amount']
- a__everything_Big_CSV_analyzer.random_author_author_link_karma_amount = author_information_random['author_link_karma_amount']
- a__everything_Big_CSV_analyzer.random_author_author_name = author_information_random['author_name']
- a__everything_Big_CSV_analyzer.random_author_comment_creation_every_x_sec = author_information_random['comment_creation_every_x_sec']
- a__everything_Big_CSV_analyzer.random_author_thread_creation_every_x_sec = author_information_random['thread_creation_every_x_sec']
- a__everything_Big_CSV_analyzer.random_author_time_acc_birth_first_iama_thread = author_information_random['time_acc_birth_first_iama_thread']
- a__everything_Big_CSV_analyzer.random_author_time_diff_acc_creation_n_first_comment = \
- a__everything_Big_CSV_analyzer.random_author_time_diff_acc_creation_n_first_thread
- a__everything_Big_CSV_analyzer.random_author_amount_creation_iama_threads_randomized = author_information_random_sampleset_randomized['amount_creation_iama_threads']

- a__everything_Big_CSV_analyzer.random_author_amount_creation_other_threads_randomized = author_information_random_sampleset_randomized['amount_creation_other_threads']
- a__everything_Big_CSV_analyzer.random_author_amount_of_comments_except_iama_randomized = author_information_random_sampleset_randomized['amount_of_comments_except_iama']
- a__everything_Big_CSV_analyzer.random_author_amount_of_comments_iama_randomized = author_information_random_sampleset_randomized['amount_of_comments_iama']
- a__everything_Big_CSV_analyzer.random_author_author_birth_date_randomized = author_information_random_sampleset_randomized['author_birth_date']
- a__everything_Big_CSV_analyzer.random_author_author_comment_karma_amount_randomized = author_information_random_sampleset_randomized['author_comment_karma_amount']
- a__everything_Big_CSV_analyzer.random_author_author_link_karma_amount_randomized = author_information_random_sampleset_randomized['author_link_karma_amount']
- a__everything_Big_CSV_analyzer.random_author_author_name_randomized = author_information_random_sampleset_randomized['author_name']
- a__everything_Big_CSV_analyzer.random_author_comment_creation_every_x_sec_randomized = author_information_random_sampleset_randomized['comment_creation_every_x_sec']
- a__everything_Big_CSV_analyzer.random_author_thread_creation_every_x_sec_randomized = author_information_random_sampleset_randomized['thread_creation_every_x_sec']
- a__everything_Big_CSV_analyzer.random_author_time_acc_birth_first_iama_thread_randomized = author_information_random_sampleset_randomized['time_acc_birth_first_iama_thread']
- a__everything_Big_CSV_analyzer.random_author_time_diff_acc_creation_n_first_comment_randomized = \
- a__everything_Big_CSV_analyzer.random_author_time_diff_acc_creation_n_first_thread_randomized
- a__everything_Big_CSV_analyzer.question_ups = question_information['Question ups']
- a__everything_Big_CSV_analyzer.question_answered_by_iAMA_host = question_information['Question answered by iAMA host']
- a__everything_Big_CSV_analyzer.thread_year = thread_information['Year']
- a__everything_Big_CSV_analyzer.thread_id = thread_information['Thread id']
- a__everything_Big_CSV_analyzer.thread_author = thread_information['Thread author']
- a__everything_Big_CSV_analyzer.thread_ups = thread_information['Thread ups']
- a__everything_Big_CSV_analyzer.thread_downs = thread_information['Thread downs']
- a__everything_Big_CSV_analyzer.thread_creation_time_stamp = thread_information['Thread creation time stamp']
- a__everything_Big_CSV_analyzer.thread_average_comment_vote_score_total
- a__everything_Big_CSV_analyzer.thread_average_comment_vote_score_tier_1
- a__everything_Big_CSV_analyzer.thread_average_comment_vote_score_tier_x
- a__everything_Big_CSV_analyzer.thread_average_question_vote_score_total
- a__everything_Big_CSV_analyzer.thread_average_question_vote_score_tier_1
- a__everything_Big_CSV_analyzer.thread_average_question_vote_score_tier_x
- a__everything_Big_CSV_analyzer.thread_num_comments_total_skewed
- a__everything_Big_CSV_analyzer.thread_num_comments_total = thread_information['Thread num comments total']
- a__everything_Big_CSV_analyzer.thread_num_comments_tier_1 = thread_information['Thread num comments tier 1']
- a__everything_Big_CSV_analyzer.thread_num_comments_tier_x = thread_information['Thread num comments tier x']
- a__everything_Big_CSV_analyzer.thread_num_questions_total = thread_information['Thread num questions total']
- a__everything_Big_CSV_analyzer.thread_num_questions_tier_1 = thread_information['Thread num questions tier 1']
- a__everything_Big_CSV_analyzer.thread_num_questions_tier_x = thread_information['Thread num questions tier x']
- a__everything_Big_CSV_analyzer.thread_num_questions_answered_by_iama_host_total
- a__everything_Big_CSV_analyzer.thread_num_questions_answered_by_iama_host_tier_1
- a__everything_Big_CSV_analyzer.thread_num_questions_answered_by_iama_host_tier_x
- a__everything_Big_CSV_analyzer.thread_num_comments_answered_by_iama_host_total

- a__everything_Big_CSV_analyzer.thread_num_comments_answered_by_iama_host_tier_1
- a__everything_Big_CSV_analyzer.thread_num_comments_answered_by_iama_host_tier_x
- a__everything_Big_CSV_analyzer.thread_average_reaction_time_between_comments_total
- a__everything_Big_CSV_analyzer.thread_average_reaction_time_between_comments_tier_1
- a__everything_Big_CSV_analyzer.thread_average_reaction_time_between_comments_tier_x
- a__everything_Big_CSV_analyzer.thread_average_reaction_time_between_questions_total
- a__everything_Big_CSV_analyzer.thread_average_reaction_time_between_questions_tier_1
- a__everything_Big_CSV_analyzer.thread_average_reaction_time_between_questions_tier_x
- a__everything_Big_CSV_analyzer.thread_average_response_to_comment_time_iama_host_total
- a__everything_Big_CSV_analyzer.thread_average_response_to_comment_time_iama_host_tier_1
- a__everything_Big_CSV_analyzer.thread_average_response_to_comment_time_iama_host_tier_x
- a__everything_Big_CSV_analyzer.thread_average_response_to_question_time_iama_host_total
- a__everything_Big_CSV_analyzer.thread_average_response_to_question_time_iama_host_tier_1
- a__everything_Big_CSV_analyzer.thread_average_response_to_question_time_iama_host_tier_x
- a__everything_Big_CSV_analyzer.thread_amount_of_questioners_total
- a__everything_Big_CSV_analyzer.thread_amount_of_questioners_tier_1
- a__everything_Big_CSV_analyzer.thread_amount_of_questioners_tier_x
- a__everything_Big_CSV_analyzer.thread_amount_of_commentators_total
- a__everything_Big_CSV_analyzer.thread_amount_of_commentators_tier_1
- a__everything_Big_CSV_analyzer.thread_amount_of_commentators_tier_x
- a__everything_Big_CSV_analyzer.thread_life_span_until_last_comment
- a__everything_Big_CSV_analyzer.thread_life_span_until_last_question

a_author_Information.py File Reference

Namespaces

- a_author_Information

Functions

- def a_author_Information.check_script_arguments ()
- def a_author_Information.initialize_mongo_db_parameters ()
- def a_author_Information.write_csv_data ()

Variables

- a_author_Information.mongo_db_client_instance = None
- a_author_Information.mongo_db_author_instance = None
- a_author_Information.mongo_db_author_collection = None
- int a_author_Information.mongo_db_author_collection_original = 0
- string a_author_Information.argument_db_to_choose = ""

a_iAMA_Commenttime_arr.py File Reference

Namespaces

- a_iAMA_Commenttime_arr

Functions

- def a_iAMA_Commenttime_arr.check_script_arguments ()
- def a_iAMA_Commenttime_arr.initialize_mongo_db_parameters (actually_processed_year)
- def a_iAMA_Commenttime_arr.start_data_generation_for_analysis ()
- def a_iAMA_Commenttime_arr.prepare_data_for_graph ()
- def a_iAMA_Commenttime_arr.add_thread_list_to_global_list (list_to_append)
- def a_iAMA_Commenttime_arr.generate_data_to_be_analyzed ()
- def a_iAMA_Commenttime_arr.calculate_ar_mean_answer_time_for_questions (id_of_thread, author_of_thread)
- def a_iAMA_Commenttime_arr.check_if_comment_is_a_question (given_string)
- def a_iAMA_Commenttime_arr.check_if_comment_is_on_tier_1 (comment_parent_id)
- def a_iAMA_Commenttime_arr.check_if_comment_is_not_from_thread_author (author_of_thread, comment_author)
- def a_iAMA_Commenttime_arr.check_if_comment_is_answer_from_thread_author (author_of_thread, comment_actual_id, comments_cursor)
- def a_iAMA_Commenttime_arr.calculate_time_difference (comment_time_stamp, answer_time_stamp_iama_host)
- def a_iAMA_Commenttime_arr.write_csv_data (list_with_information)
- def a_iAMA_Commenttime_arr.plot_generated_data ()

Variables

- int a_iAMA_Commenttime_arr.argument_year_beginning = 0
- int a_iAMA_Commenttime_arr.year_actually_in_progress = 0
- int a_iAMA_Commenttime_arr.argument_year_ending = 0
- string a_iAMA_Commenttime_arr.argument_tier_in_scope = ""
- string a_iAMA_Commenttime_arr.argument_plot_time_unit = ""
- a_iAMA_Commenttime_arr.mongo_DB_Client_Instance = None
- a_iAMA_Commenttime_arr.mongo_DB_Threads_Instance = None
- a_iAMA_Commenttime_arr.mongo_DB_Thread_Collection = None
- a_iAMA_Commenttime_arr.mongo_DB_Comments_Instance = None
- list a_iAMA_Commenttime_arr.list_To_Be_Plotted = []
- list a_iAMA_Commenttime_arr.global_thread_list = []
- list a_iAMA_Commenttime_arr.data_to_give_plotly = []

a_iAMA_Commenttime_med.py File Reference

Namespaces

- a_iAMA_Commenttime_med

Functions

- def a_iAMA_Commenttime_med.check_script_arguments ()
- def a_iAMA_Commenttime_med.initialize_mongo_db_parameters (actually_processed_year)
- def a_iAMA_Commenttime_med.start_data_generation_for_analysis ()
- def a_iAMA_Commenttime_med.prepare_data_for_graph ()
- def a_iAMA_Commenttime_med.add_thread_list_to_global_list (list_to_append)
- def a_iAMA_Commenttime_med.generate_data_to_be_analyzed ()
- def a_iAMA_Commenttime_med.calculate_ar_mean_answer_time_for_questions (id_of_thread, author_of_thread)
- def a_iAMA_Commenttime_med.check_if_comment_is_a_question (given_string)
- def a_iAMA_Commenttime_med.check_if_comment_is_on_tier_1 (comment_parent_id)
- def a_iAMA_Commenttime_med.check_if_comment_is_not_from_thread_author (author_of_thread, comment_author)
- def a_iAMA_Commenttime_med.check_if_comment_is_answer_from_thread_author (author_of_thread, comment_actual_id, comments_cursor)
- def a_iAMA_Commenttime_med.calculate_time_difference (comment_time_stamp, answer_time_stamp_iama_host)
- def a_iAMA_Commenttime_med.write_csv_data (list_with_information)
- def a_iAMA_Commenttime_med.plot_generated_data ()

Variables

- int a_iAMA_Commenttime_med.argument_year_beginning = 0
- int a_iAMA_Commenttime_med.year_actually_in_progress = 0
- int a_iAMA_Commenttime_med.argument_year_ending = 0
- string a_iAMA_Commenttime_med.argument_tier_in_scope = ""
- string a_iAMA_Commenttime_med.argument_plot_time_unit = ""
- a_iAMA_Commenttime_med.mongo_DB_Client_Instance = None
- a_iAMA_Commenttime_med.mongo_DB_Threads_Instance = None
- a_iAMA_Commenttime_med.mongo_DB_Thread_Collection = None
- a_iAMA_Commenttime_med.mongo_DB_Comments_Instance = None
- list a_iAMA_Commenttime_med.list_To_Be_Plotted = []
- list a_iAMA_Commenttime_med.global_thread_list = []
- list a_iAMA_Commenttime_med.data_to_give_plotly = []

a_question_Answered_Yes_No_Extrema.py File Reference

Namespaces

- a_question_Answered_Yes_No_Extrema

Functions

- def a_question_Answered_Yes_No_Extrema.check_script_arguments ()
- def a_question_Answered_Yes_No_Extrema.initialize_mongo_db_parameters (actually_processed_year)
- def a_question_Answered_Yes_No_Extrema.start_data_generation_for_analysis ()
- def a_question_Answered_Yes_No_Extrema.generate_data_now ()
- def a_question_Answered_Yes_No_Extrema.process_answered_questions_within_thread (id_of_thread, author_of_thread, thread_creation_date)
- def a_question_Answered_Yes_No_Extrema.check_if_comment_is_a_question (given_string)
- def a_question_Answered_Yes_No_Extrema.check_if_comment_is_not_from_thread_author (author_of_thread, comment_author)
- def a_question_Answered_Yes_No_Extrema.check_if_comment_has_been_answered_by_thread_author (author_of_thread, comment_acutal_id, comments_cursor)
- def a_question_Answered_Yes_No_Extrema.calculate_time_difference (comment_time_stamp, answer_time_stamp_iama_host)
- def a_question_Answered_Yes_No_Extrema.sort_questions (list_which_is_to_be_sorted)
- def a_question_Answered_Yes_No_Extrema.create_question_list_containing_all_years (list_with_comments_per_years)
- def a_question_Answered_Yes_No_Extrema.write_csv_and_count_unanswered (list_with_comments)
- def a_question_Answered_Yes_No_Extrema.plot_generated_data ()

Variables

- int a_question_Answered_Yes_No_Extrema.argument_year_beginning = 0
- int a_question_Answered_Yes_No_Extrema.year_actually_in_progress = 0
- int a_question_Answered_Yes_No_Extrema.argument_year_ending = 0
- a_question_Answered_Yes_No_Extrema.argument_sorting = bool
- int a_question_Answered_Yes_No_Extrema.argument_amount_of_top_quotes = 0
- a_question_Answered_Yes_No_Extrema.mongo_DB_Client_Instance = None
- a_question_Answered_Yes_No_Extrema.mongo_DB_Threads_Instance = None
- a_question_Answered_Yes_No_Extrema.mongo_DB_Thread_Collection = None
- a_question_Answered_Yes_No_Extrema.mongo_DB_Comments_Instance = None
- list a_question_Answered_Yes_No_Extrema.question_information_list = []
- list a_question_Answered_Yes_No_Extrema.data_to_give_plotly = []

a_question_Answered_Yes_No_Tier_Percentage.py File Reference

Namespaces

- a_question_Answered_Yes_No_Tier_Percentage

Functions

- def a_question_Answered_Yes_No_Tier_Percentage.check_script_arguments ()
- def a_question_Answered_Yes_No_Tier_Percentage.initialize_mongo_db_parameters (actually_processed_year)
- def a_question_Answered_Yes_No_Tier_Percentage.start_data_generation_for_analysis ()
- def a_question_Answered_Yes_No_Tier_Percentage.generate_data_to_be_analyzed ()
- def a_question_Answered_Yes_No_Tier_Percentage.question_answering_distribution_tier1_tierx_tierany (id_of_thread, author_of_thread)
- def a_question_Answered_Yes_No_Tier_Percentage.check_if_comment_is_a_question (given_string)
- def a_question_Answered_Yes_No_Tier_Percentage.check_if_comment_is_on_tier_1 (comment_parent_id)
- def a_question_Answered_Yes_No_Tier_Percentage.check_if_comment_is_not_from_thread_author (author_of_thread, comment_author)
- def a_question_Answered_Yes_No_Tier_Percentage.check_if_comment_is_answer_from_thread_author (author_of_thread, comment_actual_id, comments_cursor)
- def a_question_Answered_Yes_No_Tier_Percentage.write_csv (list_with_information)
- def a_question_Answered_Yes_No_Tier_Percentage.add_local_list_to_global_list (list_to_append)
- def a_question_Answered_Yes_No_Tier_Percentage.prepare_data_for_graph ()
- def a_question_Answered_Yes_No_Tier_Percentage.plot_generated_data ()

Variables

- int a_question_Answered_Yes_No_Tier_Percentage.argument_year_beginning = 0
- int a_question_Answered_Yes_No_Tier_Percentage.year_actually_in_progress = 0
- int a_question_Answered_Yes_No_Tier_Percentage.argument_year_ending = 0
- string a_question_Answered_Yes_No_Tier_Percentage.argument_tier_in_scope = ""
- a_question_Answered_Yes_No_Tier_Percentage.mongo_DB_Client_Instance = None
- a_question_Answered_Yes_No_Tier_Percentage.mongo_DB_Threads_Instance = None
- a_question_Answered_Yes_No_Tier_Percentage.mongo_DB_Thread_Collection = None
- a_question_Answered_Yes_No_Tier_Percentage.mongo_DB_Comments_Instance = None
- list a_question_Answered_Yes_No_Tier_Percentage.global_question_list = []
- list a_question_Answered_Yes_No_Tier_Percentage.year_question_list = []
- list a_question_Answered_Yes_No_Tier_Percentage.data_to_give_plotly = []

a_question_Tier_Distribution.py File Reference

Namespaces

- a_question_Tier_Distribution

Functions

- def a_question_Tier_Distribution.initialize_mongo_db_parameters (actually_processed_year)
- def a_question_Tier_Distribution.check_script_arguments ()
- def a_question_Tier_Distribution.start_data_generation_for_analysis ()
- def a_question_Tier_Distribution.generate_data_to_be_analyzed ()
- def a_question_Tier_Distribution.question_distribution_tier1_tierx (id_of_thread, author_of_thread)
- def a_question_Tier_Distribution.check_if_comment_is_a_question (given_string)
- def a_question_Tier_Distribution.check_if_comment_is_on_tier_1 (comment_parent_id)
- def a_question_Tier_Distribution.check_if_comment_is_not_from_thread_author (author_of_thread, comment_author)
- def a_question_Tier_Distribution.add_actual_year_list_to_global_list (list_to_append)
- def a_question_Tier_Distribution.write_csv (list_with_information)
- def a_question_Tier_Distribution.prepare_data_for_graph ()
- def a_question_Tier_Distribution.plot_generated_data ()

Variables

- int a_question_Tier_Distribution.argument_year_beginning = 0
- int a_question_Tier_Distribution.year_actually_in_progress = 0
- int a_question_Tier_Distribution.argument_year_ending = 0
- a_question_Tier_Distribution.mongo_DB_Client_Instance = None
- a_question_Tier_Distribution.mongo_DB_Threads_Instance = None
- a_question_Tier_Distribution.mongo_DB_Thread_Collection = None
- a_question_Tier_Distribution.mongo_DB_Comments_Instance = None
- list a_question_Tier_Distribution.current_year_question_list = []
- list a_question_Tier_Distribution.global_year_question_list = []
- list a_question_Tier_Distribution.data_to_give_plotly = []

a_thread_Lifespan_N_Average_Commenttime.py File Reference

Namespaces

- a_thread_Lifespan_N_Average_Commenttime

Functions

- def a_thread_Lifespan_N_Average_Commenttime.check_script_arguments ()
- def a_thread_Lifespan_N_Average_Commenttime.initialize_mongo_db_parameters (actually_processed_year)
- def a_thread_Lifespan_N_Average_Commenttime.start_data_generation_for_analysis ()
- def a_thread_Lifespan_N_Average_Commenttime.prepare_data_for_graph_life_span ()
- def a_thread_Lifespan_N_Average_Commenttime.prepare_data_for_comment_time ()
- def a_thread_Lifespan_N_Average_Commenttime.generate_data_to_be_analyzed ()
- def a_thread_Lifespan_N_Average_Commenttime.calculate_time_difference (id_of_thread, creation_date_of_thread)
- def a_thread_Lifespan_N_Average_Commenttime.write_csv (list_with_information)
- def a_thread_Lifespan_N_Average_Commenttime.add_thread_list_to_global_list (list_to_append)
- def a_thread_Lifespan_N_Average_Commenttime.prepare_dict_by_time_separation_for_comment_time ()
- def a_thread_Lifespan_N_Average_Commenttime.plot_generated_data ()

Variables

- int a_thread_Lifespan_N_Average_Commenttime.argument_year_beginning = 0
- string a_thread_Lifespan_N_Average_Commenttime.argument_calculation = ""
- int a_thread_Lifespan_N_Average_Commenttime.argument_year_ending = 0
- int a_thread_Lifespan_N_Average_Commenttime.year_actually_in_progress = 0
- string a_thread_Lifespan_N_Average_Commenttime.argument_plot_time_unit = ""
- a_thread_Lifespan_N_Average_Commenttime.mongo_DB_Client_Instance = None
- a_thread_Lifespan_N_Average_Commenttime.mongo_DB_Threads_Instance = None
- a_thread_Lifespan_N_Average_Commenttime.mongo_DB_Thread_Collection = None
- a_thread_Lifespan_N_Average_Commenttime.mongo_DB_Comments_Instance = None
- list a_thread_Lifespan_N_Average_Commenttime.global_thread_list = []
- list a_thread_Lifespan_N_Average_Commenttime.temp_time_difference_list = []
- list a_thread_Lifespan_N_Average_Commenttime.list_with_currents_year_infos = []
- list a_thread_Lifespan_N_Average_Commenttime.data_to_give_plotly = []

a_thread_Lifespan_N_Average_Questiontime.py File Reference

Namespaces

- a_thread_Lifespan_N_Average_Questiontime

Functions

- def a_thread_Lifespan_N_Average_Questiontime.check_script_arguments ()
- def a_thread_Lifespan_N_Average_Questiontime.initialize_mongo_db_parameters (actually_processed_year)
- def a_thread_Lifespan_N_Average_Questiontime.start_data_generation_for_analysis ()
- def a_thread_Lifespan_N_Average_Questiontime.prepare_data_for_graph_life_span ()
- def a_thread_Lifespan_N_Average_Questiontime.prepare_data_for_comment_time ()
- def a_thread_Lifespan_N_Average_Questiontime.generate_data_to_be_analyzed ()
- def a_thread_Lifespan_N_Average_Questiontime.calculate_time_difference (id_of_thread, creation_date_of_thread)
- def a_thread_Lifespan_N_Average_Questiontime.write_csv (list_with_information)
- def a_thread_Lifespan_N_Average_Questiontime.add_thread_list_to_global_list (list_to_append)
- def a_thread_Lifespan_N_Average_Questiontime.prepare_dict_by_time_separation_for_comment_time ()
- def a_thread_Lifespan_N_Average_Questiontime.plot_generated_data ()

Variables

- int a_thread_Lifespan_N_Average_Questiontime.argument_year_beginning = 0
- string a_thread_Lifespan_N_Average_Questiontime.argument_calculation = ""
- int a_thread_Lifespan_N_Average_Questiontime.argument_year_ending = 0
- int a_thread_Lifespan_N_Average_Questiontime.year_actually_in_progress = 0
- string a_thread_Lifespan_N_Average_Questiontime.argument_plot_time_unit = ""
- a_thread_Lifespan_N_Average_Questiontime.mongo_DB_Client_Instance = None
- a_thread_Lifespan_N_Average_Questiontime.mongo_DB_Threads_Instance = None
- a_thread_Lifespan_N_Average_Questiontime.mongo_DB_Thread_Collection = None
- a_thread_Lifespan_N_Average_Questiontime.mongo_DB_Comments_Instance = None
- list a_thread_Lifespan_N_Average_Questiontime.global_thread_list = []
- list a_thread_Lifespan_N_Average_Questiontime.temp_time_difference_list = []
- list a_thread_Lifespan_N_Average_Questiontime.list_with_currents_year_infos = []
- list a_thread_Lifespan_N_Average_Questiontime.data_to_give_plotly = []

ar_analyzer.py File Reference

Namespaces

- ar_analyzer

Functions

- def ar_analyzer.average_means_of_values_f_threads ()
- def ar_analyzer.std_derivation ()

Variables

- ar_analyzer.thread_information
- ar_analyzer.thread_year = thread_information['Year']
- ar_analyzer.thread_id = thread_information['Thread id']
- ar_analyzer.thread_author = thread_information['Thread author']
- ar_analyzer.thread_ups = thread_information['Thread ups']
- ar_analyzer.thread_downs = thread_information['Thread downs']
- ar_analyzer.thread_creation_time_stamp = thread_information['Thread creation time stamp']
- ar_analyzer.thread_average_comment_vote_score_total
- ar_analyzer.thread_average_comment_vote_score_tier_1
- ar_analyzer.thread_average_comment_vote_score_tier_x
- ar_analyzer.thread_average_question_vote_score_total
- ar_analyzer.thread_average_question_vote_score_tier_1
- ar_analyzer.thread_average_question_vote_score_tier_x
- ar_analyzer.thread_num_comments_total_skewed
- ar_analyzer.thread_num_comments_total = thread_information['Thread num comments total']
- ar_analyzer.thread_num_comments_tier_1 = thread_information['Thread num comments tier 1']
- ar_analyzer.thread_num_comments_tier_x = thread_information['Thread num comments tier x']
- ar_analyzer.thread_num_questions_total = thread_information['Thread num questions total']
- ar_analyzer.thread_num_questions_tier_1 = thread_information['Thread num questions tier 1']
- ar_analyzer.thread_num_questions_tier_x = thread_information['Thread num questions tier x']
- ar_analyzer.thread_num_questions_answered_by_iama_host_total
- ar_analyzer.thread_num_questions_answered_by_iama_host_tier_1
- ar_analyzer.thread_num_questions_answered_by_iama_host_tier_x
- ar_analyzer.thread_num_comments_answered_by_iama_host_total
- ar_analyzer.thread_num_comments_answered_by_iama_host_tier_1
- ar_analyzer.thread_num_comments_answered_by_iama_host_tier_x
- ar_analyzer.thread_average_reaction_time_between_comments_total
- ar_analyzer.thread_average_reaction_time_between_comments_tier_1
- ar_analyzer.thread_average_reaction_time_between_comments_tier_x
- ar_analyzer.thread_average_reaction_time_between_questions_total
- ar_analyzer.thread_average_reaction_time_between_questions_tier_1
- ar_analyzer.thread_average_reaction_time_between_questions_tier_x
- ar_analyzer.thread_average_response_to_comment_time_iama_host_total
- ar_analyzer.thread_average_response_to_comment_time_iama_host_tier_1
- ar_analyzer.thread_average_response_to_comment_time_iama_host_tier_x
- ar_analyzer.thread_average_response_to_question_time_iama_host_total
- ar_analyzer.thread_average_response_to_question_time_iama_host_tier_1
- ar_analyzer.thread_average_response_to_question_time_iama_host_tier_x
- ar_analyzer.thread_amount_of_questioners_total
- ar_analyzer.thread_amount_of_questioners_tier_1
- ar_analyzer.thread_amount_of_questioners_tier_x

- ar_analyzer.thread_amount_of_commentators_total
- ar_analyzer.thread_amount_of_commentators_tier_1
- ar_analyzer.thread_amount_of_commentators_tier_x
- ar_analyzer.thread_life_span_until_last_comment
- ar_analyzer.thread_life_span_until_last_question

c_crawl_Author_Information.py File Reference

Namespaces

- c_crawl_Author_Information

Functions

- def c_crawl_Author_Information.check_script_arguments ()
- def c_crawl_Author_Information.initialize_mongo_db_parameters (actually_processed_year)
- def c_crawl_Author_Information.start_data_generation_for_analysis ()
- def c_crawl_Author_Information.generate_data_now ()
- def c_crawl_Author_Information.calculate_time_difference (time_value_1, time_value_2)
- def c_crawl_Author_Information.get_author_information (name_of_author)

Variables

- int c_crawl_Author_Information.argument_year_beginning = 0
- int c_crawl_Author_Information.year_actually_in_progress = 0
- int c_crawl_Author_Information.argument_year_ending = 0
- string c_crawl_Author_Information.argument_inverse_crawling = ""
- c_crawl_Author_Information.mongo_db_client_instance = None
- c_crawl_Author_Information.mongo_db_threads_instance = None
- c_crawl_Author_Information.mongo_db_thread_collection = None
- c_crawl_Author_Information.mongo_db_author_instance = None
- c_crawl_Author_Information.reddit_instance = praw.Reddit(user_agent="University_Regensburg_iAMA_Crawler_0.001")

c_crawl_Differences.py File Reference

Namespaces

- c_crawl_Differences

Functions

- def c_crawl_Differences.check_script_arguments ()
- def c_crawl_Differences.initialize_mongo_db_parameters ()
- def c_crawl_Differences.crawl_missing_collection_into_comments_database (name_of_missing_collection)
- def c_crawl_Differences.check_if_collection_is_missing_in_comments_database ()
- def c_crawl_Differences.crawl_missing_collection_into_threads_database (name_of_missing_collection)
- def c_crawl_Differences.check_if_collection_is_missing_in_threads_database ()
- def c_crawl_Differences.start_crawling_for_diffs ()

Variables

- c_crawl_Differences.mongo_DB_Client_Instance = None
- c_crawl_Differences.mongo_DB_Threads_Instance = None
- c_crawl_Differences.mongo_DB_Thread_Collection = None
- c_crawl_Differences.mongo_DB_Comments_Instance = None
- c_crawl_Differences.mongo_DB_Comments_Collection = None
- string c_crawl_Differences.argument_year_beginning = ""
- string c_crawl_Differences.argument_year_ending = ""
- string c_crawl_Differences.argument_inverse_crawling = ""

c_crawl_Random_Author_Information.py File Reference

Namespaces

- c_crawl_Random_Author_Information

Functions

- def c_crawl_Random_Author_Information.check_script_arguments ()
- def c_crawl_Random_Author_Information.initialize_mongo_db_parameters ()
- def c_crawl_Random_Author_Information.start_data_generation_for_analysis ()
- def c_crawl_Random_Author_Information.generate_data_now (randomized_author_name)
- def c_crawl_Random_Author_Information.calculate_time_difference (time_value_1, time_value_2)
- def c_crawl_Random_Author_Information.get_author_information (name_of_author)

Variables

- c_crawl_Random_Author_Information.argument_limit_crawling_amount = None
- c_crawl_Random_Author_Information.mongo_db_client_instance = None
- c_crawl_Random_Author_Information.mongo_db_random_author_instance = None
- c_crawl_Random_Author_Information.mongo_db_random_author_collection = None
- c_crawl_Random_Author_Information.mongo_db_iama_author_instance = None
- c_crawl_Random_Author_Information.mongo_db_iama_author_collection = None
- int c_crawl_Random_Author_Information.mongo_db_iama_author_collection_amount = 0
- c_crawl_Random_Author_Information.reddit_instance = praw.Reddit(user_agent="University_Regensburg_iAMA_Crawler_0.001")

c_crawl_Threads_N_Comments.py File Reference

Namespaces

- c_crawl_Threads_N_Comments

Functions

- def c_crawl_Threads_N_Comments.initialize_mongo_db_parameters ()
- def c_crawl_Threads_N_Comments.check_script_arguments ()
- def c_crawl_Threads_N_Comments.convert_argument_year_to_epoch (year)
- def c_crawl_Threads_N_Comments.crawl_data ()
- def c_crawl_Threads_N_Comments.crawl_threads ()
- def c_crawl_Threads_N_Comments.crawl_comments ()
- def c_crawl_Threads_N_Comments.check_if_coll_in_db_already_exists_up2date (submission)

Variables

- c_crawl_Threads_N_Comments.mongo_DB_Client_Instance = None
- c_crawl_Threads_N_Comments.reddit_Instance = None
- c_crawl_Threads_N_Comments.argument_crawl_type = None
- c_crawl_Threads_N_Comments.argument_year_beginning = None
- c_crawl_Threads_N_Comments.argument_year_end = None
- c_crawl_Threads_N_Comments.argument_hours_to_shift = None
- c_crawl_Threads_N_Comments.time_shift_difference

d_create_Big_CSV_ar.py File Reference

Namespaces

- d_create_Big_CSV_ar

Functions

- def d_create_Big_CSV_ar.check_script_arguments ()
- def d_create_Big_CSV_ar.initialize_mongo_db_parameters (actually_processed_year)
- def d_create_Big_CSV_ar.start_data_generation_for_analysis ()
- def d_create_Big_CSV_ar.generate_data ()
- def d_create_Big_CSV_ar.process_specific_thread (thread_id, thread_creation_time_stamp, thread_author)
- def d_create_Big_CSV_ar.check_if_comment_is_a_question (given_string)
- def d_create_Big_CSV_ar.check_if_comment_is_on_tier_1 (comment_parent_id)
- def d_create_Big_CSV_ar.check_if_comment_is_not_from_thread_author (author_of_thread, comment_author)
- def d_create_Big_CSV_ar.check_if_comment_has_been_answered_by_thread_author (author_of_thread, comment_actual_id, comments_cursor)
- def d_create_Big_CSV_ar.calculate_time_difference (comment_time_stamp, answer_time_stamp_iama_host)
- def d_create_Big_CSV_ar.calculate_reaction_time_average (list_to_be_processed, thread_creation_time_stamp)
- def d_create_Big_CSV_ar.calculate_life_span (thread_creation_time_stamp, time_value_of_last_comment, time_value_of_last_question)
- def d_create_Big_CSV_ar.add_actual_year_list_to_global_list (list_to_append)
- def d_create_Big_CSV_ar.write_csv_data (list_with_information)

Variables

- int d_create_Big_CSV_ar.argument_year_beginning = 0
- int d_create_Big_CSV_ar.argument_year_ending = 0
- int d_create_Big_CSV_ar.year_actually_in_progress = 0
- list d_create_Big_CSV_ar.list_current_year = []
- list d_create_Big_CSV_ar.list_global_year = []

d_create_Big_CSV_med.py File Reference

Namespaces

- d_create_Big_CSV_med

Functions

- def d_create_Big_CSV_med.check_script_arguments ()
- def d_create_Big_CSV_med.initialize_mongo_db_parameters (actually_processed_year)
- def d_create_Big_CSV_med.start_data_generation_for_analysis ()
- def d_create_Big_CSV_med.generate_data ()
- def d_create_Big_CSV_med.process_specific_thread (thread_id, thread_creation_time_stamp, thread_author)
- def d_create_Big_CSV_med.check_if_comment_is_a_question (given_string)
- def d_create_Big_CSV_med.check_if_comment_is_on_tier_1 (comment_parent_id)
- def d_create_Big_CSV_med.check_if_comment_is_not_from_thread_author (author_of_thread, comment_author)
- def d_create_Big_CSV_med.check_if_comment_has_been_answered_by_thread_author (author_of_thread, comment_actual_id, comments_cursor)
- def d_create_Big_CSV_med.calculate_time_difference (comment_time_stamp, answer_time_stamp_iama_host)
- def d_create_Big_CSV_med.calculate_reaction_time_average (list_to_be_processed, thread_creation_time_stamp)
- def d_create_Big_CSV_med.calculate_life_span (thread_creation_time_stamp, time_value_of_last_comment, time_value_of_last_question)
- def d_create_Big_CSV_med.add_actual_year_list_to_global_list (list_to_append)
- def d_create_Big_CSV_med.write_csv_data (list_with_information)

Variables

- int d_create_Big_CSV_med.argument_year_beginning = 0
- int d_create_Big_CSV_med.argument_year_ending = 0
- int d_create_Big_CSV_med.year_actually_in_progress = 0
- list d_create_Big_CSV_med.list_current_year = []
- list d_create_Big_CSV_med.list_global_year = []

PlotlyBarChart.py File Reference

Classes

- class PlotlyBarChart.PlotlyBarChart

Namespaces

- PlotlyBarChart

PlotlyBarChart_5_Bars.py File Reference

Classes

- class PlotlyBarChart_5_Bars.PlotlyBarChart5Bars

Namespaces

- PlotlyBarChart_5_Bars

Index