

Calvin Pugmire
CS 470, section 001

Programming Assignment (Monte Carlo Tree Search)

1.

python ConnectFour.py mcts ab -p2 5 -n 5

	C = sqrt(2)	C = 5	C = 20
Game 1	Children: 0 : 27 -3 UB: 0.5673734801832426 1 : 73 13 UB: 0.5907118508859458 2 : 71 15 UB: 0.6296685892059573 3 : 148 44 UB: 0.5870923809671533 4 : 65 10 UB: 0.5911317707153608 5 : 45 3 UB: 0.5922185712149421 6 : 71 11 UB: 0.5733305610369431 Player 1: mcts wins!	Children: 0 : 57 -5 UB: 1.5632517209808054 1 : 60 -2 UB: 1.5758341660306223 2 : 71 6 UB: 1.5637779059484793 3 : 127 59 UB: 1.5706175838827763 4 : 60 -3 UB: 1.5591674993639557 5 : 75 9 UB: 1.559283166304462 6 : 50 -10 UB: 1.5627546764116373 Player 1: mcts wins!	Children: 0 : 68 -2 UB: 6.016786894452854 1 : 75 17 UB: 5.983799331884514 2 : 69 1 UB: 6.016718475306911 3 : 73 12 UB: 5.9998481630823655 4 : 72 10 UB: 6.014737810261014 5 : 68 -2 UB: 6.016786894452854 6 : 75 19 UB: 6.01046599855118 Player 1: mcts wins!
Game 2	Children: 0 : 26 -8 UB: 0.3837169609769133 1 : 53 -5 UB: 0.3899263302686732 2 : 28 -8 UB: 0.3805443566001897 3 : 193 36 UB: 0.4403002135667294 4 : 119 7 UB: 0.3820064419109645 5 : 53 -5 UB: 0.3899263302686732 6 : 28 -8 UB: 0.3805443566001897 Player 2: mcts wins!	Children: 0 : 63 -9 UB: 1.4275295371585504 1 : 83 5 UB: 1.4284039326436107 2 : 71 -3 UB: 1.4370173425681978 3 : 101 21 UB: 1.448190654364276 4 : 59 -11 UB: 1.436306534720024 5 : 77 1 UB: 1.4334552111826386 6 : 46 -19 UB: 1.4247553141308351 Player 2: mcts wins!	Children: 0 : 70 -2 UB: 5.93062703067611 1 : 73 3 UB: 5.876560491849489 2 : 72 0 UB: 6.027245423356338 3 : 75 13 UB: 5.930465998551181 4 : 75 11 UB: 5.903799331884514 5 : 67 -13 UB: 5.8971225772453355 6 : 68 -8 UB: 5.928551600335207 Player 2: mcts wins!
Game 3	Children: 0 : 63 9 UB: 0.5870295710667931 1 : 38 0 UB: 0.5719131374247864 2 : 71 13 UB: 0.6014995751214502 3 : 161 53 UB: 0.6070416074091809 4 : 91 21 UB: 0.600343030397825 5 : 45 3 UB: 0.5922185712149421 6 : 31 -1 UB: 0.6009421075959149 Player 1: mcts wins!	Children: 0 : 51 -7 UB: 1.6081323097588407 1 : 59 -1 UB: 1.6057980601437527 2 : 64 4 UB: 1.6205697315737084 3 : 116 53 UB: 1.6142016945561708 4 : 102 38 UB: 1.6067241528110705 5 : 63 3 UB: 1.6180057276347408 6 : 45 -11 UB: 1.6136621334135093 Player 1: mcts wins!	Children: 0 : 67 -5 UB: 6.016525562319963 1 : 71 5 UB: 5.987505989991101 2 : 73 14 UB: 6.027245423356338 3 : 76 23 UB: 6.021762953195233 4 : 75 21 UB: 6.037132665217848 5 : 72 11 UB: 6.0286266991499025 6 : 66 -7 UB: 6.031063435833043 Player 1: mcts wins!
Game 4	Children: 0 : 26 -8 UB: 0.3837169609769133 1 : 54 -4 UB: 0.40568698136074655 2 : 77 -1 UB: 0.38878206517457253 3 : 240 38 UB: 0.38590398350638383 4 : 41 -7 UB: 0.3798603508868026 5 : 30 -8 UB: 0.37700033307891573 6 : 32 -8 UB: 0.3732278926294834 Player 2: mcts wins!	Children: 0 : 70 -5 UB: 1.4183710433833132 1 : 88 10 UB: 1.4423626952503967 2 : 74 -2 UB: 1.4219483913222528 3 : 83 5 UB: 1.4284039326436107 4 : 49 -17 UB: 1.4337123462883201 5 : 67 -6 UB: 1.4332358681919308 6 : 69 -5 UB: 1.4280926623049885 Player 2: mcts wins!	Children: 0 : 69 -7 UB: 5.900776446321403 1 : 75 12 UB: 5.9171326652178475 2 : 68 -10 UB: 5.899139835629324 3 : 75 11 UB: 5.903799331884514 4 : 74 8 UB: 5.904009781505227 5 : 70 -4 UB: 5.9020556021046815 6 : 69 -7 UB: 5.900776446321403 Player 2: mcts wins!
Game 5	Children: 0 : 79 11 UB: 0.5358912980754142 1 : 18 -6 UB: 0.4976371901726448 2 : 70 8 UB: 0.5356646783827503 3 : 227 72 UB: 0.5511768910133419 4 : 14 -6 UB: 0.5136605794379874 5 : 49 1 UB: 0.5240523565257739 6 : 43 -1 UB: 0.5143793220462873 Player 1: mcts wins!	Children: 0 : 71 7 UB: 1.577862412990733 1 : 60 -2 UB: 1.5758341660306223 2 : 82 16 UB: 1.5716020967292013 3 : 80 14 UB: 1.5685799333934651 4 : 73 8 UB: 1.568455191455523 5 : 75 9 UB: 1.559283166304462 6 : 59 -4 UB: 1.554950602516634 Player 1: mcts wins!	Children: 0 : 65 -11 UB: 6.014921730840405 1 : 71 7 UB: 6.015675004075608 2 : 76 22 UB: 6.008605058458391 3 : 74 16 UB: 6.012117889613336 4 : 71 7 UB: 6.015675004075608 5 : 73 13 UB: 6.013546793219352 6 : 70 4 UB: 6.016341316390395 Player 1: mcts wins!
Game 6	Children: 0 : 61 -3 UB: 0.402214889840883 1 : 75 -1 UB: 0.3937574214432789 2 : 46 -6 UB: 0.3893732128139533 3 : 162 20 UB: 0.4004469646254495 4 : 75 -1 UB: 0.3937574214432789 5 : 49 -5 UB: 0.4016033769339371 6 : 32 -8 UB: 0.3732278926294834 Player 2: mcts wins!	Children: 0 : 53 -17 UB: 1.3913839790216451 1 : 65 -9 UB: 1.4075765865562553 2 : 99 13 UB: 1.384048330547009 3 : 105 19 UB: 1.397368672713728 4 : 49 -19 UB: 1.3928960197577078 5 : 58 -14 UB: 1.3952973184523654 6 : 71 -7 UB: 1.3806793143991836 Player 2: mcts wins!	Children: 0 : 70 -4 UB: 5.9020556021046815 1 : 66 -12 UB: 5.955305860075468 2 : 72 2 UB: 5.9036266991499025 3 : 76 14 UB: 5.903341900563654 4 : 75 13 UB: 5.930465998551181 5 : 71 -1 UB: 5.902998947737579 6 : 70 -2 UB: 5.93062703067611 Player 2: mcts wins!
Game 7	Children: 0 : 37 -3 UB: 0.49850908625863083 1 : 79 13 UB: 0.5612077537716167 2 : 75 7 UB: 0.5004240881099455 3 : 82 10 UB: 0.5112785975356139 4 : 101 15 UB: 0.49931614353437936 5 : 25 -5 UB: 0.5051018705646548 6 : 101 15 UB: 0.49931614353437936 Player 1: mcts wins!	Children: 0 : 61 3 UB: 1.6451034250575118 1 : 62 4 UB: 1.647516559312368 2 : 77 19 UB: 1.6672214449488725 3 : 93 34 UB: 1.6581058367802912 4 : 84 26 UB: 1.6695185681821043 5 : 53 -3 UB: 1.6555349224178715 6 : 70 12 UB: 1.661228186240456 Player 1: mcts wins!	Children: 0 : 74 16 UB: 6.012117889613336 1 : 69 1 UB: 6.016718475306911 2 : 75 21 UB: 6.037132665217848 3 : 72 10 UB: 6.014737810261014 4 : 66 -10 UB: 5.985608890378498 5 : 73 15 UB: 6.040944053493325 6 : 71 7 UB: 6.015675004075608 Player 1: mcts wins!

Game 8	Children: 0 : 43 -7 UB: 0.37484443832535713 1 : 56 -4 UB: 0.3996874325761365 2 : 88 1 UB: 0.3871841961337997 3 : 102 4 UB: 0.3882931286184349 4 : 53 -5 UB: 0.3899263302686732 5 : 90 2 UB: 0.39384353779381287 6 : 68 -2 UB: 0.39811904252333297 Player 2: mcts wins!	Children: 0 : 53 -10 UB: 1.5234594507197583 1 : 82 12 UB: 1.5228216089243232 2 : 68 2 UB: 1.5409614294955662 3 : 84 14 UB: 1.5266614253249615 4 : 63 -3 UB: 1.5227676323966455 5 : 79 9 UB: 1.5162963736670212 6 : 71 3 UB: 1.5215243848217188 Player 2: mcts wins!	Children: 0 : 67 -13 UB: 5.8971225772453355 1 : 68 -10 UB: 5.899139835629324 2 : 74 6 UB: 5.8769827544782 3 : 83 37 UB: 5.918435007682876 4 : 71 -3 UB: 5.874829933653072 5 : 70 -4 UB: 5.9020556021046815 6 : 67 -15 UB: 5.867271830976678 Player 1: ab5 wins!
Game 9	Children: 0 : 31 -3 UB: 0.5364259785636568 1 : 59 5 UB: 0.5437279860086357 2 : 145 40 UB: 0.5686396848995743 3 : 29 -3 UB: 0.5512223756568083 4 : 75 11 UB: 0.5537574214432789 5 : 114 26 UB: 0.5582643792838804 6 : 47 1 UB: 0.5355249875199956 Player 1: mcts wins!	Children: 0 : 69 7 UB: 1.6020057057832495 1 : 62 0 UB: 1.58300043028011 2 : 74 12 UB: 1.6111375805114418 3 : 95 31 UB: 1.6051524419806857 4 : 90 26 UB: 1.6027686502595775 5 : 68 5 UB: 1.5850790765543898 6 : 42 -14 UB: 1.5899896991175513 Player 1: mcts wins!	Children: 0 : 67 1 UB: 6.106077801125933 1 : 74 24 UB: 6.120225997721444 2 : 70 12 UB: 6.13062703067611 3 : 79 39 UB: 6.103160178212389 4 : 70 12 UB: 6.13062703067611 5 : 68 2 UB: 6.075610423864618 6 : 72 16 UB: 6.098071143594347 Player 2: ab5 wins!
Game 10	Children: 0 : 62 -4 UB: 0.3832240065166573 1 : 106 5 UB: 0.3895975505213102 2 : 10 -8 UB: 0.31486394671477225 3 : 102 4 UB: 0.3882931286184349 4 : 97 9 UB: 0.45074474530782105 5 : 41 -7 UB: 0.3798603508868026 6 : 82 0 UB: 0.38932737802341877 Player 2: mcts wins!	Children: 0 : 49 -17 UB: 1.4337123462883201 1 : 76 0 UB: 1.4297828435619662 2 : 86 8 UB: 1.4371110958133926 3 : 89 11 UB: 1.4448359955141452 4 : 63 -9 UB: 1.4275295371585504 5 : 71 -3 UB: 1.4370173425681978 6 : 66 -7 UB: 1.4282204044128064 Player 2: mcts wins!	Children: 0 : 70 -4 UB: 5.9020556021046815 1 : 77 17 UB: 5.902652013561724 2 : 68 -10 UB: 5.899139835629324 3 : 77 18 UB: 5.915639026548737 4 : 71 0 UB: 5.917083454779833 5 : 71 -3 UB: 5.874829933653072 6 : 66 -18 UB: 5.864396769166377 Player 2: mcts wins!

Smaller c values work better than larger c values. Sqrt(2) seems to work the best.

2.

python ConnectFour.py mcts ab -p2_-n 2

	max_iterations (MCTS)	depth_limit (AB)	MCTS wins / AB wins
Game 1	10	1	0 / 4
Game 2	25	2	1 / 3
Game 3	50	3	2 / 2
Game 4	75	4	3 / 1
Game 5	100	5	4 / 0

AB performs better with less computational resources.

MCTS performs better as computational resources increase.

3.

MCTS hardly loses to me with 500-1000 max_iterations.

MCTS performs well compared to AB and EM.

MCTS is definitely the strongest of my agents.

4.

5 hours.

No.

No.

```
# Modified 10.3.2023 by Chris Archibald to
# - incorporate MCTS with other code
# - pass command line param string to each AI
```

```
import numpy as np
import random
```

```
class AIPlayer:
```

```
def __init__(self, player_number, name, ptype, param):
    self.player_number = player_number
    self.name = name
    self.type = ptype
    self.player_string = 'Player {}':'.format(player_number) + self.name
    self.other_player_number = 1 if player_number == 2 else 2

    # Parameters for the different agents

    self.depth_limit = 3 # default depth-limit - change if you desire
    # Alpha-beta
    # Example of using command line param to overwrite depth limit
    if self.type == 'ab' and param:
        self.depth_limit = int(param)

    # Expectimax
    # Example of using command line param to overwrite depth limit
    if self.type == 'expmax' and param:
        self.depth_limit = int(param)

    # MCTS
    self.max_iterations = 1000 # Default max-iterations for MCTS - change if you desire
    # Example of using command line param to overwrite max-iterations for MCTS
    if self.type == 'mcts' and param:
        self.max_iterations = int(param)
```

```
def get_alpha_beta_move(self, board):
    """
```

```
    Given the current state of the board, return the next move based on
    the alpha-beta pruning algorithm
```

```
    This will play against either itself or a human player
```

```
    INPUTS:
```

```
    board - a numpy array containing the state of the board using the
    following encoding:
        - the board maintains its same two dimensions
        - row 0 is the top of the board and so is
          the last row filled
        - spaces that are unoccupied are marked as 0
        - spaces that are occupied by player 1 have a 1 in them
        - spaces that are occupied by player 2 have a 2 in them
```

```
    RETURNS:
```

```
    The 0 based index of the column that represents the next move
    """
```

```
    # moves = get_valid_moves(board)
```

```
    # best_move = np.random.choice(moves)
```

```
    # YOUR ALPHA-BETA CODE GOES HERE
```

```
    my_board = np.copy(board)
```

```
    value, best_move = self.max_value(my_board, self.depth_limit, float('-inf'), float('inf'))
```

```
    return best_move
```

```
def max_value(self, board, limit, a, b):
```

```
    v = float('-inf')
```

```
    m = -1
```

```
    if is_winning_state(board, self.player_number) or is_winning_state(board, self.other_player_number) or (limit == 0):
        return self.evaluation_function(board), m
```

```
    limit -= 1
```

```
    for act in get_valid_moves(board):
```

```
        my_board = np.copy(board)
```

```
        make_move(my_board, act, self.player_number)
```

```
        new_v, new_m = self.min_value(my_board, limit, a, b)
```

```
        if v <= new_v:
```

```
            v = new_v
```

```
            m = act
```

```

        if v >= b:
            return v, m
        a = max(a, v)

    return v, m

def min_value(self, board, limit, a, b):
    v = float('inf')
    m = -1

    if is_winning_state(board, self.player_number) or is_winning_state(board, self.other_player_number) or (limit == 0):
        return self.evaluation_function(board), m

    limit -= 1

    for act in get_valid_moves(board):
        my_board = np.copy(board)
        make_move(my_board, act, self.other_player_number)
        new_v, new_m = self.max_value(my_board, limit, a, b)
        if v >= new_v:
            v = new_v
            m = act
        if v <= a:
            return v, m
        b = min(b, v)

    return v, m

def get_mcts_move(self, board):
    """
    Use MCTS to get the next move
    """

    # How many iterations of MCTS will we do?
    max_iterations = 1000 # Modify to work for you

    # Make the MCTS root node from the current board state
    root = MCTSNode(board, self.player_number, None)

    # Run our MCTS iterations
    for i in range(max_iterations):
        # Select + Expand
        cur_node = root.select()

        # Simulate + backpropagate
        cur_node.simulate()

    # Print out the info from the root node
    root.print_node()
    print('MCTS chooses action', root.max_child())
    return root.max_child()

def get_expectimax_move(self, board):
    """
    Given the current state of the board, return the next move based on
    the expectimax algorithm.

    This will play against the random player, who chooses any valid move
    with equal probability

    INPUTS:
    board - a numpy array containing the state of the board using the
    following encoding:
        - the board maintains its same two dimensions
        - row 0 is the top of the board and so is
          the last row filled
        - spaces that are unoccupied are marked as 0
        - spaces that are occupied by player 1 have a 1 in them
        - spaces that are occupied by player 2 have a 2 in them

    RETURNS:
    The 0 based index of the column that represents the next move
    """

    # moves = get_valid_moves(board)
    # best_move = np.random.choice(moves)

    # YOUR EXPECTIMAX CODE GOES HERE

    my_board = np.copy(board)

    value, best_move = self.player_value(my_board, self.depth_limit)

```

```

        if best_move == -1:
            best_move = get_valid_moves(board)[0]

    return best_move

def player_value(self, board, limit):
    v = float('-inf')
    m = -1

    if is_winning_state(board, self.player_number) or is_winning_state(board, self.other_player_number) or (limit == 0):
        return self.evaluation_function(board), m

    limit -= 1

    for act in get_valid_moves(board):
        my_board = np.copy(board)
        make_move(my_board, act, self.player_number)
        new_v, new_m = self.chance_value(my_board, limit)
        if v <= new_v:
            v = new_v
            m = act

    return v, m

def chance_value(self, board, limit):
    v = 0
    m = -1

    if is_winning_state(board, self.player_number) or is_winning_state(board, self.other_player_number) or (limit == 0):
        return self.evaluation_function(board), m

    limit -= 1

    chance = 1 / len(get_valid_moves(board))
    for act in get_valid_moves(board):
        my_board = np.copy(board)
        make_move(my_board, act, self.other_player_number)
        new_v, new_m = self.player_value(my_board, limit)
        v += new_v * chance

    return v, m

def evaluation_function(self, board):
    """
    Given the current stat of the board, return the scalar value that
    represents the evaluation function for the current player

    INPUTS:
    board - a numpy array containing the state of the board using the
    following encoding:
    - the board maintains its same two dimensions
    - row 0 is the top of the board and so is
      the last row filled
    - spaces that are unoccupied are marked as 0
    - spaces that are occupied by player 1 have a 1 in them
    - spaces that are occupied by player 2 have a 2 in them

    RETURNS:
    The utility value for the current board
    """

    # YOUR EVALUATION FUNCTION GOES HERE

    #player_board = np.copy(board)
    #player_board[player_board == 0] = self.player_number
    #num_4s = num_in_state(player_board, '{0}{0}{0}{0}'.format(self.player_number))
    num_4s = num_in_state(board, '{0}{0}{0}{0}'.format(self.player_number))
    if num_4s > 0:
        return float('inf')
    num_4b = num_in_state(board, '{0}{0}{0}{1}'.format(self.other_player_number, self.player_number))
    num_4b += num_in_state(board, '{1}{0}{0}{0}'.format(self.other_player_number, self.player_number))
    num_4b += num_in_state(board, '{0}{0}{1}{0}'.format(self.other_player_number, self.player_number))
    num_4b += num_in_state(board, '{0}{1}{0}{0}'.format(self.other_player_number, self.player_number))
    num_3s = num_in_state(board, '{0}{0}{0}'.format(self.player_number))
    num_3b = num_in_state(board, '{0}{0}{1}'.format(self.other_player_number, self.player_number))
    num_3b += num_in_state(board, '{1}{0}{0}'.format(self.other_player_number, self.player_number))
    num_2s = num_in_state(board, '{0}{0}'.format(self.player_number))

    #enemy_board = np.copy(board)
    #enemy_board[enemy_board == 0] = self.other_player_number
    #op_num_4s = num_in_state(enemy_board, '{0}{0}{0}{0}'.format(self.other_player_number))
    op_num_4s = num_in_state(board, '{0}{0}{0}{0}'.format(self.other_player_number))

```

```

if op_num_4s > 0:
    return float('-inf')
op_num_4b = num_in_state(board, '{0}{0}{0}{1}'.format(self.player_number, self.other_player_number or 0))
op_num_4b += num_in_state(board, '{1}{0}{0}{0}'.format(self.player_number, self.other_player_number or 0))
op_num_4b += num_in_state(board, '{0}{0}{1}{0}'.format(self.player_number, self.other_player_number or 0))
op_num_4b += num_in_state(board, '{0}{1}{0}{0}'.format(self.player_number, self.other_player_number or 0))
op_num_3s = num_in_state(board, '{0}{0}{0}'.format(self.other_player_number))
op_num_3b = num_in_state(board, '{0}{0}{1}'.format(self.player_number, self.other_player_number or 0))
op_num_3b += num_in_state(board, '{1}{0}{0}'.format(self.player_number, self.other_player_number or 0))
op_num_2s = num_in_state(board, '{0}{0}'.format(self.other_player_number))

#return num_4s - op_num_4s
return (10000*num_4b + 500*num_3s + 20*num_3b + 1*num_2s) - (10000*op_num_4b + 500*op_num_3s + 20*op_num_3b + 1*op_num_2s)

def num_in_state(board, player_win_str):
    to_str = lambda a: ".join(a.astype(str))

def check_horizontal(b):
    num = 0
    for row in b:
        num += to_str(row).count(player_win_str)
    return num

def check_verticle(b):
    return check_horizontal(b.T)

def check_diagonal(b):
    num = 0

    for op in [None, np.fliplr]:
        op_board = op(b) if op else b

        root_diag = np.diagonal(op_board, offset=0).astype(int)
        num += to_str(root_diag).count(player_win_str)

        for i in range(1, b.shape[1] - 3):
            for offset in [i, -i]:
                diag = np.diagonal(op_board, offset=offset)
                diag = to_str(diag.astype(int))
                num += diag.count(player_win_str)

    return num

return (check_horizontal(board) +
        check_verticle(board) +
        check_diagonal(board))

class RandomPlayer:
    def __init__(self, player_number):
        self.player_number = player_number
        self.type = 'random'
        self.name = 'random'
        self.player_string = 'Player {}: random'.format(player_number)

    def get_move(self, board):
        """
        Given the current board state select a random column from the available
        valid moves.

        INPUTS:
        board - a numpy array containing the state of the board using the
        following encoding:
            - the board maintains its same two dimensions
            - row 0 is the top of the board and so is
              the last row filled
            - spaces that are unoccupied are marked as 0
            - spaces that are occupied by player 1 have a 1 in them
            - spaces that are occupied by player 2 have a 2 in them

        RETURNS:
        The 0 based index of the column that represents the next move
        """
        valid_cols = []
        for col in range(board.shape[1]):
            if 0 in board[:, col]:
                valid_cols.append(col)

        return np.random.choice(valid_cols)

class HumanPlayer:

```

```

def __init__(self, player_number):
    self.player_number = player_number
    self.type = 'human'
    self.name = 'human'
    self.player_string = 'Player {}: human'.format(player_number)

def get_move(self, board):
    """
    Given the current board state returns the human input for next move

    INPUTS:
    board - a numpy array containing the state of the board using the
    following encoding:
        - the board maintains its same two dimensions
        - row 0 is the top of the board and so is
          the last row filled
        - spaces that are unoccupied are marked as 0
        - spaces that are occupied by player 1 have a 1 in them
        - spaces that are occupied by player 2 have a 2 in them

    RETURNS:
    The 0 based index of the column that represents the next move
    """

    valid_cols = []
    for i, col in enumerate(board.T):
        if 0 in col:
            valid_cols.append(i)

    move = int(input('Enter your move, Human: '))

    while move not in valid_cols:
        print('Column full, choose from: {}'.format(valid_cols))
        move = int(input('Enter your move: '))

    return move

```

CODE FOR MCTS

```

class MCTSNode:
    def __init__(self, board, player_number, parent):
        self.board = board
        self.player_number = player_number
        self.other_player_number = 1 if player_number == 2 else 2
        self.parent = parent
        self.moves = get_valid_moves(board)
        self.terminal = (len(self.moves) == 0) \
            or is_winning_state(board, player_number) \
            or is_winning_state(board, self.other_player_number)
        self.children = dict()
        for m in self.moves:
            self.children[m] = None

    # Set up stats for MCTS
    # Number of visits to this node
    self.n = 0

    # Total number of wins from this node (win = +1, loss = -1, tie = +0)
    # Note: these wins are from the perspective of the PARENT node of this node
    # So, if self.player_number wins, that is -1, while if self.other_player_number wins
    # that is a +1. (Since parent will be using our UCB value to make choice)
    self.w = 0

    # c value to be used in the UCB calculation
    self.c = np.sqrt(2)

def print_tree(self):
    # Debugging utility that will print the whole subtree starting at this node
    print("*****")
    self.print_node(self)
    for m in self.moves:
        if self.children[m]:
            self.children[m].print_tree()
    print("*****")

def print_node(self):
    # Debugging utility that will print this node's information
    print('Total Node visits and wins: ', self.n, self.w)
    print('Children: ')
    for m in self.moves:
        if self.children[m] is None:
            print(' ', m, ' is None')

```

```

else:
    print(' ', m, ': ', self.children[m].n, self.children[m].w, 'UB: ',
          self.children[m].upper_bound(self.n))

def max_child(self):
    # Return the most visited child
    # This is used at the root node to make a final decision
    max_n = 0
    max_m = None

    for m in self.moves:
        if self.children[m].n > max_n:
            max_n = self.children[m].n
            max_m = m
    return max_m

def upper_bound(self, N):
    # This function returns the UCB for this node
    # N is the number of samples for the parent node, to be used in UCB calculation

    # YOUR MCTS TASK 1 CODE GOES HERE

    # To do: return the UCB for this node (look in __init__ to see the values you can use)

    u_b = (self.w / self.n) + (self.c * np.sqrt(np.log(N) / self.n))

    return u_b

def select(self):
    # This recursive function combines the selection and expansion steps of the MCTS algorithm
    # It will return either:
    # A terminal node, if this is the node selected
    # The new node added to the tree, if a leaf node is selected

    max_ub = -np.inf # Track the best upper bound found so far
    max_child = None # Track the best child found so far

    if self.terminal:
        # If this is a terminal node, then return it (the game is over)
        return self

    # For all of the children of this node
    for m in self.moves:
        if self.children[m] is None:
            # If this child doesn't exist, then create it and return it
            new_board = np.copy(self.board) # Copy board/state for the new child
            make_move(new_board, m, self.player_number) # Make the move in the state

            self.children[m] = MCTSNode(new_board, self.other_player_number, self) # Create the child node
            return self.children[m] # Return it

        # Child already exists, get it's UCB value
        current_ub = self.children[m].upper_bound(self.n)

        # Compare to previous best UCB
        if current_ub > max_ub:
            max_ub = current_ub
            max_child = m

    # Recursively return the select result for the best child
    return self.children[max_child].select()

def simulate(self):
    # This function will simulate a random game from this node's state and then call back on its
    # parent with the result

    # YOUR MCTS TASK 2 CODE GOES HERE

    # Pseudocode in comments:
    #####

    result = None

    # If this state is terminal (meaning the game is over) AND it is a winning state for self.other_player_number
    if is_winning_state(self.board, self.other_player_number):
        # Then we are done and the result is 1 (since this is from parent's perspective)
        result = 1
    #
    # Else-if this state is terminal AND is a winning state for self.player_number
    elif is_winning_state(self.board, self.player_number):
        # Then we are done and the result is -1 (since this is from parent's perspective)
        result = -1
    #

```



```

# Else-if this is not a terminal state (if it is terminal and a tie (no-one won, then result is 0))
elif len(get_valid_moves(self.board)) == 0:
    result = 0
else:
    # Then we need to perform the random rollout
    # 1. Make a copy of the board to modify
    my_board = np.copy(self.board)
    # 2. Keep track of which player's turn it is (first turn is current node's self.player_number)
    turn = self.player_number
    # 3. Until the game is over:
    while result is None:
        # 3.1 Make a random move for the player who's turn it is

        act = random.choice(get_valid_moves(my_board))
        make_move(my_board, act, turn)
        # 3.2 Check to see if someone won or the game ended in a tie
        # (Hint: you can check for a tie if there are no more valid moves)
        # 3.3 If the game is over, store the result
        if is_winning_state(my_board, self.other_player_number):
            result = 1
        elif is_winning_state(my_board, self.player_number):
            result = -1
        elif len(get_valid_moves(my_board)) == 0:
            result = 0
        # 3.4 If game is not over, change the player and continue the loop
    else:
        if turn == self.player_number:
            turn = self.other_player_number
        else:
            turn = self.player_number

    # Update this node's total reward (self.w) and visit count (self.n) values to reflect this visit and result
    self.w += result
    self.n += 1
    # Back-propagate this result
    # You do this by calling back on the parent of this node with the result of this simulation
    # This should look like: self.parent.back(result)
    # Tip: you need to negate the result to account for the fact that the other player
    # is the actor in the parent node, and so the scores will be from the opposite perspective
    self.parent.back(-result)

def back(self, score):
    # This updates the stats for this node, then backpropagates things
    # to the parent (note the inverted score)
    self.n += 1
    self.w += score
    if self.parent is not None:
        self.parent.back(-score) # Score inverted before passing along

# UTILITY FUNCTIONS

# This function will modify the board according to
# player_number moving into move column
def make_move(board, move, player_number):
    row = 0
    while row < 6 and board[row, move] == 0:
        row += 1
    board[row - 1, move] = player_number

# This function will return a list of valid moves for the given board
def get_valid_moves(board):
    valid_moves = []
    for c in range(7):
        if 0 in board[:, c]:
            valid_moves.append(c)
    return valid_moves

# This function returns true if player_num is winning on board
def is_winning_state(board, player_num):
    player_win_str = '{0}{0}{0}{0}'.format(player_num)
    to_str = lambda a: ''.join(a.astype(str))

    def check_horizontal(b):
        for row in b:
            if player_win_str in to_str(row):
                return True
        return False

    def check_verticle(b):

```

```
    return check_horizontal(b.T)

def check_diagonal(b):
    for op in [None, np.flipr]:
        op_board = op(b) if op else b

        root_diag = np.diagonal(op_board, offset=0).astype(int)
        if player_win_str in to_str(root_diag):
            return True

    for i in range(1, b.shape[1] - 3):
        for offset in [1, -1]:
            diag = np.diagonal(op_board, offset=offset)
            diag = to_str(diag.astype(int))
            if player_win_str in diag:
                return True

    return False

return (check_horizontal(board) or
        check_verticle(board) or
        check_diagonal(board))
```