

Modelling and Networked Control of Water Distribution Networks

January 18, 2022

CA733

Control and Automation, Group 733
Aalborg University
Denmark



AALBORG UNIVERSITY
DENMARK

Modelling and
Networked Control of
Water Distribution
Networks
CA733

Introduction

General optimal control problem

Infinite-Horizon Linear-Quadratic Regulator

Tracking LQR and Integral Action

Velocity-Form LQR

Exogenous input disturbance-accommodating LQR

References

Introduction

General optimal
control problem

Infinite-Horizon
Linear-Quadratic
Regulator

Tracking LQR and
Integral Action

Velocity-Form LQR

Exogenous input
disturbance-
accommodating LQR

References

- ▶ Critical societal infrastructure, responsible for the provision of water to both domestic and industrial consumers.
- ▶ Network pressure must be controlled.
 - ▶ Underpressure → insufficient service pressure → dissatisfied end users.
 - ▶ Overpressure → component failure → repair costs, supply intermittency, etc.
- ▶ Network pressure tied to level in Elevated Water Reservoir(s) (EWR) → level control is key!
- ▶ Other key components are pumps, valves, and pipes.

Introduction

Test Water Distribution Network Layout

Modelling and
Networked Control of
Water Distribution
Networks
CA733

3

Introduction

General optimal
control problem

Infinite-Horizon
Linear-Quadratic
Regulator


Tracking LQR and
Integral Action

Velocity-Form LQR

Exogenous input
disturbance-
accommodating LQR

References

We analyse a small-scale test WDN with the following layout:



Larger WDNs are typically not amenable to first-principles modelling.

11

General optimal control problem

Modelling and
Networked Control of
Water Distribution
Networks
CA733

Introduction

General optimal
control problem

Infinite-Horizon
Linear-Quadratic
Regulator

Tracking LQR and
Integral Action

Velocity-Form LQR

Exogenous input
disturbance-
accommodating LQR

References

4

The basic structure of an optimal control problem is sketched in the language of calculus of variations.

$$\dot{x} = f(x, u, t) \quad (1)$$

$$x(t_0) = x_0, \quad x \in \mathbb{R}^n, \quad u \in U \in \mathbb{R}^m \quad (2)$$

where $t \in \mathbb{R}$ is the time and x, u are functions of t , with U the set of admissible controls.

Cost functional:

$$J = \mathcal{M}(x(T)) + \int_0^T \mathcal{L}(x(t), u(t)) dt \quad (3)$$

11

Infinite-Horizon Linear-Quadratic Regulator

Modelling and
Networked Control of
Water Distribution
Networks
CA733

Introduction

General optimal
control problem

Infinite-Horizon
Linear-Quadratic
Regulator

Tracking LQR and
Integral Action

Velocity-Form LQR

Exogenous input
disturbance-
accommodating LQR

References

Control and Automation
Aalborg University
Denmark

5

The LQR timeinvariant case with no terminal cost.
System Dynamics:

$$\dot{x}(t) = Ax(t) + Bu(t) \quad (4)$$

Cost functional:

$$J = \int_{t_0}^{\infty} (x^T(t)Qx(t) + u^T(t)Ru(t)) dt \quad (5)$$

State feedback control law:

$$u^*(t) = -R^{-1}B^T Px^*(t) \quad (6)$$

P is time-invariant and fullfills the *algebraic Riccati equation*:

$$PA + A^T P + Q - PBR^{-1}B^T P = 0 \quad (7)$$

Tracking LQR and Integral Action

Tracking LQR

Modelling and
Networked Control of
Water Distribution
Networks
CA733

Introduction

General optimal
control problem

Infinite-Horizon
Linear-Quadratic
Regulator

Tracking LQR and
Integral Action

Velocity-Form LQR

Exogenous input
disturbance-
accommodating LQR

References

6

Let $\hat{x} = x - x_r$ and $\hat{u} = u - u_r$. Shifted coordinate system cost functional framed as an output tracking problem:

$$J = \int_{t_0}^{\infty} ((C\hat{x})^T Q_y (C\hat{x}) + \hat{u}^T R \hat{u}) dt = \int_{t_0}^{\infty} (\hat{y}^T Q_y \hat{y} + \hat{u}^T R \hat{u}) dt \quad (8)$$

11

States are extended with integral state x_i

$$u = -\bar{K}\bar{x} \quad (9)$$

$$\dot{\bar{x}} = \bar{A}\bar{x} + \bar{B}u + B_r r \quad (10)$$

$$y = \bar{C}\bar{x} \quad (11)$$

$$\bar{A} = \begin{bmatrix} A & 0 \\ -C & 0 \end{bmatrix}, \quad \bar{B} = \begin{bmatrix} B \\ 0 \end{bmatrix}, \quad B_r = \begin{bmatrix} 0 \\ 1 \end{bmatrix}, \quad \bar{C} = [C \quad 0] \quad (12)$$

$$\bar{K} = -[K \quad -K_i] \quad (13)$$

K_i can be an awkward weight to choose.

Velocity-Form LQR

Modelling and
Networked Control of
Water Distribution
Networks
CA733

Introduction

General optimal
control problem

Infinite-Horizon
Linear-Quadratic
Regulator

Tracking LQR and
Integral Action

Velocity-Form LQR

Exogenous input
disturbance-
accommodating LQR

References

8

Deviation variables:

$$\Delta x_k = x_k - x_{k-1}, \Delta y_k = y_k - r_k, \Delta u_k = u_k - u_{k-1} \quad (14)$$

Extended vectors and matrices:

$$\begin{aligned} \tilde{\zeta}_k &= \begin{bmatrix} \Delta x_k \\ \Delta y_k \end{bmatrix}, \tilde{u}_k = \Delta u_k, \\ \tilde{A} &= \begin{bmatrix} A & 0 \\ CA & I \end{bmatrix}, \tilde{B} = \begin{bmatrix} B \\ CB \end{bmatrix}, \tilde{C} = [0 \quad I] \end{aligned} \quad (15)$$

Cost functional:

$$J = \sum_{k_0}^{\infty} (\tilde{\zeta}^T Q \tilde{\zeta} + \tilde{u}^T R \tilde{u}) \quad (16)$$

Origin regulation! If $\tilde{\zeta} \rightarrow 0 \Rightarrow \Delta y \rightarrow 0 \Rightarrow y \rightarrow r$.

11

If linearising around equilibrium point x_e and corresponding operating point u_{op}

$$\Delta \tilde{x} = x - x_e, \quad \Delta \tilde{u} = u - u_{op} \quad (17)$$

VF-LQR will penalize deviations from the point $\{x_e, u_{op}, r\}$!

Incremental feedback law:

$$\Delta u^*(k) = -\Delta K(k) \Delta x(k) \quad (18)$$

Control input applied at time k is:

$$u^*(k) = \sum_{i=1}^k \Delta u^*(i) \quad (19)$$

with

$$\tilde{K} = (\tilde{B}^T P \tilde{B} - R)^{-1} (\tilde{B}^T P \tilde{A}) \quad (20)$$

Exogenous input disturbance- accommodating LQR

Modelling and
Networked Control of
Water Distribution
Networks
CA733

Introduction

General optimal
control problem

Infinite-Horizon
Linear-Quadratic
Regulator

Tracking LQR and
Integral Action

Velocity-Form LQR

Exogenous input
disturbance-
accommodating LQR

References

10

Standard LQR does not accommodate exogenous inputs (such as the the model of the consumer demand flows) but can be modified to do so:

$$u(k) = \sum_{i=1}^k \Delta u^*(i) - B^\dagger \mathcal{B} \delta(i) \quad (21)$$

where B^\dagger is the Moore-Penrose pseudoinverse of B and \mathcal{B} is the disturbance input matrix.

11



References

Modelling and
Networked Control of
Water Distribution
Networks
CA733

Introduction

General optimal
control problem

Infinite-Horizon
Linear-Quadratic
Regulator

Tracking LQR and
Integral Action

Velocity-Form LQR

Exogenous input
disturbance-
accommodating LQR

References

11

11

Open for questions!



AALBORG UNIVERSITY
DENMARK