Qualcomm Technologies, Inc.



Device Pairing Subsystem 3.0.0

User Guide (Authority)

DPS-User-Guide-Authority-3.0.0

November 23, 2020

Revision history

Revision	Date	Description
A		Initial release
B	November 2020	Release 3.0.0

Contents

Figures

Tables

1. Introduction

The Device Pairing Subsystem (DPS) is the subsystem of Device Identification, Registration and Blocking System (DIRBS). The main purpose of DPS is to facilitate the pairing of user's devices with their SIMs (IMSIs) over the SMS service. It also generates Pairing-list for DIRBS-Core through which it generates exception list and black list for MNOs to implement on their EIR.

The Device Identification, Registration & Blocking System (DIRBS) is a country-wide system that is developed to check, identify and discourage non-compliant devices by verifying the installed base of devices currently active in a market. It continuously monitors the mobile eco system as new devices are activated. It can be deployed in collaboration with country's regulatory bodies, Mobile operators and other technology partners.

DIRBS can verify that:

- Devices have properly allocated identifiers and type approval
- Devices are not duplicated or stolen
- Device importation takes place through legal channels

1.1. Purpose

This document is intended to give assistance to the user to use the Device Pairing Subsystem (DPS).

1.2. Supported Desktop Browsers

Table 1 - Supported Desktop Browsers

Name	Version
Internet Explorer	11.0
Firefox	82.0.3
Chrome	86.0
Safari	13.1.2
Edge	86.0

1.3. Supported Mobile Browsers

Table 2 - Supported Mobile Browsers

Name	Version
Chrome	86.0.4
UC Browser	13.3.3
Opera (Android)	60.3

Name	Version
Opera Touch (iOS)	2.5.1
Safari	13.1.2
Samsung Internet	13.0.1
Android	10

1.4. Definitions, Acronyms, and Abbreviations

Table 3 - Definitions, Acronyms, and Abbreviations

Term	Definition
DIRBS	Device Identification Registration and Blocking System
IAM	Identity Access Management
DPS	Device Pairing Subsystem
MSISDN	Mobile Subscriber Integrated Services Digital Network Number
IMEI	International Mobile Equipment Identity
MAC	Media Access Control
SMS	Short Message Service

2. System Description

Table 4 - System Description

Feature/Sections	Description
Login Screen	• To access the system, authorized user first needs to enter his/her credentials on login page. This login page authenticates user from the IAM and redirects user to the DPS
Portal Sections	The portal is divided into following sections. • **Header** Header section displays name of the system, name of the logged in user with logout functionality. • **Navigation Panel** Navigation Panel contains main navigation menu through which user can navigate the whole system. • **Main Content Area** Main Content Area contains all the content to be displayed and actions to be performed for respective feature. • **Breadcrumbs** Breadcrumbs allow user to keep track of their location within the system. • **Footer** Footer contains the software version and copyright statement.

Feature/Sections	Description
Generate Pair Code	Allows user to enter device details to generate pair code. • **Device IMEI** Enter IMEI number for which you want to get a pair code, for multiple number of IMEIs click on “Add IMEIs” button. **Device Identifiers** **Serial Number** Enter serial number of the device. **Brand** Enter brand name of the device. **Model Name** Enter model name of the device. **MAC (Wi-Fi) address** Enter MAC address of the device in below formats: A2:C9:66:F8:47:C5 A2-C9-66-F8-47-C5 A2C.966.F84.7C5 00:25:96:FF:FE:12:34:56 0025:96FF:FE12:3456 **Radio Access Technology** Select radio access technology of the system i.e. 2G, 3G, 4G, 5G etc. **Reference MSISDN** Enter MSISDN number as a reference contact number.
Search Request	Allows user to search particular request by applying different filters i.e. IMEI, Serial Number, MAC Address, Reference MSISDN

3. System Navigation

3.1 Log-In Screen

1. Enter user credentials i.e. username and password
2. Click on the “Log-In” button



Figure 1 - login Screen

3.2 Portal Sections

The portal screen is divided into following sections.

1. **Header** section displays name of the system, name of the logged-in user with logout functionality
2. **Main Navigation Panel** helps user to navigate through system
3. **Breadcrumb** is a navigational aid in UI
4. **Main Content Area** contains all relevant information related to the respective feature/option
5. **Footer** contains version and copyrights of the system



Figure 2 - Portal Overview

3.3 Generate Pair Code

1. Click on the “Generate Pair Code” tab under the “Main Navigation” heading
2. Type and Retype IMEI number in the respective field

Note: IMEI can contain alphanumeric characters (0-9, A-F, a-f). The length of the IMEI should be between 14-16 characters

3. For more IMEIs, click on “Add IMEIs” button

Note: Maximum 5 IMEI numbers can be added

4. Enter Device Identifiers (Serial Number, Brand, Model Name, MAC address, Radio Access Technology and Reference MSISDN) in the respective field

Note: Other than MAC address, all identifiers are mandatory.

5. Click on the “Submit” button



Figure 3 - Generate Pair Code

On the submission of request, a page will display details of the request i.e. Confirmation Status, Pairing Code.



Figure 4 - Request Registered Successfully

3.4 Search Request

1. To search any particular request(s) click on “Search Request” tab
2. Enter any known information (i.e. IMEI Number, Serial Number, MAC Address, Reference MSISDN) of required request
3. Click on the “Search Request” button to view searched items



Figure 5 - Search Request

4. SMS Help

4.1 Request First Pair

To request for Primary Pair, send SMS to xxxx short code from MSISDN that you want to set as Primary Pair with the particular device.
Note: Make sure that MSISDN isn't already paired with any other device as Primary Pair.

SMS Text ➔ First [Pairing Code]

4.2 Verify Pair Code

To verify the status of a pairing code for particular IMEI.

SMS Text ➔ VERIFY [Pairing Code] [IMEI]

4.3 Request Additional Pair

To request for Additional MSISDN to be paired with the device, send SMS to xxxx short code from Primary MSISDN.

SMS Text ➔ ADD [new MSISDN]

Note: Primary MSISDN can only add X Additional Pairs for a single device separately.

New MSISDN will receive below SMS to confirm the request of pairing with a device as additional pair. Here, primary MSISDN is also provided to differentiate the device as new MSISDN may pair with more than one device.

SMS Text ➔ CONFIRM [Primary MSISDN]

4.4 Confirm Additional Pair

The new MSISDN will send a confirmation SMS to allow the additional pairing.

SMS Text ➔ YES/NO [Primary MSISDN]

4.5 Find Pair

To check Additional Pairs, send SMS to xxxx short code from Primary MSISDN.

SMS Text ➔ FIND PAIRS

4.6 Release Existing Pair

4.6.1 Release Single Additional Pair

To release or remove an additional pair.

SMS Text ➔ RELEASE [MSISDN]

NOTE: Only Primary MSISDN can request for removal of additional pairs.

4.6.2 Release All Pairs

To release or remove all additional and primary pair.

SMS Text ➔ RELEASE ALL

4.7 SIM Replacement

To continue using the paired-device for Primary and Additional pairs after SIM replacement.

SMS Text ➔ SIM CHANGE

4.8 Request Help Text

To get complete information on how to use SMS function of the DPS, send “HELP” to xxxx short code.

SMS Text ➔ HELP

