

Data-Augmentation for Reducing Dataset Bias in Person Re-Identification



Queen's University
Belfast



CENTRE
FOR SECURE
INFORMATION
TECHNOLOGIES

Niall McLaughlin*, Jesus Martinez Del Rincon, Paul Miller

n.mclaughlin@qub.ac.uk

AMMDS 2015

Data-Augmentation for Reducing Dataset Bias in Person Re-Identification

Agenda for this talk:

- Explain what dataset bias is and how it applies to person re-identification
- Propose possible solutions based on:

**Increasing dataset diversity
using data augmentation**



Generating synthetic training data



- Evaluate our solutions on cross-dataset re-identification

What is Person Re-identification?

Training



- Given image-pairs from different cameras
- Learn a matching function

Testing



- Given: Image of a person seen in camera A
Gallery of persons seen in camera B
- Match the person with their image in camera B
- Changes in pose, illumination, angle of view etc.


What is Person Re-identification?

Training



- Given image-pairs from different cameras
- Learn a matching function

Testing



- Given: Image of a person seen in camera A
Gallery of persons seen in camera B
- Match the person with their image in camera B
- Changes in pose, illumination, angle of view etc.

What is dataset bias?

- **Dataset bias**

When a classifier fails to generalise outside its training dataset

Can happen in all areas of computer vision (classification, detection etc...)

Main cause: the training dataset is a biased sample from the visual world

- **Effect of Dataset Bias**

1. Develop re-identification system using dataset A
2. Test system on dataset A -> it's good! 😊
3. Test system on dataset B -> it's much worse! ☹️



Dataset A

Dataset B

Name that Dataset!

1.



2.



3.



4.



5.



6.



Which dataset do these images belong to?

Name that Dataset!

1. Viper



2. CAVIAR



3. iLids



4. ETHZ



5. CUHK



6. PRID 450



Which dataset do these images belong to?


Measuring Dataset Bias

- Can we find a way to detect dataset bias?
- Train a classifier to play “*Name that Dataset!*”
 - **Objective:** Given an image, predict its parent dataset
 - Create test set by combining multiple re-identification datasets
 - We use: Viper, iLids, Caviar, 3DPES
 - Label each image with its parent dataset
 - Split into 80% training, 20% testing
 - Note - No overlap between the *persons* in the training & testing sets to stop the classifier just recognising individual people!
 - Train a convolutional neural network (CNN) classifier
 - We use an existing network architecture successful on other problems



Measuring Dataset Bias

Architecture of our CNN classifier



CNN classifier predicts the parent dataset of a given image

Measuring Dataset Bias

- *Name that Dataset!* Classification results - confusion matrix

		Classifier's Prediction			
		Viper	iLids	Caviar	3DPES
Source Image Dataset	Viper	0.96	0.02	0.02	0
	iLids	0.03	0.91	0	0.06
	Caviar	0.02	0	0.98	0
	3DPES	0	0.01	0	0.99

- If datasets contained only unbiased random samples from the visual world, the classifier would predict each class at approx. chance levels

Measuring Dataset Bias

- *Name that Dataset!* game should be difficult...
 - Each dataset contains thousands of images
 - The datasets were collected to show large variability between persons viewed from different cameras
- Our results show that datasets are in fact easily distinguishable – therefore exhibit dataset bias
- Dataset Bias reduces real-world usefulness
 - What should happen:
 - Develop system using e.g. Viper
 - Deploy system to any real-world camera network(!)
 - Dataset bias means this may not work...

		Classifier's Prediction			
		Viper	iLids	Caviar	3DPES
Source Image Dataset	Viper	0.96	0.02	0.02	0
	iLids	0.03	0.91	0	0.06
	Caviar	0.02	0	0.98	0
	3DPES	0	0.01	0	0.99



Why does dataset bias happen?

- T. Antonio, and A Efros. "Unbiased look at dataset bias" *CVPR, 2011*
- **Selection bias**
Dataset creators prefer certain kinds of images e.g. internet images
- **Capture Bias**
People tend to take photos of similar things in similar ways
Very expensive to capture the variability present in the real world
- **Label bias**
Different people may label the same things in different ways
- **Negative set bias**
As well as the object of interest, we must define what is not of interest
Small negative set reduces classifier discrimination power
A given dataset captures only a small fraction of the visual world



Why does dataset bias happen?

T. Antonio, and A Efros. "Unbiased look at dataset bias." *CVPR, 2011*

- Dataset bias may be prevalent due to the way we usually develop and test algorithms
- Most computer vision tasks have several datasets available
- Train, validation, and test sets usually drawn from the same dataset
 - We know each dataset does not reflect the variability of the real world
 - Especially a problem for re-identification due to the small size of most datasets, and high correlation in appearance of most images
- Test results don't reflect true generalisation performance i.e. *how well does the system do outside the training dataset?*



Addressing dataset bias

- **Problems**

- Most re-identification dataset are too small
 - Lack of appearance variability
 - Images highly correlated

- **Possible Solutions**

- We could just collect more training data, however...
- Expensive and time consuming
- More data from a different dataset often harms performance!

- **Our Contribution**

- Artificially increase the variability of existing datasets
- Generate realistic synthetic training data



Data Augmentation

Problem - Re-identification dataset are small, and therefore lack variability

Proposed Solution - *Artificially increase training set size*

- During training, randomly modify each training image
- Network gets exposed to image variations not present in the training-set
- Combining data augmentation methods can further increase variability



Original



Colour



Crop



Rotation




Affine

Simulated Backgrounds

- **Problems with existing datasets**
 - Contain many images that are highly correlated (even between diff. persons)
 - Small number of images per-person
 - Difficult (for a computer) to tell which image-parts are important
- **Possible Solution**
 - Generate synthetic images with artificial background
 - PRID 450 dataset includes ground-truth segmentations (Thanks!)

Easier for re-identification system to learn which image-parts are most salient



Original

Mask

Simulated Backgrounds


Original



Mask




Background photos from internet



With Simulated Background

Re-identification System


Use a convolutional neural network (CNN) to learn feature representation for re-identification images



Training Objective

- Map Images of the same person same vectors to similar vectors
- Map images of different persons to different vectors

Re-identification System



We train a CNN to act as a feature extractor using a '*Siamese*' or embedding network architecture

In a *Siamese* network, both CNNs have identical weights

The image feature is the activations of the final layer neurons (just a vector of real numbers)

During Training:


Show network pairs of similar/dissimilar images

Training Objective:

Images of the same person should have similar final layer neuron activations

Images of different persons should have different final layer neuron activations

Re-identification System




Train the CNN using a '*Siamese*' or embedding network architecture


Show network pairs of similar/dissimilar images

Cost Function for similar images

- Encourages feature vectors to be close



Re-identification System




Train the CNN using a '*Siamese*' or embedding network architecture

Show network pairs of similar/dissimilar images


Cost Function for dissimilar images

- Encourages feature vectors to be separated by a margin m



Re-identification System


- During training the CNN has learned to act as a feature extractor
- During testing we show an image to the CNN to produce its feature representation
- Images are compared by taking the Euclidean distance between their features



Visualise Learned Features

What features does the neural network learn?

For each output layer neuron visualise the image features that cause neuron to activate strongly positive (left of each pair), or strongly negative (right of each pair)



Experimental Procedure


- **Question** - How does a given data augmentation method affect cross-dataset re-identification performance?

For all Data Augmentation Methods **Y**

For all Datasets **X**

Train re-identification system on **Dataset X** using **Augmentation Y**


Compute average CMC over all Datasets $\neq \mathbf{X}$



Cross Dataset Re-Identification

Data augmentation methods used alone


- Cropping gives biggest increase, followed by rotation and flipping
- Affine transformation and colour are worse than using no data augmentation



Cross Dataset Re-Identification

Top Combinations of data augmentation methods


- Too many combination to show all results
- The top methods all perform similarly
- Combination of Cropping + Flip is essential to good results
- Adding more augmentation methods give only small change in results



Cross Dataset Re-Identification

Simulated Background Data Augmentation


- Train on PRID 450 with / without simulated backgrounds
Note - Always using Cropping + Flipping data augmentation
- Test on all other datasets - calculate average CMC curve



Cross Dataset Re-Identification

Changing Background Data Augmentation

- How does number of training images with simulated backgrounds affect testing accuracy?



Conclusions

- **Synthetic training data can improve performance**
 - Possible to extend this line of thinking much further!
- **Need for larger datasets with greater variability**
 - Collect new very large dataset
 - Combine existing datasets
- **Cross dataset benchmarking should be emphasised**
 - May better reflect real world performance
 - Reduces risk of over-fitting to a single dataset
- **Any Questions?**
n.mclaughlin@qub.ac.uk