

CANANOLAB 1.3

Installation Guide



January 23, 2007

Table of Contents

INTRODUCTION TO CANANOLAB	1
Targeted Developer.....	1
Important Background Knowledge	1
General System Requirements	2
Open Source Technologies	2
Grid Service.....	2
Grid Service Downloads.....	2
Obtaining the caNanoLab Source	3
Source Code	3
 DATABASE TECHNOLOGY	 3
Assumptions and Requirements	3
For a Previous Installation	3
For a New Installation	3
Initializing the MySQL Database	4
Follow these steps to initialize your MySQL database system:	4
Verification.....	5
Data Migration	5
 CANANOLAB WEB APPLICATION.....	 7
Assumptions and Requirements	7
Installation and Deployment	7
Common Security Module (CSM).....	8
Before You Start caNanoLab.....	8
Verification.....	10
User Provisioning Tool (UPT).....	10
Creating User Accounts	10
UPT Example.....	11
 CANANOLAB GRID DATA SERVICE.....	 13
Assumptions and Requirements	13
Installation and Deployment	13
Verification.....	16
 CONTACTING APPLICATION SUPPORT	 16

Introduction to caNanoLab

Welcome to the cancer Nanotechnology Laboratory Analysis Bench (caNanoLab) 1.3 Installation Guide. caNanoLab is a data sharing portal designed for laboratories performing nanoparticle assays. caNanoLab provides support for the annotation of nanoparticles with characterizations resulting from physical and *in vitro* nanoparticle assays and the sharing of these characterizations in a secure fashion.

As of release 1.1, the caNanoLab domain model has been caGrid enabled. In other words, a caNanoLab grid data service can be deployed and registered with a caGrid index server, allowing sharing of public characterizations across the caGrid. For more information, see <https://cabig.nci.nih.gov/workspaces/Architecture/caGrid>. The caNanoLab web application allows remote searches against remote grid services hosting the caNanoLab data model.

Targeted Developer

The caNanoLab application development is best suited for an experienced Java developer who has some familiarity with the following J2EE and related technologies:



Important Background Knowledge

- Unix/Linux environment
 - (Configuring environment variables; Installing Ant, JDK, Apache Tomcat and JBoss servers)
 - Ant build scripts
 - J2EE web application development using the Struts framework, Servlet/JSP's, JavaScript
 - J2EE middle-ware technologies such as n-tier service-oriented architecture and software design patterns
 - caGrid 1.0 infrastructure (for setting a caNanoLab grid data service)
-

General System Requirements

The following open source technologies power a caNanoLab web application:

Open Source Technologies

- Java Software Development Kit (JDK) version 5.0 http://java.sun.com/javase/downloads/index_jdk5.jsp
 - JBoss version 4.0.5 <http://labs.jboss.com/jbossas/downloads>
 - Jakarta Ant version 1.6.5 <http://archive.apache.org/dist/ant/binaries/>
 - MySQL version 5.0.x <http://dev.mysql.com/downloads/mysql/5.0.html>
-

The caNanoLab web application has been tested within NCICB against JBoss servers hosted on Windows XP and RedHat Linux systems, and against MySQL 5.0.27 databases hosted on RedHat Linux systems and MySQL 5.0.45 on Windows XP systems. Prior to release 1.2.1, the caNanoLab web application had been tested against Oracle 9i databases hosted on Sun Solaris systems, and Oracle 10g XE database hosted on Windows XP.

Download each of the tools listed in the bulleted list and follow the installation instructions provided with each respective product for your environment. Assistance from a MySQL database administrator is expected to properly configure the MySQL database. For MySQL database configuration and maintenance, it is also helpful to download the MySQL 5.0 suite of GUI tools at <http://dev.mysql.com/downloads/gui-tools/5.0.html>.

Grid Service

Setting up a caNanoLab grid service is optional. It is recommended that you install the grid service only after you successfully install the web application and become familiar with submitting and searching data through the web application.

Grid Service Downloads

Once you have data that you would like share with the caBIG community and you intend to set up a caNanoLab grid service, download the following open source technologies that power a caNanoLab grid data service:

- The Globus Toolkit version 4.0.3 <http://www.globus.org/>
 - Apache Tomcat version 5.0.28 <http://tomcat.apache.org/>
-

Obtaining the caNanoLab Source

Source Code	<p>The caNanoLab web application source code is distributed as a zip file named <code>caNanoLab_1.3.zip</code> from the NCICB GForge site at http://gforge.nci.nih.gov/frs/?group_id=69</p> <p>The caNanoLab grid service source code is distributed as a zip file named <code>caNanoLab_grid_1.3.zip</code> from the NCICB GForge site at http://gforge.nci.nih.gov/frs/?group_id=69</p>
--------------------	---

Database Technology

Assumptions and Requirements	<p>The caNanoLab source distribution <code>caNanoLab_1.3.zip</code> has been downloaded from the NCICB download site. A MySQL database has been set up on a system (local or remote) with an administrator (or root) account. You should be familiar with the process of creating InnoDB tablespaces, databases creating users and assigning privileges to users.</p>
For a Previous Installation	<p>If you have installed caNanoLab release 1.2 or release 1.1.1 or release 1.1 against an Oracle database and have associated production data in these schemas and you would like to continue to use the same data for caNanoLab release 1.3 in MySQL, review the following database initialization steps, then go directly to <i>Data Migration</i> on page 5.</p>
For a New Installation	<p>If you are installing the caNanoLab application for the first time or want to install a new schema for release 1.3, follow the steps below to set up the required MySQL schema objects and the seed data for release 1.3.</p>

Initializing the MySQL Database

Follow these steps to initialize your MySQL database system:

Step	Action
1	<p>Extract the <code>caNanoLab_1.3.zip</code> to a location on your local system, for example, <code>C:\caNanoLab_1.3</code>. This location is referred as <code><CANANOLAB_SOURCE></code> throughout the document. Verify that the following seven SQL scripts exist in the directory <code><CANANOLAB_SOURCE>/db/1.3</code>:</p> <ul style="list-style-type: none"> • <code>app_schema.sql</code> • <code>app_priming_data.sql</code> • <code>csm_schema.sql</code> • <code>csm_priming_data.sql</code> • <code>app_csm_priming_data.sql</code> • <code>app_triggers.sql</code> • <code>mysql_seed.sql</code>
2	<p>Log into the MySQL database as the database administrator (root) and go to the directory <code><CANANOLAB_SOURCE>/db/1.3</code> and execute the script <code>mysql_seed.sql</code> to set up a schema named cananolab and its required seed data.</p> <p><i>Example:</i> On a Windows XP system hosting a MySQL 5.0.45 database, you would issue the following commands at the DOS prompt (assuming the root account has password rootpass):</p> <pre>C:\>cd c:\caNanoLab_1.3\db\1.3</pre> <pre>C:\>mysql -h localhost -u root -prootpass <mysql_seed.sql</pre>
3	<p>Log into the MySQL database as the database administrator (root) and create a user account and grant this user the following privileges to the schema cananolab: select, insert, delete, update and allow the user to connect from any hosts.</p> <p><i>Example:</i> Create a user account named cananolab_app with password go!234.</p> <pre>C:>mysql -h localhost -u root -prootpass</pre> <pre>mysql>grant select, insert, delete, update on cananolab.* to 'cananolab_app'@'%' identified by 'go!234';</pre> <p>Note: User administration and schema privileges can also be managed by the MySQL Administrator GUI as a part of the MySQL 5.0 suite of GUI tools.</p>

Verification

Once the MySQL database has been created, either through new setup or through data migration (described in the next section), verify that the following numbers of database objects are created:

- Tables 94
- Views 1
- Triggers 18

Example: Issue the following queries at the MySQL prompt, logging in as *cananolab_app*:

```
mysql> select count(*) from information_schema.tables
where table_schema='cananolab' and table_type='BASE
TABLE';

mysql> select count(*) from information_schema.tables
where table_schema='cananolab' and table_type='VIEW';

mysql> select count(*) from information_schema.triggers
where trigger_schema='cananolab';
```

Data Migration

NOTE:

If you are installing caNanoLab 1.3 for the first time or installing a new caNanoLab release 1.3 schema, you can skip this section.

This installation guide only discusses the steps for migrating from release 1.2.1 in MySQL to release 1.3 in MySQL. If you have previously installed caNanoLab release 1.2, or release 1.1.1, or release 1.1 against an Oracle database and have production data associated with these schemas that you wish to keep, you must perform a data migration to release 1.2.1 in MySQL first before migrating to release 1.3. Please see the release 1.2.1 installation guide http://gforge.nci.nih.gov/docman/index.php?group_id=69&selected_doc_group_id=2490&language_id=1 for details.

Follow these steps to complete the required data migration from release 1.2.1 in MySQL to release 1.3 in MySQL:

Step	Action
1	<p>Extract the <code>caNanoLab_1.3.zip</code> to a location on your local system, for example, <code>C:\caNanoLab_1.3</code>. This location is referred as <code><CANANOLAB_SOURCE></code> throughout the document. Verify that the following two SQL scripts exist in the directory <code><CANANOLAB_SOURCE>/db/1.3/data_migration</code>:</p> <ul style="list-style-type: none"> • <code>app_schema_changes.sql</code> • <code>app_csm_changes.sql</code>
2	<p>Log into the MySQL database as the database administrator (<code>root</code>) and go to the directory <code><CANANOLAB_SOURCE>/db/1.3/data_migration</code> and execute the above two scripts in the order specified.</p> <p><i>Example:</i> On a Windows XP system hosting a MySQL 5.0.45 database, you would issue the following commands at the DOS prompt (assuming the root account has password rootpass):</p> <pre>C:\>cd c:\caNanoLab_1.3\db\1.3\data_migration C:\>mysql -h localhost -u root -prootpass <app_schema_changes.sql C:\>mysql -h localhost -u root -prootpass <app_csm_changes.sql</pre>

After data migration, refer to the Verification section on page 5 to verify that the migration has been successful. The same number of schema objects should be generated as described in that section.

caNanoLab Web Application

Assumptions and Requirements

The database has been installed and verified, as described on pages 4 through 6. Ant has been installed. The JBoss application server has been installed on a system (local or remote) and can be started at a designated port. JBoss install directory is referred as `<JBOSS_HOME>` in the document. The JBoss application server host URL is referred as `<APP_SERVER_URL>`, for example, `localhost:18080`. It is assumed that the default configuration is used for deploying caNanoLab related web archive files; it is recommended that you change the designated port from the default port 8080 to another unused port.

For example, in the case of JBoss 4.0.5, the default configuration is located at the directory `<JBOSS_HOME>/server/default`. The caNanoLab web archive file shall be deployed at the directory `<JBOSS_HOME>server/default/deploy`. For changing the default port 8080 and associated ports, locate the file `server.xml` at the directory `<JBOSS_HOME>/server/default/deploy/jbossweb-tomcat55.sar`. Replace all occurrences of 8080, 8009 and 8443 with 18080, 18009 and 18443, respectively. For details, refer to the appropriate JBoss documentation.


Installation and Deployment

Follow these steps to install and deploy caNanoLab.

Step	Action
1	<p>Edit the Ant build properties file <code>build.properties</code> at <code><CANANOLAB_SOURCE></code> by specifying values for the following five properties:</p> <ol style="list-style-type: none"> <code>file.repository.dir</code>: A directory on the system that hosts the JBoss application server for storing uploaded files, for example, <code>C:/temp/caNanoLab/fileupload</code>. Note: This directory should be writable by the user that starts the JBoss server, and this directory should be created prior to starting the application. Either double back slashes <code>\\</code> or a single forward slash <code>/</code> should be used as the file separator if working on Windows platform. <code>sample.prefix</code>: The prefix used for auto-accessioning samples, for example, <code>NCL</code> is used for sample accessions <code>NCL-1</code>, <code>NCL-2</code>, etc at the Nanoparticle Characterization Laboratory. <code>application.owner</code>: the owner of the caNanoLab release 1.2 installation instance, for example, <code>NCL</code>. <code>grid.indexserver</code>: the grid index server from which the caNanoLab grid data services can be automatically discovered, for example, <code>http://cagrid-index-stage.nci.nih.gov:8080/wsrf/services/DefaultIndexService</code>, the NCICB's staging caGrid index server.

Step	Action
	e. <code>database</code> : This property specifies whether the application works with an Oracle database or a MySQL database. For release 1.3, use <code>mysql</code> .
2	<p>Execute the Ant build script <code>build.xml</code> located at <code><CANANOLAB_SOURCE></code> with the default target <code>build-application</code> and the default <code>build.properties</code> file configured in step 1.</p> <p><i>Example:</i> Issue the following commands to execute the Ant script:</p> <pre>C:\>cd c:\caNanoLab_1.3 C:\>ant</pre> <p>Successful execution of the Ant script creates three deployable web archive war files in the directory <code><CANANOLAB_SOURCE>/output/war</code>: <code>caNanoLab.war</code>, <code>upt.war</code>, and <code>caNanoLabSDK.war</code>. Place these war files into the default JBoss application server deploy directory, <code><JBOSS_HOME>/server/default/deploy</code>.</p>
3	Copy the file <code>mysql-connector-java-5.0.7-bin.jar</code> from <code><CANANOLAB_SOURCE>/lib</code> folder and place it in the directory <code><JBOSS_HOME>/server/default/lib/</code> .

Common Security Module (CSM)

 <p>Before You Start caNanoLab</p>	<p>Before starting the JBoss application server and running the caNanoLab application, you must configure the server with required security configurations for user authentication and authorization. The caNanoLab web application relies on a modified version of NCICB CSM (Common Security Module) version 3.1 for user authentication and role-based authorization. For more information, see the CSM documentation at http://qforge.nci.nih.gov/frs/?group_id=12.</p>
--	--

Follow these steps to complete the security configurations:

Step	Action
1	Copy the file <code>ApplicationSecurityConfig.xml</code> from the directory <code><CANANOLAB_SOURCE>/conf/csm</code> . Place it in the directory <code><JBOSS_HOME>/server/default/conf</code> :
2	Copy the file <code>caNanoLab.csm.hibernate.cfg.xml</code> from the directory <code><CANANOLAB_SOURCE>/conf/csm/mysql</code> . Place it in the directory <code><JBOSS_HOME>/server/default/conf</code> :


Step	Action
3	<p>Edit the file <code>ApplicationSecurityConfig.xml</code> at <code><JBoss_HOME>/server/default/conf</code> as follows:</p> <ul style="list-style-type: none"> Replace the token <code>@ABSOLUTE_PATH@</code> with the value <code><JBoss_HOME>/server/default/conf</code>, where <code><JBoss_HOME></code> should be replaced by the actual full path JBoss install directory name, <code>C:/jboss-4.0.5.GA</code>. <p>Note: Either double back slashes <code>\\</code> or a single forward slash <code>/</code> should be used as the file separator if working on Windows platform.</p>
4	<p>Copy the file <code>mysql-ds.xml</code> from the directory <code><CANANOLAB_SOURCE>/conf</code> and place it in the directory <code><JBoss_HOME>/server/default/deploy</code>, if such a file does not already exists. If a file named <code>oracle-ds.xml</code> exists in the directory <code><JBoss_HOME>/server/default/deploy</code>, remove it.</p>
5	<p>Edit the copied file <code>mysql-ds.xml</code> at <code><JBoss_HOME>/server/default/deploy</code> as follows:</p> <ol style="list-style-type: none"> Replace the token <code>@DBSERVER@</code> with the URL or the IP address of the system that hosts the MySQL database, for example, 127.0.0.1. Replace the token <code>@PORT@</code> with the port number of the database server, for example, 3306. Replace the token <code>@DBNAME@</code> with the name of the database service to which to connect, for example, the value is cananolab for the MySQL Database created in the Database Technology Section. Check with your Oracle DBA for your database service name configurations. Replace the token <code>@DBUSER@</code> with the user name configured in step 1 of the Database Technology instructions on page 3, for example, cananolab_app. Replace the token <code>@DBPASSWORD@</code> with the password associated with the value for the token <code>@DBUSER@</code>, for example, go!234.
6	<p>Locate the last <code></application-policy></code> tag in the file <code>login-config.xml</code> at <code><JBoss_HOME>/server/default/conf</code>, and insert the content of the file <code>login-config-segment.xml</code> at <code><CANANOLAB_SOURCE>/conf/csm/mysql</code> into the file <code><JBoss_HOME>/server/default/conf/login-config.xml</code> just below the last <code></application-policy></code> tag.</p>
7	<p>Edit the inserted file <code>login-config.xml</code> at <code><JBoss_HOME>/server/default/conf</code> by doing similar replacements as in step 4:</p> <ol style="list-style-type: none"> Replace the token <code>@DBSERVER@</code> with the URL or the IP address of the system that hosts the MySQL database, for example, 127.0.0.1. Replace the token <code>@PORT@</code> with the port number of the database server, for example, 3306. Replace the token <code>@DBNAME@</code> with the name of the database service to which to connect, for example, the value is cananolab for the MySQL Database created in the Database Technology Section. Check with your Oracle DBA for your database service name configurations. Replace the token <code>@DBUSER@</code> with the user name configured in step 1 of the Database Technology instructions on page 3, for example, cananolab_app. Replace the token <code>@DBPASSWORD@</code> with the password associated with the value for the token <code>@DBUSER@</code>, for example, go!234.

Step	Action
8	Locate the last <code></mbean></code> tag in the file <code>properties-service.xml</code> at <code><JBOSS_HOME>/server/default/deploy</code> , and insert the content of the file <code>properties-service-segment.xml</code> at <code><CANANOLAB_SOURCE>/conf/csm</code> into the file <code><JBOSS_HOME>/server/default/deploy/properties-service.xml</code> just above the last <code></mbean></code> tag.
9	<p>Edit the inserted file <code>properties-service.xml</code> at <code><JBOSS_HOME>/server/default/deploy</code> as follows:</p> <ul style="list-style-type: none"> Replace the token <code>@ABSOLUTE_PATH@</code> with the value <code><JBOSS_HOME>/server/default/conf</code>, where <code><JBOSS_HOME></code> should be replaced by the actual full path JBoss install directory name, <code>C:/jboss-4.0.5.GA</code>. <p>Note: Either double back slashes <code>\\</code> or a single forward slash <code>/</code> should be used as the file separator if working on Windows platform.</p>

Verification

Once the JBoss application server is correctly configured with the CSM settings, you can now start the JBoss application server, which in turn starts the caNanoLab application. Open the URL http://<APP_SERVER_URL>/caNanoLab/ (for example, <http://localhost:18080/caNanoLab/>). You should see a disclaimer page. Click on **CLICKING HERE** to go to the Welcome/Login page.

User Provisioning Tool (UPT)

 <p>Creating User Accounts</p>	<p>Before users can log in to the caNanoLab application to submit and search data, you must first create their user accounts and assign them to the pre-defined user groups with the pre-defined roles to access the pre-defined protection groups. The caNanoLab application makes use of the NCICB's User Provisioning Tool (UPT), a separate web application, for user account management. The concepts of users, groups, roles, protection groups are defined according the CSM/UPT principles. See the CSM documentation at http://gforge.nci.nih.gov/frs/?group_id=12 for details on these concepts and the use of the UPT tool.</p>
--	---

In release 1.3, as a part of the database seed data, a default user group `Public` has been created and has been assigned role `R` to protection groups `protocol`, `nanoparticle` and `report`, i.e. assigned access to search protocols, nanoparticles and reports.

During the caNanoLab application start up, two more default users groups are auto-generated: `<application.owner>_Researcher`, `<application.owner>_PI`, where the value for `<application.owner>` is specified in the file `build.properties` prior to building the application as described on page 7. Automatic roles are assigned for these two default user groups at start up as follows:


1. `<application.owner>_Researcher` is assigned role CURD to protection group sample, i.e. assigned access to submit samples.
2. `<application.owner>_PI` is assigned role CURD to protection groups sample, protocol, nanoparticle, and report, i.e. assigned access to submit samples, protocols, nanoparticles and reports.

In release 1.3, a user must be assigned as a caNanoLab administrator to see the ADMINISTRATION menu item in the application to log into the UPT tool.

UPT Example The following steps illustrate an example use of the UPT tool to create a new user, to assign the user to be a caNanoLab administrator, and to assign the user to a pre-defined user group.

Step	Action
1	Launch the UPT tool at <a href="http://<APP_SERVER_URL>/upt">http://<APP_SERVER_URL>/upt and login as superadmin/password . Use caNanoLab-upt as the application name when prompted at the UPT log in. Note: The user superadmin was created as a part of the database setup.
2	Once logged into the UPT tool, follow these steps: <ol style="list-style-type: none"> a. Select User > Create a New User. b. Create a new user account named admin. c. Select Application > Select an Existing Application; click Search. d. Select caNanoLab from the application list. e. Click View Details, then Associated Admins. f. Assign this user to be an administrator for the caNanoLab application. g. Click Update Association to commit the change.
3	Log out of the UPT tool and log back in as admin/admin . Use caNanoLab as the application name when prompted at the UPT log in. Note: When a new user account is created, its initial default password is the same as its login name. Given that the UPT tool is lacking a function for users to manage their own passwords, users can only update their passwords within the caNanoLab application. See the Notes below on how to update user passwords.
4	Select User > Select an Existing User , and click Search . Select admin from the User list. <ol style="list-style-type: none"> a. Click View Details, then Associated Groups. b. Select <application.owner>_PI from the pre-defined group list and assign it to the user. c. Click Update Associations to commit the change.

Follow similar steps to create other application user accounts and to assign them to different users groups, as appropriate.

<p>NOTES:</p> 	<ul style="list-style-type: none">• The initial passwords for user accounts are set to be the same as their user accounts. When a user first logs into the caNanoLab application at <a href="http://<APP_SERVER_URL>/caNanoLab">http://<APP_SERVER_URL>/caNanoLab, he/she would be prompted to change the initial password. Users can update their passwords at any time within the caNanoLab application.• Only users assigned as caNanoLab administrators and assigned to the <code><application.owner>_PI</code> group can delete characterizations.• Publicly available data can be browsed through the public browse links on the home page without logins.• Users logged into the application have to be assigned to one of the predefined user groups to be able access data.• New sample sources entered during sample creation are automatically created as new user groups. Using the UPT tool, one can assign different roles to different protection groups for these new user groups.• A user can be assigned to multiple user groups,
--	--

For more information about how to use the UPT tool for managing user accounts, contact NCICB Application Support at ncicb@pop.nci.nih.gov and request that the caNanoLab technical team give you a demonstration of the UPT tool in the context of the caNanoLab application.

caNanoLab Grid Data Service

Assumptions and Requirements

Both `caNanoLab.war` and `caNanoLabSDK.war` files have been deployed to the JBoss application server and the JBoss server has been started. Please refer back to the caNanoLab web application installation and deployment section on page 7 for details on how to deploy these war files.

Apache Tomcat has been downloaded and installed with the `CATALINA_HOME` environment variable set pointing to the Tomcat install directory. The Tomcat server URL is referred to as `<TOMCAT_SERVER_URL>` throughout the document.

Globus Toolkit has been downloaded and installed with the `GLOBUS_LOCATION` environment variable pointing to the Globus install directory.

Note: Tomcat, Globus Toolkit, and subsequent caNanoLab grid service can be installed on the same system that hosts the caNanoLab web application or can be installed on a separate system.

Installation and Deployment

Before deploying grid services, Tomcat must be pre-configured with a Globus web application that can host a grid service. Issue the following commands to complete the pre-configuration required for Tomcat to host a caNanoLab grid service:

```
C:>cd "%GLOBUS_LOCATION%"
C:>ant -f share\globus_wsrf_common\tomcat\tomcat.xml
    deployTomcat -Dtomcat.dir="%CATALINA_HOME%" -
    Dwebapp.name=wsrf-canano
```

This generates a directory `<CATALINA_HOME>/webapps/wsrf-canano` with the required Globus webapp information. Note that by specifying a `webapp.name` property (in the above command) to have a different value than the default value `wsrf`, multiple caCORE SDK backed grid services can be deployed to the same Tomcat server and function properly and independently without interference. This circumvents the current known issue with multiple caCore SDK-backed grid services interfering with each other if deployed to the same Globus webapp `wsrf` under the same Tomcat server.

Once the Tomcat server is pre-configured, complete the following steps to create and deploy a caNanoLab grid data service:

Step	Action
1	Extract caNanoLab_grid_1.3.zip to a location on your local machine, example, C:\caNanoLab_grid_1.3. This location is referred as <CANANOLAB_GRID_SOURCE> throughout the document.
2	<p>Edit the Ant build properties file deploy.properties at <CANANOLAB_GRID_SOURCE> by specifying values for the following properties:</p> <ul style="list-style-type: none"> a. <code>index.service.url</code>: The grid index server to which this caNanoLab grid service is going to register its metadata to, for example, <code>http\://cagrid-index-stage.nci.nih.gov\8080/wsrf/services/DefaultIndexService</code>, the NCICB's staging index server. b. <code>service.deployment.prefix</code>: This value should be <code>cagrid</code>. c. <code>cananolab.sdk.host</code>: The value of <APP_SERVER_URL>, or the hostname and port number for the JBoss application server hosting the caNanoLab web application, for example, <code>localhost:18080</code>. d. <code>webapp.name</code>: The globus web application name for the caNanoLab grid service. Use <code>wsrf-canano</code>. e. <code>grid.node.display.name</code>: The display name for the caNanoLab grid service, for example, <code>caNanoLab-NCICB</code>. Note: The display name is used in the caNanoLab web application as the grid node host name and is used in grid service auto-discovery from the grid index server. f. <code>grid.node.country</code>: The country in which the caNanoLab grid service is running, for example, <code>US</code>. g. <code>grid.node.locality</code>: The name of the location at which the caNanoLab grid service is running, for example, <code>NCICB</code>. h. <code>grid.node.postal.code</code>: The zip code of the location at which the caNanoLab grid service is running, for example, <code>20852</code>. i. <code>grid.node.state</code>: The state of the location at which the caNanoLab grid service is running, for example, <code>MD</code>. j. <code>grid.node.street</code>: The street of the location at which the caNanoLab grid service is running, for example, <code>2115 East Jefferson Street</code>. k. <code>your.affiliation</code>: The affiliation of the person who is responsible for maintaining the caNanoLab grid service, for example, <code>NCICB</code>. l. <code>your.email</code>: The email of the person who is responsible for maintaining the caNanoLab grid service, for example, <code>ncicb@pop.nih.gov</code> m. <code>your.first.name</code>: The first name of the person who is responsible for maintaining the caNanoLab grid service n. <code>your.last.name</code>: The last name of the person who is responsible for maintaining the caNanoLab grid service <p>Note: Properties f through i are grid service meta data that are required for the grid index server to map the location of a grid service, and are useful during grid service auto-discovery. Properties j through n are optional.</p>

Step	Action
3	<p>Execute the Ant build file (build.xml) located at <CANANOLAB_GRID_SOURCE> the default target createTomcatDeploymentTar using the default properties file (deploy.properties) in step 2. For example,</p> <pre>C:\>cd c:\caNanoLab_grid_1.3 C:\>ant</pre> <p>Execution of the Ant build script generates a file CaNanoLabSvc.tar at the <CANANOLAB_GRID_SOURCE>/output directory.</p>
4	Place the file CaNanoLabSvc.tar to the directory <CATALINA_HOME> and untar or extract the tar file within the same directory.

Before the Tomcat server is started, please complete the following steps to ensure successful grid service registration to the grid index service and to ensure successful grid service meta data aggregation from the grid index service.

Step	Action
1	<p>The Tomcat server hosting the caNanoLab grid service must have a publicly accessible IP address or DNS-resolvable host name, so the Index Service (and other clients) can connect to it. Edit the file server-config.wsdd at <CATALINA_HOME>/webapps/wsrf-canano/WEB-INF/etc/globus_wsrf_core as follows:</p> <ul style="list-style-type: none"> Add a logicalHost parameter, with its value being the public IP or host name of the Tomcat server. For example: <pre><globalConfiguration> ... <parameter name="sendXsiTypes" value="true"/> <parameter name="logicalHost" value="http://cananolab.nci.nih.gov"/> <parameter name="publishHostName" value="true"/></pre>

Step	Action
2	<p>If the Tomcat server runs on a port other than 8443 and uses http protocol instead of https, edit the file <code>web.xml</code> at <code><CATALINA_HOME>/webapps/wsrf-canano/WEB-INF</code> as follows:</p> <ul style="list-style-type: none"> Add <code>init-params</code> to the <code><servlet></code> tag. For example: <pre> <servlet> <servlet-name>WSRFServlet</servlet-name> <display-name>WSRF Container Servlet</display-name> <servlet-class> org.globus.wsrf.container.AxisServlet? </servlet-class> <init-param> <param-name>defaultProtocol</param-name> <param-value>http</param-value> </init-param> <init-param> <param-name>defaultPort</param-name> <param-value>8080</param-value> </init-param> <load-on-startup>true</load-on-startup> </servlet> </pre>

Verification

Once the Tomcat server is correctly configured, you can now start the Tomcat server, which in turn starts the caNanoLab grid service. To verify the creation of the caNanoLab grid data service, open the URL

http://<TOMCAT_SERVER_URL>/wsrf-canano/services/cagrid/CaNanoLabSvc.

You should see a page that says:

```
cagrid/CaNanoLabSvc
```

```
Hi there, this is an AXIS service!
```

It takes a short while before the grid service is successfully registered in the index server. Wait a while and log into the caNanoLab application, and click on **Browse Nanoparticles>Grid Search**. You should see the caNanoLab grid node display name you specified on page 14 listed as one of the grid node hosts, provided that the caGrid index server used in the caNanoLab web application is the same as the one used for the caNanoLab grid service.

For more information and help on caGrid service configuration and deployment, refer to the caGrid wiki page: <http://www.cagrid.org>.

If you need further assistance on setting a caNanoLab grid service, contact NCICB Application Support at ncicb@pop.nci.nih.gov.

Contacting Application Support

**NCICB
Application
Support**

<http://ncicb.nci.nih.gov/NCICB/support>

Telephone: 301-451-4384

Toll free: 888-478-4423
