



Electronic Research Administration
A program of the National Institutes of Health



National Institutes of Health
Office of Extramural Research

Intent To Pay (ITP) Web Services Technical User Guide

Version 1.2.3

Posting Date: Jan 31, 2024



TABLE OF CONTENTS

Contents

TABLE OF CONTENTS 2

1 General Information 3

 1.1 Purpose 3

 1.2 General Description 3

 1.3 Security 3

 1.4 Prerequisites 3

 1.5 Service Locations (WSDL)..... 3

2 Intent to Pay (ITP) Web Service 4

 2.1 Input Values 4

 2.2 Output Values 5

 2.3 Business Rule and Validation Error Messages 6

 2.4 Web Service End Points 8

 2.5 WSDL 8

3 WSDL Definition 9

1 General Information

1.1 Purpose

The purpose of this document is to provide a general description and usage guide for the Intent to Pay (ITP) web service.

1.2 General Description

The ITP web service is available to set the ITP Code, Fiscal Year, Council Recommendation Code, and Council Priority. This ITP web service replaces the Procedural Language/Structured Query Language (PL/SQL) Application Programming Interface (API).

1.3 Security

This system must pass credentials for a system account. For more information on system accounts, For information see [Manage System Accounts](#) in the *AMS Online Help*.

1.4 Prerequisites

Users must have a system account.

1.5 Service Locations (WSDL)

Production - https://services.internal.era.nih.gov/payplan/services/itp_ext_ws/?wsdl

2 Intent to Pay (ITP) Web Service

Institutes/Centers (ICs) need certificate-based authentication to access the ITP web service. For instructions on configuring the certificate, please refer to the [System-to-System \(S2S\) Guide for eRA Web Services](#). As indicated in Section 3 of the Internal S2S Guide for eRA Web Services, the certificate needs to be registered after it has been procured. This step is conducted by the IC Coordinator.

2.1 Input Values

After logging into the ITP Web Service, the following field information applies:

Field	Editing Rule	Values	Required	Multiple Values Allowed
Application ID	Must Exist		Yes	No
ITP Flag/Code	Editable only for primary IC of the application	Y (Yes), N (No), D (Deferred), NULL	No	No
Fiscal Year	Editable only for primary IC of the application Format - YYYY		No	No

PHS Organization Code			Yes - Only if this field is the user (System Account) has roles with multiple ICs and the Council Recommendation and Council Priority are being updated as part of the Web Service Request. If the System Account has the role for only one IC, there is no need to fill out this field.	No
Council Recommendation Code	Editable only for primary and dual ICs	1 through 8, NULL	No	No
Council Priority	Editable only for primary and dual ICs	CON (<i>Concurrence</i>), HPP (<i>High Program Priority</i>), LPP (<i>Low Program Priority</i>), NRC (<i>Not Concurring with IRG</i>), OTH (<i>Special Characters</i>), NULL	No	No

Table 1: Field Information

2.2 Output Values

The output is a standard web service response relating to the success or failure of the web service request. The web service response consists of a code (success or failure) and the associated message.

In addition, the web service response will include specific error messages related to the business rules for updating specific fields (for example, ITP cannot be updated

because the irg_recom_code is null, or status is Awarded, Terminated, Withdrawn (02), etc.).

Field	Value s
response Code	Succeeded or Failed (true or false), type is boolean
errorMessages	List of Message which contains two fields, code(string) and message(string), as detailed below.

ITP Web Service Fields

2.3 Business Rule and Validation Error Messages

Error_Code	Error_Message	How business rule applied
INVALID_ITP_UPDATE_REQUEST	Invalid itp update request according to the schema	
APPLICATION_ID_IS_NOT_EXIST	Application Id does not exist	
IRG_RECOMM_CODE_NULL	Update not allowed because IRG RECOMM Code is null	APPLS_T.IRG_RECOM_CODE IS NULL THEN error
APPL_CLASS_CODE_CONTRACT	Update to Contract records is not allowed.	APPLS_T.APPL_CLASS_CODE = 'C' THEN error
SUBPROJECT_ID_NULL	Update to Subproject records is not allowed.	APPLS_T.SUBPROJECT_ID IS NOT NULL Then error
COMPETING_APPL_TYPES	Update not allowed. The application type has to be 1, 2, 3 or 9	APPLS_T.APPL_TYPE_CODE NOT IN ('1', '2', '3', '9') Then error

COUNCIL_MEETING_DATE_00	Update not allowed. The application cannot be non-competing	COUNCIL_MEETING_DATE ending with '00', THEN error.
APPL_STATU_CODES_17	ITP can only be set to Null if application status is Pending IRG Review (17)	APPLS_T.APPL_STATUS_CODE = '17' and about to set ITP != Null THEN error
APPL_STATU_CODES_70	ITP can only be set to Null if application status is Entered into Computer (70)	APPLS_T.APPL_STATUS_CODE = '70' and about to set ITP != Null THEN error
APPL_STATU_CODES_03	ITP can only be set to Yes if application status is Terminated (03)	APPLS_T.APPL_STATUS_CODE = '03' and about to set ITP != Y THEN error
itpservice.validation.error.APPL_STATU_CODES_30	ITP can only be set to No if application status is Withdrawn (30)	APPLS_T.APPL_STATUS_CODE in ('30') and about to set ITP != N THEN error
itpservice.validation.error.APPL_STATU_CODES_01	ITP can only be set to No if application status is Withdrawn (01)	APPLS_T.APPL_STATUS_CODE in ('01') and about to set ITP != N THEN error
itpservice.validation.error.APPL_STATU_CODES_02	ITP can only be set to No if application status is Withdrawn (02)	APPLS_T.APPL_STATUS_CODE in ('02') and about to set ITP != N THEN error
itpservice.validation.error.APPL_STATU_CODES_19	ITP can only be set to Yes if application status is Pending Award (19)	APPLS_T.APPL_STATUS_CODE = '19' and about to set ITP != Y THEN error
APPL_STATUS_CODES_0506_ITPY	ITP can only be set to Yes if application status is Awarded (05 or 06)	APPLS_T.APPL_STATUS_CODE in ('05','06') and about to set ITP != Y THEN error

IRG_RECOM_CODE_6_COUNCIL_RECOMM_RECOM_CODE_7	The Council Recommendation cannot be updated to 7 (IC Designated Not Considered) because IRG Recommendation Code is 6 (Not Discussed)	APPLS_T.IRG_RECOM_CODE = 6 and about to set APPLS_T.COUNCIL_RECOM_CODE = 7 THEN error
COUNCIL_RECOMM_RECOM_CODE_6_ITP_N	Update not allowed. For applications with Council Recommendation code of 6, ITP can only be set to N or NULL.	APPLS_T.COUNCIL_RECOM_CODE = 6 and About to set ITP = Y or D THEN error
COUNCIL_RECOMM_RECOM_CODE_2_ITP_N	Update not allowed. For applications with Council Recommendation code of 2, ITP can only be set to N or NULL.	APPLS_T.COUNCIL_RECOM_CODE = 2 and About to set ITP = Y or D THEN error

Table 2: Business Rule & Validation Error Messages

2.4 Web Service End Points

Following are the end point URL's for the web service in each of the eRA environments.

For UAT, please connect to the TEST end point. TEST

https://services.internal.test.era.nih.gov/payplan/services/itp_ext_ws

STAGE

https://services.internal.stage.era.nih.gov/payplan/services/itp_ext_ws

PROD

https://services.internal.era.nih.gov/payplan/services/itp_ext_ws/?wsdl

2.5 WSDL

If the certificate is still in the process of being procured or configured, IC users can use the attached WSDL and XSD files to start coding the client software.

Find the links to download the three files (itp.xsd, itp-service.xsd, itpservice-ext.wsdl) on the <http://inside.era.nih.gov/Technical/oltp.cfm#1> and save them to the same directory on your PC, e.g., c:\itp_wsdl\, for the correct reference among the files.

3 WSDL Definition

```
<?xml version="1.0" encoding="UTF-8" standalone="no" ?>
- <wsdl:definitions xmlns:soap12="http://schemas.xmlsoap.org/wsdl/soap12/"
  xmlns:wsdl="http://schemas.xmlsoap.org/wsdl/"
  xmlns:xsd="http://www.w3.org/2001/XMLSchema"
  xmlns:tns="http://era.nih.gov/payplan/service"
  targetNamespace="http://era.nih.gov/payplan/service">
- <wsdl:types>
- <xsd:schema>
    <xsd:import namespace="http://era.nih.gov/payplan/service"
      schemaLocation="itp-service.xsd" />
  </xsd:schema>
  </wsdl:types>
- <wsdl:message name="ItpUpdateReq">
    <wsdl:part name="input" element="tns:itpExternalUpdateRequest" />
  </wsdl:message>
- <wsdl:message name="ItpUpdateRes">
    <wsdl:part name="output" element="tns:itpUpdateResponse" />
  </wsdl:message>
- <wsdl:message name="ItpUpdatFault">
    <wsdl:part name="fault" element="tns:FaultMessage" />
  </wsdl:message>
```

```
- <wsdl:portType name="itp_ext_portType">
- <wsdl:operation name="ItpUpdate">
    <wsdl:input message="tns:ItpUpdateReq" />
    <wsdl:output message="tns:ItpUpdateRes" />
    <wsdl:fault name="ItpFault" message="tns:ItpUpdatFault" />
</wsdl:operation>
</wsdl:portType>
- <wsdl:binding name="itp_ext_Binding" type="tns:itp_ext_portType">
    <soap12:binding style="document"
    transport="http://schemas.xmlsoap.org/soap/http" />
- <wsdl:operation name="ItpUpdate">
    <soap12:operation soapAction="ItpUpdate"
style="document" /> - <wsdl:input>
    <soap12:body use="literal" />
</wsdl:input>
- <wsdl:output>
    <soap12:body use="literal" />
</wsdl:output>
- <wsdl:fault name="ItpFault">
    <soap12:fault use="literal" name="ItpFault" />
</wsdl:fault>
</wsdl:operation>
</wsdl:binding>
- <wsdl:service name="itp_ext_ws">
- <wsdl:port name="HttpSoap11Endpoint" binding="tns:itp_ext_Binding">
```

```
        <soap12:address location="http://localhost:8080/payplan/services/itp_ext_ws"
        />
    </wsdl:port>
</wsdl:service>

</wsdl:definitions>
```