

PAS Technical User Guide

Purpose

The purpose of this document is to provide a general description and usage guide for eRA's Partner Authorization Service (PAS) web service.

General Description

PAS allows eRA partner organizations (e.g. ICs) to retrieve eRA role information for a user, internal and external users. This API provides extension systems with ability to retrieve eRA role information for their end users by passing the end user's domain account (e.g. NIH username). It is invoked via SOAP over HTTPS. The calling extension system must have a certificate from an authorized certificate provider that has been configured/registered for accessing this service.

Security

The Secure Socket Layer (SSL) client certificate is required for authentication and authorization.

Pre-requisites

The caller must have a certificate from an authorized certificate provider that has been configured/registered for accessing this service. This certificate must be mapped to an account with the ERA_PAS_SERV role. Information on the usage of certificates can be found at http://inside.era.nih.gov/files/S2S_guide_for_eRA_webservices.pdf

Service locations

- Staging -- <https://services.internal.stage.era.nih.gov/aasws/api/pas/getRoles>
- Production -- <https://services.internal.era.nih.gov/aasws/api/pas/getRoles>

Operations

PAS currently supports one operation:

- getRoles
 - Returns role information for username passed in as parameter.

Input Values

The following is an example request.

```
{
  "userIdentityIn": {
    "callerId": "ICE_AI_PCC",
    "userName": {
      "name": "NIH\\user1",
      "orgId": ""
    }
  }
}
```

Request parameters

callerId	(Optional) Calling System Name. This name if provided must be registered with eRA. If an invalid callerId is passed, an error will be returned (see Section 9).
----------	---

name	Username for which roles are needed. Username should be a qualified username i.e. Domain\username (e.g. NIH\user1). Please note that back slash \ is a special character in json syntax, so need to be escaped as double back slash \. Do NOT send the end-user's IMPACII username. Valid "domain names" include: • NIH • NIH-EXTERNAL • NIHEXT • FEDERATION • COMMONS Other than "NIH" and "COMMONS", the other three domains are used for OpDIV users. NIHEXT and NIH-EXTERNAL are Active Directories maintained by NIH to provide accounts to non-NIH users. "FEDERATION" usernames are for OpDIVs that are part of NIH Login Federation.
orgId	(Optional) Organization (e.g. ICs, Agencies) in which PAS checks if user has roles. This is an optional field. If the orgId is specified, PAS will return only the roles for that organization plus GLOBAL roles (GLOBAL roles are applicable across all ICs in all Agencies).

Output Values

The following is a sample output from the service:

```
{
  "UserProfile": {
    "responseTime": 1.6820889847597048E9,
    "userName": "NIH\\user1",
    "primaryOrgId": "0D",
    "profileId": [12344942],
    "role": [
      {
        "name": "CM_SRA_ROLE",
        "context": "AGENCY_IC",
        "organization": ["MH", "CA", "AA"]
      },
      {
        "name": "TA_PAYBACK_SPECIALIST_ROLE",
        "context": "GLOBAL",
        "organization": null
      }
    ]
  }
}
```

Response parameters

responseTime	Current system time
userName	Username that was passed in the request for which roles are requested
primaryOrgId	Primary Org ID of the user
profileId	The person profile ID for the user.
role	Role information. Node is repeated for each role for the user.
role/name	Name of the role
role/context	The role's context. Valid contexts are: GLOBAL – user has the role for all ICs across all Agencies AGENCY – user has the role for specific agencies (e.g. NIH, CDC, VA) AGENCY_IC – user has the role for specific ICs (e.g. NCI)

role /organization	Organization for which the user has the role. If the "context" is GLOBAL, organization is not returned. For roles with context AGENCY_IC, organization is the ICs for which the user has the roles. Repeated for each organization to which the user has the given role. If the context is AGENCY_IC, the value is two letter abbreviation of IC as defined in IMPACI18.PHS_ORG_T table's PHS_ORG_CODE column. If the context is AGENCY, the value is an agency value as defined in IMPACI18.PHS_AGENCY_CODES_T table's PHS_AGENCY_CODE column.
--------------------	--

Error messages/ Validations

- **HTTP 400 error**
 - If input data doesn't follow the json schema, the service will return 400 error.
- **HTTP 500 error** - All other error conditions, sample errors are:
 - Access denied for user
 - SQLException error
 - Account is not active.
 - Account is in pending NIH approval status for external accounts.
 - Account is in pending affiliation status.
 - User has not logged into the system in 120 days so account is locked due to inactivity.
 - Status code could not be retrieved.
 - Could not retrieve mapped user.