



Diesel Fuel

Safety Data Sheet

According to Regulation 2012 OSHA Hazard Communication Standard; 29 CFR Part 1910.1200

Section 1: Identification

1.1. Product identifier

Product form : Mixture

Product Identifier(s) : Diesel Fuel
Heating Oil
Low Sulfur Diesel
Ultra-low Sulfur Diesel
High Sulfur Diesel
Diesel
Fuel Oil #2
Furnace Oil #2
No. 2 Diesel Fuel
Hydrotreated Diesel Fuel
ULSD
Export Diesel
UULSD
Colonial Grade 67
Distillates (petroleum), hydrodesulfurized middle

Other means of identification : A complex combination of hydrocarbons obtained from a petroleum stock by treating with hydrogen to convert organic sulfur to hydrogen sulfide which is removed. It consists of hydrocarbons having carbon numbers predominantly in the range of C11 through C25 and boiling in the range of approximately 205°C to 400°C (401°F to 752°F).

CAS-No. : 64742-80-9

1.2. Recommended use of the chemical and restrictions on use

Use of the substance/mixture : Fuel

1.3. Details of the supplier of the safety data sheet

TotalEnergies Petrochemicals & Refining USA, Inc.
P O Box 674411
Houston, TX 77267-4411

For non-emergency product information:
Phone: 713-483-5000
Email: product.stewardship@totalenergies.com

1.4. Emergency telephone number

Emergency number : CHEMTREC: 1-800-424-9300 (Toll Free USA & Canada) / 703-527-3887 (Multiple languages)
TotalEnergies Petrochemicals & Refining USA, Inc.: 1-800-322-3462 (Language: English only)

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (GHS-US)

Flammable liquids Category 3
Acute toxicity (inhalation:dust,mist) Category 4
Skin corrosion/irritation Category 2
Carcinogenicity Category 2
Specific target organ toxicity (single exposure) Category 3 - Narcotic effects
Specific target organ toxicity (repeated exposure) Category 2
Aspiration hazard Category 1
Hazardous to the aquatic environment - Chronic Hazard Category 2

2.2. Label elements

Diesel Fuel

Safety Data Sheet

GHS US labeling

Hazard pictograms (GHS-US)



Signal word (GHS US)

: Danger

Hazard statements (GHS-US)

: **Flammable liquid and vapor**
May be fatal if swallowed and enters airways
Causes skin irritation
Harmful if inhaled
May cause drowsiness or dizziness
Suspected of causing cancer
May cause damage to organs (bone marrow, liver, thymus) through prolonged or repeated exposure
Toxic to aquatic life with long lasting effects

Precautionary statements (GHS-US)

: Obtain special instructions before use.
Do not handle until all safety precautions have been read and understood.
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Keep container tightly closed.
Ground/Bond container and receiving equipment.
Use explosion-proof electrical, lighting, ventilating equipment.
Use only non-sparking tools.
Take precautionary measures against static discharge.
Do not breathe mist, spray, vapors.
Wash hands, forearms and face thoroughly after handling.
Use only outdoors or in a well-ventilated area.
Avoid release to the environment.
Wear eye protection, impermeable protective gloves, flame retardant protective clothing.
Specific treatment (see Section 4.1 of SDS or information on this label).
If swallowed: Immediately call doctor, a POISON CENTER.
Do NOT induce vomiting.
If on skin: Wash with plenty of water.
If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
If skin irritation occurs: Get medical advice/attention.
If inhaled: Remove person to fresh air and keep comfortable for breathing.
Get medical advice/attention if you feel unwell.
If exposed or concerned: Get medical advice/attention.
Take off contaminated clothing and wash it before reuse.
In case of fire: Use water spray or fog, foam, dry chemical to extinguish.
Collect spillage.
Store in a well-ventilated place. Keep cool.
Store locked up.
Dispose of contents and container in accordance with all local, regional, national and international regulations.

2.3. Hazards not otherwise classified

Other hazards which do not result in classification

: Product can accumulate electrostatic charges that may cause fire by electrical discharges.

2.4. Unknown acute toxicity (GHS-US)

Not applicable

2.5. Additional information

Based on professional judgment, inconclusive testing, or sensitive individuals

: May cause mild eye irritation.
May cause mild respiratory irritation.

Section 3: Composition/Information on ingredients

3.1. Substance

Not applicable

Diesel Fuel

Safety Data Sheet

3.2. Mixture

Where concentrations in this product are displayed as ranges, it is due to batch-to-batch variability.

Name	CAS-No.	% (Weight Percent)
Hydrocarbons (C11 - C20)	-	98 – 100
Naphthalene	91-20-3	< 1
Biphenyl	92-52-4	< 1
Polycyclic Aromatic Compounds	130498-29-2	< 0.5

Section 4: First aid measures

4.1. Description of first aid measures

- First-aid measures general : Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible). Suspected of causing cancer.
- First-aid measures after inhalation : Remove victim to fresh air and keep at rest in a position comfortable for breathing. If breathing is difficult, give oxygen. If breathing stops, give artificial respiration.
- First-aid measures after skin contact : Remove affected clothing and wash all exposed skin area with mild soap and water, followed by warm water rinse.
- First-aid measures after eye contact : Rinse immediately with plenty of water. Obtain medical attention if irritation persists.
- First-aid measures after ingestion : Rinse mouth. Do NOT induce vomiting. Immediately call a poison center or doctor/physician.

4.2. Most important symptoms and effects, both acute and delayed

- Symptoms/effects after inhalation : May cause mild respiratory irritation.
- Symptoms/effects after skin contact : Causes skin irritation.
- Symptoms/effects after eye contact : May cause mild eye irritation.
- Symptoms/effects after ingestion : May be fatal if swallowed and enters airways.
- Chronic symptoms : Suspected of causing cancer. May cause damage to organs through prolonged or repeated exposure.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

Section 5: Firefighting measures

5.1. Extinguishing media

- Suitable extinguishing media : Foam. Dry powder. Carbon dioxide. Water spray. Sand.
- Unsuitable extinguishing media : Do not use a heavy water stream.

5.2. Special hazards arising from the chemical

- Fire hazard : Flammable liquid and vapor.
- Explosion hazard : May form flammable/explosive vapor-air mixture.
- Hazardous decomposition products in case of fire : Hazardous decomposition products formed under fire conditions: carbon monoxide, carbon dioxide, toxic fumes. Fire will produce dense black smoke.

5.3. Advice for firefighters

- Firefighting instructions : Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire-fighting water from entering environment.
- Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

- Emergency procedures for non-emergency personnel : Evacuate unnecessary personnel.
- Emergency procedures for emergency responders : Ventilate area.

6.2. Methods and material for containment and cleaning up

- For containment : Dike for recovery or absorb with appropriate material. Do not contaminate ground and surface water.
- Methods for cleaning up : Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect spillage. Store away from other materials.

6.3. Reference to other sections

See section 8. Exposure controls/personal protection.

Diesel Fuel

Safety Data Sheet

Section 7: Handling and storage

7.1. Precautions for safe handling

- Additional hazards when processed : Handle empty containers with care because residual vapors are flammable. Keep away from heat, sparks, open flames, hot surfaces. - No smoking.
- Precautions for safe handling : Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapor. No bare lights. No smoking. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Avoid breathing vapors, mist. Use only outdoors or in a well-ventilated area.

7.2. Conditions for safe storage, including any incompatibilities

- Technical measures : Proper grounding procedures to avoid static electricity should be followed. All efforts should be made to prevent any leaks or spills. Storage tanks should be engineered to prevent contact with water resources, as this material could contaminate the water resources. Surface spills can reach groundwater through porous soil or cracked surfaces. The storage tanks should be monitored regularly for leaks. Where spills or leaks are possible, a comprehensive response plan should be developed and implemented.
- Storage conditions : Keep only in the original container in a cool, well ventilated place away from : Direct sunlight, flames, heat sources, sparks. Keep in fireproof place. Keep container tightly closed.
- Incompatible products : Strong bases. Strong acids.
- Incompatible materials : Sources of ignition. Direct sunlight. Heat sources.

Section 8: Exposure controls/personal protection

8.1. Occupational Exposure Limits

The following constituents are the only constituents of the product which have a PEL, TLV, or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

Diesel Fuel (64742-80-9)		
USA ACGIH	ACGIH OEL TWA	100 mg/m ³ Measured as Inhalable fraction and vapor as total hydrocarbons. ACGIH Skin Notation
Naphthalene (91-20-3)		
USA ACGIH	ACGIH OEL TWA [ppm]	10 ppm
USA OSHA	OSHA PEL (TWA) [1]	50 mg/m ³
USA OSHA	OSHA PEL (TWA) [2]	10 ppm
IDLH	IDLH [ppm]	250 ppm
Biphenyl (92-52-4)		
USA ACGIH	ACGIH OEL TWA [ppm]	0.2 ppm
USA OSHA	OSHA PEL (TWA) [1]	1 mg/m ³
USA OSHA	OSHA PEL (TWA) [2]	0.2 ppm
IDLH	IDLH	100 mg/m ³

8.2. Exposure controls

- Appropriate engineering controls : Ensure adequate ventilation.
- Personal protective equipment : Avoid all unnecessary exposure.
- Hand protection : Impermeable protective gloves. Choosing the proper glove is a decision that depends not only on the type of material, but also on other quality features, which differ for each manufacturer. Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough. The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.
- Eye protection : Chemical goggles or safety glasses.
- Skin and body protection : Wear fire/flamm resistant/retardant clothing.
- Respiratory protection : An approved organic vapor respirator/supplied air or self-contained breathing apparatus must be used when vapor concentration exceeds applicable exposure limits.
- Other information : Do not eat, drink or smoke during use.

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

- Physical state : Liquid
- Color : Straw.

Diesel Fuel

Safety Data Sheet

Odor	: characteristic.
Odor threshold	: No data available
pH	: Not applicable
Relative evaporation rate (butyl acetate=1)	: No data available
Relative evaporation rate (ether=1)	: 600 x slower than ethyl ether
Melting point	: No data available
Freezing point	: No data available
Boiling point	: 160 (160 – 354.4) °C
Flash point	: 50 (≥ 50) °C Closed cup
Auto-ignition temperature	: > 200 °C
Decomposition temperature	: No data available
Flammability (solid, gas)	: Not applicable
Vapor pressure	: < 1 mm Hg @ 20°C
Relative vapor density at 20 °C	: 8 Air = 1
Relative density	: 0.87
Solubility	: Water: 0.1 – 52 mg/l @ 25°C
Partition coefficient n-octanol/water (Log Kow)	: No data available
Viscosity, kinematic	: 1 – 5 cSt at 40°C
Viscosity, dynamic	: No data available
Explosion limits	: 0.4 – 6 vol %

9.2. Other information

VOC content	: 100 %
-------------	---------

Section 10: Stability and reactivity

10.1. Reactivity

Flammable liquid and vapor.

10.2. Chemical stability

Stable at ambient temperature and under normal conditions of use.

10.3. Possibility of hazardous reactions

Under normal conditions of storage and use, hazardous polymerization will not occur.

10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures. Open flame. Overheating. Heat. Sparks.

10.5. Incompatible materials

Strong oxidizing agents.

10.6. Hazardous decomposition products

Hazardous decomposition products formed under fire conditions: carbon monoxide, carbon dioxide, toxic fumes. Fire will produce dense black smoke.

Section 11: Toxicological information

11.1. Information on toxicological effects

Likely routes of exposure : Inhalation. Ingestion. Skin and eye contact.

Acute toxicity (oral) : Not classified

Acute toxicity (dermal) : Not classified

Acute toxicity (inhalation) : Harmful if inhaled.

Combustion of hydrocarbon substances, like this product, produces potentially toxic gases which include carbon monoxide, carbon dioxide, oxides of nitrogen and/or sulfur. Exposure to carbon monoxide gas decreases the ability of the blood to carry oxygen to the body and may be potentially fatal. NIOSH lists the Immediately Dangerous to Life or Health Concentration (IDLH) for carbon monoxide gas as 1200 ppm.

Diesel Fuel (64742-80-9)	
LD50 oral rat	≈ 5000 mg/kg
LD50 dermal rabbit	> 2000 mg/kg
LC50 inhalation rat	4.6 (4.6 – 7.6) mg/l/4h Inhalation form: aerosol (mist)
Skin corrosion/irritation	: Causes skin irritation.

Diesel Fuel

Safety Data Sheet

Diesel Fuel (64742-80-9)	
Skin Irritation Data	Primary Irritation Index = 4.3-5.6
Serious eye damage/irritation	: Not classified May cause mild eye irritation.
Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Suspected of causing cancer. Petroleum middle distillates, like diesel, have been shown to cause skin tumors in mice following repeated and prolonged skin contact. Additionally, this product contains naphthalene, which has been classified as an IARC Group 2B carcinogen (possibly carcinogenic to humans).
IARC has classified diesel engine exhaust emissions as a Class 1 carcinogen - carcinogenic to humans. Prevent exposure to diesel exhaust emissions.	

Naphthalene (91-20-3)	
IARC group	2B - Possibly carcinogenic to humans
National Toxicology Program (NTP) Status	Reasonably anticipated to be Human Carcinogen
Polycyclic Aromatic Compounds (130498-29-2)	
National Toxicology Program (NTP) Status	Reasonably anticipated to be Human Carcinogen
Additional information	This product may contain polycyclic aromatic hydrocarbons, PAHs (also called polynuclear aromatics, PNAs or Aromatic Hydrocarbons, polycyclic), some of which are suspected of causing skin cancer in humans under conditions of poor personal hygiene and prolonged, repeated contact. Wear chemically impervious gloves. Always wash skin with soap and water after skin contact.
Reproductive toxicity	: Not classified
STOT-single exposure	: May cause drowsiness or dizziness.
STOT-repeated exposure	: May cause damage to organs (bone marrow, liver, thymus) through prolonged or repeated exposure.
Aspiration hazard	: May be fatal if swallowed and enters airways.
Potential Adverse human health effects and symptoms	: Dizziness. Drowsiness. Causes skin irritation. Harmful if inhaled.

Section 12: Ecological information

12.1. Toxicity

Ecology - general : Toxic to aquatic life with long lasting effects.

Diesel Fuel (64742-80-9)	
LC50 - Fish [1]	21 mg/l Oncorhynchus mykiss 96 h
EC50 - Crustacea [1]	68 mg/l Daphnia magna 48 h
EC50 - Other aquatic organisms [1]	22 mg/l Selenastrum capricornutum 72 h

12.2. Persistence and degradability

Diesel Fuel (64742-80-9)	
Persistence and degradability	Inherently biodegradable.

12.3. Bioaccumulative potential

Diesel Fuel (64742-80-9)	
Partition coefficient n-octanol/water (Log Pow)	> 3.5
Bioaccumulative potential	Not established.

12.4. Mobility in soil

Diesel Fuel (64742-80-9)	
Ecology - soil	It may pass through the soil and is likely to contaminate ground water.

12.5. Other adverse effects

Other information : Avoid release to the environment.

Diesel Fuel

Safety Data Sheet

Section 13: Disposal considerations

13.1. Waste treatment methods

- Product/Packaging disposal recommendations : Dispose in a safe manner in accordance with local/national regulations. Dispose of contents and container in accordance with all local, regional, national and international regulations.
- Additional information : Handle empty containers with care because residual vapors are flammable.
- Ecology - waste materials : Avoid release to the environment. Hazardous waste due to toxicity.

Section 14: Transport information

US Transport (DOT) for Bulk Shipments (Non-Bulk Shipments May Differ)

- Transport document description (DOT) : UN1202, Diesel fuel, 3 , PGIII
- UN or NA Number : UN1202
- Proper Shipping Name : Diesel fuel
- Primary Hazard Class : 3 - Flammable liquid
- Packing Group : PGIII
- Hazard labels :



- Emergency Response Guide (ERG) Number : 128

In accordance with the definition in 49 CFR § 171.8, a hazardous substance does not include petroleum, including crude oil or any fraction thereof which is not otherwise specifically listed or designated as such in Appendix A to 49 CFR § 172.101. Therefore, this product does not require a RQ designation.

Not a marine pollutant under DOT regulations. International shipments may differ.

Transport by sea (IMDG)

- Transport document description (IMDG) : UN 1202 DIESEL FUEL, 3, III, MARINE POLLUTANT (50°C c.c.)
- UN Number : UN1202
- Proper Shipping Name : DIESEL FUEL
- Primary Hazard Class : 3 - Flammable liquids
- Packing Group : PGIII
- Hazard labels (IMDG) :



- EmS-No. (Fire) : F-E - FIRE SCHEDULE Echo - NON-WATER-REACTIVE FLAMMABLE LIQUIDS
- EmS-No. (Spillage) : S-E - SPILLAGE SCHEDULE Echo - FLAMMABLE LIQUIDS, FLOATING ON WATER
- Stowage category (IMDG) : A
- Flash point (IMDG) : 50°C c.c.

MARPOL and US Coast Guard Regulations

- Cargo name listed in 46 CFR 30.25, Table 30.25-1 : Oil, fuel: No. 2

Air transport (IATA)

- Transport document description (IATA) : UN 1202 Diesel fuel, 3, III
- UN Number : UN1202
- Proper Shipping Name : Diesel fuel
- Primary Hazard Class : 3 - Flammable Liquids
- Packing Group : PGIII
- Hazard labels (IATA) :



Diesel Fuel

Safety Data Sheet

Section 15: Regulatory information

15.1. US Federal regulations

EPA TSCA Status

This product is a substance under TSCA (CAS No. 64742-80-9; Distillates (petroleum), hydrodesulfurized middle).

SARA Section 313 Supplier Notification

This product contains the following toxic chemical or chemicals subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR 372:

CAS number	Chemical name	Concentration
91-20-3	Naphthalene	< 1%
130498-29-2	Polycyclic Aromatic Compounds	< 0.5%

This product contains Polycyclic Aromatic Compounds (PAC). PACs are listed as a category under SARA 313 and include only specific PACs listed in 40 CFR 372.65(c). The US EPA has established Reporting Threshold for PACs of 100 lbs (40 CFR 372.28). If a facility manufactures, processes, or otherwise uses more than 100 lbs per calendar year of the PAC category SARA 313 reporting is required. See EPA "Emergency Planning and Community Right-to-know Act - Section 313: Guidance for Reporting Toxic Chemicals: Polycyclic Aromatic Compounds Category" (EPA # 260-B-01-03).

This information must be included in all Safety Data Sheets that are copied and distributed for this product. For additional information, see 40 CFR §372.45 Notification About Toxic Chemicals.

SARA Section 311/312 Hazard Classes

Physical hazard - Flammable (gases, aerosols, liquids, or solids)
Physical hazard - Hazard Not Otherwise Classified (HNOC)
Health hazard - Aspiration hazard
Health hazard - Acute toxicity (any route of exposure)
Health hazard - Carcinogenicity
Health hazard - Skin corrosion or Irritation
Health hazard - Specific target organ toxicity (single or repeated exposure)

15.2. International regulations

CANADA

No additional information available

National inventories

Diesel Fuel (64742-80-9)

Listed on or exempt from listing on the AICS (Australian Inventory of Chemical Substances)
Listed on or exempt from listing on the Canadian DSL (Domestic Substances List)
Listed on or exempt from listing on the China Inventory of Existing Chemical Substances (IECSC)
Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)
Listed on or exempt from listing on the Japanese ENCS (Existing & New Chemical Substances) inventory
Listed on or exempt from listing on the Korean ECL (Existing Chemicals List)
Listed on or exempt from listing on NZIoC (New Zealand Inventory of Chemicals)
Listed on or exempt from listing on the Philippines Inventory of Chemicals and Chemical Substances (PICCS)

15.3. US State regulations

California Proposition 65 - This product contains, or may contain, trace quantities of a substance(s) known to the state of California to cause cancer and/or reproductive toxicity, not limited to any that may be listed below.

Naphthalene (91-20-3)	
U.S. - California - Proposition 65 - Carcinogens List	Yes
U.S. - California - Proposition 65 - Developmental Toxicity	No
U.S. - California - Proposition 65 - Reproductive Toxicity - Female	No
U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No
No significant risk level (NSRL)	5.8 µg/day

Section 16: Other information


Other information : None.

Diesel Fuel

Safety Data Sheet

NFPA (National Fire Protection Association)

NFPA health hazard : 1
NFPA fire hazard : 2
NFPA reactivity : 0



Hazard System Rating

Health : 1*
Flammability : 2
Physical Hazard : 0
Personal protection : See section 8 of SDS

US OSHA LABEL as specified under 29 CFR §1910.1200 (f). The label shown may include supplemental information in addition to required elements.

Diesel Fuel

TotalEnergies Petrochemicals & Refining USA, Inc.
PO Box 674411
Houston, TX 77267-4411 USA
Tel. 713-483-5000



Danger

Flammable liquid and vapor

May be fatal if swallowed and enters airways

Causes skin irritation

Harmful if inhaled

May cause drowsiness or dizziness

Suspected of causing cancer

May cause damage to organs (bone marrow, liver, thymus) through prolonged or repeated exposure

Toxic to aquatic life with long lasting effects

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Keep container tightly closed.

Ground/Bond container and receiving equipment.

Use explosion-proof electrical, lighting, ventilating equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Do not breathe mist, spray, vapors.

Wash hands, forearms and face thoroughly after handling.

Use only outdoors or in a well-ventilated area.

Avoid release to the environment.

Wear eye protection, impermeable protective gloves, flame retardant protective clothing.

Specific treatment (see Section 4.1 of SDS or information on this label).

If swallowed: Immediately call doctor, a POISON CENTER.

Do NOT induce vomiting.

If on skin: Wash with plenty of water.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

If skin irritation occurs: Get medical advice/attention.

If inhaled: Remove person to fresh air and keep comfortable for breathing.

Get medical advice/attention if you feel unwell.

If exposed or concerned: Get medical advice/attention.

Take off contaminated clothing and wash it before reuse.

In case of fire: Use water spray or fog, foam, dry chemical to extinguish.

Collect spillage.

Store in a well-ventilated place. Keep cool.

Store locked up.

Dispose of contents and container in accordance with all local, regional, national and international regulations.

Supplemental Information

Product can accumulate electrostatic charges that may cause fire by electrical discharges.

Diesel Fuel

Safety Data Sheet

US SDS Version: 3.1

Issue date: September 9, 2021

SDS ID: DIESEL

SDS REFERENCE NUMBER: RF0049

SDS Template - TotalEnergies SDS US TEPRI Version 20.00

The information contained in this Safety Data Sheet (SDS) is believed by TotalEnergies Petrochemicals & Refining USA, Inc. (TEPRI) to be accurate on the date issued. However, materials may present unknown hazards and should be used with caution. Final determination of suitability and use of any material is the sole responsibility of the user. Neither TEPRI nor any of its subsidiaries or affiliated companies assumes any liability whatsoever for the accuracy or completeness of the information contained herein or reliance thereto. If the material is repackaged, the user is responsible and must ensure that proper health, safety and other necessary information is included with the material and/or on the container. NO WARRANTIES OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING THE MATERIALS OR THE INFORMATION CONTAINED IN THIS SDS. ALTERATION OF THIS DOCUMENT IS STRICTLY PROHIBITED.