



**"Core" connects you and me, and
"wisdom" connects the Future**



Infrared Passenger Counter WEB Version

Model: HX-HE3

Product Description:

• The statistical principle of infrared passenger flow counter is mainly infrared blocking counting. The infrared receiving module automatically identifies the pedestrian's walking direction through the infrared blocking direction and generates a count.

Application scenarios:

• The infrared passenger flow WEB version can be used in shopping malls, retail stores, public transportation, scenic spots, libraries, museums, restaurants, factories, supermarkets, parks, buildings, toilets, etc.

Product Features:

- Easy to install, suitable for non-network environments, just stick on the code and use it;
- Data management: After the device generates data, the mobile phone can connect to the device AP without downloading software, and the data generated by the device can be managed and queried directly through the mobile browser page. You can also export data files to your mobile phone for immediate use;

(The data can be downloaded, and you can query hourly data for the past 7 days, cumulative data for the past 90 days, and every day, cumulative data for the past 100 weeks, every week, cumulative data for the past 36 months, every month, and cumulative data for the past 10 years, every year.)

- Easy to operate, you can directly set and view all parameter information through the web page;
- Supports 18500 battery power supply, 2000mAH battery can last for 1-3 months; supports Type-c interface to charge the device and battery at the same time.

Product Photos:



• Accessories



3M Glue



18500Battery



Charger

Product Specifications:

Model	<ul style="list-style-type: none">HX-HE3
Installation Method	<ul style="list-style-type: none">Fixed installation on both sides of entrance and exit
Visual Parameters	<ul style="list-style-type: none">Line of sight (coverage): 1m-20m indoors, 1m-17m outdoor
Accuracy	<ul style="list-style-type: none">≥80% (under standard environment)
Height Range	<ul style="list-style-type: none">Recommended 1.0m-1.4m
Power	<ul style="list-style-type: none">0.004~0.37W
Power Supply	<ul style="list-style-type: none">3.7VLi-ion(2000mAh)/Type-c wired power supply
Storage	<ul style="list-style-type: none">Hourly for the last 7 daysAccumulated daily data for the past 90 daysCumulative weekly data for the past 100 weeksCumulative monthly data for the past 36 months

	<ul style="list-style-type: none"> Cumulative data for each year in the past 10 years
Battery life	<ul style="list-style-type: none"> 1-3 months under standard environment
Working Environment	<ul style="list-style-type: none"> Working temperature (-20°C~55°C) Working humidity (10~80%RH (non-condensing)) Storage temperature (-40°C~70°C) Storage Humidity (5~90 % RH(non-condensing))
Product Specifications	<ul style="list-style-type: none"> Dimensions (mm): 65x 50 x 25, Net weight (g): 78
Packaging Specifications	<ul style="list-style-type: none"> Dimensions (mm): 185x150x67, Weight (g): 460 (including accessories)
Outer Box Specifications	<ul style="list-style-type: none"> Dimensions (mm): 390x370x320 (the whole box can hold 20 units), net weight (Kg): 9.98/carton
Product Related Certificate	<ul style="list-style-type: none"> CE/FCC/ROSH/Quality Inspection Report/1.2 Meter Drop Test Report/Appearance patent/utility model

Company Website	Technical Support Contact	Sales Hotline	Online Purchase
www.foorir.com	+8618011496629 info@foorir.com	+86-400-9010-980 +8618981978865	huaxiniot.en.alibaba.com

We will release the upgrade software or drivers of each product on the official website in time, and you can get technical support at www.foorir.com and download the latest software or drivers for free. Huaxin Zhiyun Technology Co., Ltd. will do its best to check the errors in printing and pictures, but please understand the possible omissions. The product appearance, specifications, parameters, prices and product availability listed on this page are subject to change at any time, and the actual situation shall prevail.