
**CCA**
Common Component Architecture


Welcome to the Tutorial on Rapid, Sustainable Development for Complex HPC Software

PARA 2008
13 May 2008

CCA Forum Tutorial Working Group
[http://www.cca-forum.org/tutorials/
tutorial-wg@cca-forum.org](http://www.cca-forum.org/tutorials/tutorial-wg@cca-forum.org)

 This work is licensed under a [Creative Commons Attribution 2.5 License](http://creativecommons.org/licenses/by/2.5/)


1

**CCA**
Common Component Architecture


Supplementary material for handouts

Licensing Information

- This tutorial is distributed under the [Creative Commons Attribution 2.5 License](http://creativecommons.org/licenses/by/2.5/)
 - <http://creativecommons.org/licenses/by/2.5/>
- In summary, **you are free:**
 - to copy, distribute, display, and perform the work
 - to make derivative works
 - to make commercial use of the work
- **Under the following conditions:**
 - **Attribution.** You must attribute the work in the manner specified by the author or licensor.
- For any reuse or distribution, you must make clear to others the license terms of this work.
- Any of these conditions can be waived if you get permission from the copyright holder.
- **Your fair use and other rights are in no way affected by the above.**
- **Requested reference:**
 - **CCA Forum Tutorial Working Group, Common Component Architecture Tutorial, 2008, <http://www.cca-forum.org/tutorials/>**




2


 **CCA**
Common Component Architecture

Supplementary material for handouts

About the Printed Notes


- The printed version of these presentations includes additional slides marked *“Supplementary material for handouts”*
- Additional material to address questions sometimes raised, or provide more detail on a topic
- We are happy to discuss this material if asked


 3


 **CCA**
Common Component Architecture


Introductions

- Benjamin Allan (Sandia National Laboratories)
- Tony Drummond (Lawrence Berkeley National Laboratory)
- Stefan Muszala (Tech-X Corporation)
- Jaideep Ray (Sandia National Laboratories)
- Damian Rouson (Sandia National Laboratories)

 4


 CCA Common Component Architecture			
Agenda & Table of Contents			
Time	Title	Slide No.	Presenter
08:30-10:00	Welcome	1	Ben Allan, SNL
	Introduction to Babel and the CCA	7	Ben Allan, SNL
	The Primary Tools	54	Ben Allan, SNL
	Approaches & Experience	80	Jaideep Ray, SNL
	Closing	105	Jaideep Ray, SNL
10:00-10:30	<i>Break</i>		
10:30-11:00	Can it be that Easy? A Quick Demonstration		Ben Allan, SNL
11:00-12:00	Hands-On	Hands-On Guide	All instructors
12:00-13:30	<i>Lunch (provided for paying Tutorial Participants)</i>		
13:30-15:00	Hands-On (continued)		
15:00-15:30	<i>Break</i>		
15:30-17:00	Hands-On (continued)		

 CCA Common Component Architecture	
Who We Are: The Common Component Architecture (CCA) Forum	
<ul style="list-style-type: none">• Combination of standards body and user group for the CCA• Define specifications for high-performance scientific components & frameworks• Promote and facilitate development of tools for component-based software development, components, and component applications• Open membership, quarterly meetings...	
General mailing list: cca-forum@cca-forum.org	
Web: http://www.cca-forum.org/	
<ul style="list-style-type: none">• Center for Technology for Advanced Scientific Component Software (TASCS)<ul style="list-style-type: none">– Funded by the US DOE SciDAC program– Core development team for CCA technologies	


**CCA**
Common Component Architecture

Introduction to HPC Component Software

CCA Forum Tutorial Working Group
<http://www.cca-forum.org/tutorials/tutorial-wg> [@cca-forum.org](mailto:tutorial-wg@cca-forum.org)

 This work is licensed under a [Creative Commons Attribution 2.5 License](https://creativecommons.org/licenses/by/2.5/)

7

**CCA**
Common Component Architecture


Managing Code Complexity

Some Common Situations:

- Your code is so large and complex it has become fragile and hard to keep running
- You have a simple code, and you want to extend its capabilities – rationally
- You want to develop a computational “toolkit”
 - Many modules that can be assembled in different ways to perform different scientific calculations
 - Gives users w/o programming experience access to a flexible tool for simulation
 - Gives users w/o HPC experience access to HPC-ready software

How CCA Can Help:

- Components help you think about software in manageable chunks that interact only in well-defined ways
- Components provide a “plug-and-play” environment that allows easy, flexible application assembly



8

Example: Computational Facility for Reacting Flow Science (CFRFS)

-
- The screenshot displays the UML Component Architecture diagram for the 'UML4JModel' package. The diagram is titled 'UML4JModel' and is part of a larger project named 'UML4JModel'. The diagram shows a complex set of components and their relationships. Components are represented as boxes with properties like name, version, and interfaces. Relationships are shown as lines connecting components, often labeled with provided and required interfaces. The diagram is organized into several layers, with some components grouped together. The top layer includes components like 'UML4JModel', 'UML4JModelImpl', and 'UML4JModelImplImpl'. The middle layer includes 'UML4JModelImplImplImpl', 'UML4JModelImplImplImplImpl', and 'UML4JModelImplImplImplImplImpl'. The bottom layer includes 'UML4JModelImplImplImplImplImpl', 'UML4JModelImplImplImplImplImplImpl', and 'UML4JModelImplImplImplImplImplImplImpl'. The diagram is titled 'UML4JModel' and is part of a larger project named 'UML4JModel'.


Languages: C, C++, F77

Helping Groups Work with Software

- Many (geographically distributed) developers creating a large software system
 - Hard to coordinate, different parts of the software don't work together as required
- Groups of developers with different specialties
- Forming communities to standardize interfaces or share code


- Components are natural units for
 - Expressing software architecture
 - Individuals or small groups to develop
 - Encapsulating particular expertise
- Some component models (including CCA) provide tools to help you think about the *interface* separately from the *implementation*

10

 **CCA**
Common Component Architecture

Example: Quantum Chemistry

- Integrated state-of-the-art optimization technology into two quantum chemistry packages to explore effectiveness in chemistry applications
- Geographically distributed expertise:
 - California - chemistry
 - Illinois - optimization
 - Washington – chemistry, parallel data management
- Effective collaboration with minimal face-to-face interaction




Schematic of CCA-based molecular structure determination quantum chemistry application.


Components based on: MPQC, NWChem (quantum chem.), TAO (optimization), Global Arrays, PETSc (parallel linear algebra)

CCA tools used: Babel, Ccaffeine, and ccafe-gui

Languages: C, C++, F77, Python



11

 **CCA**
Common Component Architecture


Language Interoperability

Some Common Situations:


- Need to use existing code or libraries written in multiple languages in the same application?
- Want to allow others to access your library from multiple languages?
- Technical or sociological reasons for wanting to use multiple languages in your application?


How CCA Can Help:

- Some component models (including CCA) allow transparent mixing of languages
- Babel (CCA's language interop. tool) can be used separately from other component concepts




12

 **CCA**
Common Component Architecture

**hypre**
high performance
preconditioners

Examples



hypre

- High performance preconditioners and linear solvers
- Library written in C
- Babel-generated object-oriented interfaces provided in C, C++, Fortran


LAPACK07

- Update to LAPACK linear algebra library
 - To be released 2007
 - Library written in F77, F95
- Will use Babel-generated interfaces for: C, C++, F77, F95, Java, Python
- Possibly also ScaLAPACK (distributed version)


"I implemented a Babel-based interface for the hypre library of linear equation solvers. The Babel interface was straightforward to write and gave us interfaces to several languages for less effort than it would take to interface to a single language."

-- Jeff Painter, LLNL. 2 June 2003

CCA tools used: Babel, Chasm



13

 **CCA**
Common Component Architecture


Coupling Codes

Some Common Situations:


- Your application makes use of numerous third-party libraries
 - Some of which interact (version dependencies)
- You want to develop a simulation in which your code is coupled with others
 - They weren't designed with this coupling in mind
 - They must remain usable separately too
 - They are all under continual development, individually
 - They're all parallel and need to exchange data frequently

How CCA Can Help:

- Components are isolated from one another
 - Interactions via well-defined interfaces
 - An application can include multiple versions of a component
- Components can be composed flexibly, hierarchically
 - Standalone application as one assembly, coupled simulation as another
- CCA can be used in SPMD, MPMD, and distributed styles of parallel computing
- CCA is developing technology to facilitate data and functional coupling of parallel applications




14

 **CCA**
Common Component Architecture

Example: Integrated Fusion Simulation


- Proof-of-principle of using CCA for integrated whole-device modeling needed for the ITER fusion reactor
- Couples radio frequency (RF) heating of plasma with transport modeling
- Coarse-grain encapsulation of pre-existing programs
- Follow-on plans for RF, transport, and magneto-hydrodynamics



"Wiring diagram" for integrated fusion simulation.

Components based on: AORSA, Houlberg's transport library
New components: Driver, State
CCA tools used: Babel, Chasm, Ccaffeine, ccafe-gui
Languages: C++, F90, Python


15

 **CCA**
Common Component Architecture

What are Components?


- No universally accepted definition in computer science research, but key features include...
- A unit of software development/deployment/reuse
 - i.e. has **interesting functionality**
 - Ideally, functionality someone else might be able to **(re)use**
 - Can be **developed independently** of other components
- Interacts with the outside world only through well-defined interfaces
 - **Implementation is opaque** to the outside world
- Can be composed with other components
 - "Plug and play" model to build applications
 - **Composition based on interfaces**


16



 CCA
Common Component Architecture


What is a Component Architecture?

- A set of **standards** that allows:
 - Multiple groups to write units of software (**components**)...
 - And have confidence that their components will **work with other components** written in the same architecture
- These standards **define**...
 - The rights and responsibilities of a **component**
 - How components express their **interfaces**
 - The environment in which components are composed to form an application and executed (**framework**)
 - The rights and responsibilities of the framework

 17








CCA
Common Component Architecture

Supplementary material for handouts

Comparison of Application Development Approaches

Characteristics	Monolithic Simulation Code	Simulation Frameworks	Library -Based	Component -Based
Support for specific workflows and information flows	High	High	Low	Low
Flexibility w.r.t. workflow and information flow	Low	Medium	High	High
User-level extensibility	Low	Medium	High	High
Ease of incorporation of outside code (code reuse)	Low	Low-Medium	Medium	High
Ease of experimentation	Low	Medium	Medium	High
Amount of new code required to create a complete simulation	Low	Medium	High	High (reuse can reduce)
Breadth of current "ecosystem" for "plugins"	Low	Medium	High	Low (but growing)
Ease of coupling simulations	Low	Low	Medium	High


22


CCA
Common Component Architecture

Supplementary material for handouts

Be Aware: “Framework” Describes Many Things


- Currently in scientific computing, this term means different things to different people
- **Basic software composition environment**
 - Examples: CCA, CORBA Component Model, ...
- An environment facilitating development of applications in **a particular scientific domain** (i.e. fusion, computational chemistry, ...)
 - Example: Earth System Modeling Framework, <http://www.esmf.ucar.edu>
 - Example: Computational Facility for Reacting Flow Science, <http://cfrfs.ca.sandia.gov>
- An environment for managing complex **workflows** needed to carry out calculations
 - Example: Kepler: <http://kepler-project.org>
- **Integrated data analysis and visualization environments** (IDAVEs)
- Lines are often fuzzy
 - Example: Cactus, <http://www.cactuscode.org>
- Others types of frameworks *could* be built based on a **basic software composition environment**


23

CCA
Common Component Architecture

Relationships: Components, Objects, and Libraries


- Components are typically discussed as **objects** or collections of objects
 - **Interfaces** generally designed in **OO** terms, but...
 - Component **internals need not be OO**
 - **OO languages are not required**
- Component environments can **enforce** the use of **published interfaces** (prevent access to internals)
 - Libraries can not
- It is possible to load **several instances** (versions) of a component in a single application
 - Impossible with libraries
- Components *must* include some code to **interface with the framework/component environment**
 - Libraries and objects do not


24

 **CCA**
Common Component Architecture

What is the CCA?


- Component-based software engineering has been developed in other areas of computing
 - Especially business and internet
 - Examples: CORBA Component Model, COM, Enterprise JavaBeans
- Many of the needs are similar to those in HPC scientific computing
- But scientific computing imposes special requirements not common elsewhere
- CCA is a component environment specially designed to meet the needs of HPC scientific computing


 25

 **CCA**
Common Component Architecture

Special Needs of Scientific HPC


- Support for legacy software
 - How much **change** required for component environment?
- Performance is important
 - What **overheads** are imposed by the component environment?
- Both parallel and distributed computing are important
 - What approaches does the component model support?
 - What **constraints** are imposed?
 - What are the **performance costs**?
- Support for **languages, data types, and platforms**
 - Fortran?
 - Complex numbers? Arrays? (as first-class objects)
 - Is it available on my parallel computer?


 26

 **CCA**
Common Component Architecture


CCA: Concept and Practice

- In the following slides, we explain important **concepts** of component-based software from the CCA perspective
- We also sketch how these concepts are **manifested in code** (full details in the Hands-On)
- The **CCA Specification** is the mapping between concept and code
 - A standard established by the CCA Forum
 - Expressed in the Scientific Interface Definition Language (SIDL) for language neutrality (syntax similar to Java)
 - SIDL can be translated into bindings for specific programming languages using, e.g., the Babel language interoperability tool

 27


 **CCA**
Common Component Architecture


CCA Concepts: Components




```
graph LR; MI[MidpointIntegrator] --- NF[NonlinearFunction]; MI -- IntegratorPort --- FP1[FunctionPort]; NF -- FunctionPort --- FP2[FunctionPort];
```

- A component encapsulates some computational functionality
- Components provide/use one or more interfaces
 - A component with no interfaces is formally okay, but isn't very interesting or useful
- In SIDL, a component is a **class** that **implements** (inherits from) **`gov.cca.Component`**
 - This means it must implement the **`setServices`** method to tell framework what ports this component will **provide** and **use**
 - **`gov.cca.Component`** is defined in the CCA specification


 28


 **CCA**
Common Component Architecture

CCA Concepts: Ports




- Components interact through well-defined **interfaces**, or **ports**
 - A port expresses some **computational functionality**
 - In Fortran, a port is a bunch of subroutines or a **module**
 - In OO languages, a port is an **abstract class** or **interface**
- Ports and connections between them are a procedural (caller/callee) relationship, **not dataflow!**
 - e.g., *FunctionPort* could contain a method like `evaluate(in Arg, out Result)` with data flowing both ways


 29



 **CCA**
Common Component Architecture


CCA Concepts: *Provides* and *Uses* Ports



- Components may **provide** ports – **implement** the class or subroutines of the port (**"Provides" Port**)
 - *Providing* a port implies certain inheritance relationships between the component and the abstract definition of the interface (**more details shortly**)
 - A component can *provide* multiple ports
 - Different "views" of the same functionality, or
 - Related pieces of functionality
- Components may **use** ports – **call** methods or subroutines in the port (**"Uses" Port**)
 - *Use* of ports is just like calling a method normally except for a little additional work due to the "componentness" (**more details shortly**)
 - No inheritance relationship implied between caller and callee
 - A component can *use* multiple ports

 30





 **CCA**
Common Component Architecture

Supplementary material for handouts

Where Do Ports Come From?

- Most ports are designed and implemented by **users** of CCA
 - May be specific to an application or used more broadly (i.e. community-wide)
- The **CCA specification** defines a *small* number of ports
 - Most are services CCA frameworks must provide for use by components
 - Some are intended for users to implement in their components, and have a special meaning recognized by the framework
 - *E.g. `gov.cca.ports.GoPort`* provides a very simple protocol to start execution of component-based applications


 33


 **CCA**
Common Component Architecture

Supplementary material for handouts


Interfaces are an Investment

- The larger the community, the greater the time & effort required to obtain agreement
 - Equally true in component and non-component environments
 - MPI 1.0 (well understood at the start) took 8 months, meeting every six weeks
 - MPI 2.0 (not well understood at the start) took 1.5 years, meeting every six weeks
 - Convenient communities are often “project” and “scientific domain”
- Formality of “standards” process varies
- Biggerstaff’s Rule of Threes
 - Must look at at least **three systems** to understand what is common (reusable)
 - Reusable software requires **three times the effort** of usable software
 - Payback only after **third release**


 34


 **CCA**
Common Component Architecture

CCA Concepts: Frameworks




- The framework provides the means to “hold” components and **compose** them into applications
- Frameworks allow **connection of ports** without exposing component implementation details
- Frameworks provide a small set of **standard services** to components
 - Framework services are CCA ports, just like on components
 - Additional (non-standard) services can also be offered
 - Components can register ports as services using the *ServiceProvider* port
- *Currently*: specific frameworks are specialized for specific computing models (parallel, distributed, etc.)
- *Future*: better integration and interoperability of frameworks


 35


 **CCA**
Common Component Architecture

Components Must Keep Frameworks Informed




- Components must tell the framework about the ports they are providing and using
 - Framework will not allow connections to ports it isn't aware of
- Register them using methods on the component's **gov.cca.Services** object
 - **addProvidesPort()** and **removeProvidesPort()**
 - **registerUsesPort()** and **unregisterUsesPort()**
 - All are defined in the CCA specification
- Ports are usually registered in the component's **setServices()** method
 - Can also be added/removed dynamically during execution

 36


 **CCA**
Common Component Architecture


CCA Concepts: Language Interoperability

- Scientific software is increasingly diverse in use of programming languages
- In a component environment, users should not care what language a component is implemented in
- “Point-to-point” solutions to language interoperability are not suitable for a component environment
- The **Babel** language interoperability tool provides a common solution for all supported languages
- **Scientific Interface Definition Language** provides a language-neutral way of expressing interfaces



37






CCA
Common Component Architecture

....

CCA Supports Parallelism -- by “Staying Out of the Way” of it

- Single component multiple data (SCMD) model is component analog of widely used SPMD model
- Each process loaded with the same set of components wired the same way
- Different components in same process “talk to each” other via ports and the framework
- **Same component in different processes talk to each other through their favorite communications layer (i.e. MPI, PVM, GA)**




P0 P1 P2 P3

Components: Blue, Green, Red
Framework: Gray

Any parallel programming environments that can be mixed outside of CCA can be mixed inside

39




CCA
Common Component Architecture

Supplementary material for handouts


“Multiple-Component Multiple-Data” Applications in CCA

- Simulation composed of multiple SCMD sub-tasks
- Usage Scenarios:
 - Model coupling (e.g. Atmosphere/Ocean)
 - General multi-physics applications
 - Software licensing issues
 - i.e. limited number of instances
- Approaches
 - Run single parallel framework
 - Driver component that partitions processes and builds rest of application as appropriate (through BuilderService)
 - Run multiple parallel frameworks
 - Link through specialized communications components
 - Link as components (through AbstractFramework service)



Processors

40




CCA Common Component Architecture

Supplementary material for handouts

“Direct Connection” Details

- Directly connected components are in the **same address space**
 - Data can be passed by reference instead of copying
 - Just like “traditional” programs
 - Framework involved in **connecting** components, but **not invocations** on ports
- Cost of “CCAness” in a direct connect environment is **one level of indirection** on calls **between** components
 - Equivalent to a C++ **virtual function call**: lookup function location, invoke it
 - Overhead is on the **invocation only** (i.e. latency), not the total execution time
 - Cost equivalent of ~2.8 F77 or C function calls
 - ~48 ns vs 17 ns on 500 MHz Pentium III Linux box


42


 **CCA**
Common Component Architecture

Maintaining HPC Performance

- The performance of your application is as important to us as it is to you
- The CCA is designed to provide maximum performance
 - But the best we can do is to make your code perform **no worse, unless we give easy access to new algorithms.**
- Facts:
 - Measured overheads per function call are **low**
 - Most overheads **easily amortized** by doing enough work per call
 - Other changes made during componentization may also have performance impacts
 - **Awareness** of costs of abstraction and language interoperability facilitates design for high performance

More about performance in notes


 43

 **CCA**
Common Component Architecture

Supplementary material for handouts


Some Performance Results and References

- Lois Curfman McInnes, et al. **Parallel PDE-Based Simulations Using the Common Component Architecture.** In Are Magnus Bruaset, Petter Bjorstad, and Aslak Tveito, editors, *Numerical Solution of PDEs on Parallel Computers*. Springer-Verlag, 2005. Invited chapter, in press.
- S. Benson, et al. **Using the GA and TAO Toolkits for Solving Large-Scale Optimization Problems on Parallel Computers.** Technical report ANL/MCS-P1084-0903, Argonne National Laboratory, September 2003.
- Boyana Norris, et al. **Parallel Components for PDEs and Optimization: Some Issues and Experiences.** *Parallel Computing*, 28:1811--1831, 2002.
- David E. Bernholdt, et al. **A Component Architecture for High-Performance Computing.** In *Proceedings of the Workshop on Performance Optimization via High-Level Languages and Libraries (POHLL-02)*, 2002.




# of procs	% Overhead
1	0.05
4	0.12
16	0.14
32	0.18
64	0.20
128	0.20
170	0.11


Maximum 0.2% overhead for CCA vs native C++ code for parallel molecular dynamics up to 170 CPUs



Problem Size	Linear Solver Component (sec)	PETSc SLES (sec)
100x100	~5	~5
150x150	~25	~25
200x200	~55	~55
250x250	~95	~95

Aggregate time for linear solver component in unconstrained minimization problem w/ PETSc

 44


 **CCA**
Common Component Architecture


Supplementary material for handouts

Advanced CCA Concepts

Brief introductions only, but more info is available – just ask us!

- Leveraging the component environment to provide additional capabilities to software developers
- The Proxy Component pattern (Hands-On, papers)
- Component lifecycle (tutorial notes, Hands-On)
- Components can be dynamic (papers)
- Improving the quality of component software (papers)
- Support for advanced parallel/high-performance computing (papers)

 45

 **CCA**
Common Component Architecture

The Proxy Component Pattern


- A “proxy” component can be inserted between the user and provider of a port without either being aware of it (non-invasive)
- Proxy can observe or act on all invocations of the interface
- Similar to aspect-oriented programming
- For many purposes, proxies can be generated automatically from SIDL definition of the port

Sample uses for proxy components:


- **Performance:** instrumentation of method calls
- **Debugging:** execution tracing, watching data values
- **Testing:** Capture/replay


Performance Monitoring with TAU


Before:



After:



 46

 **CCA**
Common Component Architecture


Component Lifecycle


Additional material in notes

- **Composition Phase (assembling application)**
 - Component is **instantiated** in framework
 - Component interfaces are **connected** appropriately
- **Execution Phase (running application)**
 - Code in components uses functions provided by another component
- **Decomposition Phase (termination of application)**
 - **Connections** between component interfaces may be **broken**
 - Component may be **destroyed**

In an application, individual components may be in different phases at different times

Steps may be under human or software control


 47


 **CCA**
Common Component Architecture


Supplementary material for handouts

Component's View of Using a Port

- User calls **getPort** to obtain (handle for) port from Services
 - Finally user code can "see" provider
- **Cast** port to expected type
 - OO programming concept
 - Insures type safety
 - Helps enforce declared interface
- **Call** methods on port
 - e.g.
 $\text{sum} = \text{sum} + \text{function} \rightarrow \text{evaluate}(x)$
- Call **releasePort**



 48

CCA
Common Component Architecture


Supplementary material for handouts


Dynamic Component Assemblies

- `gov.cca.BuilderService` allows **programmatic composition** of components
 - Components can be instantiated/destroyed, and connected/disconnected under program control

Sample uses of *BuilderService*:

- Python “**driver**” **script** which can assemble and control an application
 - i.e. MCMD climate model
- **Adaptation** to changing conditions
 - Swap components in and out to give better performance, numerical accuracy, convergence rates, etc.
 - TASCs project “**Computational Quality of Service**” activity

49

CCA
Common Component Architecture

Supplementary material for handouts

Supporting Emerging HPC Hardware Environments


- CCA does not dictate a specific approach to parallelism
- **Different approaches and tools can be provided via components and custom frameworks**


Examples...

- Uintah Computational Framework (Utah) provides a multi-threaded parallel execution environment based on task graphs
 - Specialized to certain structured adaptive mesh refinement problems
- TASCs developing services to manage groups of parallel components/tasks (MCMD)

Also...

- TASCs developing support for heterogeneous processor environments
 - FPGAs, GP-GPUs, accelerators, and other co-processors
 - Accelerator code encapsulated as components, interacting w/ components on primary processors
- Integration of fault tolerance capabilities with CCA under development (CIFS-TASCs collaboration)


50




CCA
Common Component Architecture

Is CCA for You?

- Much of what CCA does can be done without such tools *if* you have sufficient discipline
 - The larger a group, the harder it becomes to impose the necessary discipline
- Projects may use different aspects of the CCA
 - CCA is *not* monolithic – use what *you* need
 - Few projects use all features of the CCA... initially
- Evaluate what *your* project needs against CCA's capabilities
 - Other groups' criteria probably differ from yours
 - CCA continues to evolve, so earlier evaluations may be out of date
- Evaluate CCA against other ways of obtaining the desired capabilities
- Suggested starting point:
 - CCA tutorial "hands-on" exercises




51




CCA
Common Component Architecture

Take an Evolutionary Approach

- The CCA is designed to allow selective use and incremental adoption
- "SIDLize" interfaces incrementally
 - Start with essential interfaces
 - Remember, only externally exposed interfaces need to be Babelized
- Componentize at successively finer granularities
 - Start with whole application as one component
 - Basic feel for components without "ripping apart" your app.
 - Subdivide into finer-grain components as appropriate
 - Code reuse opportunities
 - Plans for code evolution




52


 **CCA**
Common Component Architecture

Supplementary material for handouts

View it as an Investment


- CCA is a long-term investment in your software
 - Like most software engineering approaches
- There is a cost to adopt
- The payback is longer term
- Remember Biggerstaff's Rule of Threes
 - Look at three systems, requires three times the effort, payback after third release

 53


 **CCA**
Common Component Architecture

The Primary Tools

CCA Forum Tutorial Working Group
[http://www.cca-forum.org/tutorials/
tutorial-wg@cca-forum.org](http://www.cca-forum.org/tutorials/tutorial-wg@cca-forum.org)


 This work is licensed under a [Creative Commons Attribution 2.5 License](https://creativecommons.org/licenses/by/2.5/)


54

 **CCA**
Common Component Architecture


The tools

- Bocca – project environment
- Ccaffeine – framework
- SIDL – interoperability language
- Babel – HPC language binding generator
- CCA – specification for components, frameworks

 55


 **CCA**
Common Component Architecture

Tools Module Overview



The diagram illustrates the Tools Module Overview. It features a large light blue oval containing two gray rectangular blocks labeled 'Component A' and 'Component B'. Between these components are four interlocking arrow shapes pointing in opposite directions. Above the oval, the text 'CCA/Frameworks' has two arrows pointing down to the interlocking shapes. Below the oval, the text 'CCA IDE' is in purple. Two arrows, labeled 'Babel' and 'Chasm', point upwards from below the oval towards the interlocking shapes. A purple arrow points from the left towards the text 'CCA Development Environment'.

- CCA Development Environment
 - Frameworks
 - Language interoperability tools

 56



Bocca Development Environment

- Provides a text-based, portable environment
 - Create or import SIDL and CCA based codes.
 - Automatic build system maintenance.
 - Easy to adopt or abandon while preserving code, build.
- No GUI required.
- Still in the early beta stage of development
 - Being tested by managing the tutorial source and a regression test suite.
 - Basis for common CCA toolkit installation.
 - Manages components in all Babel-supported languages (C, C++, Fortran 77, Fortran 90, Java, Python).



57




Bocca Creates Skeletons for CCA

- Including **ports** and **interfaces**
 - Give the SIDL name and an empty port or interface is created.
- Including **components** and **classes**
 - Give the name and an empty component or class is created.
 - Some extra options: the component uses/provides ports, implemented interfaces or extended classes
- Including **build system**
 - For all ports/components in the project
 - Implemented in any CCA supported language
- Create applications with Ccaffeine GUI (today)
- Including **application** composition (coming soon)



58

 **CCA**
Common Component Architecture

Bocca Example


```
# create an empty but buildable CCA skeleton
bocca create project myproj
cd myproj
./configure


bocca create port myJob
bocca create component myWorker --provides=myJob:job1

# fill in public functionality
bocca edit port myJob


# fill in implementation
bocca edit component -i myWorker

# compile application
make
```

 59


 **CCA**
Common Component Architecture


Tools Module Overview



The diagram illustrates the Tools Module Overview. It shows two components, Component A and Component B, represented as gray rectangles. Between them are two orange arrows pointing from Component A to Component B, representing data flow. Above these arrows, the text 'CCA/Frameworks' is written in orange, with two orange arrows pointing down to the data flow arrows. Below the components, there are two gray rectangles labeled 'Babel' and 'Chasm'. Arrows point from Babel to Component A and from Chasm to Component B. A larger gray rectangle labeled 'CCA IDE' encompasses the entire scene, including Component A, Component B, Babel, Chasm, and the CCA/Frameworks text.

- CCA Interactive Development Environment
- ➔ • Frameworks
- Language interoperability tools


 60


 **CCA**
Common Component Architecture

Ccaffeine is a *Direct-Connect*, Parallel-Friendly Framework

- Supports SIDL/Babel components
 - Conforms to latest CCA specification (0.8)
 - Also supports legacy CCA specification (0.5)
 - Any C++ allowed with C and Fortran by C++ wrappers
- Provides command-line and GUI for composition
 - Scripting supports batch mode for SPMD
 - MPMD/SPMD custom drivers in any Babel language


Supported on Linux, AIX, OSX and is portable to modern UNIXes.


 61


 **CCA**
Common Component Architecture

Optional Ccaffeine GUI

- Process
 - User input is broadcast SPMD-wise from Java.
 - Changes occur in GUI *after* the C++ framework replies.
 - If your components are computing, GUI changes are blocked.
- Components interact through *port connections*
 - *provide* ports *implement* class or subroutines "Provides" Port
 - *use* ports *call* methods or subroutines in the port. "Uses" Port
 - Links denote caller/callee relationship *not* data flow




 62



Common Component Architecture

User Connects Ports

- Can only connect *uses* & *provides*
 - Not uses/uses
 - Not provides/provides
- Ports connected by type not name
 - Port names **must be unique** within a component
 - Types **must match** across components
- Framework puts info about *provider* of port into *using component's* Services object




connect
Driver
IntegratorPort
MonteCarloIntegrator
IntegratorPort

connect
MonteCarloIntegrator
FunctionPort
LinearFunction
FunctionPort

...

63




Common Component Architecture

Supplementary material for handouts

Building an Application (1 of 2)

- Components are code + XML metadata
- Using metadata, a **Palette** of available components is constructed.
- Components are instantiated by user action (i.e. by dragging from **Palette** into **Arena**).
- Framework calls component's **constructor**, then **setServices**



create
Driver
Driver

create
LinearFunction
LinearFunction

create
MonteCarloIntegrator
MonteCarloIntegrator


64

CCA
Common Component Architecture

Supplementary material for handouts

Building an Application (2 of 2)

1. Click **Configure** port to start parameter input dialogue.
2. For each connection:
click a **uses** port then click a **provides** port to establish a connection.
3. Click **Go** port to start the application.




Right-clicking a connection line breaks the connection -- enabling component substitution.

65

CCA
Common Component Architecture

Tools Module Overview



- CCA Interactive Development Environment
- Frameworks
- Language interoperability tools

66

CCA
Common Component Architecture

SIDL Facilitates *Scientific* Programming Language Interoperability

- Programming language-neutral interface descriptions
- Native support for basic scientific data types
 - Complex numbers
 - Multi-dimensional, multi-strided arrays
- Automatic object-oriented wrapper generation
- Usable standalone or in CCA environment

Supported on Linux, AIX, works on OSX, catamount;
C (ANSI C), C++ (GCC), F77 (g77, Sun f77), F90 (Intel, Lahey, GNU, Absoft, PGI), Java (1.4)

67


CCA
Common Component Architecture

Supplementary material for handouts

Clients in any supported language can access components in any other language


IOR = Intermediate Object Representation


68

 **CCA**
Common Component Architecture

The SIDL File that defines the “greetings.English” type

```
① package greetings version 1.0 {  
③   interface Hello {  
⑤     void setName( in string name );  
     string sayIt ( );  
   }  
⑥   class English implements-all Hello { }  
}
```


 69


 **CCA**
Common Component Architecture

Supplementary material for handouts

Handout Material: Code Notes

- ① Packages contain user-defined types and are used to reduce naming collisions. Packages can be nested.
- ② Packages can be versioned. User defined types must be nested inside a versioned package and gain the same version number as the innermost versioned package
- ③ SIDL has a inheritance model similar to Java and Objective C. Classes can inherit multiple interfaces, but at most one implementation (other class).
- ④ An interface describes an API, but doesn't name the implementation.
- ⑤ Note that arguments have mode, type, and name. Mode can be one of “in”, “out”, and “inout”. These SIDL modes have slightly different semantics than Fortran90 “intents”.
- ⑥ This class generates English greetings. One could imagine a strategy for internationalization that uses the Hello interface everywhere, but loads in English, French, or whatever classes based on user's preference.

 70


 **CCA**
Common Component Architecture

..

Working Code: “Hello World” in F90 Using a Babel Type

```
① program helloclient
②   use greetings_english
③   use sidl_baseinterface
④   implicit none
⑤   type(greetings_english_t) :: obj
⑥   type(sidl_baseinterface_t) :: exc
⑦   character (len=80)          :: msg
⑧   character (len=20)          :: name
⑨   name='World'
⑩  call new( obj , exc )
⑪  call setName( obj , name, exc )
⑫  call sayIt( obj , msg, exc )
⑬  call deleteRef( obj , exc )
⑭  print *, msg
⑮ end program helloclient
```

71

 **CCA**
Common Component Architecture

Supplementary material for handouts

Handout Material: Code Notes

- ① Use statement for the greetings.English type
- ② Use statement for the sidl.BaseInterface type
- ③ Obj is a F90 derived type we get from the using statement, note the “_t” extension that prevents it from colliding with the using statement.
- ④ Exc is used to hold exceptions thrown by methods
- ⑤ In C/C++ examples, this variable would be initialized by a the command-line variable “argv[1]”, but its trickier to do portably in F90 and too long, so I just initialize the name to “World”.
- ⑥ Obj is not yet initialized. The Babel idiom in F90 is to call new() to initialize the Babel type. In other languages its _create(). NOTE: good code would add error checking.
- ⑦ setName() puts data into the obj. It sets its state.
- ⑧ sayIt() returns the entire greeting including the aforementioned name.
- ⑨ deleteRef() is a subroutine that all Babel types inherit from a parent class. All Babel objects are reference counted. When there are no more outstanding references, the object is told to clean up after itself.

72

CCA
Common Component Architecture

Working Code: “Hello World” in F90 Using a Babel Type

```
program helIoclient
  use greetings_English
  use si dl _BaseInterface
  implicit none
  type(greetings_English_t) :: obj
  type(si dl _BaseInterface_t) :: exc
  character (len=80) :: msg
  character (len=20) :: name
  name=' World'
  call new( obj , exc )
  call setName( obj , name, exc )
  call sayI t( obj , msg, exc )
  call deleteRef( obj , exc )
  print *, msg
end program helIoclient
```

Looks like a native F90 derived type

These subroutines were specified in the SIDL.

Other basic subroutines are “built in” to all Babel types.

73

CCA
Common Component Architecture

Question: What language is “obj” really implemented in?

```
program helIoclient
  use greetings_English
  use si dl _BaseInterface
  implicit none
  type(greetings_English_t) :: obj
  type(si dl _BaseInterface_t) :: exc
  character (len=80) :: msg
  character (len=20) :: name
  name=' World'
  call new( obj , exc )
  call setName( obj , name, exc )
  call sayI t( obj , msg, exc )
  call deleteRef( obj , exc )
  print *, msg
end program helIoclient
```


Answer: Can't Know!

With Babel, it could be C, C++, Python, Java, Fortran77, or Fortran90/95

In fact, it could change on different runs without recompiling this code!

74

CCA uses Babel for high-performance n-way language interoperability




Each one of these red lines, is potentially a bridge between two languages. No telling which language your component will be connected to when you write it.

75

Implementation Details Must be Filled in Between Splicer Blocks

```
namespace greetings {  
class EnglishImpl {  
private:  
    // DO-NOT-DELETE splicer.begin(greetings.EnglishImpl)  
    string d_name;  
    // DO-NOT-DELETE splicer.end(greetings.EnglishImpl)  
  
string  
greetings::EnglishImpl::sayIt()  
throw ()  
{  
    // DO-NOT-DELETE splicer.begin(greetings.EnglishImpl::sayIt)  
    string msg("Hello ");  
    return msg + d_name + "!";  
    // DO-NOT-DELETE splicer.end(greetings.EnglishImpl::sayIt)  
}
```

76




CCA
Common Component Architecture


CCA uses SIDL to specify APIs and Type Hierarchy for Frameworks, Services, Components, & Ports

- A CCA framework must
 - implement gov. cca. AbstractFramework,
 - provide a gov. cca. ports. Bui l derServi ce,
 - etc.
- A CCA port must
 - be a SIDL interface extending gov. cca. Port
- A CCA component must
 - be a SIDL class implementing gov. cca. Component

The CCA Specification is a SIDL file.



77




CCA
Common Component Architecture


How to write a Babelized CCA Component (1/2)

1. Define “Ports” in SIDL
 - CCA Port =
 - a SIDL Interface
 - extends gov.cca.Port

```
package functions version 1.0 {  
    interface Function extends gov.cca.Port {  
        double evaluate( in double x );  
    }  
}
```



78



CCA
Common Component Architecture

How to write a Babelized CCA Component (2/2)


2. Define “Components” that implement those Ports

- CCA Component =
 - SIDL Class
 - implements gov.cca.Component (and any provided ports)

```
class LinearFunction implements functions.Function,  
                                gov.cca.Component {  
    double evaluate( in double x );  
    void setServices( in cca.Services svcs );  
}
```

```
class LinearFunction implements-all  
    functions.Function, gov.cca.Component { }
```


79




CCA
Common Component Architecture

Using bocca: Approaches & Experience

CCA Forum Tutorial Working Group
[http://www.cca-forum.org/tutorials/
tutorial-wg@cca-forum.org](http://www.cca-forum.org/tutorials/tutorial-wg@cca-forum.org)

 This work is licensed under a [Creative Commons Attribution 2.5 License](https://creativecommons.org/licenses/by/2.5/)

80




CCA
Common Component Architecture


Components in the Small: Impacts within a Project

Benefits include:

- Rapid [testing, debugging, and benchmarking](#)
- Wrapped legacy portions [need not be reimplemented or reverified](#)
- Interface change effects across components are clear and usually automatically found by compilers if overlooked
- Object-orientation made simpler for C and Fortran
- Support for [implementation-hiding](#) discipline
- Coordination of independent workers while [separating concerns](#) (scientific specialty, development style, etc.)
- Work of [transient contributors](#) remains as well-defined, lasting components



81



CCA
Common Component Architecture


Components in the Large: Connecting Multiple Projects

Benefits include:


- SIDL can be used to facilitate the interface consensus processes
- Different sub-projects do not have to agree on one implementation language
- Developers who never meet in person have an excellent chance of code integration working on the first try

Costs include:

- Consensus can be expensive to obtain
- Writing code for others to use is more difficult than writing it just for yourself





82

 **CCA**
Common Component Architecture

Application Decomposition Strategies


- Conceptually decompose the application into
 - cutting-edge areas (*less stable*) *and*
 - areas that can employ existing component-based libraries (*more stable*)
- Decompose each area into components for
 - physics
 - mathematics
 - data managementas dictated by the application;
sketch a typical component layout
- Many components will encapsulate *algorithmic logic only*, with little or no private data
- Most HPC applications will have a *central data abstraction* that provides data memory management and parallel communication
- In a multilanguage application, all *I/O may need to be isolated* into components written in a single common language (file based I/O should not be affected)
- Component boundaries (and port interfaces) may be set to *isolate proprietary code or difficult contributors*


 83

 **CCA**
Common Component Architecture

Interface Design: Technical Factors


- Do we make a single large port look like the underlying library or divide functions into groups on separate ports?
- Should a function with many optional arguments be split into several alternative functions with simpler usage?
- Do we make the ports more general than the existing code?
- Do we require the ports to work across languages?
Across networks?
 - If not, gains in efficiency or coding ease might be had
 - If so, memory management and I/O challenges may arise


 84

 **CCA**
Common Component Architecture

Interface Design: Social Factors (Defining Ports to Wrap Existing Code)

- Will the port hide just one implementation, or will there need to be plug compatibility with other implementations? From other teams?
- Who defines the interface and maintains it?
 1. Project dictator? (*Fast...*)
 2. The owner of the legacy functionality? (*Slow, if not you...*)
 3. A standards committee? (*Really slow...*)
- How many iterations of redefining the ports will the customers tolerate?


 85


 **CCA**
Common Component Architecture

Supplementary material for handouts

Implementation Issues in Wrapping

- Do we split large libraries into several components?
 - Splitting is difficult to do if global variables or common blocks are widely used.
- Do we expect more than one implementation instance of a port in a single run-time?
 - If not, interface contracts may include global side effects
- Do we integrate the wrapper code in the existing code's development and build processes?
 - If not, how do we ensure build consistency and on-going wrapper support?
- Code bases with large interfaces need automated wrapping tools
 - E.g., [see Chasm info in the Tools module](#) of the tutorial


 86


 **CCA**
Common Component Architecture

Supplementary material for handouts

Benefits of Wrapping Code Using CCA

- Setting a language-neutral interface definition (SIDL) can greatly clarify design discussions
- Provides a chance to reorganize the interface and hide globals
- Allows testing of alternate versions if doing performance studies
- Allows easy “experimentation” with new algorithms
- Software discipline is enforced, not optional
- Implementation decisions (to split libraries, etc) can be easily revised over time if interfaces remain constant (possibly with the addition of new interfaces)


 87


 **CCA**
Common Component Architecture

Supplementary material for handouts

Interface Design for *New Code*


- Write SIDL for each connection (port) in the sketched component layout
- If two ports must always be used together, consider merging them
- Review SIDL drafts for near-duplication of ports
- Avoid creating interface contracts that require using hidden global data
- Consider exporting tuning and/or configuration parameter inputs as a port
- All the design issues from wrapping existing code apply, also
- ***Interfaces will change.***


 88

 CCA
Common Component Architecture

Recommended Implementation Patterns


- Expect to decompose initial components further as work progresses and requirements expand
- Build systems (i.e. `make`) should be kept as simple as possible
 - Keep a subdirectory for port definitions and any implementation-independent glue code derived from the ports
 - Keep each component (and any wrapped code) in its own subdirectory
 - Keep application-wide flags in a configure script or an include file common to all components and ports
 - Consistency is key. Extract build flags from `cca-spec-babel-config` and if possible compile & link with `babel-libtool`

 89


 CCA
Common Component Architecture


Case Study: Combustion Modeling

- Computational Facility for Reacting Flow Science (CFRFS)
 - <http://cfrfs.ca.sandia.gov>
 - Funded via SciDAC initiative (PI: H. Najm)
- Focus: A toolkit to perform simulations of lab-sized unsteady flames
 - Solve the Navier-Stokes w/detailed chemistry
 - Various mechanisms up to ~50 species, 300 reactions
- Consequently:
 - Disparity of **length scales** :
 - use structured adaptively refined meshes
 - Disparity of **time scales** (transport versus chemistry) :
 - use an operator-split construction and solve chemistry implicitly
 - adaptive chemistry: use **computational singular perturbation** to find and follow low dimensional chemical manifolds



J. Ray, S. Lefantzi, J. Lee, C. Kennedy, W. Ashurst, K. Smith, M. Liu, N. Trebon, J. Ortega, C. Safta, S. Chandra, H. Johansson


 90




CCA
Common Component Architecture

Why Use CCA in the CFRFS Toolkit?

- Separate clearly the physics models, numerical algorithms, and the “CS” parts of the toolkit
 - Strictly functional!
- Realize the separation in software
- Tame *software* complexity
- Separate contributions by transient contributors
 - Form the bulk of the developers
- Create “chunks” of well-defined functionality that can be developed by experts (usually numerical analysts and combustion researchers)




91




CCA
Common Component Architecture

Design Principles of the Toolkit / 1

- **Principal Aim: Reduce software complexity**
 - We can deal with the rest
- Functional decomposition into components
 - “Data Object” and Mesh components
 - (Large) set of numerical algorithmic components (integrators, linear/nonlinear solvers, etc.)
 - (Large) set of physical models components (gas-phase combustion chemistry, thermodynamics, fluid dynamic quantities, e.g. viscous stress tensor)
 - Handful of adaptors




92

 **CCA**
Common Component Architecture


Design Principles of the Toolkit / 2


- Decomposition reflected in the port design and implementation
 - Most re-implemented port is the one that exchanges a rectangular sub-domain's data for processing by components
- Sparse connectivity between components
 - i.e., components communicate with a few others
 - Large apps (component assemblies) are composed by assembling smaller, largely independent sub-assemblies
 - Sub-assemblies usually deal with a certain physics
 - Intuitive way to assemble a *multiphysics* code




Level 1

Level 0 / Coarse Mesh

 93

 **CCA**
Common Component Architecture

The Code





Transport subassembly

Diffusion coefficients

Chemistry reaction subassembly


Separate component subsystems for transport (black) and for reaction (orange) in a reaction-diffusion code. They two are coupled at a relatively high level.

 94


 **CCA**
Common Component Architecture


CFRFS Toolkit Status

- Started in 2001
- 100+ components today, all peers, independent, mixed and matched for combustion and shock hydrodynamics
- 8 external libraries
- Contributors: 13 in all, including 3 summer students
- Only 3 of the 13 contributors are at SNL today




A Fitzhugh-Nagumo equation being solved on a block-structured adaptively refined mesh. The top image illustrates Runge phenomena at coarse-fine interfaces (dashed ovals) when using high-order schemes (6th order interpolations with 4th order discretizations). Filtering them with an 8th order filter removes them (bottom).



 95



 **CCA**
Common Component Architecture



Has the Toolkit Approach Helped Tame Software Complexity?


- How has the code evolved?
 - How often have new ports been added?
 - How many rewrites have been done?
- How large are the components?
- How many ports do they have?
 - How large are the ports?
- How many ports exist?
 - i.e., Is the design general enough to support many implementations?
- What is the connectivity of components in application codes?

 96









 **CCA**
Common Component Architecture


Scientific Productivity

- Conventional Measures (May 2008)
 - 5 journal papers in CFD/Numerics
 - 4 software-oriented journal papers, 1 book chapter
 - Over 15 conference papers, including best paper award
 - Over 60 presentations
 - 1 MS and 2 PhD theses
 - 6 test applications
 - See papers at: <http://cfrfs.ca.sandia.gov>
- Unconventional Measures
 - Did the toolkit spawn new research in app-focused CS (e.g., performance evaluation/enhancement/modeling?)
 - Can the design accommodate software which were themselves designed to be *frameworks* and *not components*?




H₂O₂ chemical subspecies profile and associated AMR mesh


 103

 **CCA**
Common Component Architecture

Using CCA: Summary

- Review of guidelines for developing high-performance scientific components (both new code and wrappers for existing code)
- CCA is an enabling technology for scientific applications
 - Has enabled mathematicians, chemists, combustion scientists, and computer scientists to contribute new strategies that are shrink-wrapped for easy re-use
 - Apart from **science research**, also spawned **new research directions in CS**
 - Has enabled research scientists to investigate unconventional approaches, for example multilevel parallelism and dynamic adaptivity
- For more info on the CCA applications/case studies, see:
 - Chemistry: <http://www.cca-forum.org/~cca-chem>
 - Combustion: <http://cfrfs.ca.sandia.gov>
- **Different facets of CCA components may be useful within different projects ... What are *your* needs and priorities?**


 104




CCA
Common Component Architecture

A Few Notes in Closing

CCA Forum Tutorial Working Group
<http://www.cca-forum.org/tutorials/>
tutorial-wg@cca-forum.org

 This work is licensed under a [Creative Commons Attribution 2.5 License](https://creativecommons.org/licenses/by/2.5/)


105




CCA
Common Component Architecture

Resources: Its All Online


- Information about all CCA tutorials, past, present, and future:
<http://www.cca-forum.org/tutorials/>
- Specifically...
 - Latest versions of hands-on materials and code:
<http://www.cca-forum.org/tutorials/#sources>
 - Hands-On designed for self-study as well as use in an organized tutorial
 - Should work on most Linux distributions, less tested on other unixen
 - Still evolving, so please contact us if you have questions or problems
 - Archives of all tutorial presentations:
<http://www.cca-forum.org/tutorials/archives/>
- Questions...
help@cca-forum.org or cca-tutorial@cca-forum.org


 106

 **CCA**
Common Component Architecture

Getting Help


- We want to help insure you have a good experience with CCA, so let us know if you're having problems!
- Tutorial or "start-up" questions
 - help@cca-forum.org or cca-tutorial@cca-forum.org
- Problems with specific tools
 - *check documentation for updated contact info*
 - cca-tools bundle (includes Chasm, Babel, Ccaffeine): [Rob Armstrong](mailto:RobArmstrong@cca-forum.org), cca-tools@cca-forum.org
 - Bocca: bocca-dev@cca-forum.org
 - Chasm: [Craig Rasmussen](mailto:CraigRasmussen@lanl.gov), crasmussen@lanl.gov
 - Babel: babel-users@lanl.gov
 - Ccaffeine: ccafe-users@cca-forum.org
- General questions, or not sure who to ask?
 - help@cca-forum.org


 107

 **CCA**
Common Component Architecture

CCA is Interactive

- Collectively, CCA developers and users span a broad range of scientific interests.
 - There's a good chance we can put you in touch with others with relevant experience with CCA
- CCA Forum Quarterly Meetings
 - Meet many CCA developers and users
 - <http://www.cca-forum.org/meetings/>
- "Coding Camps"
 - Bring together CCA users & developers for a concentrated session of coding
 - Held as needed, typically 3-5 days
 - May focus on a particular theme, but generally open to all interested participants
 - If you're interested in having one, *speack up* (to individuals or cca-forum@cca-forum.org)
- Visits, Internships, etc.


 108


 **CCA**
Common Component Architecture

Supplementary material for handouts

Acknowledgements: Tutorial Working Group

- **Computer facilities** provided by NTNU CS.
- **People:** Benjamin A. Allan, Rob Armstrong, David E. Bernholdt, Randy Bramley, Tamara L. Dahlgren, Lori Freitag Diachin, Tony Drummond, Wael Elwasif, Tom Epperly, Madhusudhan Govindaraju, Ragib Hasan, Jim Kohl, Gary Kumfert, Lois Curfman McInnes, Alan Morris, Stefan Muszala, Boyana Norris, Craig Rasmussen, Jaideep Ray, Sameer Shende
- **Institutions:** ANL, Binghamton U, Indiana U, JPL, LANL, LLNL, NASA/Goddard, ORNL, SNL, U Illinois, U Oregon


 109


 **CCA**
Common Component Architecture

Supplementary material for handouts

Special Thanks: Bocca Development Team

- Ben Allan, SNL
- Rob Armstrong, SNL
- Wael Elwasif, ORNL
- Boyana Norris, ANL

 110


 **CCA**
Common Component Architecture


Supplementary material for handouts

Acknowledgements: The CCA

- **ANL** –Steve Benson, Jay Larson, Ray Loy, Lois Curfman McInnes, Boyana Norris, Everest Ong, Jason Sarich...
- **Binghamton University** - Madhu Govindaraju, Michael Lewis, ...
- **Indiana University** - Randall Bramley, Dennis Gannon, ...
- **JPL** – Dan Katz, ...
- **LANL** - Craig Rasmussen, Matt Sotille, ...
- **LLNL** – Tammy Dahlgren, Lori Freitag Diachin, Tom Epperly, Scott Kohn, Gary Kurfert, ...
- **NASA/Goddard** – Shujia Zhou
- **ORNL** - David Bernholdt, Wael Elwasif, Jim Kohl, Torsten Wilde, ...
- **PNNL** - Jarek Nieplocha, Theresa Windus, ...
- **SNL** - Rob Armstrong, Ben Allan, Lori Freitag Diachin, Curt Janssen, Jaideep Ray, ...
- **Tech-X Corp.** – Johan Carlsson, Svetlana Shasharina, Ovsei Volberg, Nanbor Wang
- **University of Oregon** – Allen Malony, Sameer Shende, ...
- **University of Utah** - Steve Parker, ...

and many more... without whom we wouldn't have much to talk about!


 111

 **CCA**
Common Component Architecture

Thank You!

Thanks for attending this tutorial

We welcome feedback and questions

 112