


**CCA**
Common Component Architecture


Welcome to the Common Component Architecture Tutorial

SC2005 Tutorial M02
14 November 2005

CCA Forum Tutorial Working Group
[http://www.cca-forum.org/tutorials/
tutorial-wg@cca-forum.org](http://www.cca-forum.org/tutorials/tutorial-wg@cca-forum.org)


 This work is licensed under a [Creative Commons Attribution 2.5 License](http://creativecommons.org/licenses/by/2.5/)

1


**CCA**
Common Component Architecture

Licensing Information

- This tutorial is distributed under the [Creative Commons Attribution 2.5 License](http://creativecommons.org/licenses/by/2.5/)
 - <http://creativecommons.org/licenses/by/2.5/>
- In summary, **you are free:**
 - to copy, distribute, display, and perform the work
 - to make derivative works
 - to make commercial use of the work
- **Under the following conditions:**
 - **Attribution.** You must attribute the work in the manner specified by the author or licensor.
- For any reuse or distribution, you must make clear to others the license terms of this work.
- Any of these conditions can be waived if you get permission from the copyright holder.
- **Your fair use and other rights are in no way affected by the above.**
- **Requested reference:**
 - CCA Forum Tutorial Working Group, Common Component Architecture Tutorial, 2005, <http://www.cca-forum.org/tutorials/>



2

 CCA Common Component Architecture			
Agenda & Table of Contents			
Time	Title	Slide No.	Presenter
8:30-8:35am	Welcome	1	David Bernholdt, ORNL
8:35-9:30am	What can Component Technology do for Scientific Computing	5	Boyana Norris, ANL
	An Intro. to Components & the CCA	16	Boyana Norris, ANL
9:30-10:00am	CCA Tools	70	Ben Allan, SNL
10:00-10:30am Lunch			
10:30-11:10am	Language Interoperable CCA Components with Babel	113	Gary Kumfert, LLNL
11:10-11:55am	Using CCA: Approaches & Experience	136	David Bernholdt, ORNL
11:55am-12:00n	Closing	186	David Bernholdt, ORNL
12:00-1:30pm Break			
1:30-3:00pm	Hands-On	Hands-On Guide	All
3:00-3:30pm Break			
3:30-5:00pm	Hands-On (continued)		

 CCA Common Component Architecture	
<h2>Who We Are: The Common Component Architecture (CCA) Forum</h2>	
<ul style="list-style-type: none">• Combination of standards body and user group for the CCA• Define Specifications for High-Performance Scientific Components & Frameworks• Promote and Facilitate Development of Domain-Specific Common Interfaces• Goal: Interoperability between components developed by different expert teams across different institutions• Quarterly Meetings, Open membership...	
<p>Mailing List: cca-forum@cca-forum.org</p> <p>http://www.cca-forum.org/</p>	



CCA
Common Component Architecture

What Can Component Technology do for Scientific Computing?

CCA Forum Tutorial Working Group

[http://www.cca-forum.org/tutorials/
tutorial-wg](http://www.cca-forum.org/tutorials/tutorial-wg) [@cca-forum.org](mailto:cca-forum.org)



This work is licensed under a [Creative Commons Attribution 2.5 License](http://creativecommons.org/licenses/by/2.5/)

5



CCA
Common Component Architecture

Managing Code Complexity

Some Common Situations:

- Your code is so large and complex it has become fragile and hard to keep running
- You have a simple code, and you want to extend its capabilities
 - rationally
- You want to develop a computational “toolkit”
 - Many modules that can be assembled in different ways to perform different scientific calculations
 - Gives users w/o programming experience access to a flexible tool for simulation
 - Gives users w/o HPC experience access to HPC-ready software

How CCA Can Help:

- Components help you think about software in manageable chunks that interact only in well-defined ways
- Components provide a “plug-and-play” environment that allows easy, flexible application assembly




6



Example: Computational Facility for Reacting Flow Science (CFRFS)

- A toolkit to perform simulations of unsteady flames
- Solve the Navier-Stokes with detailed chemistry
 - Various mechanisms up to ~50 species, 300 reactions
 - Structured adaptive mesh refinement
- CFRFS today:
 - 61 components
 - 7 external libraries
 - 9 contributors



“Wiring diagram” for a typical CFRFS simulation, utilizing 12 components.

CCA tools used: Ccaffeine, and ccafe-gui

Languages: C, C++, F77

7



Helping Groups Work with Software

Some Common Situations:

- Many (geographically distributed) developers creating a large software system
 - Hard to coordinate, different parts of the software don't work together as required
- Groups of developers with different specialties
- Forming communities to standardize interfaces or share code

How CCA Can Help:


- Components are natural units for
 - Expressing software architecture
 - Individuals or small groups to develop
 - Encapsulating particular expertise
- Some component models (including CCA) provide tools to help you think about the *interface* separately from the *implementation*

8



Example: Quantum Chemistry

- Integrated state-of-the-art optimization technology into two quantum chemistry packages to explore effectiveness in chemistry applications
- Geographically distributed expertise:
 - California - chemistry
 - Illinois - optimization
 - Washington – chemistry, parallel data management
- Effective collaboration with minimal face-to-face interaction



Schematic of CCA-based molecular structure determination quantum chemistry application.

Components based on: MPQC, NWChem (quantum chem.), TAO (optimization), Global Arrays, PETSc (parallel linear algebra)

CCA tools used: Babel, Ccaffeine, and ccafe-gui

Languages: C, C++, F77, Python

9



Example: TSTT Unstructured Mesh Tool Interoperability

- Common interface for unstructured mesh geometry and topology
 - 7 libraries: FMDB, Frontier, GRUMMP, Mesquite, MOAB, NWGrid, Overture
 - 6 institutions: ANL, BNL/SUNY-Stony Brook, LLNL, PNNL, RPI, SNL
- Reduces need for N^2 pairwise interfaces to just N





Illustration of geometry domain hierarchy used in TSTT mesh interface.

CCA tools used: Babel (SIDL), Chasm

Library languages: C, C++, F77, F90

10



CCA
Common Component Architecture


Language Interoperability


Some Common Situations:

- Need to use existing code or libraries written in multiple languages in the same application?
- Want to allow others to access your library from multiple languages?
- Technical or sociological reasons for wanting to use multiple languages in your application?


How CCA Can Help:

- Some component models (including CCA) allow transparent mixing of languages
- Babel (CCA's language interop. tool) can be used separately from other component concepts


11




CCA
Common Component Architecture



hypre
high performance preconditioners

Examples



hypre

- High performance preconditioners and linear solvers
- Library written in C
- Babel-generated object-oriented interfaces provided in C, C++, Fortran


LAPACK07

- Update to LAPACK linear algebra library
 - To be released 2007
 - Library written in F77, F95
- Will use Babel-generated interfaces for: C, C++, F77, F95, Java, Python
- Possibly also ScaLAPACK (distributed version)

"I implemented a Babel-based interface for the hypre library of linear equation solvers. The Babel interface was straightforward to write and gave us interfaces to several languages for less effort than it would take to interface to a single language."

-- Jeff Painter, LLNL. 2 June 2003

CCA tools used: Babel, Chasm


12



Common Component Architecture

Coupling Codes

Some Common Situations:

- Your application makes use of numerous third-party libraries
 - Some of which interact (version dependencies)
- You want to develop a simulation in which your code is coupled with others
 - They weren't designed with this coupling in mind
 - They must remain usable separately too
 - They are all under continual development, individually
 - They're all parallel and need to exchange data frequently

How CCA Can Help:

- Components are isolated from one another
 - Interactions via well-defined interfaces
 - An application can include multiple versions of a component
- Components can be composed flexibly, hierarchically
 - Standalone application as one assembly, coupled simulation as another
- CCA can be used in SPMD, MPMD, and distributed styles of parallel computing
- CCA is developing technology to facilitate data and functional coupling of parallel applications

13




Common Component Architecture

Example: Global Climate Modeling and the Model Coupling Toolkit (MCT)



- MCT is the basis for Community Climate System Model (CCSM3.0) coupler (cpl6)
- Computes interfacial fluxes and manages redistribution of data among parallel processes
- Written in F90, Babel-generated bindings for C++, Python
- **CCA tools used:** Babel, Chasm



Schematic of CCSM showing coupler managing data exchanges between atmosphere, sea ice, ocean, and land models.
(From <http://www.cesm.ucar.edu/models/ccsm3.0/cpl6/>)


14



CCA
Common Component Architecture

Example: Integrated Fusion Simulation

- Proof-of-principle of using CCA for integrated whole-device modeling needed for the ITER fusion reactor
- Couples radio frequency (RF) heating of plasma with transport modeling
- Coarse-grain encapsulation of pre-existing programs
- Follow-on plans for RF, transport, and magneto-hydrodynamics



"Wiring diagram" for integrated fusion simulation.

Components based on: AORSA, Houlberg's transport library

New components: Driver, State

CCA tools used: Babel, Chasm, Ccaffeine, ccafe-gui

Languages: C++, F90, Python

15



CCA
Common Component Architecture

An Introduction to Components and the Common Component Architecture

CCA Forum Tutorial Working Group

<http://www.cca-forum.org/tutorials/>
tutorial-wg@cca-forum.org



This work is licensed under a [Creative Commons Attribution 2.5 License](https://creativecommons.org/licenses/by/2.5/)

16



Goals of This Module

- Introduce basic **concepts and vocabulary** of component-based software engineering and the CCA
- Highlight the special **demands of high-performance scientific computing** on component environments
- Give you sufficient **understanding** of the CCA to begin **evaluating** whether it would be useful to you



What are Components?

- No universally accepted definition in computer science research, but key features include...
- A unit of software development/deployment/reuse
 - i.e. has **interesting functionality**
 - Ideally, functionality someone else might be able to **(re)use**
 - Can be **developed independently** of other components
- Interacts with the outside world only through well-defined interfaces
 - **Implementation is opaque** to the outside world
- Can be composed with other components
 - “Plug and play” model to build applications
 - **Composition based on interfaces**





What is a Component Architecture?

- A set of **standards** that allows:
 - Multiple groups to write units of software (**components**)...
 - And have confidence that their components will **work with other components** written in the same architecture
- These standards **define**...
 - The rights and responsibilities of a **component**
 - How components express their **interfaces**
 - The environment in which components are composed to form an application and executed (**framework**)
 - The rights and responsibilities of the framework




19







A Simple Example: Numerical Integration Components


*Interoperable components
(provide same interfaces)*



20








CCA
Common Component Architecture

Comparison of Application Development Approaches

Characteristics	Monolithic Simulation Code	Simulation Frameworks	Library -Based	Component -Based
Support for specific workflows and information flows	High	High	Low	Low
Flexibility w.r.t. workflow and information flow	Low	Medium	High	High
User-level extensibility	Low	Medium	High	High
Ease of incorporation of outside code (code reuse)	Low	Low-Medium	Medium	High
Ease of experimentation	Low	Medium	Medium	High
Amount of new code required to create a complete simulation	Low	Medium	High	High (reuse can reduce)
Breadth of current “ecosystem” for “plugins”	Low	Medium	High	Low (but growing)
Ease of coupling simulations	Low	Low	Medium	High

25



CCA
Common Component Architecture

Be Aware: “Framework” Describes Many Things

- Currently in scientific computing, this term means different things to different people
- **Basic software composition environment**
 - Examples: CCA, CORBA Component Model, ...
- An environment facilitating development of applications in **a particular scientific domain** (i.e. fusion, computational chemistry, ...)
 - Example: Earth System Modeling Framework, <http://www.esmf.ucar.edu>
 - Example: Computational Facility for Reacting Flow Science, <http://cfrfs.ca.sandia.gov>
- An environment for managing complex **workflows** needed to carry out calculations
 - Example: Kepler: <http://kepler-project.org>
- **Integrated data analysis and visualization environments** (IDAVEs)
- Lines are often fuzzy
 - Example: Cactus, <http://www.cactuscode.org>
- Others types of frameworks *could* be built based on a **basic software composition environment**

26



Relationships: Components, Objects, and Libraries

- Components are typically discussed as **objects** or collections of objects
 - **Interfaces** generally designed in **OO** terms, but...
 - Component **internals need not be OO**
 - **OO languages are not required**
- Component environments can **enforce** the use of **published interfaces** (prevent access to internals)
 - Libraries can not
- It is possible to load **several instances** (versions) of a component in a single application
 - Impossible with libraries
- Components *must* include some code to **interface with the framework/component environment**
 - Libraries and objects do not



27



What is the CCA?

- Component-based software engineering has been developed in other areas of computing
 - Especially business and internet
 - Examples: CORBA Component Model, COM, Enterprise JavaBeans
- Many of the needs are similar to those in HPC scientific computing
- But scientific computing imposes special requirements not common elsewhere
- **CCA is a component environment specially designed to meet the needs of HPC scientific computing**



28



Special Needs of Scientific HPC

- Support for legacy software
 - How much **change** required for component environment?
- Performance is important
 - What **overheads** are imposed by the component environment?
- Both parallel and distributed computing are important
 - What approaches does the component model support?
 - What **constraints** are imposed?
 - What are the **performance costs**?
- Support for **languages, data types, and platforms**
 - Fortran?
 - Complex numbers? Arrays? (as first-class objects)
 - Is it available on my parallel computer?



29



CCA: Concept and Practice


- In the following slides, we explain important **concepts** of component-based software from the CCA perspective
- We also sketch how these concepts are **manifested in code** (full details in the Hands-On)
- The **CCA Specification** is the mapping between concept and code
 - A standard established by the CCA Forum
 - Expressed in the Scientific Interface Definition Language (SIDL) for language neutrality (syntax similar to Java)
 - SIDL can be translated into bindings for specific programming languages using, e.g., the Babel language interoperability tool



30



CCA Concepts: Components




- A component encapsulates some computational functionality
- Components provide/use one or more interfaces
 - A component with no interfaces is formally okay, but isn't very interesting or useful
- In SIDL, a component is a **class** that **implements** (inherits from) **gov.cca.Component**
 - This means it must implement the **setServices** method to tell framework what ports this component will **provide** and **use**
 - **gov.cca.Component** is defined in the CCA specification

31




CCA Concepts: Ports



- Components interact through well-defined **interfaces**, or **ports**
 - A port expresses some **computational functionality**
 - In Fortran, a port is a bunch of subroutines or a **module**
 - In OO languages, a port is an **abstract class** or **interface**
- Ports and connections between them are a procedural (caller/callee) relationship, **not dataflow!**
 - e.g., *FunctionPort* could contain a method like **evaluate(in Arg, out Result)** with data flowing both ways

32

CCA Concepts: *Provides* and *Uses* Ports



The diagram shows two components: **MidpointIntegrator** and **NonlinearFunction**. **MidpointIntegrator** has two ports: **IntegratorPort** (blue) and **FunctionPort** (yellow). **NonlinearFunction** has one port: **FunctionPort** (blue). A red line connects the **FunctionPort** of **MidpointIntegrator** to the **FunctionPort** of **NonlinearFunction**, indicating a "Provides" relationship.

- Components may **provide** ports – **implement** the class or subroutines of the port (**"Provides" Port**)
 - *Providing* a port implies certain inheritance relationships between the component and the abstract definition of the interface (**more details shortly**)
 - A component can *provide* multiple ports
 - Different "views" of the same functionality, or
 - Related pieces of functionality
- Components may **use** ports – **call** methods or subroutines in the port (**"Uses" Port**)
 - *Use* of ports is just like calling a method normally except for a little additional work due to the "componentness" (**more details shortly**)
 - No inheritance relationship implied between caller and callee
 - A component can *use* multiple ports

33


Components and Ports (in UML)

Note that only the **provides** ports appear in the component's inheritance hierarchy. **Uses** ports do not.

A port must **extend** the CCA spec's port interface

A component must **implement** the CCA spec's component interface

A component must **implement** the port(s) it provides





The UML diagram shows the following elements and relationships:

- gov.cca.Component**: An interface with the method `setServices(services: gov.cca.Services)`. It is the base interface for all components.
- gov.cca.Port**: An interface that is the base for all ports.
- integrator.IntegratorPort**: A port interface that extends **gov.cca.Port** (indicated by a dashed arrow) and has the method `integrate(lowBound: double, upBound: double, count: int): double`.
- MidpointIntegrator**: A component class that implements **gov.cca.Component** (indicated by a solid arrow) and provides the **IntegratorPort** and **FunctionPort** (indicated by a dashed arrow).
- Midpoint**: A class that implements **integrator.IntegratorPort** (indicated by a solid arrow).

Class for Midpoint Integrator component

Key:
 ↑ = Inheritance
 ... = SIDL keywords

34





Where Do Ports Come From?


- Most ports are designed and implemented by **users** of CCA
 - May be specific to an application or used more broadly (i.e. community-wide)
- The **CCA specification** defines a *small* number of ports
 - Most are services CCA frameworks must provide for use by components
 - Some are intended for users to implement in their components, and have a special meaning recognized by the framework
 - *E.g. `gov.cca.ports.GoPort`* provides a very simple protocol to start execution of component-based applications

37



Interfaces are Key to Reuse and Interoperability of Code

- **Interoperability** -- multiple implementations conforming to the same interface
- **Reuse** – ability to use a component in many applications
- The larger the community that agrees to the interface, the greater the opportunity for interoperability and reuse



38




Interfaces are an Investment

- The larger the community, the greater the time & effort required to obtain agreement
 - Equally true in component and non-component environments
 - MPI 1.0 (well understood at the start) took 8 months, meeting every six weeks
 - MPI 2.0 (not well understood at the start) took 1.5 years, meeting every six weeks
 - Convenient communities are often “project” and “scientific domain”
- Formality of “standards” process varies
- Biggerstaff’s Rule of Threes
 - Must look at at least **three systems** to understand what is common (reusable)
 - Reusable software requires **three times the effort** of usable software
 - Payback only after **third release**

39



CCA Concepts: Frameworks




- The framework provides the means to “hold” components and **compose** them into applications
- Frameworks allow **connection of ports** without exposing component implementation details
- Frameworks provide a small set of **standard services** to components
 - Framework services are CCA ports, just like on components
 - Additional (non-standard) services can also be offered
 - Components can register ports as services using the *ServiceProvider* port
- *Currently*: specific frameworks are specialized for specific computing models (parallel, distributed, etc.)
- *Future*: better integration and interoperability of frameworks

40



Components Must Keep Frameworks Informed



- Components must tell the framework about the ports they are providing and using
 - Framework will not allow connections to ports it isn't aware of
- Register them using methods on the component's `gov.cca.Services` object
 - `addProvidesPort()` and `removeProvidesPort()`
 - `registerUsesPort()` and `unregisterUsesPort()`
 - All are defined in the CCA specification
- Ports are usually registered in the component's `setServices()` method
 - Can also be added/removed dynamically during execution




41






CCA Concepts: Language Interoperability

- Scientific software is increasingly diverse in use of programming languages
- In a component environment, users should not care what language a component is implemented in
- “Point-to-point” solutions to language interoperability are not suitable for a component environment
- The [Babel](#) language interoperability tool provides a common solution for all supported languages
- [Scientific Interface Definition Language](#) provides language-neutral way of expressing interfaces



42







CCA
Common Component Architecture


“Multiple-Component Multiple-Data” Applications in CCA

- Simulation composed of multiple SCMD sub-tasks
- Usage Scenarios:
 - Model coupling (e.g. Atmosphere/Ocean)
 - General multi-physics applications
 - Software licensing issues
 - i.e. limited number of instances
- Approaches
 - Run single parallel framework
 - Driver component that partitions processes and builds rest of application as appropriate (through BuilderService)
 - Run multiple parallel frameworks
 - Link through specialized communications components
 - Link as components (through AbstractFramework service)



Processors →


45








CCA
Common Component Architecture


....

MCMD Within A Single Framework


See example in the *Using CCA* module (multilevel parallelism in quantum chemistry)

-  Framework
-  Application driver & MCMD support component
-  Components on all processes
-  Components only on process group A
-  Components only on process group B

P0P1P2P3




Group A
Group B


46




CCA Supports High-Performance Local and Distributed Computing

- “**Direct connection**” preserves high performance of local (“in-process”) and parallel components
 - Framework makes **connection**
 - But is not involved in **invocation**
- **Distributed computing** has same uses/provides pattern, but **framework intervenes** between user and provider
 - Framework provides a *proxy* provides port local to the *uses* port
 - Framework conveys invocation from proxy to actual provides port



Direct Connection




47



“Direct Connection” Details

- Directly connected components are in the **same address space**
 - Data can be passed by reference instead of copying
 - Just like “traditional” programs
 - Framework involved in **connecting** components, but **not invocations** on ports
- Cost of “CCAness” in a direct connect environment is **a level of indirection** on calls **between** components
 - Equivalent to a C++ **virtual function call**: lookup function location, invoke it
 - Overhead is on the **invocation only** (i.e. latency), not the total execution time
 - Cost equivalent of ~2.8 F77 or C function calls
 - ~48 ns vs 17 ns on 500 MHz Pentium III Linux box

48



CCA
Common Component Architecture


Performance, the Big Picture

Direct-Connect, Parallel


- No CCA overhead on...
 - calls within component
 - parallel communications across components
- Small overheads on invocations on ports
 - Virtual function call (CCAness)
 - Language Interoperability (some data types)

Distributed

- No CCA overhead on calls within component
- Overheads on invocations on ports
 - Language interoperability (some data types)
 - Framework
 - (Wide area) network




Parallel Computer



Distributed Environment

49



CCA
Common Component Architecture

Maintaining HPC Performance

- The performance of your application is as important to us as it is to you
- The CCA is designed to provide maximum performance
 - But the best we can do is to make your code perform **no worse**
- Facts:
 - Measured overheads per function call are **low**
 - Most overheads **easily amortized** by doing enough work per call
 - Other changes made during componentization may also have performance impacts
 - **Awareness** of costs of abstraction and language interoperability facilitates design for high performance

More about
performance in notes

50




Common Component Architecture


Supplementary material for handouts

Some Performance Results and References

- Lois Curfman McInnes, et al. **Parallel PDE-Based Simulations Using the Common Component Architecture**. In Are Magnus Bruaset, Petter Bjorstad, and Aslak Tveito, editors, *Numerical Solution of PDEs on Parallel Computers*. Springer-Verlag, 2005. Invited chapter, in press.
- S. Benson, et al. **Using the GA and TAO Toolkits for Solving Large-Scale Optimization Problems on Parallel Computers**. Technical report ANL/MCS-P1084-0903, Argonne National Laboratory, September 2003.
- Boyana Norris, et al. **Parallel Components for PDEs and Optimization: Some Issues and Experiences**. *Parallel Computing*, 28:1811--1831, 2002.
- David E. Bernholdt, et al. **A Component Architecture for High-Performance Computing**. In *Proceedings of the Workshop on Performance Optimization via High-Level Languages and Libraries (POHLL-02)*, 2002.



Maximum 0.2% overhead for CCA vs native C++ code for parallel molecular dynamics up to 170 CPUs



Aggregate time for linear solver component in unconstrained minimization problem w/ PETSc

51



Common Component Architecture

Supplementary material for handouts

Overhead from Component Invocation

- Invoke a component with different arguments
 - Array
 - Complex
 - Double Complex
- Compare with f77 method invocation
- Environment
 - 500 MHz Pentium III
 - Linux 2.4.18
 - GCC 2.95.4-15
- Components took 3X longer
- Ensure granularity is appropriate!
- Paper by Bernholdt, Elwasif, Kohl and Epperly


Function arg type	f77	Component
Array	80 ns	224ns
Complex	75ns	209ns
Double complex	86ns	241ns

52



Scalability : Component versus Non-component. I

- Quantum chemistry simulation
- Sandia's MPQC code
 - Both componentized and non-componentized versions
- Componentized version used TAO's optimization algorithms
- Problem : Structure of isoprene HF/6-311G(2df,2pd)




Parallel Scaling of MPQC w/ native and TAO optimizers

53



Scalability : Component versus Non-component. II

- Hydrodynamics; uses CFRFS set of components
- Uses GrACEComponent
- Shock-hydro code with no refinement
- 200 x 200 & 350 x 350 meshes
- Cplant cluster
 - 400 MHz EV5 Alphas
 - 1 Gb/s Myrinet
- Negligible component overhead
- Worst perf : 73% scaling efficiency for 200x200 mesh on 48 procs



Reference: S. Lefantzi, J. Ray, and H. Najm, Using the Common Component Architecture to Design High Performance Scientific Simulation Codes, *Proc of Int. Parallel and Distributed Processing Symposium*, Nice, France, 2003.

54



Advanced CCA Concepts

Brief introductions only, but more info is available – just ask us!

- The Proxy Component pattern (Hands-On Ch. 6, papers)
- Component lifecycle (tutorial notes, Hands-On)
- Components can be dynamic (papers)
- Frameworks can provide a specialized programming environment (papers)




The Proxy Component Pattern

- Component **interfaces** offer an obvious place to collect information about method invocations for performance, debugging, or other purposes
 - No intrusion on component internals
- A “**proxy**” component can be inserted between the user and provider of a port without either being aware of it
- Proxies can often be **generated automatically** from SIDL definition of the port

Sample uses for proxy components:

- **Performance**: instrumentation of method calls
- **Debugging**: execution tracing, watching data values
- **Testing**: Capture/replay

Performance Monitoring with TAU





Common Component Architecture

Component Lifecycle

Additional
material
in notes

- **Composition Phase (assembling application)**
 - Component is **instantiated** in framework
 - Component interfaces are **connected** appropriately
- **Execution Phase (running application)**
 - Code in components uses functions provided by another component
- **Decomposition Phase (termination of application)**
 - **Connections** between component interfaces may be **broken**
 - Component may be **destroyed**

In an application, individual components may be in different phases at different times

Steps may be under human or software control

57



Common Component Architecture

Supplementary material for handouts


User Viewpoint: Loading and Instantiating Components

- Components are code + metadata
- Using metadata, a **Palette** of available components is constructed
- Components are instantiated by user action (i.e. by dragging from **Palette** into **Arena**)
- Framework calls component's **constructor**, then **setServices**
- Details are **framework-specific!**
- **Ccaffeine** currently provides both command line and GUI approaches

create
create
create

Driver
LinearFunction
MonteCarloIntegrator

Driver
LinearFunction
MonteCarloIntegrator




58



User Connects Ports

- Can only connect uses & provides
 - Not uses/uses or provides/provides
- Ports connected by type, not name
 - Port names must be unique within component
 - Types must match across components
- Framework puts info about *provider* of port into *using* component's Services object





connect	Driver	IntegratorPort	MonteCarloIntegrator	IntegratorPort
connect	MonteCarloIntegrator	FunctionPort	LinearFunction	FunctionPort
...				

59




Component's View of Instantiation

- Framework calls component's **constructor**
- Component initializes internal data, etc.
 - Knows *nothing* outside itself
- Framework calls component's **setServices**
 - Passes setServices an object representing everything "outside"
 - setServices declares ports component *uses* and *provides*
- Component *still* knows nothing outside itself
 - But Services object provides the means of communication w/ framework
- Framework now knows how to "decorate" component and how it might connect with others




60



CCA
Common Component Architecture


Supplementary material for handouts



Component's View of Connection

- Framework puts info about provider into **user component's** Services object
 - *MonteCarloIntegrator's* Services object is aware of connection
 - *NonlinearFunction* is not!
- MCI's** integrator code cannot yet call functions on FunctionPort

61




CCA
Common Component Architecture

Supplementary material for handouts

Component's View of Using a Port

- User calls **getPort** to obtain (handle for) port from Services
 - Finally user code can “see” provider
- Cast** port to expected type
 - OO programming concept
 - Insures type safety
 - Helps enforce declared interface
- Call** methods on port
 - e.g.
sum = sum + **function->evaluate(x)**
- Call **releasePort**



62



Components can be Dynamic

- `gov.cca.BuilderService` allows **programmatic composition** of components
 - Components can be instantiated/destroyed, and connected/disconnected under program control

Sample uses of *BuilderService*:

- Python “**driver**” **script** which can assemble and control an application
 - i.e. MCMD climate model
- **Adaptation** to changing conditions
 - Swap components in and out to give better performance, numerical accuracy, convergence rates, etc.
- **Encapsulation** of reusable complex component assemblies
 - Create a “container component” which exposes selected ports from the enclosed components



63



Frameworks can Provide Specialized Parallel Programming Environments

- By definition, all execution of components takes place within a framework
- CCA does not dictate a particular approach to parallelism
- Therefore, a specialized parallel programming environment can be made part of a CCA framework
 - May simplify design
 - Components depending on it won't be useable in other frameworks, even if they are also CCA-compliant

Example:

- Uintah Computational Framework, based on SCIRun2 (Utah) provides a multi-threaded parallel execution environment based on task graphs
 - Graphs express interdependencies of each task's inputs and outputs
 - Specialized to a class of problems using structured adaptive mesh refinement



64



Is CCA for You?

- Much of what CCA does can be done without such tools *if* you have sufficient discipline
 - The larger a group, the harder it becomes to impose the necessary discipline
- Projects may use different aspects of the CCA
 - CCA is *not* monolithic – use what *you* need
 - Few projects use all features of the CCA... initially
- Evaluate what *your* project needs against CCA's capabilities
 - Other groups' criteria probably differ from yours
 - CCA continues to evolve, so earlier evaluations may be out of date
- Evaluate CCA against other ways of obtaining the desired capabilities
- Suggested starting point:
 - CCA tutorial "hands-on" exercises



65



Take an Evolutionary Approach

- The CCA is designed to allow selective use and incremental adoption
- "SIDLize" interfaces incrementally
 - Start with essential interfaces
 - Remember, only externally exposed interfaces need to be Babelized
- Componentize at successively finer granularities
 - Start with whole application as one component
 - Basic feel for components without "ripping apart" your app.
 - Subdivide into finer-grain components as appropriate
 - Code reuse opportunities
 - Plans for code evolution



66



View it as an Investment

- CCA is a long-term investment in your software
 - Like most software engineering approaches
- There is a cost to adopt
- The payback is longer term
- Remember Biggerstaff's Rule of Threes
 - Look at three systems, requires three times the effort, payback after third release



67



CCA is Still Under Development

- We've got...
 - A stable component model
 - Working tools
 - Active users
- But...
 - We know its not perfect
 - We're not "done" by any stretch
- Talk to us...
 - If you're evaluating CCA and and need help or have questions
 - If you don't think CCA meets your needs
 - If you've got suggestions for things we might do better



68



What Can CCA Do Today?

- Ccaffeine framework for HPC/parallel
 - XCAT and other options for distributed computing
- Language interoperability
 - Fortran 77/90/95, C, C++, Java, Python
 - Support for Fortran/C user-defined data structures under development
- CCA Tools working on a variety of platforms
 - Linux most widely used
 - Mac OS X second
 - Some IBM AIX users
 - Ports in progress for Cray X1 and XT3
 - Porting is driven by user needs



69



Common Component Architecture

CCA Tools – Language Interoperability and Frameworks

CCA Forum Tutorial Working Group

<http://www.cca-forum.org/tutorials/>
tutorial-wg@cca-forum.org



This work is licensed under a [Creative Commons Attribution 2.5 License](http://creativecommons.org/licenses/by/2.5/)

70

CCA
Common Component Architecture

Goal of This Module

- Describe **tools** for multi-lingual, scientific component 'plug-and-play'

IDE = Interactive Development Environment

71

CCA
Common Component Architecture

CCA adds value to component development

Babel runtime library & Chasm F90 array library

Language compiler & linker

Compiled Components (object libraries)

Generated language code

Babel compiler (SIDL → language)

Port Definitions (SIDL)

Component Definition (SIDL)

Component source code


Application (component assembly)
CCA Framework

CCA IDE

Key:


- User code
- CCA Tools
- Standard Tools
- Generated code
- Object libraries

72




CCA
Common Component Architecture


Tools Module Overview



- Language interoperability tools
- Frameworks
- CCA Interactive Development Environment



73




CCA
Common Component Architecture


Babel

Babel Facilitates Scientific Programming Language Interoperability



- Programming language-neutral interface descriptions
- Native support for basic scientific data types
 - Complex numbers
 - Multi-dimensional, multi-strided arrays
- Automatic object-oriented wrapper generation




Supported on Linux, AIX, and Solaris 2.7, works on OSX;
 C (ANSI C), C++ (GCC), F77 (g77, Sun f77), F90 (Intel, Lahey, GNU, Absoft), Java (1.4)



74




 **CCA**
Common Component Architecture

Babel


Supplementary material for notes

Recent and Upcoming Features

- Remote Method Invocation (BabelRMI) *ALPHA*
- Design-by-Contract *ALPHA*
- Pre- and post-method invocation hooks *ALPHA*



77


 **CCA**
Common Component Architecture

Chasm


Chasm Provides Language Interoperability for Fortran, C, and C++

- Extracts interfaces from C/C++ and Fortran90 codes
- Uses library of XSLT stylesheets for language transformations → easily extended
 - Generates XML and SIDL representations
 - Generates Fortran90 Babel implementation glue
- Provides Fortran array descriptor library used by Babel

Supported on Linux, AIX, and Solaris 2.7, works on OSX;
C (ANSI C), C++ (GCC), F90 (Intel, Lahey, GNU, Absoft)



78



CCA Common Component Architecture *Chasm* *Supplementary material for notes*

Chasm-Assisted Glue Code Generation

1. Create functions_LinearFunction.impl.xml
2. Create xml description of source procedures



```

% gfortran -fdump-parse-tree LinearFunction.f90 >
  LinearFunction.ptd
% gfortran2xml < LinearFunction.ptd >
  LinearFunction.xml
      
```
3. Create .sidl, _Impl.F90, and _Mod.F90


```

% xalan -o functions_LinearFunction.sidl
  functions_LinearFunction.impl.xml
  cca-f90-comp.sidl.xsl
% xalan -o functions_LinearFunction_Impl.F90
  functions_LinearFunction.impl.xml
  cca-f90.impl.xsl
% xalan -o functions_LinearFunction_Mod.F90
  functions_LinearFunction.impl.xml
  cca-f90.mod.xsl
      
```
4. Run Babel...

80

 **CCA**
Common Component Architecture

Chasm

Supplementary material for notes


User-Created XML Component Description File

```
<componentImplementation name="LinearFunction" package="functions">
  <language name="F90">
    <property name="impl-scope" value="LinearFunction"/>
    <property name="impl-xml" value="/home/cca/LinearFunction.xml"/>

    <ports>
      <provides name="FunctionPort" package="function">
        <MethodsBlock>
          <Method name="evaluate" impl="evaluate_if"/>
        </MethodsBlock>
      </provides>
    </ports>

  </language>
</componentImplementation>
```

81

 **CCA**
Common Component Architecture


Chasm

Supplementary material for notes

Recent and Upcoming Features


- Generate Fortran 2003 MPI Bindings *1Q 2006*
- Update XML processor and generator to new PDToolkit releases *1Q 2006*

82





CCA
Common Component Architecture

Tools Module Overview



- Language interoperability tools
- ➔ • Frameworks
- CCA Interactive Development Environment



83




CCA
Common Component Architecture

Frameworks are Specialized to Different Computing Environments


- “**Direct connection**” preserves high performance of local (“in-process”) and parallel components
 - Framework makes **connection**
 - Framework *not* involved in **invocation**
- **Distributed computing** has same uses/provides pattern, but the framework **intervenes** between user and provider
 - Framework provides a **proxy port** local to the user's *uses* port
 - Framework conveys invocation from **proxy to actual** provides port



Direct Connection



Network Connection


84



Graphical User Interfaces (GUIs) Deliver Plug-and-Play Experience

- Plug & play for:
 - Application software assembly
 - Visualization pipelines
 - Workflow management
- Assembling “wiring” diagrams is almost universal.
 - Software assembly: Ccaffeine, XCAT, SciRUN
 - Workflow: XCAT, SciRUN
 - Visualization: SciRUN

None of these (yet) plug into your favorite Integrated Development Environment (e.g., Eclipse, MS Dev. Studio, Java Studio, ...).

85



Ccaffeine Framework

Ccaffeine is a *Direct-Connect*, Parallel-Friendly Framework

- Supports SIDL/Babel components
 - Conforms to latest CCA specification (0.7)
 - Also supports legacy CCA specification (0.5)
 - Any C++ allowed with C and Fortran by C++ wrappers
- Provides command-line and GUI for composition
 - Scripting supports batch mode for SPMD
 - MPMD/SPMD custom drivers in any Babel language

Supported on Linux, AIX, OSX and is portable to modern UNIXes.

86



Common Component Architecture

Ccaffeine Framework

Ccaffeine Involves a Minimum of Three Steps

- As easy as 1-2-3:
 - Write your component.
 - Describe it with an XML file.
 - Add a line to your Ccaffeine input file to load the component at runtime.
- Proceed to plug & play...

There are many details and automated tools that help manage components.

87




Common Component Architecture

Ccaffeine Framework (ccafe-gui)

Optional

Ccaffeine GUI

- Process
 - User input is broadcast SPMD-wise from Java.
 - Changes occur in GUI *after* the C++ framework replies.
 - If your components are computing, GUI changes are blocked.
- Components interact through *port connections*
 - *provide* ports *implement* class or subroutines "Provides" Port
 - *use* ports *call* methods or subroutines in the port. "Uses" Port
 - Links denote caller/callee relationship *not* data flow



Java is required.

88




Common Component Architecture

Ccaffeine Framework (ccafe-gui)

Supplementary material for notes

User Connects Ports

- Can only connect *uses* & *provides*
 - Not uses/uses
 - Not provides/provides
- Ports connected by type not name
 - Port names **must be unique** within component
 - Types **must match** across components
- Framework puts info about *provider* of port into *using* component's Services object



connect	Driver	IntegratorPort	MonteCarloIntegrator	IntegratorPort
connect	MonteCarloIntegrator	FunctionPort	LinearFunction	FunctionPort
...				

89




Common Component Architecture

Ccaffeine Framework (ccafe-gui)

Building an Application (1 of 2)

- Components are code + XML metadata
- Using metadata, a **Palette** of available components is constructed.
- Components are instantiated by user action (i.e. by dragging from **Palette** into **Arena**).
- Framework calls component's **constructor**, then **setServices**



create	Driver	Driver
create	LinearFunction	LinearFunction
create	MonteCarloIntegrator	MonteCarloIntegrator

90

CCA
Common Component Architecture

Caffeine Framework (ccafe-gui)

Building an Application (2 of 2)

1. Click **Configure** port to start parameter input dialogue.
2. For each connection:
click a **uses** port then click a **provides** port to establish a connection.
3. Click **Go** port to start the application.

Right-clicking a connection line breaks the connection -- enabling component substitution.

91

CCA
Common Component Architecture

Caffeine Framework (ccafe-gui)


Supplementary material for notes

Application Configurations can be Re-used

1. Click **Save** or **Save As...** to save actions.
2. Click **Open** to replay actions.

- Script optimization
% **simplify-bld** saved_file.bld > faster_file.bld
- Batch conversion
% **bld2rc** faster_file.bld > faster_file.batch
- C++ stand-alone execution
% **bld2babel-cpp** faster_file.bld faster_file_babel outdir
or % **bld2neo** faster_file.bld faster_file.batch outdir

92


 **CCA**
Common Component Architecture

Caffeine Framework


Supplementary material for notes

Recent and Upcoming Features


- Interoperate with other CCA frameworks
 - Via Babel RMI *2H 2006*



93

 **CCA**
Common Component Architecture


XCAT-C++ Framework



XCAT is a Web-services based Distributed Component Framework



- Remote references
 - Port types described in C++ header files or in WSDL documents
- User Interface
 - C++ and Python interface to CCA *BuilderService*
 - Uses SWIG for Python-C++ translations
- Component creation
 - Remote creation via SSH
- Component communication
 - Proteus multi-protocol library
 - Communication libraries can be loaded at run-time


Tested on Linux.



WSDL = Web Service Definition Language

94






CCA
Common Component Architecture


XCAT-C++ Framework

Supplementary material for notes




Recent and Upcoming Features

- Support GRAM for component creation 1H 2006
 - Allow use of grid resources
- Automated component registration and discovery 2H 2006
- Support new protocols such as UDT (in Proteus) 1H 2006
- Support Babel's Remote Method Invocation 2H 2006
 - Allows access to Babel objects through remote Babel stubs
 - Provides direct support for SIDL in distributed applications
 - Leverages Proteus



GRAM = Grid Resource Allocation Management UDT = UDP-based Data Transfer protocol

97




CCA
Common Component Architecture

SCIRun2 Framework



SCIRun2 is a Cross-Component Model, Distributed Component Framework


- Semi-automatically bridges component *models*
 - Templated components connected at run-time generate bridges
- Parallel Interface Definition Language (PIDL) – a SIDL variant
- User interface – GUI and textual
 - Dynamic composition
- Component and framework creation
 - Remote via SSH
- Component communication
 - C++ RMI with co-location optimization
 - MPI/ Parallel Remote Method Invocation (PRMI)



Supported on Linux.

98




 **CCA**
Common Component Architecture

SCIRun2 Framework


Supplementary material for notes

Simple SCIRun2 CCA (PIDL) and Babel Bridge



The screenshot shows the SCIRun2 application window. The top menu bar includes 'File', 'Proxy Frameworks', 'CCA', 'Corba', 'Dataflow', 'Tao', 'Vtk', and 'babel'. The main window is divided into two panes. The left pane displays a component diagram with three components: 'Hello Component', 'Hello_NewPort', and 'NewPortConn'. 'Hello Component' is connected to 'Hello_NewPort', which is connected to 'NewPortConn'. The right pane shows a 'Messages' log with the text: 'SCIRun2 Framework URL: socket://ottawa.sci.utah.edu:51484/134768216'. A small dialog box titled 'Hello' is open, displaying the message 'NewPort.StringPort_impl: getString CALLED' and an 'OK' button.

101

 **CCA**
Common Component Architecture

SCIRun2 Framework

Supplementary material for notes

Recent and Upcoming Features

- Merge PIDL with SIDL/Babel *1H 2005*
- Support additional component models
 - Kepler workflows *1H 2006*
- Support Babel's Remote Method Invocation PRMI *2H 2006*
- Automate bridging *On-going*


102

Framework	Purpose	Summary
Distributed CCA Framework (DCA)	MxN research	<ul style="list-style-type: none"> • Goal: explore MxN Parallel-Remote Method Invocation (PRMI) using MPI • Parallel data transfer and redistribution integrated into port invocation mechanism
LegionCCA	Grid-based research	<ul style="list-style-type: none"> • Goal: allow component-based CCA applications to run in Grid-scale environments using Legion • Supports creation, scheduling, persistence, migration, and fault notification; relies on Legion's built-in RPC mechanism (~Unix sockets)
XCAT-Java	Globus-based Grid research	<ul style="list-style-type: none"> • Goal: explore web interface for launching distributed applications • This (alpha) version compatible with latest CCA specification and provides built-in seamless compatibility with OGSi.




OGSI = Open Grid Services Infrastructure

103



104


**CCA**
Common Component Architecture

CCA IDE


Component Development Environment Provided via **Eclipse** Plug-ins

- Provides a high-level graphical environment
 - Creating new SIDL-based components
 - Componentizing legacy codes
 - C, C++, Java and Fortran
- Automatic code generation

Supported on Linux, Windows, MacOS.



105


**CCA**
Common Component Architecture

CCA IDE

Component Development Environment Starts at the Eclipse Platform Level

Plug-ins for:


- SIDL Editor
- Wizards
- Preliminary automated build support



The screenshot shows the Eclipse IDE with the CCA project structure in the Navigator. The project is named 'newFile.sidl' and is located in the 'gov.cca' package. The code editor shows the following SIDL code:

```
/*
 * Folder: /SIDL/Test
 * File: newFile.sidl
 * This file was created on: 2005-06-18 17:07:17
 */
package TestPackage2 version 2.0 {
    interface HI {
        void sayHi(in string name);
    }
    <class HelloWorld implements all TestPackage2.HI {
    }
}
```

Imperative that you start by creating a new project!




106



Wizards are Available for Adding Packages and Classes or Generating SIDL from Legacy Codes


- Intuitive interfaces to port and component definition
- Helper wizards for setting port, component and (in the future) application properties




107



A Wizard is also Available for Adding Methods



108




CCA
Common Component Architecture


CCA IDE

Supplementary material for notes

Recent and Upcoming Features

- Provide automated build support 1H 2005
- Launch application via GUI 1H 2006


109




CCA
Common Component Architecture


CCA IDE

Supplementary material for notes

CCA Tools Contacts (1 of 2)

Tool	Purpose	More information
Babel	Scientific language interoperability tool kit	URL: www.llnl.gov/CASC/components Email: components@llnl.gov or babel-users@lists.llnl.gov
Ccaffeine	Direct-connect, parallel-friendly framework	URL: www.cca-forum.org/software/ Email: Ben Allan, ccafe-help@z.ca.sandia.gov Wiki: https://www.cca-forum.org/wiki
Chasm	Fortran90 interoperability wrapper	URL: chasm-interop.sourceforge.net Examples: chasm/example/cca-tutorial
DCA	MxN research framework	URL: www.cs.indiana.edu/~febertra/mxn Email: Felipe Bertrand, febertra@cs.indiana.edu
CCA IDE	CCA development environment	Email: usability@cca-forum.org



110

**CCA**
Common Component Architecture


Supplementary material for notes


CCA Tools Contacts (2 of 2)

Tool	Purpose	More information
LegionCCA	Grid-based research framework	URL: grid.cs.binghamton.edu/projects/legioncca.html Email: Michael J. Lewis, mlewis@binghamton.edu
SCIRun2	Cross-component model framework	URL: www.sci.utah.edu/ Email: Steve Parker, sparker@cs.utah.edu
XCAT-C++	Globus-based GRID framework	URL: grid.cs.binghamton.edu/projects/xcats/ Email: Madhu Govindaraju, mgovinda@cs.binghamton.edu
XCAT-Java	Grid research framework	URL: www.extreme.indiana.edu/xcats/ Email: Dennis Gannon, gannon@cs.indiana.edu




111







CCA
Common Component Architecture



CCA Forum Tutorial Working Group
[http://www.cca-forum.org/tutorials/
tutorial-wg@cca-forum.org](http://www.cca-forum.org/tutorials/tutorial-wg@cca-forum.org)

 This work is licensed under a [Creative Commons Attribution 2.5 License](https://creativecommons.org/licenses/by/2.5/)

113



CCA
Common Component Architecture


Goal of This Module

Learn how existing code is


- **Wrapped into Babel objects, and**
- **Promoted to CCA components**

In the process, also need to learn about

- **Scientific Interface Definition Language (SIDL)**
- **Using the Babel tool**
- **Characteristics of Babelized software**



114



CCA
Common Component Architecture

..

Working Code: “Hello World” in F90 Using a Babel Type

```


① program helIoclient
  use greetings_English
  implicit none
② type(greetings_English_t) :: obj
  character (len=80)      :: msg
  character (len=20)      :: name

③   name='World'
④   call new( obj )
⑤   call setName( obj , name )
⑥   call sayIt( obj , msg )
⑦   call deleteRef( obj )
  print *, msg

end program helIoclient

```

115



CCA
Common Component Architecture

Handout Material: Code Notes

- ① Use statement for the greetings.English type
- ② Obj is a F90 derived type we get from the using statement, note the “_t” extension that prevents it from colliding with the using statement.
- ③ In C/C++ examples, this variable would be initialized by a the command-line variable “argv[1]”, but its trickier to do portably in F90 and too long, so I just initialize the name to “World”.
- ④ Obj is not yet initialized. The Babel idiom in F90 is to call new() to initialize the Babel type. In other languages its _create().
NOTE: good code would add error checking.
- ⑤ setName() puts data into the obj. It sets its state.
- ⑥ sayIt() returns the entire greeting including the aforementioned name.
- ⑦ deleteRef() is a subroutine that all Babel types inherit from a parent class. All Babel objects are reference counted. When there are no more outstanding references, the object is told to clean up after itself.

116

Working Code: “Hello World” in F90 Using a Babel Type

```

program helloClient
  use greetings_English
  implicit none
  type(greetings_English_t) :: obj
  character (len=80)          :: msg
  character (len=20)          :: name

  name='World'
  call new( obj )
  call setName( obj, name )
  call sayIt( obj, msg )
  call deleteRef( obj )
  print *, msg
end program helloClient

```

Looks like a native F90 derived type

These subroutines were specified in the SIDL.

Other basic subroutines are “built in” to all Babel types.

117

The SIDL File that defines the “greetings.English” type

```

①② package greetings version 1.0 {
③④   interface Hello {
⑤       void setName( in string name );
        string sayIt ( );
    }
⑥   class English implements-all Hello { }
}

```

118



Handout Material: Code Notes

- ① Packages contain user-defined types and are used to reduce naming collisions. Packages can be nested.
- ② Packages can be versioned. User defined types must be nested inside a versioned package and gain the same version number as the innermost versioned package
- ③ SIDL has a inheritance model similar to Java and Objective C. Classes can inherit multiple interfaces, but at most one implementation (other class).
- ④ An interface describes an API, but doesn't name the implementation.
- ⑤ Note that arguments have mode, type, and name. Mode can be one of "in", "out", and "inout". These SIDL modes have slightly different semantics than Fortran90 "intents".
- ⑥ This class generates English greetings. One could imagine a strategy for internationalization that uses the Hello interface everywhere, but loads in English, French, or whatever classes based on user's preference.



Question: What language is "obj" really implemented in?

```

program helloclient
  use greetings_English
  implicit none
  type(greetings_English_t) :: obj
  character (len=80)          :: msg
  character (len=20)          :: name

  name='World'
  call new( obj )
  call setName( obj, name )
  call sayIt( obj, msg )
  call deleteRef( obj )
  print *, msg


end program helloclient

```

Answer: Can't Know!


With Babel, it could be C, C++, Python, Java, Fortran77, or Fortran90/95

In fact, it could change on different runs without recompiling this code!




CCA
Common Component Architecture

CCA uses Babel for high-performance n-way language interoperability



Each one of these red lines, is potentially a bridge between two languages. No telling which language your component will be connected to when you write it.

121





CCA
Common Component Architecture



CCA uses SIDL to specify APIs and Type Hierarchy for Frameworks, Services, Components, & Ports


- **A CCA framework must**
 - implement gov. cca. AbstractFramework,
 - provide a gov. cca. ports. BuilderService,
 - etc.
- **A CCA port must**
 - be a SIDL interface extending gov. cca. Port
- **A CCA component must**
 - be a SIDL class implementing gov. cca. Component

The CCA Specification is a SIDL file.

122







CCA
Common Component Architecture

Implementation Details Must be Filled in Between Splicer Blocks

```
namespace greetings {
class Engli sh_ i mpl {
private:
    // DO-NOT-DELETE spl i cer. begi n(greeti ngs. Engli sh. _i mpl )
    string d_name;
    // DO-NOT-DELETE spl i cer. end(greeti ngs. Engli sh. _i mpl )

string
greeti ngs:: Engli sh_ i mpl :: sayl t()
throw ()
{
    // DO-NOT-DELETE spl i cer. begi n(greeti ngs. Engli sh. sayl t)
    string msg("Hello ");
    return msg + d_name + "!";
    // DO-NOT-DELETE spl i cer. end(greeti ngs. Engli sh. sayl t)
}
```

128



Quick Review of Babel in general before proceeding to CCA specifics

- Babel can be used as a standalone tool
- Each language binding strikes a balance
 - support the SIDL type system (OO, exceptions, etc.)
 - provide it in a manner “natural” to experienced programmers in the target language
- For more details about Babel and SIDL
 - SC|04 tutorial slides for Babel
<http://www.llnl.gov/CASC/components/docs/sc04.html>
 - Babel User’s Guide (aka. the BUG)



129



How to write a Babelized CCA Component (1/3)

1. Define “Ports” in SIDL

- CCA Port =
 - a SIDL Interface
 - extends gov.cca.Port

```
package functions version 1.0 {  
    interface Function extends gov.cca.Port {  
        double evaluate( in double x );  
    }  
}
```



130



How to write a Babelized CCA Component (2/3)

2. Define “Components” that implement those Ports

- CCA Component =
 - SIDL Class
 - implements gov.cca.Component (and any provided ports)


```
class LinearFunction implements functions.Function,
                                gov.cca.Component {
    double evaluate( in double x );
    void setServices( in cca.Services svcs );
}
```

```
class LinearFunction implements-all
    functions.Function, gov.cca.Component { }
```


131



Tip: Use Babel's XML output like precompiled headers in C++



1. Precompile SIDL into XML using '--text=xml'
2. Store XML in a directory
3. Use Babel's -R option to specify search directories



132

CCA
Common Component Architecture

How to write a Babelized CCA Component (3/3)

```
graph LR; Repo[(Repo XML)] --> Babel[Babel Compiler]; functions[functions.sidl] --> Babel; Babel --> Stubs[C Stubs]; Babel --> IORs[IORs]; Babel --> Skeletons[C Skeletons]; Babel --> Implementations[Implementations]; Implementations -.-> libfunctions[libfunctions.so]; smiley(( )) -- green arrow --> functions; smiley --> Implementations
```

3. Use Babel to generate the interoperability glue
 - Execute ``babel --server=C -RRepo functions.sidl``
4. Fill in Implementations as needed

133

CCA
Common Component Architecture

Review: Goal of This Module

Learn how existing code is

- Wrapped into Babel objects, and
- Promoted to CCA components

In the process, also need to learn about

- Scientific Interface Definition Language (SIDL)
- Using the Babel tool
- Characteristics of Babelized software

134




CCA
Common Component Architecture

Contact Information

- Project: <http://www.llnl.gov/CASC/components>
- Project Team Email: components@llnl.gov
- Mailing Lists: majordomo@lists.llnl.gov
subscribe [babel-users](#) [email address]
subscribe [babel-announce](#) [email address]
- Bug Tracking: <https://www.cca-forum.org/bugs/babel/>
or email to babel-bugs@cca-forum.org




135



CCA
Common Component Architecture

Using CCA: Approaches & Experience

CCA Forum Tutorial Working Group
[http://www.cca-forum.org/tutorials/
tutorial-wg@cca-forum.org](http://www.cca-forum.org/tutorials/tutorial-wg@cca-forum.org)



This work is licensed under a [Creative Commons Attribution 2.5 License](#)

136

CCA
Common Component Architecture

Modern Scientific Software Development

- Complex codes, often **coupling** multiple types of physics, time or length scales, involving a broad range of computational and numerical techniques
- Different parts of the code require significantly **different expertise** to write (well)
- Generally written by **teams** rather than individuals

137

CCA
Common Component Architecture

Using CCA to Help Manage Complexity

- Application areas participating in the CCA:
astronomy, astrophysics, biological and medical simulations, chemically reacting flow, climate and weather modelling, combustion, computational chemistry, data management, fusion and plasma physics modelling, linear algebra, materials science, molecular electronics, nanoscience, nuclear power plant simulations, structured adaptive meshes, unstructured meshes, and visualization
- Research agencies sponsoring software development using the CCA:
DOE (SciDAC, Office of Science, NNSA/ASC), NASA, NIH, NSF, DoD, European Union

138



Outline

- Developing Components
 - Strategies for both developing new codes and wrapping existing codes
- Case Studies
 - Chemistry project
 - Moderate-sized multi-disciplinary, multi-institutional team
 - Using Ccaffeine framework, SIDL components
 - Combustion toolkit
 - Small team, both new and wrapped codes
 - Using Ccaffeine framework, C++ components



Developing Components (Both New Codes and Wrappers to Existing Codes)

- Productivity Benefits
- Application Decomposition Strategies
- Interface Design Issues
 - Social factors
 - Technical factors
- Implementation Issues and Patterns





CCA Productivity Benefits

- Fast algorithmic **experiments** and benchmarks by substituting components
- Once ports are defined, domain-expert component implementers can **work separately** in their own **favorite languages**
- Work of **transient contributors** remains as well-defined, lasting components
- Wrapped legacy portions **need not be reimplemented or reverified**



Components in the Small: Impacts within a Project

Benefits include:

- Rapid testing, debugging, and benchmarking
- Support for implementation-hiding discipline
- Coordination of independent workers
- Interface change effects across components are clear and usually automatically found by compilers if overlooked
- Object-orientation made simpler for C and Fortran





Components in the Large: Connecting Multiple Projects

Benefits include:

- SIDL can be used to facilitate the interface consensus processes
- Different sub-projects do not have to agree on one implementation language
- Developers who never meet in person have an excellent chance of code integration working on the first try

Costs include:

- Consensus can be expensive to obtain
- Writing code for others to use is more difficult than writing it just for yourself



Application Decomposition Strategies

- Conceptually decompose the application into
 - cutting-edge areas (*less stable*) and
 - areas that can employ existing component-based libraries (*more stable*)
- Decompose each area into components for
 - *physics*
 - *mathematics*
 - *data management*as dictated by the application; sketch a typical component layout
- Many components will encapsulate *algorithmic logic only*, with little or no private data
- Most HPC applications will have a *central data abstraction* that provides data memory management and parallel communication
- In a multilanguage application, all *I/O may need to be isolated* into components written in a single common language (file based I/O should not be affected)
- Component boundaries (and port interfaces) may be set to *isolate proprietary code or difficult contributors*





Interface Design: Social Factors (Defining Ports to Wrap Existing Code)

- Will the port hide just one implementation, or will there need to be plug compatibility with other implementations? From other teams?
- Who defines the interface and maintains it?
 1. Project dictator? (Fast)
 2. The owner of the legacy functionality? (Slow, if not you)
 3. A standards committee? (Really slow)
- How many iterations of redefining the ports will the customers tolerate?



145



Interface Design: Technical Factors

- Do we make a single large port look like the underlying library or divide functions into groups on separate ports?
- Should a function with many optional arguments be split into several alternative functions with simpler usage?
- Do we make the ports more general than the existing code?
- Do we require the ports to work across languages?
Across networks?
 - If not, gains in efficiency or coding ease might be had
 - If so, memory management and I/O challenges may arise



146



Implementation Issues in Wrapping

- Do we split large libraries into several components?
 - Splitting is difficult to do if global variables or common blocks are widely used.
- Do we expect more than one implementation instance of a port in a single run-time?
 - If not, interface contracts may include global side effects
- Do we integrate the wrapper code in the existing code's development and build processes?
 - If not, how do we ensure build consistency and on-going wrapper support?
- Code bases with large interfaces need automated wrapping tools
 - E.g., [see Chasm info in the Tools module](#) of the tutorial

147



Benefits of Wrapping Code Using CCA

- Setting a language-neutral interface definition (SIDL) can greatly clarify design discussions
- Provides a chance to reorganize the interface and hide globals
- Allows testing of alternate versions if doing performance studies
- Allows easy “experimentation” with new algorithms
- Software discipline is enforced, not optional
- Implementation decisions (to split libraries, etc) can be easily revised over time if interfaces remain constant (possibly with the addition of new interfaces)

148



Interface Design for *New Code*

- Write SIDL for each connection (port) in the sketched component layout
- If two ports must always be used together, consider merging them
- Review SIDL drafts for near-duplication of ports
- Avoid creating interface contracts that require using hidden global data
- Consider exporting tuning and/or configuration parameter inputs as a port
- All the design issues from wrapping existing code apply, also
- ***Interfaces will change.***



149



Recommended Implementation Patterns

- Expect to decompose initial components further as work progresses and requirements expand
- Build systems (`make`) should be kept as simple as possible
 - Keep a subdirectory for port definitions and any implementation-independent glue code derived from the ports
 - Keep each component (and any wrapped code) in its own subdirectory
 - Keep application-wide flags in a configure script or an include file common to all components and ports
 - Consistency is key. Extract build flags from `cca-spec-babel-config` and if possible compile & link with `babel-libtool`



150



Outline

- Developing Components
 - Strategies for both developing new codes and wrapping existing codes



Case Studies

- Chemistry project
 - Moderate-sized multi-disciplinary, multi-institutional team
 - Using Ccaffeine framework, SIDL components
- Combustion toolkit
 - Small team, both new and wrapped codes
 - Using Ccaffeine framework, C++ components




151




Case Study 1: Chemistry Project

- Funded via SciDAC initiative
- Initial focus: Full-featured components for structure optimization
 - **Chemistry models** provided by MPQC (SNL) & NWChem (PNNL)
 - **Numerical optimization** provided by TAO (ANL) solvers
 - **Linear algebra** provided by GA (PNNL) and PETSc (ANL)
- Recent work:
 - Multi-level parallelism
 - Low-level chemistry model integration (e.g., molecular integrals)



152


**CCA**
Common Component Architecture


CCA-Chemistry Project Participants


Pacific Northwest National Laboratory
Theresa L. Windus
Yuri Alexeev
Manojkumar Krishnan
Jarek Nieplocha
Carl Fahlstrom
Elizabeth Jurrus


Argonne National Laboratory
Steve Benson
Lois Curfman McInnes
Jason Sarich


Sandia National Laboratory
Curtis L. Janssen
Joseph P. Kenney




**Pacific Northwest
National Laboratory**
Operated by Battelle for the
U.S. Department of Energy

**ARGONNE NATIONAL LABORATORY**
UNIVERSITY OF CHICAGO

**Sandia
National
Laboratories**




153

**CCA**
Common Component Architecture



CCA Impacts in Computational Chemistry

Through 4 chemistry applications we consider different facets of CCA functionality:

- **Molecular Geometry Optimization**
 - Combining diverse expertise of 5 different research groups
- **Lennard-Jones Molecular Dynamics**
 - Achieving good scalability and low CCA overhead
- **Multi-level Parallelism in Computational Chemistry**
 - Combining SPMD and MPMD parallelism
- **Molecular Integral Evaluation**
 - Component interoperability at deeper levels within chemistry libraries




154





Common Component Architecture

Performance Gains with Better Optimization Algorithms



CCA-based integration of the state of the art optimization algorithms from the TAO toolkit provides up to 40% improvement in the time required to optimize molecular structures with MPQC and NWChem.¹


¹Journal of Computational Chemistry 25: 1717-1725, 2004.

157



Common Component Architecture

App 2: Molecular Dynamics




CCA component wiring diagram for Lennard-Jones energy optimization, which integrates TAO, GA and Lennard-Jones molecular dynamics components

158




Common Component Architecture

Good Scalability, Negligible Overhead



Speedup in the Lennard-Jones potential energy optimization for 32,768 and 65,536 particles

Overhead of CCA component (using SIDL) vs. "native" C++ implementation of a parallel Lennard-Jones molecular dynamics simulation



% Overhead using CCA Components


159



Common Component Architecture



App 3: Multilevel Parallelism Using CCA

- Massive numbers of CPUs in future systems require leading edge tools to exploit all available parallelism
- GA helps exploit multi-level parallelism
- Multi-level parallelism using CCA and GA processor groups: Combining SCMD (Single Component Multiple Data) and MCMD (Multiple Component Multiple Data) paradigms



The MCMD Driver launches multiple instances of NWChem components on subsets of processors (also assigns a GA communicator for every instance). Each NWChem QM component does multiple energy computations on subgroups.

160





CCA Impacts in Computational Chemistry

Review: Through 4 chemistry applications we considered different facets of CCA functionality:

- Combining diverse expertise of 5 different research groups
- Achieving good scalability and low CCA overhead
- Implementing multi-level parallelism by combining SPMD and MPMD paradigms
- Addressing component interoperability at deeper levels within chemistry libraries




CCA Impacts in Computational Chemistry: Review

Through 4 chemistry applications we considered different facets of CCA functionality:

- Combining diverse expertise of 5 different research groups
- Achieving good scalability and low CCA overhead
- Implementing multi-level parallelism by combining SPMD and MPMD paradigms
- Addressing component interoperability at deeper levels within chemistry libraries








CCA
Common Component Architecture

Case Study 2: Combustion Project

- Computational Facility for Reacting Flow Science (CFRFS)
 - <http://cfrfs.ca.sandia.gov>
 - Funded via SciDAC initiative (PI: H. Najm)
- Focus: A toolkit to perform simulations of lab-sized unsteady flames
 - Solve the Navier-Stokes with detailed chemistry
 - Various mechanisms up to ~50 species, 300 reactions
- Consequently:
 - Disparity of **length scales** :
 - use structured adaptively refined meshes
 - Disparity of **time scales** (transport versus chemistry) :
 - use an operator-split construction and solve chemistry implicitly
 - adaptive chemistry: use **computational singular perturbation** to find and follow low dimensional chemical manifolds
- Contributions to research and codebase:
 - J. Ray, S. Lefantzi, J. Lee, C. Kennedy, W. Ashurst, K. Smith, M. Liu, N. Trebon





165



CCA
Common Component Architecture

Why Use CCA in the CFRFS Toolkit?

- Separate clearly the physics models, numerical algorithms, and the “CS” parts of the toolkit
 - Strictly functional!
- Realize the separation in software
- Tame **software** complexity
- Separate contributions by transient contributors
 - Form the bulk of the developers
- Create “chunks” of well-defined functionality that can be developed by experts (usually numerical analysts and combustion researchers)


166




Design Principles of the Toolkit - 1


- **Principal Aim: Reduce software complexity**
 - We can deal with the rest
- Functional decomposition into components
 - “Data Object” and Mesh components
 - (Large) set of numerical algorithmic components (integrators, linear/nonlinear solvers, etc.)
 - (Large) set of physical models components (gas-phase combustion chemistry, thermodynamics, fluid dynamic quantities, e.g. viscous stress tensor)
 - Handful of adaptors



Design Principles of the Toolkit - 2


- Decomposition reflected in the port design and implementation
 - Most re-implemented port is the one that exchanges a rectangular sub-domain's data for processing by components
- Sparse connectivity between components
 - i.e., components communicate with a few others
 - Large apps (component assemblies) are composed by assembling smaller, largely independent sub-assemblies
 - Sub-assemblies usually deal with a certain physics
 - Intuitive way to assemble a *multiphysics* code






CCA
Common Component Architecture

The Code



Separate component subsystems for transport (dark blue) and for reaction (orange) in a reaction-diffusion code. They two are coupled at a relatively high level.

169



CCA
Common Component Architecture

Has the Toolkit Approach Helped Tame Software Complexity?

Questions to consider:


- How has the code evolved?
 - How often have new ports been added?
 - How many rewrites have been done?
- How large are the components?
- How many ports do they have?
 - How large are the ports?
- How many ports exist?
 - i.e., Is the design general enough to support many implementations?
- What is the connectivity of components in application codes?

170



CFRFS Toolkit Status

- Started in 2001
- 61 components today, all peers, independent, mixed and matched for combustion and shock hydrodynamics
- 7 external libraries
- Contributors: 9 in all, including 3 summer students
- Only 2 of the 9 contributors are at SNL today




A Fitzhugh-Nagumo equation being solved on a block-structured adaptively refined mesh. The top image illustrates Runge phenomena at coarse-fine interfaces (dashed ovals) when using high-order schemes (6th order interpolations with 4th order discretizations). Filtering them with an 8th order filter removes them (bottom).

171







Scalability: Capability Growth without Rewrites





- Port designs typically occur in spurts followed by long component development times.
- Ports may have multiple implementations; hence the number of ports is typically less than the number of components.
- As the toolkit has matured, the number of ports is seen to be asymptoting to a slow growth rate.

172









Common Component Architecture

Adaptive Codes

- A CCA code is an assembly of components
 - Components are shared libraries
 - Component applications can be non-optimal because
 - The mathematical characteristics of the simulation are different from those of the component
 - The component is badly implemented
- So, can one dynamically “re-arrange” an assembly to improve performance?
- Simplistically, 2 approaches
 - Create a performance model of each component, use the best one
 - Create an expert system that analyzes a problem and picks a good solution strategy



179



Common Component Architecture

Performance Measurement in a Component World

- Different from traditional software
 - The researcher may not be the author of the component
 - Will need performance info on a component granularity
 - Will need a non-intrusive way of getting it.
- Proxies: Simple component to be inserted between a caller and a callee component
 - Intercepts and forward method calls
 - Can be used to log size of arrays etc
 - Can be use to turn on a “clock” on be called; can turn it off when returning to called.
- A proxy’s ports are the same as the callee’s
- Its functionality is pretty mundane
 - Can it be automatically generated?





180



Integrated Performance Measurement

Measurement infrastructure:


- Proxy
 - Generated automatically using PDT
 - Logs parameters to MasterMind
- MasterMind
 - Collects and stores all measurement data
- TAU
 - Makes all performance measurements
- Work done at University of Oregon by A. Malony and team




181



Component Application with Proxies



182



CCA
Common Component Architecture

Incorporating Other Frameworks

- Chombo (by P. Colella, LBNL) has solvers (AMRGodunov, AMRElliptic, etc.) that
 - Work on block structured adaptive meshes
 - Accept Chombo-specific data structures
 - But fundamentally require:
 - A double pointer, an array, where variables on a patch (box) are stored in blocked format
 - A bunch of integer arrays that describe the array
- Challenge: Can Chombo be used within CCA ?
- Need a standardized way of getting data into Chombo
 - Pointer aliasing, not data copy
- Implementation of this “standard” interface

Using Chombo to solve the Poisson equation (needed for CFRFS flame simulations).

184



Using CCA: Summary

- Review of guidelines for developing high-performance scientific components (both new code and wrappers for existing code)
- CCA is an enabling technology for scientific applications
 - Has enabled mathematicians, chemists, combustion scientists, and computer scientists to contribute new strategies, which are shrink-wrapped for easy re-use
 - Apart from the *science research*, has also spawned *new research directions in CS*
 - Has enabled research scientists to investigate unconventional approaches, for example multilevel parallelism and dynamic adaptivity
- For more info on the CCA applications in these case studies, see:
 - Chemistry: <http://www.cca-forum.org/~cca-chem>
 - Combustion: <http://cfrfs.ca.sandia.gov>
- Different facets of CCA components may be useful within different projects ... What are **your** needs and priorities?



A Few Notes in Closing

CCA Forum Tutorial Working Group
[http://www.cca-forum.org/tutorials/
tutorial-wg@cca-forum.org](http://www.cca-forum.org/tutorials/tutorial-wg@cca-forum.org)





Resources: Its All Online

- Information about all CCA tutorials, past, present, and future:
<http://www.cca-forum.org/tutorials/>
- Specifically...
 - Latest versions of hands-on materials and code:
<http://www.cca-forum.org/tutorials/#sources>
 - Hands-On designed for self-study as well as use in an organized tutorial
 - Should work on most Linux distributions, less tested on other unixen
 - Still evolving, so please contact us if you have questions or problems
 - Archives of all tutorial presentations:
<http://www.cca-forum.org/tutorials/archives/>
- Questions...
tutorial-wg@cca-forum.org



Getting Help

- We want to help insure you have a good experience with CCA, so let us know if you're having problems!
- Tutorial or "start-up" questions
 - tutorial-wg@cca-forum.org
- Problems with specific tools
 - *check documentation for updated contact info*
 - cca-tools bundle (includes Chasm, Babel, Ccaffeine): [Rob Armstrong, rob@sandia.gov](mailto:Rob.Armstrong@sandia.gov)
 - Chasm: [Craig Rasmussen, crasmussen@lanl.gov](mailto:crasmussen@lanl.gov)
 - Babel: babel-users@lanl.gov
 - Ccaffeine: ccafe-users@cca-forum.org
- General questions, or not sure who to ask?
 - cca-forum@cca-forum.org





Common Component Architecture

CCA is Interactive

- Collectively, CCA developers and users span a broad range of scientific interests.
 - There's a good chance we can put you in touch with others with relevant experience with CCA
- CCA Forum Quarterly Meetings
 - Meet many CCA developers and users
 - <http://www.cca-forum.org/meetings/>
- “Coding Camps”
 - Bring together CCA users & developers for a concentrated session of coding
 - Held as needed, typically 3-5 days
 - May focus on a particular theme, but generally open to all interested participants
 - If you're interested in having one, *speak up* (to individuals or cca-forum@cca-forum.org)
- Visits, Internships, etc.



189



Common Component Architecture

Acknowledgements: Tutorial Working Group

- **People:** Benjamin A. Allan, Rob Armstrong, David E. Bernholdt, Randy Bramley, Tamara L. Dahlgren, Lori Freitag Diachin, Wael Elwasif, Tom Epperly, Madhusudhan Govindaraju, Ragib Hasan, Dan Katz, Jim Kohl, Gary Kurfert, Lois Curfman McInnes, Alan Morris, Boyana Norris, Craig Rasmussen, Jaideep Ray, Sameer Shende, Torsten Wilde, Shujia Zhou
- **Institutions:** ANL, Binghamton U, Indiana U, JPL, LANL, LLNL, NASA/Goddard, ORNL, SNL, U Illinois, U Oregon
- **Computer facilities** provided by the Computer Science Department and University Information Technology Services of Indiana University, supported in part by NSF grants CDA-9601632 and EIA-0202048.



190



Acknowledgements: The CCA

- **ANL** –Steve Benson, Jay Larson, Ray Loy, Lois Curfman McInnes, Boyana Norris, Everest Ong, Jason Sarich...
 - **Binghamton University** - Madhu Govindaraju, Michael Lewis, ...
 - **Indiana University** - Randall Bramley, Dennis Gannon, ...
 - **JPL** – Dan Katz, ...
 - **LANL** - Craig Rasmussen, Matt Sotille, ...
 - **LLNL** – Tammy Dahlgren, Lori Freitag Diachin, Tom Epperly, Scott Kohn, Gary Kurfert, ...
 - **NASA/Goddard** – Shujia Zhou
 - **ORNL** - David Bernholdt, Wael Elwasif, Jim Kohl, Torsten Wilde, ...
 - **PNNL** - Jarek Nieplocha, Theresa Windus, ...
 - **SNL** - Rob Armstrong, Ben Allan, Lori Freitag Diachin, Curt Janssen, Jaideep Ray, ...
 - **Tech-X Corp.** – Johan Carlsson, Svetlana Shasharina, Ovsei Volberg, Nanbor Wang
 - **University of Oregon** – Allen Malony, Sameer Shende, ...
 - **University of Utah** - Steve Parker, ...
- and many more... without whom we wouldn't have much to talk about!



191



Thank You!

Thanks for attending this tutorial

We welcome feedback and questions



192