Factorization-Based Data Modeling Practical Work 3

Umut Şimşekli, Simon Henriet Télécom ParisTech, Université Paris-Saclay, Paris, France umut.simsekli@telecom-paristech.fr

Instructions: (please read carefully)

- 1. This homework can be done in groups of **maximum 2** people.
- 2. Prepare your report as a pdf file in English by using LATEX or a similar software (Word etc). Do not submit scanned papers.
- 3. Put all your files (code and/or report) in a zip file: <code>surname_name_tp3.zip</code> and submit it to https://www.dropbox.com/request/eAojIxq3NIkD9I8UFLvT. The deadline is February 3, 2019, 23:59. Late submissions will not be accepted.
- 4. One submission per group is sufficient.

1 Distributed Stochastic Gradient Descent

In this practical work, the aim is to implement the Distributed Stochastic Gradient Descent $(DSGD)^1$ algorithm, which we covered earlier. You will implement the algorithm in C/C++ by using the OpenMPI and GSL libraries.

Throughout this practical work, we will only consider the usual matrix factorization problem, given as follows:

$$(Z_1^{\star}, Z_2^{\star}) = \underset{Z_1, Z_2}{\operatorname{arg\,min}} \frac{1}{2} \| M \odot (X - Z_1 Z_2) \|_F^2$$
 (1)

where we have changed the notation from the earlier notes.

2 Exercises

In the following questions, we will work on the MovieLens 1 Million dataset. We will assume we have 4 processors, therefore the observed matrix will be partitioned into a 4×4 blocks.

- 1. Complete the file dsgd_mf_template.cpp.
- 2. Set the rank to 10 and the step size to 0.00001. Run the code for MovieLens 1 Million Dataset.
- 3. Compute the RMSE by using the code compute_rmse.cpp and plot the RMSE in Matlab by using plot_rmse.m.
- 4. Play with the rank and the step-size. What do you observe?

¹Gemulla, Rainer, et al. "Large-scale matrix factorization with distributed stochastic gradient descent.", Proceedings of the 17th ACM SIGKDD international conference on Knowledge discovery and data mining. ACM, 2011.